

No.	Time	Source	Destination	Protocol	Length	Info
12920	20:22:04.046333	10.145.59.51	128.119.245.12	HTTP	551	GET /wireshark-labs/INTRO-wireshark-file1.html HTTP/1.1
Frame 12920: Packet, 551 bytes on wire (4408 bits), 551 bytes captured (4408 bits) on interface \Device\NPF_{4964A9C0-2FC2-4109-A69A-EFF07D0F3CF}, id 0						
Ethernet II, Src: CloudNetwork_a7:b3:1d (d8:b3:2f:a7:b3:1d), Dst: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)						
Destination: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)						
.... .0. = LG bit: Globally unique address (factory default)						
.... ..0. = IG bit: Individual address (unicast)						
Source: CloudNetwork_a7:b3:1d (d8:b3:2f:a7:b3:1d)						
.... .0. = LG bit: Globally unique address (factory default)						
.... ..0. = IG bit: Individual address (unicast)						
Type: IPv4 (0x0800)						
[Stream index: 0]						
Internet Protocol Version 4, Src: 10.145.59.51, Dst: 128.119.245.12						
0100 = Version: 4						
.... 0101 = Header Length: 20 bytes (5)						
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)						
Total Length: 537						
Identification: 0xa52b (42283)						
010. = Flags: 0x2, Don't fragment						
...0 0000 0000 0000 = Fragment Offset: 0						
Time to Live: 128						
Protocol: TCP (6)						
Header Checksum: 0x986b [validation disabled]						
[Header checksum status: Unverified]						
Source Address: 10.145.59.51						
Destination Address: 128.119.245.12						
[Stream index: 6]						
Transmission Control Protocol, Src Port: 63189, Dst Port: 80, Seq: 1, Ack: 1, Len: 497						
Hypertext Transfer Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
13312	20:22:04.290235	128.119.245.12	10.145.59.51	HTTP	495	HTTP/1.1 200 OK (text/html)
Frame 13312: Packet, 495 bytes on wire (3960 bits), 495 bytes captured (3960 bits) on interface \Device\NPF_{4964A9C0-2FC2-4109-A69A-EFF07D0F3CF}, id 0						
Ethernet II, Src: Cisco_4c:7a:9f (70:61:7b:4c:7a:9f), Dst: CloudNetwork_a7:b3:1d (d8:b3:2f:a7:b3:1d)						
Destination: CloudNetwork_a7:b3:1d (d8:b3:2f:a7:b3:1d)						
.... .0. = LG bit: Globally unique address (factory default)						
.... ..0. = IG bit: Individual address (unicast)						
Source: Cisco_4c:7a:9f (70:61:7b:4c:7a:9f)						
.... .0. = LG bit: Globally unique address (factory default)						
.... ..0. = IG bit: Individual address (unicast)						
Type: IPv4 (0x0800)						
[Stream index: 1]						
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 10.145.59.51						
0100 = Version: 4						
.... 0101 = Header Length: 20 bytes (5)						
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)						
Total Length: 481						
Identification: 0x0037 (55)						
010. = Flags: 0x2, Don't fragment						
...0 0000 0000 0000 = Fragment Offset: 0						
Time to Live: 43						
Protocol: TCP (6)						
Header Checksum: 0x9298 [validation disabled]						
[Header checksum status: Unverified]						
Source Address: 128.119.245.12						
Destination Address: 10.145.59.51						
[Stream index: 6]						
Transmission Control Protocol, Src Port: 80, Dst Port: 63189, Seq: 1, Ack: 498, Len: 441						
Hypertext Transfer Protocol						
Line-based text data: text/html (3 lines)						