# Java Real Time Tools 🄰 git **JU**nit ŸJIRA eclipse **JProfiler**

An Introduction to Ant

Ph: 9246212143,809696969

www.durgasoft.com

# **Index**

- Installing Ant
- Ant Setup
- Project Organization
- Anatomy of a Build File
- Projects
- Build File
- Properties
- Build File with Properties
- Targets
- Build File with Targets
- Tasks
- Initialization Target & Tasks
- Compilation Target & Tasks
- Javadoc Target & Tasks
- Cleanup Target & Tasks
- Completed Build File (1 of 2)
- Completed Build File (2 of 2)
- Running Ant Command Line
- Running Ant Eclipse

•

LEARN FROM EXPERT & DIAMOND FACULTIES OF AMEERPET...

JAVAMEANS DURGASOFT
INDIA'S NO. 1 SOFTWARE TRAINING INSTITUTE

#202 2nd FLOOR
www.durgasoft.com

040-64512786
+91 9246212143
+91 8096969696




### What is Ant?

- Ant is a Java based tool for automating the buildprocess
- Similar to make but implemented using Java
- Platform independent commands (works on Windows, Mac & Unix)
- XML based format
- Avoids the dreaded tab issue in make files
- Easily extendable using Java classes
- Ant is an open source (free) Apache project

### **Automating the Build (C & make)**

• The goal is to automate the build process



a.out: driver.o foo.o bar.o gcc driver.o foo.o bar.o driver.o: driver.c foo.h bar.h gcc -c driver.c foo.o: foo.c foo.h gcc -c foo.c bar.o: gcc -c bar.c

linux3[1]% make gcc -c driver.c gcc -c foo.c gcc -c bar.c gcc driver.o foo.o bar.o linux3[2]%



### **Installing Ant**


- Ant can be downloaded from...– http://ant.apache.org/
- Ant comes bundled as a zip file or a tarball
- Simply unwrap the file to some directorywhere you want to store the executables
- I typically unwrap the zip file into C:\ProgramFiles, and rename to C:\Program Files\ant\
- This directory is known as ANT HOME

### **Ant Setup**

- Set the ANT\_HOME environment variable towhere you installed Ant
- Add the ANT\_HOME/bin directory to your path
- Set the JAVA\_HOME environment variable to the location where you installed Java
- Setting environment variables
- Windows: right click My Computer □ Properties □ Advanced □ Environment Variables
- UNIX: shell specific settings

### **Project Organization**

• The following example assumes that yourworkspace will be organized like so...





### Anatomy of a Build File

- Ant's build files are written in XML
- Convention is to call file build.xml
- Each build file contains
- A project
- At least 1 target
- Targets are composed of some number of tasks
- Build files may also contain properties
- Like macros in a make file
- Comments are within <!-- --> blocks

### **Projects**

- The project tag is used to define the project you wish to work with
- Projects tags typically contain 3 attributes
- name a logical name for the project
- default the default target to execute
- basedir the base directory for which alloperations are done relative to
- Additionally, a description for the project can be specified from within the project tag

### **Build File**



### **Properties**

- Build files may contain constants (knownas properties) to assign a value to avariable which can then be usedthroughout the project
- Makes maintaining large build files moremanageable
- Projects can have a set of properties
- Property tags consist of a name/value pair
- Analogous to macros from make

## **Build File with Properties**

### **Targets**

- The target tag has the following required attribute
- name the logical name for a target
- Targets may also have optional attributes such as
- depends a list of other target names for which this task is dependant upon, the specified task(s) get executed first
- description a description of what a target does
- Like make files, targets in Ant can depend on some number of other targets
- For example, we might have a target to create a jarfile, which first depends upon another target to compile the code
- A build file may additionally specify a default target



### **Build File with Targets**

### **Tasks**

- A task represents an action that needs execution
- Tasks have a variable number of attributes which aretask dependant
- There are a number of build-in tasks, most of which arethings which you would typically do as part of a buildprocess
- Create a directory
- Compile java source code
- Run the javadoc tool over some files
- Create a jar file from a set of files
- Remove files/directories
- And many, many others...
- For a full list see: <a href="http://ant.apache.org/manual/coretasklist.html">http://ant.apache.org/manual/coretasklist.html</a>

### **Initialization Target & Tasks**

Our initialization target creates the buildand documentation directories
 The mkdir task creates a directory

```
<!-- set up some directories used by this project -->
<target name="init" description="setup project directories">
```

```
<mkdirdir="\${build.dir}"/>
<mkdirdir="\${doc.dir}"/>
```

</target>

</project>



### **Compilation Target & Tasks**

- Our compilation target will compile all javafiles in the source directory
- The javac task compiles sources into classes

### **Javadoc Target & Tasks**

Our documentation target will create theHTML documentation
 The javadoc task generates HTMLdocumentation for all sources
 project name="Sample Project" default="compile" basedir=".">
 ...
 <!-- Generate javadocs for current project into \${doc.dir} -->
 <target name="doc" depends="init" description="generate documentation">
 <javadocsourcepath="\${source.dir}" destdir="\${doc.dir}"/>
 </target>

### **Cleanup Target & Tasks**



### **Completed Build File (1 of 2)**

```
<target name="compile" depends="init" description="compile java sources"> <javacsrcdir="${source.dir}" destdir="${build.dir}"/> </target>
```


### **Completed Build File (2 of 2)**

```
<!-- Generate javadocs for current project into ${doc.dir} -->
<target name="doc" depends="init" description="generate documentation">
<javadocsourcepath="${source.dir}" destdir="${doc.dir}"/>
</target>
<!-- Delete the build & doc directories and Emacs backup (*~) files -->
<target name="clean" description="tidy up the workspace">
<delete dir="${build.dir}"/>
<delete dir="${doc.dir}"/>
<delete>
<filesetdefaultexcludes="no" dir="${source.dir}" includes="**/*~"/>
</delete>
</target>
</target>
```



### **Running Ant – Command Line**

- Simply cd into the directory with the build.xml file and type ant to run the project default target
- Or, type ant followed by the name of a target



### **Running Ant – Eclipse**

- Eclipse comes with out of thebox support for Ant
- No need to separately download and configure Ant
- Eclipse provides an Ant view
- Window □ Show View □ Ant
- Simply drag and drop a buildfile into the Ant view, thendouble click the target to run



