

ADV.JAVA Means DURGA SIR

Adv. Java means DURGA SIR..

ADV.JAVA

With

SCWCD / OCWCD

Question Bank

Chapter : 7. Building JSP Pages Using the Expression Language (EL)



DURGA M.Tech

(Sun certified & Realtime Expert)

Ex. IBM Employee

**Trained Lakhs of Students
for last 14 years across INDIA**

India's No.1 Software Training Institute

DURGASOFT

www.durgasoft.com Ph: 9246212143, 8096969696

Page 1

Plot No : 202, IInd Floor ,HUDA Maitrivanam,Ameerpet, Hyd-500038.

www.durgasoft.com

ADV.JAVA Means DURGA SIR

7. Building JSP Pages Using the Expression Language (EL)

- Given a scenario, write EL code that accesses the following implicit variables including pageScope, requestScope, sessionScope, and applicationScope, param and paramValues, header and headerValues, cookie, initParam and pageContext.
- Given a scenario, write EL code that uses the following operators: property access (the . operator), collection access (the [] operator).

Q1. Which EL expression evaluates to the request URI?

- A. \${requestURI}
- B. \${request.URI}
- C. \${request.getURI}
- D. \${request.requestURI}
- E. \${requestScope.requestURI}
- F. \${pageContext.request.requestURI}
- G. \${requestScope.request.requestURI}

Answer: F

Q2. Given:

1. <% int[] nums = {42,420,4200};
2. request.setAttribute("foo", nums); %>
3. \${5 + 3 lt 6}
4. \${requestScope['foo'][0] ne 10 div 0}
5. \${10 div 0}

What is the result?

- A. true true
- B. false true
- C. false true 0
- D. true true Infinity
- E. false true Infinity
- F. An exception is thrown.
- G. Compilation or translation fails.

Answer: E

Q3. You have created a web application that you license to real estate brokers. The webapp is highly customizable including the email address of the broker, which is placed on the footer of each page. This is configured as a context parameter in the deployment descriptor:

10. <context-param>
11. <param-name>footerEmail</param-name>
12. <param-value>joe@estates-r-us.biz</param-value>

ADV.JAVA Means DURGA SIR

13. </context-param>

Which EL code snippet will insert this context parameter into the footer?

- A. Contact me
- B. Contact me
- C. Contact me
- D. Contact me
- E. Contact me

Answer: C

Q4. Given an EL function foo, in namespace func, that requires a long as a parameter and returns a Map, which two are valid invocations of function foo? (Choose two.)

- A. \${func(1)}
- B. \${foo:func(4)}
- C. \${func:foo(2)}
- D. \${foo(5):func}
- E. \${func:foo("easy")}
- F. \${func:foo("3").name}

Answer: C, F

Q5. Click the Exhibit button.

The Appliance class is a Singleton that loads a set of properties into a Map from an external data source. Assume:

An instance of the Appliance class exists in the application-scoped attribute, appl

The appliance object includes the name property that maps to the value Cobia.

The request-scoped attribute, prop, has the value name.

Which two EL code snippets will display the string Cobia? (Choose two.)

```
1. package com.example;
2. import java.util.*;
3. public class Appliance {
4.     private Map<String,String> props;
5.     public Appliance() {
6.         this.props = new
HashMap<String,String>();
7.         initialize();
8.     }
9.     public Map<String,String>
getProperties() {
10.         return this.props;
11.     }
12.     private void initialize() {
13.         // code to load appliance properties
14.     }
15. }
```

ADV.JAVA Means DURGA SIR

- A. `${appl.properties.name}`
- B. `${appl.properties.prop}`
- C. `${appl.properties[prop]}`
- D. `${appl.properties[name]}`
- E. `${appl.getProperties().get(prop)}`
- F. `${appl.getProperties().get('name')}`

Answer: A, C

Q6.Given:

- 11. `<%`
- 12. `request.setAttribute("vals", new String[]{"1","2","3","4"});`
- 13. `request.setAttribute("index", "2");`
- 14. `%>`
- 15. `<%-- insert code here --%>`

Which three EL expressions, inserted at line 15, are valid and evaluate to "3"?
(Choose three.)

- | | |
|---|---------------------------------------|
| A. <code>\${vals.2}</code> | B. <code>\${vals["2"]}</code> |
| C. <code>\${vals.index}</code> | D. <code>\${vals[index]}</code> |
| E. <code>\${vals}[index]</code> | F. <code>\${vals.(vals.index)}</code> |
| G. <code>\${vals[vals[index-1]]}</code> | |

Answer: B, D, G

www.durgasoftonlinetraining.com



**Online Training
Pre Recorded Video
Classes Training
Corporate Training**

**Ph: +91-8885252627, 7207212427
+91-7207212428**

 **USA Ph : 4433326786**

E-mail : durgasoftonlinetraining@gmail.com

Q7. Given:

- 11. `<% java.util.Map map = new java.util.HashMap();`
- 12. `request.setAttribute("map", map);`
- 13. `map.put("a", "true");`
- 14. `map.put("b", "false");`
- 15. `map.put("c", "42"); %>`

ADV.JAVA Means DURGA SIR

Which three EL expressions are valid and evaluate to true? (Choose three.)

- A. `${not map.c}`
- B. `${map.d or map.a}`
- C. `${map.a and map.d}`
- D. `${map.false or map.true}`
- E. `${map.a and map.b or map.a}`
- F. `${map['true'] or map['false']}`

Answer: A, B, E

Q8. Given:

`http://com.example/myServlet.jsp?num=one&num=two&num=three`

Which two produce the output "one, two and three"? (Choose two.)

- A. `${param.num[0],[1] and [2]}`
- B. `${paramValues[0],[1] and [2]}`
- C. `${param.num[0]}, ${param.num[1]} and ${param.num[2]}`
- D. `${paramValues.num[0]}, ${paramValues.num[1]} and ${paramValues.num[2]}`
- E. `${paramValues["num"][0]}, ${paramValues["num"][1]} and ${paramValues["num"][2]}`
- F. `${parameterValues.num[0]}, ${parameterValues.num[1]} and ${parameterValues.num[2]}`
- G. `${parameterValues["num"]["0"]}, ${parameterValues["num"]["1"]} and ${parameterValues["num"]["2"]}`

Answer: D, E



Q9. Given a web application in which the cookie userName is expected to

ADV.JAVA Means DURGA SIR

contain the name of the user. Which EL expression evaluates to that user name?

- A. `${userName}`
- B. `${cookie.userName}`
- C. `${cookie.user.name}`
- D. `${cookies.userName[0]}`
- E. `${cookies.userName}[1]`
- F. `${cookies.get('userName')}`

Answer: B

Q10. Given an EL function declared with:

- 11. `<function>`
- 12. `<name>spin</name>`
- 13. `<function-class>com.example.Spinner</function-class>`
- 14. `<function-signature>`
- 15. `java.lang.String spinIt()`
- 16. `</function-signature>`
- 17. `</function>`

Which two are true? (Choose two.)

- A. The function method must have the signature:
`public String spin()`.
- B. The method must be mapped to the logical name "spin" in the web.xml file.
- C. The function method must have the signature:
`public String spinIt()`.
- D. The function method must have the signature
`public static String spin()`.
- E. The function method must have the signature:
`public static String spinIt()`.
- F. The function class must be named Spinner, and must be in the package com.example.

Answer: E, F

Q11. You need to create a JSP that generates some JavaScript code to populate an array of strings used on the client-side. Which JSP code snippet will create this array?

- A.

```
MY_ARRAY = new Array();
<% for ( int i = 0; i < serverArray.length; i++ ) {
MY_ARRAY[<%= i %>] = '<%= serverArray[i] %>';
} %>
```
- B.

```
MY_ARRAY = new Array();
<% for ( int i = 0; i < serverArray.length; i++ ) {
```

ADV.JAVA Means DURGA SIR

```
MY_ARRAY[${i}] = '${serverArray[i]}';
} %>
C. MY_ARRAY = new Array();
<% for ( int i = 0; i < serverArray.length; i++ ) { %>
MY_ARRAY[<%= i %>] = '<%= serverArray[i] %>';
<% } %>
D. MY_ARRAY = new Array();
<% for ( int i = 0; i < serverArray.length; i++ ) { %>
MY_ARRAY[${i}] = '${serverArray[i]}';
<% } %>
```

Answer: C

LEARN FROM EXPERT & DIAMOND FACULTIES OF AMEERPET...

JAVA MEANS DURGASOFT

INDIA'S NO. 1 SOFTWARE TRAINING INSTITUTE

AN ISO 9001:2008 CERTIFIED
DURGA
SOFTWARE SOLUTIONS

#202 2nd FLOOR
www.durgasoft.com

040-64512786
+91 9246212143
+91 8096969696

Q12. Given:

6. `<% int[] nums = {42, 420, 4200};`
7. `request.setAttribute("foo", nums); %>`
Which two successfully translate and result in a value of true?
(Choose two.)
A. `${true or false}`
B. `${requestScope[foo][0] > 500}`
C. `${requestScope['foo'][1] = 420}`
D. `${(requestScope['foo'][0] lt 50) && (3 gt 2)}`

Answer: A, D

Q13. Click the Exhibit button.

Given:

11. `<% com.example.Advisor advisor = new com.example.Advisor(); %>`
12. `<% request.setAttribute("foo", advisor); %>`
Assuming there are no other "foo" attributes in the web application, which three are valid EL expressions for retrieving the advice property of advisor? (Choose three.)

ADV.JAVA Means DURGA SIR

```
1. package com.example;
2.
3. public class Advisor {
4.     private String advice="take out the
garbage";
5.     public String getAdvice() {
6.         return advice;
7.     }
8.     public void setAdvice(String advice) {
9.         this.advice = advice;
10.    }
11. }
```

- A. \${foo.advice}
- B. \${request.foo.advice}
- C. \${requestScope.foo.advice}
- D. \${requestScope[foo[advice]]}
- E. \${requestScope["foo"]["advice"]}
- F. \${requestScope["foo"]["advice"]}

Answer: A, C, E

Q14. You are creating an error page that provides a user-friendly screen whenever a server exception occurs. You want to hide the stack trace, but you do want to provide the exception's error message to the user so the user can provide it to the customer service agent at your company. Which EL code snippet inserts this error message into the error page?

- A. Message: \${exception.message}
- B. Message: \${exception.errorMessage}
- C. Message: \${request.exception.message}
- D. Message: \${pageContext.exception.message}
- E. Message: \${request.exception.errorMessage}
- F. Message: \${pageContext.exception.errorMessage}

Answer: D

Q15. You are building a dating web site. The client's date of birth is collected along with lots of other information. You have created an EL function with the signature: calcAge(java.util.Date):int and it is assigned to the name, age, in the namespace, funct. In one of your JSPs you need to print a special message to clients who are younger than 25. Which EL code snippet will return true for this condition?

- A. \${calcAge(client.birthDate) < 25}
- B. \${calcAge[client.birthDate] < 25}
- C. \${funct:age(client.birthDate) < 25}
- D. \${funct:age[client.birthDate] < 25}
- E. \${funct:calcAge(client.birthDate) < 25}
- F. \${funct:calcAge[client.birthDate] < 25}

ADV.JAVA Means DURGA SIR

Answer: C

Q16. Given:

11. `<% java.util.Map map = new java.util.HashMap();`

12. `request.setAttribute("map", map);`

13. `map.put("a", "b");`

14. `map.put("b", "c");`

15. `map.put("c", "d"); %>`

16. `<%-- insert code here --%>`

Which three EL expressions, inserted at line 16, are valid and evaluate to "d"?

(Choose three.)

- A. `${map.c}`
- B. `${map[c]}`
- C. `${map["c"]}`
- D. `${map.map.b}`
- E. `${map[map.b]}`
- F. `${map.(map.b)}`

Answer: A, C, E



Q17. Assume the tag handler for a `st:simple` tag extends `SimpleTagSupport`. In what way can scriptlet code be used in the body of `st:simple`?

- A. set the body content type to JSP in the TLD
- B. Scriptlet code is NOT legal in the body of `st:simple`.
- C. add `scripting-enabled="true"` to the start tag for the `st:simple` element
- D. add a pass-through Classic tag with a body content type of JSP to the body of `st:simple`, and place the scriptlet code in the body of that tag

Answer: B

ADV.JAVA Means DURGA SIR

Q18. You have built your own light-weight templating mechanism. Your servlets, which handle each request, dispatch the request to one of a small set of template JSP pages. Each template JSP controls the layout of the view by inserting the header, body, and footer elements into specific locations within the template page. The URLs for these three elements are stored in request-scoped variables called, headerURL, bodyURL, and footerURL, respectively. These attribute names are never used for other purposes. Which JSP code snippet should be used in the template JSP to insert the JSP content for the body of the page?

- A. `<jsp:insert page='${bodyURL}' />`
- B. `<jsp:insert file='${bodyURL}' />`
- C. `<jsp:include page='${bodyURL}' />`
- D. `<jsp:include file='${bodyURL}' />`
- E. `<jsp:insert page='<%= bodyURL %>' />`
- F. `<jsp:include page='<%= bodyURL %>' />`

Answer: C

Q19. Given tutorial.jsp:

2. `<h1>EL Tutorial</h1>`

3. `<h2>Example 1</h2>`

4. `<p>`

5. `Dear ${my:nickname(user)}`

6. `</p>`

Which, when added to the web application deployment descriptor, ensures that line 5 is included verbatim in the JSP output?

- A. `<jsp-config>`
`<url-pattern>*.jsp</url-pattern>`
`<el-ignored>true</el-ignored>`
`</jsp-config>`
- B. `<jsp-config>`
`<url-pattern>*.jsp</url-pattern>`
`<isELIgnored>true</isELIgnored>`
`</jsp-config>`
- C. `<jsp-config>`
`<jsp-property-group>`
`<el-ignored>*.jsp</el-ignored>`
`</jsp-property-group>`
`</jsp-config>`
- D. `<jsp-config>`
`<jsp-property-group>`
`<url-pattern>*.jsp</url-pattern>`
`<el-ignored>true</el-ignored>`
`</jsp-property-group>`

ADV.JAVA Means DURGA SIR

```
</jsp-config>
E. <jsp-config>
<jsp-property-group>
<url-pattern>*.jsp</url-pattern>
<isElIgnored>true</isElIgnored>
</jsp-property-group>
</jsp-config>
```

Answer: D

A rectangular advertisement with a red border. At the top, the website URL 'www.durgasoftonlinelearning.com' is written in white on a red background. Below this, on a yellow background, is a small image of four people in a meeting. To the right of the image, the text 'Online Training', 'Pre Recorded Video', 'Classes Training', and 'Corporate Training' is written in bold, purple and red fonts. Below this, the phone numbers 'Ph: +91-8885252627, 7207212427' and '+91-7207212428' are listed in bold black font. Underneath the phone numbers is a small American flag icon followed by 'USA Ph : 4433326786' in bold black font. At the bottom, the email address 'E-mail : durgasoftonlinelearning@gmail.com' is written in bold black font on a red background.

Q 20. All of your JSPs need to have a link that permits users to email the web master. This web application is licensed to many small businesses, each of which have a different email address for the web master. You have decided to use a context parameter that you specify in the deployment descriptor, like this:

42. <context-param>

43. <param-name>webmasterEmail</param-name>

44. <param-value>master@example.com</param-value>

45. </context-param>

Which JSP code snippet creates this email link?

A. contact us

B. contact us

C. contact us

D. contact us

Answer: D

ADV.JAVA Means DURGA SIR

Q21. A web application allows the HTML title banner to be set using a servlet context initialization parameter called titleStr. Which two properly set the title in this scenario? (Choose two.)

- A. `<title>${titleStr}</title>`
- B. `<title>${initParam.titleStr}</title>`
- C. `<title>${params[0].titleStr}</title>`
- D. `<title>${paramValues.titleStr}</title>`
- E. `<title>${initParam['titleStr']}</title>`
- F. `<title>${servletParams.titleStr}</title>`
- G. `<title>${request.get("titleStr")}</title>`

Answer: B, E

Q22. You are building a dating service web site. Part of the form to submit a client's profile is a group of radio buttons for the person's hobbies:

- 20. `<input type='radio' name='hobbyEnum' value='HIKING'>Hiking
`
- 21. `<input type='radio' name='hobbyEnum' value='SKIING'>Skiing
`
- 22. `<input type='radio' name='hobbyEnum' value='SCUBA'>SCUBA Diving`
- 23. `<!-- and more options -->`

After the user submits this form, a confirmation screen is displayed with these hobbies listed. Assume that an application-scoped variable, hobbies, holds a map between the Hobby enumerated type and the display name.

Which EL code snippet will display Nth element of the user's selected hobbies?

- A. `${hobbies[hobbyEnum[N]]}`
- B. `${hobbies[paramValues.hobbyEnum[N]]}`
- C. `${hobbies[paramValues@'hobbyEnum'@N]}`
- D. `${hobbies.get(paramValues.hobbyEnum[N])}`
- E. `${hobbies[paramValues.hobbyEnum.get(N)]}`

Answer: B

Q23. Given a web application in which the request parameter productID contains a product identifier. Which two EL expressions evaluate the value of the productID? (Choose two.)

ADV.JAVA Means DURGA SIR

- A. `${productID}`
- B. `${param.productID}`
- C. `${params.productID}`
- D. `${params.productID[1]}`
- E. `${paramValues.productID}`
- F. `${paramValues.productID[0]}`
- G. `${pageContext.request.productID}`

Answer: B, F

Q 24. You are building a web application with a scheduling component. On the JSP, you need to show the current date, the date of the previous week, and the date of the next week. To help you present this information, you have created the following EL functions in the 'd' namespace:

name: curDate; **signature:** java.util.Date currentDate()

name: addWeek; **signature:** java.util.Date addWeek(java.util.Date, int)

name: dateString; **signature:** java.util.String getDateString(java.util.Date)

Which EL code snippet will generate the string for the previous week?

- A. `${d:dateString(addWeek(curDate(), -1))}`
- B. `${d:dateString[addWeek[curDate[], -1]]}`
- C. `${d:dateString[d:addWeek[d:curDate[], -1]]}`
- D. `${d:dateString(d:addWeek(d:curDate(), -1))}`

Answer: D

Q25. You are building a dating web site. The client's date of birth is collected along with lots of other information. The Person class has a derived method, `getAge():int`, which returns the person's age calculated from the date of birth and today's date. In one of your JSPs you need to print a special message to clients within the age group of 25 through 35. Which two EL code snippets will return true for this condition? (Choose two.)

- A. `${client.age in [25,35]}`
- B. `${client.age between [25,35]}`
- C. `${client.age between 25 and 35}`
- D. `${client.age <= 35 && client.age >= 25}`
- E. `${client.age le 35 and client.age ge 25}`
- F. `${not client.age > 35 && client.age < 25}`

Answer: D, E

LEARN FROM EXPERT & DIAMOND FACULTIES OF AMEERPET...

JAVA MEANS DURGASOFT

INDIA'S NO. 1 SOFTWARE TRAINING INSTITUTE

AN ISO 9001:2008 CERTIFIED
DURGA
SOFTWARE SOLUTIONS

#202 2nd FLOOR
www.durgasoft.com

040-64512786
+91 9246212143
+91 8096969696

ADV.JAVA Means DURGA SIR

LEARN FROM EXPERTS ...

COMPLETE JAVA

CORE JAVA, ADV. JAVA, ORACLE, STRUTS, HIBERNATE, SPRING, WEB SERVICES,...

COMPLETE .NET

C#.NET, ASP.NET, SQL SERVER, MVC 5 & WCF

TESTING TOOLS

MANUAL + SELENIUM

ORACLE D2K

MSBI SHARE POINT

HADOOP ANDROID

C, C++, DS, UNIX

CRT & APTITUDE TRAINING

AN ISO 9001:2008 CERTIFIED

DURGA
Software Solutions®

202, 2nd Floor, HUDA Maitrivanam,
Ameerpet, Hyd. Ph: 040-64512786,

9246212143, 8096969696

www.durgasoft.com