Name: Harsh Patil
Class: D20C/25

Experiment No. 2

Aim:
Create a Blockchain using Python.

Theory:
Blockchain is a distributed and immutable ledger that records data in a sequence of linked blocks. Each block contains a timestamp, proof (from Proof-of-Work), and the hash of the previous block, ensuring integrity and security.
In this program:

- **Block Creation** – A block is generated using create_block() with a proof and previous hash.
- **Proof-of-Work (PoW)** – Implemented to mine a block by solving a cryptographic puzzle (finding a hash with leading zeros).
- **Hashing** – SHA-256 algorithm ensures data immutability.
- **Validation** – is_chain_valid() checks that every block correctly references the previous hash and satisfies PoW conditions.
- **Flask Web API** – Routes /mine_block, /get_chain, and /is_valid allow mining, fetching the chain, and verifying blockchain integrity through a browser or API client.

This program runs on a local server and simulates mining a blockchain without a network of nodes, making it an ideal introductory model to understand blockchain basics.

Code:
```
import datetime
import hashlib
import json
from flask import Flask, jsonify
class Blockchain:
    def __init__(self):
        self.chain = []
        self.transactions = []
        self.create_block(proof=1,
previous_hash='0')

    def create_block(self, proof, previous_hash,
transactions=None):
        if transactions is None:
            transactions = []
        block = {
            'index': len(self.chain) + 1,
            'timestamp':
str(datetime.datetime.now()),
            'proof': proof,
            'previous_hash': previous_hash,
            'transactions': transactions
        }
        self.chain.append(block)
        return block

    def get_previous_block(self):
        return self.chain[-1]

    def create_Transactions(self):
        if self.transactions:
            previous_block =
self.get_previous_block()
            previous_proof = previous_block['proof']
            proof =
self.proof_of_work(previous_proof)
            previous_hash =
self.hash(previous_block)
            transactions_to_mine =
self.transactions.copy()
            self.transactions = []
            block = self.create_block(
                proof,
                previous_hash,
                transactions_to_mine
            )
            return block
        return None

    def proof_of_work(self, previous_proof):
        new_proof = 1
        check_proof = False
        while check_proof is False:
            hash_operation = hashlib.sha256(
                str(new_proof**2 -
previous_proof**2).encode()
```

```
            ).hexdigest()
            if hash_operation[:3] == '000':
                check_proof = True
            else:
                new_proof += 1
        return new_proof

    def hash(self, block):
        encoded_block = json.dumps(
            block,
            sort_keys=True
        ).encode()
        return
hashlib.sha256(encoded_block).hexdigest()

    def is_chain_valid(self, chain):
        previous_block = chain[0]
        block_index = 1
        while block_index < len(chain):
            block = chain[block_index]
            if block['previous_hash'] !=
self.hash(previous_block):
                return False
            previous_proof = previous_block['proof']
            proof = block['proof']
            hash_operation = hashlib.sha256(
                str(proof**2 -
previous_proof**2).encode()
            ).hexdigest()
            if hash_operation[:3] != '000':
                return False
            previous_block = block
            block_index += 1
        return True

app = Flask(__name__)
blockchain = Blockchain()

@app.route('/mine_block', methods=['GET'])
def mine_block():
    previous_block =
blockchain.get_previous_block()
    previous_proof = previous_block['proof']
    proof =
blockchain.proof_of_work(previous_proof)
    previous_hash =
blockchain.hash(previous_block)
    block = blockchain.create_block(
        proof,
        previous_hash,
        blockchain.transactions
    )
    blockchain.transactions = []
    response = {
        'message': 'Congratulations, you just mined
a block!',
        'index': block['index'],
        'timestamp': block['timestamp'],
        'proof': block['proof'],
        'previous_hash': block['previous_hash'],
        'transactions': block['transactions']
    }
    return jsonify(response), 200

@app.route('/get_chain', methods=['GET'])
def get_chain():
    response = {
        'chain': blockchain.chain,
        'length': len(blockchain.chain)
    }
    return jsonify(response), 200

@app.route('/is_valid', methods=['GET'])
def is_valid():
    valid = blockchain.is_chain_valid(
        blockchain.chain
    )
    if valid:
        response = {
            'message': 'All good. The Blockchain is
valid.'
        }
    else:
        response = {
            'message': 'The Blockchain is not valid.'
        }
    return jsonify(response), 200

if __name__ == '__main__':
    app.run(host='0.0.0.0', port=5000)
```

Output:

```
Server running on: http://127.0.0.1:5000/
```

```python
import datetime
import hashlib
import json
from flask import Flask, jsonify


class Blockchain:

    def __init__(self):
        self.chain = []
        self.transactions = []

        # Create Genesis Block
        self.create_block(proof=1, previous_hash='0')

    def create_block(self, proof, previous_hash, transactions=None):

        if transactions is None:
            transactions = []
```

```
(venv) PS C:\Users\Shakti\Desktop\BC 2> python blockchain.py
 * Debug mode: off
WARNING: This is a development server. Do not use it in a production deployment. Use a production WSGI server instead.
 * Running on all addresses (0.0.0.0)
 * Running on http://127.0.0.1:5000
 * Running on http://192.168.10.102:5000
Press CTRL+C to quit
127.0.0.1 - - [23/Aug/2026 22:40:17] "GET /mine_block HTTP/1.1" 200 -
127.0.0.1 - - [23/Aug/2026 22:42:12] "GET /mine_block HTTP/1.1" 200 -
127.0.0.1 - - [23/Aug/2026 22:42:57] "GET /get_chain HTTP/1.1" 200 -
127.0.0.1 - - [23/Aug/2026 22:43:34] "GET /get_chain HTTP/1.1" 200 -
127.0.0.1 - - [23/Aug/2026 22:44:13] "GET /is_valid HTTP/1.1" 200 -
127.0.0.1 - - [23/Aug/2026 22:44:44] "GET /is_valid HTTP/1.1" 200 -
```

Output on http://127.0.0.1:5000/mine_block

127.0.0.1:5000/mine_block


Pretty-print


```
{
  "index": 2,
  "message": "Congratulations, you just mined a block!",
  "previous_hash": "03748dbbfdfe1ce7058de227c0ea3af7de9abe13ce493fc20e7138ccaf369bf9",
  "proof": 533,
  "timestamp": "2026-08-23 22:40:17.085882",
  "transactions": []
}
```





Output on http://127.0.0.1:5000/get_chain





Output on http://127.0.0.1:5000/is_valid





Conclusion:

We successfully created a basic blockchain using Python and Flask that supports block mining, chain retrieval, and validity checks. Proof-of-Work ensures security by making block creation computationally intensive, while cryptographic hashing guarantees immutability. The implementation demonstrates core blockchain principles—decentralization, immutability, and consensus—in a simplified environment, providing a strong foundation for building more advanced blockchain systems.