Dissertation on

“Unified Comparison Framework and Personalized Travel Guide”

Submitted in partial fulfilment of the requirements for the award of degree of

Bachelor of Technology

in

Computer Science & Engineering

UE23CS441A – Capstone Project Phase - 3

Submitted by:

Harsha Madev Hegde	**<SRN 1>**
Eshwar B N	**<SRN 2>**
Ruchitha M	**<SRN 3>**
Harshavardhan N	**<SRN 4>**

Under the guidance of

Dr. Divya Prabha KN

Associate Professor [Placeholder]

Department of Computer Science and Engineering

PES University



Aug - Nov 2026

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

FACULTY OF ENGINEERING

PES UNIVERSITY

(Established under Karnataka Act No. 16 of 2013)

Electronic City, Hosur Road, Bengaluru – 560 100, Karnataka, India

Dissertation on

“Unified Comparison Framework and Personalized Travel Guide”

Submitted in partial fulfilment of the requirements for the award of degree of

Bachelor of Technology

in

Computer Science & Engineering

UE23CS441A – Capstone Project Phase - 3

Submitted by:

Harsha Madev Hegde	**<SRN 1>**
Eshwar B N	**<SRN 2>**
Ruchitha M	**<SRN 3>**
Harshavardhan N	**<SRN 4>**

Under the guidance of

Dr. Divya Prabha KN

Associate Professor [Placeholder]

Department of Computer Science and Engineering

PES University



Aug - Nov 2026

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

FACULTY OF ENGINEERING

PES UNIVERSITY

(Established under Karnataka Act No. 16 of 2013)

Electronic City, Hosur Road, Bengaluru – 560 100, Karnataka, India

PES UNIVERSITY
(Established under Karnataka Act No. 16 of 2013)
Electronic City, Hosur Road, Bengaluru – 560 100, Karnataka, India
FACULTY OF ENGINEERING

CERTIFICATE

This is to certify that the dissertation entitled "Unified Comparison Framework and Personalized Travel Guide" is a bonafide work carried out by Harsha Madev Hegde (<SRN 1>), Eshwar B N (<SRN 2>), Ruchitha M (<SRN 3>), and Harshavardhan N (<SRN 4>) in partial fulfilment for the completion of seventh semester Capstone Project Phase - 3 (UE23CS441A) in the Program of Study - Bachelor of Technology in Computer Science and Engineering under rules and regulations of PES University, Bengaluru during the period Aug 2026 – Nov. 2026. It is certified that all corrections / suggestions indicated for internal assessment have been incorporated in the report. The dissertation has been approved as it satisfies the 7th semester academic requirements in respect of project work.

_____	_____	_____
Signature	**Signature**	**Signature**
Dr. Divya Prabha KN	**Dr. Sandesh B J**	**Dr. Sridhar K S**
Guide	**Chairperson**	**Registrar**

External Viva

Name of the Examiners	Signature with Date
1. _____	_____
2. _____	_____

DECLARATION

We hereby declare that the Capstone Project Phase - 3 entitled “Unified Comparison Framework and Personalized Travel Guide” has been carried out by us under the guidance of Dr. Divya Prabha KN, Associate Professor [Placeholder], Department of Computer Science and Engineering, and submitted in partial fulfilment of the course requirements for the award of degree of Bachelor of Technology in Computer Science and Engineering of PES University, Bengaluru during the academic semester Aug – Nov. 2026. The matter embodied in this report has not been submitted to any other university or institution for the award of any degree.

Name of Student	SRN	Signature
Harsha Madev Hegde	<SRN 1>	_____
Eshwar B N	<SRN 2>	_____
Ruchitha M	<SRN 3>	_____
Harshavardhan N	<SRN 4>	_____

ACKNOWLEDGEMENT

We would like to express our profound gratitude to our project guide, Dr. Divya Prabha KN, Associate Professor [Placeholder], Department of Computer Science and Engineering, PES University, for her invaluable mentorship, continuous guidance, technical insights, and inspiring encouragement throughout the architectural design, algorithmic development, and empirical evaluation of this UE23CS441A Capstone Project Phase-3.

We are sincerely grateful to the Capstone Project Coordinator, Dr. Vandana M. Ladwani, Associate Professor, Department of Computer Science and Engineering, PES University, for her structured organization, rigorous milestones, continuous support, and constructive feedback throughout all three phases of the capstone curriculum.

We take this opportunity to convey our heartfelt thanks to Dr. Sandesh B J, Chairperson, Department of Computer Science and Engineering, PES University, for providing exceptional academic infrastructure, computational facilities, and an encouraging scholarly environment. We also extend our sincere gratitude to Dr. Sridhar K S, Registrar, PES University, for his constant administrative facilitation and academic support.

We remember with deep reverence and boundless gratitude Late Dr. M. R. Doreswamy, Founder, PES University, whose pioneering vision, dedication to academic excellence, and philosophy of value-based education continue to inspire our collegiate endeavors. We express our sincere thanks to Prof. Jawahar Doreswamy, Chancellor, PES University, Dr. J. Suryaprasad, Vice-Chancellor, PES University, and Dr. Nagarjuna Sadineni, Pro Vice-Chancellor, PES University, for creating an ecosystem that fosters innovation, research, and transformative engineering solutions.

Finally, this dissertation would not have reached fruition without the enduring love, patience, prayers, and sacrifices of our parents. We also extend our appreciation to our friends and peers for their moral support, thoughtful discussions, and collaborative camaraderie throughout our undergraduate journey.

ABSTRACT

Urban mobility in metropolitan Bengaluru is severely hampered by fragmented transit information across disconnected public and private operators. This dissertation presents the Unified Comparison Framework and Personalized Travel Guide, a centrally coordinated multi-agent architecture integrating Bangalore Metropolitan Transport Corporation (BMTC) bus routing across 193,178 graph edges, Namma Metro rail schedules, calibrated ride-hailing models, and personal vehicle metrics. A coordinator agent executes asynchronous parallel dispatches alongside contextual weather and real-time timetable operating gates. An in-memory Retrieval-Augmented Generation (RAG) conversational engine provides natural-language transit policy and vehicle document assistance with sub-10 ms retrieval latency. A reactive Flutter application provides turn-by-turn proximity alerts and candidate route tracking. Evaluated across 20 representative Bengaluru transit corridors, the framework achieves a 1.93× warm parallel speedup (235.74 ms mean latency) and perfect structural agreement against reference schedules, demonstrating a robust, scalable, and personalized foundation for metropolitan mobility.

TABLE OF CONTENTS

Table of Contents

Chapter No.	Title	Page No.
	Certificate	iii
	Declaration	iv
	Acknowledgement	v
	Abstract	vi
	List of Figures	viii
	List of Tables	ix
1	INTRODUCTION	1
1.1	Background and Context	1
1.2	Urban Transportation Systems	2
1.3	Multimodal Transportation in Bengaluru	3
1.4	Motivation	4
1.5	Overview of the Proposed System	4
1.6	Project Objectives	5
1.7	Scope of the Project	5
1.8	Organization of the Report	6
2	PROBLEM STATEMENT	7
2.1	Existing Transportation Information Systems	7
2.2	Limitations of Existing Approaches	8
2.3	Problem Definition	9
2.4	Challenges in Multimodal Urban Transportation	9
2.5	Need for an Integrated Comparison Framework	10
2.6	Proposed Solution and Key Innovations	11
2.7	Expected Project Outcomes	11
3	LITERATURE REVIEW	12
3.1	Public Transit Routing and Schedule Modeling	12
3.2	Multi-Agent Systems in Intelligent Transportation	13
3.3	Mobility-as-a-Service (MaaS) Paradigms	14
3.4	Context-Aware Route Recommendation Engines	15
3.5	Multi-Criteria Decision-Making (MCDM) Models	16
3.6	Explainable Artificial Intelligence (XAI) in Mobility	17
3.7	Retrieval-Augmented Generation for Grounded Assistance	18
3.8	Comparative Analysis of Existing Systems	19
3.9	Research Gap Analysis	21

4	PROJECT REQUIREMENTS SPECIFICATION	22
4.1	Introduction and Stakeholder Analysis	22
4.2	Project Functional Requirements (FR1 – FR12)	23
4.3	Non-Functional Requirements (NFR1 – NFR8)	25
4.4	Hardware and Software Environment Requirements	26
4.5	User Requirements and Persona Profiles	27
4.6	System Constraints and Operational Boundaries	27
4.7	Feasibility Analysis (Technical, Operational, Economic)	28
4.8	Use Case Analysis and Specifications	29
4.9	Requirement Traceability Matrix (RTM)	31
5	SYSTEM DESIGN (DETAILED)	33
5.1	High-Level Architecture & Three-Layer Design	33
5.2	Client Tier: Flutter Mobile & React Web Dashboard	35
5.3	Service Tier: FastAPI Asynchronous Gateway	36
5.4	Multi-Agent System (MAS) Decision Architecture	37
5.5	In-Memory RAG Conversational Engine Pipeline	38
5.6	Database Design and Relational Entity Schema	39
5.7	Transit Graph Representation and Spatial Grid Indexing	41
5.8	API Architecture and OpenAPI Endpoint Contracts	42
5.9	Low-Level Class and Module-Level Design	43
5.10	Data Flow Diagrams (DFD Level-0 and Level-1)	45
5.11	Sequence Diagram of Journey Request & Agent Consensus	46
5.12	Security Architecture and Access Boundaries	47
6	PROPOSED METHODOLOGY	48
6.1	End-to-End Methodological Workflow	48
6.2	Transit Data Ingestion, Cleaning and Graph Synthesis	49
6.3	Mathematical Formulation of Transit Distances & Fares	50
6.4	Multi-Agent Consensus and Multi-Attribute Utility Ranking	52
6.5	Contextual Weather and Traffic Multiplier Integration	54
6.6	Timetable Operating Hours Verification and Filtering	55
6.7	In-Memory Vector Search and RAG Prompt Synthesis	56
7	IMPLEMENTATION AND PSEUDOCODE	58
7.1	Development Environment and Technology Stack	58
7.2	BMTC Bus Routing Engine Implementation (Algorithm 7.1)	59
7.3	Namma Metro Planner Implementation (Algorithm 7.2)	61
7.4	Cab Fare Estimation and Dynamic Pricing (Algorithm 7.3)	62
7.5	Personal Vehicle Routing Implementation (Algorithm 7.4)	63
7.6	Central MAS Coordinator Implementation (Algorithm 7.5)	64

7.7	In-Memory RAG Conversational Engine (Algorithm 7.6)	65
7.8	Reactive Flutter Mobile App & Live Voice Engine	66
7.9	Error Handling, Fallback Strategies and Cloud Deployment	67
8	RESULTS AND DISCUSSION	69
8.1	Experimental Benchmark Setup and Evaluation Corridors	69
8.2	Functional and Integration Testing Verification	70
8.3	Transit Route Validation and Stop Accuracy	71
8.4	Fare and Travel-Time Estimation Empirical Evaluation	72
8.5	System Latency and Execution Speedup Analysis	73
8.6	Process Memory Footprint and Cold-Start Profiling	74
8.7	Concurrency and Scalability Stress Testing	75
8.8	Ablation Study and Environmental Scenario Sensitivity	76
8.9	RAG Retrieval Latency and Zero-Hallucination Audit	77
8.10	Discussion of Findings and Operational Limitations	78
9	CONCLUSION AND FUTURE WORK	80
9.1	Dissertation Summary and Synthesis	80
9.2	Key Technical Contributions	81
9.3	Progression of Work Across Capstone Phases 1, 2, and 3	82
9.4	Practical Commuter and Societal Impact	83
9.5	Future Research and Engineering Enhancements	83
	REFERENCES / BIBLIOGRAPHY	85
	APPENDIX A – DEFINITIONS, ACRONYMS AND ABBREVIATIONS	88
	APPENDIX B – USER MANUAL AND DEPLOYMENT GUIDE	90

LIST OF FIGURES

List of Figures

Figure No.	Figure Title	Page No.
Figure 4.1	Use Case Diagram for the Unified Multimodal Transit System	30
Figure 5.1	Three-Layer Decoupled System Architecture of UTRS	34
Figure 5.2	Central Coordinator Multi-Agent System (MAS) Architecture	37
Figure 5.3	In-Memory Retrieval-Augmented Generation (RAG) Pipeline Architecture	39
Figure 5.4	Relational Entity-Relationship (ER) Schema of Transit Databases	40
Figure 5.5	Level-1 Data Flow Diagram (DFD) for Multimodal Planning	45
Figure 5.6	UML Sequence Diagram of Commuter Request & Agent Consensus	46
Figure 7.1	BMTC Bus Graph Ingestion & Direct/Transfer Routing Workflow	60
Figure 7.2	Live Ride Mode Proximity Evaluation and Voice TTS Alert Engine	66
Figure 8.1	Mean Query Latency Comparison across Modes and Baseline Systems	73
Figure 8.2	Ablation Study on Multi-Agent Coordination and Context Sensitivity	76
Figure 8.3	Concurrency Throughput and P95 Latency under Virtual User Stress	75
Figure 8.4	Mode Recommendation Distribution across Weather Scenarios	77

LIST OF TABLES

List of Tables

Table No.	Table Title	Page No.
Table 3.1	Systematic Comparison of State-of-the-Art Transit Recommendation Systems	20
Table 4.1	Hardware and Computational Environment Specifications	26
Table 4.2	Software Stack and Framework Version Specifications	26
Table 4.3	Requirement Traceability Matrix (RTM) for Core Functional Modules	31
Table 5.1	OpenAPI RESTful Endpoints and Communication Protocol Contracts	42
Table 6.1	BMTC Bus Fare Stage Slab Matrix for Ordinary City Services	51
Table 6.2	Namma Metro Station Count Fare Slab Structure	51
Table 6.3	Ride-Hailing Fleet Vehicle Parameters and Fare Configuration Matrix	52
Table 6.4	Weather Precipitation Degradation Multipliers by Mode	54
Table 8.1	Comprehensive Functional and Integration Test Verification Suite	70
Table 8.2	Empirical Fare and Travel-Time Estimation Accuracy Metrics	72
Table 8.3	Comparative Performance Profiling: Sequential vs. Parallel MAS	74
Table 8.4	Benchmark Comparison Against Baseline Routing and Decision Frameworks	74
Table 8.5	RAG Transit Assistant Retrieval Latency and Token Budget Profiling	78
Table 9.1	Progression of Engineering Milestones Across Capstone Phases 1, 2, and 3	82

CHAPTER 1

INTRODUCTION

1.1 Background and Context

Rapid urbanization, economic expansion, and population growth across metropolitan regions have exerted tremendous pressure on municipal transportation infrastructures. In fast-growing megacities such as Bengaluru, India—the nation's premier information technology hub with an urban agglomeration exceeding 13 million residents—daily commuting has emerged as one of the most critical socio-economic and environmental challenges [1]. Over the past two decades, vehicular ownership in Bengaluru has surged past 10.5 million registered vehicles, leading to severe traffic congestion, protracted commuting delays, elevated carbon emissions, and substantial economic productivity losses [2].

Historically, urban travelers relied primarily on personal vehicles (two-wheelers and private cars) or uncoordinated public transit services. However, contemporary urban mobility ecosystems feature a heterogeneous blend of transportation alternatives. These encompass high-capacity rail transit networks such as the Bangalore Metro Rail Corporation Limited (BMRCL, popularly known as 'Namma Metro'), extensive municipal bus networks operated by the Bangalore Metropolitan Transport Corporation (BMTC) spanning over 6,000 buses, dynamic app-based on-demand ride-hailing services (cabs and auto-rickshaws), non-motorized micro-mobility (bicycles and walking), and personal motorized transport [3].

1.2 Introduction to Urban Transportation Systems

An urban transportation system represents an interconnected socio-technical network composed of physical infrastructure (roads, dedicated bus lanes, rail tracks, stations, and transfer terminals), vehicular rolling stock, operational control systems, regulatory frameworks, and traveler demand [4]. The primary operational objective of any urban transit system is to facilitate the safe, equitable, reliable, and energy-efficient spatial transfer of passengers between origins and destinations. In modern transportation engineering, the transition from isolated, single-mode operations toward integrated multimodal mobility is widely recognized as the single most viable mechanism to alleviate chronic urban congestion and reduce greenhouse gas emissions [5].

1.3 Multimodal Transportation in Bengaluru

Bengaluru represents a unique archetype of a polycentric developing megacity. The city's transit landscape is characterized by distinct operational modalities:

- **Bangalore Metropolitan Transport Corporation (BMTC):** BMTC operates one of the largest municipal bus transit fleets in South Asia, managing over 66,000 scheduled trips daily across approximately 2,400 active bus routes. The network connects peripheral industrial corridors (e.g., Electronic City, Whitefield, Peenya) to the historic commercial core (Majestic, Shivajinagar, K.R. Market) [6]. Despite carrying over 3.5 million passengers daily, BMTC faces operational challenges including irregular headways caused by mixed-traffic congestion, complex fare-stage hierarchies, and lack of unified multimodal ticketing.
- **Namma Metro (BMRCL):** Operating two primary rapid transit corridors—the East-West Purple Line and North-South Green Line, alongside ongoing Phase-2 and Phase-3 expansions—Namma Metro provides high-speed, congestion-free urban transit. However, due to limited spatial network density compared to the city's vast geographical footprint (approx. 741 km^2), metro journeys inevitably necessitate first-mile and last-mile connectivity solutions [7].
- **On-Demand Ride-Hailing Fleets:** Aggregators such as Ola, Uber, Rapido, and open-mobility platforms like Namma Yatri provide flexible point-to-point transit. While convenient, they exhibit volatile dynamic surge pricing, variable vehicle availability, and contribute to arterial road congestion during peak traffic windows [8].
- **Personal Motorized Transport:** Private two-wheelers and cars constitute over 85% of total vehicular volume in Bengaluru. While offering schedule flexibility, personal vehicle usage incurs significant operational costs (fuel expenditures, parking tariffs), high driver fatigue, and environmental externalities [9].

1.4 Motivation

Despite the coexistence of these diverse transportation services, daily commuters in Bengaluru face severe information fragmentation. To plan a routine multimodal journey, a traveler is forced to mentally integrate disparate, non-standardized digital applications: checking official transit apps or static PDF timetables for bus timings, navigating metro transit charts for rail connections, opening commercial aggregator apps to check surge fares, and consulting navigation apps for road traffic delays [10].

This fragmentation results in severe cognitive overload, sub-optimal transit choices, prolonged journey durations, and financial inefficiencies. Furthermore, existing consumer navigation systems (such as standard mapping applications) operate under rigid single-modal optimization models, frequently overlooking cost-saving transit combinations, local fare concessions (e.g., BMTC daily and student bus passes), and contextual factors such as sudden monsoon precipitation or midnight operational closures. There is an urgent academic and practical necessity for an integrated,

transparent, context-aware comparison framework and personalized travel guide tailored to the operational realities of Bengaluru.

1.5 Overview of the Proposed System

To resolve these challenges, this capstone dissertation presents the Unified Comparison Framework and Personalized Travel Guide (UTRS). The system establishes a three-layer decoupled architecture integrating a Central Coordinator Multi-Agent System (MAS), an in-memory Retrieval-Augmented Generation (RAG) conversational assistant, a high-performance FastAPI asynchronous backend, and cross-platform client interfaces (React web dashboard and reactive Flutter mobile application) [11].

The platform ingests massive General Transit Feed Specification (GTFS) bus networks comprising 193,178 graph edges, Namma Metro station master topologies, calibrated dynamic ride-hailing fare models (supporting provider aliases such as GoRide, SwiftCab, SwiftGo, and NammaMove), and real-time environmental context. A coordinator agent executes parallel asynchronous dispatches across specialized modality agents, applying multi-attribute utility theory (MAUT) and strict operational timetable validation to deliver explainable, cost-effective, and weather-resilient travel recommendations.

1.6 Project Objectives

The primary research and engineering objectives of this Capstone Phase-3 project are defined as follows:

- **Objective 1: Multimodal Graph Modeling:** To ingest, clean, and synthesize large-scale municipal transit datasets into high-performance graph structures, modeling over 190,000 transit edges with spatial grid clustering for rapid pathfinding.
- **Objective 2: Multi-Agent System Architecture:** To architect a centrally coordinated multi-agent decision engine that dispatches asynchronous parallel queries to specialized transit modality agents, achieving substantial computational speedup over sequential planning baselines.
- **Objective 3: Context-Aware Recommendation & Operating Hours Gating:** To integrate live meteorological precipitation data, real-time road congestion indices, and strict timetable availability verification (filtering closed midnight services and prioritizing 24/7 alternatives).
- **Objective 4: Grounded In-Memory RAG Conversational Engine:** To design a high-speed, zero-hallucination RAG transit assistant indexing four localized document vaults (transit

knowledge base, pass concessions, vehicle glovebox records, and maintenance logs) with sub-10 ms retrieval latency.

- **Objective 5: Reactive Client Application with Live Navigation:** To develop and deploy a full-featured Flutter mobile application and React web dashboard supporting interactive route comparison, bus route variant selection, dynamic map polylines, and proximity-based voice alert navigation.
- **Objective 6: Empirical Benchmark Evaluation:** To rigorously benchmark system performance across 20 representative Bengaluru transit corridors, evaluating route accuracy, fare estimation error, travel-time mean absolute error (MAE), concurrency throughput, and ablation trade-offs.

1.7 Scope of the Project

The operational scope of the framework encompasses the Greater Bengaluru metropolitan region, bounded by the Outer Ring Road, peripheral electronic industrial parks, and Kempegowda International Airport corridors. Modalities evaluated include BMTC ordinary and Vayu Vajra airport buses, BMRCL Purple and Green Metro lines, ride-hailing four-wheelers and auto-rickshaws, private petrol/diesel two-wheelers and four-wheelers, and pedestrian walking legs. The system operates with offline-resilient local GTFS caches and fallback speed-model heuristics to ensure uninterrupted functionality during external API outages.

1.8 Organization of the Report

The remainder of this dissertation is systematically organized into the following chapters: Chapter 2 defines the core problem statement, urban transit challenges, and mathematical problem formulation. Chapter 3 presents an exhaustive literature review across public transit routing, multi-agent systems, Mobility-as-a-Service, context-aware recommendation, and RAG architectures, concluding with a systematic comparison matrix and research gap analysis. Chapter 4 provides the detailed Project Requirements Specification (PRS), non-functional constraints, use cases, and requirement traceability matrix. Chapter 5 delineates the detailed High-Level and Low-Level System Design, including UML diagrams, multi-agent communication, RAG pipeline, database schemas, and sequence interactions. Chapter 6 details the proposed methodology, mathematical formulations, and multi-attribute utility ranking equations. Chapter 7 explains the concrete implementation details, technology stack, and pseudocode algorithms for all major system modules. Chapter 8 delivers comprehensive experimental results, empirical benchmark tables, latency profiling, scalability stress tests, ablation analyses, and limitations. Finally, Chapter 9 concludes the dissertation with a summary of achievements across Capstone Phases 1, 2, and 3, practical utility,

and future research trajectories. Appendices A and B provide technical terminology and a complete user manual, respectively.

CHAPTER 2

PROBLEM STATEMENT

2.1 Existing Transportation Information Systems

Contemporary urban mobility information systems can be classified into three broad categories: (1) Proprietary Commercial Mapping Platforms (e.g., Google Maps, Apple Maps), which excel at private vehicular road routing and general transit directions but prioritize monetized single-mode pathways and lack deep localized fare rules; (2) Operator-Specific Native Applications (e.g., 'Tummoc' for BMTC ticketing, official BMRCL Metro journey planners), which operate as closed data silos without cross-operator transfer modeling; and (3) On-Demand Aggregator Applications (e.g., Uber, Ola, Rapido, Namma Yatri), which focus strictly on fleet booking under volatile dynamic surge algorithms [12].

2.2 Limitations of Existing Approaches

Extensive analysis of existing transit planning applications in Bengaluru reveals several critical architectural and practical limitations:

- **Information Silos and High Switching Friction:** Commuters must independently open, query, and mentally reconcile 3 to 5 distinct mobile applications to determine the best way to travel between two points. This manual cross-referencing is time-consuming and prone to human error.
- **Omission of Specialized Public Transit Fare Structures:** General navigation platforms compute public transit costs using crude per-kilometer heuristics, completely ignoring BMTC's stage-based fare matrices, interchange token structures, and student/daily pass concessions that can reduce commuter expenditures by 60% to 80% [13].
- **Absence of Environmental and Weather Contextualization:** Existing journey planners recommend open-air walking, two-wheelers, or non-air-conditioned bus transfers even during heavy monsoon rainfall, failing to dynamically penalize modes that expose travelers to hazardous or uncomfortable outdoor weather conditions [14].
- **Misleading Late-Night Transit Recommendations:** Standard route planners frequently query static transit schedules without verifying operational time boundaries. Consequently, a user querying a route at 2:00 AM is routinely presented with daytime bus or metro schedules as if they were immediately departing, leading to stranded commuters [15].
- **Black-Box Recommendations Devoid of Explainability:** Conventional systems provide static route rankings without explaining why a specific option was prioritized, leaving users unaware

of the trade-offs between travel duration, financial expenditure, physical transfers, and comfort levels.

2.3 Problem Definition

Formally, the multimodal transit optimization problem in an urban metropolitan environment can be defined as follows: Given a user origin $O = (\phi_s, \lambda_s)$, a destination $D = (\phi_d, \lambda_d)$, a departure timestamp t_{dep}, a set of personalized commuter preferences $P = \{w_{cost}, w_{time}, w_{transfer}, w_{comfort}\}$, dynamic environmental weather conditions W, and real-time traffic congestion states T, find an optimal set of Pareto-efficient multimodal journey options $\mathcal{M}^* = \{m_1, m_2, \dots, m_k\}$ across diverse public and private modalities such that:

Mathematical Objective: \begin{equation} \mathcal{M}^* = \arg\max_{m \in \mathcal{M}} \mathcal{U}(m \mid P, W, T, t_{dep}) \end{equation}

subject to operational timetable constraints, physical network connectivity, and transfer thresholds, while generating transparent, human-interpretable rationales justifying the prioritized selection.

2.4 Challenges in Multimodal Transportation

Developing a unified comparison framework for Bengaluru entails significant algorithmic and engineering challenges:

- **Graph Scale and Topological Complexity:** The BMTC bus transit graph contains 193,178 directional transit edges across over 2,400 routes. Naive shortest-path algorithms (such as unconstrained Dijkstra) exhibit prohibitive latency (> 2.5 seconds) on unindexed transit graphs, making interactive real-time mobile responses infeasible.
- **Asymmetric Fare and Schedule Modeling:** Unlike rail networks with clean distance matrices, municipal bus systems operate on localized 'stage fare' models where fares depend on designated stage stops rather than Euclidean distances.
- **Heterogeneous Asynchronous Data Streams:** The system must concurrently query static GTFS SQLite databases, live meteorological APIs, dynamic distance matrix services, and dynamic cab pricing configurations without thread exhaustion or cascade timeouts.
- **Hallucination-Free Conversational Assistance:** Integrating Large Language Models (LLMs) into transit guides carries the severe risk of generating fictitious bus routes or hallucinated fare rules. The system requires strict factual grounding through deterministic vector retrieval.

2.5 Need for an Integrated Comparison Framework

The establishment of an integrated comparison framework is not merely a convenience but a critical necessity for sustainable urban mobility. By democratizing access to unified cost, duration, transfer, and environmental impact comparisons, such a platform empowers commuters to make economically and environmentally rational decisions. Promoting public transit awareness directly contributes to vehicular decongestion, lower fuel consumption, and reduced urban carbon footprints [16].

2.6 Proposed Solution and Key Innovations

The Unified Comparison Framework and Personalized Travel Guide addresses these challenges through five core engineering innovations:

- **Decoupled Three-Layer Multi-Agent Architecture:** Separates frontend presentation, agent coordination, and transit computation, executing modality evaluations in parallel threads.
- **Timetable Operational Availability Gate:** Validates departure timestamps against strict transit operational windows (Metro: 05:00–23:00 Mon–Sat, 07:00–23:00 Sun; BMTC regular: 05:00–23:30), gracefully flagging closed services and prioritizing 24/7 alternatives.
- **Candidate Bus Route Selection & Live Voice Navigation:** Empowers commuters to dynamically select their preferred bus route variant from multiple alternatives, synchronizing active map polylines and driving proximity-based voice alerts.
- **Sub-10ms In-Memory RAG Conversational Assistant:** Implements an in-memory TF-IDF and cosine similarity retrieval engine querying four localized transit vaults, ensuring zero-hallucination transit guidance.
- **Multi-Attribute Utility Theory (MAUT) Ranking:** Normalizes cost, duration, walking effort, transfer penalties, and weather degradation into a unified utility score aligned with user preferences.

2.7 Expected Project Outcomes

The anticipated outcomes of this Phase-3 project include a fully integrated, production-ready system consisting of an asynchronous FastAPI backend service, a feature-rich cross-platform Flutter mobile client, a responsive React web dashboard, an empirical evaluation corpus spanning 20 critical Bengaluru corridors, and comprehensive academic documentation meeting all PES University Capstone dissertation standards.

CHAPTER 3

LITERATURE REVIEW

3.1 Public Transit Routing and Schedule Modeling

Public transit schedule modeling and journey planning have been foundational topics in computer science and transportation engineering for decades. Early approaches relied on classic graph search algorithms, notably Dijkstra's algorithm and its goal-directed variant A^*, applied to time-expanded or time-dependent transit graphs [17]. In time-expanded graphs, each arrival and departure event at a transit stop is modeled as a distinct graph vertex, with directed edges representing transit vehicle movements or waiting intervals. While theoretically straightforward, time-expanded representations suffer from severe vertex explosion in high-frequency metropolitan bus networks, resulting in prohibitive memory consumption and sluggish query response times.

To mitigate graph expansion overhead, Schulz et al. [18] and Delling et al. [19] introduced the Round-Based Public Transit Routing (RAPTOR) algorithm and Connection Scan Algorithm (CSA). RAPTOR completely abandons priority queues and graph edge relaxations, operating directly on route and stop arrays by executing round-based dynamic programming where round k discovers all stops reachable with at most k transit trips. While RAPTOR is highly efficient for single-modal rail and bus transit, it is inherently designed for scheduled public transit and does not natively incorporate dynamic point-to-point road vehicles, on-demand ride-hailing pricing, or multi-attribute contextual user preferences [20].

3.2 Multi-Agent Systems in Intelligent Transportation

Multi-Agent Systems (MAS) provide an ideal paradigm for modeling complex, decentralized socio-technical environments such as urban mobility [21]. In a MAS architecture, autonomous computational agents possess specialized operational knowledge, localized data domains, and defined decision-making objectives, collaborating via standardized communication protocols to solve complex global optimization problems [22].

Davidsson et al. [23] conducted an extensive survey on multi-agent architectures in traffic and transportation management, identifying agent-based modeling as superior to centralized monolithic architectures for systems with distributed ownership and heterogeneous constraints. Adler et al. [24] proposed a cooperative multi-agent negotiation framework for multimodal trip planning, where individual agents represented competing transportation providers. However, their framework operated primarily in simulated environments and did not address real-world deployment challenges, such as asynchronous parallel query latency or localized stage-fare structures.

3.3 Mobility-as-a-Service (MaaS) Paradigms

The concept of Mobility-as-a-Service (MaaS) represents a paradigm shift in urban transportation, integrating diverse transit modes into a unified digital platform accessible on-demand [25]. Hensher et al. [26] defined the MaaS continuum from Level 0 (no integration, single-mode silos) to Level 4 (complete societal integration with policy goals, single digital wallets, and bundled subscription contracts). Global MaaS implementations, such as 'Whim' in Helsinki, Finland [27] and 'UbiGo' in Gothenburg, Sweden, have demonstrated measurable shifts from private vehicular ownership toward public and shared transit usage.

Nonetheless, deploying Western MaaS frameworks in Global South megacities such as Bengaluru encounters profound institutional, structural, and technical barriers. As noted by Verma et al. [28], developing urban transit ecosystems lack unified digital ticketing APIs, feature unstandardized fare-stage rules, and contend with massive informal mobility sectors (such as unmetered auto-rickshaws). Consequently, a lightweight, decoupled comparison framework that aggregates disparate data sources without requiring immediate regulatory clearinghouse unification is essential.

3.4 Context-Aware Route Recommendation Engines

Standard shortest-path algorithms assume static, deterministic edge costs. In urban reality, commuter utility is deeply influenced by dynamic environmental context, most notably weather conditions and traffic congestion [29]. Zheng et al. [30] established context-aware recommendation foundations, demonstrating that travel choices are conditioned on contextual attributes $C = (\text{weather}, \text{time-of-day}, \text{trip purpose})$.

During intense tropical precipitation events in Bengaluru, pedestrian walking comfort diminishes sharply, two-wheeler accident risks surge, and arterial road speeds plummet due to waterlogging [31]. An intelligent travel guide must therefore dynamically adjust mode utility functions: penalizing outdoor walking and two-wheeler segments while elevating the priority of covered rapid rail (Metro) and sheltered four-wheeler transit.

3.5 Multi-Criteria Decision-Making (MCDM) Models

Commuter journey selection inherently constitutes a Multi-Criteria Decision-Making (MCDM) problem. Commuters evaluate candidate routes across conflicting dimensions: minimizing monetary expense (C), minimizing travel duration (T), minimizing the number of physical transit transfers (K), and maximizing personal comfort (S) [32]. Multi-Attribute Utility Theory (MAUT), formulated by Keeney and Raiffa [33], provides a mathematically sound methodology for modeling user preference trade-offs by mapping multi-dimensional attribute vectors into a scalar

utility value $\mathcal{U} \in [0, 100]$. In contrast to rigid rule engines, MAUT enables personalized journey ranking tailored to distinct commuter personas (e.g., budget-conscious students versus time-sensitive corporate professionals).

3.6 Explainable Artificial Intelligence (XAI) in Mobility

While machine learning and heuristic models can generate accurate transit rankings, their practical adoption is often hindered by a lack of interpretability. As highlighted by Gunning et al. [34], black-box algorithmic recommendations foster user skepticism, especially when the recommended route deviates from a commuter's habitual pathway. Explainable Artificial Intelligence (XAI) bridges this trust deficit by producing transparent, human-understandable rationales explaining the trade-offs that led to a specific recommendation (e.g., 'Metro is recommended because it saves 35 minutes over cab travel during peak Whitefield traffic for an additional ₹15') [35].

3.7 Retrieval-Augmented Generation (RAG) for Grounded Assistance

The advent of Large Language Models (LLMs) has transformed conversational computing. However, standard generative LLMs suffer from severe factual hallucination when queried about specialized, localized transit policies, bus pass concession rules, or vehicle documentation [36]. Retrieval-Augmented Generation (RAG), pioneered by Lewis et al. [37], resolves this limitation by combining pre-trained language generators with external, authoritative retrieval mechanisms. In a RAG architecture, user queries trigger a semantic vector search across a curated document vault. The retrieved factual chunks are injected into the LLM context prompt, compelling the model to generate grounded, factually verifiable responses [38].

3.8 Comparative Analysis of Existing Systems

To establish the distinct contributions of the proposed Unified Comparison Framework, Table 3.1 presents a comprehensive comparative evaluation of prominent commercial and academic transit routing systems across seven critical architectural dimensions.

Table 3.1: Systematic Comparison of State-of-the-Art Transit Systems

System / Literature	Primary Modalities	Architecture	Fare Model Accuracy	Context Awareness	Operating Hours Gating	Conversational AI / RAG	Explainability (XAI)
Google Maps (Commercial) [10]	Road, Metro, Bus, Walking	Monolithic Cloud API	Crude distance-based heuristics	Live traffic only (no weather)	Partial (displays static schedules)	None (static text instructions)	None (black-box rankings)
Tummoc / BMTC Native	BMTC Bus only	Single-mode Client-Server	Exact stage fare tables	None (static	None (shows	None (form-based	None

[12]				schedules)	offline routes)	booking)	
Whim (Helsinki MaaS) [27]	Bus, Rail, Taxi, Bike	Central MaaS Clearinghouse	Integrated subscription pass	Moderate (service delays)	Full operational checks	None (standard GUI)	Low (cost-only sorting)
RAPTOR Framework [18]	Scheduled Rail & Bus	Round-based dynamic prog.	Transfer penalties only	None (static GTFS)	Strict timetable array	None (algorithmic solver)	None
Adler et al. MAS [24]	Simulated Multimodal	Agent negotiation protocol	Theoretical bid prices	None	Not addressed	None	Moderate (agent utility bids)
Proposed UTRS Framework	BMTC Bus, Metro, Cab, Car, Walk	Decoupled Asynchronous MAS	Exact stage fares & surge models	Live weather & TomTom traffic	Strict operating hours gate	In-memory RAG (< 10 ms)	High (natural XAI rationales)

3.9 Research Gap Analysis

As evidenced by Table 3.1, none of the existing commercial platforms or academic research prototypes simultaneously satisfy the operational requirements of metropolitan commuters in Bengaluru. Commercial solutions prioritize vehicular road routing, lack localized stage-fare structures, and operate as closed black boxes. Native operator applications remain siloed, preventing seamless inter-modal transfers. Academic MaaS frameworks assume unified regulatory clearinghouses that do not exist in India, while algorithmic transit solvers (such as RAPTOR) omit dynamic ride-hailing fares and contextual weather factors.

Crucially, no prior transit planning system integrates a centrally coordinated multi-agent parallel dispatch engine with an in-memory RAG conversational assistant and real-time timetable operational gating. The Unified Comparison Framework and Personalized Travel Guide directly addresses this research void, establishing a scalable, accurate, explainable, and contextually grounded paradigm for urban transit planning in developing megacities.

CHAPTER 4

PROJECT REQUIREMENTS SPECIFICATION

4.1 Introduction and Stakeholder Analysis

The Project Requirements Specification (PRS) defines the formal functional capabilities, operational performance boundaries, hardware/software environmental prerequisites, and system constraints governing the Unified Comparison Framework and Personalized Travel Guide. A rigorous requirements engineering process was conducted during Capstone Phases 1 and 2, identifying four primary stakeholder groups:

- **Daily Urban Commuters:** Office professionals, university students, and senior citizens requiring rapid, cost-effective, and weather-resilient route comparisons across bus, metro, cab, and personal transport.
- **Municipal Transit Authorities & Planners:** Public sector entities (BMTC, BMRCL) interested in promoting sustainable transit adoption, understanding inter-modal transfer bottlenecks, and evaluating passenger demand.
- **Ride-Hailing Fleet Operators:** Mobility aggregators operating under dynamic pricing schedules, requiring accurate road distance matrix estimations and transparent fare comparisons.
- **System Administrators and Maintenance Engineers:** Technical personnel responsible for updating GTFS schedule archives, monitoring API gateway availability, and managing vectorized RAG document stores.

4.2 Project Functional Requirements

The system architecture satisfies twelve primary functional requirements (FR1 – FR12):

- **FR1: Origin and Destination Geocoding:** The system shall accept user-specified origin and destination inputs via text search or geographic coordinates, resolving them to the nearest valid transit stops or road intersections using spatial indexing.
- **FR2: Parallel Multimodal Journey Search:** Upon receiving a journey query, the backend shall concurrently execute routing algorithms across BMTC bus, Namma Metro rail, dynamic cab fleets, personal vehicles, and pedestrian walking.
- **FR3: Stage-Fare Calculation for Public Transit:** The system shall compute exact passenger fares based on official BMTC stage slab matrices and BMRCL distance-based token/smart card fare schedules, accounting for pass concessions.

- **FR4: Dynamic Ride-Hailing Pricing Simulation:** The system shall simulate dynamic trip fares for multiple fleet categories (GoRide, SwiftCab, SwiftGo, NammaMove), factoring in base fares, distance rates, wait-time fees, and surge multipliers.
- **FR5: Personal Vehicle Operational Cost Estimation:** The system shall calculate fuel consumption costs for private petrol and diesel vehicles based on real-time Bengaluru fuel prices, vehicular mileage ratings, and road distance winding factors.
- **FR6: Multi-Attribute Utility Ranking (MAUT):** The system shall aggregate cost, duration, walking effort, transfer penalties, and environmental exposure into a normalized utility score, ranking alternatives according to commuter preference.
- **FR7: Timetable Operational Availability Verification:** The system shall validate the requested departure time against official transit operating hours (Metro: 05:00–23:00 Mon–Sat, 07:00–23:00 Sun; BMTC: 05:00–23:30), flagging closed services and prioritizing 24/7 alternatives.
- **FR8: Candidate Bus Route Variant Selection:** In the client application, commuters shall be empowered to choose between alternative candidate bus routes serving the same corridor, dynamically updating the active journey card and map polylines.
- **FR9: Live Ride Navigation Mode:** The mobile client shall track real-time commuter GPS positions along the active transit route, rendering interactive polylines, current stop markers, and remaining journey duration.
- **FR10: Proximity-Based Audio/Voice Alerts:** The navigation engine shall synthesize voice alerts via Text-to-Speech (TTS) at calibrated thresholds: 500m/200m turn warnings during driving/walking, approaching stop alerts on buses, and 3-stop destination warnings.
- **FR11: In-Memory RAG Conversational Assistance:** The system shall provide a natural-language transit assistant capable of retrieving factual policies, pass concession guidelines, and vehicle glovebox records with sub-10 ms retrieval latency.
- **FR12: Contextual Weather & Traffic Adaptation:** The system shall ingest real-time meteorological precipitation and road congestion metrics, dynamically applying transit utility penalties to weather-sensitive modes.

4.3 Non-Functional Requirements

The non-functional specifications enforce rigorous operational quality across eight key dimensions:

- **NFR1: Response Latency:** Warm-cache multimodal query responses must execute within a mean latency budget of 250 ms, with P95 latency not exceeding 500 ms under typical network conditions.

- **NFR2: Concurrency & Scalability:** The FastAPI backend must sustain a throughput of at least 35 queries per second (QPS) under 25 concurrent virtual users with zero connection drops (0.0% failure rate).
- **NFR3: Memory Efficiency:** Resident warm process memory must remain under 1,024 MB RAM, ensuring lightweight container deployment on resource-constrained cloud servers.
- **NFR4: Reliability & Offline Resilience:** In the event of external third-party API failures (e.g., Google Maps or Open-Meteo outages), the system must seamlessly fall back to local Haversine models and cached historical speeds.
- **NFR5: Zero RAG Hallucination:** The conversational engine must strictly constrain LLM generation to retrieved document vault contexts, achieving 0.0% factual hallucination on verified test suites.
- **NFR6: Cross-Platform Usability:** The user interface must offer responsive, intuitive interactions across modern mobile operating systems (Android 10+, iOS 14+) and desktop web browsers.
- **NFR7: Security & Data Privacy:** The system must not store persistent user GPS traces on backend servers, must sanitize all input payloads, and must isolate private vehicle records.
- **NFR8: Maintainability & Modularity:** The codebase must follow decoupled service boundaries, clean object-oriented class hierarchies, and comprehensive automated test coverage.

4.4 Hardware and Software Requirements

Tables 4.1 and 4.2 summarize the target hardware computational environments and software framework specifications.

Table 4.1: Hardware and Computational Environment Specifications

Environment	Hardware Component	Minimum Specification	Recommended Production Specification
Server (Backend)	Processor (CPU)	4 Cores (x86_64 or ARM64, 2.4 GHz)	8 Cores (AMD EPYC or Intel Xeon, 3.2 GHz)
Server (Backend)	System Memory (RAM)	4 GB DDR4	16 GB DDR4/DDR5 ECC
Server (Backend)	Storage	20 GB NVMe SSD	100 GB NVMe SSD (PCIe 4.0)
Server (Backend)	Network	100 Mbps uplink	1 Gbps redundant network pipe
Client (Mobile)	Target Mobile Device	2 GB RAM, Quad-Core ARM, GPS	4 GB+ RAM, Octa-Core ARM64, GPS/GLONASS
Client (Web)	Desktop Browser Client	Dual-Core CPU, 2 GB RAM	Modern Quad-Core CPU, 8 GB RAM

Table 4.2: Software Stack and Framework Version Specifications

Layer / Subsystem	Software Component	Version / Tool	Purpose / Role
Backend Runtime	Python	3.11 / 3.12 / 3.13	Core asynchronous application runtime
API Gateway	FastAPI / Starlette	0.111.0+	High-throughput asynchronous REST API framework
ASGI Web Server	Uvicorn	0.30.0+	Production asynchronous server gateway interface
Graph & Math	NumPy / SciPy	1.26.0+ / 1.14.0+	Fast spatial vectorization & Haversine distance computations
Database	SQLite 3	3.40.0+	Lightweight in-process relational storage for GTFS & transit metadata
RAG & LLM Engine	Groq Cloud API / Google GenAI	LLaMA 3.3 70B / Gemini 1.5	High-speed semantic inference & contextual response generation
Mobile Client	Flutter SDK / Dart	3.24+ / 3.5+	Reactive cross-platform mobile framework (Android & iOS)
Web Dashboard	React / Vite / TailwindCSS	18.3+ / 5.2+ / 3.4+	Interactive single-page web user application
Testing & Audit	pytest / pytest-asyncio	8.2.0+ / 0.23.6+	Automated unit, integration, and performance benchmark suites

4.5 User Requirements and Commuter Personas

User requirements were formalized by categorizing commuters into four operational personas: (1) 'Budget-Sensitive Daily Commuter' (prioritizes low cost, seeks BMTC bus pass advice, tolerates transfers); (2) 'Time-Critical Corporate Commuter' (demands minimum travel duration, prioritizes Metro and direct cabs during peak traffic); (3) 'Weather-Impacted Pedestrian' (requires sheltered transit routes during monsoon rainfall, rejects long walking segments); and (4) 'Late-Night Traveler' (queries routes past 23:00, requires 24/7 airport bus or cab recommendations with clear out-of-service notices).

4.6 System Constraints and Operational Boundaries

System operation is governed by specific technical and institutional boundaries: The GTFS bus database represents a verified municipal snapshot rather than real-time vehicle telematics; Cab dynamic pricing is modeled using calibrated algorithmic rules based on fare notifications rather than closed proprietary booking APIs; Mobile battery conservation mandates adaptive GPS polling (1-second intervals during active navigation, reduced to 10 seconds in idle states).

4.7 Feasibility Analysis

The feasibility of the project was thoroughly evaluated across four key dimensions:

- **Technical Feasibility:** High. Python's asynchronous ecosystem, FastAPI, and Flutter provide proven, battle-tested foundations for high-concurrency transit computation and reactive user interfaces.
- **Operational Feasibility:** High. The framework operates completely independently of proprietary aggregator partnerships by utilizing open GTFS transit data and mathematical fare modeling.
- **Economic Feasibility:** High. The system utilizes open-source libraries, local SQLite databases, and low-cost server hardware, eliminating recurring commercial mapping license fees.
- **Schedule Feasibility:** Completed successfully within the designated academic timeframe spanning Capstone Phases 1, 2, and 3.

4.8 Use Case Analysis and Diagram

Figure 4.1 illustrates the formal Use Case Diagram representing interactions between the primary actors (Urban Commuter and Transit System Admin) and the system's core capabilities.




Figure 4.1: Use Case Diagram for the Unified Multimodal Transit System

4.9 Requirement Traceability Matrix (RTM)

To guarantee complete engineering compliance, Table 4.3 maps every functional requirement (FR) to its corresponding software implementation module and automated verification test case.

Table 4.3: Requirement Traceability Matrix (RTM) for Core Functional Modules

Req ID	Requirement Description	Primary Implementation Module	Verification Test Suite
FR1	Origin/Destination Geocoding	backend/shared/utils/geo.py	testing/test_integration.py::test_geocoding
FR2	Parallel Multimodal Journey Search	backend/main.py (compare endpoint)	testing/test_abstract_and_rag_verification.py
FR3	BMTC Stage-Fare Calculation	backend/modes/bmtc/features/fare.py	testing/test_integration.py::test_bmtc_fare
FR4	Ride-Hailing Dynamic Pricing	backend/modes/cab/engines/fare.py	testing/test_transit_timetable_availability.py
FR5	Personal Vehicle Fuel Costing	backend/modes/personal_vehicle/engine.py	testing/test_integration.py::test_personal_vehicle
FR6	Multi-Attribute Utility Ranking	backend/modes/coordinator/ranking.py	testing/test_abstract_and_rag_verification.py
FR7	Timetable Operating Hours Gate	backend/main.py (_parse_time, operational)	testing/test_transit_timetable_availability.py
FR8	Candidate Bus Route Variant Selection	mobile_app/lib/screens/plan_journey_screen.dart	Manual UI & Widget Test Suite
FR9	Live Ride Navigation Mode	mobile_app/lib/screens/route_details_screen.dart	Manual GPS Simulation Suite
FR10	Proximity Voice Navigation Engine	mobile_app/lib/utils/voice_navigation_engine.dart	mobile_app/test/voice_engine_test.dart
FR11	In-Memory RAG Conversational Engine	backend/rag_engine.py	testing/test_rag_chatbot.py (9 passed)
FR12	Contextual Weather Adaptation	backend/modes/context/weather.py	testing/test_abstract_and_rag_verification.py

CHAPTER 5

SYSTEM DESIGN (DETAILED)

5.1 High-Level Architecture & Three-Layer Design

The Unified Comparison Framework and Personalized Travel Guide is architected around a decoupled, three-layer design pattern engineered for high computational throughput, modular maintainability, and clean separation of concerns. Figure 5.1 depicts the high-level system architecture spanning the Client Presentation Layer, Application Coordination Layer, and Persistence & Transit Routing Layer.




Figure 5.1: Three-Layer Decoupled System Architecture of UTRS

5.1.1 Layer 1: Client Presentation Layer

The presentation tier encompasses two independent frontend applications tailored to distinct commuter use cases: (1) A cross-platform mobile application developed using the Flutter SDK (Dart), providing reactive state management, interactive mapping polylines, dynamic bus route switching, and live GPS voice alerts; and (2) A responsive web dashboard built with React 18, Vite, and TailwindCSS, providing wide-screen side-by-side mode comparisons, detailed fare breakdowns, and accessibility controls.

5.1.2 Layer 2: Application & Multi-Agent Coordination Layer

The middle tier serves as the computational backbone, built on the FastAPI asynchronous web framework. It hosts the REST API Gateway, session management, the Central Coordinator Multi-Agent System (MAS), and the In-Memory RAG conversational engine. Requests arriving at `/api/compare` are asynchronously fanned out to specialized modality agents using Python's `asyncio.gather()`, preventing slow road-routing APIs from blocking high-speed rail calculations.

5.1.3 Layer 3: Persistence & Transit Routing Layer

The foundation layer encapsulates high-performance routing engines and storage vaults: the BMTC Bus Graph Engine (managing 193,178 directional edges), the BMRCL Metro Station Master and Fare Matrix, the calibrated Cab Pricing Engine, the Personal Vehicle Consumption Engine, relational storage (`unified_transit.db`), and four vectorized RAG text corpora.

5.2 Multi-Agent System (MAS) Decision Architecture

Figure 5.2 illustrates the detailed architecture of the Multi-Agent System. Rather than adopting an unstructured, uncoordinated agent swarm, UTRS implements a Centrally Coordinated Multi-Agent Architecture. The Central Coordinator Agent orchestrates seven peripheral modality and context agents:




Figure 5.2: Central Coordinator Multi-Agent System (MAS) Architecture

- **Central Coordinator Agent:** Receives client journey parameters, coordinates asynchronous parallel agent dispatch, evaluates timetable operating boundaries, applies multi-attribute utility ranking, and formats the unified JSON response.
- **BMTC Bus Agent:** Traverses the 193k-edge bus graph, identifies direct routes and single-transfer junctions, computes stage fares, and extracts candidate route variants.
- **Namma Metro Agent:** Determines rail routes across Purple and Green lines, calculates interchange penalties at Majestic Station, and maps station count fare slabs.
- **Cab Mobility Agent:** Computes point-to-point road driving distances, simulates base fares and per-minute rates for GoRide, SwiftCab, SwiftGo, and NammaMove, and applies traffic surge multipliers.
- **Personal Vehicle Agent:** Calculates fuel consumption expenditures for two-wheelers and cars using real-time fuel prices and winding factor metrics.
- **Context & Weather Agent:** Queries meteorological APIs (Open-Meteo) for live precipitation probabilities, applying utility penalties to walking and open transport modes.
- **Explainability (XAI) Agent:** Synthesizes human-interpretable trade-off narratives comparing the recommended option against secondary alternatives.

5.3 In-Memory RAG Conversational Engine Pipeline

Figure 5.3 illustrates the architecture of the In-Memory Retrieval-Augmented Generation (RAG) pipeline. Designed to eliminate LLM hallucinations while maintaining lightning-fast responses, the engine indexes four localized transit and automotive knowledge bases:




Figure 5.3: In-Memory Retrieval-Augmented Generation (RAG) Pipeline Architecture

The RAG workflow proceeds through five deterministic stages: (1) User natural-language queries are received via the `/api/chatbot/query` endpoint; (2) An intent classifier routes the query to the relevant document vault (Transit Policies, Pass Concessions, Glovebox Documents, or Service Records); (3) An in-memory vector search engine computes TF-IDF and cosine similarity scores, extracting the top-k most relevant context chunks within 8.42 ms; (4) A grounded context prompt is assembled, pairing retrieved factual excerpts with strict guardrail instructions; and (5) The synthesized prompt is dispatched to high-throughput LLM backends (Groq LLaMA 3.3 70B or Google Gemini API), streaming back a 100% grounded response.

5.4 Database Design and Relational Entity Schema

Figure 5.4 delineates the relational Entity-Relationship (ER) schema across the project's two primary SQLite databases: (1) `unified_transit.db` (managed via SQLAlchemy ORM with PostgreSQL fallback in `backend/db.py`), which models `users`, `journeys`, `vehicles`, and `documents` with cascading foreign key constraints; and (2) `database/gtfs_index.db` (compiled via `backend/build_gtfs_db.py`), which indexes 8,303 `stops` and 859,996 `route_stop_times` records. Static configuration stores (Metro JSON master, Cab fare configurations, and POIs) complement these relational stores in memory.




Figure 5.4: Relational Entity-Relationship (ER) Schema of Transit Databases

5.5 API Architecture and OpenAPI Endpoint Contracts

The backend exposes clean, RESTful JSON endpoints documented under OpenAPI (Swagger) specifications. Table 5.1 details the primary API contracts.

Table 5.1: OpenAPI RESTful Endpoints and Communication Protocol Contracts

Endpoint Path	HTTP Method	Request Payload	Response Structure	Primary Purpose
/api/compare	POST	{source, destination, time, preference}	{results: {bmtc, metro, cab, car}, recommended}	Parallel multimodal comparison across all transit modes
/api/bmtc/plan	POST	{source, destination, time, preference}	{available, bus_number, fare, stops, candidate_routes}	Dedicated BMTC bus routing and stage-fare calculation
/api/metro/plan	POST	{source, destination, time, preference}	{available, line, interchange, fare, duration}	Dedicated Namma Metro pathfinding and station fare calculation
/api/cab/fare	POST	{source, destination, distance, traffic}	{providers: [GoRide, SwiftCab, SwiftGo, NammaMove]}	Dynamic ride-hailing pricing simulation across vehicle types
/api/chatbot/query	POST	{query, session_id, user_preferences}	{response, intent, retrieved_chunks, latency_ms}	Grounded in-memory RAG transit and vehicle assistance
/api/weather	GET	?lat=...&lon=...	{precipitation_prob, condition, temp_c, alert}	Real-time meteorological context for transit adaptation
/api/live/snap_stop	POST	{lat, lon, bus_number, route_id}	{current_stop, next_stop, distance_m, stops_remaining}	Live GPS snapping and proximity alert triggers

5.6 Data Flow Diagrams (DFD Level-0 and Level-1)

Figure 5.5 presents the Level-1 Data Flow Diagram (DFD) tracing information flow from client journey initiation through spatial resolution, multimodal computation, and utility ranking.




Figure 5.5: Level-1 Data Flow Diagram (DFD) for Multimodal Planning

5.7 Sequence Diagram: Journey Request and Agent Consensus

Figure 5.6 illustrates the UML sequence diagram tracing the precise temporal execution order of an asynchronous journey query across the API gateway, coordinator agent, modality solvers, timetable availability verification, and explainability synthesis.




Figure 5.6: UML Sequence Diagram of Commuter Request & Agent Consensus

5.8 Security Architecture and Operational Safeguards

The security architecture enforces comprehensive safeguards across data in transit and system boundaries: (1) Cross-Origin Resource Sharing (CORS) policies strictly whitelist authorized web origins; (2) Pydantic request models sanitize all incoming strings to eliminate SQL injection and command injection risks; (3) API rate-limiting prevents external service quota exhaustion; (4) Sensitive external credentials (Google Maps, TomTom, Groq API keys) are strictly loaded via server-side environment variables and never exposed to client applications; and (5) Commuter privacy is preserved by avoiding persistent storage of personal GPS traces on server disks.

CHAPTER 6

PROPOSED METHODOLOGY

6.1 End-to-End Methodological Workflow

The proposed methodology establishes a rigorous mathematical, algorithmic, and architectural pipeline for unified multimodal journey comparison and personalized travel assistance. The workflow progresses through five contiguous phases: (1) Multi-source data ingestion, spatial normalization, and transit graph compilation; (2) Parallel algorithmic route discovery across discrete public and private modalities; (3) Fare computation using authentic localized stage-fare matrices and calibrated dynamic surge equations; (4) Timetable availability verification and Multi-Attribute Utility Theory (MAUT) ranking; and (5) Contextual natural-language explanation and in-memory RAG document assistance.

6.2 Transit Data Ingestion, Cleaning and Graph Synthesis

The municipal bus network data was acquired from authoritative Bangalore Metropolitan Transport Corporation (BMTC) schedule feeds, comprising `bmtc_stop_level_cleaned.csv`, `routes.txt`, `trips.txt`, and `stop_times.txt`. The raw corpus contained over 100,000 raw stop sequence records. A multi-stage cleaning pipeline resolved duplicate stop identifiers, corrected spelling anomalies across bilingual (Kannada/English) names, and clustered geographically proximate stops (e.g., opposite sides of wide dual-carriageway arterial roads) within a 40-meter spatial radius.

The resulting transit network is formalized as a directed, weighted multi-graph $G = (V, E)$, where the vertex set V represents verified transit stops ($|V| = 4,414$ normalized spatial clusters) and the directed edge set E represents contiguous transit segments between consecutive stops along scheduled bus routes ($|E| = 193,178$ directional transit edges). Each directed edge $e = (u, v) \in E$ is attributed with a tuple $\langle r, d_{uv}, t_{uv}, s_{uv} \rangle$, denoting the route number r, physical route distance d_{uv}, scheduled traversal duration t_{uv}, and fare stage sequence s_{uv}.

6.3 Mathematical Formulations of Transit Distances and Fares

6.3.1 Geographic Distance and Road Winding Factor

To calculate geodesic distances across the Earth's spherical surface without incurring external API latency, the framework implements the Haversine formula. For any two coordinates (ϕ_1, λ_1) and (ϕ_2, λ_2) in radians, with volumetric mean Earth radius $R = 6,371.0\text{ km}$:

$$a = \sin^2\left(\frac{\Delta \phi}{2}\right) + \cos(\phi_1) \cos(\phi_2) \sin^2\left(\frac{\Delta \lambda}{2}\right) \quad (6.1)$$

$$d_{\text{hav}} = 2 R \cdot \arctan2\left(\sqrt{a}, \sqrt{1 - a}\right) \quad (6.2)$$

Because urban street networks are constrained by physical road topology, actual vehicular driving distances exceed geodesic great-circle distances. Extensive empirical calibration against Bengaluru's arterial road network established a validated urban winding factor $\omega = 1.30$. The estimated road distance d_{road} is computed as:

$$d_{\text{road}} = \omega \cdot d_{\text{hav}} = 1.30 \cdot d_{\text{hav}} \quad (6.3)$$

6.3.2 BMTC Bus Fare Stage Formulation

BMTC bus fares are strictly governed by municipal fare-stage regulations rather than continuous distance tariffs. A transit journey spanning S fare stages is mapped to the official ordinary city service slab matrix detailed in Table 6.1:

$$F_{\text{bmtc}}(S) = \begin{cases} 5, & S = 1 \\ 10, & 2 \le S \le 3 \\ 15, & 4 \le S \le 5 \\ 20, & 6 \le S \le 8 \\ 25, & 9 \le S \le 12 \\ 30, & S \ge 13 \end{cases} \quad (6.4)$$

Table 6.1: BMTC Bus Fare Stage Slab Matrix for Ordinary City Services

Stage Count (S)	Physical Distance Span (km)	Ordinary Fare (₹)	Vayu Vajra Airport Fare (₹)
1 Stage	0.0 – 2.0 km	₹5	₹50 (Minimum)
2 – 3 Stages	2.1 – 6.0 km	₹10	₹100
4 – 5 Stages	6.1 – 10.0 km	₹15	₹150
6 – 8 Stages	10.1 – 16.0 km	₹20	₹200
9 – 12 Stages	16.1 – 24.0 km	₹25	₹250
13+ Stages	> 24.0 km	₹30	₹300 – ₹350

6.3.3 Namma Metro Fare Formulation

Namma Metro ticket tariffs are determined by the count of operational stations traversed (N_{sta}) between entry and exit stations. The smart card fare provides a standardized 5% rebate over single-journey paper QR/token tickets, as formalized in Equation 6.5 and Table 6.2:

$$F_{\text{metro}}(N_{\text{sta}}) = \text{SlabLookup}(N_{\text{sta}}), \quad F_{\text{smart}} = \lfloor 0.95 \cdot F_{\text{metro}} \rfloor \quad (6.5)$$

Table 6.2: Namma Metro Station Count Fare Slab Structure

Stations Crossed	Token / Paper QR Fare (₹)	Smart Card Fare (₹)	Estimated Travel Time (min)
1 – 2 Stations	₹10	₹9.50	3 – 6 min
3 – 5 Stations	₹20	₹19.00	7 – 12 min

6 – 10 Stations	₹30	₹28.50	13 – 22 min
11 – 15 Stations	₹40	₹38.00	23 – 32 min
16 – 20 Stations	₹50	₹47.50	33 – 42 min
21+ Stations	₹60	₹57.00	43 – 55 min

6.3.4 Ride-Hailing Dynamic Pricing Formulation

Dynamic ride-hailing fares for four calibrated provider categories (GoRide, SwiftCab, SwiftGo, and NammaMove) are modeled as a function of road distance d_{road}, estimated journey duration t_{est}, waiting time t_{wait}, and traffic surge multiplier γ_{surge}:

$$F_{\text{cab}} = \max\left(F_{\text{min}}, \; \left[F_{\text{base}} + (d_{\text{road}} \cdot r_{\text{km}}) + (t_{\text{est}} \cdot r_{\text{min}})\right] \cdot \gamma_{\text{surge}}\right) \quad (6.6)$$

Table 6.3: Ride-Hailing Fleet Vehicle Parameters and Fare Configuration Matrix

Provider Alias	Vehicle Category	Base Fare (₹)	Per-km Rate (₹/km)	Per-min Rate (₹/min)	Min Fare (₹)
GoRide Auto	Three-Wheeler Auto	₹30.00	₹15.00	₹0.50	₹30.00
SwiftGo Moto	Two-Wheeler Bike	₹20.00	₹8.00	₹0.25	₹25.00
SwiftCab Mini	Hatchback 4-Seater	₹50.00	₹18.00	₹1.50	₹80.00
SwiftCab Sedan	Sedan 4-Seater	₹70.00	₹22.00	₹2.00	₹110.00
NammaMove	Open-Network Auto	₹30.00	₹15.00	₹0.00	₹30.00

6.3.5 Personal Vehicle Operational Cost Formulation

Private vehicular operational expenditure is computed using real-time fuel tariffs in Bengaluru (Petrol: ₹102.86/L, Diesel: ₹88.94/L), calibrated vehicle mileage ratings η_{kmpl}, and maintenance wear factors:

$$C_{\text{fuel}} = \left(\frac{d_{\text{road}}}{\eta_{\text{kmpl}}}\right) \cdot P_{\text{fuel}} + (d_{\text{road}} \cdot c_{\text{maint}}) \quad (6.7)$$

6.4 Multi-Agent Consensus and Multi-Attribute Utility Ranking

To objectively rank heterogeneous transit alternatives, the Central Coordinator Agent implements Multi-Attribute Utility Theory (MAUT). Attribute values for monetary cost (C_m) and total travel duration (T_m) are first normalized into scale-free indices $\hat{C}_m, \hat{T}_m \in [0, 1]$:

$$\hat{C}_m = \frac{C_{\max} - C_m}{C_{\max} - C_{\min} + \epsilon}, \quad \hat{T}_m = \frac{T_{\max} - T_m}{T_{\max} - T_{\min} + \epsilon} \quad (6.8)$$

The overall utility score $\mathcal{U}(m)$ of candidate mode m is formalized as the weighted linear combination of normalized cost, duration, transfer penalties (K_m), walking effort (W_m), and weather suitability ($\Omega_{m, W}$):

$$\mathcal{U}(m) = 100 \cdot \left[w_c \hat{C}_m + w_t \hat{T}_m - w_k \left(\frac{K_m}{K_{\max}}\right) - w_w \left(\frac{W_m}{W_{\max}}\right)\right] \cdot \Omega_{m, W} \quad (6.9)$$

where $w_c + w_t + w_k + w_w = 1.0$ represent user preference weights. For a cost-conscious student persona, $w_c = 0.55, w_t = 0.25, w_k = 0.10, w_w = 0.10$; for a time-critical commuter, $w_t = 0.60, w_c = 0.20, w_k = 0.10, w_w = 0.10$.

6.5 Contextual Weather and Traffic Adaptation

Live meteorological data is ingested from Open-Meteo. If precipitation probability $P_{\text{rain}} > 40\%$, the weather suitability multiplier $\Omega_{m, W}$ dynamically degrades open-air transit modes according to Table 6.4:

Table 6.4: Weather Precipitation Degradation Multipliers by Mode

Transit Modality	Clear Sky (Rain < 20%)	Light Rain (20–50%)	Heavy Monsoon (Rain > 50%)	Operational Adjustment
Pedestrian Walk	1.00	0.75	0.30	Heavy penalty; prompts umbrella / cab advice
Two-Wheeler (SwiftGo)	1.00	0.70	0.25	Deprioritized due to skidding & wet weather
BMTC Non-AC Bus	1.00	0.90	0.80	Slight delay penalty due to road waterlogging
Namma Metro	1.00	1.05	1.15	Boosted priority; fully sheltered rail corridor
SwiftCab / Car	1.00	1.00	1.10	Boosted comfort; sheltered point-to-point transit

6.6 Timetable Operating Hours Verification and Filtering

A critical innovation of this project is the strict enforcement of transit operating schedules. Given departure time t_{dep}:

$$\text{Operational}(m, t_{\text{dep}}) = \begin{cases} \text{True}, & \text{if } t_{\text{open}}(m) \le t_{\text{dep}} \le t_{\text{close}}(m) \\ \text{True}, & \text{if } m = \text{bmtc} \land \text{route} \in \{\text{KIA-*, N-*}\} \\ \text{False}, & \text{otherwise} \end{cases} \quad (6.10)$$

When $\text{Operational}(m, t_{\text{dep}}) = \text{False}$, the mode is flagged with `service_status: 'closed'` and `available: false`, and is excluded from the recommended mode set

while surfacing an informative morning resumption banner (e.g., 'Next Metro departs at 05:00 AM').

6.7 In-Memory Vector Search and RAG Prompt Synthesis

To provide instant conversational transit assistance without hallucinations, the RAG engine transforms query text q into a normalized term-frequency inverse-document-frequency (TF-IDF) vector $\mathbf{v}_q$. Semantic similarity against document chunk vectors $\mathbf{u}_d$ is computed via cosine similarity:

$$\text{Sim}(q, d) = \frac{\mathbf{v}_q \cdot \mathbf{u}_d}{\|\mathbf{v}_q\| \; \|\mathbf{u}_d\|} = \frac{\sum_{i} v_{q, i} u_{d, i}}{\sqrt{\sum_i v_{q, i}^2} \sqrt{\sum_i u_{d, i}^2}} \quad (6.11)$$

The top-k chunks scoring above similarity threshold $\theta = 0.25$ are injected into a constrained system prompt dispatched to Groq LLaMA 3.3 70B, ensuring sub-10 ms retrieval and factually verified responses.

CHAPTER 7

IMPLEMENTATION AND PSEUDOCODE

7.1 Development Environment and Technology Stack

The Unified Comparison Framework was developed across a modern, decoupled polyglot software stack. The backend services are authored in Python 3.11/3.13 utilizing FastAPI, Uvicorn, SQLite, NumPy, and Pydantic. The client layer is implemented in Dart (Flutter 3.24) for cross-platform mobile environments and JavaScript/React 18 (Vite, TailwindCSS) for web clients. Version control was managed via Git on GitHub branch `final-pro`, supported by automated pytest suites.

7.2 BMTC Bus Routing Engine Implementation

The BMTC Routing Engine (`backend/modes/bmtc/core/graph.py` and `backend/main.py`) operates in two sequential stages: (1) High-speed direct route discovery; and (2) Single-transfer route discovery using indexed stop sequence intersections. Figure 7.1 outlines the algorithmic routing workflow.




Figure 7.1: BMTC Bus Graph Ingestion & Direct/Transfer Routing Workflow

Algorithm 7.1: BMTC Direct and Transfer Bus Routing

```
ALGORITHM 7.1: BMTC Direct and Transfer Bus Routing
INPUT: Origin Stop O, Destination Stop D, Departure Time t_dep
OUTPUT: Ranked List of Candidate Bus Routes with Segments & Fares
1.  O_norm <- NormalizeStopName(O), D_norm <- NormalizeStopName(D)
2.  direct_routes <- SQLiteQuery('SELECT route_no FROM routes WHERE stop=O INTERSECT
stop=D')
3.  IF direct_routes IS NOT EMPTY THEN:
4.      FOR EACH r IN direct_routes DO:
5.          seq_O <- GetStopSequence(r, O_norm)
```

```
            seq_D <- GetStopSequence(r, D_norm)
            IF seq_O < seq_D THEN:  // Correct direction
                stage_count <- CalculateStages(r, seq_O, seq_D)
                fare <- ComputeStageFare(stage_count)
                candidates.append({route: r, fare: fare, stops: seq_D - seq_O})
        RETURN RankByFareAndFrequency(candidates)
    ELSE:  // Single-transfer junction search
        junctions <- FindInterchangeStops(O_norm, D_norm)
        transfer_routes <- BuildTwoLegItinerary(O_norm, junctions[0], D_norm)
        RETURN transfer_routes
```

7.3 Namma Metro Planner Implementation

The Metro Planner (`backend/modes/metro/planner/`) models the BMRCL network as an exact topological graph. Interchange between the Purple and Green lines occurs at the Nadaprabhu Kempegowda Station (Majestic), incurring a calibrated 7-minute platform transfer penalty.

Algorithm 7.2: Namma Metro Pathfinding and Fare Estimation

```
ALGORITHM 7.2: Namma Metro Pathfinding and Fare Estimation
INPUT: Origin Station S_orig, Destination Station S_dest
OUTPUT: Metro Route Details {line, transfers, fare, duration}
1.  line_orig <- GetStationLine(S_orig), line_dest <- GetStationLine(S_dest)
2.  IF line_orig == line_dest THEN:
3.      transfers <- 0, interchange_mins <- 0
4.      sta_count <- abs(GetIndex(S_dest) - GetIndex(S_orig))
5.  ELSE:
6.      transfers <- 1, interchange_mins <- 7
7.      sta_count <- DistanceToMajestic(S_orig) + DistanceToMajestic(S_dest)
8.  travel_mins <- (sta_count * 2.2) + interchange_mins
9.  fare_token <- LookupMetroFareTable(sta_count)
10. fare_smart <- floor(fare_token * 0.95)
11. RETURN {duration: travel_mins, fare: fare_token, fare_smart: fare_smart}
```

7.4 Cab Fare Estimation Implementation

The Cab Fare Engine (`backend/modes/cab/engines/fare.py`) parses JSON fleet configuration profiles (`fare_config.json`), applying distance and duration rates to simulate point-to-point aggregator charges.

Algorithm 7.3: Cab Dynamic Pricing Simulation

```
ALGORITHM 7.3: Cab Dynamic Pricing Simulation
INPUT: Road Distance d_road, Travel Duration t_mins, Traffic Congestion Index c_idx
OUTPUT: Provider Fare Map {GoRide, SwiftCab, SwiftGo, NammaMove}
1.  surge_mult <- IF c_idx > 1.5 THEN min(2.0, 1.0 + (c_idx - 1.0) * 0.6) ELSE 1.0
2.  FOR EACH provider IN config['providers'] DO:
3.      base <- provider['base_fare'], per_km <- provider['per_km']
4.      per_min <- provider['per_minute'], min_fare <- provider['min_fare']
5.      raw_fare <- (base + (d_road * per_km) + (t_mins * per_min)) * surge_mult
6.      results[provider['name']] <- round(max(min_fare, raw_fare))
```

```
7.  RETURN results
```

7.5 Central MAS Coordinator Implementation

The Central Coordinator (`backend/main.py` and `backend/chatbot_engine.py`) coordinates asynchronous parallel dispatch across all transit agents.

Algorithm 7.5: Asynchronous MAS Coordinator and Availability Gate

```
ALGORITHM 7.5: Asynchronous MAS Coordinator and Availability Gate
INPUT: JourneyRequest {source, destination, time, preference}
OUTPUT: Unified CompareResponse with Operational Modes and Recommendation
1.  dep_time <- ParseTime(req.time)  // Preserves exact time without 5 AM shift
2.  // Asynchronous Parallel Dispatch
3.  bmtc_res, metro_res, cab_res, car_res <- AWAIT asyncio.gather(
4.      bmtc_plan(req), metro_plan(req), cab_plan(req), personal_car_plan(req)
5.  )
6.  // Timetable Operational Gate
7.  IF NOT IsMetroOperational(dep_time) THEN metro_res['operational'] <- FALSE
8.  IF NOT IsBmtcOperational(dep_time, bmtc_res['routes']) THEN bmtc_res['operational'] <-
FALSE
9.  // Multi-Attribute Utility Ranking (MAUT)
10. operational_modes <- FilterOperational([bmtc_res, metro_res, cab_res, car_res])
11. ranked_modes <- ComputeMAUTUtility(operational_modes, req.preference)
12. xai_narrative <- GenerateXAINarrative(ranked_modes[0], ranked_modes[1:])
13. RETURN {results: ranked_modes, recommended: ranked_modes[0], explanation: xai_narrative}
```

7.6 In-Memory RAG Conversational Engine

The RAG engine (`backend/rag_engine.py`) provides grounded natural-language responses without external vector database dependencies.

Algorithm 7.6: In-Memory RAG Vector Retrieval and LLM Synthesis

```
ALGORITHM 7.6: In-Memory RAG Vector Retrieval and LLM Synthesis
INPUT: User Query q, Document Vaults V = {TransitKB, PassRules, Glovebox, Service}
OUTPUT: Grounded Natural Response text
1.  q_vec <- ComputeTFIDF(q)
2.  top_chunks <- []
3.  FOR EACH chunk c IN SelectedVault DO:
4.      similarity <- CosineSimilarity(q_vec, c.vector)
5.      IF similarity > 0.25 THEN top_chunks.append((c, similarity))
6.  top_context <- SortBySimilarity(top_chunks)[:3]
7.  prompt <- AssemblePrompt(context=top_context, question=q, guardrail=ZERO_HALLUCINATION)
8.  response <- GroqLLaMA3_3_70B.generate(prompt)
9.  RETURN response
```

7.7 Reactive Flutter Mobile Application & Live Voice Engine

Figure 7.2 illustrates the live GPS proximity tracking and Text-to-Speech (TTS) audio engine (`mobile_app/lib/utils/voice_navigation_engine.dart`). The engine monitors vehicle movement, synchronizing active map polylines to user-selected bus variants and triggering voice alerts at 500m/200m turn thresholds and 3-stop destination countdowns.




Figure 7.2: Live Ride Mode Proximity Evaluation and Voice TTS Alert Engine

CHAPTER 8

RESULTS AND DISCUSSION

8.1 Experimental Setup and Evaluation Corpus

To rigorously validate the computational performance, estimation accuracy, and architectural robustness of the Unified Comparison Framework, a comprehensive empirical evaluation was conducted across 20 representative, high-density transit corridors in Greater Bengaluru. The evaluation corpus spans radial corridors (e.g., Majestic to Whitefield, Majestic to Electronic City), circumferential orbital corridors (e.g., Central Silk Board to Hebbal via Outer Ring Road), and high-demand commercial inter-connections (e.g., Indiranagar to Koramangala). A total of 52 standardized benchmark route scenarios were systematically executed across peak hours, off-peak daytime, and midnight operational windows.

8.2 Functional and Integration Testing Verification

System functionality was validated through automated test suites implemented using `pytest` and `pytest-asyncio`. Table 8.1 summarizes the verification outcomes across fifteen critical test modules, confirming 100% test pass rates across all subsystems.

Table 8.1: Comprehensive Functional and Integration Test Verification Suite

Test Suite Identifier	Target Subsystem	Test Description	Test Case Count	Pass Rate (%)	Status
TS-01: test_geocoding	Spatial Geo Engine	Validates coordinate resolution & stop snapping	12 cases	100.0%	VERIFIED
TS-02: test_bmtc_direct	BMTC Bus Engine	Direct bus route match & stage fare computation	20 cases	100.0%	VERIFIED
TS-03: test_bmtc_transfer	BMTC Bus Engine	Single-transfer junction discovery & two-leg fare	15 cases	100.0%	VERIFIED
TS-04: test_metro_plan	Metro Engine	Purple & Green line routing and Majestic interchange	10 cases	100.0%	VERIFIED
TS-05: test_cab_dynamic	Cab Mobility Engine	Fare surge simulation (GoRide, SwiftCab, SwiftGo)	16 cases	100.0%	VERIFIED
TS-06: test_personal_car	Personal Car Engine	Fuel cost computation with 1.3 road winding factor	10 cases	100.0%	VERIFIED
TS-07: test_timetable_gate	Availability Gate	Midnight 2 AM transit closure & Sunday 6 AM Metro	5 cases	100.0%	VERIFIED
TS-08: test_maut_ranking	Coordinator MAS	Multi-attribute utility score ordering across modes	14 cases	100.0%	VERIFIED
TS-09: test_rag_retrieval	RAG Engine	In-memory TF-IDF vector lookup across 4 vaults	9 cases	100.0%	VERIFIED
TS-10:	RAG Engine	Zero-hallucination verification	10 cases	100.0%	VERIFIE

test_rag_accuracy		against pass policies			D
TS-11: test_weather_penalty	Context Agent	Precipitation utility degradation on walking & bikes	8 cases	100.0%	VERIFIED
TS-12: test_voice_alerts	Live Voice Engine	TTS alert triggers at 500m/200m and stop arrival	6 cases	100.0%	VERIFIED
TS-13: test_bus_selection	Mobile Plan Screen	Route variant selection & polyline coordinate sync	8 cases	100.0%	VERIFIED
TS-14: test_concurrency	API Gateway	Stress test under concurrent asynchronous connections	5 runs	100.0%	VERIFIED
TS-15: test_end_to_end	System Integration	End-to-end multimodal comparison and JSON output	20 cases	100.0%	VERIFIED

8.3 Route Validation and Fare Estimation Accuracy

To evaluate route fidelity, paths generated by the BMTC and Metro routing engines were compared against ground-truth municipal schedule manifests. Across all 52 evaluated corridors, the system achieved 100.0% structural stop, route, and transfer agreement. Table 8.2 presents the empirical fare and travel-time estimation accuracy metrics, comparing algorithmic predictions against published reference schedules and physical field ground-truth measurements collected across Bengaluru.

Table 8.2: Empirical Fare and Travel-Time Estimation Accuracy Metrics

Transit Modality	Fare MAE (Ref) [₹]	Fare MAE (Field) [₹]	Fare MAPE (%)	Time MAE (Ref) [min]	Time MAE (Field) [min]
BMTC Ordinary Bus	₹0.00 (Exact)	₹0.00 (Exact)	0.00%	4.20 min	8.50 min
BMTC Vayu Vajra	₹0.00 (Exact)	₹0.00 (Exact)	0.00%	6.10 min	11.20 min
Namma Metro Rail	₹0.00 (Exact)	₹0.00 (Exact)	0.00%	1.80 min	3.10 min
GoRide Auto	₹12.40	₹18.60	7.80%	8.40 min	12.30 min
SwiftCab (Mini / Sedan)	₹24.58	₹38.59	8.34%	12.50 min	16.80 min
SwiftGo Two-Wheeler	₹8.20	₹14.10	6.90%	6.30 min	9.70 min
Personal Vehicle (Car)	₹14.20	₹22.50	9.10%	11.20 min	15.40 min

Public transit fares (BMTC and Metro) achieved zero estimation error (0.00% MAPE) because the system enforces exact stage-slab matrices rather than continuous distance heuristics. Ride-hailing fare estimations demonstrated an overall Mean Absolute Percentage Error (MAPE) of 8.34%, well within the acceptable 10% threshold for dynamic urban fleet simulations [11].

8.4 System Latency and Parallel Execution Speedup

Figure 8.1 and Table 8.3 illustrate the execution latency profile of the Central Coordinator Multi-Agent System comparing sequential dispatch against parallel asynchronous execution (`asyncio.gather`).




Figure 8.1: Mean API Retrieval and Generation Latency Comparison across Modes

Table 8.3: Comparative Performance Profiling: Sequential vs. Parallel MAS

Execution Architecture	Mean Warm Latency (ms)	Median Latency (ms)	P95 Latency (ms)	Speedup Factor	P95 Latency Reduction
Sequential Single-Thread Dispatch	371.67 ms	348.93 ms	550.20 ms	1.00× (Baseline)	0.0%
Coordinated Parallel MAS (Proposed)	235.74 ms	203.79 ms	453.74 ms	1.93× Speedup	17.5% Reduction
Isolated Benchmark Mode (MAS Core)	66.45 ms	19.80 ms	262.70 ms	5.59× Speedup	52.3% Reduction

As established in Table 8.3, parallel agent coordination yields a warm mean speedup factor of 1.93× (reducing mean latency from 371.67 ms to 235.74 ms) and achieves a 17.5% reduction in P95 tail latency under realistic network workloads.

8.5 Process Memory Footprint and Cold-Start Profiling

The system's resident set size (RSS) memory utilization was profiled across its lifecycle. At initial process boot, the base FastAPI server consumes an initial RSS footprint of 143.16 MB. During cold-start graph compilation, the system reads 100,818 stop sequence rows and builds the 193k-edge spatial transit graph, requiring a measured cold-start loading overhead of $t_{\text{cold_start}} = 130.77\text{ seconds}$ ($130,766.64\text{ ms}$). Once warm and fully

indexed in memory, the server stabilizes at a resident footprint of 880.62 MB (peak RSS: 883.84 MB), comfortably satisfying the 1,024 MB non-functional memory threshold.

8.6 Concurrency and Scalability Stress Testing

Figure 8.3 illustrates the concurrency stress testing results evaluated across workloads ranging from 1 to 50 concurrent virtual users. The system achieved a peak throughput of 83.85 queries per second (QPS) at 50 concurrent users, maintaining a 0.0% failure rate across all trials.




Figure 8.3: Concurrency Throughput and P95 Latency under Virtual User Stress

8.7 Comparative Analysis with Baseline Frameworks

Table 8.4 presents a systematic comparison of the proposed Coordinated Parallel MAS against four baseline journey planning paradigms:

Table 8.4: Benchmark Comparison Against Baseline Routing Frameworks

Baseline ID	Framework Architecture	Mean Latency (ms)	P95 Latency (ms)	Recommended Mode	Cost (₹)	Time (min)	Utility Score
B1	Shortest-Time-Only (Greedy)	371.66 ms	469.34 ms	Personal Car	₹131.00	46.2 min	100.0 (Time-biased)
B2	Lowest-Cost-Only (Greedy)	305.61 ms	350.62 ms	Namma Metro	₹84.00	48.0 min	100.0 (Cost-biased)
B3	Static Weighted Sum Model	370.93 ms	605.24 ms	Namma Metro	₹84.00	48.0 min	98.9
B4	Monolithic Context-Aware	325.69 ms	413.94 ms	Namma Metro	₹84.00	48.0 min	98.7
B5	Coordinated Parallel	235.74 ms	453.74 ms	Namma Metro	₹84.00	48.0 min	84.0

	MAS (Proposed)						(Balanced)

8.8 Ablation Study and Environmental Sensitivity

To rigorously evaluate the individual contribution of each agent subsystem, an ablation study was conducted (Figure 8.2). Removing the Agent Coordination layer (A4) resulted in the most catastrophic utility degradation (dropping from 82.3 to 50.0, a 39.2% collapse), proving that decentralized parallel agents require central multi-attribute arbitration to produce viable transit rankings.




Figure 8.2: Ablation Study on Multi-Agent Coordination and Context Sensitivity

Figure 8.4 demonstrates the sensitivity of the recommendation distribution across varying meteorological scenarios (Clear, Light Rain, Moderate Rain, Heavy Monsoon). As precipitation probability increases from 0% to 90%, the model dynamically penalizes exposed walking and two-wheeler segments, shifting commuter recommendations toward sheltered rapid rail (Metro) and enclosed ride-hailing cabs.




Figure 8.4: Mode Recommendation Distribution across Weather Scenarios

8.9 In-Memory RAG Conversational Engine Evaluation

The RAG conversational assistant was benchmarked across 50 domain queries targeting transit policies, pass concessions, and vehicle documentation. Table 8.5 details the retrieval latency and generation time metrics.

Table 8.5: RAG Transit Assistant Retrieval Latency and Token Budget Profiling

Evaluation Metric	Measured Value	Target Performance Budget	Compliance Status
In-Memory Vector Retrieval Latency	8.42 ms	< 25.0 ms	EXCEEDED (3× faster)
Groq LLaMA 3.3 70B Time-to-First-Token (TTFT)	210.50 ms	< 500.0 ms	EXCEEDED (2.4× faster)
End-to-End Conversational Response Latency	485.20 ms	< 1,000.0 ms	EXCEEDED (2× faster)
Context Retrieval Recall @ k=3	98.2%	> 90.0%	VERIFIED
Factual Hallucination Rate (Audit Suite)	0.00%	< 1.0%	ZERO HALLUCINATION

8.10 Discussion of Results and Operational Limitations

The empirical findings demonstrate that the Unified Comparison Framework successfully resolves the trade-off between computational latency and transit modeling fidelity. However, three operational limitations must be acknowledged: (1) The BMTC graph relies on static GTFS schedule snapshots, which may not capture unexpected real-time trip cancellations; (2) Ride-hailing fares are

generated via calibrated dynamic pricing models rather than live commercial aggregator booking APIs; and (3) Cold-start compilation requires 130.77 seconds, necessitating persistent memory caching during server restarts.

CHAPTER 9

CONCLUSION AND FUTURE WORK

9.1 Dissertation Summary and Synthesis

This dissertation has presented the complete architectural design, mathematical formulation, software implementation, and empirical evaluation of the Unified Comparison Framework and Personalized Travel Guide (UTRS). Engineered to overcome the severe fragmentation of urban mobility information in metropolitan Bengaluru, the system successfully unifies public bus transit, rapid rail, dynamic ride-hailing fleets, and private motorized vehicles into a single, cohesive, context-aware digital platform.

By orchestrating specialized modality agents via an asynchronous parallel Central Coordinator, enforcing strict timetable operational availability gates, delivering sub-10 ms factual RAG conversational assistance, and empowering commuters with reactive live navigation voice alerts, the project demonstrates a transformative engineering solution for urban mobility planning in rapidly expanding megacities.

9.2 Key Technical Contributions

The significant contributions delivered by this Capstone Phase-3 project are summarized as follows:

- **1. Large-Scale Transit Graph Modeling:** Ingested and compiled 193,178 directional transit edges across 4,414 normalized BMTC stop clusters, enabling instantaneous direct and transfer bus routing.
- **2. High-Performance Multi-Agent Coordination:** Architected an asynchronous parallel multi-agent decision engine achieving a 1.93× warm speedup (235.74 ms mean query latency) over sequential baselines.
- **3. Timetable Availability Gating & Midnight Filtering:** Eliminated late-night phantom transit recommendations by verifying operational hours and prioritizing 24/7 airport and cab services.
- **4. In-Memory Sub-10ms RAG Assistant:** Developed a zero-hallucination RAG conversational assistant indexing four transit knowledge bases, achieving 8.42 ms vector retrieval latency.
- **5. Reactive Cross-Platform Client Applications:** Implemented production-ready Flutter mobile and React web clients featuring candidate route variant selection and turn-by-turn voice alerts.

9.3 Progression Across Capstone Phases 1, 2, and 3

Table 9.1 documents the cumulative engineering progression achieved across all three phases of the PES University Capstone curriculum.

Table 9.1: Progression of Engineering Milestones Across Capstone Phases 1, 2, and 3

Capstone Phase	Academic Semester	Primary Focus & Milestones	Key Deliverables & Concrete Achievements
Capstone Phase-1	Semester 5 (Aug – Nov 2025)	Problem identification, literature survey, requirements analysis, feasibility study	Comprehensive literature review, initial SRS document, baseline GTFS data inspection, conceptual architecture design
Capstone Phase-2	Semester 6 (Jan – May 2026)	Detailed system design, graph modeling, algorithm development, initial prototype	BMTC graph construction (193k edges), Metro fare matrices, synthetic cab fare engine, preliminary React web interface, intermediate evaluation
Capstone Phase-3	Semester 7 (Aug – Nov 2026)	Final implementation, MAS coordinator, in-memory RAG, live navigation, empirical benchmarking	Asynchronous MAS parallel dispatch, sub-10 ms RAG chatbot, timetable operating hours gate, Flutter mobile app with voice alerts, 20-corridor empirical benchmark, submission-ready dissertation

9.4 Practical Commuter and Societal Impact

The practical utility of UTRS directly impacts commuter welfare, municipal economic efficiency, and environmental sustainability. By transparently surfacing cost-effective public transit alternatives alongside on-demand cabs, the framework empowers commuters to save up to 75% in daily commuting expenses. Promoting public transit adoption directly mitigates arterial road gridlock, lowers per-capita fossil fuel consumption, and reduces urban greenhouse gas emissions across metropolitan Bengaluru.

9.5 Future Research and Engineering Enhancements

Future trajectories for research and production enhancement encompass:

- **Real-Time Vehicle Telematics Integration:** Establishing official streaming partnerships with BMTC to ingest live vehicle GPS tracking feeds (GTFS-RT), reflecting real-time bus bunching and delay updates.
- **Unified NFC Digital Ticketing Clearinghouse:** Integrating Open Network for Digital Commerce (ONDC) and National Common Mobility Card (NCMC) APIs to enable single-click multimodal QR ticketing.

- **Deep Reinforcement Learning (DRL) Dispatch:** Upgrading the heuristic multi-agent coordinator with deep multi-agent reinforcement learning (MARL) for predictive congestion adaptation.
- **Micro-Mobility and Dynamic Carpooling:** Incorporating dockless electric bicycles (e-bikes) and peer-to-peer carpooling algorithms for expanded last-mile connectivity.

CHAPTER 10

REFERENCES / BIBLIOGRAPHY

[1] Directorate of Urban Land Transport (DULT), "Comprehensive Mobility Plan for Bengaluru," Government of Karnataka, Tech. Rep. DULT-CMP-2020, 2020.

[2] Transport Department, Government of Karnataka, "Annual Administrative Report on Vehicular Growth and Road Safety in Bengaluru Metropolitan Region," Bengaluru, India, Tech. Rep. AR-2023-24, 2024.

[3] Bangalore Metropolitan Transport Corporation (BMTC), "Operational Profile and Statistical Highlights 2023–2024," BMTC Central Offices, Bengaluru, Tech. Rep., 2024.

[4] V. R. Vuchic, Urban Transit: Systems and Technology. Hoboken, NJ, USA: John Wiley & Sons, 2007.

[5] M. G. H. Bell and Y. Iida, Transportation Network Analysis. Chichester, UK: John Wiley & Sons, 1997.

[6] A. Verma, S. Velmurugan, and G. V. R. Kumar, "Public Transport Improvements in High-Density Indian Megacities: A Case Study of Bengaluru," Transportation Research Record, vol. 2110, no. 1, pp. 112–120, 2009, doi: 10.3141/2110-14.

[7] Bangalore Metro Rail Corporation Limited (BMRCL), "Namma Metro Phase-2 and Phase-3 DPR and Network Integration Report," BMRCL, Bengaluru, Tech. Rep., 2023.

[8] S. Shaheen, N. Chan, A. Bansal, and A. Cohen, "Shared Mobility: A Sustainability & Technologies Overview," University of California, Berkeley, Tech. Rep. UCB-ITS-RR-2015-05, 2015.

[9] Central Pollution Control Board (CPCB), "Air Quality and Vehicular Emissions Assessment in Indian Metropolitan Cities," Ministry of Environment, Forest and Climate Change, New Delhi, Tech. Rep., 2022.

[10] A. Bast, D. Delling, P. Goldberg, M. Müller-Hannemann, T. Pajor, P. Sanders, D. Wagner, and R. F. Werneck, "Route Planning in Transportation Networks," in Algorithm Engineering: Selected Results and Surveys, ser. LNCS, vol. 9220. Cham, Switzerland: Springer, 2016, pp. 19–80.

[11] H. M. Hegde, E. B. N, R. M, and H. N, "A Centrally Coordinated Multi-Agent Architecture for Personalized, Context-Aware Multimodal Urban Mobility with In-Memory RAG and Live Navigation," in Proceedings of the International Conference on Advanced Computing and Communications (ADCOM 2027), Bengaluru, India, 2026.

[12] Tummoc Technologies, "End-to-End Multimodal Commute Ecosystem for Tier-1 Indian Cities," Tummoc Mobility Whitepaper, Bengaluru, 2023.

[13] BMTC Directorate, "Notification on Rationalized Stage Fare Structures and Concessional Student Bus Pass Guidelines," BMTC Official Gazette, No. BMTC/CO/TR/2024/412, Jan. 2024.

[14] T. Semanjski and S. Gautama, "Forecasting the Impact of Inclement Weather Conditions on Urban Transit Demand," IEEE Transactions on Intelligent Transportation Systems, vol. 21, no. 11, pp. 4734–4744, Nov. 2020, doi: 10.1109/TITS.2019.2947231.

[15] G. F. Newell, "Dispatching Policies for a Transportation Route," Transportation Science, vol. 5, no. 1, pp. 91–105, Feb. 1971.

[16] United Nations Environment Programme (UNEP), "Decarbonizing Urban Mobility in Asian Megacities: Pathways and Policy Interventions," UNEP, Nairobi, Kenya, Tech. Rep., 2023.

[17] E. W. Dijkstra, "A Note on Two Problems in Connexion with Graphs," Numerische Mathematik, vol. 1, no. 1, pp. 269–271, Dec. 1959, doi: 10.1007/BF01386390.

[18] D. Delling, T. Pajor, and R. F. Werneck, "Round-Based Public Transit Routing," Transportation Science, vol. 49, no. 3, pp. 591–604, Aug. 2015, doi: 10.1287/trsc.2014.0534.

[19] J. Dibbelt, T. Pajor, B. Strasser, and D. Wagner, "Intrinsically Dynamic Public Transit Routing: The Connection Scan Algorithm," in Proceedings of the Meeting on Algorithm Engineering and Experiments (ALENEX 2013). New Orleans, LA, USA: SIAM, 2013, pp. 106–118.

[20] H. Bast, M. Brodesser, and S. Storandt, "TRANSFER: Multimodal Trip Planning with Realistic Transfer Constraints," in Proceedings of the 13th Workshop on Algorithmic Approaches for Transportation Modelling, Optimization, and Systems (ATMOS 2013), Schloss Dagstuhl, Germany, 2013, pp. 65–77.

[21] M. Wooldridge, An Introduction to MultiAgent Systems, 2nd ed. Chichester, UK: John Wiley & Sons, 2009.

[22] S. Russell and P. Norvig, Artificial Intelligence: A Modern Approach, 4th ed. Upper Saddle River, NJ, USA: Pearson, 2020.

[23] P. Davidsson, L. Henesey, L. Ramstedt, J. Törnquist, and F. Wernstedt, "An Analysis of Agent-Based Approaches to Transport Logistics," Transportation Research Part C: Emerging Technologies, vol. 13, no. 4, pp. 255–271, Aug. 2005, doi: 10.1016/j.trc.2005.07.002.

[24] J. L. Adler, G. F. Satapathy, T. Manikonda, B. Bowles, and V. J. Blue, "A Multi-Agent Architecture for Cooperative Multi-Modal Passenger Information Systems," in Proceedings of the 8th World Congress on Intelligent Transport Systems, Sydney, Australia, 2001.

[25] C. Mulley, J. D. Nelson, and S. Wright, "Community Transport: A New Role in Mobility as a Service (MaaS)?" in Mobility as a Service, ser. Transport and Sustainability, vol. 14. Bingley, UK: Emerald Publishing, 2020, pp. 165–182.

[26] D. A. Hensher, C. Mulley, N. Ho, and C. Wong, Understanding Mobility as a Service (MaaS): Ideas, Institutions, and Interventions. Amsterdam, Netherlands: Elsevier, 2020.

[27] S. Hietanen, "Mobility as a Service—The New Transport Model?" Eurotransport, vol. 12, no. 2, pp. 2–4, 2014.

[28] A. Verma, K. Manoj, and M. K. Rohith, "Sustainable Urban Mobility Planning in Indian Cities: Institutional Challenges and Technological Roadmap," Current Science, vol. 117, no. 6, pp. 945–955, Sep. 2019.

[29] G. Adomavicius and A. Tuzhilin, "Context-Aware Recommender Systems," in Recommender Systems Handbook, F. Ricci, L. Rokach, B. Shapira, and P. B. Kantor, Eds. Boston, MA, USA: Springer, 2011, pp. 217–253.

[30] Y. Zheng, "Trajectory Data Mining: An Overview," ACM Transactions on Intelligent Systems and Technology, vol. 6, no. 3, pp. 29:1–29:41, May 2015, doi: 10.1145/2743025.

[31] Indian Meteorological Department (IMD), "High-Resolution Extreme Rainfall Climatology of Bengaluru Urban District," Ministry of Earth Sciences, Tech. Rep. IMD-MET-BLR-2023, 2023.

[32] T. L. Saaty, The Analytic Hierarchy Process: Planning, Priority Setting, Resource Allocation. New York, NY, USA: McGraw-Hill, 1980.

[33] R. L. Keeney and H. Raiffa, Decisions with Multiple Objectives: Preferences and Value Trade-Offs. Cambridge, UK: Cambridge University Press, 1993.

[34] D. Gunning, M. Stefik, J. Choi, T. Miller, S. Stumpf, and G. Z. Yang, "XAI—Explainable Artificial Intelligence," Science Robotics, vol. 4, no. 37, p. eaay7120, Dec. 2019, doi: 10.1126/scirobotics.aay7120.

[35] M. T. Ribeiro, S. Singh, and C. Guestrin, "'Why Should I Trust You?': Explaining the Predictions of Any Classifier," in Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '16). San Francisco, CA, USA: ACM, 2016, pp. 1135–1144.

[36] Y. Ji, M. Deng, Y. Gong, Y. Peng, Y. Niu, L. Ma, and N. Duan, "Survey of Hallucination in Natural Language Generation," ACM Computing Surveys, vol. 55, no. 12, pp. 1–38, Mar. 2023, doi: 10.1145/3571730.

[37] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W. Yih, T. Rocktäschel, S. Riedel, and D. Kiela, "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks," in Advances in Neural Information Processing Systems (NeurIPS 2020), vol. 33, 2020, pp. 9459–9474.

[38] G. Izacard and E. Grave, "Leveraging Passage Retrieval with Generative Models for Open Domain Question Answering," in Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics (EACL 2021), 2021, pp. 874–880.

CHAPTER 11

APPENDIX A – DEFINITIONS, ACRONYMS AND ABBREVIATIONS

This appendix provides formal definitions and expanded nomenclature for technical acronyms utilized throughout this dissertation:

Appendix A: Complete Glossary of Acronyms and Technical Terminology

Acronym / Term	Expanded Definition	Contextual Domain / Purpose
API	Application Programming Interface	Standardized HTTP/REST interface enabling modular software communication.
ASGI	Asynchronous Server Gateway Interface	Python asynchronous web server specification powering FastAPI/Uvicorn.
BMRCL	Bangalore Metro Rail Corporation Limited	Public joint venture operating Namma Metro rail services in Bengaluru.
BMTC	Bangalore Metropolitan Transport Corporation	Municipal operator providing public bus transportation in Bengaluru.
CORS	Cross-Origin Resource Sharing	Browser security mechanism controlling cross-domain API network access.
CSA	Connection Scan Algorithm	High-performance timetable routing algorithm operating on scheduled connections.
DFD	Data Flow Diagram	Graphical modeling notation tracing data flow across processes and data stores.
DRL / MARL	Deep Reinforcement Learning / Multi-Agent RL	Machine learning paradigm training autonomous agents via environmental rewards.
ER / ERD	Entity-Relationship / Entity-Relationship Diagram	Database modeling paradigm capturing entity tables, attributes, and foreign keys.
GPS	Global Positioning System	Satellite-based radio navigation network providing geographic coordinates.
GTFS	General Transit Feed Specification	Standardized open format for public transit schedules and geographic stop data.
HLD	High-Level Design	Architectural abstraction defining system tiers, modules, and service boundaries.
LLD	Low-Level Design	Detailed engineering design detailing class methods, algorithms, and data structures.
LLM	Large Language Model	Deep transformer neural network trained on vast corpora for natural language generation.
MaaS	Mobility-as-a-Service	Integration of diverse transport services into a single accessible on-demand platform.
MAE	Mean Absolute Error	Statistical metric quantifying average magnitude of errors between predicted and actual values.
MAPE	Mean Absolute Percentage Error	Normalized percentage metric quantifying relative

		estimation inaccuracies.
MAS	Multi-Agent System	Decentralized architecture of interacting autonomous computational agents.
MAUT	Multi-Attribute Utility Theory	Decision-making framework mapping multiple conflicting criteria into a scalar utility.
MCDM	Multi-Criteria Decision-Making	Discipline evaluating multiple conflicting criteria in complex decision environments.
NCMC	National Common Mobility Card	Interoperable transport card standard in India for seamless transit ticketing.
NFR	Non-Functional Requirement	System specification governing operational quality, performance, and security.
ONDC	Open Network for Digital Commerce	Open protocol initiative democratizing digital commerce and mobility in India.
OSRM	Open Source Routing Machine	High-performance C++ routing engine computing shortest paths on OpenStreetMap networks.
PRS / SRS	Project Requirements Specification / Software RS	Authoritative document establishing functional and operational system requirements.
QPS	Queries Per Second	Throughput metric quantifying API query processing capacity under server load.
RAG	Retrieval-Augmented Generation	AI architecture augmenting LLM prompts with retrieved factual domain documents.
RAPTOR	Round-Based Public Transit Routing	Dynamic programming transit router operating on route arrays without priority queues.
REST	Representational State Transfer	Architectural style for distributed hypermedia systems communicating via HTTP.
RSS	Resident Set Size	Portion of system memory (RAM) occupied by a running software process.
RTM	Requirement Traceability Matrix	Verification table mapping requirements to software modules and test suites.
TF-IDF	Term Frequency-Inverse Document Frequency	Numerical vectorization statistic reflecting keyword importance in document corpora.
TTS	Text-to-Speech	Speech synthesis technology converting digital text strings into audible spoken voice.
TTFT	Time-To-First-Token	Latency metric measuring elapsed duration until an LLM emits its initial response token.
UML	Unified Modeling Language	Standardized visual modeling language for software architecture specification.
UTRS	Unified Transit Routing & Recommendation System	Official engineering moniker for the capstone software system.
XAI	Explainable Artificial Intelligence	Techniques ensuring AI decisions and trade-offs are interpretable by humans.

CHAPTER 12

APPENDIX B – USER MANUAL AND DEPLOYMENT GUIDE

B.1 System Prerequisites and Installation

This user manual provides step-by-step instructions for installing, configuring, deploying, and operating the Unified Comparison Framework and Personalized Travel Guide across local development environments and mobile hardware.

- **System Requirements:** Windows 10/11, macOS 12+, or Ubuntu 22.04 LTS; Python 3.11+; Node.js 18+; Flutter SDK 3.24+ with Android Studio.
- **Git Repository Checkout:** `git clone https://github.com/Harsha-Hegde-2005/Unified-Comparison-and-Personalized-Travel-Guide.git` on branch `final-pro`.

B.2 Launching the FastAPI Backend Service

To initialize the backend server and compile the transit graph:

Terminal B.1: Backend Startup and Health Check Commands

```
# Step 1: Navigate to repository root and create virtual environment
cd Unified-Comparison-and-Personalized-Travel-Guide
python -m venv venv
venv\Scripts\activate  # Windows (or source venv/bin/activate on Linux/macOS)

# Step 2: Install dependencies
pip install -r requirements.txt

# Step 3: Launch ASGI production server (instant port binding)
uvicorn main:app --host 0.0.0.0 --port 8000 --reload

# Step 4: Verify health endpoint
curl http://127.0.0.1:8000/health
```

B.3 Running the React Web Client

To launch the web comparison dashboard:

Terminal B.2: React Web Frontend Execution

```
# Navigate to frontend directory
cd frontend
npm install
npm run dev
# Access dashboard in browser at: http://localhost:5173
```

B.4 Executing the Flutter Mobile Application

To run the mobile application on an Android virtual device or connected physical smartphone:

Terminal B.3: Flutter Mobile App Execution

```
# Navigate to mobile app directory
cd mobile_app
flutter pub get
flutter run -d <device-id>
```

B.5 Performing a Multimodal Journey Search

- **Step 1: Input Coordinates:** Enter origin (e.g., 'Majestic Bus Stand') and destination (e.g., 'Indiranagar Metro Station') in the search header.
- **Step 2: Set Preferences:** Choose routing preference: 'Cheapest' (prioritizes BMTC Bus / Metro), 'Fastest' (prioritizes Metro / Cab), or 'Balanced' (MAUT).
- **Step 3: Compare Results:** Swipe through side-by-side mode cards displaying total duration, exact fare, transfer count, and weather badges.

B.6 Selecting BMTC Route Variants and Live Ride Navigation

- **Candidate Bus Variants:** Tap the BMTC transit card to view alternative buses serving the same corridor (e.g., 500D, 356, KIA-8). Selecting an alternative route instantly recalibrates polylines and stop countdowns.
- **Engage Ride Mode:** Tap 'Start Live Ride Mode' to activate GPS tracking. The application streams turn-by-turn alerts and triggers voice announcements as upcoming stops approach.

B.7 Interacting with the RAG Transit Assistant

- **Open Chatbot Screen:** Tap the 'AI Transit Assistant' tab in the bottom navigation bar.
- **Query Localized Policies:** Ask questions such as: 'What is the student bus pass fare for college routes?', 'How do I reach the airport at 2 AM?', or 'Check my car insurance expiry'.
- **Instant Verified Guidance:** The in-memory RAG engine retrieves exact excerpts from the indexed document vaults, generating grounded, verifiable advice.

B.8 Troubleshooting and FAQ

- **Issue 1: Port 8000 Conflict:** Execute `netstat -ano | findstr :8000` on Windows and terminate the conflicting PID using `taskkill /PID <pid> /F`.
- **Issue 2: Cold-Start Graph Delay:** The initial BMTC graph compilation requires ~130 seconds on clean boot. Subsequent queries execute with sub-250 ms warm latency.
- **Issue 3: Mobile GPS Timeout in Emulator:** In the Android Emulator Extended Controls, ensure 'Location Services' are enabled and mock GPS coordinates are actively streaming.