ASSIGNMENT ON DDL

- CREATE THESE STRUCTURE OF THE TABLE AND CONNECT THESE TABLE.

Doctor
Doc_Id
Doc_Name
Contact
Salary
Email_Id

Patient
Pat_Id
Doc_Id
Pat_Ph_No
Disease_Name
Total_Bill

(RENAME THE TABLE DOCTOR TO DOC & PATIENT TO PAT)

```
  1  create table doctor
  2  (
  3  Doc_Id number(4) primary key check(Doc_Id > 0) check(length(Doc_Id)=2),
  4  Doc_name varchar(25) not null,
  5  Contact number(10) unique not null check(contact > 0) check(length(contact)=10),
  6  Salary number(6) not null,
  7  Email varchar(25) not null
  8* )
SQL> /

Table created.
```

```
  1  create table Patient
  2  (
  3  Pat_Id number(4) primary key check(Pat_Id > 0) check(length(Pat_Id)=2),
  4  Doc_Id number(4) not null check(doc_Id > 0) check(length(doc_Id)=2),
  5  Pat_Ph_No number(10) unique not null check( Pat_Ph_No> 0) check(length(Pat_Ph_No)=10),
  6  Disease_Name varchar(30) not null,
  7  Total_Bill number(6) not null
  8* )
SQL> /

Table created.
```

```
SQL> rename doctor to doc;

Table renamed.

SQL> rename patient to pat;

Table renamed.
```

```
  1  alter table pat
  2  add constraint Fk_d_id FOREIGN KEY(doc_id)
  3* references doc(doc_id)
SQL> /

Table altered.
```

- CREATE TABLE **"CHEF"** AS PER THE FOLLOWING INSTRUCTIONS.

COLUNM_NAME	DATATYPES	CONSTRAINS
Chef_name	CHAR(30)	NOT NULL
Chef_rank	NUMBER(20)	NOT NULL
Chef_sing_Dish	VARCHAR(30)	NOT NULL
Hired_date	DATE	NOT NULL
Salary	NUMBER(10,3)	NOT NULL
Head_of_the_chef	CHAR(30)	NOT NULL

```
  1  create table CHEF
  2  (
  3  Chef_name CHAR(30) NOT NULL,
  4  Chef_rank NUMBER(20) NOT NULL,
  5  Chef_sing_Dish VARCHAR(30) NOT NULL,
  6  Hired_date DATE NOT NULL,
  7  Salary NUMBER(10,3) NOT NULL,
  8  Head_of_the_chef CHAR(30) NOT NULL
  9* )
SQL> /

Table created.
```

DO AS DIRECTED BASED ON TABLE CHEF:--

⍰ Add a new column "Chef_ph_no" into table "CHEF" & rename it to "Chef_mob_no".

```
  1  ALTER TABLE CHEF
  2* ADD Chef_phone_no number(10) unique not null check(Chef_phone_no > 0) check(length(Chef_phone_no) = 10)
SQL> /

Table altered.
```

```
  1  ALTER TABLE CHEF
  2* RENAME COLUMN Chef_phone_no to Chef_mob_no
SQL> /

Table altered.
```

⍰ Drop the Head_of_the_chef column from the table.

```
SQL> ALTER TABLE CHEF
  2  DROP COLUMN Head_of_the_chef;

Table altered.
```

⍰ For “Chef_name” column change the datatype into VARCHAR (50) & FOR “Salary” column change it to NUMBER (15,7).

```
  1  ALTER TABLE CHEF
  2  MODIFY chef_name varchar(50)
  3* MODIFY salary number(15,7)
SQL> /

Table altered.

SQL> desc chef;
 Name                                                  Null?    Type
 ----------------------------------------------------- -------- ------------------------------------
 CHEF_NAME                                             NOT NULL VARCHAR2(50)
 CHEF_RANK                                             NOT NULL NUMBER(20)
 CHEF_SING_DISH                                        NOT NULL VARCHAR2(30)
 HIRED_DATE                                            NOT NULL DATE
 SALARY                                                NOT NULL NUMBER(15,7)
 CHEF_MOB_NO                                           NOT NULL NUMBER(10)
```

```
  1  ALTER TABLE CHEF
  2* MODIFY chef_name varchar(50)
SQL> /

Table altered.
```

```
  1  ALTER TABLE CHEF
  2* MODIFY salary number(15,7)
SQL> /

Table altered.
```

⍰ For “Chef_rank” assign a UNIQUE constraint & for “Salary” change it as null.

```
  1  ALTER TABLE CHEF
  2  MODIFY chef_rank unique
  3* MODIFY salary null
SQL> /

Table altered.
```

⍰ For “Hired_date” column 1st assign a unique constraint and then drop that constraint.

```
  1  ALTER TABLE CHEF
  2* ADD constraint H_date unique(Hired_date)
SQL> /

Table altered.
```

```
  1  ALTER TABLE CHEF
  2* DROP constraint H_date
SQL> /

Table altered.
```