AIAC ASSIGNMENT - 16.1

N.HARSHA

HTNO: 2303A51773

BATCH – 12

Taskl: Design a database schema for a Student Information System and generate queries using Al.

```
--Task; Design a database schema for a Student Tnfornation Systen and berate queriev using At. -- Or-OP tables already exist (to avoid errors)

DROPTABLE EXISTS Ennollnents;

OROP TABLE IF EXISTS students; DROP TABLE IF EXISTS Courses;

-- Students Table
CREATE TABLE Students (
    student_id INTEGER PRIMARY KEY AUTOINCREMENT,
    first_name TEXT NOT NULL,
    last_name TEXT NOT NULL,
    date_of_birth TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);

-- Courses Table
CREATE TABLE Courses (
    course_id INTEGER PRIMARY KEY AUTOINCREMENT,
    course_name TEXT NOT NULL,
    course_code TEXT UNIQUE NOT NULL,
    credits INTEGER NOT NULL
);

-- Enrollments Table
CREATE TABLE Enrollments (
    enrollment_id INTEGER PRIMARY KEY AUTOINCREMENT,
    student_id INTEGER NOT NULL,
    course_id INTEGER NOT NULL,
    enrollment_date TEXT NOT NULL,
    FOREIGN KEY (student_id) REFERENCES Students(student_id),
    FOREIGN KEY (course_id) REFERENCES Courses(course_id)
);
```

1. Query : Insert a new student record

```
-- Enrollments Table
CREATE TABLE Enrollments (
    enrollment_id INTEGER PRIMARY KEY AUTOINCREMENT,
    student_id INTEGER NOT NULL,
    course_id INTEGER NOT NULL,
    enrollment_date TEXT NOT NULL,
    FOREIGN KEY (student_id) REFERENCES Students(student_id),
    FOREIGN KEY (course_id) REFERENCES Courses(course_id)
);

-- Insert Students
INSERT INTO Students (first_name, last_name, date_of_birth, e
VALUES
('John', 'Doe', '2000-01-15', 'john@example.com'),
('Jane', 'Smith', '1999-05-20', 'jane@example.com');
```

email)

- Insert Courses

InsERT INTO (course_name. credits)
'WOE s
(Introduction to Computer Science • •cslgl% 3),
C • Oatabase Systens•, •CS182% 4);

```
-- Enrollments
INSERT INTO Enrollments (student_id, course_id, enrol
VALUES
(1, 1, '2024-01-10'),
(1, 2, '2024-01-12'),
(2, 1, '2024-01-11');
```

Ime n t_ date)

2. Query : Fetch all courses enrolled by a student.

```
-- Insert Students
INSERT INTO Students (first_name, last_name, date_of_bi
VALUES
('John', 'Doe', '2000-01-15', 'john@example.com'),
('Jane', 'Smith', '1999-05-20', 'jane@example.com');

-- Insert Courses
INSERT INTO Courses (course_name, course_code, credits)
VALUES
('Introduction to Computer Science', 'CS101', 3),
('Database Systems', 'CS102', 4);

-- Enrollments
INSERT INTO Enrollments (student_id, course_id, enrolln
VALUES
(1, 1, '2024-01-10'),
(1, 2, '2024-01-12'),
(2, 1, '2024-01-11');

-- Query
SELECT s.first_name, s.last_name, c.course_name
FROM Students s
JOIN Enrollments e ON s.student_id = e.student_id
JOIN Courses c ON e.course_id = c.course_id
WHERE c.course_code = 'CS101';
```

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	course_name
John	Doe	Introduction to Computer Science
Jane	Smith	Introduction to Computer Science

3. Query : Count number of students in each course.

SQL ▾ 1 / 1 1 - 2 of 2

course_name	student_count
Introduction to Computer Science	2
Database Systems	1

..Count number of students In each Course.
SELECT c. Course_nme. COUNT (e. student_id) AS student cc
FRO" Courses c
LEFT Enrollnent5 e c. course_id = e.course_id
GROUP BY c.course_åd;

TASK 2 : Create schema and queries for a Hospital Management System.

- Create schema and queries for a Hospital management System

-- Drop tables if already exist (to avoid errors)
DROP TABLE IF EXISTS Appointments;
DROP TABLE IF EXISTS Patients;

OROP TABLE IF EXISTS Doctors; -- Patients Table

CREATE TABLE Patients (patient_id TNTEGER PRIMARY KEY AUTOINCREMENT, first naæ TEXT NOT NULL, last name

TEXT NOT NULL, date of birth TEXT NOT WLL, email TEXT UNIQUE TOT NULL

-- Doctors Table

CREATE TABLE Doctors doctor id INTEGER PRIMARY KEY AUTOINCRENENT, first name TEXT NOT NULL, last name TEXT NOT

NULL, specialty TEXT NOT NULL, email TEXT UNIQUE WLL

-- Appointments Table

CREATE TABLE Appointments (appointment_id INTEGER PRIMARY KEY AUTOINCREMENT, patient_id INTEGER NOT NULL, doctor id INTEGER MJLL, appointment_date TEXT NOT NULL,
FOREIGN KEV (patient_id) REFERENCES Patients(patient id). FOREIGN KEY (doctor_ld) REFERENCES

Doctors(doctor_id)

-- Appointments Table
CREATE TABLE Appointments (appointment_ld INTEGER PRIMARY KEY AUTOINCREMENT, patient_id INTEGER NOT NULL,
doctor Id INTEGER NOT 'LLC , appoint.ent_date TEXT NULL,
FOREIGN KEY (patient_id) REFERENCES patients (patient_id). FOREIGN KEV (doctor_id) REFERENCES

Doctors(doctor_id)

-- Insert Patients

INSERT INTO patients (first_nane, last_name, date_of_birth, email)
VALUES

ly',•clark% • anilyæxample. con ') ,
(•nichael , 'Broun•, '1990-11-es•, nichael@exanple.com) ;

-- Insert Doctors
IISERT INTO Doctors (first_name, last_name, specialty, email) VALUES
(•Dr. Sarah', •Johnson', • Cardiology' sarah.johnson@example.con•),
('Dr.David% 'Smith', •Neurology•, 'davld.smith@example.com');

-- Insert Appointnents
IISERT INTO Appointments (patient_id, doctor_id, appointment_date)
VALUES
(1, 1, '2024-07-01'),
(1, 2, '2024-07-15'),
(2, 1, '2024-07-10');

Query 1: List all appointments for a specific doctor.

```sql
-- Insert Patients
INSERT INTO Patients (first_name, last_name, date_of_birth, email)
VALUES
('Emily', 'Clark', '1985-07-12', 'emily@example.com'),
('Michael', 'Brown', '1990-11-05', 'michael@example.com');
-- Insert Doctors
INSERT INTO Doctors (first_name, last_name, specialty, email)
VALUES
('Dr. Sarah', 'Johnson', 'Cardiology', 'sarah.johnson@example.com'),
('Dr. David', 'Smith', 'Neurology', 'david.smith@example.com');
-- Insert Appointments
INSERT INTO Appointments (patient_id, doctor_id, appointment_date)
VALUES
(1, 1, '2024-07-01'),
(1, 2, '2024-07-15'),
(2, 1, '2024-07-10');

Ask for Edits Ctrl+I
-- List all appointments for a specific doctor.
SELECT p.first_name, p.last_name, a.appointment_date
FROM Patients p
JOIN Appointments a ON p.patient_id = a.patient_id
JOIN Doctors d ON a.doctor_id = d.doctor_id
WHERE d.email = 'sarah.johnson@example.com';
```

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	appointment_date
Emily	Clark	2024-07-01
Michael	Brown	2024-07-10

Query 2 : Retrieve patient history by patient ID.

```sql
-- List all appointments for a specific doctor.
SELECT p.first_name, p.last_name, a.appointment_date
FROM Patients p
JOIN Appointments a ON p.patient_id = a.patient_id
JOIN Doctors d ON a.doctor_id = d.doctor_id
WHERE d.email = 'sarah.johnson@example.com';

-- Retrieve patient history by patient ID.
SELECT d.first_name, d.last_name, a.appointment_date
FROM Doctors d
JOIN Appointments a ON d.doctor_id = a.doctor_id
JOIN Patients p ON a.patient_id = p.patient_id
WHERE p.patient_id = 1;
```

I-st

first

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	appointment_date
Emily	Clark	2024-07-01
Michael	Brown	2024-07-10

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	appointment_date
Dr. Sarah	Johnson	2024-07-01
Dr. David	Smith	2024-07-15

Query 3 : Count total patients treated by each doctor.

```sql
Ask for Edits Ctrl+I
-- Count total patients treated by each doctor.
SELECT d.first_name, d.last_name, COUNT(a.patient_id) AS patient_cour
FROM Doctors d
LEFT JOIN Appointments a ON d.doctor_id = a.doctor_id
GROUP BY d.doctor_id;
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	patient_count
Dr. Sarah	Johnson	2
Dr. David	Smith	1

TASK 3 : Design schema for a Library Management System

- Design schema for a Library Management System

Drop tables if already exist (to avoid errors)

```
DROP TABLE IF EXISTS Borryowings;
OROP TABLE IF EXISTS Books;

OROP TABLE IF EXISTS Membe
- Members Table
CREATE TABLE            ( id INTEGER PRIMARY
            AUTOINCREMENT. first_nane TEXT NOT last
            TEXT 'KIT NULL, email TEXT              ""T
      paJLL

Books Table
CREATE TABLE Books ( book_id INTEGER PRIMARY
      KEY AUTOINCREMENT. title        NOT UULL,
      author TEXT NOT NULL,
      isbn TEXT UNIWE
            NULL

- Borrowings Table
CREATE TABLE            ( borroulng_åd INTEGER PRIMARY
            AUTOINCREMENT, nor,ber id INTEGER   WLL,
```

book Id INTEGER NOT POLL, bor•rou date TEXT
NULL, retur•n date TEXT,
FOREIGN KEY REFERENCES S Members(member_id),
FOREIGN KEY (book_ld) Books(book_id)
REFERENCES

-- Insert members

INSERT
INTO
Venber•s

```
('Alice', 'Johnson', 'alice@example.com'),
('Bob', 'Smith', 'bob@example.com');
-- Insert Books
(first_name,last_nane, email )
('The Great Gatsby', 'F. Scott Fitzgerald', '978-0-7432-7356-5'),
('To Kill a Mockingbird', 'Harper Lee', '978-0-06-114803-6');
-- Insert Borrowings
INSERT INTO Borrowings (member_id, book_id, borrow_date, return_d
VALUES
(1, 1, '2024-08-01', '2024-08-15'),
(1, 2, '2024-08-16', NULL),
(2, 1, '2024-08-05', '2024-08-20');
```

return date)

VALUES

INSERT INTO Books (title, author, Isbn)
'ALOES

Query 1 : Retrieve all books currently issued.

```
-- Retrieve all books currently issued.
SELECT b.title, m.first_name, m.last_name, br.borrow_date
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
JOIN Members m ON br.member_id = m.member_id
WHERE br.return_date IS NULL;
```

1 / 1 1 - 1 0f1

SQL

title	first name	las t nam	date
To Kill %ckin8båre	•lice		ma-e-*-16

Query 2 : Find the most purchased product.

```
-- Retrieve all books currently issued.
SELECT b.title, m.first_name, m.last_name, br.borrow_date
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
JOIN Members m ON br.member_id = m.member_id
WHERE br.return_date IS NULL;

-- Find the most purchased product.
SELECT b.title, COUNT(br.borrowing_id) AS borrow_count
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
GROUP BY b.book_id
ORDER BY borrow_count DESC
LIMIT 1;
```

SQL ▾ 1 / 1 1 - 0 of 0

SQL ▾ 1 / 1 1 - 1 of 1

title	first_name	last_name	borrow_date
To Kill a Mockingbird	Alice	Johnson	2024-08-16

SQL ▾ 1 / 1 1 - 1 of 1

title	borrow_count
The Great Gatsby	2

Query 3 : Count number of books loaned by each member.

```
-- Find the most purchased product.
SELECT b.title, COUNT(br.borrowing_id) AS borrow_count
FROM Books b
JOIN Borrowings br ON b.book_id = br.book_id
GROUP BY b.book_id
ORDER BY borrow_count DESC
LIMIT 1;
Ask for Edits Ctrl+I
-- Count number of books loaned by each member.
SELECT m.first_name, m.last_name, COUNT(br.borrowing_id) AS borrow_count
FROM Members m
LEFT JOIN Borrowings br ON m.member_id = br.member_id
GROUP BY m.member_id;
```

To Kill a Mockingbird | Alice | Johnson | 2024-08-16

SQL ▾ 1 / 1 1 - 1 of 1

title	borrow_count
The Great Gatsby	2

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	borrow_count
Alice	Johnson	2
Bob	Smith	1

TASK 4 : Design a database for an E-commerce platform.

-- Design a database for an E-cor"erce platform,

-- Drop tables if already exist (to avoid errors)

DROP IF EXISTS Orders;
DROP TABLE IF EXISTS Products;
DROP TABLE If EXISTS custoners:

-- Customers Table
CREATE 'ABLE customers (customer_id INTEGER
PRIMARY KEY AUTOINCREMENT, first_name
TEXT NOT NULL.
last_name TEXT nor NULL s email

TEXT NOTNULL

Products I able
CREATE products (product_id PRIMRY KEY
AUTOINCREMENT , product_nane TEXT
WLL, pr•fte REAL KOT UULL, stock
INTEGER NOT 'WLL

-- Orders Table

CREATE TABLE orders C order Id INTEGER PRIMARY

KEY AUTOINCREtE-UT. stomer_id INTEGER NOT
'a.'LL, product_id TUTEGER NOT NULL, order date
TEXT NOT UI-ILL, quantity INTEGER
NULL,

FOREIGN KEY (customer id) REFERENCES customers(customer Id).
FOREIGN KEY (product_id) REFERENCES

Products(product_id)

-- Insert Custmers

INSERT INTO Customers (fir5t_nae. last_nane,email)
VALUES
(• John • 'Doe'. • •johneexarple.ccn•).
(• Jane • , • Stfth•. 'jane@example.com');

-• Insert Products
INSERT INTO Products (product_name, price, stock)
VALUES ('Laptop',
999.99, 1B),
('Mouse', 29.99, 50);
-- Insert Orders
INSERT INTO Orders (customer_id, product_id, order_date, quantity)
VALUES
(1, 1, '2024-08-01', 1),
(1, 2, '2024-08-01', 2),
(2, 1, '2024-08-02', 1);

Query 1 : Retrieve all orders by a user.

```
-- Retrieve all orders by a user.
SELECT c.first_name, c.last_name, p.product_name, o.order_date, o
FROM Customers c
JOIN Orders o ON c.customer_id = o.customer_id
JOIN Products p ON o.product_id = p.product_id
WHERE c.email = 'john@example.com';
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	product_name	order_date	quantity
John	Doe	Laptop	2024-08-01	1
John	Doe	Mouse	2024-08-01	2

2 : Find the most purchased product. Query

```
-- Retrieve all orders by a user.
SELECT c.first_name, c.last_name, p.product_name, o.order_date, o
FROM Customers c
JOIN Orders o ON c.customer_id = o.customer_id
JOIN Products p ON o.product_id = p.product_id
WHERE c.email = 'john@example.com';

-- Find the most purchased product.
SELECT p.product_name, SUM(o.quantity) AS total_quantity
FROM Products p
JOIN Orders o ON p.product_id = o.product_id
GROUP BY p.product_id
ORDER BY total_quantity DESC
LIMIT 1;
```

SQL ▾ 1 / 1 1 - 2 of 2

first_name	last_name	product_name	order_date	quantity
John	Doe	Laptop	2024-08-01	1
John	Doe	Mouse	2024-08-01	2

SQL ▾ 1 / 1 1 - 1 of 1

product_name	total_quantity
Laptop	2

Query 3 : Calculate total revenue in a given month

```
-- Find the most purchased product.
SELECT p.product_name, SUM(o.quantity) AS total_quantity
FROM Products p
JOIN Orders o ON p.product_id = o.product_id
GROUP BY p.product_id
ORDER BY total_quantity DESC
Ask for Edits Ctrl+I

-- Calculate total revenue in a given month
SELECT strftime('%Y-%m', o.order_date) AS month, SUM(p.price * o.
FROM Orders o
JOIN Products p ON o.product_id = p.product_id
GROUP BY month
ORDER BY month;
```

John	Doe	Mouse	2024-08-01	2

SQL ▾ 1 / 1 1 - 1 of 1

product_name	total_quantity
Laptop	2

SQL ▾ 1 / 1 1 - 1 of 1

month	total_revenue
2024-08	2059.96

1 - 1 of 1

TASK 5 : Design a database schema for a University Examination System and generate SQL queries using Al.

- Design a database schema for university Examination System and generate SQL queries using Al. - Orop tables if already exist (to avoid

OROP

DROP TABLE IF EX15T5 students;

DROP TABLE IF EX15T5 Exams; -.-

Students Table

CREATE TABLE students (student_id INTEGER PRIRARV KEY

AUTOINCREMENT, first_name TEXT NULL, last name

```
    last_name TEXT NOT NULL,
    date_of_birth TEXT NOT NULL,
    email TEXT UNIQUE NOT NULL
);
-- Exams Table
CREATE TABLE Exams (
    exam_id INTEGER PRIMARY KEY AUTOINCREMENT,
    course_name TEXT NOT NULL,
    exam_date TEXT NOT NULL
);
-- ExamResults Table
CREATE TABLE ExamResults (
    result_id INTEGER PRIMARY KEY
    student_id INTEGER NOT NULL,
    exam_id INTEGER NOT NULL,
```

AUTOINCREMEUT.

exam id TUTEGER score

REAL NOT NULL,

FOREIGN KEY (student_id) REFEREuCäS

FOREIGN KEY (exer_id) REFERENCES

CREATE TAELE Exams (exam_id INTEGER PRIMARY KEY

AUTOINCREMENT, course name TEXT NULL,

exam_date TEXT NULL

-.- ExamResuIts Table

CREATE TABLE ExanResu1ts (result id TUTE6ER PRrmARY KEV

AUTOTNcREHENT,

student id NOT NULL

exam_id TuTF6ER NOT uuLL,

scoreREAL NOTNULL.

FORF16N KEY (student_id) REFERENCES ES Students(student_id),

FOREIGN KEY (exam_id) REFERENCES Exams(exam_id)

-— Insert Students

INSERT students (first_nane, last_name, date_of_birth, email)

VALUES

(•Alice• , •Johnson', •2em-ø3-22", •alice@example.com•),

('Bob' , • Smith' . • 2øee-e7-Is•,'bob@example.com');

_- Insert

Exams

INSERT INTO Exans (course_name, exam_date)

VALUES

'2e24•e-zs•). (

'Physics'.

Insert Exam ResuLt5

(student_id, exam_id score)

VALUES

(1, 1, gs.5).

(1.

g2.

ey.

(2, 1, 78.e),

Query I : Insert examination results for a student.

__Query 1 : Insert examination results for a student.

INSERT INTO ExamResu1ts (student_id, exam_id, score)

VALUES (1, 1, 85.5);

Query 2: Retrieve subject-wise marks for a student.

```
-- Query 2: Retrieve subject-wise marks for a student.
SELECT e.course_name, er.score
FROM ExamResults er
JOIN Exams e ON er.exam_id = e.exam_id
WHERE er.student_id = 1;
```

smaøe_næe	Score
"athenatiC5	85. S
"athematics	85.5

Query 3 : Calculate average marks for each subject.

```
-- Query 3: Calculate the average score for a specific exam.
SELECT e.course_name, AVG(er.score) AS average_score
FROM ExamResults er
JOIN Exams e ON er.exam_id = e.exam_id
WHERE e.course_name = 'Mathematics'
GROUP BY e.exam_id;
```

Mathematics | 85.5

SQL ▾ 1 / 1 1 - 1 of 1

course_name	average_score
Mathematics	83.0

1 - 1 0+1

LAB OBSERVATIONS

- Objective

To design and implement database schemas for various real-world systems and perform SQL operations such as table creation, data insertion, and query execution using SQL.

Observation 1: Student Information System

- Createdthreetables: Students, Courses, Enrollments.
- Established many-to-many relationship usingabridge table (Enrollments).
- Used primary keys and foreign keys to maintaindata integrity.

- Inserted sample student and course data successfully.
- Performed queries to:
- Retrieve students enrolled in a specific course.
- Count number of students in each course.
- Observedthat JOIN operations help combinedatafrom multiple tables.

Observation 2: Hospital Management System

- Designedtables: Patients, Doctors, Appointments.
- Implemented relationships using foreign keys.
- Inserted patient, doctor, and appointment data.
- Executed queries to:
- List appointments for a specific doctor.
- Retrieve patient history.
- Count total patients handled by each doctor.
- Observedthat LEFT JOIN helpsincludedoctors with no appomtments.

Observation 3: Library Management System

- Createdtables: Members, Books, Borrowings.
- Maintained relationships using foreign keys.
- Inserted borrowing records with return status.
- Executed queries to:
- Find currently issued books (using NULL condition).
- Identify most borrowed book.
- Count books borrowed by each member.
- Observed that NULL values are useful for tracking incomplete actions (e.g., not returned books).
- Observation 4: E-Commerce System
- Designed tables: Customers, Products, Orders.
- Established relationships using foreign keys.
- Inserted sample order and product data.

- Executed queries to:
- Retrieve all orders by a specific customer.
- Find most purchased product.
- Calculate total revenue per month.
- Observed that aggregate functions (SUM, COUNT) are useful for business analysis.

- Observation 5: University Examination System

.Created tables: Students, Exams,ExamResults .

- Linked students and exams using a result table.
- Inserted exam and result data.
- Executed queries to:
- Retrieve subject-wise marks.
- Calculate average scores for exams.

.Observed that GROUP BY and AVG functionshelp in performance evaluation.