

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*

1. State how you checked your analytic gradient computations and whether you think that your gradient computations were bug free. Give evidence for these conclusions.

Gradient for the network parameter theta: W and b were implemented based on the analytical solution. Correctness of the computed analytical gradients are validated against numerically computed gradients(fast) measured in terms of relative error. Relative error is computed from the $rerr(g_a, g_n)$ function. g_a : Analytical gradient & g_n : Numerical gradient.

$$\frac{|g_a - g_n|}{\max(\epsilon, |g_a| + |g_n|)}$$
 where ϵ is a small number;

Results were obtained as follows:

For feature size = 20, n = 2 images, h = 1e-5

Relative error	W1	b1	W2	b2
Lambda = 0	2.19e-06	6.31e-06	5.83e-07	1.99e-06
Lambda = 0.1	9.64e-05	6.31e-06	1.18e-04	1.99e-06
Lambda = 1	1.15e-04	6.28e-06	1.04e-04	1.99e-06

Relative error values are very low. Thus, the correctness of the implementation of analytical gradient is ensured. Even with significant value of hyperparameter *lamda* the relative error remained low.

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*

2. The curves for the training and validation cost when using the cyclical learning rates with the default values, that is replicate figures 3 and 4. Also comment on the curves.




Figure a

Cost plot with cyclic learning rate strategy




Figure b

Cost plot without cyclic learning rate strategy




Figure c

Accuracy plot with cyclic learning strategy




Figure d

Accuracy plot without cyclic learning strategy

Note: Instead of updates, epoch is considered for figure a & b, due to my PC not handle the load of cost evaluation at each update. Here each epoch corresponds to 100 updates. At each epoch the batches were shuffled. The hyper-parameter settings of the training algorithm are $\eta_{\min} = 1e-5$, $\eta_{\max} = 1e-1$, $\lambda=0.01$ and $n_s=500$.

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*

Training is the crucial part of neural network. Performance of this system is based on the convergence of the network parameters to its optimal values corresponding to minimal cost. Cyclical learning rate is a strategy which accelerates the rate of convergence.

From the above graphs it's evident that with the application of cyclical learning rate strategy, better accuracy & lower cost are achieved in the same limited time by huge margin. Graph also indicates the divergence in accuracy and cost amongst validation and training set, however, it is the question about regularization whose value λ needs to be selected properly. Total time taken in either cases were $\sim 227s$.

Accuracy plot and eta values captured at each update is shown below. Total time $\sim 420s$.




Figure e
Accuracy plot with cyclic learning strategy




Figure f
eta values at each update

Similarly for the hyper-parameter settings $\eta_{\min} = 1e-5$, $\eta_{\max} = 1e-1$, $\lambda=0.01$ and $n_s=800$, 3 cycles. The graphs are shown below.

Extension to the previous case, learning was carried out until 3 cycles. Significant rise from 60% training accuracy to 72% for two extra cycle is huge computational leap. End of training, 47.02% of accuracy on test data was achieved.

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*




Figure e
eta values at each update




Figure a
Cost plot with cyclic learning rate strategy




Figure b
Cost plot without cyclic learning rate strategy




Figure c
Accuracy plot with cyclic learning strategy




Figure d
Accuracy plot without cyclic learning strategy

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*

3. State the range of the values you searched for λ , the number of cycles used for training during the coarse search and the hyper-parameter settings for the 3 best performing networks you trained.

Range of λ $1e-5$ to $1e-1.5$, range of η $1e-5$ to $1e-1$ cyclic, 2 cycles, batch_size = 100, ns = 800, Layers = 2, Hidden nodes = 50. Graph below is a plot of Accuracy vs. λ




Fig 2. Coarse search: Accuracy vs. Lambda Plot.

Data set: Train set = 40,000 (PC hardware limitations), Validation set = 5000, Test set = 10,000. Best performance were observed for $\lambda = 1e-3.25$, $1e-4$ and $1e-4.25$ with accuracy above 51% with peak of 52.22% around $1e-3.25$ for the validation set.

4. State the range of the values you searched for λ , the number of cycles used for training during the fine search, and the hyper-parameter settings for the 3 best performing networks you Trained.

Range of λ chosen in the vicinity of peak accuracy observed in the coarse search i.e., about $1e-3.25$ and thus, the fine search bandwidth is set as $1e-3.75$ to $1e-2.75$, range of η $1e-5$ to $1e-1$ cyclic, 2 cycles, batch_size = 100, ns = 800, Layers = 2, Hidden nodes = 50. Graph below is a plot of Accuracy vs. λ

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*




Fig 3. Fine search: Accuracy vs. Lambda Plot.

Data set: Train set = 40,000 (PC hardware limitations), Validation set = 5000, Test set = 10,000. Best performance were observed for $\lambda = 1e-2.98$, $1e-3.07$ and $1e-3.23$ with accuracy all above 52% with peak of 52.81% at $1e-2.98$ for the validation set.

5. For your best found lambda setting , train the network on all the training data, except for 1000 examples in a validation set, for 3 cycles. Plot the training and validation loss plots and then report the learnt network's performance on the test data.

Value of λ chosen to be $1e-2.98$, range of η $1e-5$ to $1e-1$ cyclic, 3 cycles, batch_size = 100, ns = 800, Layers = 2, Hidden nodes = 50. Graph below is a plot of Accuracy vs. λ .




Figure a
Cost plot




Figure b
Accuracy plot

DD2424 A2

Harsha Holenarasipura Narasanna *harshahn@kth.se*

Involved Epochs: 12, Itr: 1, Cycles: 3, Updates: 5880, Training data size: 49,000 images, Validation data size: 1,000. Test data size: 10,000. Final accuracy on test set: 52.28% and total time taken 941.33s




Figure c
eta values at each update