

API Documentation

The application interacts with a RESTful API at `http://localhost:5000/api` (configurable via environment variables). In development mode, API calls are mocked with data stored in `localStorage`. Below are the primary endpoints used by the frontend.

Authentication

- **POST /api/auth/register** - Register a new user

- Body: `{ username, email, password }`

- Response: `{ token, user }`

- **POST /api/auth/login** - Login an existing user

- Body: `{ email, password }`

- Response: `{ token, user }`

- **GET /api/auth/me** - Get current user information

- Headers: `Authorization: Bearer <token>`

- Response: `{ user }`

- **PUT /api/auth/profile** - Update user profile

- Headers: `Authorization: Bearer <token>`

- Body: `{ firstName, lastName, email, username, bio, phone, address }`

- Response: `{ message, user }`

Books

- ****GET /api/books**** - Get list of books with pagination and search
 - Query Params: `page, limit, search`
 - Response: `{ books, totalPages, currentPage, total }`
- ****GET /api/books/:id**** - Get details of a specific book
 - Response: `{ \_id, title, authors, description, price, stock, category, imageLinks }`
- ****GET /api/books/google/search**** - Search Google Books API through backend
 - Query Params: `q, startIndex, maxResults, filter`
 - Response: `{ books, totalItems }`
- ****POST /api/books/import/:googleBookId**** - Import a book from Google Books
 - Body: `{ title, authors, description, price, stock, category }`
 - Response: `{ \_id, title, authors, ... }`

Cart

- ****GET /api/cart**** - Get current user's cart
 - Headers: `Authorization: Bearer <token>`
 - Response: `{ cart: { items, totalAmount } }`

- ****POST /api/cart/add**** - Add item to cart
 - Headers: ` Authorization: Bearer <token> `
 - Body: `{ bookId, quantity }`
 - Response: `{ success, cart }`
- ****PUT /api/cart/update/:itemId**** - Update cart item quantity
 - Headers: ` Authorization: Bearer <token> `
 - Body: `{ quantity }`
 - Response: `{ success, cart }`
- ****DELETE /api/cart/remove/:itemId**** - Remove item from cart
 - Headers: ` Authorization: Bearer <token> `
 - Response: `{ success, cart }`
- ****DELETE /api/cart/clear**** - Clear cart
 - Headers: ` Authorization: Bearer <token> `
 - Response: `{ success, cart }`

Orders

- ****POST /api/orders/checkout**** - Complete purchase and create order
 - Headers: ` Authorization: Bearer <token> `
 - Body: `{ items, shippingInfo, paymentInfo, totalAmount }`
 - Response: `{ success, order }`

- ****GET /api/orders**** - Get user's order history

- Headers: ` Authorization: Bearer <token> `

- Response: `{ orders }`

- ****GET /api/orders/:id**** - Get specific order details

- Headers: ` Authorization: Bearer <token> `

- Response: `{ order }`