



Data Science Intern at Data Glacier

Project: Hate Speech Detection using Transformers (Deep Learning)

Week 10: Report

Name: Harshad S. Chormare

University: University of Mumbai

Email: chormareharshad@gmail.com

Country: India

Specialization: Data Science

Batch Code: LISUM19

Date: 30 May 2023

Submitted to: Data Glacier

Table of Contents:

1. Project Plan	3
2. Problem Statement.....	3
3. Data Collection	3
4. Data Preprocessing	4
4.1. Text Cleaning.....	4
4.1.1. Lower Case.....	4
4.1.2. Remove Punctuation.....	4
4.1.3. Remove URL.....	4
4.1.4. Remove @tags.....	4
4.1.5. Remove Special Characters.....	4
4.2. Preprocessing Operations	4
4.2.1. Tokenization.....	4
4.2.2. Remove Stop Words.....	5
4.2.3. Lemmatization.....	5
4.2.4. WorldCloud	5
4.3. Feature Extraction.....	6
4.3.1. TF-IDF Model	6
4.4. Split the Dataset into Train and Test	6
5. Build the Model	6
5.1. CNN with LSTM	6
6. Result Evaluation	7
6.1. Evaluation Criteria.....	7
7. Application Design	8
7.1. Turning ML Model Into Flask Framework	9
7.2. Running Procedure	10
8. Conclusion	11
Reference.....	12

1. Project Plan

Weeks	Date	Plan
Weeks 07	April 19, 2023	Problem Statement, Data Collection, Data Report
Weeks 08	April 26, 2023	Data Preprocessing (Text Cleaning)
Weeks 09	May 2, 2023	Data Preprocessing (Preprocessing Operation + Feature Extraction)
Weeks 10	May 9,2023	Building the Model
Weeks 11	May 16,2023	Model Result Evaluation
Weeks 12	May 23,2023	Build ML APP Based on Flask
Weeks 13	May 30,2023	Final Submission (Report + Code + Presentation + Application)

2. Problem Statement

The term hate speech is understood as any type of verbal, written or behavioural communication that attacks or uses derogatory or discriminatory language against a person or group based on what they are, in other words, based on their religion, ethnicity, nationality, race, color, ancestry, sex or another identity factor. In this problem, we will take you through a hate speech detection model with Machine Learning and Python.

Hate Speech Detection is a task of sentiment classification. So, for training, a model that can classify hate speech from a certain piece of text can be achieved by training it on a data that is used to classify sentiments. So, for the task of hate speech detection model, we will use the Twitter tweets to identify tweets containing Hate speech.

3. Data Collection

The Data is about Twitter hate Speech taken from Kaggle which contains the 3 number of features and 31962 number of observations. Dataset using Twitter data, it was used to research hate-speech detection. The text is classified as: hate-speech, offensive language, and neither. Due to the nature of the study, it is important to note that this dataset contains text that can be considered racist, sexist, homophobic, or offensive.

Table 1: Data Information

Total number of observations	31962
Total number of files	1
Total number of features	3
Base format of the file	csv
Size of the data	2.95 MB

4. Data Preprocessing

In part, we explain the data preprocessing approach that we apply in the text data.

4.1 Text Cleaning

First, we clean our text because it was so messy data.

4.1.1 Lowercase

Converting a word to lower case (NLP -> nlp). Words like Racism and racism mean the same but when not converted to the lower case those two are represented as two different words in the vector space model (resulting in more dimensions). Therefore, we convert all text word into lower case letter.

4.1.2 Remove Punctuation

It is important to remove the Punctuation because is not important. Therefore, we remove that Punctuation to do that we use regular expression.

4.1.3 Remove URLs

In this part, we remove URLs because we are working on hate speech application which detect the hate and free speech and to get the output, we need to give only text not URLs therefore, we remove the URLs because we need only clean text input.

4.1.4 Remove @tags

In this part, we remove @tags which used when we mentioned someone So, it's doesn't concern to our application therefore, we remove @tags by using regular expressions.

4.1.5 Remove Special Characters

Remove Special Characters is essentially the following set of symbols [!"#\$%&'()*+,-./:;<=>?@[^_`{|}~] which basically don't have meaning. Therefore, we remove that kind of symbols because we don't need that. To remove we use python isalnum method.

4.2 Preprocessing Operation

In this part, we implement the preprocessing operation

4.2.1 Tokenization

Tokenization is breaking the raw text into small chunks. Our text data is into paragraph so to convert into work tokenize we use nltk word_tokenize library. These tokens help in

understanding the context or developing the model for the NLP. The tokenization helps in interpreting the meaning of the text by analyzing the sequence of the words.

4.2.2 Removing StopWords

StopWords is basically ‘a,’ ‘is,’ ‘the,’ ‘are’ etc. If we see our dictionary, then these words do not have meaning and don’t need that to build Hate speech detection application. To remove stop words from a sentence, we divide text into words which we did above in tokenization and then remove the word if it exists in the list of stop words provided by NLTK. To do that, we first import the StopWords collection from the nltk.


4.2.3 Lemmatization

Lemmatization is the process of grouping together the different inflected forms of a word so they can be analyzed as a single item. Lemmatization is like stemming but it brings context to the words. So, it links words with similar meanings to one word. Like the word Intelligently, intelligence, convert into root form intelligent.

4.2.4 WordCloud

A Wordcloud is a visual representation of text data, which is often used to depict keyword metadata on websites, or to visualize free form text. Tags are usually single words, and the importance of each tag is shown with font size or color.

Below you see the hate speech and free speech WorldCloud:



4.3 Feature Extraction

4.3.1 TF-IDF Model

Once the dictionary is ready, we apply Term Frequency-Inverse Document Frequency (TF-IDF) model, and we take 2000 most frequent words from dictionaries for each Hate/Free Speech of the whole dataset. Each word count vector contains the frequency of 2000 words in the whole dataset file.

4.4 Split the Data into Train into Test


In this part, we split the data into Train. And we split 80% for training and 20% for test. Data splitting is when data is divided into two or more subsets. Typically, with a two-part split, one part is used to evaluate or test the data and the other to train the model. Data splitting is an important aspect of data science, particularly for creating models based on data.

4.5 Build the Model

In this part, we build the CNN with LSTM Model using Tensorflow.

4.5.1 CNN with LSTM

The CNN LSTM architecture involves using Convolutional Neural Network (CNN) layers for feature extraction on input data combined with LSTMs to support sequence prediction. This architecture was originally referred to as a Long-term Recurrent Convolutional Network or LRCN model, although we will use the more generic name “CNN LSTM” to refer to LSTMs that use a CNN as a front end in this lesson. [2].



5. Result Evaluation and Discussion

In this chapter, we evaluate our Result and also define the evaluation criteria to calculate the performances of our best classification model.

5.1 Evaluation Criteria

The confusion matrix was used to evaluate the classification models throughout the training process. The confusion matrix is a table that compares predicted and actual outcomes. It is frequently used to describe a classification model's performance on a set of test data.

Class	Predicted Negative	Predicted Positive
Actual Negative	TN	FP
Actual Positive	FN	TP

Important metrics were constructed from the confusion matrix in order to evaluate the classification models. In addition to the accurate classification rate or accuracy, other metrics for evaluation included True Positive Rate (TPR), True Negative Rate (TNR), False Positive Rate (FPR), False Negative Rate (FNR), Precision, F1 score, and Misclassification rate.





Table 6.2 shows the final result that we evaluate on the basis of confusion matrix result

Classifiers	Accuracy	Precision	TPR	FPR	F1 Score	Error Rate	Specificity
CNN with LSTM	0.9577	0.8382	0.4191	0.0055	0.5588	0.0422	0.9944

Below you can see the visualization result of above table as well.



5. Application Design

In this chapter, we develop a Model & Deploy It with Flask. Our model systems workflow is like this: Train offline -> Make model available as a service -> Predict online.

- A classifier is trained offline with Fake and True news.
- The trained model is deployed as a service to serve users.