

🌟 LECTURE 16 — REDUCE, MAP & SET

◆ REDUCE() — Array → Single Value

👉 What is reduce()?

`reduce()` ek **array method** hai jo poore array par iterate karke **ek final result** banata hai.

📌 Final result **kisi bhi type ka ho sakta hai**:

- 📦 Number
- 🗄 String
- 📄 Object
- 📑 Array

💡 First-Principle Explanation (Box Analogy)

Socho ek **dabba (box)** hai:

- har array element dabbe me jaata hai
- dabba har step pe update hota rehta hai
- **end me jo bachta hai → wahi reduce ka output**

➡ Isi process ko JS `reduce()` kehta hai.

◆ Reduce Syntax

```
array.reduce((accumulator, currentValue) => {  
  // logic  
  return updatedAccumulator;  
}, initialValue);
```

◆ Parameters Explained

- **accumulator (acc)** → pichle step ka result
- **currentValue (curr)** → current element
- **initialValue** → starting value (MOST IMPORTANT)

📌 Rule:

- sum ke liye → 0
- object banana ho → {}

◆ Example 1: Sum of Numbers

```
const arr = [10, 20, 30, 40, 50];
```

```
const sum = arr.reduce((acc, curr) => acc + curr, 0);
```

```
console.log(sum);
```

✅ Output

150

🧠 Working

- $acc = 0$
 - $0 + 10 \rightarrow 10$
 - $10 + 20 \rightarrow 30$
 - $30 + 30 \rightarrow 60$
 - $60 + 40 \rightarrow 100$
 - $100 + 50 \rightarrow \mathbf{150}$
-

◆ Example 2: Frequency Count (VERY IMPORTANT)

```
let fruits = [  
  "orange", "apple", "banana",  
  "orange", "apple", "banana",  
  "orange", "grapes"  
];  
  
const result = fruits.reduce((acc, curr) => {  
  if (acc.hasOwnProperty(curr)) {  
    acc[curr]++;  
  } else {  
    acc[curr] = 1;  
  }  
  return acc;  
}, {});
```

✅ Output

```
{  
  orange: 3,  
  apple: 2,  
  banana: 2,  
  grapes: 1  
}
```

📌 Use-cases

- word count
- votes count

- cart items
- analytics

🧠 One-line Yaad Rakhna

“Sabko mila, ek cheez bana” = `reduce()`

◆ MAP — Advanced Key-Value Store

👉 What is Map?

Map ek **built-in object** hai jo **key-value pairs** store karta hai.

◆ Why Map is Powerful

- keys **kisi bhi type** ki ho sakti hain
 - insertion order maintain hota hai
 - fast add / delete / search
-

◆ Basic Map Operations

```
const map1 = new Map();
```

```
map1.set(3, 90);
```

```
map1.set("Rohit", 45);
```

```
map1.set(20, "Mohan");
```

```
map1.set("Rohit", 40); // overwrite
```

```
map1.delete(3);
```

```
console.log(map1.has("Rohit")); // true
```

```
console.log(map1.size); // 2
```

```
map1.clear();  
  
console.log(map1); // Map(0) {}
```

◆ Map with Initial Values

```
const map2 = new Map([  
  [4, "rohit"],  
  ["Moahn", "rohan"],  
  [30, 9],  
  [63, 78]  
]);
```

◆ Iterating Map

```
for (let [key, value] of map2) {  
  console.log(key, value);  
}  
  
map2.forEach((value, key) => {  
  console.log(key, "👉", value);  
});
```

◆ Map vs Object

Feature	Object	Map
Key Type	String	Any
Order	✗	✓
Size	✗	✓
Iterable	✗	✓

📌 Interview Points

- Map iterable hota hai
- `10 !== "10"` in Map

◆ SET — Unique Values Collection

👉 What is Set?

Set sirf **unique values** store karta hai.
Duplicate values **automatically remove** ho jaati hain.

◆ Set with Duplicates

```
const setA = new Set([10, 20, 30, 40, 10, 30]);  
  
console.log(setA);
```

✓ Output

```
Set(4) {10, 20, 30, 40}
```

◆ Set Methods

```
const set1 = new Set();
```

```
set1.add(4);
```

```
set1.add("Rohit");
```

```
set1.add(30);
```

```
set1.delete(6);
```

```
console.log(set1.size);
```

◆ Array → Set → Array (Remove Duplicates)

```
let arr = [10, 30, 20, 10, 40, 50, 30];
```

```
arr = [...new Set(arr)];
```

```
console.log(arr);
```

✅ Output

```
[10, 30, 20, 40, 50]
```

📌 MOST COMMON INTERVIEW QUESTION

◆ Set Operations




```
// Union
```

```
new Set([...setX, ...setY]);
```

```
// Intersection
```

```
new Set([...setX].filter(x => setY.has(x)));
```

SHORT SUMMARY – Ek Nazar Me

-  **reduce()** → Array → single value/object
-  **Map** → advanced key-value store
-  **Set** → unique values only

Memory Trick

- reduce = calculation
- Map = lookup table
- Set = no duplicates

Harshal Chauhan