# Graph Class - 7 [ MEGA ]

Special class

**Love Babbar** • Mar 8, 2024


Dijkstra
SSSP
Greedy
Set
heap
re-evaluate


src
A
B
C
2
4
3
digest this
will be back
in 2 min


{3, C}
{2, B}
{0, A}
{0, src}
set / pq


A
2
B
3
C


B
2
4
C


dist
0
1
2
0
2
3
A
B
C

-ve weights :-







set/pq




-ve cycle
DIJ
fails
src
A
B
C
-2
-4
-3
{-11, 1}
{-1, 4}
{-1, 1}
{-2, 1B}
{0, A}
ACT/PQ
0
-2
B
-9
A
-2
-3
C
-4
A
A
B
C
-9
-11
-5
0
1
2


-ve cycle
Bellman ford Algo:
SSSP
SP
-ve cycle - SP/A
N nods
N-1
times
why
Relaxation
if ( dist[u] + wt < dist(v) )
update
4 nods
src
A
x
y
z


N=5
N-1 → 1 times
Edge List
A 0 -1 → B
B -1 2 → C
C 1 3 → D
D -2 5 → E
A 0 4 → E
B -1 3 → E
B -1 2 → D
D -2 1 → B
A
B
C
D
E
-1
2
3
1
2
4
-2
5
dist
0
-1
1
-2
2
3
4
No updation
stop
final


B.F
N-1
N-1
guarantee
S.D
1 declaration
-ve cycle
Updation
No Updation

Floyd warshall :)

mssp




dist

| | 0 | 1 | 2 | 3 |
|---|---|---|---|---|
| 0 | 0 | ∞ | ∞ | ∞ |
| 1 | ∞ | 0 | ∞ | ∞ |
| 2 | ∞ | ∞ | 0 | ∞ |
| 3 | ∞ | ∞ | ∞ | 0 |




initial stuff → src → src → 0

dist[src][dst]

(dist[src][0] + dist[0][dst])

(dist[src][1] + dist[1][dst])

(dist[src][2] + dist[2][dst])

(dist[src][3] + dist[3][dst])

min


Gif
5-min
15.-20 min
3 week
Name
Phone no
Email id
registered email Id
2 → 3 min
Subscribe 2.0
Payment screenshot
Invoice details
Feedback
Review
Subscribe 2.0
Photo
Face → Passport Size
Invoice
JS

# Strongly Connected Component :- Kosaraju



→ Kosaraju ⟶ 2 tools ⟶ Edge Reversal

Dfs → count




0
1
3
2
5
4
6
7


dfs(0)
dfs(3)
dfs(2)
dfs(1)
SCC1


dfs(4)
dfs(6)
dfs(5)
SCC2


dfs(7)
SCC3


stack
0
1
2
3
4
5
6
7


Bridge in a Graph
Edge
Remove
no of disconnected component increases
1
0
2
3
4
Bridge
Bridge


tin
low
1
1
timer
1
already
vis
0
No back
2
tin
5
low
1
1 > 1
1 > 2
3
src
thr
Optional
tree
B.T
nbr
4
tin
4
low
4
node → time
curr → tin
low → low
low
timer → 1
A → B - 4
10 == 3
3 > 2
1 > 3
Bridge
found


tin
low
parent ignore
0
1
2
3
4
5
6
tin
low
Bridge
6 > 2