

# BOOTSTRAP 5

## 1. Setting Up Bootstrap 5

### Exercise 1.1: Bootstrap via CDN

```
<!DOCTYPE html>
<html>
<head>
  <title>Bootstrap CDN</title>

  <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>

<div class="container">
  <h1 class="text-primary">
    Welcome to Bootstrap 5
  </h1>
</div>

</body>
</html>
```

### Exercise 1.2: Bootstrap Using Downloaded Files

```
<!DOCTYPE html>
<html>
<head>
  <title>Bootstrap Local Files</title>

  <link rel="stylesheet" href="css/bootstrap.min.css">
</head>
<body>

<div class="container">
  <h2 class="text-success">
    Bootstrap Local Setup
  </h2>
</div>

<script src="js/bootstrap.bundle.min.js"></script>

</body>
</html>
```

## 2. Bootstrap Structure and Files

### Exercise 2.1

#### Bootstrap Folder Structure

### Exercise 2.2

```
<script src="js/bootstrap.bundle.min.js"></script>
```

## 3. Fundamentals of Responsive Grid Layout

### Exercise 3.1

```
<div class="container">
  <div class="row">

    <div class="col-12 col-md-6 col-lg-4 bg-primary text-white">
      Column 1
    </div>

    <div class="col-12 col-md-6 col-lg-4 bg-success text-white">
      Column 2
    </div>

    <div class="col-12 col-md-12 col-lg-4 bg-danger text-white">
      Column 3
    </div>

  </div>
</div>
```

### Exercise 3.2

```
<div class="container">

  <div class="row">

    <div class="col-sm-4 bg-info">
      First
    </div>

    <div class="col-sm-4 bg-warning">
      Second
    </div>

    <div class="col-sm-4 bg-secondary text-white">
      Third
    </div>

  </div>
</div>
```

## 4. Column Layouts and Grid Classes

### Exercise 4.1

```
<div class="container">
  <div class="row">

    <div class="col-md-3 bg-light">
      Sidebar
    </div>

    <div class="col-md-9 bg-info">
      Content Area
    </div>

  </div>
</div>
```

### Exercise 4.2

```
<div class="container">
  <div class="row">

    <div class="col-sm-3">Column 1</div>
    <div class="col-sm-3">Column 2</div>
    <div class="col-sm-3">Column 3</div>
    <div class="col-sm-3">Column 4</div>

  </div>
</div>
```

## 5. Alignment and Reordering in Grid

### Exercise 5.1

```
<div class="container">
  <div class="row justify-content-center align-items-center"
    style="height:200px;">
    <div class="col-4 bg-primary text-white">
      Centered Content
    </div>
  </div>
</div>
```

### Exercise 5.2

```
<div class="container">
  <div class="row">

    <div class="col-md-6 order-md-2 bg-warning">
```

```

        Column A
    </div>

    <div class="col-md-6 order-md-1 bg-success">
        Column B
    </div>

</div>
</div>

```

## 6. Responsive Flexbox Utilities

### Exercise 6.1

```

<nav class="d-flex flex-column flex-md-row bg-light p-3">

    <a class="p-2" href="#">Home</a>

    <a class="p-2" href="#">Events</a>

    <a class="p-2" href="#">Contact</a>

</nav>

```

### Exercise 6.2

```

<div class="card p-3">

    <div class="d-flex justify-content-between align-items-center">

        <h5>Community Event</h5>

        <button class="btn btn-primary">
            Register
        </button>

    </div>

</div>

```

## 7. Typography

### Exercise 7.1

```

<div class="container">

    <h1 class="display-1">
        Community Portal
    </h1>


```

```
<p class="lead">
  Welcome to Local Events
</p>
```

```
<p class="text-muted">
  Upcoming Activities
</p>
```

```
<p class="fw-bold">
  Important Notice
</p>
```

```
</div>
```

## Exercise 7.2

```
<p class="text-uppercase">
  community portal
</p>
```

```
<p class="text-lowercase">
  COMMUNITY EVENTS
</p>
```

```
<p class="text-capitalize">
  local community event portal
</p>
```

## 8. Forms

### Exercise 8.1

```
<form>
```

```
<div class="mb-3">
```

```
<input type="text"
class="form-control"
placeholder="Name">
```

```
</div>
```

```
<div class="mb-3">
```

```
<input type="email"
class="form-control"
placeholder="Email">
```

```
</div>
```

```
<div class="form-check">

<input type="checkbox"
class="form-check-input">

<label>
Subscribe
</label>

</div>

<div class="input-group mt-3">

<span class="input-group-text">
@
</span>

<input type="text"
class="form-control">

</div>

</form>
```

## Exercise 8.2

```
<form class="w-50">

<div class="form-floating mb-3">

<input type="email"
class="form-control"
id="email">

<label>Email</label>

</div>

<div class="form-floating">

<input type="password"
class="form-control"
id="password">

<label>Password</label>

</div>

</form>
```

## 9. Buttons

### Exercise 9.1

```
<button class="btn btn-primary">  
Primary  
</button>
```

```
<button class="btn btn-secondary">  
Secondary  
</button>
```

```
<button class="btn btn-success">  
Success  
</button>
```

```
<button class="btn btn-danger">  
Danger  
</button>
```

```
<button class="btn btn-outline-primary">  
Outline  
</button>
```

### Exercise 9.2

```
<div class="btn-group">
```

```
<button class="btn btn-primary">  
Left  
</button>
```

```
<button class="btn btn-primary">  
Middle  
</button>
```

```
<button class="btn btn-primary">  
Right  
</button>
```

```
</div>
```

```
<br><br>
```

```
<input type="checkbox"  
class="btn-check"  
id="btn1">
```

```
<label class="btn btn-outline-success"  
for="btn1">
```

Toggle

</label>

## 10. Navbars and Navigation

### Exercise 10.1

```
<nav class="navbar navbar-expand-lg navbar-dark bg-dark">
```

```
<div class="container-fluid">
```

```
<a class="navbar-brand">
```

LOGO

```
</a>
```

```
<button class="navbar-toggler"
```

```
data-bs-toggle="collapse"
```

```
data-bs-target="#menu">
```

```
<span class="navbar-toggler-icon"></span>
```

```
</button>
```

```
<div class="collapse navbar-collapse"
```

```
id="menu">
```

```
<ul class="navbar-nav me-auto">
```

```
<li class="nav-item">
```

```
<a class="nav-link">Home</a>
```

```
</li>
```

```
<li class="nav-item">
```

```
<a class="nav-link">Events</a>
```

```
</li>
```

```
</ul>
```

```
<form class="d-flex">
```

```
<input class="form-control"
```

```
placeholder="Search">
```

```
</form>
```

```
</div>
```

```
</div>
```



</nav>

## Exercise 10.2

<ul class="nav nav-tabs">

<li class="nav-item">

<a class="nav-link active">

Home

</a>

</li>

<li class="nav-item">

<a class="nav-link">

Events

</a>

</li>

</ul>

<br>

<ul class="nav nav-pills">

<li class="nav-item">

<a class="nav-link active">

Profile

</a>

</li>

<li class="nav-item">

<a class="nav-link">

Settings

</a>

</li>

</ul>

## 11. Cards and Media Objects

### Exercise 11.1: Profile Card

<!DOCTYPE html>

<html>

<head>

<link rel="stylesheet"

href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css">

```

</head>
<body>

<div class="container mt-5">

<div class="card" style="width:18rem;">



<div class="card-body">

<h5 class="card-title">
John Smith
</h5>

<p class="card-text">
Community Volunteer
</p>

<a href="#"
class="btn btn-primary">

View Profile

</a>

</div>

</div>

</div>

</body>
</html>

```

## Exercise 11.2: Media Object Layout

```

<!DOCTYPE html>
<html>
<head>

<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css">

</head>
<body>

<div class="container mt-4">

```

```
<div class="d-flex">



<div>

<h5>Community Event</h5>

<p>
Local residents are invited to participate
in various activities and workshops.
</p>

</div>

</div>

</div>

</body>
</html>
```

## 12. Spacing Utilities

### Exercise 12.1: Margin and Padding

```
<div class="container">

<div class="bg-primary text-white m-3 p-2">

Section One

</div>

<div class="bg-success text-white mt-4 py-5">

Section Two

</div>

</div>
```

### Exercise 12.2: Pricing Section

```
<div class="container py-5">

<div class="row">
```

```
<div class="col-md-4">
```

```
<div class="card p-4">
```

```
<h3>Basic</h3>
```

```
<h4>₹499</h4>
```

```
</div>
```

```
</div>
```

```
<div class="col-md-4">
```

```
<div class="card p-4">
```

```
<h3>Standard</h3>
```

```
<h4>₹999</h4>
```

```
</div>
```

```
</div>
```

```
<div class="col-md-4">
```

```
<div class="card p-4">
```

```
<h3>Premium</h3>
```

```
<h4>₹1499</h4>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
</div>
```

## 13. Colors and Backgrounds

### Exercise 13.1: Dashboard

```
<div class="container">
```

```
<div class="bg-primary text-white p-3 mb-3">
```

```
Primary Section
```

```
</div>
```

```
<div class="bg-warning text-dark p-3 mb-3">  
Warning Section  
</div>
```

```
<div class="bg-success text-white p-3 mb-3">  
Success Section  
</div>
```

```
<div class="bg-danger text-white p-3">  
Danger Section  
</div>
```

```
</div>
```

### **Exercise 13.2: Gradient Background**

```
<div class="bg-dark bg-gradient text-white p-5">
```

```
<h2>  
Bootstrap Gradient Background  
</h2>
```

```
<p>  
Community Event Portal  
</p>
```

```
</div>
```

## **14. Display and Visibility**

### **Exercise 14.1: Hide and Show Content**

```
<div class="d-none d-md-block">
```

Visible on Tablet and Desktop

```
</div>
```

```
<div class="d-none d-lg-flex">
```

Visible only on Large Screens

```
</div>
```

### **Exercise 14.2: Responsive Sidebar**

```
<div class="container-fluid">
```

```
<div class="row">
```

```
<div class="col-md-3 d-none d-md-block bg-light">
```

Sidebar Menu

```
</div>
```

```
<div class="col-md-9">
```

Main Content

```
</div>
```

```
</div>
```

```
</div>
```

## 15. Borders, Shadows and Rounded Corners

### Exercise 15.1: Border Utilities

```

```

### Exercise 15.2: Shadow and Rounded Pill

```
<div class="card shadow-lg p-4 rounded-pill">
```

```
<h4>
```

Bootstrap Card

```
</h4>
```

```
<p>
```

Card with Shadow and Rounded Pill

```
</p>
```

```
</div>
```

## 16. Positioning Utilities

### Exercise 16.1: Fixed Footer

```
<footer
```

```
class="position-fixed
```

```
bottom-0
w-100
bg-dark
text-white
text-center
p-2">
```

Copyright © 2025

```
</footer>
```

## Exercise 16.2: Badge Overlay on Image

```
<div class="position-relative d-inline-block">
```

```

```

```
<span class="badge bg-danger
position-absolute
top-0
start-100
translate-middle">
```

New

```
</span>
```

```
</div>
```

## 17. Icons with Bootstrap Icons

### Exercise 17.1: Social Media Icons

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.11.3/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<footer class="bg-dark text-white text-center p-4">
```

```
<a href="#" class="text-white me-3">
<i class="bi bi-facebook fs-2"></i>
</a>
```

```
<a href="#" class="text-white me-3">
<i class="bi bi-instagram fs-2"></i>
</a>
```

```
<a href="#" class="text-white me-3">
<i class="bi bi-twitter-x fs-2"></i>
</a>
```

```
<a href="#" class="text-white">
<i class="bi bi-youtube fs-2"></i>
</a>
```

```
</footer>
```

```
</body>
</html>
```

### Exercise 17.2: Icon-Only Buttons

```
<!DOCTYPE html>
<html>
<head>

<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css">

<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.11.3/font/bootstrap-icons.css">

</head>

<body>

<div class="container mt-4">

<button class="btn btn-primary">
<i class="bi bi-house-fill"></i>
</button>

<button class="btn btn-success">
<i class="bi bi-check-circle-fill"></i>
</button>

<button class="btn btn-danger">
<i class="bi bi-trash-fill"></i>
</button>

<button class="btn btn-warning">
<i class="bi bi-pencil-fill"></i>
```



</button>

</div>

</body>

</html>

## 18. Bootstrap 5 JavaScript Plugins

### Exercise 18.1: Modal Popup

<!DOCTYPE html>

<html>

<head>

<link rel="stylesheet"

href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css">

</head>

<body>

<div class="container mt-5">

<button class="btn btn-primary"

data-bs-toggle="modal"

data-bs-target="#myModal">

Open Modal

</button>

<div class="modal fade"

id="myModal">

<div class="modal-dialog">

<div class="modal-content">

<div class="modal-header">

<h5 class="modal-title">

Community Event

</h5>

<button class="btn-close"

data-bs-dismiss="modal">

</button>

</div>

```
<div class="modal-body">

Welcome to Bootstrap Modal.

</div>

<div class="modal-footer">

<button class="btn btn-secondary"
data-bs-dismiss="modal">

Close

</button>

</div>

</div>

</div>

</div>

</div>

</div>

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></
script>

</body>
</html>
```

### **Exercise 18.2: Accordion**

```
<!DOCTYPE html>
<html>
<head>

<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css">

</head>

<body>

<div class="container mt-5">

<div class="accordion"
id="accordionExample">
```

```
<div class="accordion-item">
```

```
<h2 class="accordion-header">
```

```
<button  
class="accordion-button"  
data-bs-toggle="collapse"  
data-bs-target="#collapseOne">
```

Music Event

```
</button>
```

```
</h2>
```

```
<div id="collapseOne"  
class="accordion-collapse collapse show">
```

```
<div class="accordion-body">
```

Music Event Details

```
</div>
```

```
</div>
```

```
</div>
```

```
<div class="accordion-item">
```

```
<h2 class="accordion-header">
```

```
<button  
class="accordion-button collapsed"  
data-bs-toggle="collapse"  
data-bs-target="#collapseTwo">
```

Sports Event

```
</button>
```

```
</h2>
```

```
<div id="collapseTwo"  
class="accordion-collapse collapse">
```

```
<div class="accordion-body">
```

Sports Event Details

</div>

</div>

</div>

</div>

</div>

```
<script  
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>
```

</body>

</html>

## 19. Customization with Sass

### Exercise 19.1: Bootstrap with Sass

#### Install Bootstrap

```
npm init -y  
npm install bootstrap  
npm install sass
```

#### custom.scss

```
@import "../node_modules/bootstrap/scss/bootstrap";
```

#### Compile

```
npx sass scss/custom.scss css/custom.css
```

### Exercise 19.2: Customize Primary Color and Border Radius

#### \_variables.scss

```
$primary: #ff6600;
```

```
$border-radius: 1rem;
```

#### custom.scss

```
@import "variables";
```

```
@import "../node_modules/bootstrap/scss/bootstrap";
```

## Recompile

```
npx sass scss/custom.scss css/custom.css
```

## Test Page

```
<!DOCTYPE html>
<html>
<head>

<link rel="stylesheet"
href="css/custom.css">

</head>

<body>

<div class="container mt-5">

<button class="btn btn-primary">
Custom Button
</button>

<div class="card p-3 mt-3">
Customized Bootstrap Card
</div>

</div>

</body>
</html>
```