



UNIVERSITY OF PETROLEUM & ENERGY STUDIES

Dehradun

ACO LAB

Name- Harsha Agarwal

Sap id- 500096741

Roll no- R2142211158

Batch- B-4

Course- Btech Devops

Submitted to- Dr Hitesh Kumar Sharma

Lab Exercise 9– Creating Replica set in Kubernetes

Step 1: Create a ReplicaSet Configuration File

Create a file named `replicaset.yaml` with the following configuration:

```
apiVersion: apps/v1
```

```
kind: ReplicaSet
```

```
metadata:
```

```
  name: my-nginx-rs
```

```
spec:
```

```
  replicas: 3
```

```
  selector:
```

```
    matchLabels:
```

```
      app: lbnginx
```

```
  template:
```

```
    metadata:
```

```
      labels:
```

```
        app: lbnginx
```

```
    spec:
```

```
      containers:
```

```
        - name: nginx
```

```
          image: nginx
```

```
Welcome replicaset.yaml X
C: > Users > ABC > OneDrive > Desktop > ACO > ! replicaset.yaml
1  apiVersion: apps/v1
2  kind: ReplicaSet
3  metadata:
4    name: my-nginx-rs
5  spec:
6    replicas: 3
7    selector:
8      matchLabels:
9        app: lbnginx
10   template:
11     metadata:
12       labels:
13         app: lbnginx
14     spec:
15       containers:
16       - name: nginx
17         image: nginx
18
```

```
! service.yaml ● ! pod.yaml ● ! replicaset.yaml
! pod.yaml
1  apiVersion: v1
2  kind: Pod
3  metadata:
4    name: my-nginx-pod
5    labels:
6      app: lbnginx
7  spec:
8    containers:
9    - name: nginx-container
10     image: nginx
```

```
! service.yaml ● ! pod.yaml ● ! replicaset.yaml
! service.yaml
1  apiVersion: v1
2  kind: Service
3  metadata:
4    name: my-nginx-service-1
5  spec:
6    selector:
7      app: lbnginx
8    ports:
9      - protocol: TCP
10      port: 80
11      nodePort: 30003
12    type: NodePort
13
```

Step 2: Apply the ReplicaSet Configuration Apply

`apply -f replicaset.yaml`

```
C:\Users\ABC\OneDrive\Desktop\ACO\Kube>kubectl apply -f replicaset.yaml
replicaset.apps/my-nginx-rs created
C:\Users\ABC\OneDrive\Desktop\ACO\Kube>
```

Step 3: View the ReplicaSet and Pods

kubectl get replicaset

kubectl get pods

```
C:\Users\ABC\OneDrive\Desktop\ACO\Kube>kubectl get replicaset
NAME          DESIRED  CURRENT  READY  AGE
my-nginx-rs   3        3        0      26s

C:\Users\ABC\OneDrive\Desktop\ACO\Kube>kubectl get pods
NAME          READY  STATUS             RESTARTS  AGE
my-nginx-rs-7zw9t  0/1   ContainerCreating   0          34s
my-nginx-rs-l26mb  0/1   ContainerCreating   0          34s
my-nginx-rs-zzrnw  0/1   ContainerCreating   0          34s

C:\Users\ABC\OneDrive\Desktop\ACO\Kube>
```

Step 4: Scale the ReplicaSet

kubectl scale replicaset my-nginx-rs --replicas=5

```
C:\Users\ABC\OneDrive\Desktop\ACO\Kube>kubectl scale replicaset my-nginx-rs --replicas=5
replicaset.apps/my-nginx-rs scaled

C:\Users\ABC\OneDrive\Desktop\ACO\Kube>kubectl get pods
NAME          READY  STATUS             RESTARTS  AGE
my-nginx-rs-7zw9t  0/1   ContainerCreating   0          99s
my-nginx-rs-ds6lk  0/1   ContainerCreating   0          19s
my-nginx-rs-l26mb  0/1   ContainerCreating   0          99s
my-nginx-rs-s989d  0/1   ContainerCreating   0          19s
my-nginx-rs-zzrnw  0/1   ContainerCreating   0          99s
```

Step 5: Delete the ReplicaSet

Delete the ReplicaSet:

kubectl delete replicaset my-replicaset

```
C:\Users\ABC\OneDrive\Desktop\ACO\Kube>kubectl delete replicaset my-nginx-rs
replicaset.apps "my-nginx-rs" deleted

C:\Users\ABC\OneDrive\Desktop\ACO\Kube>
```

Conclusion

This exercise demonstrated how to create, manage, and update a ReplicaSet in Kubernetes. You learned how to scale the ReplicaSet, update the image, and delete the ReplicaSet from the cluster. Experiment further with different configurations and scaling options to deepen your understanding of managing ReplicaSets in Kubernetes.