Internet and web programming

- Harshil Gupta
- 17BCE1112

```
1.
 <html>
<head>
<title>Webpage</title>
</head>
<body>
<input type="text" id="text" value="Monday">
<button class="button" onclick="F()">Next day</button><br><br>
<input type="text" id="text1" value="Januray">
<button onclick="F2()">Next month</button>
<script>
function F() {
var day= ['Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday', 'Sunday'];
var x =document.getElementById("text").value;
var x1= (day.indexOf(x)+1)\%7;
document.getElementById("text").value = day[x1];
}
function F2() {
var months=['Januray', 'February', 'March', 'April', 'May', 'June', 'July', 'August', 'September', 'October'
,'November','December'];
var x3 = document.getElementById("text1").value;
var x2 = (months.indexOf(x3)+1)%12;
```

```
document.getElementById("text1").value = months[x2];
}
</script>
</body>
</html>
```



```
document.getElementById("text").style.fontSize="larger";
}
</script>
</body>
</html>
```



```
3.
    <html>
    <head>
    <title>Create a table</title>
    <style type="text/css">
```

```
body {margin: 30px;}
</style>
</head>
<script>
function createTable()
 var rn=document.getElementById("text").value;
 var cn=document.getElementById("text1").value;
for(var r=0;r<parseInt(rn,10);r++)</pre>
 var x=document.getElementById('myTable').insertRow(r);
 for(var c=0;c<parseInt(cn,10);c++)</pre>
  var y= x.insertCell(c);
  y.innerHTML="Row-"+r+" Column-"+c;
 }
 }
}
</script>
<body>
 Number of rows
 <input type="text" id="text"><br><br>
 Number of columns
 <input type="text" id="text1"><br>
<br>
<button onclick="createTable()">Create table</button>
</body>
</html>
```

