

W4 Final Submission

FlyRank Internship - Backend Track - Week 2 Assignment A4

Auth - Login & protect

Generated: 2026-09-06

Project

FastAPI backend with Supabase Auth, bearer-token protected routes, Swagger authorization, and the existing containerized PostgreSQL task API.

GitHub

```
origin https://github.com/Harshini-priya989/FlyRank_W1_A3_Containerized_Postgres (fetch)
origin https://github.com/Harshini-priya989/FlyRank_W1_A3_Containerized_Postgres (push)
```

Evidence Note

- Swagger screenshot is not present yet. Add docs/swagger-auth.png after testing with your Supabase token.

Implemented Requirements

- POST /auth/signup validates email/password and calls Supabase sign_up.
- POST /auth/login validates credentials and returns Supabase access and refresh tokens.
- POST /auth/logout is protected and returns 204.
- GET /public/info is open to everyone.
- GET /protected/profile verifies Authorization: Bearer <token> with Supabase get_user.
- GET /protected/dashboard reuses the same FastAPI dependency.
- Missing, malformed, invalid, and expired tokens return 401 JSON errors.
- FastAPI HTTPBearer is applied to protected routes so Swagger UI shows bearer auth padlocks.
- .env is ignored; .env.example documents Supabase placeholders without real secrets.

Recent Commits

805ede5 Add final database evidence
e1bcd0b Add final submission document
e849143 Stage 5: one-command stack + docs
7bc519d Stage 4: docker-compose the whole stack
7586ce5 Stage 3: full CRUD on Postgres
b462ded Stage 2: read from Postgres
c2616b9 Stage 1: connect via env and create table
6a8ac0e Stage 0: Postgres in Docker + gitignore
556a2dd Stage 5: database documentation
2fea4a2 Stage 4: explored SQLite

Run And Test

Setup

```
Copy-Item .env.example .env
# Fill SUPABASE_URL and SUPABASE_KEY from Supabase Project Settings -> API
docker compose up --build
```

curl Flow

```
curl -i -X POST http://localhost:8000/auth/signup -H "Content-Type: application/json" -d
{"email\":\"test@example.com\",\"password\":\"password123\"}
curl -i -X POST http://localhost:8000/auth/login -H "Content-Type: application/json" -d
{"email\":\"test@example.com\",\"password\":\"password123\"}
curl -i http://localhost:8000/protected/profile -H "Authorization: Bearer
PASTE_ACCESS_TOKEN_HERE"
curl -i http://localhost:8000/protected/profile
```

Swagger

Open <http://localhost:8000/docs>, click Authorize, paste the access token, and run GET /protected/profile.

Key Files

.env.example

```
POSTGRES_USER=postgres
POSTGRES_PASSWORD=dev
POSTGRES_DB=tasks
DATABASE_URL=postgresql://postgres:dev@localhost:5432/tasks
SUPABASE_URL=your_supabase_project_url
SUPABASE_KEY=your_supabase_anon_key
```

Auth routes and dependency

Implemented in main.py and auth_service.py.

W4 Checklist

W4 Auth submission checklist

- [x] Supabase Auth dependency added
- [x] `SUPABASE\_URL` and `SUPABASE\_KEY` documented in `.env.example`
- [x] `.env` remains git-ignored
- [x] `POST /auth/signup` route added
- [x] `POST /auth/login` route added
- [x] `POST /auth/logout` protected route added
- [x] `GET /public/info` open route added
- [x] `GET /protected/profile` protected route added
- [x] `GET /protected/dashboard` uses the same auth dependency
- [x] Protected routes use `Authorization: Bearer <token>`
- [x] Token verification uses `supabase.auth.get\_user(token)`
- [x] Swagger bearer auth padlock is configured with FastAPI `HTTPBearer`
- [] Real Supabase project values added locally to `.env`
- [] Supabase email confirmation disabled for practice testing
- [] Signup/login/profile flow tested with real Supabase account
- [] Tampered token returns `401`
- [] Swagger screenshot saved as `docs/swagger-auth.png`
- [] Final changes pushed to GitHub