

EXPERIMENT - 1

Name: Harshit Kumawat

Section:

24AIT_KRG1_B

Subject: ADBMS

UID: 24BAI70025

Subject Code: 24CSP-310

Date: 12/07/2026

(A)

Write an SQL solution to calculate the total number of bank accounts belonging to each salary category. The classification categories are:

1. **"Low Salary"**: All monthly salaries strictly less than \$20,000.
2. **"Average Salary"**: All monthly salaries in the inclusive range [\$20,000, \$50,000].
3. **"High Salary"**: All monthly salaries strictly greater than \$50,000. The final result table must report all three categories, even if a category contains zero accounts.

Output Table	
category	accounts_count
Low Salary	1
Average Salary	1
High Salary	3

```
SELECT 'LOW SALARY' AS CATEGORY,
COUNT (ACCOUNT_ID) AS ACCOUNTS_COUNT
FROM ACCOUNTS
WHERE INCOME < 20000
UNION ALL
SELECT 'AVERAGE SALARY' AS CATEGORY,
COUNT (ACCOUNT_ID) AS ACCOUNTS_COUNT
FROM ACCOUNTS
WHERE INCOME >= 20000 AND INCOME<=50000
UNION ALL
SELECT 'HIGH SALARY' AS CATEGORY,
```

```
COUNT (ACCOUNT_ID) AS ACCOUNTS_COUNT
FROM ACCOUNTS
WHERE INCOME > 50000;
```

(B)

Design an Employee Management System database architecture by implementing the following operations sequentially:

1. Create and populate structural tracking tables for Departments, Employees, and Salaries.
2. Query the system using multi-table Joins to pull clear department breakdowns of employees, department and salaries, apply a 10% salary enhancement across all members of the HR department, and delete any individual salary record dropping strictly below \$30,000.
3. List all remaining active employees whose personal salary exceeds the overall company-wide average salary.

1:

```
CREATE TABLE Departments (
    dept_id INT PRIMARY KEY,
    dept_name VARCHAR(50) NOT NULL
);
CREATE TABLE Employees (
    emp_id INT PRIMARY KEY,
    name VARCHAR(50) NOT NULL,
    dept_id INT REFERENCES Departments(dept_id)
);
CREATE TABLE Salaries (
    emp_id INT PRIMARY KEY REFERENCES Employees(emp_id) ON DELETE CASCADE,
    salary INT NOT NULL
);
INSERT INTO Departments (dept_id, dept_name) VALUES
(10, 'HR'), (20, 'IT'), (30, 'Sales');

INSERT INTO Employees (emp_id, name, dept_id) VALUES
(1, 'Alice', 10), (2, 'Bob', 10), (3, 'Charlie', 20), (4, 'David', 20),
(5, 'Emma', 30);

INSERT INTO Salaries (emp_id, salary) VALUES
(1, 50000), (2, 25000), (3, 80000), (4, 40000), (5, 45000);
```

2.I:

```
SELECT E.*,D.*,S.*
FROM EMPLOYEES E
JOIN DEPARTMENTS D
ON E.DEPT_ID = D.DEPT_ID
JOIN SALARIES S
ON E.EMP_ID = S.EMP_ID;
```

2.II:

```
UPDATE SALARIES
SET SALARY = SALARY*0.10 + SALARY
WHERE EMP_ID
IN
(
    SELECT E.EMP_ID
    FROM EMPLOYEES E
    JOIN DEPARTMENTS D
    ON
    E.DEPT_ID = D.DEPT_ID
    WHERE D.DEPT_NAME = 'HR'
);
```

2.III:

```
DELETE FROM SALARIES
WHERE SALARY<30000
RETURNING *;
```

3:

```
SELECT E.EMP_ID,E.NAME,D.DEPT_NAME,S.SALARY
FROM EMPLOYEES E
JOIN DEPARTMENTS D
ON E.DEPT_ID = D.DEPT_ID
JOIN SALARIES S
ON E.EMP_ID = S.EMP_ID
WHERE S.SALARY >
(
    SELECT AVG(SALARY)
    FROM SALARIES
```

```
) ;
```

(C)

A pizza restaurant stores all the available pizza toppings and their ingredient costs in a table called pizza_toppings.

Every customer must choose **exactly 3 different toppings** to prepare a pizza.

Write a PostgreSQL query to generate **every possible 3-topping pizza combination** along with its **total ingredient cost**.

Requirements

Every pizza must contain **exactly 3 different toppings**.

The same topping **cannot appear more than once** in a pizza.

Different arrangements of the same toppings should be considered the **same pizza**.

Example:

Chicken, Pepperoni, Sausage

Pepperoni, Chicken, Sausage

Sausage, Chicken, Pepperoni

These are all the same pizza, so only **one** should appear.

Display the topping names separated by commas.

Display the total ingredient cost of each pizza.

Sort the output:

First by **highest total cost**

If two pizzas have the same cost, sort them alphabetically.

```
SELECT
CONCAT(T1.TOPPING_NAME, ', ', T2.TOPPING_NAME, ', ', T3.TOPPING_NAME) AS
PIZZA,
(T1.INGREDIENT_COST+T2.INGREDIENT_COST+T3.INGREDIENT_COST) AS TOTAL_COST
FROM PIZZA_TOPPINGS AS T1
JOIN
PIZZA_TOPPINGS AS T2
ON
T1.TOPPING_NAME < T2.TOPPING_NAME
JOIN
PIZZA_TOPPINGS AS T3
ON
T2.TOPPING_NAME < T3.TOPPING_NAME
ORDER BY
TOTAL_COST DESC, PIZZA ASC;
```

(D)

Amazon wants to identify **returning customers** who made another purchase shortly after their first purchase. Write a PostgreSQL query to find all users who made **another purchase within 1 to 7 days** of an earlier purchase.

Requirements

1. Compare purchases **made by the same user only**.
2. Ignore comparisons where the same transaction is matched with itself.
3. The second purchase must occur **after** the first purchase.
4. Same-day purchases must **not** be considered.
5. The second purchase must occur within **7 days** of the first purchase.
6. Display only the **unique User IDs** that satisfy the above conditions.
7. Sort the output in ascending order of user_id.

```
WITH DAILY AS (  
SELECT DISTINCT USER_ID, CREATED_AT:: DATE AS PURCHASE_DATE  
FROM  
AMAZON_TRANSACTIONS),  
FIRST_PURCHASE AS  
(  
SELECT USER_ID, MIN(PURCHASE_DATE) AS FIRST_PURCHASE  
FROM DAILY  
GROUP BY USER_ID  
)  
SELECT D.USER_ID  
FROM DAILY D  
JOIN FIRST_PURCHASE FP  
ON  
D.USER_ID = FP.USER_ID  
WHERE D.PURCHASE_DATE > FP.FIRST_PURCHASE  
GROUP BY  
D.USER_ID, FP.FIRST_PURCHASE  
HAVING (MIN(D.PURCHASE_DATE) - FP.FIRST_PURCHASE) BETWEEN 1 AND 7  
ORDER BY  
D.USER_ID;
```