

Q1.

```
SELECT D.DEPT_NAME, E.EMP_NAME, E.SALARY
FROM EMPLOYEE E
JOIN DEPARTMENT D
ON E.DEPT_ID = D.DEPT_ID
WHERE E.SALARY > (
    SELECT AVG(E2.SALARY)
    FROM EMPLOYEE E2
    WHERE E2.DEPT_ID = E.DEPT_ID
)
AND E.DEPT_ID IN (
    SELECT DEPT_ID
    FROM EMPLOYEE
    GROUP BY DEPT_ID
    HAVING COUNT(*) >=3
);
```

Output:

CREATE TABLE

CREATE TABLE

INSERT 0 3

INSERT 0 8

dept_name	emp_name	salary
IT	Aman	90000.00
Sales	Priya	80000.00

(2 rows)

Q2.

```
CREATE OR REPLACE FUNCTION CUST_AUDIT_FUN()
RETURNS TRIGGER
LANGUAGE PLPGSQL
AS $$
BEGIN
    IF TG_OP = 'INSERT' THEN
        INSERT INTO CUSTOMER_AUDIT
        (CUSTOMER_ID,CUSTOMER_NAME,ACTION,ACTION_TIME)
        VALUES
        (NEW.CUSTOMER_ID,NEW.CUSTOMER_NAME,'ADDED',CURRENT_TIMESTAMP);
        RETURN NEW;
    ELSEIF TG_OP = 'DELETE' THEN
        INSERT INTO CUSTOMER_AUDIT
        (CUSTOMER_ID,CUSTOMER_NAME,ACTION,ACTION_TIME)
        VALUES
        (OLD.CUSTOMER_ID,OLD.CUSTOMER_NAME,'REMOVED',CURRENT_TIMESTAMP);
        RETURN OLD;
    END IF;
END; $$;

CREATE TRIGGER CUST_AUDIT_TRIGGER
AFTER INSERT OR DELETE
ON BANK_CUSTOMER
FOR EACH ROW
EXECUTE FUNCTION CUST_AUDIT_FUN();

INSERT INTO BANK_CUSTOMER
VALUES (3, 'Aman', 60000);
DELETE FROM BANK_CUSTOMER
WHERE CUSTOMER_ID = 1;
SELECT *
FROM CUSTOMER_AUDIT;
```

Output:

CREATE TABLE

CREATE TABLE

INSERT 0 2

CREATE FUNCTION

CREATE TRIGGER

INSERT 0 1

DELETE 1

audit_id	customer_id	customer_name	action	action_time
1	3	Aman	ADDED	2026-09-28 09:58:20.795347
2	1	Rahul	REMOVED	2026-09-28 09:58:20.796248

(2 rows)

CREATE FUNCTION