

SESSION-COOKIES

What is a PHP Session?

When you work with an application, you open it, do some changes, and then you close it. This is much like a Session. The computer knows who you are. It knows when you start the application and when you end. But on the internet there is one problem: the web server does not know who you are or what you do, because the HTTP address doesn't maintain state.

Session variables solve this problem by storing user information to be used across multiple pages (e.g. username, favorite color, etc). By default, session variables last until the user closes the browser.

Start a PHP Session

A session is started with the `session_start()` function.

Session variables are set with the PHP global variable: `$_SESSION`.

Now, let's create a new page called "demo_session1.php". In this page, we start a new PHP session and set some session variables:

Example

```
<?php
// Start the session
session_start();
?>
<!DOCTYPE html>
<html>
<body>

<?php
// Set session variables
```

```
$_SESSION["favcolor"] = "green";
$_SESSION["favanimal"] = "cat";
echo "Session variables are set.";
?>
```

```
</body>
</html>
```

Get PHP Session Variable Values

Next, we create another page called "demo_session2.php". From this page, we will access the session information we set on the first page ("demo_session1.php").

Notice that session variables are not passed individually to each new page, instead they are retrieved from the session we open at the beginning of each page (`session_start()`).

Also notice that all session variable values are stored in the global `$_SESSION` variable:

Example

```
<?php
session_start();
?>
<!DOCTYPE html>
<html>
<body>

<?php
// Echo session variables that were set on previous page
echo "Favorite color is " . $_SESSION["favcolor"] . "<br>";
echo "Favorite animal is " . $_SESSION["favanimal"] . ".";
?>
```

```
</body>
</html>
```

Modify a PHP Session Variable

To change a session variable, just overwrite it:

Example

```
<?php
session_start();
?>
<!DOCTYPE html>
<html>
<body>

<?php
// to change a session variable, just overwrite it
$_SESSION["favcolor"] = "yellow";
print_r($_SESSION);
?>

</body>
</html>
```

Destroy a PHP Session

To remove all global session variables and destroy the session, use `session_unset()` and `session_destroy()`:

Example

```
<?php
session_start();
?>
<!DOCTYPE html>
<html>
```

```
<body>

<?php
// remove all session variables
session_unset();

// destroy the session
session_destroy();
?>

</body>
</html>
```

What is a Cookie?

A cookie is often used to identify a user. A cookie is a small file that the server embeds on the user's computer. Each time the same computer requests a page with a browser, it will send the cookie too. With PHP, you can both create and retrieve cookie values.

Create Cookies With PHP

A cookie is created with the `setcookie()` function.

Syntax

```
setcookie(name, value, expire, path, domain, secure, httponly);
```

Only the *name* parameter is required. All other parameters are optional.

PHP Create/Retrieve a Cookie

The following example creates a cookie named "user" with the value "John Doe". The cookie will expire after 30 days (86400 * 30). The "/"

means that the cookie is available in entire website (otherwise, select the directory you prefer).

We then retrieve the value of the cookie "user" (using the global variable `$_COOKIE`). We also use the `isset()` function to find out if the cookie is set:

Example

```
<?php
$cookie_name = "user";
$cookie_value = "John Doe";
setcookie($cookie_name, $cookie_value, time() +
(86400 * 30), "/"); // 86400 = 1 day
?>

<html>
<body>

<?php
if(!isset($_COOKIE[$cookie_name])) {
    echo "Cookie named '" . $cookie_name . "' is not set!";
} else {
    echo "Cookie '" . $cookie_name . "' is set!<br>";
    echo "Value is: " . $_COOKIE[$cookie_name];
}
?>

</body>
</html>
```

Note: The `setcookie()` function must appear BEFORE the `<html>` tag.

Note: The value of the cookie is automatically URLencoded when sending the cookie, and automatically decoded when received (to prevent URLencoding, use `setrawcookie()` instead).

Modify a Cookie Value

To modify a cookie, just set (again) the cookie using the `setcookie()` function:

Example

```
<?php
$cookie_name = "user";
$cookie_value = "Alex Porter";
setcookie($cookie_name, $cookie_value, time() + (86400 * 30), "/");
?>

<html>
<body>

<?php
if(!isset($_COOKIE[$cookie_name])) {
    echo "Cookie named '" . $cookie_name . "' is not set!";
} else {
    echo "Cookie '" . $cookie_name . "' is set!<br>";
    echo "Value is: " . $_COOKIE[$cookie_name];
}
?>

</body>
</html>
```

Delete a Cookie

To delete a cookie, use the `setcookie()` function with an expiration date in the past:

Example

```
<?php
// set the expiration date to one hour ago
setcookie("user", "", time() - 3600);
?>

<html>
<body>
```

```
<?php
echo "Cookie 'user' is deleted.";
?>
```

```
</body>
</html>
```

Check if Cookies are Enabled

The following example creates a small script that checks whether cookies are enabled. First, try to create a test cookie with the `setcookie()` function, then count the `$_COOKIE` array variable:

Example

```
<?php
setcookie("test_cookie", "test", time() + 3600, '/');
?>
```

```
<html>
<body>
```

```
<?php
if(count($_COOKIE) > 0) {
    echo "Cookies are enabled.";
} else {
    echo "Cookies are disabled.";
}
?>
```

```
</body>
</html>
```