

# Topic 16: Propagators<sup>1</sup>

(Version of 6th December 2018)

---

Pierre Flener

Optimisation Group

Department of Information Technology  
Uppsala University  
Sweden

Course 1DL441:  
Combinatorial Optimisation and Constraint Programming,  
whose part 1 is Course 1DL451:  
Modelling for Combinatorial Optimisation

---

<sup>1</sup>Based partly on material by N. Beldiceanu and Ch. Schulte



# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC

Propagator

Efficient DC

Propagator

Efficient BC

Propagator

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator



# Outline

---

## Reification

### Global Constraints

linear

channel

element

extensional

distinct

Naïve DC

Propagator

Efficient DC

Propagator

Efficient BC

Propagator

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator



# Reification

## Implementation of $b \Leftrightarrow \gamma(\dots)$ :

When there are search decisions or other constraints on the reifying 0/1-variable  $b$ :

- If the variable  $b$  becomes 1,  
then the constraint  $\gamma(\dots)$  is propagated.
- If the variable  $b$  becomes 0,  
then the constraint  $\neg\gamma(\dots)$  is propagated.
- If the constraint  $\gamma(\dots)$  is subsumed,  
then the variable  $b$  is fixed to 1.
- If the constraint  $\neg\gamma(\dots)$  is subsumed,  
then the variable  $b$  is fixed to 0.

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



## Constraint combination with reification:

With reification, constraints can be arbitrarily combined with logical connectives: negation ( $\neg$ ), disjunction ( $\vee$ ), conjunction ( $\&$ ), implication ( $\Rightarrow$ ), and equivalence ( $\Leftrightarrow$ ). However, propagation may be very poor!

### Example

The composite constraint  $(\gamma_1 \ \& \ \gamma_2) \vee \gamma_3$  is modelled as

$$(b_1 \Leftrightarrow \gamma_1) \ \& \ (b_2 \Leftrightarrow \gamma_2) \ \& \ (b_3 \Leftrightarrow \gamma_3) \\ \& \ (b_1 \cdot b_2 = b) \ \& \ (b + b_3 \geq 1)$$

Hence even the constraints  $\gamma_1$  and  $\gamma_2$  must be reified.

If  $\gamma_1$  is  $x = y + 1$  and  $\gamma_2$  is  $y = x + 1$ , then  $\gamma_1 \ \& \ \gamma_2$  is unsat; however,  $b$  is then **not** assigned value 0 by propagation, as each propagator works individually and there is **no** communication through the shared variables  $x$  and  $y$ ; hence  $b_3 = 1$  is **not** propagated and  $\gamma_3$  is **not** forced to hold.



Remember the advice in Topic 2: Basic Modelling that the disjunctive combination of constraints (with  $\setminus$ ,  $<-$ ,  $->$ , or  $<->$ ) often makes the solving slow?

## Reification

### Global Constraints

linear

channel

element

extensional

distinct

Naïve DC

Propagator

Efficient DC

Propagator

Efficient BC

Propagator

## Example

The MiniZinc disjunctive constraint

```
constraint x = 0 \ / x = 9;
```

is flattened for Gecode as follows, with reification:

$$(b_0 \Leftrightarrow x = 0) \ \& \ (b_9 \Leftrightarrow x = 9) \ \& \ (b_0 + b_9 \geq 1)$$

But it is logically equivalent to the variable declaration

```
var {0,9} : x;
```

where no reification is involved, and even no propagation.



Remember the strong warning in Topic 2: Basic Modelling about a conditional `if  $\theta$  then  $\phi_1$  else  $\phi_2$  endif` or a comprehension, say `[i | i in  $\rho$  where  $\theta$ ]`, in MiniZinc having a test  $\theta$  that depends on variables?

## Example

Consider `var 1..9: x` and `var 1..9: y` for

```
forall(i in 1..9 where i > x) (i > y)
```

Recall that this is syntactic sugar for

```
forall([i > y | i in 1..9 where i > x])
```

This is flattened for Gecode into the equivalent of

```
forall(i in 1..9) (i > x -> i > y)
```

that is with a logical implication ( $\rightarrow$ ), hence with a hidden logical disjunction ( $\setminus /$ ): for each  $i$ , **both** sub-constraints are **reified** as both have variables.



# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC Propagator  
Efficient DC Propagator  
Efficient BC Propagator

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator





## Definition

- A **primitive constraint** is **not** decomposable.
- A **global constraint** **is** definable by a logical formula (usually a conjunction) involving primitive constraints, but not always in a trivial way.

For domain consistency, all solutions to a constraint need to be considered: a naïve propagator, first computing all the solutions and then projecting them onto the domains of the variables, often takes too much time and space:

## Example (already seen in Topic 13: Consistency)

The store  $\{x \mapsto \{2, \dots, 7\}, y \mapsto \{0, 1, 2\}, z \mapsto \{-1, \dots, 2\}\}$  has the solutions  $\langle 3, 1, 0 \rangle$ ,  $\langle 5, 0, 1 \rangle$ , and  $\langle 6, 2, 0 \rangle$  to the linear equality constraint  $x = 3 \cdot y + 5 \cdot z$ . Hence the store  $\{x \mapsto \{3, 5, 6\}, y \mapsto \{0, 1, 2\}, z \mapsto \{0, 1\}\}$  is domain-consistent.



# Globality from a Semantic Point of View

Some constraints **cannot** be defined by a conjunction of primitive constraints without introducing more variables:

**Example** (`count` ( $[x_1, \dots, x_n], v, \geq, \ell$ ))

At least  $\ell$  variables of  $[x_1, \dots, x_n]$  take the constant value  $v$ :

$$(\forall i \in 1..n : b_i \Leftrightarrow x_i = v) \ \& \ \sum_{i=1}^n b_i \geq \ell$$

Some constraints **can** be defined by a conjunction of primitive constraints without introducing more variables:

**Example** (`distinct` ( $[x_1, \dots, x_n]$ ))

$$\forall i, j \in 1..n \text{ where } i < j : x_i \neq x_j$$



# Globality from a Propagation Point of View

Some constraints **can** be defined by a conjunction of primitive constraints, **but** it leads to **weak propagation**:

## Example

Consider the store  $\{x_1, x_2, x_3 \mapsto \{4, 5\}\}$ :

- Upon `distinct`( $[x_1, x_2, x_3]$ ):  
Propagation fails under domain or bounds consistency.
- Upon  $x_1 \neq x_2$  &  $x_1 \neq x_3$  &  $x_2 \neq x_3$ :  
Propagation succeeds, and it is only search that fails.



# Globality from a Propagation Point of View

Some constraints **can** be defined by a conjunction of primitive constraints, with **strong propagation**, **but** it leads to **propagation with poor time or memory performance**:

## Example

- Upon  $\text{inequalities}(\{x_1 < x_2, x_2 < x_3, x_3 < x_4, x_4 < x_1\})$ :  
Propagation fails.  
(This predicate does not exist in Gecode.)
- Upon  $x_1 < x_2 \ \& \ x_2 < x_3 \ \& \ x_3 < x_4 \ \& \ x_4 < x_1$ :  
Propagation fails, but the runtime complexity depends on the sizes of the domains, rather than on the number of variables.



# Outline

---

Reification

Global  
Constraints

**linear**

channel

element

extensional

distinct

Naïve DC Propagator  
Efficient DC Propagator  
Efficient BC Propagator

1. Reification

2. Global Constraints

**3. linear**

4. channel

5. element

6. extensional

7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator



# The linear Predicate

## Definition

A  $\text{linear}([a_1, \dots, a_n], [x_1, \dots, x_n], R, d)$  constraint, with

- $[a_1, \dots, a_n]$  a sequence of non-zero integer constants,
- $[x_1, \dots, x_n]$  a sequence of integer variables,
- $R$  in  $\{<, \leq, =, \neq, \geq, >\}$ , and
- $d$  an integer constant,

holds iff the linear relation  $\left( \sum_{i=1}^n a_i \cdot x_i \right) R d$  holds.

We now show how to enforce bounds consistency cheaply on linear **equality**. For simplicity of notation, we pick  $n = 2$ , giving  $a_1 \cdot x_1 + a_2 \cdot x_2 = d$ , and rename into  $a \cdot x + b \cdot y = d$ .



## BC propagator for a binary linear equality:

Rewrite for  $x$  (the handling of  $y$  is analogous and omitted):

$$a \cdot x + b \cdot y = d \Leftrightarrow x = (d - b \cdot y) / a$$

Upper bound on  $x$ , starting from store  $s$ :

$$x \leq \left\lfloor \underbrace{\max \{(d - b \cdot n) / a \mid n \in s(y)\}}_M \right\rfloor$$

and (analogously, hence further details are omitted):

$$x \geq \lceil \min \{(d - b \cdot n) / a \mid n \in s(y)\} \rceil$$

Computing  $M$ :

$$M = \begin{cases} \max \{(d - b \cdot n) \mid n \in s(y)\} / a & \text{if } a > 0 \\ \min \{(d - b \cdot n) \mid n \in s(y)\} / a & \text{if } a < 0 \end{cases}$$



## BC propagator for a binary linear equality (end):

For  $a > 0$  (the case  $a < 0$  is analogous and omitted):

$$\begin{aligned} M &= \max \{ (d - b \cdot n) \mid n \in s(y) \} / a \\ &= (d - \min \{ b \cdot n \mid n \in s(y) \}) / a \\ &= \begin{cases} (d - b \cdot \min(s(y))) / a & \text{if } b > 0 \\ (d - b \cdot \max(s(y))) / a & \text{if } b < 0 \end{cases} \end{aligned}$$

This value can be computed and rounded in constant time, since the constants  $\min(s(y))$  and  $\max(s(y))$  can be queried in constant time and since  $a, b, d$  are constants.



**BC propagator for  $n$ -ary linear equality, with  $n \geq 1$ :**

Repeat until fixpoint, so as to achieve idempotency:

propagate for each variable  $x_i$ .

A speed-up can be obtained by computing two general expressions once and then adjusting them for each  $x_i$ :

see § 6.4 of Krzysztof R. Apt, [Principles of Constraint Programming](#), Cambridge University Press, 2003.

**Example (Justification for aiming at idempotency)**

Propagate  $2 \cdot x = 3 \cdot y$  for  $\{x \mapsto \{0, \dots, 8\}, y \mapsto \{0, \dots, 9\}\}$ :

Propagating for  $x$  gives:  $\{x \mapsto \{0, \dots, 8\}, y \mapsto \{0, \dots, 9\}\}$

Propagating for  $y$  gives:  $\{x \mapsto \{0, \dots, 8\}, y \mapsto \{0, \dots, 5\}\}$

Propagating for  $x$  gives:  $\{x \mapsto \{0, \dots, 7\}, y \mapsto \{0, \dots, 5\}\}$

Propagating for  $y$  gives:  $\{x \mapsto \{0, \dots, 7\}, y \mapsto \{0, \dots, 4\}\}$

Propagating for  $x$  gives:  $\{x \mapsto \{0, \dots, 6\}, y \mapsto \{0, \dots, 4\}\}$

Propagating for  $y$  gives:  $\{x \mapsto \{0, \dots, 6\}, y \mapsto \{0, \dots, 4\}\}$



## Consistency on $n$ -ary linear constraints:

- Linear equality ( $=$ ): The seen propagator enforces  $\text{BC}(\mathbb{R})$  in  $\mathcal{O}(n)$  time, but DC takes time exponential in  $n$ .

### Example (Why $\text{BC}(\mathbb{R})$ and not $\text{BC}(\mathbb{Z} / \mathbb{D})$ for equality?)

Propagate  $x = 3 \cdot y + 5 \cdot z$  from the store

$\{x \mapsto \{2, \dots, 7\}, y \mapsto \{0, 1, 2\}, z \mapsto \{0, 1\}\}$ :

The described bounds( $\mathbb{R}$ ) propagator gives

$\{x \mapsto \{2, \dots, 7\}, y \mapsto \{0, 1, 2\}, z \mapsto \{0, 1\}\}$ ,

while a bounds( $\mathbb{Z}$ ) or bounds( $\mathbb{D}$ ) propagator would give

$\{x \mapsto \{3, \dots, 6\}, y \mapsto \{0, 1, 2\}, z \mapsto \{0, 1\}\}$ .

Indeed, the described propagator considers the existence of **real**-number solutions, even though the constraint is over **integer** variables.

Compare with the domain-consistent store on slide 9.

- Linear disequality ( $\neq$ ): DC is cheaper than  $\text{BC}(\mathbb{R})$ .
- Linear inequality ( $<, \leq, \geq, >$ ):  $\text{BC}(\mathbb{R}) = \text{DC}$ ;  $\mathcal{O}(n)$  time.



# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC Propagator  
Efficient DC Propagator  
Efficient BC Propagator

1. Reification

2. Global Constraints

3. linear

4. channel

5. element

6. extensional

7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator



# The channel Predicate

## Definition

A `channel`  $([x_1, \dots, x_n], [y_1, \dots, y_n])$  constraint holds if and only if:

$$\forall i, j \in 1..n : x_i = j \Leftrightarrow y_j = i$$

Propagator for domain consistency:

- For each  $i \notin \text{dom}(y_j)$ : remove  $j$  from  $\text{dom}(x_i)$ .
- For each  $j \notin \text{dom}(x_i)$ : remove  $i$  from  $\text{dom}(y_j)$ .
- Post `distinct`  $([x_1, \dots, x_n])$  as implied constraint:  
if  $x_a = j = x_b$  with  $a \neq b$ , then  $y_j$  has to take two distinct values, namely  $a$  and  $b$ , which is impossible.
- Posting also `distinct`  $([y_1, \dots, y_n])$  as implied constraint would bring no further propagation.



# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC Propagator  
Efficient DC Propagator  
Efficient BC Propagator

1. Reification

2. Global Constraints

3. linear

4. channel

5. **element**

6. extensional

7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator



# The element Predicate

## Definition (Van Hentenryck and Carillon, 1988)

An `element`  $([x_1, \dots, x_n], i, e)$  constraint, where the  $x_j$  are variables,  $i$  is an integer **variable**, and  $e$  is a variable, holds if and only if  $x_i = e$ .

## Example

From the store  $\{i \mapsto \{1, 2, 3, 4\}, e \mapsto \{7, 8, 9\}\}$ , the constraint `element`  $([6, 8, 7, 8], i, e)$  propagates under DC to fixpoint  $\{i \mapsto \{2, 3, 4\}, e \mapsto \{7, 8\}\}$ . If the domain of  $i$  is pruned to  $\{2, 4\}$  by another constraint or a search decision, then  $e \mapsto \{8\}$  and subsumption are inferred under DC.

Possible definition of `element`  $([x_1, \dots, x_n], i, e)$ :  
 $(i = 1 \Rightarrow x_1 = e) \ \& \ \dots \ \& \ (i = n \Rightarrow x_n = e)$ , with  
 implicative constraints  $\alpha(\dots) \Rightarrow \beta(\dots)$  definable, under  
 little propagation, by  $a \Leftrightarrow \alpha(\dots) \ \& \ b \Leftrightarrow \beta(\dots) \ \& \ a \leq b$ .



## Propagation on an array of constants:

We insist on **domain** consistency, as BC would be too weak.

Objective, for  $\text{element}([x_1, \dots, x_n], i, e)$  and a store  $s$ :

- $i$  Keep only  $k$  in  $s(i)$  such that  $x_k = j$  for some  $j$  in  $s(e)$ .
- $e$  Keep only  $j$  in  $s(e)$  such that  $x_k = j$  for some  $k$  in  $s(i)$ .

## Naïve DC propagator:

The computed new domains must be **ordered** sets:

- $i$  The new domain of  $i$  is  $s(i) \cap \{k \in 1..n \mid x_k \in s(e)\}$ .
- $e$  The new domain of  $e$  is  $s(e) \cap \{x_k \mid k \in s(i)\}$ .

Sources of inefficiency:

- This **always** iterates over the **entire** array  $[x_1, \dots, x_n]$ .
- This **always** requires set intersection.
- This **always** requires sorting the 2nd argument of the 2nd intersection (or performing ordered set insertion).




## Example

Consider the constraint `element([4, 5, 9, 7], i, e)` and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

**Smart DC propagator (Van Hentenryck & Carillon, 1988):**

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:








## Example

Consider the constraint `element`( $[4, 5, 9, 7], i, e$ ) and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

### Smart DC propagator (Van Hentenryck & Carillon, 1988):

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:



- i* Follow the *i*-links: if a value is not in  $s(i)$ , then unlink the corresponding two nodes from the two lists.




## Example

Consider the constraint `element([4, 5, 9, 7], i, e)` and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

**Smart DC propagator (Van Hentenryck & Carillon, 1988):**

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:



- i* Follow the *i*-links: if a value is not in  $s(i)$ , then unlink the corresponding two nodes from the two lists.




## Example

Consider the constraint `element([4, 5, 9, 7], i, e)` and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

### Smart DC propagator (Van Hentenryck & Carillon, 1988):

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:



- i* Follow the *i*-links: if a value is not in  $s(i)$ , then unlink the corresponding two nodes from the two lists.




## Example

Consider the constraint `element([4, 5, 9, 7], i, e)` and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

### Smart DC propagator (Van Hentenryck & Carillon, 1988):

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:



- i* Follow the *i*-links: if a value is not in  $s(i)$ , then unlink the corresponding two nodes from the two lists.
- e* Follow the *e*-links: if a value is not in  $s(e)$ , then unlink the corresponding two nodes from the two lists.




## Example

Consider the constraint `element`  $([4, 5, 9, 7], i, e)$  and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

### Smart DC propagator (Van Hentenryck & Carillon, 1988):

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:



- i* Follow the *i*-links: if a value is not in  $s(i)$ , then unlink the corresponding two nodes from the two lists.
- e* Follow the *e*-links: if a value is not in  $s(e)$ , then unlink the corresponding two nodes from the two lists.




## Example

Consider the constraint `element`  $([4, 5, 9, 7], i, e)$  and the store  $s = \{i \mapsto \{2, 3, 4\}, e \mapsto \{2, 3, 4, 5, 6, 7, 8\}\}$ . Domain consistency gives the store  $\{i \mapsto \{2, 4\}, e \mapsto \{5, 7\}\}$ .

### Smart DC propagator (Van Hentenryck & Carillon, 1988):

Construct from  $[4, 5, 9, 7]$  two ordered doubly-linked lists:



- i* Follow the *i*-links: if a value is not in  $s(i)$ , then unlink the corresponding two nodes from the two lists.
- e* Follow the *e*-links: if a value is not in  $s(e)$ , then unlink the corresponding two nodes from the two lists.

The lists are sorted and are the new domains of *i* and *e*.



## Analysis:

- Each unlinking takes **constant** time.
- **No** set intersection needs to be computed.

## Definition

An **incremental propagator**, instead of throwing away any internal data structure when at fixpoint, keeps it for its next invocation: it first repairs that data structure according to the pruning done by other propagators since its previous invocation, and then only attempts its own pruning.

- Incremental propagation for `element`:
  - This requires sorting only at the **first** invocation, namely of the array (here `[4, 5, 9, 7]`).
  - This **always** iterates over an array **at most** as long as at the previous invocation.



# Outline

---

Reification

Global  
Constraints

linear

channel

element

**extensional**

distinct

Naïve DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator

1. Reification

2. Global Constraints

3. linear

4. channel

5. element

6. **extensional**

7. distinct

Naïve DC Propagator

Efficient DC Propagator


Efficient BC Propagator





# Deterministic Finite Automaton (DFA)

Example (DFA for regular expression  $ss(ts)^*|ts(t|ss)^*$ )



## Conventions:

- **Start state**, marked by arc coming in from nowhere: A.
- **Accepting states**, marked by double circles: D and E.
- **Determinism**: There is one outgoing arc per symbol in alphabet  $\Sigma = \{s, t\}$ ; missing arcs go to a non-accepting missing state that has self-loops on every symbol in  $\Sigma$ .



# The extensional Predicate

## Definition

An  $\text{extensional}([x_1, \dots, x_n], \mathcal{D})$  constraint holds iff the values taken by the sequence  $[x_1, \dots, x_n]$  of variables form a string of the regular language accepted by the DFA  $\mathcal{D}$ .

## Example

The constraint  $\text{extensional}([x_1, x_2, x_3, x_4], \mathcal{A})$ , where  $\mathcal{A}$  is the DFA of the previous slide, is propagated under domain consistency from the store

$$\{ x_1 \mapsto \{s, t\}, x_2 \mapsto \{s, t\}, x_3 \mapsto \{s, t\}, x_4 \mapsto \{s, t\} \}$$

to the fixpoint

$$\{ x_1 \mapsto \{s, t\}, x_2 \mapsto \{s\}, x_3 \mapsto \{s, t\}, x_4 \mapsto \{s, t\} \}$$

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Let us propagate `extensional` ( $[x_1, x_2, x_3, x_4], \mathcal{A}$ ), where  $\mathcal{A}$  is the DFA of two slides ago, from the following store:

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$

Reification

Global  
Constraints

linear

channel

element

**extensional**

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$

A0

Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naïve DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator






# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naïve DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Forward Phase:** Build all paths according to the values in the domains. (B3 & C3 and D4 & E4 can be merged.)

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, t\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Backward Phase:** Remove all paths not of length 4 or not ending in a vertex corresponding to an accepting state.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator






# Efficient DC Propagator (Pesant, 2004)

**Backward Phase:** Remove all paths not of length 4 or not ending in a vertex corresponding to an accepting state.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Pruning Phase:** Remove **unsupported values**; at fixpoint.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s, \textcolor{red}{t}\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

**Pruning Phase:** Remove **unsupported values**; at fixpoint.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_1 = t$  to fixpoint.

$$x_1 \mapsto \{s, t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_1 = t$  to fixpoint.

$$x_1 \mapsto \{t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_1 = t$  to fixpoint.

$$x_1 \mapsto \{t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_3 = s$  to subsumption.

$$x_1 \mapsto \{t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s, t\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_3 = s$  to subsumption.

$$x_1 \mapsto \{t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator






# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_3 = s$  to subsumption.

$$x_1 \mapsto \{t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s\} \quad x_4 \mapsto \{s, t\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct


Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Efficient DC Propagator (Pesant, 2004)

Incremental propagation upon  $x_3 = s$  to subsumption.

$$x_1 \mapsto \{t\} \quad x_2 \mapsto \{s\} \quad x_3 \mapsto \{s\} \quad x_4 \mapsto \{s\}$$



Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



# Complexity and Incrementality

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator

## Complexity:

The described DC propagator takes  $\mathcal{O}(n \cdot m \cdot q)$  time and space for  $n$  variables,  $m$  values in their domains, and  $q$  states in the DFA.

## Incrementality via a stateful propagator:

Keep the graph between propagator invocations.

When the propagator is re-invoked:

- 1 Remove edges that no longer correspond to the store.
- 2 Run the forward, backward, and pruning phases.



# Bibliography

---



Beldiceanu, Nicolas; Carlsson, Mats; Petit, Thierry.  
**Deriving filtering algorithms from constraint checkers.**  
*Proceedings of CP 2004*, Lecture Notes in Computer  
Science 3258, pages 107 – 122. Springer, 2004.



Pesant, Gilles.  
**A regular language membership constraint for finite  
sequences of variables.**  
*Proceedings of CP 2004*, Lecture Notes in Computer  
Science 3258, pages 482 – 495. Springer, 2004.



Hopcroft, John E.; Motwani, Rajeev; Ullman, Jeffrey D.  
**Intro. to Automata Theory, Languages, & Computation.**  
Third edition. Addison-Wesley, 2007.



# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

**distinct**

Naïve DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. **distinct**

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator



# The distinct Predicate

## Definition (Laurière, 1978)

A `distinct`  $([x_1, \dots, x_n])$  constraint holds if and only if all the variables  $x_i$  take different values.

This is equivalent to  $\frac{n \cdot (n-1)}{2}$  disequality constraints:

$$\forall i, j \in 1..n \text{ where } i < j : x_i \neq x_j$$

Originally, the `distinct` constraint was just a wrapper for posting those  $\frac{n \cdot (n-1)}{2}$  disequality constraints. The first efficient domain-consistency propagators for `distinct` were introduced in 1994; one of them is discussed below. After that, several other efficient propagators have been proposed to enforce various consistencies.

Reification

Global  
Constraints

linear

channel

element

extensional

**distinct**

Naïve DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator



## Example

Consider the store  $\{x_1, x_2, x_3 \mapsto \{4, 5\}\}$   
and the constraint  $\text{distinct}([x_1, x_2, x_3])$ :

- Value consistency: Nothing is done to the domains.
- Bounds consistency: A failure is detected.
- Domain consistency (DC): A failure is detected.

What consistency to use is **problem-dependent** and even **instance-dependent**!

## Example ( $\text{distinct}([u, v, w, x, y, z])$ )

From the store

$$\left\{ \begin{array}{l} u \mapsto \{0, 1\}, v \mapsto \{1, 2\}, w \mapsto \{0, 2\}, \\ x \mapsto \{1, 3\}, y \mapsto \{2, 3, 4, 5\}, z \mapsto \{5, 6\} \end{array} \right\}$$

the **pink** values are pruned upon DC.



# Is DC Needed for distinct?

## Example (Golomb Rulers)

Design a ruler with  $n$  ticks such that:

- The distances between any 2 distinct ticks are distinct.
- The length of the ruler is minimal.

For  $n = 6$ , an optimal ruler is  $[0, 1, 4, 10, 12, 17]$ .

This very hard problem has applications in crystallography.

$n$	value consistency	domain consistency
7	950 nodes	474 nodes
8	7,622 nodes	3,076 nodes
9	55,930 nodes	16,608 nodes
10	413,922 nodes	97,782 nodes
11	6,330,568 nodes	1,448,666 nodes

Good search-tree reduction: worth looking for a propagator!

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator  
Efficient DC  
Propagator  
Efficient BC  
Propagator





# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC  
Propagator

Efficient DC  
Propagator

Efficient BC  
Propagator

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. **distinct**

Naïve DC Propagator


Efficient DC Propagator

Efficient BC Propagator



## Variable-Value Graph:


Construct a bipartite graph from the current domains:





## Variable-Value Graph:


A (maximum) matching is a (max-size) subset of edges so that no vertex is incident to two of its edges. **Example 1:**





## Variable-Value Graph:


A (maximum) matching is a (max-size) subset of edges so that no vertex is incident to two of its edges. Example 2:





## Variable-Value Graph:

A (maximum) matching is a (max-size) subset of edges so that no vertex is incident to two of its edges. **Example 2:**



A max matching is (here) **perfect** iff it covers all variables:  
it is a solution to the considered `distinct(...)` constraint.



## Naïve DC propagator:

- 1 If no perfect matching exists, then fail.
- 2 Compute all perfect matchings and mark their edges.
- 3 For every unmarked edge between a variable  $v$  and a value  $d$ : prune value  $d$  from  $\text{dom}(v)$ .

But there are as many perfect matchings as solutions!

☞ We have solved the space issue, but **not** the time issue.

## Matching theory to the rescue!

There is a relationship between the edges in a maximum matching and the edges in all other maximum matchings!

☞ Hence we need only compute **one** perfect matching!



# Outline

---

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC  
Propagator

Efficient DC  
Propagator

Efficient BC  
Propagator

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. distinct

Naïve DC Propagator


Efficient DC Propagator

Efficient BC Propagator



## Efficient DC propagator (Régim, 1994) (Costa, 1994):

Start from a perfect matching, and orient all edges: if in matching, then from variable to value, else the other way.








## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Start from a perfect matching, and orient all edges: if in matching, then from variable to value, else the other way.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Start from all unmatched vertices (necessarily values here) and mark all arcs on all simple paths: arcs can be flipped.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Start from all unmatched vertices (necessarily values here) and mark all arcs on all simple paths: arcs can be flipped.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Start from all unmatched vertices (necessarily values here) and mark all arcs on all simple paths: arcs can be flipped.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Start from all unmatched vertices (necessarily values here) and mark all arcs on all simple paths: arcs can be flipped.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Start from all unmatched vertices (necessarily values here) and mark all arcs on all simple paths: arcs can be flipped.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):

Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.








## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Mark all arcs in all strongly connected components (SCCs):  
the variables of an SCC take all the values of that SCC.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Every arc that is neither **in the chosen perfect matching** nor **marked** is in *no* perfect matching: **prune** accordingly.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):


Every arc that is neither **in the chosen perfect matching** nor **marked** is in *no* perfect matching: **prune** accordingly.





## Efficient DC propagator (Régim, 1994) (Costa, 1994):

Every arc that is neither **in the chosen perfect matching** nor **marked** is in *no* perfect matching: **prune** accordingly.







## Efficient DC propagator (Régim, 1994) (Costa, 1994):

Every arc that is neither **in the chosen perfect matching** nor **marked** is in *no* perfect matching: **prune** accordingly.

$$u \mapsto \{0, 1\}$$



$$v \mapsto \{1, 2\}$$



$$w \mapsto \{0, 2\}$$




$$x \mapsto \{1, 3\}$$



$$y \mapsto \{2, 3, 4, 5\}$$



$$z \mapsto \{5, 6\}$$





## Efficient DC propagator (Régim, 1994) (Costa, 1994):

Every arc that is **in the chosen perfect matching** but not **marked** is in *every* perfect matching: fixed variable.

$$u \mapsto \{0, 1\}$$



$$v \mapsto \{1, 2\}$$



$$w \mapsto \{0, 2\}$$




$$x \mapsto \{1, 3\}$$



$$y \mapsto \{2, 3, 4, 5\}$$



$$z \mapsto \{5, 6\}$$





# Underlying Theorem from Matching Theory

## Theorem (Berge, 1970) (Petersen, 1891)

Edge  $e$  belongs to some maximum matching if and only if, for an arbitrarily chosen maximum matching  $M$ :

$e$  belongs to a path of an even number of edges that starts at some node that is not incident to an edge of  $M$  and that alternates between edges in  $M$  and edges not in  $M$ ;

or  $e$  belongs to a cycle of an even number of edges that alternates between edges in  $M$  and edges not in  $M$  (that is, the arc corresponding to  $e$  belongs to an SCC).

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naive DC  
Propagator

Efficient DC  
Propagator

Efficient BC  
Propagator



# Complexity and Incrementality

## Complexity:

The described DC propagator takes

$$\mathcal{O}(m \cdot \sqrt{n}) \text{ time and } \mathcal{O}(m \cdot n) \text{ space}$$

for  $n$  variables and  $m \geq n$  values in their domains.

## Incrementality via stateful propagator:

Keep the variable-value graph between invocations.

When the propagator is re-invoked:

- 1 Remove marks on arcs.
- 2 Remove arcs that no longer correspond to the store.
- 3 If an arc of the old perfect matching was removed, then first compute a new perfect matching.
- 4 Mark and prune.



# Outline

---

## 1. Reification

## 2. Global Constraints

## 3. linear

## 4. channel

## 5. element

## 6. extensional

## 7. distinct

Naïve DC Propagator

Efficient DC Propagator

Efficient BC Propagator

Reification

Global  
Constraints

linear

channel

element

extensional

distinct

Naïve DC  
Propagator  
Efficient DC  
Propagator

Efficient BC  
Propagator



## Is BC Needed for `distinct`?

Propagation to BC often suffices for `distinct`.

### Example

Propagation to BC suffices to infer unsatisfiability for `distinct([x, y, z])` from the store  $\{x, y, z \mapsto \{4, 5\}\}$ .

### Efficient BC propagators:

There are BC propagators that take  $\mathcal{O}(n \cdot \lg n)$  time:

- Puget @ AAAI 1998
- Mehlhorn and Thiel @ CP 2000
- López-Ortiz, Quimper, Tromp, van Beek @ IJCAI 2003

The latter two run in  $\mathcal{O}(n)$  time if sorting can be avoided, say when there are as many values as variables.



# Bibliography

---



Régin, Jean-Charles.

A filtering algo. for constraints of difference in CSPs.  
*AAAI 1994*, pages 362 – 367, 1994.



Costa, Marie-Christine.

Persistency in maximum cardinality bipartite matchings.  
*Operations Research Letters*, 15(3):143 – 149, 1994.



Berge, Claude.

*Graphes et Hypergraphes*. Dunod, 1970.



Petersen, Julius.

Die Theorie der regulären graphs.  
*Acta Mathematica*, 15(1):193 – 220, 1891.



van Hoeve, Willem-Jan.

The Alldifferent Constraint: A Survey.  
Extended from the version in *ERCIM Workshop 2001*.