


Using and Improving GladLibs

HashMap

New Structures

- GladLib program works!
 - Design flaws, but can be modified
- Counting frequencies, 'CGAT' to 'AB..YZ'
 - Extended to words with two ArrayLists
 - From 4 to 26 to 5,280* counters!



New Structures

- GladLib program works!
 - Design flaws, but can be modified
- Counting frequencies, 'CGAT' to 'AB..YZ'
 - Extended to words with two ArrayLists
 - From 4 to 26 to 5,280* counters!



New Structures

- GladLib program works!
 - Design flaws, but can be modified
- Counting frequencies, 'CGAT' to 'AB..YZ'
 - Extended to words with two ArrayLists
 - From 4 to 26 to 5,280* counters!

"the"	"green"		"dog"		myWords
2	1		3		myFreqs

New Structures

- GladLib program works!
 - Design flaws, but can be modified
- Counting frequencies, 'CGAT' to 'AB..YZ'
 - Extended to words with two ArrayLists
 - From 4 to 26 to 5,280* counters!
- From parallel ArrayLists to HashMap
 - Code in GladLib easier to modify
 - Much faster to count word frequencies

Starting with Parallel ArrayLists

- Seen code using parallel arrays to count word occurrences, calls **.indexOf(s)**

```
public void findUnique(){
    FileResource resource = new FileResource();
    for(String s : resource.words()){
        s = s.toLowerCase();
        int index = myWords.indexOf(s);
        if (index == -1){
            myWords.add(s);
            myFreqs.add(1);
        }
        else {
            int freq = myFreqs.get(index);
            myFreqs.set(index, freq+1);
        }
    }
}
```

Starting with Parallel ArrayLists

- Seen code using parallel arrays to count word occurrences, calls **.indexOf(s)**

```
public void findUnique(){
    FileResource resource = new FileResource();
    for(String s : resource.words()){
        s = s.toLowerCase();
        int index = myWords.indexOf(s);
        if (index == -1){
            myWords.add(s);
            myFreqs.add(1);
        }
        else {
            int freq = myFreqs.get(index);
            myFreqs.set(index, freq+1);
        }
    }
}
```

Starting with Parallel ArrayLists

- Seen code using parallel arrays to count word occurrences, calls `.indexOf(s)`

```
public void findUnique(){
    FileResource resource = new FileResource();
    for(String s : resource.words()){
        s = s.toLowerCase();
        int index = myWords.indexOf(s);
        if (index == -1){
            myWords.add(s);
            myFreqs.add(1);
        }
        else {
            int freq = myFreqs.get(index);
            myFreqs.set(index, freq+1);
        }
    }
}
```


Starting with Parallel ArrayLists

- Seen code using parallel arrays to count word occurrences, calls `.indexOf(s)`

```
public void findUnique(){
    FileResource resource = new FileResource();
    for(String s : resource.words()){
        s = s.toLowerCase();
        int index = myWords.indexOf(s);
        if (index == -1){
            myWords.add(s);
            myFreqs.add(1);
        }
        else {
            int freq = myFreqs.get(index);
            myFreqs.set(index, freq+1);
        }
    }
}
```


Starting with Parallel ArrayLists

- Seen code using parallel arrays to count word occurrences, calls **.indexOf(s)**

```
public void findUnique(){
    FileResource resource = new FileResource();
    for(String s : resource.words()){
        s = s.toLowerCase();
        int index = myWords.indexOf(s);
        if (index == -1){
            myWords.add(s);
            myFreqs.add(1);
        }
        else {
            int freq = myFreqs.get(index);
            myFreqs.set(index, freq+1);
        }
    }
}
```

Motivating HashMap

- A HashMap is a class that associates keys with values, generally called a map



Motivating HashMap


- A HashMap is a class that associates keys with values, generally called a map
 - More mathematical than geographical
 - Key is element in domain, value is what key maps to in range
- Look up key, get associated value

rainbow	23
football	41
wonderful	17
truth	23

Motivating HashMap

- A HashMap is a class that associates keys with values, generally called a map
 - More mathematical than geographical
 - Key is element in domain, value is what key maps to in range
- Look up key, get associated value

`map.get("rainbow")`




Motivating HashMap

- A HashMap is a class that associates keys with values, generally called a map
 - More mathematical than geographical
 - Key is element in domain, value is what key maps to in range
- Look up key, get associated value

`map.get("rainbow")`

`map.get("truth")`




Motivating HashMap

- A HashMap is a class that associates keys with values, generally called a map
 - More mathematical than geographical
 - Key is element in domain, value is what key maps to in range
- Look up key, get associated value

`map.get("rainbow")`

`map.get("truth")`

`map.get("football")`



Motivating HashMap


- A HashMap is a class that associates keys with values, generally called a map
 - More mathematical than geographical
 - Key is element in domain, value is what key maps to in range
- Look up key, get associated value

`map.get("rainbow")`

`map.get("truth")`

`map.get("football")`

`map.get("wonderful")`



Updating Values in HashMap

- One HashMap replaces two ArrayLists

```
public void findUnique(){
    FileResource resource = new FileResource();
    for(String s : resource.words()){
        s = s.toLowerCase();
        int index = myWords.indexOf(s);
        if (index == -1){
            myWords.add(s);
            myFreqs.add(1);
        }
        else {
            int freq = myFreqs.get(index);
            myFreqs.set(index, freq+1);
        }
    }
}
```

Updating Values in HashMap

- One HashMap replaces two ArrayLists
 - Key is String, associated value is Integer

```
public void countWordsMap(){
    FileResource resource = new FileResource();
    HashMap<String,Integer> map = new HashMap<String,Integer>();

    for(String w : resource.words()){
        w = w.toLowerCase();
        if (!map.containsKey(w)){
            map.put(w,1);
        }
        else {
            map.put(w,map.get(w)+1);
        }
    }
}
```

Updating Values in HashMap

- One HashMap replaces two ArrayLists
 - Key is String, associated value is Integer

```
public void countWordsMap(){
    FileResource resource = new FileResource();
    HashMap<String,Integer> map = new HashMap<String,Integer>();

    for(String w : resource.words()){
        w = w.toLowerCase();
        if (!map.containsKey(w)){
            map.put(w,1);
        }
        else {
            map.put(w,map.get(w)+1);
        }
    }
}
```

Updating Values in HashMap

- One HashMap replaces two ArrayLists
 - Key is String, associated value is Integer

```
public void countWordsMap(){
    FileResource resource = new FileResource();
    HashMap<String,Integer> map = new HashMap<String,Integer>();

    for(String w : resource.words()){
        w = w.toLowerCase();
        if (!map.containsKey(w)){
            map.put(w,1);
        }
        else {
            map.put(w,map.get(w)+1);
        }
    }
}
```


Updating Values in HashMap

- One HashMap replaces two ArrayLists
 - Key is String, associated value is Integer
 - Is key new, unseen? put value 1, else update

```
public void countWordsMap(){
    FileResource resource = new FileResource();
    HashMap<String,Integer> map = new HashMap<String,Integer>();

    for(String w : resource.words()){
        w = w.toLowerCase();
        if (!map.containsKey(w)){
            map.put(w,1);
        }
        else {
            map.put(w,map.get(w)+1);
        }
    }
}
```

Updating Values in HashMap

- One HashMap replaces two ArrayLists
 - Key is String, associated value is Integer
 - Is key new, unseen? put value 1, else update

```
public void countWordsMap(){
    FileResource resource = new FileResource();
    HashMap<String,Integer> map = new HashMap<String,Integer>();

    for(String w : resource.words()){
        w = w.toLowerCase();
        if (!map.containsKey(w)){
            map.put(w,1);
        }
        else {
            map.put(w,map.get(w)+1);
        }
    }
}
```

Updating Values in HashMap

- One HashMap replaces two ArrayLists
 - Key is String, associated value is Integer
 - Is key new, unseen? put value 1, else update

```
public void countWordsMap(){
    FileResource resource = new FileResource();
    HashMap<String,Integer> map = new HashMap<String,Integer>();

    for(String w : resource.words()){
        w = w.toLowerCase();
        if (!map.containsKey(w)){
            map.put(w,1);
        }
        else {
            map.put(w,map.get(w)+1);
        }
    }
}
```

Accessing All Values in Map

- Printing all values in parallel arrays uses for loop with index accessing word and freq

```
public void printWords(){  
    for(int k=0; k < myFreqs.size(); k++){  
        System.out.println(myFreqs.get(k)+"\t"+myWords.get(k));  
    }  
}
```


Accessing All Values in Map

- Printing all values in parallel arrays uses for loop with index accessing word and freq
- Printing all values in map requires looping over keys, get value associated with key

```
public void printWords(){  
    for(String s : myMap.keySet()){  
        System.out.println(myMaps.get(s)+"\t"+s);  
    }  
}
```

Accessing All Values in Map

- Printing all values in parallel arrays uses for loop with index accessing word and freq
- Printing all values in map requires looping over keys, get value associated with key
 - Iterable `.keySet()`, similar to `.words()` or `.lines()` or `.data()`

```
public void printWords(){  
    for(String s : myMap.keySet()){  
        System.out.println(myMaps.get(s)+"\t"+s);  
    }  
}
```

Accessing All Values in Map

- Printing all values in parallel arrays uses for loop with index accessing word and freq
- Printing all values in map requires looping over keys, get value associated with key
 - Iterable `.keySet()`, similar to `.words()` or `.lines()` or `.data()`

```
public void printWords(){  
    for(String s : myMap.keySet()){  
        System.out.println(myMaps.get(s)+"\t"+s);  
    }  
}
```

Maps are Very Efficient!

- When files are large, efficiency matters

	<i>Total Words</i>	<i>Different Words</i>	<i>Time ArrayList</i>	<i>Time HashMap</i>
<i>Julius Caesar</i>	20,869	4,443	0.25	0.03
<i>Confucius</i>	34,582	6,558	0.4	0.05
<i>Scarlet Letter</i>	85,754	13,543	1.3	0.1
<i>King James Bible</i>	823,135	32,675	20.8	0.48

Maps are Very Efficient!

- When files are large, efficiency matters

	<i>Total Words</i>	<i>Different Words</i>	<i>Time ArrayList</i>	<i>Time HashMap</i>
<i>Julius Caesar</i>	20,869	4,443	0.25	0.03
<i>Confucius</i>	34,582	6,558	0.4	0.05
<i>Scarlet Letter</i>	85,754	13,543	1.3	0.1
<i>King James Bible</i>	823,135	32,675	20.8	0.48

Maps are Very Efficient!

- When files are large, efficiency matters

	<i>Total Words</i>	<i>Different Words</i>	<i>Time ArrayList</i>	<i>Time HashMap</i>
<i>Julius Caesar</i>	20,869	4,443	0.25	0.03
<i>Confucius</i>	34,582	6,558	0.4	0.05
<i>Scarlet Letter</i>	85,754	13,543	1.3	0.1
<i>King James Bible</i>	823,135	32,675	20.8	0.48

Maps are Very Efficient!

- When files are large, efficiency matters

	<i>Total Words</i>	<i>Different Words</i>	<i>Time ArrayList</i>	<i>Time HashMap</i>
<i>Julius Caesar</i>	20,869	4,443	0.25	0.03
<i>Confucius</i>	34,582	6,558	0.4	0.05
<i>Scarlet Letter</i>	85,754	13,543	1.3	0.1
<i>King James Bible</i>	823,135	32,675	20.8	0.48

Maps are Very Efficient!

- When files are large, efficiency matters

	<i>Total Words</i>	<i>Different Words</i>	<i>Time ArrayList</i>	<i>Time HashMap</i>
<i>Julius Caesar</i>	20,869	4,443	0.25	0.03
<i>Confucius</i>	34,582	6,558	0.4	0.05
<i>Scarlet Letter</i>	85,754	13,543	1.3	0.1
<i>King James Bible</i>	823,135	32,675	20.8	0.48

Maps are Very Efficient!

- When files are large, efficiency matters
 - Look up in map is independent of number of keys! ArrayList requires looking at all elements

	<i>Total Words</i>	<i>Different Words</i>	<i>Time ArrayList</i>	<i>Time HashMap</i>
<i>Julius Caesar</i>	20,869	4,443	0.25	0.03
<i>Confucius</i>	34,582	6,558	0.4	0.05
<i>Scarlet Letter</i>	85,754	13,543	1.3	0.1
<i>King James Bible</i>	823,135	32,675	20.8	0.48