

```
from sklearn.datasets import load_iris
from sklearn.tree import DecisionTreeClassifier, plot_tree, export_text
from sklearn.model_selection import train_test_split
import matplotlib.pyplot as plt
```

```
iris = load_iris()
X, y = iris.data, iris.target
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
```

```
tree = DecisionTreeClassifier(max_depth=2, random_state=42)
tree.fit(X_train, y_train)
print(f'Train accuracy: {tree.score(X_train, y_train):.2%}')
print(f'Test accuracy: {tree.score(X_test, y_test):.2%}')
```


```
Train accuracy: 95.00%
Test accuracy: 96.67%
```

```
print(export_text(tree, feature_names=iris.feature_names))
```

```
|--- petal length (cm) <= 2.45
|   |--- class: 0
|--- petal length (cm) > 2.45
|   |--- petal length (cm) <= 4.75
|       |--- class: 1
|   |--- petal length (cm) > 4.75
|       |--- class: 2
```

```
plt.figure(figsize=(10, 6))
plot_tree(tree, feature_names=iris.feature_names,
          class_names=iris.target_names,
          filled=True, rounded=False, fontsize=12)
plt.title('Iris Decision Tree (max_depth=4)'); plt.tight_layout(); plt.show()
```

Iris Decision Tree (max_depth=4)



```
new_flower = [[5.1, 3.5, 1.4, 0.2]]
pred = tree.predict(new_flower)[0]
print(f'Predicted species: {iris.target_names[pred]}')
print(f'Probabilities : {tree.predict_proba(new_flower)[0]}')
```

```
Predicted species: setosa
Probabilities : [1. 0. 0.]
```

```
import numpy as np
from sklearn.tree import DecisionTreeClassifier
import matplotlib.pyplot as plt
```

```
def gini_impurity(labels):
    """Calculate Gini impurity for a list of class labels."""
    labels = np.array(labels)
    n = len(labels)
    if n == 0: return 0
    classes = np.unique(labels)
    gini = 1.0
    for c in classes:
        p = np.sum(labels == c) / n # proportion of class c
        gini -= p ** 2
    return gini
```

```
print('Pure node (all same) :', gini_impurity([1,1,1,1,1])) # 0.00
print('50-50 split :', gini_impurity([0,0,0,1,1,1])) # 0.50
print('70-30 split :', gini_impurity([0,0,0,0,0,0,1,1,1])) # 0.42
print('90-10 split :', gini_impurity([0]*9 + [1])) # 0.18
```

```
Pure node (all same) : 0.0
50-50 split : 0.5
70-30 split : 0.42000000000000004
90-10 split : 0.17999999999999994
```

```
def weighted_gini(left_labels, right_labels):
    """Gini after a split – weighted by group size."""
    n_total = len(left_labels) + len(right_labels)
    w_left = len(left_labels) / n_total
    w_right = len(right_labels) / n_total
    return w_left * gini_impurity(left_labels) + w_right * gini_impurity(right_labels)
```

```
left_A = [0,0,0,0,1]
right_A = [0,1,1,1,1]
```

```
left_B = [0,0,1,1,0]
right_B = [0,1,0,1,1]
```

```
print(f'Weighted Gini – Glucose split: {weighted_gini(left_A, right_A):.3f}')
print(f'Weighted Gini – Age split : {weighted_gini(left_B, right_B):.3f}')
print('Tree picks the split with LOWER weighted Gini → Glucose split is better!')
```

```
Weighted Gini – Glucose split: 0.320
Weighted Gini – Age split : 0.480
Tree picks the split with LOWER weighted Gini → Glucose split is better!
```

```
from sklearn.datasets import make_classification
from sklearn.tree import export_text
X, y = make_classification(n_samples=200, n_features=4, random_state=42)
tree = DecisionTreeClassifier(max_depth=2, random_state=42)
tree.fit(X, y)
```

```
DecisionTreeClassifier
DecisionTreeClassifier(max_depth=2, random_state=42)
```

```
print(export_text(tree, feature_names=['F1', 'F2', 'F3', 'F4']))
```

```
|--- F1 <= -0.15
|   |--- F3 <= -0.44
|   |   |--- class: 0
|   |--- F3 > -0.44
|   |   |--- class: 0
|--- F1 > -0.15
|   |--- F3 <= 0.63
|   |   |--- class: 1
|   |--- F3 > 0.63
|   |   |--- class: 0
```


```
from sklearn.tree import DecisionTreeClassifier
from sklearn.datasets import make_classification
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score
import matplotlib.pyplot as plt
```

```
X, y = make_classification(n_samples=600, n_features=10, random_state=42)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
depths = range(1, 21)
train_acc, test_acc = [], []
```

```
for d in depths:
    tree = DecisionTreeClassifier(max_depth=d, random_state=42)
    tree.fit(X_train, y_train)
    train_acc.append(accuracy_score(y_train, tree.predict(X_train)))
    test_acc.append(accuracy_score(y_test, tree.predict(X_test)))
    best_depth = depths[test_acc.index(max(test_acc))]
```

```
X, y = make_classification(n_samples=600, n_features=6, random_state=42)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
depths = range(1, 21)
train_acc, test_acc = [], []
for d in depths:
    tree = DecisionTreeClassifier(max_depth=d, random_state=42)
    tree.fit(X_train, y_train)
    train_acc.append(accuracy_score(y_train, tree.predict(X_train)))
    test_acc.append(accuracy_score(y_test, tree.predict(X_test)))
best_depth = depths[test_acc.index(max(test_acc))]
```

```
plt.figure(figsize=(9, 5))
plt.plot(depths, train_acc, 'o-', color='steelblue', lw=2, label='Train Accuracy')
plt.plot(depths, test_acc, 's-', color='tomato', lw=2, label='Test Accuracy')
plt.axvline(x=best_depth, color='green', linestyle='--', lw=2,
            label=f'Best depth = {best_depth}')
plt.fill_between(depths,
                 train_acc, test_acc,
                 alpha=0.15, color='gray', label='Overfitting gap')
plt.xlabel('max_depth', fontsize=12)
plt.ylabel('Accuracy', fontsize=12)
plt.title('Overfitting Curve: Train vs Test Accuracy', fontsize=13)
plt.legend(); plt.grid(alpha=0.3); plt.tight_layout(); plt.show()
```



```
from sklearn.tree import DecisionTreeClassifier
from sklearn.model_selection import cross_val_score
import numpy as np
```

```
configs = [
    {'max_depth': None},
    {'max_depth': 5},
    {'max_depth': 5, 'min_samples_split': 10},
    {'max_depth': 5, 'min_samples_leaf': 5},
    {'max_depth': 5, 'max_features': 'sqrt'},
]
```

```
print(f'{{Config:45s}} {{CV Score (mean±std):20s}}')
print('-' * 68)
```

```
for cfg in configs:
    tree = DecisionTreeClassifier(**cfg, random_state=42)
    scores = cross_val_score(tree, X, y, cv=5, scoring='accuracy')
    print(f'{str(cfg):45s} {scores.mean():.3f} ± {scores.std():.3f}')
```

Config	CV Score (mean±std)
-----	-----
{'max_depth': None}	0.892 ± 0.031
{'max_depth': 5}	0.907 ± 0.026
{'max_depth': 5, 'min_samples_split': 10}	0.908 ± 0.018
{'max_depth': 5, 'min_samples_leaf': 5}	0.907 ± 0.017
{'max_depth': 5, 'max_features': 'sqrt'}	0.895 ± 0.015

Start coding or [generate](#) with AI.