LAB SHEET-6

NAME: GUDDETI HARSHITHA

REGD:23BCE7967

SLOT: L37+L38

1. Use MongoDB to implement the following DB operations

   1. Create a database called ‘vehicles’ and *write* a MongoDB query to select database as “vehicles”.

```
test> use vehicles
switched to db vehicles
```

   2. Write a MongoDB query to display all the databases.

```
vehicles> show dbs
admin                     40.00 KiB
config                    60.00 KiB
employee                 120.00 KiB
local                     96.00 KiB
mongodbVSCodePlaygroundDB 72.00 KiB
```

   3. Create a collection called ‘two_wheelers’. (use capping) and Create a collection called ‘four_wheelers’.

```
vehicles> db.createCollection("two_wheelers", { capped: true, size: 500000, max: 100 })
{ ok: 1 }
vehicles> db.createCollection("four_wheelers")
{ ok: 1 }
```

   4. Add 5 two-wheeler details to the collection named ‘two_wheelers’. Each document consists of following fields as bike_name, model (gear or gearless), category (100cc, 125cc, 150cc, 200cc), colors_available (red, black, blue, sport red etc) as array, manufacturer, performance (out of 10), timestamp (date and year release) and price.

```
vehicles> db.two_wheelers.insertMany([
... {
... bike_name: "Honda Shine",
... model: "gear",
... category: "125cc",
... colors_available: ["red","black","blue"],
... manufacturer: "Honda",
... performance: 8,
... timestamp: new Date("2022-03-10"),
... price: 80000
... },
... {
... bike_name: "TVS Apache",
... model: "gear",
... category: "150cc",
... colors_available: ["black","sport red"],
... manufacturer: "TVS",
... performance: 9,
... timestamp: new Date("2021-05-12"),
... price: 110000
... },
... {
... bike_name: "Hero Splendor",
... model: "gear",
... category: "100cc",
... colors_available: ["black","blue"],
... manufacturer: "Hero",
... performance: 7,
... timestamp: new Date("2020-01-18"),
... price: 75000
... },
```

```
... bike_name: "Honda Activa",
... model: "gearless",
... category: "125cc",
... colors_available: ["red","white","blue"],
... manufacturer: "Honda",
... performance: 8,
... timestamp: new Date("2023-02-01"),
... price: 85000
... },
... {
... bike_name: "Bajaj Pulsar",
... model: "gear",
... category: "200cc",
... colors_available: ["black","sport red"],
... manufacturer: "Bajaj",
... performance: 9,
... timestamp: new Date("2022-07-15"),
... price: 150000
... }
... ])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69b14ee908b1463dc350eb67'),
    '1': ObjectId('69b14ee908b1463dc350eb68'),
    '2': ObjectId('69b14ee908b1463dc350eb69'),
    '3': ObjectId('69b14ee908b1463dc350eb6a'),
    '4': ObjectId('69b14ee908b1463dc350eb6b')
  }
}
```

5. Add 5 four-wheeler details to the collection named ‘four_wheelers’. Each document consists of following fields as vehicle_name, model (commercial or own), category (car, lorry, bus, mini truck, heavy truck, containers), variants (vxi, zxi, petrol, diesel etc) as array, manufacturer, performance (out of 10), timestamp (date and year release) and price.

```
vehicles> db.four_wheelers.insertMany([
... {
... vehicle_name: "Maruti Swift",
... model: "own",
... category: "car",
... variants: ["vxi","petrol"],
... manufacturer: "Maruti",
... performance: 8,
... timestamp: new Date("2021-06-12"),
... price: 650000
... },
... {
... vehicle_name: "Tata Ace",
... model: "commercial",
... category: "mini truck",
... variants: ["diesel"],
... manufacturer: "Tata",
... performance: 7,
... timestamp: new Date("2020-09-05"),
... price: 500000
... },
... {
... vehicle_name: "Ashok Leyland Bus",
... model: "commercial",
... category: "bus",
... variants: ["diesel"],
... manufacturer: "Ashok Leyland",
... performance: 8,
... timestamp: new Date("2019-08-10"),
... price: 2500000
... },
```

```
... {
... vehicle_name: "Mahindra Bolero",
... model: "own",
... category: "car",
... variants: ["zxi","diesel"],
... manufacturer: "Mahindra",
... performance: 8,
... timestamp: new Date("2022-04-11"),
... price: 900000
... },
... {
... vehicle_name: "Volvo Container",
... model: "commercial",
... category: "containers",
... variants: ["diesel"],
... manufacturer: "Volvo",
... performance: 9,
... timestamp: new Date("2021-11-19"),
... price: 4000000
... }
... ])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69b14ef808b1463dc350eb6c'),
    '1': ObjectId('69b14ef808b1463dc350eb6d'),
    '2': ObjectId('69b14ef808b1463dc350eb6e'),
    '3': ObjectId('69b14ef808b1463dc350eb6f'),
    '4': ObjectId('69b14ef808b1463dc350eb70')
```

6. Write a MongoDB query to display all documents available in two_wheelers and four_wheelers.

```
vehicles> db.two_wheelers.find()
...
[
  {
    _id: ObjectId('69b14ee908b1463dc350eb67'),
    bike_name: 'Honda Shine',
    model: 'gear',
    category: '125cc',
    colors_available: [ 'red', 'black', 'blue' ],
    manufacturer: 'Honda',
    performance: 8,
    timestamp: ISODate('2022-03-10T00:00:00.000Z'),
    price: 80000
  },
  {
    _id: ObjectId('69b14ee908b1463dc350eb68'),
    bike_name: 'TVS Apache',
    model: 'gear',
    category: '150cc',
    colors_available: [ 'black', 'sport red' ],
    manufacturer: 'TVS',
    performance: 9,
    timestamp: ISODate('2021-05-12T00:00:00.000Z'),
    price: 110000
  },
  {
    _id: ObjectId('69b14ee908b1463dc350eb69'),
    bike_name: 'Hero Splendor',
    model: 'gear',
    category: '100cc',
    colors_available: [ 'black', 'blue' ],
    manufacturer: 'Hero',
    performance: 7,
    timestamp: ISODate('2020-01-18T00:00:00.000Z'),
    price: 75000
  },
```

```
  {
    _id: ObjectId('69b14ee908b1463dc350eb6a'),
    bike_name: 'Honda Activa',
    model: 'gearless',
    category: '125cc',
    colors_available: [ 'red', 'white', 'blue' ],
    manufacturer: 'Honda',
    performance: 8,
    timestamp: ISODate('2023-02-01T00:00:00.000Z'),
    price: 85000
  },
  {
    _id: ObjectId('69b14ee908b1463dc350eb6b'),
    bike_name: 'Bajaj Pulsar',
    model: 'gear',
    category: '200cc',
    colors_available: [ 'black', 'sport red' ],
    manufacturer: 'Bajaj',
    performance: 9,
    timestamp: ISODate('2022-07-15T00:00:00.000Z'),
    price: 150000
  }
]
```

```
vehicles> db.four_wheelers.find()
[
  {
    _id: ObjectId('69b14ef808b1463dc350eb6c'),
    vehicle_name: 'Maruti Swift',
    model: 'own',
    category: 'car',
    variants: [ 'vxi', 'petrol' ],
    manufacturer: 'Maruti',
    performance: 8,
    timestamp: ISODate('2021-06-12T00:00:00.000Z'),
    price: 650000
  },
  {
    _id: ObjectId('69b14ef808b1463dc350eb6d'),
    vehicle_name: 'Tata Ace',
    model: 'commercial',
    category: 'mini truck',
    variants: [ 'diesel' ],
    manufacturer: 'Tata',
    performance: 7,
    timestamp: ISODate('2020-09-05T00:00:00.000Z'),
    price: 500000
  },
  {
    _id: ObjectId('69b14ef808b1463dc350eb6e'),
    vehicle_name: 'Ashok Leyland Bus',
    model: 'commercial',
    category: 'bus',
    variants: [ 'diesel' ],
    manufacturer: 'Ashok Leyland',
    performance: 8,
    timestamp: ISODate('2019-08-10T00:00:00.000Z'),
    price: 2500000
  },
```

```
  {
    _id: ObjectId('69b14ef808b1463dc350eb6f'),
    vehicle_name: 'Mahindra Bolero',
    model: 'own',
    category: 'car',
    variants: [ 'zxi', 'diesel' ],
    manufacturer: 'Mahindra',
    performance: 8,
    timestamp: ISODate('2022-04-11T00:00:00.000Z'),
    price: 900000
  },
  {
    _id: ObjectId('69b14ef808b1463dc350eb70'),
    vehicle_name: 'Volvo Container',
    model: 'commercial',
    category: 'containers',
    variants: [ 'diesel' ],
    manufacturer: 'Volvo',
    performance: 9,
    timestamp: ISODate('2021-11-19T00:00:00.000Z'),
    price: 4000000
  }
]
```

7. Write a MongoDB query to display only vehicle name and price in all the collection of the database

```
vehicles> db.two_wheelers.find({}, {bike_name:1, price:1, _id:0})
[
  { bike_name: 'Honda Shine', price: 80000 },
  { bike_name: 'TVS Apache', price: 110000 },
  { bike_name: 'Hero Splendor', price: 75000 },
  { bike_name: 'Honda Activa', price: 85000 },
  { bike_name: 'Bajaj Pulsar', price: 150000 }
]
```

```
vehicles> db.four_wheelers.find({}, {vehicle_name:1, price:1, _id:0})
[
  { vehicle_name: 'Maruti Swift', price: 650000 },
  { vehicle_name: 'Tata Ace', price: 500000 },
  { vehicle_name: 'Ashok Leyland Bus', price: 2500000 },
  { vehicle_name: 'Mahindra Bolero', price: 900000 },
  { vehicle_name: 'Volvo Container', price: 4000000 }
]
```

8. Write a MongoDB query to display two_wheelers from a particular company

```
vehicles> db.two_wheelers.find({manufacturer:"Bajaj"})
[
  {
    _id: ObjectId('69b14ee908b1463dc350eb6b'),
    bike_name: 'Bajaj Pulsar',
    model: 'gear',
    category: '200cc',
    colors_available: [ 'black', 'sport red' ],
    manufacturer: 'Bajaj',
    performance: 9,
    timestamp: ISODate('2022-07-15T00:00:00.000Z'),
    price: 150000
  }
]
```

9. Write a MongoDB query to display four_wheelers available in diesel variants

```
vehicles> db.four_wheelers.find({variants:"diesel"})
[
  {
    _id: ObjectId('69b14ef808b1463dc350eb6d'),
    vehicle_name: 'Tata Ace',
    model: 'commercial',
    category: 'mini truck',
    variants: [ 'diesel' ],
    manufacturer: 'Tata',
    performance: 7,
    timestamp: ISODate('2020-09-05T00:00:00.000Z'),
    price: 500000
  },
  {
    _id: ObjectId('69b14ef808b1463dc350eb6e'),
    vehicle_name: 'Ashok Leyland Bus',
    model: 'commercial',
    category: 'bus',
    variants: [ 'diesel' ],
    manufacturer: 'Ashok Leyland',
    performance: 8,
    timestamp: ISODate('2019-08-10T00:00:00.000Z'),
    price: 2500000
  },
```

```
  {
    _id: ObjectId('69b14ef808b1463dc350eb6f'),
    vehicle_name: 'Mahindra Bolero',
    model: 'own',
    category: 'car',
    variants: [ 'zxi', 'diesel' ],
    manufacturer: 'Mahindra',
    performance: 8,
    timestamp: ISODate('2022-04-11T00:00:00.000Z'),
    price: 900000
  },
  {
    _id: ObjectId('69b14ef808b1463dc350eb70'),
    vehicle_name: 'Volvo Container',
    model: 'commercial',
    category: 'containers',
    variants: [ 'diesel' ],
    manufacturer: 'Volvo',
    performance: 9,
    timestamp: ISODate('2021-11-19T00:00:00.000Z'),
    price: 4000000
  }
]
```

10. Write a MongoDB query to display vehicles name, category and manufacturer details whose rating is more than 5.

```
vehicles> db.two_wheelers.find(
... {performance: {$gt:5}},
... {bike_name:1, category:1, manufacturer:1, _id:0}
... )
...
[
  {
    bike_name: 'Honda Shine',
    category: '125cc',
    manufacturer: 'Honda'
  },
  { bike_name: 'TVS Apache', category: '150cc', manufacturer: 'TVS' },
  {
    bike_name: 'Hero Splendor',
    category: '100cc',
    manufacturer: 'Hero'
  },
  {
    bike_name: 'Honda Activa',
    category: '125cc',
    manufacturer: 'Honda'
  },
  {
    bike_name: 'Bajaj Pulsar',
    category: '200cc',
    manufacturer: 'Bajaj'
  }
]
```

```
vehicles> db.four_wheelers.find(
... {performance: {$gt:5}},
... {vehicle_name:1, category:1, manufacturer:1, _id:0}
... )
[
  {
    vehicle_name: 'Maruti Swift',
    category: 'car',
    manufacturer: 'Maruti'
  },
  {
    vehicle_name: 'Tata Ace',
    category: 'mini truck',
    manufacturer: 'Tata'
  },
  {
    vehicle_name: 'Ashok Leyland Bus',
    category: 'bus',
    manufacturer: 'Ashok Leyland'
  },
  {
    vehicle_name: 'Mahindra Bolero',
    category: 'car',
    manufacturer: 'Mahindra'
  },
  {
    vehicle_name: 'Volvo Container',
    category: 'containers',
    manufacturer: 'Volvo'
  }
]
```

2. Use MongoDB to implement the following DB operations for a Zoo

1. Create a database called ‘animal’ and *write* a MongoDB query to select database as ‘animal’.

```
test> use animal
switched to db animal
```

2. Write a MongoDB query to display all the databases.

```
animal> show dbs
admin                    40.00 KiB
config                   72.00 KiB
employee                120.00 KiB
local                    96.00 KiB
mongodbVSCodePlaygroundDB  72.00 KiB
vehicles                 80.00 KiB
```

3. Create a collection called ‘wild_animals’.(use capping) and Create a collection called ‘domestic_animals’.

```
animal> db.createCollection("wild_animals", { capped:true, size:500000, max:100 })
{ ok: 1 }
animal> db.createCollection("domestic_animals")
{ ok: 1 }
```

4. Add 5 wild_animal details to the collection named ‘wild_animals’. Each document consists of following fields as animal_name, nature (harm or harmless), favorite_foods (meat, rabbits, deer etc) as array, care_taker_name, life span (in years), timestamp (when the animal registered at the Zoo) and expenses.

```
animal> db.wild_animals.insertMany([{animal_name:"Lion",nature:"harm",favorite_foods:["meat","deer"],care_taker_name:"Ravi",life_span:15,timest
amp:new Date(),expenses:5000},{animal_name:"Tiger",nature:"harm",favorite_foods:["meat","rabbit"],care_taker_name:"Suresh",life_span:18,timesta
mp:new Date(),expenses:6000},{animal_name:"Elephant",nature:"harmless",favorite_foods:["grass","fruits"],care_taker_name:"Mahesh",life_span:60,
timestamp:new Date(),expenses:8000},{animal_name:"Bear",nature:"harm",favorite_foods:["fish","meat"],care_taker_name:"Ravi",life_span:20,timest
amp:new Date(),expenses:5500},{animal_name:"Deer",nature:"harmless",favorite_foods:["grass"],care_taker_name:"Kiran",
... life_span:12,timestamp:new Date(),expenses:2000}])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69b15d0974121cd1c150eb67'),
    '1': ObjectId('69b15d0974121cd1c150eb68'),
    '2': ObjectId('69b15d0974121cd1c150eb69'),
    '3': ObjectId('69b15d0974121cd1c150eb6a'),
    '4': ObjectId('69b15d0974121cd1c150eb6b')
  }
}
```

5. Add 5 domestic-animal details to the collection named ‘domestic_animals’. Each document consists of following fields as

animal_name, gender (male or female), favorite_foods (meat, rabbits, deer etc) as array, animal_petname, life span (in years), timestamp (when the animal registered at the Zoo) and expenses.

```
animal> db.domestic_animals.insertMany([{animal_name:"Dog",gender:"male",favorite_foods:["meat","biscuits"],animal_petname:"Tommy",life_span:12
,timestamp:new Date(),expenses:2000},{animal_name:"Cat",gender:"female",favorite_foods:["milk","fish"],animal_petname:"Kitty",life_span:15,time
stamp:new Date(),expenses:1500},{animal_name:"Cow",gender:"female",favorite_foods:["grass"],animal_petname:"Lakshmi",life_span:20,timestamp:new
 Date(),expenses:3000},{animal_name:"Goat",gender:"male",favorite_foods:["grass","leaves"],animal_petname:"Bunny",life_span:10,timestamp:new Da
te(),expenses:1200},{animal_name:"Rabbit",gender:"female",favorite_foods:["carrot","grass"],animal_petname:"Snowy",life_span:8,timestamp:new Da
Date(),expenses:900}])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69b15d5474121cd1c150eb6c'),
    '1': ObjectId('69b15d5474121cd1c150eb6d'),
    '2': ObjectId('69b15d5474121cd1c150eb6e'),
    '3': ObjectId('69b15d5474121cd1c150eb6f'),
    '4': ObjectId('69b15d5474121cd1c150eb70')
  }
}
```

6. Write a MongoDB query to display all documents available in wild_animals and domestic_animals.

```
animal> db.wild_animals.find()
...
[
  {
    _id: ObjectId('69b15d0974121cd1c150eb67'),
    animal_name: 'Lion',
    nature: 'harm',
    favorite_foods: [ 'meat', 'deer' ],
    care_taker_name: 'Ravi',
    life_span: 15,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 5000
  },
  {
    _id: ObjectId('69b15d0974121cd1c150eb68'),
    animal_name: 'Tiger',
    nature: 'harm',
    favorite_foods: [ 'meat', 'rabbit' ],
    care_taker_name: 'Suresh',
    life_span: 18,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 6000
  },
  {
    _id: ObjectId('69b15d0974121cd1c150eb69'),
    animal_name: 'Elephant',
    nature: 'harmless',
    favorite_foods: [ 'grass', 'fruits' ],
    care_taker_name: 'Mahesh',
    life_span: 60,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 8000
  },
```

```
  {
    _id: ObjectId('69b15d0974121cd1c150eb6a'),
    animal_name: 'Bear',
    nature: 'harm',
    favorite_foods: [ 'fish', 'meat' ],
    care_taker_name: 'Ravi',
    life_span: 20,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 5500
  },
  {
    _id: ObjectId('69b15d0974121cd1c150eb6b'),
    animal_name: 'Deer',
    nature: 'harmless',
    favorite_foods: [ 'grass' ],
    care_taker_name: 'Kiran',
    life_span: 12,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 2000
  }
]
animal> db.domestic_animals.find()
[
  {
    _id: ObjectId('69b15d5474121cd1c150eb6c'),
    animal_name: 'Dog',
    gender: 'male',
    favorite_foods: [ 'meat', 'biscuits' ],
    animal_petname: 'Tommy',
    life_span: 12,
    timestamp: ISODate('2026-03-11T12:17:24.701Z'),
    expenses: 2000
  },
```

```
{
  _id: ObjectId('69b15d5474121cd1c150eb6d'),
  animal_name: 'Cat',
  gender: 'female',
  favorite_foods: [ 'milk', 'fish' ],
  animal_petname: 'Kitty',
  life_span: 15,
  timestamp: ISODate('2026-03-11T12:17:24.701Z'),
  expenses: 1500
},
{
  _id: ObjectId('69b15d5474121cd1c150eb6e'),
  animal_name: 'Cow',
  gender: 'female',
  favorite_foods: [ 'grass' ],
  animal_petname: 'Lakshmi',
  life_span: 20,
  timestamp: ISODate('2026-03-11T12:17:24.701Z'),
  expenses: 3000
},
{
  _id: ObjectId('69b15d5474121cd1c150eb6f'),
  animal_name: 'Goat',
  gender: 'male',
  favorite_foods: [ 'grass', 'leaves' ],
  animal_petname: 'Bunny',
  life_span: 10,
  timestamp: ISODate('2026-03-11T12:17:24.701Z'),
  expenses: 1200
},
```

```
  {
    _id: ObjectId('69b15d5474121cd1c150eb70'),
    animal_name: 'Rabbit',
    gender: 'female',
    favorite_foods: [ 'carrot', 'grass' ],
    animal_petname: 'Snowy',
    life_span: 8,
    timestamp: ISODate('2026-03-11T12:17:24.701Z'),
    expenses: 900
  }
]
```

7. Write a MongoDB query to display only animal name and expenses in all the collection of the database

```
animal> db.wild_animals.find({}, {animal_name:1, expenses:1, _id:0})
[
  { animal_name: 'Lion', expenses: 5000 },
  { animal_name: 'Tiger', expenses: 6000 },
  { animal_name: 'Elephant', expenses: 8000 },
  { animal_name: 'Bear', expenses: 5500 },
  { animal_name: 'Deer', expenses: 2000 }
]
animal> db.domestic_animals.find({}, {animal_name:1, expenses:1, _id:0})
[
  { animal_name: 'Dog', expenses: 2000 },
  { animal_name: 'Cat', expenses: 1500 },
  { animal_name: 'Cow', expenses: 3000 },
  { animal_name: 'Goat', expenses: 1200 },
  { animal_name: 'Rabbit', expenses: 900 }
]
```

8. Write a MongoDB query to display domestic_animals whose life is a particular year

```
animal> db.domestic_animals.find({life_span:10})
[
  {
    _id: ObjectId('69b15d5474121cd1c150eb6f'),
    animal_name: 'Goat',
    gender: 'male',
    favorite_foods: [ 'grass', 'leaves' ],
    animal_petname: 'Bunny',
    life_span: 10,
    timestamp: ISODate('2026-03-11T12:17:24.701Z'),
    expenses: 1200
  }
]
```

9. Write a MongoDB query to display wild_animals available under a particular care_taker

```
animal> db.wild_animals.find({care_taker_name:"Ravi"})
[
  {
    _id: ObjectId('69b15d0974121cd1c150eb67'),
    animal_name: 'Lion',
    nature: 'harm',
    favorite_foods: [ 'meat', 'deer' ],
    care_taker_name: 'Ravi',
    life_span: 15,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 5000
  },
  {
    _id: ObjectId('69b15d0974121cd1c150eb6a'),
    animal_name: 'Bear',
    nature: 'harm',
    favorite_foods: [ 'fish', 'meat' ],
    care_taker_name: 'Ravi',
    life_span: 20,
    timestamp: ISODate('2026-03-11T12:16:09.348Z'),
    expenses: 5500
  }
]
```

10. Write a MongoDB query to display animal name, favorite_foods and expense details whose lifespan is more than 5 years.

```
animal> db.wild_animals.find({life_span: {$gt:5}},{animal_name:1, favorite_foods:1, expenses:1, _id:0})
[
  {
    animal_name: 'Lion',
    favorite_foods: [ 'meat', 'deer' ],
    expenses: 5000
  },
  {
    animal_name: 'Tiger',
    favorite_foods: [ 'meat', 'rabbit' ],
    expenses: 6000
  },
  {
    animal_name: 'Elephant',
    favorite_foods: [ 'grass', 'fruits' ],
    expenses: 8000
  },
  {
    animal_name: 'Bear',
    favorite_foods: [ 'fish', 'meat' ],
    expenses: 5500
  },
  { animal_name: 'Deer', favorite_foods: [ 'grass' ], expenses: 2000 }
]
```

```
animal> db.domestic_animals.find({life_span:{$gt:5}},{animal_name:1, favorite_foods:1, expenses:1, _id:0})
[
  {
    animal_name: 'Dog',
    favorite_foods: [ 'meat', 'biscuits' ],
    expenses: 2000
  },
  {
    animal_name: 'Cat',
    favorite_foods: [ 'milk', 'fish' ],
    expenses: 1500
  },
  { animal_name: 'Cow', favorite_foods: [ 'grass' ], expenses: 3000 },
  {
    animal_name: 'Goat',
    favorite_foods: [ 'grass', 'leaves' ],
    expenses: 1200
  },
  {
    animal_name: 'Rabbit',
    favorite_foods: [ 'carrot', 'grass' ],
    expenses: 900
  }
]
```