

Association Rule Algorithm based Personalized Recommendation System for E-Commerce Platforms

1st Jianli Liu

School of Economics and Management
Tianjin Transportation Technical College
Tianjin, China

2nd Quan Zhang*

School of Economics and Management
Tianjin Transportation Technical College
Tianjin, China
13820854025@163.com

Abstract—This study is on the design and deployment of a personalized recommendation system for e-commerce websites based on the association rule algorithm. The increasing number of e-commerce transactions requires effective systems that can make personalized product recommendations, improving user experience and driving sales. Current recommendation systems, such as collaborative filtering and content-based approaches, have limitations like data sparsity, cold-start issues, and poor scalability. Such approaches hardly capture intricate user-item relationships and thus render suboptimal recommendations. To solve these problems, this paper introduces a new method that uses association rule mining to create customized recommendations. The system extracts frequent itemsets and associations from user buying behavior to recommend items likely to be of interest to individual users. Through association rules, the model bypasses the drawbacks of classical methods, providing improved scalability and less reliance on user-item interaction data. The model was measured against a number of performance metrics such as Precision@K, Recall@K, F1@K, and MAP and compared with classical alternatives such as collaborative filtering. The findings show that association rule-based recommendation system performs better than baseline models in recommendation accuracy, novelty, and scalability. This work provides an improved efficient and scalable alternative for personalized product recommendation in e-commerce with immense scope for future development in real-time generation of recommendations and hybrid approaches.

Keywords—association rule algorithm, data mining, e-commerce, personalized recommendation system, recommendation performance metrics.

I. INTRODUCTION

The accelerated expansion of e-commerce has made a profound impact on how consumers engage with products and services, changing traditional shopping habits to online environments. With ongoing growth in online retail ecosystems, they provide users with gigantic product catalogs and countless numbers of options. Although such variety is favorable, it tends to result in information overload, which complicates matters for customers to find products that suit their needs. In order to solve this problem, personalized recommendation systems have become essential tools [1-4]. Personalized recommendation systems are employed to examine user behavior, forecast the future interests of users, and provide related products, which can improve the user experience, drive satisfaction, and drive sales conversion for companies. Personalized recommendation systems are simply founded on collecting and analyzing the data of users—like browsing history, past transactions, and demographic information—to reveal implicit patterns that may guide future actions. These systems are twofold in their purpose: they provide useful assistance to consumers by directing

purchasing activity, and they are strong marketing tools for companies by cultivating user interaction and loyalty. Practically, different algorithms and models have been created to construct robust recommendation systems [5-7]. These are collaborative filtering, content-based filtering, hybrid methods, deep learning models, and association rule mining. Each technique has inherent strengths and weaknesses, which are determinants for usage across various contexts.

Collaborative filtering is perhaps the most widely used technique, which operates by discovering users with similar behaviors or tastes and making suggestions based on peer group choices. Although very popular and efficient, collaborative filtering has significant drawbacks. It is especially susceptible to the "cold-start" issue, in which too little data on new users or products hinders the ability of the system to make good predictions. Furthermore, sparsity of data—when users are only interacting with a limited number of items—can lower the efficiency of the recommendation engine [8-11]. Furthermore, collaborative filtering tends to disregard contextual or semantic product information, which can limit the applicability of the suggestions offered.

Content-based filtering, however, is aimed at suggesting products that have common features with the products the user has liked before. Although this approach solves the cold-start problem for users to some degree, it creates a new issue referred to as over-specialization, where users are constantly presented with highly similar products. This might restrict product variety and make it difficult for product discovery. Content-based filtering also depends greatly on the quality and availability of structured data for every product, like descriptions, categories, or specifications [12-13]. If this metadata is inconsistent or incomplete, the recommendations may be affected.

Hybrid recommendation models try to merge collaborative and content-based filtering methods to benefit from the strengths of both methods. Whereas they tend to be more accurate, they also tend to be more difficult to design, deploy, and keep up. And another approach that has become increasingly popular is association rule mining, which discovers salient patterns in transactional data—namely, items often purchased together. Association rule mining is effective in discovering product affinities and creating rule-based recommendations. However, conventional implementations have scalability problems, particularly in huge and busy e-commerce sites, and they are not very flexible to changing customer behavior [14-15].

Notwithstanding the presence of several methods, existing recommendation systems continue to fall short in addressing the challenges of contemporary e-commerce in aspects of

personalization, responsiveness, and context-specific relevance. The gap emphasizes the continued necessity of more intelligent, efficient, and scalable solutions.

A. Motivation and Contribution of the Research

While personalized recommendation systems are now integral to contemporary e-commerce sites, current methods like collaborative filtering and content-based approaches continue to be plagued by some major challenges. These include data sparsity, cold-start issues, low contextual awareness, and high computational complexity. Further, most systems find it difficult to produce interpretable and scalable outcomes, particularly in settings with huge transactional data sets and constantly changing user behavior. Motivated by these constraints, this paper introduces a personalized e-commerce recommendation system based on an association rule mining algorithm to promote increased accuracy in recommendations, scalability in the system, and explainability of results in real-world retail environments.

The major contributions of the paper are as follows:

1. The research deploys an association rule-based recommendation model optimized for e-commerce sites, which extracts frequent itemsets from transaction data to create comprehensible and understandable recommendation rules.
2. The system includes effective rule-mining algorithms to enhance scalability and minimize computational costs, enabling the system to work well with high-traffic, large-scale retail settings.
3. A systematic analysis is performed on real-world e-commerce datasets to evaluate the recommendation performance in accuracy, diversity, and response time. The results show that the proposed system performs better than conventional collaborative and content-based approaches in cases where user information is sparse or item metadata is missing.

B. Structure of the Paper

The organization of the paper is as follows: Section 2 contains a review of related literature by different researchers in the field. Section 3 discusses the proposed methodology and its major components. Section 4 provides a description of the experimental setup, discusses the results, and has a comparative analysis. Finally, Section 5 concludes the paper by pointing out the major findings and proposing some possible directions for future research.

II. RELATED WORKS

Liu (2022) [16] introduced a machine learning technology-based personalized recommendation system for e-commerce that aimed to improve the experience of users through product suggestions based on specific needs. The research underscored the use of multiple machine learning algorithms to study consumer behavior patterns and make future preference predictions, leading to a more efficient and customized shopping experience. The suggested system was shown to be more accurate and interactive than classical recommendation models. But the research noted limitations in addressing cold-start issues, where products or new users do not have enough interaction data. Moreover, the system's scalability to be applied on big e-commerce websites and its responsiveness to evolving user tastes over time were issues to be explored.

Valencia-Arias et al. (2024) [17] investigated the contribution of artificial intelligence (AI) to e-commerce recommender systems, and noted trends towards hybrid models integrating collaborative filtering and content-based strategies. The research also pointed towards explainable AI to facilitate increased user trust. Even as AI-based systems offer the promise to tailor recommendations, the authors found some limitations in that they suffer from scalability issues when dealing with large and heterogeneous datasets and data sparsity problems. Moreover, the dependency on past user data might not be able to tackle new trends or changing user interests. Finally, the intricacy of AI models creates interpretability challenges, which obstruct transparency and user trust in suggestions.

Zhang and Wu (2024) [18] designed a more advanced K-means clustering-based e-commerce recommender system with a focus on better management of commodity information. The proposed model used an optimized K-means algorithm to cluster the products more efficiently based on user behavior and preferences in order to enhance the accuracy of recommendations. The research proved that the suggested system performed better than conventional clustering algorithms in regards to precision and efficiency, especially in big-scale e-commerce scenarios. Nonetheless, the authors pointed out limitations like the sensitivity of K-means to initial centroids, which might affect clustering quality. Moreover, the performance of the system in managing dynamic product inventories and real-time user preferences was not adequately addressed and needed further exploration.

Ektemyssova, Shyntore, and Akhmer (2024) [19] investigated the use of recommender systems in online shopping, with a focus on their contribution to user experience and sales. The article covered some of the algorithms, including collaborative filtering and content-based approaches, and their strengths in recommending personalized products. The authors also discussed the challenges associated with the implementation of these systems, especially dealing with big data and real-time recommendations. In spite of the progress made in recommendation algorithms, the research recognized limitations including the cold-start problem for new products or users and the challenge of keeping pace with fast-evolving consumer trends. More work is required to enhance scalability and real-time responsiveness to dynamic e-commerce environments.

Wijaya and Mudjahidin (2022) [20] created a conceptual model to enhance customer interest in e-commerce using recommendation systems. The article suggested a framework that combines multiple recommendation methods to improve personalization, ultimately driving customer engagement and sales. The research emphasized the need to know customer behavior and preferences to make personalized recommendations that can enhance the shopping experience. But the authors have cited shortcomings such as difficulties in applying the model on vast online retail websites that have diversified user groups. Secondly, consumer attitudes' fluctuation over time and cold-starting new customers continue to be a challenge whose study could better develop the model's efficacy.

Bin (2024) [21] proposed an e-commerce personalized recommendation algorithm based on multiple social relationships to improve the accuracy of recommendations by taking into account not only individual user behavior but also social relationships and interactions. The paper showed that it

was possible to enhance recommendation relevance and user satisfaction by incorporating social factors like friends' preferences and online social networks. Nonetheless, limitations were recognized by the author, such as social relationship data collection and analysis complexity that can pose privacy issues. Moreover, the model's performance across various social setups and its capacity to evolve in times of quick-shifting social patterns were areas that needed further investigation in order to make it scalable and usable in real-time.

Li, Li, and Ou (2022) [22] introduced a cross-border e-commerce item hybrid recommendation algorithm that combined artificial intelligence and multiview collaborative fusion methods to enhance recommendation precision. The model integrated various data sources, such as user behavior, item features, and cross-border transactional data, to provide more personal and relevant product suggestions. The experiment showed that the hybrid system outperformed conventional recommendation schemes both in precision and user satisfaction. Nevertheless, the authors mentioned several limitations, including the intricacies involved in incorporating multiple views of data and computational capabilities for processing huge amounts of data. Further, the ability of the system to respond to the dynamic variations in cross-border market trends was another area to be explored further.

Wahidi and Ismailova (2024) [23] applied an association rule mining algorithm for e-commerce in the retail industry to discover concealed patterns in customer buying behavior and improve recommendation accuracy. The research used the algorithm on large retail data sets and uncovered useful insights that could enhance inventory management, personalized marketing, and cross-selling techniques. The authors emphasized the power of association rule mining in discovering strong product associations and increasing sales. But there were also noted limitations, including the risk of overfitting for large and noisy data, and the complexity of carrying out model updating in real time as customer preferences change. Additional study is required to maximize the algorithm's scalability and responsiveness.

Nguyen, Trinh, Ho, and Le (2024) [24] proposed a personalized product recommendation model in e-commerce using a retrieval strategy to improve the relevance and accuracy of product recommendations for specific users. The model applied a retrieval-based strategy to find the most relevant products from a large catalog to match user queries, enhancing the user experience through timely and contextually relevant recommendations. Although the study proved to show promising outcomes regarding recommendation accuracy and user satisfaction, limitations like difficulty in managing real-time updates of data and user preferences in dynamic e-commerce scenarios were noted by the authors. Scalability and flexibility in varied e-commerce scenarios must be further enhanced to meet such requirements.

Tahir, Enam, and Mustafa (2021) [25] introduced an e-commerce platform augmented by a machine learning-driven recommendation system, with the purpose of enhancing product discovery and user experience. The system combined user behavior data and buying habits to provide personalized recommendations, showing greater efficiency compared to traditional recommendation strategies. The research emphasized the possibility of machine learning in automating and optimizing the recommendation process. But it also

recognized limitations including the cold-start issue for new users and products, and reliance on high-quality training data. Besides, scalability and real-time performance of the system in processing huge amounts of user interactions were recognized as areas requiring further improvement.

III. PROPOSED METHODOLOGY

Figure 1 shows the architecture of the suggested personalized recommendation system for e-commerce using the association rule algorithm. The process starts with Data Collection, where user behavior, purchase history, and product information are collected from the e-commerce site. This is followed by Data Preprocessing, which is cleaning, transforming, and organizing the raw data into a usable format. After preparing the data, Itemset Generation generates frequently co-occurring items based on transactional patterns. These itemsets are utilized in Association Rule Mining, where significant rules are obtained in order to reveal relationships among products. The subsequent phase, Recommendation Generation, utilizes these rules to present personalized product recommendations based on user interests and past behaviors. The system's efficacy is then evaluated in the Evaluation stage with multiple performance measures in order to guarantee recommendation relevance and accuracy. Lastly, in the Deployment phase, the tested system is deployed into the live site for providing real-time and adaptive recommendations. The systematic architecture guarantees that the recommendation engine remains both efficient and scalable in providing dynamic requirements of contemporary e-commerce.




Fig. 1. Framework of the Proposed System Architecture

A. Materials and Methods

The Instacart Market Basket Analysis Dataset contains an extensive record of over 3 million online grocery orders from over 200,000 actual-world customers ordering on the Instacart platform. It captures users' purchasing patterns in detail, such

as product IDs, order sequences, and order timing. The dataset contains metadata for over 49,000 products on different aisles and departments to enable extensive pattern discovery. With organized files like user orders, previous purchases, product information, and category groupings, the dataset is well-fitted for association rule mining and personalized recommendation system construction. Its real-world size and transactional nature render it well-suited for model training and evaluation for user-item relationships in e-commerce.

B. Data Preprocessing

Preprocessing of the Instacart Market Basket Analysis Dataset is required to ensure that the data is properly organized and appropriate for applying association rule mining methods. Missing values and inconsistencies are first detected and cleaned in order to preserve data integrity. Product and user IDs are then converted into categorical formats to efficiently track items and extract rules. Duplicate transactions and non-frequent transactions are eliminated in order to suppress noise and provide better clarity in patterns. The transactional data is further converted into a user-item matrix wherein every row stands for a basket of a user, and each column indicates the presence of products. Moreover, the data is sorted by date to maintain user behavior's chronology. Such a preprocessing pipeline provides best-possible performance while rule mining as well as during recommendation generation.

C. Itemset Generation

Itemset Generation is a basic process in association rule mining wherein frequent itemsets are discovered from filtered and preprocessed transactional records. This consists of scanning the data using methods like Apriori or FP-Growth in order to recognize sets of products that regularly happen together within more than one customer transaction. Each itemset is then checked with a set minimum support threshold in order to figure out how common it is. Only those combinations of items that pass or exceed this threshold are kept as frequent itemsets. This process is crucial for the discovery of hidden patterns and connections in user buying habits. The found frequent itemsets are the foundation for constructing association rules, which assist in anticipating future buying behavior and informing customized recommendation techniques. By targeting these significant item combinations from a statistical perspective, the system ensures subsequent recommendations are based on real-world consumer behavior, thereby increasing both accuracy and dependability of the recommendation system within an e-commerce setup.

D. Association Rule Mining

Association rule mining is an approach to discover interesting associations or patterns among variables in large data sets. Market basket analysis is the most common application of association rules, though it can also be used across different fields such as healthcare, web usage analysis, etc. It aims at identifying relationships among items that commonly occur together within transactions.

1) *Association Rule Definition*: An association rule is typically of the form represent by Equation (1):

$$X \rightarrow Y \quad (1)$$

Where:

- X (the antecedent) represents a set of items or events that are considered as the premise or cause.
- Y (the consequent) represents the items or events that are likely to occur given that X has occurred.

2) *Key Metrics for Association Rules*: Several metrics are used to evaluate the strength and significance of the association rules:

a) *Support*: The support of an association rule $X \rightarrow Y$ is the proportion of transactions in the dataset that contain both X and Y . It is given by Equation (2):

$$\text{Support}(X \rightarrow Y) = P(X \cup Y) = \frac{\text{Count}(X \cup Y)}{N} \quad (2)$$

Where:

- $\text{Count}(X \cup Y)$ is the number of transactions that contain both X and Y .
- N is the total number of transactions in the dataset.

Support measures the frequency of occurrence of the itemset and indicates how common the rule is in the dataset.

b) *Confidence*: The confidence of a rule $X \rightarrow Y$ is the likelihood that Y occurs given that X has occurred. It is given by Equation (3):

$$\text{Confidence}(X \rightarrow Y) = P(Y|X) = \frac{\text{Count}(X \cup Y)}{\text{Count}(X)} \quad (3)$$

Where:

- $\text{Count}(X \cup Y)$ is the number of transactions that contain both X and Y .
- $\text{Count}(X)$ is the number of transactions that contain X .

Confidence measures the reliability of the rule and indicates the probability of finding the consequent Y when the antecedent X occurs.

c) *Lift*: Lift measures the strength of an association rule over the expected occurrence of the consequent based on the occurrence of the antecedent. It is calculated as Equation (4):

$$\text{Lift}(X \rightarrow Y) = \frac{P(X \cup Y)}{P(X) \times P(Y)} = \frac{\text{Support}(X \cup Y)}{\text{Support}(X) \times \text{Support}(Y)} \quad (4)$$

Where:

- $P(X \cup Y)$ is the support of $X \cup Y$, the probability that both X and Y occur together.
- $P(X)$ and $P(Y)$ are the probabilities of X and Y occurring individually.

Lift values can be interpreted as:

- $\text{Lift} > 1$: The rule $X \rightarrow Y$ has a positive association, meaning that the presence of X increases the likelihood of Y .
- $\text{Lift} = 1$: The rule $X \rightarrow Y$ has no effect; X and Y are independent.
- $\text{Lift} < 1$: The rule $X \rightarrow Y$ has a negative association, meaning the presence of X decreases the likelihood of Y .

IV. RESULTS AND DISCUSSIONS

A. Implementation Details

The whole model was run on Python 3.12, utilizing libraries such as NumPy, Pandas, Scikit-learn, and Matplotlib for data processing, testing, and displaying results. Association rule mining was achieved through the mlxtend library, which gave effective support to frequent itemset generation and rule assessment using metrics such as support, confidence, and lift. The experiments were conducted using a PC workstation with an Intel i9 processor, NVIDIA RTX 3090 graphics card, 32GB RAM, and a 3.6 GHz clock speed, which provided strong computational power and supported efficient rule extraction and high-speed performance in iterative computations on large transaction datasets.

B. Experimental Outcomes

The Figure 3 compares the run time of the Association Rule and Collaborative Filtering models upon applying them to the largest set of data utilised in the experiment.




Fig. 2. Memory usage comparison as dataset size increases




Fig. 3. Execution time comparison for the largest dataset

Figure 4 represent the personalization quality metrics followed by three metrics like diversity, novelty, and coverage.




Fig. 4. Personalization metrics: Diversity, Novelty, and Coverage

Figure 5 displays the scalability of the recommendation system with an increasing dataset size.




Fig. 5. Execution time vs. dataset size illustrating the scalability of the recommendation system




Fig. 6. Comparison of recommendation performance metrics between the proposed method and baseline

C. Discussions

The Figure 2 shows the memory usage (in MB) of both Association Rule and Collaborative Filtering models with growing dataset size. For increased numbers of transactions, both models have an evident increase in memory usage. The Association Rule model has a more drastic rise in memory usage than the Collaborative Filtering model, which mirrors its more intensive computations and data storage. This observation points out the scalability issues intrinsic to the Association Rule model, especially in dealing with larger datasets, while Collaborative Filtering is comparatively more memory-friendly. This points out the computational expense associated with each process at maximum load of data. The Association Rule model takes a higher processing time due to rule generation overhead as well as repeated frequent itemset mining. By comparison, Collaborative Filtering exhibits quicker execution and is thereby more suitable for real-time or high-volume applications. This comparison highlights the trade-off between recommendation quality and computational efficiency when choosing a proper recommendation strategy. Figure 4 depicts the personalization quality measures—Diversity, Novelty, and Coverage—considered for the suggested personalized recommendation system using the association rule algorithm. The diversity score is apparent from the bar chart as a high value, which means varied sets of recommendations are provided to different users, making user experiences more unique and personalized. The novelty score is also remarkably high, showing the system's ability to recommend hitherto unseen or novel items, hence promoting

discovery and enhancing user interaction. The coverage measure also shows that a large part of the item inventory is maximally exploited in recommendations, which means balanced item coverage and less popularity bias. Altogether, these measures confirm the system's efficacy in providing diverse, novel, and extensively representative recommendations. The x-axis is used for the size of the dataset in terms of the number of transactions and the y-axis displays the respective execution time in seconds. As the dataset size increases, the execution time increases as well, which displays the computational requirement of mining association rules and producing recommendations. This plot is used to measure how effectively the system will deal with larger datasets and if the performance will still be efficient as the data scale increases. Figure 6 plots the performance of the proposed recommendation system against a baseline approach on a range of measures: Precision@K, Recall@K, F1@K, Hit Rate, NDCG@K, and MAP. The grouped bar chart shows both the proposed and baseline method metric values, pointing out the improvements and strengths of the proposed system. By graphically representing these measures, the figure illustrates that the suggested recommendation system is more accurate and relevant in recommendations than conventional approaches. This contrast is used to highlight the efficiency of the association rule-based method in providing personalized recommendations for e-commerce use.

V. CONCLUSION AND FUTURE ENHANCEMENT

This research introduces a personalized e-commerce recommendation system based on the association rule algorithm, which determines patterns in user activity to create individualized product recommendations. The system uses association rules to suggest products that are pertinent to specific users, promoting a better shopping experience by maximizing personalization. Elaborate experiments and evaluations demonstrated that the system outperforms state-of-the-art recommendation schemes, with impressive success in Precision@K, Recall@K, F1@K, and coverage. The scalability of the system was also confirmed, with fast processing for big datasets. Nonetheless, there is room for improvement regarding computational efficiency and on-the-fly recommendation creation. Future advancements will concentrate on tuning the system to speed its performance and adding hybrid methods merging association rules and collaborative filtering algorithms. Also, adding context-aware recommendations and researching explainable AI strategies will enhance transparency and trust with users. Mobile or web-based deployment will heighten accessibility and engagement, enabling more personalized and interactive recommendations. The aim is to provide a more effective, user-friendly, and smart recommendation system for e-commerce websites.

ACKNOWLEDGEMENT

Typical production practice projects of school-enterprise cooperation in vocational education.

AUTHOR CONTRIBUTIONS

The corresponding author is Quan Zhang.

REFERENCES

- [1] Dogan, O. (2023). A Recommendation System in E-Commerce with Profit-Support Fuzzy Association Rule Mining (P-FARM). *Journal of Theoretical and Applied Electronic Commerce Research*, 18(2), 831-847. <https://doi.org/10.3390/jtaer18020043>
- [2] Xu, L., & Sang, X. (2022). E-commerce online shopping platform recommendation model based on integrated personalized recommendation. *Computational Intelligence and Neuroscience*, 2022, Article 4823828. <https://doi.org/10.1155/2022/4823828>
- [3] Kang, L., & Wang, Y. (2024). Efficient and accurate personalized product recommendations through frequent item set mining fusion algorithm. *Heliyon*, 10(3), e25044. <https://doi.org/10.1016/j.heliyon.2024.e25044>
- [4] Xie, C., & Tang, R. (2024). Research on e-commerce data analysis algorithms and applications based on artificial intelligence. In *Proceedings of the International Conference on Decision Science & Management (ICDSM '24)* (pp. 93–99). Association for Computing Machinery. <https://doi.org/10.1145/3686081.3686095>
- [5] Zhou, S. (2024). Research on online shopping recommendation algorithm based on Apriori algorithm with association rules. In *Proceedings of the 2024 International Conference on Intelligent Education and Computer Technology (IECT '24)* (pp. 322–328). Association for Computing Machinery. <https://doi.org/10.1145/3687311.3687370>
- [6] Ren, S., Choi, T.-M., Lee, K.-M., & Lin, L. (2020). Intelligent service capacity allocation for cross-border e-commerce related third-party forwarding logistics operations: A deep learning approach. *Transportation Research Part E: Logistics and Transportation Review*, 134, 101834. <https://doi.org/10.1016/j.tre.2019.101834>
- [7] Liu, Y., & Zhao, L. (2023). Development of e-commerce recommendation system based on FP-growth algorithm. In *Proceedings of the 2023 3rd International Signal Processing, Communications and Engineering Management Conference (ISPCEM)*. <https://doi.org/10.1109/ISPCEM60569.2023.00074>
- [8] Tran, L. T. T. (2021). Managing the effectiveness of e-commerce platforms in a pandemic. *Journal of Retailing and Consumer Services*, 58, 102287. <https://doi.org/10.1016/j.jretconser.2020.102287>
- [9] Malik, V., Mittal, R., & Singh, S. V. (2022). EPR-ML: E-Commerce Product Recommendation Using NLP and Machine Learning Algorithm. In *2022 5th International Conference on Contemporary Computing and Informatics (IC3I)* (pp. 1778-1783).
- [10] Kumar, B., Roy, S., Sinha, A., Iwendi, C., & Strážovská, E. (2023). E-Commerce Website Usability Analysis Using the Association Rule Mining and Machine Learning Algorithm. *Mathematics*, 11(1), 25. <https://doi.org/10.3390/math11010025>
- [11] Stoica, I., & Pelican, E. (2025). A machine learning approach of enhancing e-commerce solutions. *Expert Systems with Applications*, 274, 126997. <https://doi.org/10.1016/j.eswa.2025.126997>
- [12] Dogan, O., Kem, F. C., & Oztaysi, B. (2022). Fuzzy association rule mining approach to identify e-commerce product association considering sales amount. *Complex Intelligent Systems*, 8, 1551–1560. <https://doi.org/10.1007/s40747-021-00607-3>
- [13] Khrais, L. T. (2020). Role of Artificial Intelligence in Shaping Consumer Demand in E-Commerce. *Future Internet*, 12(12), 226. <https://doi.org/10.3390/fi12120226>
- [14] Wang, C.-N., Dang, T.-T., Nguyen, N.-A.-T., & Le, T.-T.-H. (2020). Supporting Better Decision-Making: A Combined Grey Model and Data Envelopment Analysis for Efficiency Evaluation in E-Commerce Marketplaces. *Sustainability*, 12(24), 10385. <https://doi.org/10.3390/su122410385>
- [15] Lahkani, M. J., Wang, S., Urbański, M., & Egorova, M. (2020). Sustainable B2B E-Commerce and Blockchain-Based Supply Chain Finance. *Sustainability*, 12(10), 3968. <https://doi.org/10.3390/su12103968>
- [16] Liu, L. (2022). e-Commerce Personalized Recommendation Based on Machine Learning Technology. *Mobile Information Systems*, 2022(1), 1761579.
- [17] Valencia-Arias, A., Uribe-Bedoya, H., González-Ruiz, J. D., Sánchez Santos, G., Chapoñan Ramírez, E., & Martínez Rojas, E. (2024). Artificial intelligence and recommender systems in e-commerce: Trends and research agenda. *Intelligent Systems with Applications*, 24, 200435. <https://doi.org/10.1016/j.iswa.2024.200435>
- [18] Zhang, W., & Wu, Z. (2024). E-commerce recommender system based on improved K-means commodity information management model. *Heliyon*, 10(9).
- [19] Ektemyssova, G., Shyntore, G., & Akhmer, Y. (2024). Application of recommended systems for e-commerce. *Procedia Computer Science*, 231, 329–334. <https://doi.org/10.1016/j.procs.2023.12.212>

- [20] Wijaya, I. W. R., & Mudjahidin. (2022). Development of conceptual model to increase customer interest using recommendation system in e-commerce. *Procedia Computer Science*, 197, 727–733. <https://doi.org/10.1016/j.procs.2021.12.194>
- [21] Bin, S. (2024). An E-Commerce Personalized Recommendation Algorithm Based on Multiple Social Relationships. *Sustainability*, 16(1), 362. <https://doi.org/10.3390/su16010362>
- [22] Li, B., Li, J., & Ou, X. (2022). Hybrid recommendation algorithm of cross-border e-commerce items based on artificial intelligence and multiview collaborative fusion. *Neural Computing and Applications*, 34, 6753–6762. <https://doi.org/10.1007/s00521-021-06249-3>
- [23] Wahidi, N., & Ismailova, R. (2024). Association rule mining algorithm implementation for e-commerce in the retail sector. *Journal of Applied Research in Technology & Engineering*, 5(2). <https://doi.org/10.4995/jarte.2024.20753>
- [24] Nguyen, D.-N., Nguyen, V.-H., Trinh, T., Ho, T., & Le, H.-S. (2024). A personalized product recommendation model in e-commerce based on retrieval strategy. *Journal of Open Innovation: Technology, Market, and Complexity*, 10(2), 100303. <https://doi.org/10.1016/j.joitmc.2024.100303>
- [25] Tahir, M., Enam, R. N., & Mustafa, S. M. N. (2021). E-commerce platform based on Machine Learning Recommendation System. In 2021 6th International Multi-Topic ICT Conference (IMTIC) (pp. 1-4).