Quantum Traffic Gridlock — Technical Report

Team: Prakhar Keshniya, Harsh Sahu, Pranav Keshniya · Code, outputs and run instructions: https://github.com/Harshu3605/quantum-traffic-gridlock-qaoa

1. Traffic model and official cost

Decision bits are x = (A1..A4, B1..B4), with 1 = NS green and 0 = EW green. For each approach k (node n, direction d), the queue follows the PS recursion: $q_{k,t} = q_{k,t-1} + a_{k,t} + u_{k,t} - \min(c, q_{k,t-1} + a_{k,t} + u_{k,t})\cdot g_{k,t}$. Here g is the green indicator: x for NS and 1−x for EW. The term u is the transfer, and it is non-zero only for B's linked approach: $u_{t+1} = \lfloor f\cdot s^{A}_t + ½ \rfloor$, where s^{A}_t is the number of vehicles A's linked approach serves in slot t. The cost is $C(x) = \Sigma_t \Sigma_k [q_{k,t} + w_o\cdot\max(0, q_{k,t} - \text{storage})] + w_s\cdot\#\text{switches}$. Every cost in this report is computed by the organisers' unmodified `official/scorer.py`, which reproduces 116, 146, 237 and 92.5. Our own simulator matches it exactly: on all 256 schedules for 40 random scenarios, including the decimal half-up transfer rounding.

2. QUBO derivation (scenario-independent modelling rule)

Exact decomposition. $C(x) = \Sigma_k D_k(x_{S_k}) + w_s \Sigma_{i,t} (x_{i,t} \oplus x_{i,t-1})$. Each per-approach queue cost D_k depends only on its *support* S_k:

- For three of the four approach groups, S_k is the four bits of the approach's own intersection.
- For B's linked approach, S_k also includes A's four bits, because its inflow is A's linked departures. This dependence carries the A→B coordination.

The decomposition is verified exactly on all 256 schedules (`test_decomposition_is_exact`).

Switch term. This term is already quadratic: $x_t \oplus x_{t-1} = x_t + x_{t-1} - 2x_t\, x_{t-1}$. It is encoded exactly.

Queue terms. D_k is not quadratic. The min and max operations inside the Lindley recursion create interactions of order up to $|S_k|$. We replace each D_k by its *L2-optimal quadratic surrogate on its own support*. In spin variables s = 1−2x, $D_k = \Sigma_{A\subseteq S_k} \hat{c}_A \Pi_{i\in A} s_i$ (Walsh–Fourier expansion), and we keep the terms with $|A| \le 2$. Under the uniform measure, this truncation is the least-squares best quadratic, so no schedule is preferred in the fit. The coefficients $\hat{c}_A = 2^{-|S_k|} \Sigma\, D_k(s)\cdot\Pi\, s_i$ are computed by running the single-approach queue recursion over that approach's support cube. Linearity then gives the full QUBO: $Q = \Sigma_k \text{proj}_2(D_k)$ + exact switch terms.

Integrity. The rule is identical for every scenario. It uses only traffic dynamics: arrivals, capacity, storage, transfer and weights. It never ranks schedules, never locates the optimum, and never encodes a target answer, and enumeration of the official cost appears only in the benchmarks. There is one honest caveat. Because the support of B's linked approach is all 8 bits, computing that one approach's projection touches all 256 assignments of that single approach's queue. Summed over approaches, the result equals the global order-2 Walsh truncation of C. It is still a fixed approximation rule that has no knowledge of the minimizer.

Size. 8 binary variables, 8 qubits, no auxiliary variables. The fully linked approach makes the coupling graph complete, with 28 ZZ terms. The Ising form uses x = (1−z)/2.

Penalties. Overflow is soft, as specified, with weight w_o. A multiplier λ_o on the overflow part is kept as an ablation knob, default 1, so the QUBO matches the official weights.

3. QAOA design

- **Ansatz.** $|+\rangle^{8}$, then p layers of $e^{-i\gamma H_C}$ (RZZ and RZ gates) followed by an RX(2β) mixer. Default p = 4, the maximum allowed. Training normalises the cost to zero mean and unit standard deviation over the cube, so the γ ranges are scenario-independent. The physical angles γ/σ are bound into the exported circuit.
- **Training.** Exact numpy statevector for 256 amplitudes. The objective is the expected QUBO energy, because lift is a mean-cost metric.
- **Initialisation (INTERP).** Score 7 linear-ramp (TQA) starts at p = 1. Then for each depth d = 1…p, run COBYLA and linearly interpolate the angles to depth d+1. All of this shares a hard **300-evaluation** budget that the code enforces. The seed adds a small jitter to the starting angles.
- **Sampling and consistency.** Final sampling uses Qiskit `StatevectorSampler(seed)` with exactly 4,096 shots. We check that the Qiskit statevector of the bound circuit matches the trained numpy distribution (TVD ≈ 1e−15). A test also re-imports `circuit.qasm` and checks it against `counts.json`.
- **Resources.** One run takes about 0.4–2 s on CPU, far below the 10-minute limit.

4. Results (5 seeds: 0–4; costs are official costs)

	R	H (official)

(1) best alternating	116.0 (1010|1010)	261.0 (1010|0101)
(2) greedy (larger queue, ties NS)	92.5 (0111|1001)	244.0 (1010|0111)
(3) exact optimum C*	**72.0** (1110|1010)	**234.0** (1000|0111)
(4) uniform-random mean C_rand	151.25	300.28
(5) QUBO exact minimizer (surrogate ceiling)	72.0, regret 0 %	236.0, regret 0.9 %
corr(QUBO, official) over 256 schedules	0.995	0.993
(6) raw QAOA E_Q (mean over seeds)	88.2	242.3
lift: mean / **worst seed**	0.796 / **0.792**	0.875 / **0.873**
elite enrichment (13 best)	12.55×	16.95×
P(optimal schedule) per shot	8.3 %	11.5 %
hybrid QAOA + bit-flip local search (labelled, not raw)	72.0	234.0

On both scenarios the mean cost of the raw QAOA samples (E_Q) beats the alternating baseline. It also beats the single greedy schedule: 88.2 vs 92.5 on R, and 242.3 vs 244 on H. About 8 % (R) and 11.5 % (H) of shots hit the exact optimum. The most frequent H sample, 1001|0111 (written to `schedule.json` as the primary schedule), costs 235, which is 0.4 % above C*.

Generalisation. 30 random scenarios from the published hidden ranges, with a fixed generator seed of 2026; files are in `outputs/experiments/random_scenarios`.

- QUBO regret: mean 0.9 %, at most 5 % on 93 % of scenarios, and exactly zero on 60 %.
- Worst case: 10.6 % (rand17). The next worst is 8.0 %.
- Lift: mean 0.84. The worst seed's lift has a median of 0.85 and a minimum of 0.64.
- Enrichment: mean 12.3×.
- Greedy's mean regret is 5.4 %.
- The labelled hybrid reached C* on all 30 scenarios for every seed.

Ablations (5 seeds each; worst-seed lift shown).

p	1	2	3	4
R, INTERP	0.613	0.729	0.772	**0.792**
R, linear ramp only	0.613	0.687	0.692	0.515
R, random init	0.613	0.593	0.591	0.597
H, INTERP	0.427	0.663	0.837	**0.873**
H, linear ramp only	0.427	0.588	0.588	0.374
H, random init	0.019	0.422	0.454	0.721

Only INTERP improves steadily with depth. Without layer-wise warm starts, COBYLA with 300 evaluations gets stuck at $p \geq 3$. The overflow multiplier $\lambda_o \in \{0.5, 1, 1.5, 2\}$ changes lift by less than 0.02. On H, $\lambda_o = 0.5$ happens to lower the regret from 0.9 % to 0.4 %. We kept $\lambda_o = 1$ because tuning it on the evaluation scenario would be overfitting.

5. Limitations (honest)

- The quadratic surrogate is approximate. Regret can reach about 10 % when queue saturation creates strong higher-order interactions. A fix with auxiliary slack variables (≤ 8 spare qubits) is a possible extension that we did not implement.
- Training uses the exact noiseless statevector, which is legitimate in simulation because training shots are optional. We performed no noise or hardware study.
- At 8 qubits, enumeration is trivial, so we claim no quantum advantage. QAOA here is a sampler whose distribution is strongly concentrated on low-cost schedules: about 12× elite enrichment.
- R and H use the organisers' official files. The unseen scenario S runs with the same unchanged code.