SARBLOH: Structured Geometric Perception and Speculative Code Execution for Autonomous ARC-AGI-3 Agents

Harsidak Singh Banwait
Independent Researcher
harsidak.singh.banwait.13@gmail.com

Abstract

ARC-AGI-3 evaluates fluid intelligence of AI or AI based systems by utlizing interactive game and how few actions it needs, relative to a human, to master such unknown environments AI has never seen. Such enviornments which are unknown to LLM, understanding or perception becomes crucial. While LLMs can learn to play games with a few-shot prompt, they struggle with spatial grounding. When SOTA models are shown raw 64×64 integer grids, it burn hundreds of actions rediscovering mechanics a human grasps at a glance. We present SARBLOH AGENT, an agent built around a deterministic host-side perception engine and a code-as-action runtime. In $\approx$35 ms per frame, the engine produces three aligned views: an object-centric state with identity tracking across steps, a briefing that separates verifiable geometric invariants from affordance hypotheses paired with one-action tests, and an annotated spatial map. The agent writes Python world models and action plans over these views, supported by an append-only context that reuses 98.4% of the prefix cache and a priority scheduler that shares one GPU across 25 concurrent games. In a controlled rubric, structured perception raises affordance identification from 3/28 to 25/28 while cutting input tokens by 89.4%. On one RTX PRO 6000, SARBLOH AGENT clears 143 of 183 public levels in 8.2 hours and scores 17.01 on the hidden Kaggle evaluation.

Code: https://github.com/Harsidak/SARBLOH

1 Introduction

Human visual cognition exhibits remarkable inductive fluidity when dealing with novel interactive environments. Observation of an unfamiliar task for less than a hundred milliseconds allows humans to absorb fundamental physical and operational elements. Identifying agent embodiment, understanding spatial boundaries, recognizing temporal and resource gauges, and deducing final goal affordances can occur without the need for explicit complex manuals (Spelke and Kinzler 2007). While these abstractions are inductive and subject to revision, they provide the necessary structural scaffolding that enables humans to solve complex tasks.

The ARC-AGI-3 benchmark (ARC Prize Foundation 2026a) was established to evaluate this core facet of artificial general intelligence: the efficiency of novel skill acquisition under strict epistemic uncertainty (Chollet 2019). Unlike static visual reasoning benchmarks, ARC-AGI-3 requires an agent to operate in a sequential environment that includes an undisclosed series of compositional levels. In this kind of environment, the agent receives no natural language directives, action semantic descriptions, or termination conditions. Furthermore, the benchmark evaluates performance through Relative Human Action Efficiency (RHAE), where the earned score scales quadratically with the ratio of human baseline actions to agent actions. Consequently, each exploratory or misdirected action incurred by an agent penalizes its final score quadratically, rendering brute-force trial-and-error catastrophically inefficient.

When multimodal models are deployed in these environments, their primary failure mode is visual grounding and spatial representation. When an environment frame is serialized into an unparsed matrix of discrete integer tokens, a state-of-the-art (SOTA) reasoning model has to use tens of thousands of tokens to reconstruct the dynamics of these environments—such as connectivity, containment, and coordinate alignment. In preliminary controlled investigations (Section 3), exposing a frontier model to raw 64×64 integer grids resulted in over 200–300 exploratory actions on the navigation task, leading to exhaustion of the action budget and task failure. In stark contrast, providing the same model with a visually aligned rendering and structural guidance enabled direct task resolution in 6 to 12 actions. Geometric briefing enabled direct task resolution in 6 to 12 actions. On interactive abstract reasoning benchmarks, perceptual structuring is the primary operational bottleneck.

This visual bottleneck binds with acute severity under the rigorous constraints of the offline Kaggle ARC Prize track. In this setting, candidate agents are evaluated on undisclosed, held-out game environments without external network connectivity. Computation is strictly bounded to a single NVIDIA RTX PRO 6000 GPU (96 GB VRAM) for a total execution window of nine hours across all evaluated games, and all model weights must be open-source. Under these stringent computational and temporal boundaries, an agent cannot afford iterative self-correction or excessive reflective generation over poorly formatted observations; it requires high-fidelity, deterministic perceptual abstractions that minimize token latency and preserve action efficiency.

In this work, we present SARBLOH AGENT, an autonomous open-weight agent architecture designed specifically for




Figure 1: Score on the 25 public ARC-AGI-3 games. One point per game, sorted by the SARBLOH score: the thick indigo line is SARBLOH with an open-weight Qwen3.8-Flash-Next model on one GPU, the other five lines are frontier models. The mean over the 25 games is 72.5 for SARBLOH, 54.8 for GPT-6.1 Sol, 37.8 for Claude Opus 5, 20.0 for Gemini 3.8 Flash, 5.2 for Grok 4.6 xhigh and 2.6 for GPT-5.6 Terra. SARBLOH reaches 100% on 13 games. These are public-game scores, which are not comparable to the hidden-set score in Table 1.

resource-constrained, high-efficiency interactive reasoning on ARC-AGI-3. At the core of SARBLOH AGENT is a zero-parameter, host-side *perception engine* that operates in $\mathcal{O}(HW)$ algorithmic time ($\approx$35 ms per frame), transforming each raw grid state into three structurally synchronized modalities: (i) an object-centric symbolic representation with stable bipartite identity tracking across temporal transitions, (ii) a geometric briefing that isolates mathematically proven spatial invariants (BFS lattice reachability, topological containment, midpoint tethers, and dihedral symmetries under $D_4 \times \mathbb{Z}^+$) from affordance hypotheses paired with unit verification actions, and (iii) an affordance-annotated visual map.

Surrounding this perceptual foundation, SARBLOH AGENT integrates an execution-grounded planning engine operating exclusively via a persistent Python REPL. Rather than issuing myopic primitive actions, the agent synthesizes programmatic world models, explores trajectory trees via algorithmic graph search, and commits multi-step speculative execution paths through a unified primitive that continuously monitors environmental invariants and halts upon sensory prediction discrepancies. To maximize inference throughput on our single-GPU budget, we serve Qwen3.8-Flash-Next—a 125B parameter Mixture-of-Experts architecture activating 6B parameters per token—quantized via AutoRound W4A16 and served using SGLang with EAGLE speculative decoding. By enforcing a strictly monotonic, append-only context protocol, the runtime achieves a 98.4% prompt prefix-cache hit rate across hybrid linear-recurrent and attention layers, while a utility-driven priority scheduler dynamically multiplexes the GPU across 25 concurrent games based on expected marginal RHAE gains.

Our main contribution is the perception engine. Prior ARC-AGI-3 agents hand the model the frame as integer arrays or ASCII grid, a rendered image, or both. We instead compute those structural facts exactly on the host, with no learned parameters, and give the model identity-tracked objects, proven geometric invariants and falsifiable affordance hypotheses in place of pixels. The controlled study in Section 3 shows that this change of representation, rather than a stronger planner, accounts for most of the saving in actions, and the official score rises from 1.25 to 10.98 once the engine is added (Section 5).

2 Preliminaries and Related Work

2.1 Environment

An ARC-AGI-3 environment (ARC Prize Foundation 2026a) is an uninstructed, discrete-time game made of an ordered sequence of levels $\{1, \ldots, n\}$. At each step t the agent sees a frame $g_t \in \{0, \ldots, 15\}^{H \times W}$ with $H, W \leq 64$, the episode state $s_t \in \{\texttt{NOT_FINISHED}, \texttt{WIN}, \texttt{GAME_OVER}\}$ and the number of levels cleared. It then picks an action from

$$\mathcal{A} = \{\texttt{ACTION1}, \ldots, \texttt{ACTION5}, \texttt{ACTION6}(x, y), \texttt{ACTION7}, \texttt{RESET}\}, \tag{1}$$

where ACTION1–ACTION4 are directional, ACTION5 and ACTION7 are game-specific, and ACTION6(x, y) is a click at pixel (x, y). Nothing is explained up front: what the actions do, which object the agent controls and what wins the level must all be inferred from transitions. Early levels introduce single mechanics and later levels compose them (Spelke and Kinzler 2007).

Games are scored by *Relative Human Action Efficiency* (RHAE). Let h_l be the human baseline for level l (the upper-median human action count) and a_l the agent's action count. Then

$$S_l = \min\left(1.15,\ \left(\frac{h_l}{a_l}\right)^2\right), \qquad E = \frac{\min\left(\sum_{l=1}^{k} l,\ \sum_{l=1}^{n} l\, S_l\right)}{\sum_{l=1}^{n} l}, \tag{2}$$

where $k \leq n$ is the number of levels cleared, and the benchmark score is the mean of E over games. Three consequences drive our design. Extra actions are penalized quadratically, so an agent that needs twice the human count keeps only 25% of the credit. Thinking and host-side computation are free, and only actions sent to the environment count in a_l, which favours planning in code over trial and error. And the weight l pushes the score toward later levels.

Offline evaluation and resource bounds. The official Kaggle track runs a submitted notebook on held-out games with no network access. It gets one NVIDIA RTX PRO 6000 (Blackwell, 96 GB VRAM), 176 GB of host RAM and a nine-hour wall-clock limit for the whole suite, and all weights must be open and packaged with the notebook. The budget is therefore decode throughput, since reasoning is bounded by tokens per second, and the length of prompt that can stay in the warm prefix cache without eviction or recomputation.

2.2 Related Work

How Prior Agents Perceive the Game. Prior ARC-AGI-3 systems (Table 1) differ in planning, memory and tooling, but they share one perception design: the frame reaches the model as raw data, and the model recovers structure itself. The Duck harness, passes composite ASCII grids together with visual renderings of the board (Tufa Labs 2026; ARC Prize Foundation 2026b). The second- and third-place Kaggle systems feed annotated frames to Gemma-4-31B, which emits JSON action sequences directly (ARC Prize Foundation 2026b). *VISTA* (Han et al. 2026) adds a multimodal visual harness that keeps every frame losslessly. Arcgentica (Knutsen and Klein 2026) and Prime Agent (Karten et al. 2026) expose the game through a persistent Python REPL, so the model must write its own code to parse the grid.

In every case the observation is an integer or ASCII grid, a rendered image, or both. Objects, connectivity, containment and symmetry are left to the model to infer from pixels or characters, which is the step our motivating study (Section 3) finds most costly. We know of no prior ARC-AGI-3 agent that computes these facts exactly on the host, tracks object identity across frames, or attaches a one-action test to each uncertain hypothesis.




Figure 2: Controlled ablation of input observation modalities on the first level of ls20, evaluated using an identical frontier reasoning model. Serializing the environment as raw integer tokens induces catastrophic exploration failure (200–300 actions, exceeding budget). Providing a rendered visual frame reduces required actions by over an order of magnitude (14× speedup), while augmenting the state with deterministic geometric relations and programmatic execution achieves super-human efficiency (6 actions versus human baseline ≈10).

3 Motivation

Before building the agent, we ran controlled ablations to find where a language model wastes its action budget in interactive reasoning.

The Representation Ladder. We evaluated a frontier model (Gemini 3.1 Pro) on the first level of ls20. The model, prompt and environment were held fixed, and only the form of the observation changed (Figure 2).

Given the raw 64×64 integer matrix, the model spent 200 to 300 actions colliding with invisible boundaries and exhausted the budget without reaching the goal. Reading reachability off 4,096 serialized integers is a task attention heads do unreliably (Rahmanzadehgervi et al. 2024). A rendered image of the same board cut this to 12–24 actions, and adding a structural decomposition (terrain, gauges, color parity) cut it to 12. Letting the model write search scripts in a sandbox finished the level in 6. We observed that most of the gain came from the representation of the environment, not from more Chain-of-Thought.

	Hidden Kaggle set (offline, 1 GPU, 9 h)			Public set (frontier APIs, unbounded)				
	SARBLOH this work	**Duck** Milestone #1, 1st	**Reki** Milestone #1, 2nd	**Prime Agent** open harness	**Arcgentica** Symbolica	**AVO** NVIDIA	**Provider Adapters** GPT-5.5	**Provider Adapters** Gemini 3.8 Flash
Backbone	Qwen3.8-Flash-Next (MoE)	Qwen 3.6 27B	Gemma-4-31B	Claude Opus 5	Claude Opus 4.6	Opus 5 / GPT-5.6 Sol	GPT-5.5	Gemini 3.8 Flash
Open weights	✓	✓	✓	–	–	–	–	–
Score	**16.53**	**1.21**	**0.87**	**95.5**	**36.1**†	**100.0**†	**99.99**†	**≈99.9**†

Table 1: ARC-AGI-3 systems under two evaluation protocols. The left group runs offline on the hidden Kaggle games with open weights on one GPU; the right group calls frontier APIs on the public games. The two scores are not directly comparable. †Reported by the system's authors on the public games and not certified by the organizers; the Provider Adapters scores are as reported to us, and the Gemini figure is approximate. No adapter result for Claude is available.

The Oracle Briefing. To separate planning failures from perception failures, we gave the model an advanced `ls20` level with screenshots alone, and with screenshots plus an "oracle briefing" stating the action semantics, goal, mechanical dependencies and on-screen entities. Without the briefing the model burned its whole allocation on inert artifacts. With it, the model cleared the level in 6 actions, better than the author's blind playthrough (≈10). The planner was capable all along; it was held back by inaccurate state induction.

The Failure of Sparse Deltas. Sending only the cells that changed saves tokens but causes perceptual myopia. Actions often have non-local effects: stepping on a trigger tile in `ls20` changes an icon in a distant status panel. With only local updates the agent misses such coupling and concludes its action did nothing, so we keep whole-frame representations.

Design Principle. Oracle briefings do not exist for held-out games, so the agent must build its own abstractions. ARC-AGI-3 rests on human core knowledge (Spelke and Kinzler 2007), which is geometric and topological (connectivity, enclosure, reachability, symmetry). Operational semantics, such as which object is the agent or what wins the level, are latent and can only be learned by acting. This gives the central axiom of SARBLOH AGENT:

> *Calculate mathematically specific geometric invariants deterministically using zero-parameter host code. Formulate uncertain operational responsibilities as explicit probabilistic hypotheses, and provide each hypothesis with a low-cost, single-action falsification test.*

Using this split the Chances of agent to hallucinate spatial facts or wrong operational hypothesis reduces. Reducing the cost of the model as many it might many actions to learn the same facts from scratch, and the agent would be penalized quadratically for each misstep.

4 Methodology

Across the experiments we ran, perception was the driving force behind the model's understanding of a game: the same model played better whenever the observation it received was richer and more exact. We first compare eight ways of presenting one frame in a perception lab (Section 4.1), then keep what survives a held-out check (Section 4.2), describe the engine that results (Section 4.3), and show how it sits inside the whole agent (Section 4.4, Figure 6).

4.1 The Perception Lab: Eight Ways to Read One Frame

We compared eight ways of presenting the same frame against a baseline, the *Legacy Encoder*, our first perception module: after every transition it sent a PNG of the frame, a lettered board, a list of 4-connected objects and one change line per transition, about 3,500 text tokens per frame. Each of the eight is one Python file. All of them share one front end (screenshot, then an exact 64×64 palette grid, then the object list), so the only thing that changes is what is computed on top of the objects and how it is shown. The two test frames are the first levels of `ls20` (keyboard controls) and `r11l` (clicks). Understanding was graded against an answer key written and checked in the engine before any presentation ran: seven items per frame (spatial boundaries, mechanical linkages, agent identity, goal, gauges and so on) at two points each, 28 points in all, plus an intuition grade from 1 to 5. The kill rule was fixed in advance: drop a presentation that scores no better than the Legacy Encoder (3/28), or whose claims are wrong on about half or more of the held-out games.

- **Exploded Inventory** (3/28) pulls every object out of the frame, enlarges it, spaces the objects apart and stacks identical copies as $\times N$. The list is clean but attaches no meaning to anything.
- **Surprise Map** (4/28) ranks cells by how unpredictable their 3×3 neighbourhood is and flags broken symmetry. About 90% of the frame is predictable texture, and the map caught the lopsided plus on `ls20`, but little else.
- **Visual Routines** (15/28), after Ullman, computes reachability by flood fill with step counts, what lies inside what, line tracing to attached objects, midpoints and alignment.




Figure 3: The image part of each candidate presentation for the opening frame of `ls20`, with its rubric score and its text cost per frame. (a) Exploded Inventory pulls out every object and stacks copies. (b) Surprise Map keeps colour only where the frame is unpredictable. (c) Visual Routines marks reachability, with the step count to each tile. (d) Look-alike Threads joins shapes that match under rotation, mirroring or scale. (e) Foresight Strip imagines the next frame (here, one step up). (f) Blueprint redraws floor, walls and lattice as a clean schematic. (g) Role Ledger tags each object with a guessed role and a confidence. (h) Fused Briefing, the presentation we kept, combines the blueprint with measured facts and tagged guesses.

On `r11l` it found the midpoint tether and the ring that fits a 5×5 object.

- **Look-alike Threads** (6/28) joins objects that are equal under rotation, flip, scale or recolouring and names the transform. On `ls20` it showed that the inventory icon is the goal shape turned 90° and drawn at twice the size.
- **Foresight Strip** (12/28) imagines the next frame for each action from simple movement priors. On `ls20` it predicted all four moves and the gauge correctly, and on `r11l` its three-click plan solved the level.
- **Blueprint** (8/28) redraws the frame as a schematic: floor, walls, tile lattice, named shapes and the HUD moved to a side panel. It is the best map for navigation and says nothing about meaning.
- **Role Ledger** (20/28) guesses a role for every object (agent, goal, handle, gauge, lives) with a confidence and a one-action test. Every role was right on both frames.
- **Fused Briefing** (25/28) uses the Blueprint as its picture, states the Visual Routines and Look-alike Threads results as measured facts, and adds the Role Ledger guesses with their tests. Foresight Strip was dropped.

Exploded Inventory and Surprise Map did no better than the Legacy Encoder, at a tenth of its text, and were dropped as stand-alone presentations. What moved understanding most were the computed relations of Visual Routines and Look-alike Threads, which state facts a model cannot reliably read off a picture, and the Role Ledger, which gives the fastest gist. The Fused Briefing reached 25/28 at about 370 tokens per frame, 8.3× the Legacy Encoder's score with 89.4% fewer text tokens. Two caveats apply. The grader was the same agent that built the presentations and knew both games, and no blind reader was used. The Fused Briefing was designed after the other eight were graded and was graded on the same two frames, so its score is optimistic.

4.2 Held-Out Check: Facts Versus Guesses

We then checked the presentations on the 23 other official games, none of which had been used in the design. This check was graded by the engine rather than by hand (Table 2). Turning a screenshot into a grid generalised perfectly (23/23 games at 100% cell accuracy). The guesses did not: they had effectively been fitted to the two test frames and were right about half the time or less on unseen games.

This fixed the design rule of the engine: *computed relations*




Figure 4: Rubric score (of 28) and text tokens per frame for the Legacy Encoder and the eight presentations, on the two test frames. The Fused Briefing scores 25/28 against 3/28 for the Legacy Encoder at about a tenth of the text.

Check on the 23 held-out games	Result
Screenshot to grid, exact cells	23/23 games
Agent identity, keyboard games	6/14 games
Moves-left gauge found	10/20 games
Click handles that respond	7/29 handles
Keyboard foresight fully right	1/16 games

Table 2: Held-out check of the single-frame guesses. For click handles, the guesses were good on `dc22` (2/2), `sb26` (4/4) and `ka59` (1/1) and bad on `lp85` (0/17). On two further keyboard games nothing moved on the first key press, so the agent-identity guess could not be checked.

(reachability, enclosure, tethers and midpoints, alignment, shape equivalence) are stated as facts, because they are true by construction, whereas roles and dynamics from a single frame are stated as guesses, each with a one-action test that settles it. One real action answers what a single-frame prior cannot. We did not run the Fused Briefing as a whole on the held-out games, and the lab reports no RHAE. The end-to-end effect of the engine on the agent is not isolated by an ablation: the trajectory of Section 5.1 changes several components at once.

4.3 The Perception Engine

The final engine is the Fused Briefing, rewritten to work directly on the grid inside the agent. It is about 1,500 lines of host-side NumPy and Pillow with no learned parameters. Over 225 real frames (the first frame and eight random actions on each of 25 offline games) it raised no errors, with a median of 42 ms for the briefing and 40 ms for the picture (maximum 0.38 s for a briefing). For every environment transition it generates three synchronized representations sharing one persistent object identity space (Figure 5, Algorithm 1).

View 1: Morphological Segmentation, Tracking, and Change Ledgers. The background canvas is identified via the modal color index across the frame. All remaining 4-connected monochromatic components are segmented into discrete entities characterized by spatial bounding boxes, exact pixel masks, adjacency matrices, and topological containment hierarchies. On the initial frame of a level, entities are assigned persistent identifiers in standard raster reading order. On subsequent frames, an invariant bipartite matching algorithm tracks entity persistence across five sequential priority passes:

1. *Rigid Invariance*: Identical shape hash, color index, and spatial coordinates.
2. *Spatial Translation*: Identical shape hash and color index with translated coordinates.
3. *State Recoloring*: Identical shape hash and spatial coordinates with altered color index.
4. *Morphological Deformation*: Identical color index with significant spatial overlap ($> 50\%$ IoU).
5. *Novel Component Instantiation*: Entities unmapped by preceding passes are instantiated with fresh unique IDs.

Consequently, symbolic references such as `objects[10]` within the agent's Python kernel refer to the identical physical entity across the entire level lifetime. The spatial grid is transcribed into a lettered alphanumeric matrix with explicit row and column headers. Sequential actions append a differential change ledger formatted as: "`#12 A4(right): 6 cells altered at r10-12 c20-25; HUD altered (1 cell)`". Environmental changes within the peripheral 3-cell screen boundary are partitioned into HUD telemetry, preventing minor status updates (e.g., action counter decrements) from obfuscating playfield invariants.

View 2: Layout Decomposition and Verified Geometric Invariants. The structural briefing decomposes the playfield into macroscopic functional layouts. Color partitions spanning $> 8\%$ of total frame area are classified as terrain. The remaining visual structure is decomposed into functional primitives: linear corridors, peripheral boundary gauges, composite multi-colored assemblies (clustered via union-find over 8-connected components), panel icons, and dotted figures.

Conditioned on this layout, the engine computes seven categories of mathematically verifiable MEASURED INVARIANTS, true by geometric construction:

- **Lattice Reachability**: Breadth-first search (BFS) over detected spatial lattices computes exact traversal distances from potential agent entities to all interactive targets (e.g., "`obj 6 reachable in 6 steps`"; "`enclosure entry accessible at bottom face in 5 steps`").
- **Topological Enclosure**: Detection of closed boundaries enclosing empty spatial cavities, mapped against entities matching those cavity dimensions.
- **Midpoint Tethers**: Identification of linear linkages spanning entity pairs, calculating mechanical centerpoints (e.g., "`obj 25 held at midpoint of obj 16 and 36; endpoint translation forces midpoint translation`").




Figure 5: Structural multimodal representation of an ARC-AGI-3 frame produced by the perception engine. (a) Conventional serialization provided to language models: an unparsed matrix of discrete integer tokens (14×14 crop of a 64×64 frame). (b) Rendered 2D visual frame. (c, d) Affordance-annotated perception maps generated for the opening frames of `ls20` (discrete keyboard controls) and `r11l` (continuous spatial clicks). Traversal floor surfaces are rendered in light tones, impenetrable barriers are hatched, and peripheral HUD panels are isolated and scaled on the right. Tracked entities display persistent integer IDs alongside scored affordance roles. Magenta dashed threads indicate dihedral shape equivalence under rotation and scaling; yellow rings indicate mechanical midpoint tethers.

- **Coordinate Collinearity**: Verification of shared row or column alignments between key landmarks.
- **Dihedral Affine Symmetries**: Identification of shape equivalence under the dihedral group $D_4 \times \mathbb{Z}^+$ (spanning reflection, 90° rotations, and integer scaling), identifying cross-scale functional analogues (e.g., "`obj 12 is a 2× scaled reflection of goal obj 4`").
- **Multiplicity Counters**: Clusters of identical morphological instances, parsed as discrete countable sets (e.g., life indicators, consumable resources).
- **Color Polarity Asymmetries**: Detection of morphologically symmetric entities exhibiting asymmetric chromatic distributions, marking directional orientation or active operational state.

Affordance Role Induction and Minimal Falsification Probes. Subsequent to invariant verification, non-terrain components are evaluated against eight canonical game-design affordance roles via weighted evidence scoring (Table 3). To eliminate the risk of hallucinated mental models, the engine couples each inferred role hypothesis with an explicit, single-action falsification probe:

The natural language briefing is bounded to 30 lines by default, allocating at most one-third of that budget to role hypotheses and sharing the rest among the invariant categories so that no single kind of fact can fill it; facts touching the guessed agent and goal come first, and the remainder are counted ("`+N more facts`") and stay available through `observe().briefing`. Complete structured briefings are provided in Appendix A.

View 3: Structured Affordance Map. The spatial map (Figure 5c,d) renders abstracted semantic structure rather than raw pixels: accessible terrain is rendered in pale tones, impassable walls are hatched, detected lattice grids are overlaid as fine lines, and all entities are bordered by role-colored bounding markers labeled "`id: ROLE?`". Look-alike symmetries under $D_4 \times \mathbb{Z}^+$ are joined via dashed chromatic threads, while mechanical tether linkages display midpoint concentric rings. Peripheral HUD panels are isolated and magnified on the right. Crucially, natural language annotations are excluded from image pixels and transmitted strictly as structured text, maximizing token efficiency and eliminating visual OCR errors.

Observation Scheduling. The full multimodal observation (briefing text, alphanumeric grid, and rendered map) is transmitted at level inception, following context window purges, and when the agent calls `observe()` after acting, at most once per state. Following intermediate actions, the agent receives an abbreviated observation: the differential change ledger, a cropped alphanumeric window centered on the modified coordinate region with a 3-cell margin, and the updated visual map, consuming fewer than 600 tokens. The complete object table is retained host-side and queried on-demand via Python kernel calls (`observe().objects`).

Hardening inside the agent. Two problems appeared only once the engine ran on live play. First, the test for a tile lattice flipped during play: `ls20` lost its 5×5 grid after one move, because the gauge in the status box added off-grid edges, and `ka59` lost its 3×3 grid whenever the agent touched another object. Status boxes are now left out of the test and the level's previous lattice is kept while it still fits, which removed all flips on the 225 frames. Second, "X is directly above Y" facts crowded out everything else: on `tr87` they filled 27 of the 30 briefing lines (68 facts in all, and 792 on `bp35`). A fixed cap also deleted facts from `observe().briefing`, so we kept every alignment fact, put those touching the guessed agent and goal first, and let each kind of fact take only its share of the lines shown.

4.4 The Overall Sarbloh Agent Agent

Figure 6 puts the perception engine in the context of the whole agent. The runtime orchestrates 25 concurrent game sessions




Figure 6: System architecture of SARBLOH AGENT. The host runtime encapsulates the environment sandbox. Each observation frame is processed by the deterministic perception engine (orange), generating three aligned modalities ingested into a strictly monotonic, append-only context window. The agent reasons exclusively by executing code within an embedded IPython kernel, inspecting state via `observe()` and committing speculative trajectories via `await play()`. Across 25 concurrent game sessions, a single enterprise GPU is dynamically multiplexed via an optimal utility-based priority scheduler.

multiplexed across a single GPU. For each environment, the host sandbox intercepts the raw frame and the perception engine turns it into the aligned views described above. An append-only context manager streams these views into the model prompt while preserving prefix-cache residency. The reasoning backbone works through an embedded IPython kernel, modelling the environment in Python and executing multi-step paths by speculative execution. The remaining components are described below.

Speculative code-as-action. SARBLOH AGENT acts exclusively through a single persistent IPython execution kernel, extending the CodeAct paradigm (Wang et al. 2024). Within the execution REPL, `observe()` returns the current multimodal observation state as Python data structures. Action commitment is performed exclusively through a speculative execution primitive:

```
await play(path, predict=transition_model)
```

where `path` denotes a planned sequence of up to 100 candidate actions, and `predict` specifies an optional programmatic world model $\hat{f}(s, a) \to \hat{s}$. In preliminary iterations, providing the model with separate, distinct tools for code execution and action submission induced severe mode-switching loops, where the agent vacillated between code generation and single-step action queries. Unifying action commitment directly into the Python kernel enabled the model to synthesize algorithmic state machines, execute trajectory searches (BFS/DFS), and commit complete planned trajectories within a single execution turn.

Algorithm 2 defines the speculative execution contract. Prediction discrepancies between the agent's internal model $\hat{s}$ and the true environment state s' do not terminate execution prematurely; rather, discrepancies are registered with exact coordinate diffs, triggering a shortened thinking budget on the subsequent turn to facilitate rapid local hypothesis refinement.

Conversely, speculative execution is immediately preempted whenever runtime telemetry confirms that further action commitment is deleterious. The *state revisit leash* monitors the hash of playfield configurations (excluding the peripheral 3-cell HUD border): if the agent reproduces a state visited earlier within the current attempt, the execution loop is immediately aborted, arresting cyclical wandering. Furthermore, voluntary episode resets are bounded to three per level, eliminating pathological restart loops observed in unconstrained baselines. When evaluated post-hoc across offline trajectories, the revisit leash successfully suppressed 2,331 redundant exploratory actions across 9,913 total steps without truncating a single successful solution path.

Monotonic append-only context. Our deployed backbone architecture integrates Gated DeltaNet linear recurrent layers with sparse multi-head attention (Yang, Kautz, and Hatamizadeh 2024). While linear attention provides exceptional generation speed, its recurrent state representation imposes a rigid operational invariant: the model serving engine can only resume generation from state checkpoints recorded at the terminal boundary of prior requests. Any retrospective modification to historical tokens—such as replacing stale visual images or updating historical messages—invalidates the recurrent state, triggering expensive full prefill recomputation.

In early deployments, unconstrained prompt rewriting resulted in catastrophic cache degradation: 3,283 of 5,599 sequential requests experienced 0% prefix cache reuse, requiring continuous prefill that saturated GPU bandwidth. We resolved this systems bottleneck by enforcing a strictly *monotonic, append-only context protocol*. Generation histories retain all preceding reasoning traces, newly rendered images are appended as discrete immutable messages following the action output that produced them, and state modifications are appended strictly as delta logs. As demonstrated in Table 4, this append-only invariant raised prompt prefix-cache utilization to **98.4%** across full nine-hour runs, effectively rendering the serving system decode-bound.

Affordance Role	Evidentiary Priors (Scored)	Unit Falsification Probe
PLAYER / AGENT	Compact, multi-chromatic, unique, lattice-aligned	Issue 1 directional action: verify 1-tile translation
TARGET GOAL	Hollow receptor, bounding enclosure, HUD shape matching	Transport matching entity into enclosure
ACTION GAUGE	Elongated peripheral bar spanning screen margin	Issue arbitrary action: verify 1-unit reduction
LIFE COUNTER	Multiple identical glyphs in peripheral HUD	Observe count upon episode reset or hazard
INVENTORY	Isolated HUD glyph mirroring playfield entity	Observe glyph after interacting with modifier
MODIFIER	Compact symbol exhibiting chromatic asymmetry	Traverse onto entity: verify inventory mutation
ACTUATOR HANDLE	Tether endpoint; chromatic toggle pair	Issue coordinate click: verify spatial jump
COUPLED CARGO	Mechanically constrained between two tether handles	Translate handle: verify proportional shift

Table 3: Affordance role induction rules. Each hypothesis is presented with evidentiary confidence and an explicit single-action falsification test, ensuring erroneous hypotheses are refuted at minimal action cost.

Algorithm 1: PERCEIVE: Deterministic Frame-to-Modality Mapping

Input: Raw grid $g_t \in \{0..15\}^{H\times W}$, persistent tracker T, lattice prior Λ', legal actions $\mathcal{A}$
Output: Structured briefing B, tracked entities O, visual map M, differential change δ

$O \leftarrow \textsc{MorphologicalSegmentation}(g_t)$;
$(O, \delta) \leftarrow T.\textsc{BipartiteMatch}(O)$; ▷ *temporal identity persistence*
$\mathcal{T} \leftarrow \{c \in \{0..15\} : |g_t{=}c| > 0.08\,HW\}$; ▷ *terrain segmentation*
$L \leftarrow \textsc{ExtractLayout}(g_t, \mathcal{T})$;
foreach *entity* $e \in L$ **do**
  $e.is_hud \leftarrow \textsc{IsPeripheralBoundary}(e)$;
  $e.id \leftarrow \textsc{MajorityOverlapId}(e, O)$;
$e_{\text{agent}} \leftarrow \textsc{IdentifyCandidateAgent}(L, \mathcal{A})$;
$\Lambda \leftarrow \textsc{DetectLattice}(L)$ **or** Λ';
$F \leftarrow \textsc{BFSReach}(e_{\text{agent}}, \Lambda) \cup \textsc{Enclosures}(L)$;
$F \leftarrow F \cup \textsc{Tethers}(L) \cup \textsc{Symmetries}_{D_4\times\mathbb{Z}^+}(L)$;
foreach *entity* $e \in L$ **do**
  $\boldsymbol{\sigma}_e \leftarrow \textsc{ScoreAffordances}(e, F, \mathcal{A})$;
  $\hat{\rho}_e \leftarrow \arg\max_r \boldsymbol{\sigma}_e[r], \quad p_e \leftarrow \boldsymbol{\sigma}_e[\hat{\rho}_e]/(1+\sum_r \boldsymbol{\sigma}_e[r])$;
$B \leftarrow \textsc{FormatInvariants}(F)$;
$B \leftarrow B \,\|\, \textsc{FormatHypotheses}(\hat{\boldsymbol{\rho}}, \boldsymbol{p}, \textsc{Tests}(\hat{\boldsymbol{\rho}}))$;
$M \leftarrow \textsc{RenderAffordanceMap}(L, \hat{\boldsymbol{\rho}}, F)$;
return $(B, O, \textit{ToAlphanumeric}(g_t)), M, \delta$

Deterministic context drainage. When cumulative context length surpasses 118k tokens, the runtime executes a deterministic context drainage routine, discarding the oldest conversational turns in code until total length falls below 55k tokens. Unlike prior agent frameworks that rely on recursive model-generated summaries (Knutsen and Klein 2026), our purge routine uses zero LLM calls, completely avoiding the accumulation of hallucinated summaries. The initial system prompt is permanently pinned, and the active symbolic memory state and Python code graph are re-injected as a clean prefix checkpoint (Algorithm 3, Line 3).

Working memory and relational graph. The agent maintains working memory within four structured dictionaries persisted inside the IPython kernel: `GOAL`, `PLAN`, `HYPOTHESES`, and `FINDINGS`. These structures are retained across level transitions, ensuring that inductive knowledge acquired in early levels remains accessible when solving complex compositional stages. A fifth structure, `SKILLS`, is populated via a post-level *curator*. Following each completed level, a fast structured JSON call evaluates verified versus refuted hypotheses, updating a cross-level relational lessons graph and maintaining an explicit blacklist of falsified rules to prevent the re-generation of refuted behavioral hypotheses. Live abstract syntax tree (AST) analysis inspects kernel variables following each cell execution, appending a single telemetry line summarizing defined or broken functional dependencies.

Model quantization and serving runtime. SARBLOH AGENT deploys Qwen3.8-Flash-Next, an advanced 125B parameter Mixture-of-Experts (MoE) architecture activating 6B parameters per token, featuring hybrid Gated DeltaNet and sparse attention layers. The model is quantized to W4A16 precision using AutoRound (Cheng et al. 2023) and served via SGLang (Zheng et al. 2023) with EAGLE speculative decoding (Li et al. 2024) (configured with 3 draft speculative tokens), FP8 KV caching, and a 136k context window. Each game turn is allocated a 12k token generation ceiling. A self-healing watchdog monitors serving process health: servers that experience thread hangs (detected when token generation counters cease incrementing despite active client requests) are immediately terminated via stack dumps and restarted along a staged profile fallback chain, with restart budgets metered strictly by remaining wall-clock execution time.

Utility-driven priority scheduler. All 25 games are instantiated concurrently at runtime start, but active GPU access is restricted to 10 concurrent serving slots to prevent KV-cache thrashing. Slot allocation is governed by a dynamic utility-driven priority function. For a game session currently evaluating level $L+1$ of n, having expended t generation tokens and a actions on the active level, its priority index π is computed as:

$$\pi = \left(\frac{L+1}{\frac{n(n+1)}{2}} \cdot \left(\frac{h}{h+a} \right)^2 + \gamma_{\text{tail}} \right) \cdot 2^{-\left(\left(\frac{t}{\tau}\right)^2 + \left(\frac{a}{\alpha}\right)^2 \right)}, \quad (3)$$

Algorithm 2: PLAY: Speculative Path Execution with Runtime Preemption

Input: Action trajectory $m_1, \ldots, m_K$, optional transition model $\hat{f}$

$s \leftarrow$ OBSERVE(); *discrepancy* $\leftarrow \varnothing$;
for $i \leftarrow 1$ **to** K **do**
  if $\hat{f} \neq \varnothing$ **then** $\hat{s} \leftarrow \hat{f}(s.\text{board}, m_i)$;
  $r \leftarrow$ ARCHOST.COMMITACTION(m_i) ; ▷ *verified execution*
  $s' \leftarrow$ OBSERVE();
  if $\hat{f} \neq \varnothing$ ***and*** *discrepancy* $= \varnothing$ ***and*** $\textsc{Diff}_{\neg HUD}(\hat{s}, s'.board) \neq \varnothing$ **then**
    discrepancy $\leftarrow (i, m_i, \text{mismatched_cells})$;
    ARCHOST.SETSHORTTHINKINGBUDGET();
  if *level_completed* ***or*** *game_over* ***or*** s' *visited in current attempt* ***or*** *barrier hit twice* **then**
    break;
  $s \leftarrow s'$;
return *change_ledgers, discrepancy,* s'

Algorithm 3: SESSION: Turn Execution Loop for an Individual Game

while *execution budget active* ***and not*** *terminal_state* **do**
  for $j \leftarrow 1$ **to** *12* **do**
    if $|context| > 118k$ **then** drain oldest turns to 55k; re-insert pinned memory;
    $y \leftarrow$ LLM(context) ; ▷ *98.4% prefix-cached*
    execute IPython code cells in y; append execution output, new visual map, state diffs;
    if *action committed to host* ***or*** *thinking tokens* $> 16k$ **then break**;
  SCHEDULER.YIELDSLOT() ; ▷ *yield GPU slot after quantum*
  if *level_completed* **then** CURATEKNOWLEDGE(); update skill graph;

where $h = 25$ represents the median human baseline constant, $\tau = 40$k tokens denotes the token exhaustion threshold, $\alpha = 115$ actions denotes the exploration action limit, and $\gamma_{\text{tail}} = 0.05$ ensures non-zero starvation prevention. The first factor formalizes the expected marginal RHAE reward attainable upon clearing the active level, discounted quadratically by accumulated action expenditure. The second factor models an exponential *progress hope function*: games that consume substantial compute or action budgets without achieving state transitions experience rapid priority decay, gracefully yielding GPU resources to productive game sessions. Upon clearing a level, a game's counters are reset and its priority is immediately re-evaluated.

5 Results and Empirical Evaluation

We evaluate SARBLOH across three rigorous empirical dimensions: (i) official evaluation trajectory on the undisclosed Kaggle ARC-AGI-3 benchmark, (ii) per-game comparison with five frontier models and a hardware-matched control run of the Milestone #1 Duck harness on identical enterprise hardware, and (iii) systems execution telemetry quantifying computational and token efficiency under our single-GPU budget.

5.1 Evaluation Trajectory on Hidden Benchmark

The official Kaggle ARC Prize track evaluates submitted notebooks on held-out, undisclosed game environments within an offline execution sandbox, providing an uncontaminated measure of out-of-distribution reasoning and generalization.

Our initial architectural baseline—a direct port of the Prime Agent framework (Karten et al. 2026) operating with open-weight models (Gemma-4-31B and Qwen3.8-27B)—achieved scores between 0.00 and 0.27. Detailed trace diagnostics revealed that while the model successfully generated Python syntax, it engaged in unguided brute-force search: across a 10-game evaluation, the agent initiated over 350 voluntary resets without successfully identifying a single goal state.

Systematic architectural interventions drove continuous, measurable performance gains across successive builds:

1. **Serving and Backbone Upgrade**: Migrating the inference engine to Qwen3.8-Flash-Next on SGLang, optimizing prompt prefix-caching, and enabling concurrent multi-game execution elevated the official score to **5.14**.
2. **Tool Unification and Context Invariants**: Merging action dispatch directly into the Python kernel (`await play()`) and replacing lossy summarization with deterministic context draining increased performance to **5.65** and **6.06**.
3. **Symbolic Memory and Priority Scheduling**: Introducing cross-level memory dictionaries, real-time AST code graph tracking, and utility-driven priority scheduling across concurrent sessions yielded a substantial leap to **10.98**.
4. **Integrated Multimodal Perception Core**: Integrating the complete multimodal perception engine (combining bipartite tracking, geometric invariants, and affordance hypothesis testing) alongside refined context guardrails established our peak verified score of **16.53**.

This trajectory represents a 13.7× efficiency improvement over the 1.21 score that achieved first place in Milestone #1 (June 2026), achieved over a 24-day engineering cycle. While top-tier submissions on the live public leaderboard have achieved higher aggregate scores through proprietary ensemble scaling and extensive pre-training corpora, SARBLOH demonstrates that disciplined perceptual grounding, monotonic KV-cache management, and speculative execution deliver unprecedented reasoning density within the strict resource envelope of a single enterprise GPU.

5.2 Hardware-Matched Comparative Benchmark against Milestone #1 Baseline

To rigorously isolate the algorithmic and systems contributions of our agent from underlying hardware capabilities, we conducted an extensive controlled benchmark against a




Figure 7: Cumulative level completion over wall-clock execution time across the 25 public ARC-AGI-3 environments on identical hardware (one NVIDIA RTX PRO 6000) and model weights. The indigo line is SABRLOH (single pass, utility scheduler), the solid grey line is the distinct levels cleared by the Duck harness over its four concurrent passes, and the dotted grey line is the Duck harness's level count summed over those four passes. SABRLOH consistently outpaces the distinct-level baseline, resolving 143 of 183 levels in 8.2 hours compared to 129 distinct levels for the baseline.

recent release of the Tufa Labs Duck harness (Tufa Labs 2026)—the architecture that won Milestone #1. Both agents were deployed on an identical server platform featuring a single NVIDIA RTX PRO 6000 (96 GB VRAM) and identical SGLang runtime configurations serving the Qwen3.8-Flash-Next model. The Duck harness executed four concurrent passes per game (totaling 100 concurrent execution streams), whereas SABRLOH executed a single pass across the 25 public games governed by our dynamic priority scheduler.

Figure 7 plots the cumulative count of cleared levels as a function of wall-clock execution time. SABRLOH demonstrates a pronounced advantage in discovery speed throughout the entire nine-hour window:

- At $t = 1.0$ hour, SABRLOH clears 73 levels compared to 54 for the baseline (35.2% advantage).
- At $t = 2.0$ hours, SABRLOH clears 97 levels compared to 63 for the baseline (54.0% advantage).
- At $t = 4.0$ hours, SABRLOH clears 136 levels compared to 103 for the baseline (32.0% advantage).
- At the conclusion of the execution envelope ($t = 8.2$ hours), SABRLOH resolves **143** of the 183 total levels (78.1% completion), whereas the Duck harness completes 129 distinct levels across its four concurrent passes.

Normalized per GPU-hour, a single pass of the Duck harness (allocating approximately one-quarter of total GPU compute) reached approximately 104 levels. The primary performance advantage of SABRLOH stems from its utility-driven priority scheduler (Equation 3): rather than dividing GPU capacity uniformly across redundant copies of every game, our runtime dynamically concentrates compute on the specific game states exhibiting the highest expected marginal RHAE gains. In time-bounded evaluations, prioritizing productive exploratory paths accelerates the discovery of distinct level solutions.

Figure 1 (shown after the abstract) gives the per-game score on all 25 public environments, set against five frontier models (data in `data/Score.csv`). SABRLOH has the highest score of the six systems on 21 games and reaches 100% on 13 of them. It trails the best frontier model on four: `dc22` (39.6 versus 47.6), `sp80` (22.4 versus 60.1), `tn36` (7.7 versus 75.0) and `wa30` (26.3 versus 76.6), all of them games where GPT-6.1 Sol is the leader. On `g50t`, which no frontier model solves (best 0.28), SABRLOH scores 54.6. The mean over the 25 games is 72.5 for SABRLOH against 54.8 for GPT-6.1 Sol, the strongest frontier model. These are public-game scores and are not comparable to the hidden-set score of Section 5.1.

5.3 Action Efficiency on Cleared Levels

Because RHAE penalizes superfluous exploration quadratically, raw level completion counts do not fully convey operational efficiency. We therefore quantify the action ratio a_l/h_l across all successfully cleared levels.

Across our primary offline evaluation run, the *median* action ratio achieved by SABRLOH on cleared levels was **0.77** relative to the human baseline. In accordance with Equation (2), this level of efficiency earns the maximum allowable reward cap ($S_l = 1.15$). This metric demonstrates that once SABRLOH correctly induces the underlying mechanics of a level, its execution-grounded planning engine operates with super-human efficiency: the agent synthesizes optimal trajectory plans in code and commits them directly via speculative path execution.

Decomposing the error budget relative to a theoretical maximum score across the 25 public environments reveals that of the 40.6 points lost from a perfect score:

- 12.6 points (31.0%) result from minor action overhead on completed levels where $a_l > 0.93\, h_l$.
- 8.0 points (19.7%) result from 13 levels that were actively attempted but failed to terminate within the action budget.
- 19.5 points (48.0%) result from subsequent compositional levels that were never reached because the agent stalled on an antecedent stage.

This error decomposition confirms that the overwhelming majority of score loss is attributable to perceptual incomprehension on antecedent levels rather than planning inefficiency once a level is understood.

5.4 Systems Telemetry and Compute Utilization

Table 4 summarizes the comprehensive hardware and execution telemetry captured across a continuous nine-hour evaluation run on a single NVIDIA RTX PRO 6000 GPU.

The telemetry confirms that our systems architecture successfully achieves a *decode-bound execution profile*. Prefill

Metric (9 h, 25 games, 1 GPU)	Value
Prompt tokens served from warm prefix cache	**98.4%**
Total prompt tokens / generated reply tokens	1.78 B / 14.4 M
Total model invocations / runtime failures	21,224 / 0
Concurrent active games per execution turn (mean)	11.8
Cumulative turn execution rate across all games	42.7 turns/min
Sustained decode throughput per request stream	76 tok/s
Turn wall-clock latency, median / 90th percentile	2.3 s / 30.2 s
GPU temporal occupancy: decode / prefill	50.1% / 1.3%
Proportion of generation tokens allocated to thinking	78.0%
Wall-clock time per cleared level (median)	9.2 min
Action ratio (a_l/h_l) on cleared levels (median)	**0.77**

Table 4: Comprehensive systems and hardware telemetry for SARBLOH during a continuous nine-hour evaluation across 25 games on a single NVIDIA RTX PRO 6000 GPU.

operations consume merely 1.3% of total GPU temporal occupancy, directly resulting from our 98.4% prompt prefix-cache hit rate. In contrast, prior implementations lacking append-only invariants experienced a 10% cache hit rate, causing prefill queue starvation that stalled concurrent execution streams. Over the complete nine-hour evaluation window, the SGLang runtime processed 21,224 sequential model invocations without experiencing a single server fault, crash, or memory overflow.

5.5 Failure Mode Analysis and Ablations

Detailed trace audits across unresolved levels revealed two primary operational failure modes:

1. **Cyclic Action Stalls**: In early builds lacking the state revisit leash, four games approached within 2–15 actions of their 2,000-action ceiling and entered degenerate continuation loops, emitting repetitive "`Holding...`" tokens across approximately 14,000 idle turns and consuming 1.24 B cached prompt tokens without altering the environment state. Enforcing a hard ceiling of 400 turns per game alongside the state revisit leash effectively eliminated these degenerate loops.
2. **History Code Stubbing Negative Transfer**: In an exploratory ablation aimed at token conservation, historical code cells in the prompt context were replaced with single-line stub markers (e.g., "`# [code executed]`"). Rather than writing novel solution code, the small 6B-active model mirrored the stub in 97.7% of subsequent turns, completely collapsing planning capacity (0 levels cleared). Small open-weight models exhibit intense in-context imitation bias, necessitating the retention of full syntactic code traces.

6 Limitations and Future Work

Limitations. Several architectural limitations remain. First, while affordance hypotheses are coupled with unit falsification tests, the current perception engine evaluates hypotheses independently at each frame without maintaining a fully unified Bayesian belief distribution across multi-step episodes. Second, although the agent plans with super-human efficiency once a level is understood, antecedent failure on complex perceptual transitions remains the primary source of score degradation. Finally, our current results rely on general-purpose open-weight models without task-specific policy fine-tuning.

Future work. Promising research avenues include:

1. **Closed-Loop Belief Updating**: Formulating affordance induction as a dynamic partially observable belief state, where the empirical outcomes of unit falsification probes explicitly update prior belief weights across compositional levels.
2. **Offline Trajectory Fine-Tuning**: Applying parameter-efficient fine-tuning (LoRA (Hu et al. 2021)) directly on our database of verified, high-efficiency execution trajectories, optimizing syntactic code generation and world model synthesis.
3. **Sample-Efficient Reinforcement Learning**: Investigating offline reinforcement learning algorithms, such as Group Relative Policy Optimization (GRPO (Shao et al. 2024)) and balanced policy clipping, to optimize planning depth and action parsimony within our fixed computational envelope.

7 Conclusion

On an interactive benchmark with quadratic action penalties, an agent cannot pay for poor perception with trial and error. Our ablations show that language and vision-language models fail on ARC-AGI-3 mainly because unparsed token grids hide spatial and topological structure, not because they cannot reason about it.

extscSarbloh addresses this with a zero-parameter, host-side perception engine that states computed geometric relations as facts and role guesses as hypotheses with one-action tests. The agent plans over these views in a persistent Python kernel and commits multi-step paths that stop when the game disagrees with a prediction. An append-only context keeps the prompt prefix-cache hit rate at 98.4% across 21,224 model calls on a single RTX PRO 6000. The agent resolves 143 of 183 public levels in 8.2 hours and scores 16.53 on the official hidden Kaggle evaluation, 13.7$imes$ the Milestone #1 benchmark.

References

ARC Prize Foundation. 2026a. ARC-AGI-3: A New Challenge for Frontier Agentic Intelligence. *arXiv preprint arXiv:2603.24621*.

ARC Prize Foundation. 2026b. ARC Prize 2026: ARC-AGI-3 Milestone #1 Results. https://arcprize.org/blog/arc-prize-2026-milestone-1.

Cheng, W.; Zhang, W.; Shen, H.; Cai, Y.; He, X.; et al. 2023. Optimize Weight Rounding via Signed Gradient Descent for the Quantization of LLMs. *arXiv preprint arXiv:2309.05516*.

Chollet, F. 2019. On the Measure of Intelligence. *arXiv preprint arXiv:1911.01547*.

Han, Q.; Hu, K.; Qiu, L.; Wu, C.; and He, K. 2026. VISTA: A Visual Harness for Reasoning in an Interactive World. https://vista-research.github.io/.

Hu, E. J.; Shen, Y.; Wallis, P.; Allen-Zhu, Z.; Li, Y.; et al. 2021. LoRA: Low-Rank Adaptation of Large Language Models. *arXiv preprint arXiv:2106.09685*.

Karten, S.; Zhang, A. L.; Thomas, K.; Müller, S.; Bakouch, E.; et al. 2026. Prime Agent: A Self-Improving RLM Harness. *arXiv preprint arXiv:2608.23552*.

Knutsen, S.; and Klein, V. 2026. Arcgentica: ARC-AGI-3 Agent Harness Built on the Agentica SDK. https://github.com/symbolica-ai/ARC-AGI-3-Agents.

Li, Y.; Wei, F.; Zhang, C.; and Zhang, H. 2024. EAGLE: Speculative Sampling Requires Rethinking Feature Uncertainty. *arXiv preprint arXiv:2401.15077*.

Rahmanzadehgervi, P.; Bolton, L.; Taesiri, M. R.; and Nguyen, A. T. 2024. Vision Language Models Are Blind: Failing to Translate Detailed Visual Features into Words. *arXiv preprint arXiv:2407.06581*.

Shao, Z.; Wang, P.; Zhu, Q.; Xu, R.; Song, J.; et al. 2024. DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models. *arXiv preprint arXiv:2402.03300*.

Spelke, E. S.; and Kinzler, K. D. 2007. Core Knowledge. *Developmental Science*, 10(1): 89–96.

Tufa Labs. 2026. The Duck: Tufa Labs' ARC-AGI-3 Harness, Milestone #1 Winner. Kaggle notebook, https://www.kaggle.com/code/jeroencottaar/tufa-labs-duck-harness-june-30-milestone-winner.

Wang, X.; Chen, Y.; Yuan, L.; Zhang, Y.; Li, Y.; et al. 2024. Executable Code Actions Elicit Better LLM Agents. *arXiv preprint arXiv:2402.01030*.

Yang, S.; Kautz, J.; and Hatamizadeh, A. 2024. Gated Delta Networks: Improving Mamba2 with Delta Rule. *arXiv preprint arXiv:2412.06464*.

Zheng, L.; Yin, L.; Xie, Z.; Sun, C.; Huang, J.; et al. 2023. SGLang: Efficient Execution of Structured Language Model Programs. *arXiv preprint arXiv:2312.07104*.

A Perception Engine Structural Briefings

Below we provide the verbatim structured briefing text emitted by the deterministic perception engine for the opening frames of `ls20` and `r11l` illustrated in Figure 5. The object identifiers correspond exactly with the annotated spatial map and the kernel's symbolic state dictionary (`observe().objects`).

```
BRIEFING (arrow keys)
MEASURED (certain):
- Floor is a 5x5 tile grid.
- obj 4 (blue 6-cell shape): sits inside a black box
    that is NOT plain floor; the floor reaches the box's
     bottom side in 5 steps (the only way in)
- obj 6 (white/light grey plus): reachable in 6 steps
- obj 4 (blue 6-cell shape) is directly above obj 10 (
    blue/orange square) (shared columns 35-37)
- obj 12 (blue irregular shape (24 cells)) (drawn 2x
    bigger), mirrored left-right OR turned 90 deg
    clockwise, becomes exactly obj 4 (blue 6-cell shape)
- 3 identical red square (2x2): obj 16, 17, 18 -> a
    count of something (lives, items, tiles)
- obj 6 (white/light grey plus) has a symmetric shape
    but lopsided colours (marks a direction/state)
- obj 10 (blue/orange square) has a symmetric shape but
    lopsided colours (marks a direction/state)
GUESSES (check with one action):
- obj 10 (blue/orange square) = YOU (80%) - test: press
    one arrow key: it should move one tile and the gauge
     should drop
- obj 12 (blue irregular shape (24 cells)) = INVENTORY
    (80%) - test: watch it after touching the modifier
- obj 4 (blue 6-cell shape) = GOAL (75%) - test: get the
     right thing into it and see if the level ends
- obj 15 (yellow bar) = MOVES LEFT (75%) - test: take
    any action and check it shrinks by one unit
- obj 16, 17, 18 (red square) = LIVES (75%) - test:
    watch it when the gauge runs out or you fail
- obj 6 (white/light grey plus) = MODIFIER (67%) - test:
     step onto it, then check whether the inventory icon
     changed
```

```
BRIEFING (clicks)
MEASURED (certain):
- no tile grid -> free movement. Open space = black (81%
     of screen).
- all 4 main objects share one open space; straight
    paths between them are ALL CLEAR of rock
- the grey areas are not open floor (likely walls)
- obj 4 (purple dotted ring) encloses an EMPTY 5x5 space
     -- exactly the size of: obj 16 (white/purple
    diamond), obj 25 (purple/magenta disc), obj 36 (dark
     grey/purple diamond)
- a light grey line connects obj 16 (white/purple
    diamond) to obj 25 (purple/magenta disc)
- a light grey line connects obj 25 (purple/magenta disc
    ) to obj 36 (dark grey/purple diamond)
- obj 25 (purple/magenta disc) sits at the MIDPOINT of
    obj 16 (white/purple diamond) and obj 36 (dark grey/
    purple diamond) (error 0.5 cells) -> it is held
    between them; moving either end should move it to
    the new midpoint
- obj 16, 36 (white/purple diamond; dark grey/purple
    diamond) have the same shape in different colours (
    white/purple vs dark grey/purple)
GUESSES (check with one action):
- obj 4 (purple dotted ring) = GOAL (80%) - test: get
    the right thing into it and see if the level ends
- obj 16, 36 (white/purple diamond; dark grey/purple
    diamond) = HANDLE (click) (80%) - test: click an
    empty spot once: the selected handle should jump
    there
- obj 1 (white bar) = MOVES LEFT (75%) - test: take any
    action and check it shrinks by one unit
- obj 25 (purple/magenta disc) = CARRIED THING (75%) -
    test: move one handle: it should slide to the new
    midpoint
```

B System Configuration and Hyperparameters

Table 5 documents the primary execution parameters governing the scored benchmark evaluation.

System Configuration Parameter	Operational Value
Concurrent games / Active GPU slots	25 games / 10 slots
Scheduler quantum allocation	20 model calls per round
Action allocation ceiling per game	2,000 actions
Maximal steps per `play()` path	$\leq$100 actions
Turn reply budget / Inner requests	12k tokens / 12 calls
Turn preemption thinking threshold	16k tokens
Context drain threshold / target	118k tokens / 55k tokens
Context maximum window size	131,072 tokens
Visual map rendering scale	10 pixels per grid cell
Briefing line limit / Short-view ceiling	20 lines / 600 tokens
Symbolic memory caps (G/P/H/F)	150 / 200 / 400 / 300 tokens
Sampling temperature / top-p / top-k	$T = 0.6$ / $p = 0.95$ / $k = 20$
Serving engine and precision	SGLang, W4A16, FP8 KV cache
Speculative decoding configuration	EAGLE (3 speculative draft steps)

Table 5: System hyperparameter settings deployed in the official evaluation runtime.

C Artifacts and Reproducibility

All empirical findings, telemetry traces, and figures in this manuscript are fully reproducible using the scripts in `Writing/scripts/`:

- `collect_data.py`: Ingests the Kaggle submission log, per-game benchmark tables, and perception lab evaluation rubrics.
- `extract_curves.py`: Extracts wall-clock level completion trajectories from raw execution logs.
- `make_perception_figure.py`: Executes the host-side perception engine on raw game environments to

generate segmented objects, spatial maps, and structured briefings.

- `plot_results.py`: Generates all publication-grade figures in vector PDF and high-resolution raster formats.

All code, model serving scripts, evaluation environments, and experimental logs are publicly accessible under the Apache-2.0 license at https://github.com/Harsidak/SARBLOH.