

Sub Queries Hands-on Solutions

Q1: SELECT EMPNO,ENAME,DEPTNO FROM EMP WHERE DEPTNO=(SELECT DEPTNO FROM EMP WHERE ENAME='SMITH');

Q2: SELECT * FROM EMP WHERE SAL>(SELECT AVG(SAL) FROM EMP);

Q3: SELECT ENAME,JOB FROM EMP E WHERE EXISTS (SELECT 1 FROM EMP X WHERE X.MGR=E.EMPNO);

Q4: SELECT * FROM EMP WHERE SAL<ALL(SELECT SAL FROM EMP WHERE DEPTNO=10);

Q5: SELECT * FROM EMP WHERE (DEPTNO,MGR)=(SELECT DEPTNO,MGR FROM EMP WHERE ENAME='SMITH') AND ENAME<>(SELECT ENAME FROM EMP WHERE DEPTNO=MGR);

Q6: SELECT EMPNO,ENAME FROM EMP WHERE DEPTNO IN (SELECT DEPTNO FROM EMP WHERE ENAME LIKE '%R%');

Q7: SELECT ENAME,DEPTNO,JOB FROM EMP WHERE DEPTNO=(SELECT DEPTNO FROM DEPT WHERE LOC='NEW YORK');

Q8: ACCEPT P_LOC CHAR PROMPT 'Enter Location:'
SELECT ENAME FROM EMP WHERE DEPTNO=(SELECT DEPTNO FROM DEPT WHERE LOC='&P_LOC');

Q9: SELECT ENAME,SAL FROM EMP WHERE MGR=(SELECT EMPNO FROM EMP WHERE ENAME='KING');

Q10: SELECT * FROM EMP WHERE DEPTNO=(SELECT DEPTNO FROM EMP WHERE ENAME='JAMES');

Q11: SELECT * FROM EMP E WHERE SAL<(SELECT AVG(SAL) FROM EMP WHERE DEPTNO=E.DEPTNO);

Q12: SELECT LOC,(SELECT AVG(SAL) FROM EMP WHERE EMP.DEPTNO=DEPT.DEPTNO) AVG_SAL FROM DEPT;

Q13: SELECT * FROM (SELECT * FROM EMP ORDER BY SAL) WHERE ROWNUM<=&N;

Q14: SELECT * FROM EMP E1 WHERE &N>(SELECT COUNT(*) FROM EMP E2 WHERE E2.EMPNO>E1.EMPNO);

Q15: SELECT * FROM EMP WHERE DEPTNO=(SELECT DEPTNO FROM DEPT WHERE LOC='DALLAS') ORDER BY ENAME;

Q16: SELECT E.*,V.AVGSAL FROM EMP E JOIN (SELECT DEPTNO,AVG(SAL) AVGSAL FROM EMP GROUP BY DEPTNO) V ON E.DEPTNO=V.DEPTNO;

Q17: WITH D AS (SELECT DEPTNO,SUM(SAL) SS FROM EMP GROUP BY DEPTNO),A AS (SELECT AVG(SAL) AV FROM EMP GROUP BY DEPTNO)