

# image\_fourier\_2

December 5, 2022

```
[2]: import numpy as np
import matplotlib.pyplot as plt
from skimage.draw import disk # circle - for older version of skimage
from skimage.feature import match_template
from skimage import io, data, img_as_float, img_as_ubyte, restoration
from scipy.signal import convolve2d
from scipy.fft import fft2, fftshift, ifft2
```

## 1 High pass filtering


```
[3]: im = img_as_float(data.camera())

r = 100
imw = np.ones_like(im)
cx, cy = np.round(np.array(im.shape)/2)
# rr, cc = circle(cx, cy, r, im.shape) # for older version of skimage
rr, cc = disk((cx, cy), r, shape=im.shape)
imw[rr, cc] = 0

imfft = fftshift(fft2(im))
imm = np.log(np.abs(imfft))
imfft[imw==0] = 0
imf = np.abs(ifft2(imfft))

fig = plt.figure()
ax = fig.add_subplot(1, 2, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')

ax = fig.add_subplot(1, 2, 2)
p = plt.imshow(imf, cmap='gray')
c = plt.colorbar(orientation='horizontal')
```



## 2 Butterworth High Pass Filter


```
[4]: im = img_as_float(data.camera())

xs, ys = np.array(im.shape)
xl = np.linspace(0,xs,xs)
yl = np.linspace(0,ys,ys)
x, y = np.meshgrid(xl, yl)
x = (x-xs/2)/xs
y = (y-ys/2)/ys
n = 1
K = 0.1
imw = 1 / (1 + (K / (np.sqrt(x**2+y**2)**(2*n) )))

imfft = fftshift(fft2(im))
imfft = imfft * imw
imf = np.abs(iff2(imfft))
imm = np.log(np.abs(imfft))
imm = imm * imw

fig = plt.figure()
ax = fig.add_subplot(1, 2, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')
```

```
ax = fig.add_subplot(1, 2, 2)
p = plt.imshow(imf, cmap='gray')
c = plt.colorbar(orientation='horizontal')
```



### 3 Low pass filtering


```
[6]: im = img_as_float(data.camera())

r = 100
imw = np.zeros_like(im)
cx, cy = np.round(np.array(im.shape)/2)
# rr, cc = circle(cx, cy, r, im.shape) # for older version of skimage
rr, cc = disk((cx, cy), r, shape=im.shape)
imw[rr, cc] = 1

imfft = fftshift(fft2(im))
imm = np.log(np.abs(imfft))
imfft[imw==0] = 0
imf = np.abs(iff2(imfft))

fig = plt.figure()
ax = fig.add_subplot(1, 2, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')
```

```
ax = fig.add_subplot(1, 2, 2)
p = plt.imshow(imf, cmap='gray')
c = plt.colorbar(orientation='horizontal')
```



## 4 Gaussian Low Pass Filter

```
[7]: im = img_as_float(data.camera())

xs, ys = np.array(im.shape)
xl = np.linspace(0,xs,xs)
yl = np.linspace(0,ys,ys)
x, y = np.meshgrid(xl, yl)
x = (x-xs/2)/xs
y = (y-ys/2)/ys
s = 0.05
imw = np.exp(-(x**2+y**2)/(2*s**2))
# imw = np.exp(-((x/s)**2+(y/s)**2))

imfft = fftshift(fft2(im))
imfft = imfft * imw
imf = np.abs(iff2(imfft))
imm = np.log(np.abs(imfft))
imm = imm * imw


fig = plt.figure()
```

```

ax = fig.add_subplot(1, 2, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')

ax = fig.add_subplot(1, 2, 2)
p = plt.imshow(imf, cmap='gray')
c = plt.colorbar(orientation='horizontal')

```



## 5 Butterworth Low Pass Filter

```

[8]: im = img_as_float(data.camera())

xs, ys = np.array(im.shape)
xl = np.linspace(0,xs,xs)
yl = np.linspace(0,ys,ys)
x, y = np.meshgrid(xl, yl)
x = (x-xs/2)/xs
y = (y-ys/2)/ys
n = 1
K = 0.001
imw = 1 / (1 + ((np.sqrt(x**2+y**2)**(2*n) / K)))

imfft = fftshift(fft2(im))
imfft = imfft * imw
imf = np.abs(iff2(imfft))

```


```

imm = np.log(np.abs(imfft))
imm = imm * imw

fig = plt.figure()
ax = fig.add_subplot(1, 2, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')

ax = fig.add_subplot(1, 2, 2)
p = plt.imshow(imf, cmap='gray')
c = plt.colorbar(orientation='horizontal')

```



## 6 Correlation

```

[9]: im = img_as_float(data.camera())
imtemp = im[70:160,186:266]
imm = match_template(im, imtemp)

fig = plt.figure()
ax = fig.add_subplot(1, 3, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')

ax = fig.add_subplot(1, 3, 2)
p = plt.imshow(imtemp, cmap='gray')


```

```

c = plt.colorbar(orientation='horizontal')

ax = fig.add_subplot(1, 3, 3)
p = plt.imshow(imm, cmap='gray')
c = plt.colorbar(orientation='horizontal')

```



```

[10]: im = img_as_float(data.camera())
      imtemp = im[70:160,186:266]

      imm = np.log(np.abs(iff2(np.divide(fft2(im), fft2(imtemp,im.shape))))))
      imtempf = np.log(np.abs(fftshift(fft2(imtemp,im.shape))))


      fig = plt.figure()
      ax = fig.add_subplot(1, 4, 1)
      p = plt.imshow(im, cmap='gray')
      c = plt.colorbar(orientation='horizontal')

      ax = fig.add_subplot(1, 4, 2)
      p = plt.imshow(imtemp, cmap='gray')
      c = plt.colorbar(orientation='horizontal')

      ax = fig.add_subplot(1, 4, 3)
      p = plt.imshow(imtempf, cmap='gray')
      c = plt.colorbar(orientation='horizontal')

      ax = fig.add_subplot(1, 4, 4)
      p = plt.imshow(imm, cmap='gray')
      c = plt.colorbar(orientation='horizontal')

```



## 7 Deconvolution


```
[11]: im = img_as_float(data.camera())
kernel = np.ones((5,5)) / 25
im = convolve2d(im, kernel, 'same')

im += 0.1 * im.std() * np.random.standard_normal(im.shape)
imf, _ = restoration.unsupervised_wiener(im, kernel)

fig = plt.figure()
ax = fig.add_subplot(1, 2, 1)
p = plt.imshow(im, cmap='gray')
c = plt.colorbar(orientation='horizontal')

ax = fig.add_subplot(1, 2, 2)
p = plt.imshow(imf, cmap='gray')
c = plt.colorbar(orientation='horizontal')
```





[ ]: