
PSyclone Documentation

Release 2.3.1

**Andrew Coughtrie, Rupert Ford, Joerg Henrichs, Iva Kavcic,
Andrew Porter and Sergi Siso**

Jul 20, 2023

TABLE OF CONTENTS

1	Introduction	1
2	Getting Going	3
2.1	Download	3
2.2	Environment	3
2.3	Dependencies	5
2.4	Configuration	8
2.5	Test	8
2.6	Run	8
3	The psyclone command	11
3.1	Running	11
3.2	Basic Use	12
3.3	Choosing the API	12
3.4	File output	13
3.5	Algorithm files with no invokes	13
3.6	Kernel search directory	13
3.7	Transformation script	14
3.8	Fortran line length	14
3.9	Distributed memory	15
3.10	Automatic Profiling Instrumentation	15
3.11	Outputting of Transformed Kernels	15
3.12	Fortran INCLUDE Files and Modules	15
3.13	C Pre-processor #include Files	16
4	Tutorial	17
5	Examples	19
5.1	Compilation	19
5.2	GOcean	21
5.3	LFRic	23
5.4	NEMO	28
5.5	PSyIR	29
6	Libraries	31
6.1	Available libraries	31
6.2	Dependencies	32
6.3	Compilation	32
7	System-specific Set-up for Users	35
7.1	Installing dependencies	35

7.2	Installing PSyclone	36
7.3	Common installation	36
8	Kernel layer	37
8.1	API	37
8.2	Metadata	38
9	Algorithm layer	41
9.1	API	41
9.2	Limitations	43
10	PSy layer	45
10.1	Code Generation	45
10.2	API	46
11	Built-ins	51
11.1	Example	51
11.2	Supported Built-in operations	55
11.3	Adding new Built-in operations	55
12	LFRic (Dynamo0.3) API	57
12.1	Algorithm	57
12.2	Mixed Precision	62
12.3	PSy-layer	66
12.4	Kernel	66
12.5	Built-ins	89
12.6	Boundary Conditions	108
12.7	Conventions	109
12.8	Configuration	109
12.9	Transformations	111
13	GOcean1.0 API	121
13.1	Introduction	121
13.2	The GOcean Library	121
13.3	Algorithm	125
13.4	Kernel	126
13.5	Built-ins	132
13.6	Conventions	132
13.7	Configuration	133
13.8	Transformations	135
14	NEMO API	141
14.1	Algorithm	141
14.2	Constructing the PSyIR	141
14.3	Example	142
14.4	Transformations	143
14.5	Limitations	149
15	PSyIR : The PSyclone Internal Representation	151
15.1	PSyIR Nodes	151
15.2	Node Descriptions	152
15.3	Text Representation	153
15.4	Tree Navigation	154
15.5	DataTypes	158
15.6	Symbols and Symbol Tables	160

15.7	Creating PSyIR	163
15.8	Comparing PSyIR nodes	165
15.9	Modifying the PSyIR	166
16	Transformations	169
16.1	Finding	169
16.2	Standard Functionality	170
16.3	Available transformations	170
16.4	Algorithm-layer	208
16.5	Kernels	208
16.6	Applying	212
16.7	OpenMP	216
16.8	OpenCL	217
16.9	OpenACC	219
16.10	SIR	220
17	Distributed Memory	221
17.1	Correctness	221
17.2	Performance	221
17.3	Implementation	222
17.4	Control	222
17.5	Status	222
18	PSyclone Kernel Tools	223
18.1	The psyclone-kern Command	223
18.2	Kernel-stub Generator	224
18.3	Algorithm Generator	230
19	Line length	233
19.1	Script	233
19.2	Interactive	233
19.3	Limitations	234
20	Fortran Naming Conventions	235
21	API	237
21.1	The generator module	237
21.2	The parse module	238
21.3	The transformations module	239
21.4	The psyGen module	259
21.5	The alg_gen module	260
21.6	The line_length module	261
22	PSyData API	263
22.1	Read-Only Verification	264
22.2	NAN Test	265
23	Profiling	267
23.1	Interface to Third Party Profiling Tools	267
23.2	Required Modifications to the Program	268
23.3	Profiling Command-Line Options	269
23.4	Profiling in Scripts - ProfileTrans	272
23.5	Naming Profiling Regions	272
24	PSy Kernel Extractor (PSyKE)	275

24.1	Introduction	275
24.2	Use	277
24.3	Extraction Libraries	280
25	Configuration	283
25.1	Options	283
	Bibliography	289
	Python Module Index	291
	Index	293

INTRODUCTION

PSyclone, the PSy code generator, is being developed for use in finite element, finite volume and finite difference codes. PSyclone development started with the aim to support the emerging API in the GungHo project for a finite element dynamical core.

The [GungHo project](#) was initiated in 2011 to address challenges of weather and climate prediction on the next generation of supercomputers. The project ran for 5 years as a collaboration between the Met Office, NERC (via NERC funded academics) and STFC. It laid a foundation for redesign of the heart of the Met Office's Unified Model, known as the dynamical core, from the choices of numerical methods and model grids to the implementation of parallel algorithms that will scale to millions of cores.

The software infrastructure based on the GungHo project recommendations is now being developed in the [LFRic project](#) and is expected to start preparations for operational deployment in 2025. Its development is led by the requirements to support multiple meshes and element types, thus allowing for future model development.

GungHo also proposed a novel separation of concerns for the software implementation of the dynamical core. This approach distinguishes between three layers: the Algorithm layer, the Kernel layer and the Parallelisation System (PSy) layer. Together this separation is termed PSyKAI.

The Algorithm layer specifies the algorithm that the scientist would like to run (in terms of calls to kernel routines and built-in operations) and logically operates on full fields.

The Kernel layer provides the implementation of the code kernels as subroutines. These subroutines operate on local fields (a set of elements, a vertical column, or a set of vertical columns, depending on the kernel).

The PSy layer sits in-between the algorithm and kernel layers and its primary role is to provide node-based parallel performance for the target architecture. The PSy layer can be optimised for a particular hardware architecture, such as multi-core, many-core, GPGPUs, or some combination thereof with no change to the algorithm or kernel layer code. This approach therefore offers the potential for portable performance.

Rather than writing the PSy layer manually, the PSyclone code generation system can help a user to optimise the code for a particular architecture (by providing optimisations such as blocking, loop merging, inlining etc), or alternatively, generate the PSy layer automatically.

PSyclone is also being extended to support an API being developed in the *GOcean project* <<https://www.hartree.stfc.ac.uk/publications/case-studies/2016/07/15/developing-next-generation-ocean-modelling-techniques>> for two finite difference ocean model benchmarks, one of which is based on the [NEMO](#) ocean model.

GETTING GOING

2.1 Download

The following instructions are intended for a PSyclone user who wants to work with a released version of the code. If you are a developer or wish to test a specific branch of PSyclone from the GitHub repository please see [Installation](#) in the [Developer Guide](#).

PSyclone is available on the Python Package Index ([PyPI](#)) and is hosted on GitHub:

`https://github.com/stfc/PSyclone`

The latest release is 2.3.1 and the latest stable version is on the master branch.

There are two ways to install PSyclone. The first one is directly from PyPI using pip install, see [Installation from PyPI](#) for more detailed information.

Alternatively, PSyclone can be downloaded from GitHub - either see 2.3.1 in the Tags [tab](#) on the PSyclone page or download and extract the latest release of PSyclone directly, e.g.

```
> wget https://github.com/stfc/PSyclone/archive/2.3.1.tar.gz
> tar xzf 2.3.1.tar.gz
> ls
PSyclone-2.3.1
```

After the source package is downloaded and unpacked, it can be installed using pip install, albeit in a slightly different way to the PyPI installation, see [Installation from source](#) for more detailed information.

Hereon the location where you download or clone PSyclone (including the PSyclone directory itself) will be referred to as <PSYCLONEHOME>.

2.2 Environment

In order to use PSyclone (including running the test suite and building documentation) you will need to install it. Before starting the installation process, please refer to the [Dependencies](#) section below.

2.2.1 Installation from PyPI

The simplest, and recommended, installation process is from [PyPI](#) using pip:

```
> pip install psyclone
```

for the latest available release, or:

```
> pip install psyclone==X.Y.Z
```

where X.Y.Z is the specific PSyclone release version (e.g. 2.3.1).

By default, pip will attempt a system-wide install. If you wish to do a user-local install instead then supply the `--user` flag:

```
> pip install --user psyclone
```

PSyclone can also be installed to a specific location using `--install-option` (see pip [documentation](#) for more detailed information):

```
> pip install --install-option="--prefix=/my/install/path" psyclone==X.Y.Z
```

Depending on the installation option (e.g. system-wide, user), PSyclone will be installed in different *locations*.

2.2.2 Installation from source

PSyclone can also be installed from a *downloaded* release or repository clone. The simplest way to do this is to use pip with the supplied `setup.py`:

```
> cd <PSYCLONEHOME>
> pip install .
```

As above, this attempts a system-wide install. For a user-local install use:

```
> pip install --user .
```

and for a specific location use:

```
> pip install --install-option="--prefix=/my/install/path" .
```

If for some reason you would rather not use pip then you can run the setup manually:

```
> python setup.py install
```

or, if you do not have root access:

```
> python setup.py install --user
```

or:

```
> python setup.py install --install-option="--prefix=/my/install/path"
```

As for the *PyPI installation*, different installation options lead to different *locations* of PSyclone installation.

2.2.3 Location and structure of PSyclone installation

Location of installed Pyclone scripts, modules and other accompanying resources is similar to other Python packages:

- The *psyclone script* is located in `<python-base-prefix>/bin` directory (depending on your Linux distribution, you may need to add this location to your `$PATH`).
- The PSyclone Python modules are located in `<python-base-prefix>/lib/pythonX.Y/site-packages` directory (where X.Y is the version of Python that you are using).
- The *configuration file*, *examples*, *tutorial* and *libraries* are installed in `<python-base-prefix>/share/psyclone` directory.

For a system-wide installation on Linux, `<python-base-prefix>` will likely be `/usr` and if a user-local installation is performed it will likely be `~/local`.

For an installation to a specific location, `<python-base-prefix>` is simply the path given to the `--install-option="--prefix=/my/install/path"`. Note that if using this method, it will be necessary to take further action to ensure PSyclone can find the *configuration file* installed as a part of this process.

2.2.4 Windows environment

PSyclone can also be installed in [Python Windows environment](#) using pip as described above. There are some differences in directory structure from Linux, for instance the script directory is usually called `Scripts` instead of `bin` and the modules directory `Lib` instead of `lib`.

Installation in an [Anaconda Python](#) environment on Windows also needs to be done using pip as `conda install` for PSyclone is currently not supported.

2.3 Dependencies

PSyclone is written in Python so needs Python 3 to be installed on the target machine. PSyclone is regularly tested with Python 3.7, 3.8 and 3.11 but should work with any version `>= 3.6`. (The last PSyclone release to support Python 2.7 was version 2.1.0.)

PSyclone immediately relies on four external Python packages; `configparser`, `fparser`, `sympy`, and `pyparsing`. The easiest way to satisfy the Python dependencies is to use the [PyPI installation](#) and pip.

If everything is working correctly then using pip to install PSyclone:

```
> pip install psyclone
```

will automatically install the Python dependencies.

Warning: Starting with the release 1.6.1, PSyclone will install a specific release of `fparser` (version specified in the `setup.py` script).

In addition to the mandatory dependencies just described, PSyclone also has optional dependencies on both `graphviz` and `termcolor`. PSyclone can use `graphviz` to produce a visualisation of a schedule's dependency graph. If this is desired then the Python package `graphviz` (for the Python bindings) as well as the `graphviz` package itself must be installed. If the `graphviz` package is not available then the associated PSyclone routines will return silently and no visualisations will be produced. The Python package `termcolor` is used for pretty-printing a schedule in terminals that support coloured text. If the package is not available then the schedule is simply printed in plain text without colour highlighting.

2.3.1 System-specific set-up

System-specific Set-up for Users instructions are available for Ubuntu 14.04.2 and OpenSUSE 42.2.

2.3.2 fparser

The fparser package (<https://github.com/stfc/fparser>) is a Fortran parser originally developed as a part of the f2py project.

fparser is available from the Python Package Index and thus may be installed using pip (<https://packaging.python.org/installing/#requirements-for-installing-packages>):

```
> pip install fparser
```

If you do not have sufficient permissions to perform a system-wide install then you can instruct pip to do a user-local install:

```
> pip install --user fparser
```

Should you wish to remove fparser then simply do:

```
> pip uninstall fparser
```

If you have already installed fparser and want to upgrade to the latest version simply do:

```
> pip install fparser --upgrade
```

Warning: Due to the above-mentioned reliance of PSyclone on a specific fparser release, it is not advisable to install fparser independently unless it is not to be used with PSyclone. An exception is installation of PSyclone from source for development purposes, see [Installation](#) in the [Developer Guide](#).

2.3.3 pyparsing

PSyclone requires pyparsing, a library designed to allow parsers to be built in Python. PSyclone uses pyparsing to parse Fortran regular expressions as fparser does not fully parse these (see [here](#) for more information).

PSyclone has been tested with pyparsing versions 1.5.2, 2.0.1 and 2.2.0.

You can test whether pyparsing is already installed on your machine by typing `import pyparsing` from the Python command line. If pyparsing is installed, this command will complete successfully. If pyparsing is installed you can check its version by typing `pyparsing.__version__` after successfully importing it.

If pyparsing is not installed on your system then it may be installed from the Python Package Index using pip:

```
> pip install pyparsing
```

Should you wish to, uninstalling is simply performed by doing:

```
> pip uninstall pyparsing
```

If you do not have sufficient privileges for a system-wide install then you can instruct pip to do a user-local install:

```
> pip install --user pyparsing
```

Alternatively, you could follow [these instructions](#).

2.3.4 SymPy

PSyclone requires sympy, a library for symbolic mathematics. PSyclone uses sympy to reason about expression being equal or not, e.g. $i+j$ and $j+i$. PSyclone has been tested with sympy versions 1.7.1.

You can test whether sympy is already installed on your machine by typing `import sympy` from the Python command line. If sympy is installed, this command will complete successfully. If sympy is installed you can check its version by typing `sympy.__version__` after successfully importing it.

If sympy is not installed on your system then it may be installed from the Python Package Index using pip:

```
> pip install sympy
```

Should you wish to, uninstalling is simply performed by doing:

```
> pip uninstall sympy
```

If you do not have sufficient privileges for a system-wide install then you can instruct pip to do a user-local install:

```
> pip install --user sympy
```

Alternatively, you could follow the instructions on the [SymPy web page](#).

2.3.5 Graphviz

The data dependencies of a PSyIR schedule determine the validity of changes to this schedule. PSyclone supports the visualisation of these dependencies as a graph using graphviz. This visualisation is not needed to use PSyclone.

If the Python bindings to graphviz are not installed on your system then it may be installed from the Python Package Index using pip:

```
> sudo pip install graphviz
```

Should you wish to, uninstalling is simply performed by doing:

```
> sudo pip uninstall graphviz
```

If you do not have sufficient privileges for a system-wide install then you can instruct pip to do a user-local install:

```
> pip install --user graphviz
```

If graphviz itself is not installed on your system and your system supports the apt package manager then see below, otherwise please refer to the download and install instructions which are available [here](#).

If your system supports the apt package manager then it can be installed and removed in the following way:

```
> sudo apt install graphviz
> sudo apt remove graphviz
```

2.3.6 termcolor

By default, the `view()` method available on any PSyIR (PSyclone Internal Representation) object prints a plain-text representation to standard-out. However, if the `termcolor` package is available then PSyclone uses this to add colour highlighting to the output text.

Installation (and uninstallation) of this package can be done via `pip` in exactly the same way as for `graphviz`, as described above.

2.4 Configuration

Various aspects of PSyclone are configured through a configuration file, `psyclone.cfg`. The default version of this file is installed to `<python-base-prefix>/shared/psyclone/` during the installation process. Similar to what is described [above](#), if a system-wide installation is being performed then this will likely be `/usr/share/psyclone/`. If a user-local installation is performed (`--user` flag to `pip install`) then the location will be something like `~/.local/share/psyclone/`.

Warning: If PSyclone is installed to a non-standard location (e.g. by specifying the `--install-option="--prefix=.` option to `pip install`) then PSyclone will not be able to find the configuration file at execution time. There are two solutions to this: 1. copy the configuration file to a location where PSyclone will find it (see [Configuration](#)) or 2. set the `PSYCLONE_CONFIG` environment variable to the full-path to the configuration file, e.g.:

```
> export PSYCLONE_CONFIG=/some/path/PSyclone/config/psyclone.cfg
```

Warning: When installing in ‘editable’ mode (`-e` flag to `pip`), `pip` does *not* install the configuration file. You will have to take one of the two actions described above.

See [Configuration](#) for details of the settings contained within the config file.

2.5 Test

PSyclone contains an extensive test suite, but this test suite is not part of a standard installation. If you want to run the full test suite, you need to install PSyclone from source, see [above](#) or [Installation](#) in the [Developer Guide](#).

2.6 Run

You are now ready to try running PSyclone on the [examples](#). One way of doing this is to use the `psyclone` driver script. Assuming it is on your `PATH`:

```
> psyclone
usage: psyclone [-h] [-oalg OALG] [-opsy OPSY] [-okern OKERN] [-api API]
               [-s SCRIPT] [-d DIRECTORY] [-I INCLUDE] [-l {off,all,output}]
               [-dm] [-nodm] [--kernel-renaming {multiple,single}]
               [--profile {invokes,kernels}] [--config CONFIG] [--version]
               filename
psyclone: error: the following arguments are required: filename
```

As indicated above, the `psyclone` script takes the name of the Fortran source file containing the algorithm specification (in terms of calls to `invoke()`). It parses this, finds the necessary kernel source files and produces two Fortran files. The first contains the *PSy, middle layer* and the second a re-write of the *algorithm code* to use that layer. These files are named according to the user-supplied arguments (options `-oalg` and `-opsy`). If those arguments are not supplied then the script writes the generated/re-written Fortran to the terminal. For details of the other command-line arguments please see the *The `psyclone` command* Section.

Examples are provided in the `examples` directory of the PSyclone Git repository - if you have cloned the repository then `EGS_HOME` in what follows is the root PSyclone directory. Alternatively, if you have installed PSyclone using `pip` then they may be found in the `share/psyclone` directory under your Python installation (see *above* for location of PSyclone installation). In this case you should copy the whole `examples` directory to some convenient location (hereafter called `EGS_HOME`) before attempting to carry out the following instructions. Depending on your precise setup, you may also need to set `PSYCLONE_CONFIG` to the full-path to the PSyclone configuration file (see *Configuration*).

There are seven subdirectories, three of which (`lfric`, `gocean` and `nemo`) correspond to the different APIs/domains that are supported by PSyclone. (Note, that we are currently in the process of renaming the `dynamo0.3` API to `lfric`.) In this case we are going to use one of the LFRic examples:

```
> cd <EGS_HOME>/examples/lfric/eg1
> psyclone -api dynamo0.3 -d ../code -nodm -oalg alg.f90 \
  -opsy psy.f90 ./single_invoke.x90
```

You should see two new files created, called `alg.f90` (containing the re-written algorithm layer) and `psy.f90` (containing the generated PSy- or middle-layer). Since this is an LFRic example the Fortran source code has dependencies on the LFRic system and therefore cannot be compiled stand-alone.

The PSy-layer that PSyclone creates is constructed using the PSyclone Internal Representation (*PSyIR*). Accessing this is demonstrated by the `print_psyir_trans.py` script in the second LFRic example:

```
> cd <EGS_HOME>/examples/lfric/eg2
> psyclone -api dynamo0.3 -d ../code -s ./print_psyir_trans.py \
  -opsy psy.f90 -oalg alg.f90 ./multi_invoke_mod.x90
```

Take a look at the `print_psyir_trans.py` script for more information. *Hint*; you can insert a single line in that script in order to break into the Python interpreter during execution: `import pdb; pdb.set_trace()`. This then enables interactive exploration of the PSyIR if you are interested. Alternatively, you can play with some interactive examples on [Binder](#).

THE PSYCLONE COMMAND

The simplest way to run PSyclone is to use the `psyclone` command. If you installed PSyclone using `pip` then this command should be available on your `PATH` (see [Environment](#) for more details). Alternatively it can be found in the `<PSYCLONEHOME>/bin` directory. The command takes an algorithm file as input and outputs modified algorithm code and generated PSy code. This section walks through its functionality.

3.1 Running

The `psyclone` command is an executable script designed to be run from the command line, e.g.:

```
> psyclone <args>
```

The optional `-h` argument gives a description of the options provided by the command:

```
> psyclone -h
usage: psyclone [-h] [-oalg OALG] [-opsy OPSY] [-okern OKERN] [-api API]
               [-s SCRIPT] [-d DIRECTORY] [-I INCLUDE] [-l {off,all,output}]
               [-dm] [-nodm] [--kernel-renaming {multiple,single}]
               [--profile {invokes,kernels}] [--config CONFIG] [--version]
               filename
```

Run the PSyclone code generator on a particular file

positional arguments:

filename algorithm-layer source code

optional arguments:

`-h, --help` show this help message and exit
`-oalg OALG` filename of transformed algorithm code
`-opsy OPSY` filename of generated PSy code
`-okern OKERN` directory in which to put transformed kernels,
 default is the current working directory.
`-api API` choose a particular api from ['dynamo0.3',
 'gocean1.0', 'nemo'], default 'dynamo0.3'.
`-s SCRIPT, --script SCRIPT`
 filename of a PSyclone optimisation script
`-d DIRECTORY, --directory DIRECTORY`
 path to a root directory structure containing kernel
 source code. Multiple roots can be specified by using
 multiple `-d` arguments.
`-I INCLUDE, --include INCLUDE`

```
        path to Fortran INCLUDE or module files
-l {off,all,output}, --limit {off,all,output}
        limit the Fortran line length to 132 characters
        (default 'off'). Use 'all' to apply limit to both
        input and output Fortran. Use 'output' to apply
        line-length limit to output Fortran only.
-dm, --dist_mem      generate distributed memory code
-nodm, --no_dist_mem do not generate distributed memory code
--kernel-renaming {multiple,single}
        Naming scheme to use when re-naming transformed
        kernels
--profile {invokes,kernels}, -p {invokes,kernels}
        Add profiling hooks for either 'kernels' or 'invokes'
--config CONFIG      Config file with PSyclone specific options.
--version, -v        Display version information (2.3.1)
```

3.2 Basic Use

The simplest way to use psyclone is to provide it with an algorithm file:

```
> psyclone alg.f90
```

If the algorithm file is invalid for some reason, the command should return with an appropriate error. For example, if we use the Python psyclone-kern script as an algorithm file we get the following:

```
> psyclone <PSYCLONEHOME>/bin/psyclone-kern
Parse Error: algorithm.py:parse_fp2: Syntax error in file '<PSYCLONEHOME>/bin/psyclone-kern':
at line 1
>>>#!/usr/bin/env python
```

If the algorithm file is valid then the modified algorithm code and the generated PSy code will be output to the terminal screen.

3.3 Choosing the API

In the previous section we relied on PSyclone using the default API. The default API, along with the supported APIs can be seen by running the psyclone command with the -h option.

If you use a particular API frequently and it is not the default then you can change the default by creating a copy of the default psyclone.cfg file and editing it. See [Configuration](#) for more details.

If your code uses an API that is different to the default then you can specify this as an argument to the psyclone command.

```
> psyclone -api gocean1.0 alg.f90
```

3.4 File output

By default the modified algorithm code and the generated PSy code are output to the terminal. These can instead be output to files by using the `-oalg <file>` and `-opsy <file>` options, respectively. For example, the following will output the generated PSy code to the file ‘psy.f90’ but the algorithm code will be output to the terminal:

```
> psyclone -opsy psy.f90 alg.f90
```

If PSyclone is being used to transform Kernels then the location to write these to is specified using the `-okern <directory>` option. If this is not supplied then they are written to the current working directory. By default, PSyclone will overwrite any kernel of the same name in that directory. To change this behaviour, the user can use the `--no_kernel_clobber` option. This causes PSyclone to re-name any transformed kernel that would clash with any of those already present in the output directory.

3.5 Algorithm files with no invokes

If psyclone is provided with a file that contains no invoke calls then the command outputs a warning to stdout and copies the input file to stdout, or to the specified algorithm file (if the `-oalg <file>` option is used). No PSy code will be output. If a file is specified using the `-opsy <file>` option this file will not be created.

```
> psyclone -opsy psy.f90 -oalg alg_new.f90 empty_alg.f90
Warning: 'Algorithm Error: Algorithm file contains no invoke() calls: refusing to
generate empty PSy code'
```

3.6 Kernel search directory

When an algorithm file is parsed, the parser looks for the associated kernel files. The way in which this is done requires that any user-defined kernel routine (as opposed to *Built-ins*) called within an invoke must have an explicit use statement. For example, the following code gives an error:

```
> cat no_use.f90
program no_use
  call invoke(testkern_type(a,b,c,d,e))
end program no_use
> psyclone -api gocean1.0 no_use.f90
"Parse Error: kernel call 'testkern_type' must either be named in a use statement or be a recognised built-
↳in (one of '[]' for this API)"
```

(If the chosen API has any *Built-ins* defined then these will be listed within the `[]` in the above error message.) If the name of the kernel is provided in a use statement then the parser will look for a file with the same name as the module in the use statement. In the example below, the parser will look for a file called “testkern.f90” or “testkern.F90”:

```
> cat use.f90
program use
  use testkern, only : testkern_type
  call invoke(testkern_type(a,b,c,d,e))
end program use
```

Therefore, for PSyclone to find kernel files, the module name of a kernel file must be the same as its filename. By default the parser looks for the kernel file in the same directory as the algorithm file. If this file is not found then an error is reported.

```
> psyclone use.f90
Kernel file 'testkern.[fF]90' not found in <location>
```

The `-d` option can be used to tell psyclone where to look for kernel files by supplying it with a directory. The execution will recurse from the specified directory path to look for the required file. There must be only one instance of the specified file within (or below) the specified directory:

```
> cd <PSYCLONEHOME>/src/psyclone
> psyclone -d . use.f90
More than one match for kernel file 'testkern.[fF]90' found!
> psyclone -d tests/test_files/dynamo0p3 -api dynamo0.3 use.f90
[code output]
```

Note: The `-d` option can be repeated to add as many search directories as is required, with the constraint that there must be only one instance of the specified file within (or below) the specified directories.

3.7 Transformation script

By default the psyclone command will generate ‘vanilla’ Algorithm-layer and PSy-layer code with unmodified kernels for the gocean1.0 and lfrc (dynamo0.3) APIs. For the nemo API, psyclone will not perform any transformations on the input code.

The `-s` option allows a Python script to be specified which can contain PSyclone transformations to transform the code. This option is discussed in more detail in the [Script](#) section.

3.8 Fortran line length

By default the psyclone command will generate Fortran code with no consideration of Fortran line-length limits. As the line-length limit for free-format Fortran is 132 characters, the code that is output may be non-conformant.

Line length is not an issue for many compilers as they allow compiler flags to be set which allow lines longer than the Fortran standard. However this is not the case for all compilers.

When either the `-l all` or `-l output` option is specified to the psyclone command, the output will be line wrapped so that the output lines are always within the 132 character limit.

The `-l all` additionally checks the parsed algorithm and kernel files for conformance and raises an error if they do not conform.

Line wrapping is not performed by default. There are two reasons for this. This first reason is that most compilers are able to cope with long lines. The second reason is that the line wrapping implementation could fail in certain pathological cases. The implementation and limitations of line wrapping are discussed in the [Limitations](#) section.

3.9 Distributed memory

By default the `psyclone` command will generate distributed memory (DM) code (i.e. parallelised using MPI). As with the choice of API, this default may be configured by editing `psyclone.cfg` - see [Configuration](#). Alternatively, whether or not to generate DM code can be specified as an argument to the `psyclone` command using the `-dm/--dist_mem` or `-nodm/--no_dist_mem` flags, respectively.

For details of PSyclone's support for generating DM code see [Distributed Memory](#).

3.10 Automatic Profiling Instrumentation

The `--profile` option allows the user to instruct PSyclone to automatically insert profiling calls within the generated PSy code. Two options are provided, `invokes` and `kernels`. The first of these causes PSyclone to insert profiling-start and -stop calls at the beginning and end of every generated invoke routine. The second puts profiling calls around every kernel call (including the associated loops). The generated code must be linked against the PSyclone profiling interface and the profiling tool itself. The application that calls the PSyclone-generated code is responsible for initialising and finalising the profiling library that is being used. For full details on the use of this profiling functionality please see the [Profiling](#) section.

3.11 Outputting of Transformed Kernels

When transforming kernels there are two use-cases to consider:

1. a given kernel will be transformed only once and that version then used from multiple, different Invokes and Algorithms;
2. a given kernel is used from multiple, different Invokes and Algorithms and is transformed differently, depending on the Invoke.

Whenever PSyclone is used to transform a kernel, the new kernel must be re-named in order to avoid clashing with other possible calls to the original. By default (`--kernel-renaming multiple`), PSyclone generates a new, unique name for each kernel that is transformed. Since PSyclone is run on one Algorithm file at a time, it uses the chosen kernel output directory (`-okern`) to ensure that names created by different invocations do not clash. Therefore, when building a single application, the same kernel output directory must be used for each separate invocation of PSyclone.

Alternatively, in order to support use case 1, a user may specify `--kernel-renaming single`: now, before transforming a kernel, PSyclone will check the kernel output directory and if a transformed version of that kernel is already present then that will be used. Note, if the kernel file on disk does not match with what would be generated then PSyclone will raise an exception.

3.12 Fortran INCLUDE Files and Modules

For the NEMO API, if the source code to be processed by PSyclone contains `INCLUDE` statements then the location of any `INCLUDE`'d files *must* be supplied to PSyclone via the `-I` or `--include` option. (This is necessary because `INCLUDE` lines are a part of the Fortran language and must therefore be parsed - they are not handled by any pre-processing step.) Multiple locations may be specified by using multiple `-I` flags, e.g.:

```
> psyclone api "nemo" -I /some/path -I /some/other/path alg.f90
```

If no include paths are specified then the directory containing the source file currently being parsed is searched by default. If the specified `INCLUDE` file is not found then PSyclone will abort with an appropriate error.

Attempting to specify `-I/--include` for any API other than NEMO will be rejected by PSyclone.

Currently, the PSyKAl-based APIs (LFRic and GOcean) will ignore (but preserve) `INCLUDE` statements in algorithm-layer code. However, `INCLUDE` statements in kernels will, in general, cause the kernel parsing to fail unless the file(s) referenced in such statements are in the same directory as the kernel file. Once kernel parsing has been re-implemented to use `fparser2` (issue #239) and the PSyclone Internal Representation then the behaviour will be the same as for the NEMO API.

Since PSyclone does not attempt to be a full compiler, it does not require that the code be available for any Fortran modules referred to by `use` statements. However, certain transformations *do* require that e.g. type information be determined for all variables in the code being transformed. In this case PSyclone *will* need to be able to find and process any referenced modules. To do this it searches in the directories specified by the `-I/--include` flags. (Currently this search assumes that a module named e.g. “my_mod” will be in a file named “my_mod.*90” - see issue #1895.)

3.13 C Pre-processor `#include` Files

PSyclone currently only supports Fortran input. As such, if a file to be processed contains CPP `#include` statements then it must first be processed by a suitable pre-processor before being passed to PSyclone. PSyclone will abort with an appropriate error if it encounters a `#include` in any code being processed. This is true of all of the PSyclone APIs.

TUTORIAL

PSyclone provides a tutorial, part of which uses Jupyter notebooks. This can be launched from a browser using binder: <https://mybinder.org/v2/gh/stfc/psyclone/master?filepath=tutorial%2Fnotebooks%2Fintroduction.ipynb/>.

If PSyclone is installed on your system then you can run the tutorial locally. First find the tutorial. If you have installed PSyclone using pip then the examples may be found in `share/psyclone/tutorial/notebooks` under your Python installation (see [here](#) for possible locations). Next, copy the tutorial to a local writable space (as the notebooks will be modified as you go through the tutorial) and change directory to this tutorial. Lastly, start up the tutorial's introduction jupyter-notebook `introduction.ipynb`.

Another part of the tutorial are [practicals](#) that provide hands-on introductions to various functionality contained in the *LFRic* and *NEMO* APIs. The sections in the included directories are worked through using PSyclone in a “normal” Linux environment.

Note: Hands-on practicals are not currently included in a PSyclone installation.

EXAMPLES

Various examples of the use of PSyclone are provided under the examples directory in the Git repository. If you have installed PSyclone using pip then the examples may be found in `share/psyclone/examples` under your Python installation (see [here](#) for possible locations).

Running any of these examples requires that PSyclone be installed on the host system, see Section [Getting Going](#). This section is intended to provide an overview of the various examples so that a user can find one that is appropriate to them. For details of what each example does and how to run each example please see the `README.md` files in the associated directories.

Alternatively, some of the examples have associated Jupyter notebooks that may be launched with Binder on [MyBinder](#). This is most easily done by following the links from the top-level [README](#).

For the purposes of correctness checking, the whole suite of examples may be executed using Gnu make (this functionality is used by GitHub Actions alongside the test suite). The default target is `transform` which just performs the PSyclone code transformation steps for each example. For those examples that support it, the `compile` target also requests that the generated code be compiled. The `notebook` target checks the various Jupyter notebooks using `nbconvert`.

Note: As outlined in the [Run](#) section, if working with the examples from a PSyclone installation, it is advisable to copy the whole examples directory to some convenient location before running them. If you have copied the examples directory but still wish to use make then you will also have to set the `PSYCLONE_CONFIG` environment variable to the full path to the PSyclone configuration file, e.g. `PSYCLONE_CONFIG=/some/path/psyclone.cfg make`.

5.1 Compilation

Some of the examples support compilation (and some even execution of a compiled binary). Please consult the `README.md` to check which ones can be compiled and executed.

As mentioned above, by default each example will execute the `transform` target, which performs the PSyclone code transformation steps. In order to compile the sources, use the target `compile`:

```
make compile
```

which will first perform the transformation steps before compiling any created Fortran source files. If the example also supports running a compiled and linked binary, use the target:

```
make run
```

This will first trigger compilation using the `compile` target, and then execute the program with any parameters that might be required (check the corresponding `README.md` document for details).

All Makefiles support the variables F90 and F90FLAGS to specify the compiler and compilation flags to use. By default, the Gnu Fortran compiler (gfortran) is used, and the compilation flags will be set to debugging. If you want to change the compiler or flags, just define these as environment variables:

```
F90=ifort F90FLAGS="-g -check bounds" make compile
```

To clean all compiled files (and potential output files from a run), use:

```
make clean
```

This will clean up in the examples directory. If you want to change compilers or compiler flags, you should run make allclean, see the section about *Dependencies* for details.

5.1.1 Supported Compilers

All examples have been tested with the following compilers. Please let the developers know if you have problems using a compiler that has been tested or if you are working with a different compiler so it can be recorded in this table.

Compiler	Version
Gnu Fortran compiler	9.3
Intel Fortran compiler	17, 21

5.1.2 Dependencies

Any required library that is included in PSyclone (typically the infrastructure libraries for the APIs, or *PSyData wrapper libraries*) will automatically be compiled with the same compiler and compilation flags as the examples.

Note: Once a dependent library is compiled, changing the compilation flags will not trigger a recompilation of this library. For example, if an example is first compiled with debug options, and later the same or a different example is compiled with optimisations, the dependent library will not automatically be recompiled!

All Makefiles support an allclean target, which will not only clean the current directory, but also all libraries the current example depends on.

Important: Using make allclean is especially important if the compiler is changed. Typically, one compiler cannot read module information from a different compiler, and then compilation will fail.

NetCDF

Some examples require NetCDF for compilation. Installation of NetCDF is described in detail in [the hands-on practicals documentation](#).

5.2 GOcean

5.2.1 Example 1: Loop transformations

Examples of applying various transformations (loop fusion, OpenMP, OpenMP Taskloop, OpenACC, OpenCL) to the semi-PSyKAI'd version of the Shallow benchmark. ("semi" because not all kernels are called from within `invoke()`'s.) Also includes an example of generating a DAG from an `InvokeSchedule`.

5.2.2 Example 2: OpenACC

This is a simple but complete example of using PSyclone to enable an application to run on a GPU by adding OpenACC directives. A Makefile is included which will use PSyclone to generate the PSy code and transformed kernels and then compile the application. This compilation requires that the `dl_esm_inf` library be installed/available - it is provided as a Git submodule of the PSyclone project (see [Installation](#) in the Developers' Guide for details on working with submodules).

The supplied Makefile also provides a second, `profile` target which performs the same OpenACC transformations but then encloses the whole of the resulting PSy layer in a profiling region. By linking this with the PSyclone NVTX profiling wrapper (and the NVTX library itself), the resulting application can be profiled using NVIDIA's `nvprof` or `nvvp` tools.

5.2.3 Example 3: OpenCL

Example of the use of PSyclone to generate an OpenCL driver version of the PSy layer and OpenCL kernels. The Makefile in this example provides a target (`make compile-ocl`) to compile the generated OpenCL code. This requires an OpenCL implementation installed in the system. Read the README provided in the example folder for more details about how to compile and execute the generated OpenCL code.

5.2.4 Example 4: Kernels containing use statements

Transforming kernels for use with either OpenACC or OpenCL requires that we handle those that access data and/or routines via module use statements. This example shows the various forms for which support is being implemented. Although there is support for converting global-data accesses into kernel arguments, PSyclone does not yet support nested use of modules (i.e. data accessed via a module that in turn imports that symbol from another module) and kernels that call other kernels (Issue #342).

5.2.5 Example 5: PSyData

This directory contains all examples that use the *PSyData API*. At this stage there are three runnable examples:

Example 5.1: Kernel data extraction

This example shows the use of kernel data extraction in PSyclone. It instruments each of the two invokes in the example program with the PSyData-based kernel extraction code. Detailed compilation instructions are in the README.md file, including how to switch from using the stand-alone extraction library to the NetCDF-based one (see [Extraction Libraries](#) for details).

The Makefile in this example will create the binary that extracts the data at run time, as well as two driver programs that can read in the extracted data, call the kernel, and compare the results. These driver programs are independent of the dl_esm_inf infrastructure library. These drivers can only read the corresponding file format, i.e. a NetCDF driver program cannot read in extraction data that is based on Fortran IO and vice versa.

Note: At this stage the driver program still needs the infrastructure library when compiling the kernels, see #1757.

Example 5.2: Profiling

This example shows how to use the profiling support in PSyclone. It instruments two invoke statements and can link in with any of the following profiling wrapper libraries: template, simple_timer, dl_timer, and DrHook (see [Interface to Third Party Profiling Tools](#)). The README.md file contains detailed instructions on how to build the different executables. By default (i.e. just using make without additional parameters) it links in with the template profiling library included in PSyclone. This library just prints out the name of the module and region before and after each invoke is executed. This example can actually be executed to test the behaviour of the various profiling wrappers, and is also useful if you want to develop your own wrapper libraries.

Example 5.3: Read-only-verification

This example shows the use of read-only-verification with PSyclone. It instruments each of the two invokes in the example program with the PSyData-based read-only-verification code. It uses the dl_esm_inf-specific read-only-verification library (lib/read_only/dl_esm_inf/).

Note: The update_field_mod subroutine contains some very buggy and non-standard code to change the value of some read-only variables and fields, even though the variables are all declared with intent(in). It uses the addresses of variables and then out-of-bound writes to a writeable array to actually overwrite the read-only variables. Using array bounds checking at runtime will be triggered by these out-of-bound writes.

The Makefile in this example will link with the compiled read-only-verification library. You can execute the created binary and it will print two warnings about modified read-only variables:

```
-----  
Double precision field b fld has been modified in main : update  
Original checksum: 4611686018427387904  
New checksum:      4638355772470722560  
-----  
-----  
Double precision variable z has been modified in main : update  
Original value: 1.0000000000000000  
New value:      123.0000000000000000  
-----
```

Example 5.4: Valid Number Verification (NaN Test)

This example shows the use of valid number verification with PSyclone. It instruments each of the two invokes in the example program with the PSyData-based NaN-verification code. It uses the `dl_esm_inf`-specific `nan_test` library (`lib/nan_test/dl_esm_inf/`).

Note: The `update_field_mod` subroutine contains code that will trigger a division by 0 to create NaNs. If the compiler should add floating point exception handling code, this will take effect before the NaN testing is done by the PSyData-based verification code.

The Makefile in this example will link with the compiled `nan_test` library. You can execute the created binary and it will print five warnings about invalid numbers at the indices 1 1, ..., 5 5:

```
PSyData: Variable a_fld has the invalid value
          Infinity at index/indices      1      1
mainupdate
...
```

5.2.6 Example 6: PSy-layer Code Creation using PSyIR

This example informs the development of the code generation of PSy-layer code using the PSyIR language backends.

5.3 LFRic

These examples illustrate the functionality of PSyclone for the LFRic domain.

5.3.1 Example 1: Basic Operation

Basic operation of PSyclone with an `invoke()` containing two kernels, one *user-supplied*, the other a *Built-in*. Code is generated both with and without distributed-memory support. Also demonstrates the use of the `-d` flag to specify where to search for user-supplied kernel code (see *The psyclone command* section for more details).

5.3.2 Example 2: Applying Transformations

A more complex example showing the use of PSyclone *transformations* to change the generated PSy-layer code. Provides examples of kernel-inlining and loop-fusion transformations.

5.3.3 Example 3: Distributed and Shared Memory

Shows the use of colouring and OpenMP for the Dynamo 0.3 API. Includes multi-kernel, named invokes with both user-supplied and built-in kernels. Also shows the use of Wchi function space metadata for coordinate fields in LFRic.

5.3.4 Example 4: Multiple Built-ins, Named Invokes and Boundary Conditions

Demonstrates the use of the special `enforce_bc` kernel which PSyclone recognises as a boundary-condition kernel.

5.3.5 Example 5: Stencils

Example of kernels which require stencil information.

5.3.6 Example 6: Reductions

Example of applying OpenMP to an InvokeSchedule containing kernels that perform reduction operations. Two scripts are provided, one of which demonstrates how to request that PSyclone generate code for a reproducible OpenMP reduction. (The default OpenMP reduction is not guaranteed to be reproducible from one run to the next on the same number of threads.)

5.3.7 Example 7: Column-Matrix Assembly Operators

Example of kernels requiring Column-Matrix Assembly operators.

5.3.8 Example 8: Redundant Computation

Example of the use of the redundant-computation and move transformations to eliminate and re-order halo exchanges.

5.3.9 Example 9: Writing to Discontinuous Fields

Demonstrates the behaviour of PSyclone for kernels that read and write quantities on horizontally-discontinuous function spaces. In addition, this example demonstrates how to write a PSyclone transformation script that only colours loops over continuous spaces.

5.3.10 Example 10: Inter-grid Kernels

Demonstrates the use of “inter-grid” kernels that prolong or restrict fields (map between grids of different resolutions), as well as the use of `ANY_DISCONTINUOUS_SPACE` function space metadata.

5.3.11 Example 11: Asynchronous Halo Exchanges

Example of the use of transformations to introduce redundant computation, split synchronous halo exchanges into asynchronous exchanges (start and stop) and move the starts of those exchanges in order to overlap them with computation.

5.3.12 Example 12: Code Extraction

Example of applying code extraction to Nodes in an Invoke Schedule:

```
> psyclone -nodm -s ./extract_nodes.py \
    gw_mixed_schur_preconditioner_alg_mod.x90
```

or to a Kernel in an Invoke after applying transformations:

```
> psyclone -nodm -s ./extract_kernel_with_transformations.py \
    gw_mixed_schur_preconditioner_alg_mod.x90
```

For now it only inserts comments in appropriate locations while the the full support for code extraction is being developed.

This example also contains a Python helper script `find_kernel.py` which displays the names and Schedules of Invokes containing call(s) to the specified Kernel:

```
> python find_kernel.py
```

5.3.13 Example 13 : Kernel Transformation

Demonstrates how an LFRic kernel can be transformed. The example transformation makes Kernel values constant where appropriate. For example, the number of levels is usually passed into a kernel by argument but the transformation allows a particular value to be specified which the transformation then sets as a parameter in the kernel. Hard-coding values in a kernel helps the compiler to do a better job when optimising the code.

5.3.14 Example 14: OpenACC

Example of adding OpenACC directives in the dynamo0.3 API. A single transformation script (`acc_parallel_dm.py`) is provided which demonstrates how to add OpenACC Loop, Parallel and Enter Data directives to the PSy-layer. It supports distributed memory being switched on by placing an OpenACC Parallel directive around each OpenACC Loop directive, rather than having one for the whole invoke. This approach avoids having halo exchanges within an OpenACC Parallel region. The script also uses *ACCRoutineTrans* to transform the one user-supplied kernel through the addition of an `!$acc` routine directive. This ensures that the compiler builds a version suitable for execution on the accelerator (GPU).

The generated code has two problems:

1. There are no checks on whether loops are safe to parallelise or not, it is just assumed they are - i.e. support for colouring or locking is not yet implemented.
2. Although the user-supplied kernel is transformed so as to have the necessary `!$acc` routine directive, the associated (but unnecessary) use statement in the transformed Algorithm layer still uses the name of the original, untransformed kernel (issue #1724).

Since no colouring is required in this case, the generated Alg layer may be fixed by hand (by simply deleting the offending use statement) and the resulting code compiled and run on GPU. However, performance will be very poor as, with the limited optimisations and directives currently applied, the NVIDIA compiler refuses to run the user-supplied kernel in parallel.

5.3.15 Example 15: CPU Optimisation of Matvec

Example of optimising the LFRic matvec kernel for CPUs. This is work in progress with the idea being that PSyclone transformations will be able to reproduce hand-optimised code.

There is one script which, when run:

```
> psyclone ./matvec_opt.py ../code/gw_mixed_schur_preconditioner_alg_mod.x90
```

will print out the modified matvec kernel code. At the moment no transformations are included (as they are work-in-progress) so the code that is output is the same as the original (but looks different as it has been translated to PSyIR and then output by the PSyIR Fortran back-end).

5.3.16 Example 16: Generating LFRic Code Using LFRic-specific PSyIR

This example shows how LFRic-specific PSyIR can be used to create LFRic kernel code. There is one Python script provided which when run:

```
> python create.py
```

will print out generated LFRic kernel code. The script makes use of LFRic-specific data symbols to simplify code generation.

5.3.17 Example 17: Runnable Simplified Examples

This directory contains three simplified LFRic examples that can be compiled and executed - of course, a suitable Fortran compiler is required. The examples are using a subset of the LFRic infrastructure library, which is contained in PSyclone and which has been slightly modified to make it easier to create stand-alone, non-MPI LFRic codes.

Example 17.1: A Simple Runnable Example

The subdirectory `full_example` contains a very simple example code that uses PSyclone to process two invokes. It uses unit-testing code from various classes to create the required data structures like initial grid etc. The code can be compiled with `make compile`, and the binary executed with either `make run` or `./example`.

Example 17.2: A Simple Runnable Example With NetCDF

The subdirectory `full_example_netcdf` contains code very similar to the previous example, but uses NetCDF to read the initial grid from the NetCDF file `mesh_BiP128x16-400x100.nc`. Installation of NetCDF is described in [the hands-on practicals documentation](#). The code can be compiled with `make compile`, and the binary executed with either `make run` or `./example`.

Example 17.3: Kernel Data Extraction

The example in the subdirectory `full_example_extract` shows the use of *kernel extraction*. The code can be compiled with `make compile`, and the binary executed with either `make run` or `./extract.standalone`. By default, it will be using a stand-alone extraction library (see *Extraction Libraries*). If you want to use the NetCDF version, set the environment variable `TYPE` to be `netcdf`:

```
TYPE=netcdf make compile
```

This requires the installation of a NetCDF development environment (see [here](#) for installing NetCDF). The binary will be called `extract.netcdf`, and the output files will have the `.nc` extension.

Running the compiled binary will create two Fortran binary files or two NetCDF files if the NetCDF library was used. They contain the input and output parameters for the two invokes in this example:

```
cd full_example_extraction
TYPE=netcdf make compile
./extract.netcdf
ncdump ./main-update.nc | less
```

5.3.18 Example 18: Special Accesses of Continuous Fields - Incrementing After Reading and Writing Before (Potentially) Reading

Example containing one kernel with a `GH_READINC` access and one with a `GH_WRITE` access, both for continuous fields. A kernel with `GH_READINC` access first reads the field data and then increments the field data. This contrasts with a `GH_INC` access which simply increments the field data. As an increment is effectively a read followed by a write, it may not be clear why we need to distinguish between these cases. The reason for distinguishing is that the `GH_INC` access is able to remove a halo exchange (or at least reduce its depth by one) in certain circumstances, whereas a `GH_READINC` is not able to take advantage of this optimisation.

A kernel with a `GH_WRITE` access for a continuous field must guarantee to write the same value to a given shared DoF, independent of which cell is being updated. As [described](#) in the Developer Guide, this means that annexed DoFs are computed correctly without the need to iterate into the L1 halo and thus can remove the need for halo exchanges on those fields that are read.

5.3.19 Example 19: Mixed Precision

This example shows the use of the LFRic *mixed-precision support* to call a kernel with *scalars*, *fields* and *operators* of different precision.

5.3.20 Example 20: Algorithm Generation

Illustration of the use of the `psyclone-kern` tool to create an algorithm layer for a kernel. A makefile is provide that also runs `psyclone` to create an executable program from the generated algorithm layer and original kernel code. To see the generated algorithm layer run:

```
cd eg20/
psyclone-kern -gen alg ../code/testkern_mod.F90
```

5.4 NEMO

These examples may all be found in the `examples/nemo` directory.

5.4.1 Example 1: OpenMP parallelisation of `tra_adv`

Demonstrates the use of PSyclone to parallelise loops in a NEMO tracer-advection benchmark using OpenMP for CPUs and for GPUs.

5.4.2 Example 2: OpenMP parallelisation of `traldf_iso`

Demonstrates the use of PSyclone to parallelise in some NEMO tracer-diffusion code using OpenMP for CPUs and for GPUs.

5.4.3 Example 3: OpenACC parallelisation of `tra_adv`

Demonstrates the introduction of simple OpenACC parallelisation (using the `data` and `kernels` directives) for a NEMO tracer-advection benchmark.

5.4.4 Example 4: Transforming Fortran code to the SIR

Demonstrates that simple Fortran code examples which conform to the NEMO API can be transformed to the Stencil Intermediate Representation (SIR). The SIR is the front-end language to DAWN (<https://github.com/MeteoSwiss-APN/dawn>), a tool which generates optimised cuda, or gridtools code. Thus various simple Fortran examples and the computational part of the tracer-advection benchmark can be transformed to optimised cuda and/or gridtools code by using PSyclone and then DAWN.

5.4.5 Example 5: Kernel Data Extraction

This example shows the use of kernel data extraction in PSyclone for the NEMO API. It instruments each kernel in the NEMO tracer-advection benchmark with the PSyData-based kernel extraction code. Detailed compilation instructions are in the `README.md` file, including how to switch from using the stand-alone extraction library to the NetCDF-based one (see [Extraction Libraries](#) for details).

5.4.6 Scripts

This contains examples of two different scripts that aid the use of PSyclone with the full NEMO model. The first, `process_nemo.py` is a simple wrapper script that allows a user to control which source files are transformed, which only have profiling instrumentation added and which are ignored altogether. The second, `kernels_trans.py` is a PSyclone transformation script which adds the largest possible OpenACC Kernels regions to the code being processed.

For more details see the `examples/nemo/README.md` file.

Note that these scripts are here to support the ongoing development of the NEMO API in PSyclone. They are *not* intended as ‘turn-key’ solutions but as a starting point.

5.5 PSyIR

Examples may all be found in the `examples/psyir` directory. Read the `README.md` file in this directory for full details.

5.5.1 Example 1: Constructing PSyIR and Generating Code

`create.py` is a Python script that demonstrates the use of the various `create` methods to build a PSyIR tree from scratch.

5.5.2 Example 2: Creating PSyIR for Structure Types

`create_structure_types.py` demonstrates the representation of structure types (i.e. Fortran derived types or C structs) in the PSyIR.

LIBRARIES

PSyclone provides *PSyData-API-based* wrappers to various external libraries. These wrapper libraries provide PSyclone transformations that insert callbacks to an external library at runtime. The callbacks then allow third-party libraries to access data structures at specified locations in the code for different purposes, such as profiling and extraction of argument values.

These wrapper libraries can be found under the `lib` directory in the Git repository. If you have installed PSyclone using pip then the libraries may be found in `share/psyclone/lib` under your Python (or PSyclone, depending on the pip install options) installation (see [here](#) for possible locations).

Note: If working with wrapper libraries from a PSyclone installation, it is advisable to copy the entire `lib` directory to some convenient location before building and using them. The provided Makefiles support the options to specify paths to the libraries and their dependencies, see [compilation](#) for more information.

6.1 Available libraries

An overview of the currently available functionality is below. For details of what each library does and how to build and use it please see the related sections in the User Guide and the specific README.md files in the associated directories.

6.1.1 Profiling

PSyclone provides wrapper libraries for some common performance profiling tools, such as `dl_timer` and `Dr Hook`. More information can be found in the [Profiling](#) section.

Profiling libraries are located in the `lib/profiling` directory. For detailed instructions on how to build and use them please refer to their specific README.md documentation.

6.1.2 Kernel Data Extraction

These libraries enable PSyclone to add callbacks that provide access to all input variables before, and output variables after a kernel invocation. More information can be found in the [PSy Kernel Extractor \(PSyKE\)](#) section.

Example libraries that extract input and output data into a NetCDF file for *LFRic (Dynamo0.3)* and *GOcean1.0* APIs are included with PSyclone in the `lib/extract/netcdf` directory. For detailed instructions on how to build and use these libraries please refer to their specific README.md documentation.

6.1.3 Access Verification

Read-only libraries check that a field declared as read-only is not modified during a kernel call. More information can be found in the *Read-Only Verification* section.

The libraries for *LFRic (Dynamo0.3)* and *GOcean1.0* APIs are included with PSyclone in the `lib/read_only` directory. For detailed instructions on how to build and use these libraries please refer to their specific README.md documentation.

6.1.4 NAN Test

These libraries test all input and output parameters of a kernel to make sure they are not NaN or infinite. More information can be found in the *NAN Test* section.

The libraries for *LFRic (Dynamo0.3)* and *GOcean1.0* APIs are included with PSyclone in the `lib/nan_test` directory. For detailed instructions on how to build and use these libraries please refer to their specific README.md documentation.

6.2 Dependencies

Building and using the wrapper libraries requires that PSyclone be installed on the host system, see section *Getting Going*. A Fortran compiler (e.g. Gnu Fortran compiler, gfortran, is free and easily installed) and Gnu Make are also required.

The majority of wrapper libraries use Jinja templates to create PSyData-derived classes (please refer to `psy_data` and *Jinja Support in the Base Class* for full details about the PSyData API).

Compilation of `extract`, `nan_test`, `read_only` and some of the profiling wrapper libraries depends on infrastructure libraries relevant to the API they are used for. *LFRic API* uses the LFRic infrastructure and *GOcean1.0* uses the `dl_esm_inf` library. The LFRic infrastructure can be obtained from the LFRic *code repository*, however this requires access to the *Met Office Science Repository Service (MOSRS)*. A useful contact for LFRic-related questions (including access to MOSRS) is the “lfric” mailing list which gathers the Met Office and external LFRic developers and users. The `dl_esm_inf` library is freely available and can be downloaded from https://github.com/stfc/dl_esm_inf.

Some libraries require NetCDF for compilation. Installation of NetCDF is described in details in the *hands-on practicals documentation*.

Profiling wrapper libraries that depend on external tools (e.g. `dl_timer`) require these tools be installed and configured beforehand.

6.3 Compilation

Each library is compiled with make using the provided Makefile that has configurable options for compiler flags and locations of dependencies.

As in case of *examples*, `F90` and `F90FLAGS` specify the compiler and compilation flags to use. The default value for `F90` is `gfortran`.

Locations of the top-level lib directory and the required Jinja templates are specified with the `PSYDATA_LIB_DIR` and `LIB_TMPLT_DIR` variables. For testing purposes their default values are set to relative paths to the respective directories in the PSyclone repository.

The locations of the infrastructure libraries for LFRic and GOcean1.0 applications can be configured with the variables `LFRIC_INF_DIR` and `GOCEAN_INF_DIR`, respectively. Their default values are set to relative paths to the

locations of these libraries in the PSyclone repository. The `dl_esm_inf` library is provided as a Git submodule of the PSyclone project (see [Installation](#) in the Developers' Guide for details on working with submodules) and a pared-down version of LFRic infrastructure is also available in the PSyclone repository (please refer to the `README.md` documentation of relevant wrapper libraries). However, the infrastructure libraries are not available in a PSyclone installation and they need to be downloaded separately, see [Dependencies](#) for more information. In this case `LFRIC_INF_DIR` and `GOCEAN_INF_DIR` **must be set** to the exact paths to where the respective infrastructure source can be found. For instance,

```
GOCEAN_INF_DIR=$HOME/dl_esm_inf/finite_difference make
```

Profiling wrapper libraries that depend on external tools have specific variables that configure paths to where these libraries are located in a user environment.

For more information on how to build and configure a specific library please refer to its `README.md` documentation.

Similar to compilation of the [examples](#), the compiled library can be removed by running `make clean`. There is also the `allclean` target that removes the compiled wrapper library as well as the compiled infrastructure library that the wrapper may depend on.

The compilation of wrapper libraries was tested with the Gnu and Intel Fortran compilers, see [here](#) for the full list. Please let the PSyclone developers know if you have problems using a compiler that has been tested or if you are working with a different compiler.

SYSTEM-SPECIFIC SET-UP FOR USERS

This chapter describes the setup for a user of PSyclone. It includes all steps necessary to be able to use PSyclone. And while you could obviously do some development, none of the required tools for testing or documentation creation will be installed.

The [System-specific Developer Set-up](#) in the Developers' Guide describes the additional installation of all required tools to run tests and create documentation.

Detailed instructions are provided for Ubuntu 16.04.2 and OpenSUSE 42.2 - if you are working with a different Linux distribution some adjustments will be necessary. You will need a terminal window open in which to enter the commands.

7.1 Installing dependencies

Most required dependencies are installed from the Python Package Index (<https://packaging.python.org/installing/>) using the program pip ("PIP Installs Packages"). Besides pip it is also recommended to install the graphviz package to be able to visualise dependency graphs. This is optional and the associated routine will silently return if the graphviz bindings are not installed.

7.1.1 Installing dependencies on Ubuntu

On Ubuntu pip and graphviz are installed using apt-get. Remember that graphviz is optional and that you'll need to install the graphviz package in addition to the Python bindings.

```
> sudo apt-get install python-pip graphviz
```

7.1.2 Installing dependencies on OpenSUSE

The vanilla OpenSUSE installation includes pip for Python 3. Note that the graphviz package is installed by default.

```
> sudo zypper install python-pip
```

7.2 Installing PSyclone

Change your working directory to where you would like to place the code and download the latest stable release of PSyclone.

```
> cd <PSYCLONEHOME>
> wget https://github.com/stfc/PSyclone/archive/2.3.1.tar.gz
> gunzip 2.3.1.tar.gz
> tar xf 2.3.1.tar
> rm 2.3.1.tar
> cd PSyclone-2.3.1
> export PYTHONPATH=`pwd`/src:${PYTHONPATH}
> export PATH=`pwd`/bin:${PATH}
```

This sets up your python path and path appropriately. You may want to set these paths permanently (e.g. by editing your `${HOME}/.bashrc` file if you run the BASH shell). You can also use the latest version using git, as described in [Installing PSyclone From GitHub](#).

7.3 Common installation

To avoid warnings during the dependency installation, it is recommended to update pip to the latest version:

```
> sudo pip install --upgrade pip
```

Next you need to install the fparser, pyparsing and sympy packages:

```
> sudo pip install fparser pyparsing sympy
```

Tip: With pip it is possible to install packages either system-wide (which requires root privileges) as above, or for a single user only (in `~/.local`). While the latter is only useful for one particular user, it means that PSyclone can be installed using pip without needing root privileges. In order to install a package for a user, add the `--user` command line option to all pip commands. This flag requests that the packages be installed locally for the current user rather than requiring root access:

```
> pip install --user fparser pyparsing sympy
```

You may remove the use of `sudo` and add the `--user` option to all pip commands described in this document.

Uninstalling is simply a matter of doing:

```
> sudo pip uninstall fparser pyparsing sympy
```

PSyclone supports the ability to output a schedule dependency graph using the graphviz package. This is optional and the associated routine will silently return if the graphviz bindings are not installed. If you have the graphviz package installed (see especially section [Installing dependencies on Ubuntu](#) if you are on Ubuntu), you also need to install the python bindings to the graphviz package:

```
> sudo pip install graphviz
```

If you just want to use PSyclone then you've installed all you need and you are ready to go to the getting-going [Run](#) section.

KERNEL LAYER

In the PSyKA1 separation of concerns, Kernel code (code which is created to run within the Kernel layer), operates on a subset of a field (such as a column of cells). The reason for doing this is that it gives the PSy layer the responsibility of calling the Kernel over the spatial domain which is where parallelism is typically exploited in finite element and finite difference codes. The PSy layer is therefore able to call the kernel layer in a flexible way (blocked and/or in parallel for example). Kernel code in the kernel layer is not allowed to include any parallelisation calls or directives and works on raw Fortran arrays (to allow the compiler to optimise the code).

Since a Kernel is called over the spatial domain (by the PSy layer) it must take at least one field or operator as an argument.

8.1 API

Kernels in the kernel layer are implemented as subroutines within Fortran modules. One or more kernel modules are allowed, each of which can contain one or more kernel subroutines. In the example below there is one module `integrate_one_module` which contains one kernel subroutine `integrate_one_code`. The kernel subroutines contain the code that operates over a subset of the field (such as a column).

Metadata describing the kernel subroutines is required by the PSyclone system to generate appropriate PSy layer code. The metadata is written by the kernel developer and is kept with the kernel code in the same module using a sub-type of the `kernel_type` type. In the example below the `w3_solver_kernel_type` type specifies the appropriate metadata information describing the kernel code for the dynamo0.3 api:

```
module w3_solver_kernel_mod

  use kernel_mod,          only : kernel_type
  use constants_mod,       only : r_def, i_def
  use fs_continuity_mod,   only : W3, Wchi
  use argument_mod,        only : arg_type, func_type, &
                             GH_FIELD, GH_SCALAR, &
                             GH_REAL, GH_READ, GH_WRITE, &
                             GH_BASIS, GH_DIFF_BASIS, &
                             GH_QUADRATURE_XYzZ, CELLS

  implicit none

  private

  type, public, extends(kernel_type) :: w3_solver_kernel_type
    private
    type(arg_type) :: meta_args(4) = (/ &
```

(continues on next page)

(continued from previous page)

```

    arg_type(GH_FIELD, GH_REAL, GH_WRITE, W3), &
    arg_type(GH_FIELD, GH_REAL, GH_READ, W3), &
    arg_type(GH_FIELD*3, GH_REAL, GH_READ, Wchi), &
    arg_type(GH_SCALAR, GH_REAL, GH_READ)      &
  /)
  type(func_type) :: meta_funcs(2) = (/          &
    func_type(W3, GH_BASIS),          &
    func_type(Wchi, GH_DIFF_BASIS)    &
  /)
  integer :: gh_shape = GH_QUADRATURE_XYZ
  integer :: operates_on = CELL_COLUMN
contains
  procedure, nopass :: solver_w3_code
end type

contains

subroutine solver_w3_code(nlayers,          &
  x, rhs,          &
  chi_1, chi_2, chi_3, ascalar,          &
  ndf_w3, undf_w3, map_w3, w3_basis,      &
  ndf_w0, undf_w0, map_w0, w0_diff_basis, &
  nqp_h, nqp_v, wqp_h, wqp_v)
  ...
end subroutine solver_w3_code

end module w3_solver_kernel_mod

```

8.2 Metadata

Kernel metadata is not required if the PSy layer is going to be written manually - its sole purpose is to let PSyclone know how to generate the PSy layer. The content of Kernel metadata differs depending on the particular API and this information can be found in the API-specific sections of this document.

In all APIs the kernel metadata is implemented as an extension of the *kernel_type* type. The reason for using a type to specify metadata is that it allows the metadata to be kept with the code and for it to be compilable. In addition, currently all APIs will contain information about the arguments in an array called `meta_args`, a specification of what data the kernel code expects in a variable called `operates_on` and a reference to the kernel code itself as a type-bound procedure:

```

type, extends(kernel_type) :: integrate_one_kernel
...
type(...) :: meta_args(...) = (/ ... /)
...
integer :: operates_on = ...
...
contains
...
procedure ...
...
end type integrate_one_kernel

```

If no type-bound procedure is declared then a named interface with module procedures must be included in the module:

```
type, extends(kernel_type) :: integrate_one_kernel
...
type(...) :: meta_args(...) = (/ ... /)
...
integer :: operates_on = ...
...
end type integrate_one_kernel

interface ...
  module procedure ...
end interface
```

These module procedures provide alternative implementations (using different precisions) of the kernel code. They are selected as appropriate by the Fortran compiler, depending on the precision of the fields being passed to them.

ALGORITHM LAYER

In the PSyKAl separation of concerns, the Algorithm layer specifies the algorithm that the scientist would like to run (in terms of calls to kernel routines and Built-in operations) and logically operates on full fields. Algorithm code in the algorithm layer is not allowed to include any parallelisation calls or directives and passes datatypes specified by the particular API.

9.1 API

The Algorithm layer is forbidden from calling the Kernel layer directly. In PSyclone, if the programmer would like to call a Kernel routine or a Built-in operation from the algorithm layer they must use the `invoke` call (which is common to all APIs). The `invoke` call is not necessary (and indeed will not work) if the PSy layer is written manually.

To make an `invoke` call, the algorithm layer developer adds one or more `call invoke()` statements to their code and within the content of the `invoke` call they add a reference to the required Kernel/Built-in and the data to pass to it. For example,

```
...  
call invoke(integrate_one_kernel(arg1,arg2))  
...
```

For more information on the concept of Built-in operations see the [Built-ins](#) Section. Details of which operations are supported for a specific API are given in the documentation of that API.

The algorithm layer can consist of an arbitrary number of files containing fortran code, any of which may contain as many `invoke()` calls as is required. PSyclone is applied to an individual algorithm layer file and must therefore be run multiple times if multiple files containing `invoke()` calls exist in the algorithm layer.

The algorithm developer is also able to reference more than one Kernel/Built-in within an `invoke`. In fact this feature is encouraged for performance reasons. **As a general guideline the developer should aim to use as few invokes as possible with as many Kernel references within them as is possible.** The reason for this is that it allows for greater freedom for optimisation in the PSy layer as PSy layer optimisations are limited to the contents of individual `invoke` calls - PSyclone currently does not attempt to optimise the PSy layer over multiple `invoke` calls.

As well as generating the PSy layer code, PSyclone modifies the Algorithm layer code, replacing `invoke` calls with calls to the generated PSy layer so that the algorithm code is compilable and linkable to the PSy layer and adding in the appropriate use statement. For example, the above `integrate_one_kernel` `invoke` is translated into something like the following:

```
...  
use psy, only : invoke_0_integrate_one_kernel  
...
```

(continues on next page)

(continued from previous page)

```
call invoke__0_integrate__one__kernel(arg1,arg2)
...
```

In addition, any use statements importing Kernels (`integrate__one__kernel` in this example) are removed because they are no longer required in the transformed algorithm code.

You may have noticed from other examples in this guide that an algorithm specification in an `invoke` call references the metadata type in an `invoke` call, not the code directly; this is by design.

For example, in the `invoke` call below, `integrate__one__kernel` is used.

```
...
call invoke(integrate__one__kernel(arg1,arg2))
...
```

`integrate__one__kernel` is the name of the metadata type in the module, not the name of the subroutine in the Kernel

```
...
```

```
module integrate__one__module
...
  type, extends(kernel__type) :: integrate__one__kernel
...
end type
...
contains
...
  subroutine integrate__one__code(...)
...
  end subroutine integrate__one__code
...
end module integrate__one__module
```

9.1.1 Named Invokes

PSyclone permits the user to optionally specify a label for an `invoke` call like so:

```
...
call invoke(integrate__one__kernel(arg1,arg2), &
           name="compute something")
...
```

The name argument to the `invoke` call is optional. If supplied it must be a string literal. The content of this string (with any spaces replaced by `'_'` characters) is used in naming the corresponding PSy-layer routine generated by PSyclone. So, for the above example, the generated PSy-layer subroutine will be named `"invoke_compute_something."` Each `invoke` label must currently be unique within an Algorithm source file. Note that, in keeping with the Fortran language, labels are not case sensitive and, after having any spaces replaced by underscores, must be valid Fortran names (e.g. `name="compute(1)"` is invalid). In the future it is intended that the labelling of invokes will help to support `invoke`-specific optimisations to be applied as well as enabling more readable profiling output. It may also be used to instruct PSyclone to just generate a single subroutine to implement all invokes that share the same label.

9.2 Limitations

In order to re-write the Algorithm layer, as just described, PSyclone must obviously be able to parse the invoke calls. Since the Fortran expression parser used by PSyclone is relatively simple, this means there are limitations on what Fortran may be used when specifying kernel arguments in an invoke call. Since these limitations can have a direct impact on the natural science code, the PSyclone developers endeavour to keep them to a minimum.

The current list of known limitations/restrictions on the form of kernel arguments within an invoke is:

- No arithmetic expressions (e.g. `kernel_type(a+b)` or `kernel_type(-a)`)
- No named (optional) arguments (e.g. `kernel_type(fn(my_arg=a))`)

If you encounter any other limitations (or have a burning desire to use one of the above forms) then please contact the PSyclone developers.

PSY LAYER

In the PSyKAI separation of concerns, the PSy layer is responsible for linking together the Algorithm and Kernel layers and for providing the implementation of any Built-in operations used. Its functional responsibilities are to

1. map the arguments supplied by an Algorithm invoke call to the arguments required by a Built-in or Kernel call (as these will not have a one-to-one correspondence).
2. call any Kernel routines such that they cover the required iteration space and
3. perform any Built-in operations (either by including the necessary code directly in the PSy layer or by e.g. calling a maths library) and
4. include any required distributed memory operations such as halo swaps and reductions.

Its other role is to allow the optimisation expert to optimise any required distributed memory operations, include and optimise any shared memory parallelism and optimise for single node (e.g. cache and vectorisation) performance.

10.1 Code Generation

The PSy layer can be written manually but this is error prone and potentially complex to optimise. The PSyclone code generation system generates the PSy layer so there is no need to write the code manually.

To generate correct PSy layer code, PSyclone needs to understand the arguments and datatypes passed by the algorithm layer and the arguments and datatypes expected by the Kernel layer; it needs to know the name of the Kernel subroutine(s); it needs to know the iteration space that the Kernel(s) is/are written to iterate over; it also needs to know the ordering of Kernels and Built-ins as specified in the algorithm layer. Finally, it needs to know where to place any distributed memory operations.

PSyclone determines the above information by being told the API in question (by the user), by reading the appropriate Kernel and Built-in metadata and by reading the order of Kernels and Built-ins in an invoke call (as specified in the algorithm layer).

PSyclone has an API-specific parsing stage which reads the algorithm layer and all associated Kernel metadata. This information is passed to a PSy-generation stage which creates a high level view of the PSy layer. From this high level view the PSy-generation stage can generate the required PSy code.

For example, the following Python code shows a code being parsed, a PSy-generation object being created using the output from the parser and the PSy layer code being generated by the PSy-generation object.

```
from psyclone.parse.algorithm import parse
from psyclone.psyGen import PSyFactory

# This example uses the LFRic (Dynamo 0.3) API
api = "dynamo0.3"
```

(continues on next page)

(continued from previous page)

```
# Parse the file containing the algorithm specification and
# return the Abstract Syntax Tree and invokeInfo objects
ast, invokeInfo = parse("dynamo.F90", api=api)

# Create the PSy-layer object using the invokeInfo
psy = PSyFactory(api).create(invokeInfo)
# Generate the Fortran code for the PSy layer
print psy.gen
```

10.2 API

The PSy-layer of a single algorithm file is represented by the **PSy** class. The PSy class has an **Invokes** object which contain one or more **Invoke** instances (one for each invoke in the algorithm layer). Each **Invoke** has an **InvokeSchedule** object with the PSyIR tree that describes the PSy layer invoke subroutine. This subroutine is called by the Algorithm layer and itself calls one or more kernels and/or implements any required Built-in operations.

All this classes can be specialised in each PSyclone API to support the specific features of the APIs. The class diagram for the above base classes is shown below using the dynamo0.3 API as an illustration. This class diagram was generated from the source code with pyreverse and edited with inkscape.



The InvokeSchedule can currently contain nodes of type: **Loop**, **Kernel**, **Built-in** (see the *Built-ins* section), **Directive** (of various types), **HaloExchange**, or **GlobalSum** (the latter two are only used if distributed memory is supported and is switched on; see the *Distributed Memory* section). The order of the tree (depth first) indicates the order of the associated Fortran code.

PSyclone will initially create a “vanilla” (functionally correct but not optimised) InvokeSchedule. This “vanilla” InvokeSchedule can be modified by changing the objects within it. For example, the order that two Kernel calls appear in the generated code can be changed by changing their order in the tree. The ability to modify this high level view of a InvokeSchedule allows the PSy layer to be optimised for a particular architecture (by applying optimisations such as blocking, loop merging, inlining, OpenMP parallelisation etc.). The tree could be manipulated directly, however, to simplify optimisation, a set of transformations are supplied. These transformations are discussed in the next section.

10.2.1 InvokeSchedule visualisation

PSyclone supports visualising an InvokeSchedule (or any other PSyIR node) in two ways. First the *view()* method outputs textual information about the contents of a PSyIR node. If we were to look at the LFRic eg6 example we would see the following output:

```
>>> print(schedule.view())
InvokeSchedule[invoke='invoke_0', dm=True]
  0: Directive[OMP parallel do]
    Schedule[]
      0: Loop[type='dofs',field_space='any_space_1',it_space='dofs','upper_bound='ndofs']
        Literal[value:'NOT_INITIALISED']
        Literal[value:'NOT_INITIALISED']
        Literal[value:'1']
        Schedule[]
          0: BuiltIn setval_X_code(p,z)
          1: BuiltIn X_innerproduct_Y_code(rs_old,res,z)
      1: GlobalSum[scalar='rs_old']
```

The above output tells us that the invoke name for the InvokeSchedule we are looking at is *invoke_0* and that the *distributed_memory* option has been switched on. Within the InvokeSchedule is an OpenMP parallel directive containing a loop which itself contains two built-in calls. As the latter of the two built-in calls requires a reduction and distributed memory is switched on, PSyclone has added a GlobalSum call for the appropriate scalar.

Second, the *dag()* method (standing for directed acyclic graph), outputs the PSyIR nodes and its data dependencies. By default a file in dot format is output with the name *dag* and a file in svg format is output with the name *dag.svg*. The file name can be changed using the *file_name* optional argument and the output file format can be changed using the *file_format* optional argument. The *file_format* value is simply passed on to graphviz so the graphviz documentation should be consulted for valid formats if svg is not required.

```
>>> schedule.dag(file_name="lovely", file_format="png")
```

Note: The dag method can be called from any node and will output the dag for that node and all of its children.

If we were to look at the LFRic eg6 example we would see the following image:



In the image, all PSyIR nodes with children are split into a start vertex and an end vertex (for example the InvokeSchedule node has both *schedule_start* and *schedule_end* vertices). Blue arrows indicate that there is a parent to child relationship (from a start node) or a child to parent relationship (to an end node). Green arrows indicate that a Node depends on another Node later in the schedule (which we call a forward dependence). Therefore the OMP parallel loop must complete before the globalsum is performed. Red arrows indicate that a Node depends on another Node that is earlier in the schedule (which we call a backward dependence). However the direction of the red arrows are reversed to improve the flow of the dag layout. In this example the forward and backward dependence is the same, however this is not always the case. The two built-ins do not depend on each other, so they have no associated green or red arrows.

The dependence graph output gives an indication of whether nodes can be moved within the InvokeSchedule. In this case it is valid to run the built-ins in either order. The underlying dependence analysis used to create this graph is used to determine whether a transformation of a Schedule is valid from the perspective of data dependencies.

BUILT-INS

Built-ins (named by analogy with the native functionality provided by Python) are operations which can be specified within an invoke call in the algorithm layer but do not require an associated kernel to be implemented as they are provided directly by the infrastructure.

One use of Built-ins is for commonly used operations. In this case Built-ins simplify the use of the system as users do not need to write kernel routines. Built-ins also offer a potential performance advantage as they provide a specification of what is required without an implementation. Therefore the PSy layer is free to implement these operations in whatever way it chooses.

Note: In general, PSyclone will need to know the types of the arguments being passed to any Built-ins. The parser obtains this information from an API-specific file that contains the metadata for all Built-in operations supported for that API.

Note: When a particular Built-in is used, the name of this Built-in should not be used for anything else within the same scope. For example, it is not valid to make use of a Built-in called `setval_c` and for its parent subroutine to also be called `setval_c`. In this case PSyclone will raise an exception.

11.1 Example

In the following example, the invoke call includes a call to two Built-ins (`setval_c` and `X_divideby_Y`) and a user-supplied kernel (`matrix_vector_kernel_mm_type`). The `setval_c` Built-in sets all values in the field `Ax` to 1.0 and the `X_divideby_Y` Built-in divides values in the field `rhs` by their equivalent (per degree of freedom) values in the field `lumped_weight` (see [supported LFRic \(Dynamo0.3\) API Built-ins](#)). Notice that, unlike the kernel call, no use association is required for the Built-ins since they are provided as part of the environment (*c.f.* Fortran intrinsics such as `sin()`).

```
module solver_mod
...
use matrix_vector_mm_mod, only: matrix_vector_kernel_mm_type
...

subroutine jacobi_solver_algorithm(lhs, rhs, mm, mesh, n_iter)

  integer(kind=i_def), intent(in)  :: n_iter
  type(field_type),  intent(inout) :: lhs
  type(field_type),  intent(in)    :: rhs
```

(continues on next page)

(continued from previous page)

```

type(operator_type), intent(in)  :: mm
type(mesh_type),   intent(in)   :: mesh
type(field_type)   :: Ax, lumped_weight, res

real(kind=r_def), parameter :: MU = 0.9_r_def
...

! Compute mass lump
call invoke( name = "Jacobi_mass_lump",
              setval_c(Ax, 1.0_r_def),
              matrix_vector_kernel_mm_type(lumped_weight, Ax, mm), &
              X_divideby_Y(lhs, rhs, lumped_weight) )

end subroutine jacobi_solver_algorithm
...

end module solver_mod

```

Below is an example of a kernel that is consistent with the `matrix_vector_kernel_mm_type` kernel specified in the example above.

```

module matrix_vector_mm_mod
  type, public, extends(kernel_type) :: matrix_vector_kernel_mm_type
  private
  type(arg_type) :: meta_args(3) = (/
    arg_type(GH_FIELD, GH_REAL, GH_INC, ANY_SPACE_1),
    arg_type(GH_FIELD, GH_REAL, GH_READ, ANY_SPACE_1),
    arg_type(GH_OPERATOR, GH_REAL, GH_READ, ANY_SPACE_1, ANY_SPACE_1) &
  /)
  integer :: operates_on = CELL_COLUMN
contains
  procedure, nopass :: matrix_vector_mm_code
end type
contains
  subroutine matrix_vector_mm_code(cell,
    nlayers,
    lhs, x,
    ncell_3d,
    mass_matrix, &
    ndf, undf, map)
  end subroutine matrix_vector_mm_code
end module matrix_vector_mm_mod

```

We now translate the algorithm layer code and generate the PSy layer code. The algorithm code is assumed to be in a file called `solver_mod.x90` (see Example 3 in *LFRic examples* section). In this case we use the top level Python interface. See the *API* section for different ways to translate/generate code.

```

> psyclone -nodm -oalg solver_mod.f90 -opsy solver_mod_psy.f90 \
> solver_mod.x90

```

The resultant generated algorithm code is given below.

Ignoring the difference in case (which is due to the output format of the code parser) the differences between the original algorithm code and the translated algorithm code are:

- The generic calls to invoke have been replaced by specific CALL invoke_<xx>. The kernel calls within the original invoke are removed, as are duplicate arguments and any literals, leaving the five fields and one operator as arguments;
- A use statement is added for the each of the new CALL invoke_<xx> which will call the generated PSy layer code.

The existence of calls to Built-ins has made no difference at this point:

```

SUBROUTINE jacobi_solver_algorithm(lhs, rhs, mm, mesh, n_iter)
  USE solver_mod_psy, ONLY: invoke_jacobi_iterloop
  USE solver_mod_psy, ONLY: invoke_21
  USE solver_mod_psy, ONLY: invoke_jacobi_mass_lump

  IMPLICIT NONE

  INTEGER(KIND = i_def), INTENT(IN) :: n_iter
  TYPE(field_type), INTENT(OUT) :: lhs
  TYPE(field_type), INTENT(IN) :: rhs
  TYPE(operator_type), INTENT(IN) :: mm
  TYPE(mesh_type), INTENT(IN) :: mesh
  TYPE(field_type) :: Ax, lumped_weight, res

  REAL(KIND = r_def), PARAMETER :: MU = 0.9_r_def

  INTEGER(KIND = i_def) :: iter
  INTEGER(KIND = i_def) :: rhs_fs
  TYPE(function_space_type) :: fs

  ...
  CALL invoke_jacobi_mass_lump(ax, lumped_weight, mm, lhs, rhs)
  ...

END SUBROUTINE jacobi_solver_algorithm

```

A vanilla (with no distributed and shared-memory optimisations) version of the generated PSy layer is given below. As expected, the kernel code is called from the PSy layer. However, in the case of the Built-ins, the code for these has been written directly into the PSy layer:

- setval_c translates to the loop setting `ax_proxy%data(df) = 1.0_r_def`;
- X_divideby_Y translates to the loop setting `lhs_proxy%data(df) = rhs_proxy%data(df) / lumped_weight_proxy%data(df)`.

This example illustrates that Built-ins may be implemented in whatever way PSyclone sees fit with no change to the algorithm and kernel layers.

```

MODULE solver_mod_psy
  ...

  SUBROUTINE invoke_jacobi_mass_lump(ax, lumped_weight, mm, lhs, rhs)
    USE matrix_vector_mm_mod, ONLY: matrix_vector_mm_code
    TYPE(field_type), intent(in) :: ax, lumped_weight, lhs, rhs
    TYPE(operator_type), intent(in) :: mm
    ...
    !

```

(continues on next page)

(continued from previous page)

```

! Initialise field and/or operator proxies
!
ax_proxy = ax%get_proxy()
lumped_weight_proxy = lumped_weight%get_proxy()
mm_proxy = mm%get_proxy()
lhs_proxy = lhs%get_proxy()
rhs_proxy = rhs%get_proxy()
!
! Initialise number of layers
!
nlayers = ax_proxy%vspace%get_nlayers()
!
! Look-up dofmaps for each function space
!
map_aspc1_lumped_weight => lumped_weight_proxy%vspace%get_whole_dofmap()
!
! Initialise number of DoFs for aspc1_ax
!
ndf_aspc1_ax = ax_proxy%vspace%get_ndf()
undf_aspc1_ax = ax_proxy%vspace%get_undf()
!
! Initialise number of DoFs for aspc1_lumped_weight
!
ndf_aspc1_lumped_weight = lumped_weight_proxy%vspace%get_ndf()
undf_aspc1_lumped_weight = lumped_weight_proxy%vspace%get_undf()
!
! Initialise number of DoFs for aspc1_lhs
!
ndf_aspc1_lhs = lhs_proxy%vspace%get_ndf()
undf_aspc1_lhs = lhs_proxy%vspace%get_undf()
!
! Call our kernels
!
DO df=1,undf_aspc1_ax
  ax_proxy%data(df) = 1.0_r_def
END DO
DO cell=1,lumped_weight_proxy%vspace%get_ncell()
  !
  CALL matrix_vector_mm_code(cell, nlayers,      &
                             lumped_weight_proxy%data, &
                             ax_proxy%data,      &
                             mm_proxy%ncell_3d,   &
                             mm_proxy%local_stencil, &
                             ndf_aspc1_lumped_weight, &
                             undf_aspc1_lumped_weight, &
                             map_aspc1_lumped_weight(:,cell))
END DO
DO df=1,undf_aspc1_lhs
  lhs_proxy%data(df) = rhs_proxy%data(df) / lumped_weight_proxy%data(df)
END DO
!
END SUBROUTINE invoke_jacobi_mass_lump

```

(continues on next page)

(continued from previous page)

```
...
END MODULE solver_mod_psy
```

This example is distributed with PSyclone and can be found in `<PSYCLONEHOME>/examples/lfric/eg3`.

11.2 Supported Built-in operations

The list of supported Built-ins is API-specific and therefore is described under the documentation of each API.

11.3 Adding new Built-in operations

1. Identify the PSyclone source file for the API to be extended. *e.g.* for the LFRic API it is `src/psyclone/domain/lfric/lfric_builtins.py`.
2. Edit this source file to create the class for this new call. It must inherit from the API-specific parent class for Built-in operations (LFRicBuiltInKern for the LFRic API).
3. Implement `__str__` and `gen_code()` methods for this new class.
4. Add the name of the new Built-in operation and its corresponding class to the `BUILTIN_MAP` dictionary in that source file.
5. Add metadata describing this call to the appropriate file specified in the `BUILTIN_DEFINITIONS_FILE` in that source file. For the LFRic API this is `src/psyclone/parse/lfric_builtins_mod.f90`.
6. Add relevant tests to the PSyclone test files for the API to be extended. *e.g.* for the LFRic API they are `* src/psyclone/tests/domain/lfric/lfric_builtins_test.py`, `* src/psyclone/tests/domain/lfric/lfric_integer_builtins_test.py`. The tests rely on single_invoke Fortran examples in the relevant `src/psyclone/tests/test_files/` subdirectory.
7. Add an appropriate Fortran single_invoke example for the new Built-in in the relevant `src/psyclone/tests/test_files/` subdirectory. *e.g.* for the LFRic API it is `src/psyclone/tests/test_files/dynamo0p3/`. Names of examples follow the template `<category.number>.<subcategory.number>_<built-in_name>.f90`. *e.g.* for the LFRic API `<category.number>` is 15 and `<built-in_name>` follows the [LFRic API Built-in naming scheme](#).
8. Document the new Built-in in the documentation of the relevant API (*e.g.* `doc/dynamo0p3.rst` for LFRic (Dynamo0.3) API).

If the API being extended does not currently support any Built-ins then the `BUILTIN_MAP` and `BUILTIN_DEFINITIONS_FILE` module variables must be added to the source file for the API. A Fortran module file must be created in the PSyclone `src/parse` directory (with the name specified in `BUILTIN_DEFINITIONS_FILE`) containing metadata describing the Built-in operations. Finally, `parse.get_builtin_defs()` must be extended to import `BUILTIN_MAP` and `BUILTIN_DEFINITIONS_FILE` for this API.

LFRIC (DYNAMO0.3) API

This section describes the LFRic (Dynamo0.3) application programming interface (API). This API explains what a user needs to write in order to make use of the LFRic API in PSyclone.

As with the majority of PSyclone APIs, the LFRic (Dynamo0.3) specifies how a user needs to write the algorithm layer and the kernel layer to allow PSyclone to generate the PSy layer. These algorithm and kernel APIs are discussed separately in the following sections.

The LFRic API supports the Met Office's finite element (hereafter FEM) based GungHo dynamical core (see [Introduction](#)). This dynamical core with atmospheric physics parameterisation schemes is a part of the Met Office LFRic modelling system [AFH+19], currently being developed in preparation for exascale computing in the 2020s. The LFRic repository and the associated wiki are hosted at the [Met Office Science Repository Service](#). The code is BSD-licensed, however browsing the [LFRic wiki](#) and [code repository](#) requires login access to MOSRS. For more technical details on the implementation of LFRic, please see the [LFRic documentation](#).

12.1 Algorithm

The general requirements for the structure of an Algorithm are explained in the [Algorithm layer](#) section. This section explains the LFRic-API-specific specialisations and extensions.

12.1.1 Example

An example LFRic (Dynamo0.3) API invoke call is given below with various different types of objects supported by the API. These different objects and their use are discussed in the following sections.

```
real(kind=r_def)      :: rscalar
integer(kind=i_def)   :: iscalar
logical(kind=l_def)   :: lscalar
integer(kind=i_def)   :: stencil_extent
type(field_type)      :: field1, field2, field3
type(field_type)      :: field5(3), field6(3)
type(integer_field_type) :: field7
type(quadrature_type)  :: qr
type(operator_type)    :: operator1
type(columnwise_operator_type) :: cma_op1
...
call invoke( kernel1(field1, field2, operator1, qr),      &
             builtin1(rscalar, field2, field3),          &
             int_builtin2(iscalar, field7),              &
             kernel2(field1, stencil_extent, field3, lscalar), &
```

(continues on next page)

(continued from previous page)

```
        assembly_kernel(cma_op1, operator1),      &
        name="some_calculation"                  &
    )
call invoke( prolong_kernel_type(field1, field4),  &
            restrict_kernel_type(field5, field6)
    )
```

Please see the *Algorithm layer* section for a description of the name argument.

Objects in the LFRic API can be categorised by their functionality as data structures and information that specifies supported operations on a particular data structure. These data structures are represented by the five LFRic (Dynamo 0.3) API argument types: *scalar*, *field*, *field vector*, *operator* and *column-wise operator*. All of them except the field vector are represented in the above example. *qr* represents a quadrature object which provides information required by a kernel to operate on fields (see section *Quadrature* for more details).

12.1.2 Scalar

In the LFRic API a scalar is a single-valued argument that is identified with GH_SCALAR metadata. Scalar arguments can have real, integer or logical data type in *user-defined Kernels* (logical data type is not supported in the *LFRic Built-ins*).

12.1.3 Field

LFRic API fields, identified with GH_FIELD metadata, represent FEM discretisations of various dynamical core prognostic and diagnostic variables. In FEM, variables are discretised by placing them into a function space (see *Supported Function Spaces*) from which they inherit a polynomial expansion via the basis functions of that space. Field values at points within a cell are evaluated as the sum of a set of basis functions multiplied by coefficients which are the data points. Points of evaluation are determined by a quadrature object (*Quadrature*) and are independent of the function space the field is on. Placement of field data points, also called degrees of freedom (hereafter “DoFs”), is determined by the function space the field is on. LFRic fields passed as arguments to any *LFRic kernel* can be of real or integer primitive type. In the LFRic infrastructure, these fields are represented by instances of the `field_type` and `integer_field_type` classes, respectively.

12.1.4 Field Vector

Depending on the function space a field lives on, the field data value at a point can be a scalar or a vector (see *Supported Function Spaces* for the list of scalar and vector function spaces). There is an additional option, called a *field vector*, to represent a bundle of either scalar- or vector-valued fields. Field vectors are represented as GH_FIELD*N where N is the size of the vector. The 3D coordinate field, for example, has (x, y, z) scalar values at the nodes and therefore has a vector size of 3.

12.1.5 Operator

Represents a matrix constructed on a per-cell basis using Local Matrix Assembly (LMA) and is identified with GH_OPERATOR metadata. In the LFRic infrastructure, operators are represented by instances of the operator_type class. LFRic operators can only have real-valued data in *user-defined Kernels* (*LFRic Built-ins* do not currently support operators).

12.1.6 Column-wise Operator

The LFRic API has support for the construction and use of column-wise/Column Matrix Assembly (CMA) operators whose metadata identifier is GH_COLUMNWISE_OPERATOR. In the LFRic infrastructure, column-wise operators are represented by instances of the columnwise_operator_type class. As for the LMA operators above, LFRic column-wise operators can only have real-valued *data*.

As the name suggests, these are operators constructed for a whole column of the mesh. These are themselves constructed from the Local Matrix Assembly (LMA) operators of each cell in the column. The rules governing Kernels that have CMA operators as arguments are given in the *Kernel* section below.

There are three recognised Kernel types involving CMA operations; construction, application (including inverse application) and matrix-matrix. The following example sketches-out what the use of such kernels might look like in the Algorithm layer:

```
use field_mod, only: field_type
use operator_mod, only : operator_type
use columnwise_operator_mod, only : columnwise_operator_type
type(field_type) :: field1, field2, field3
type(operator_type) :: lma_op1, lma_op2
type(columnwise_operator_type) :: cma_op1, cma_op2, cma_op3
real(kind=r_def) :: alpha
...
call invoke(
    assembly_kernel(cma_op1, lma_op1, lma_op2), &
    assembly_kernel2(cma_op2, lma_op1, lma_op2, field3), &
    apply_kernel(field1, field2, cma_op1), &
    matrix_matrix_kernel(cma_op3, cma_op1, alpha, cma_op2), &
    apply_kernel(field3, field1, cma_op3), &
    name="cma_example")
```

The above invoke uses two LMA operators to construct the CMA operator cma_op1. A second CMA operator, cma_op2, is assembled from the same two LMA operators but also uses a field. The first of these CMA operators is then applied to field2 and the result stored in field1 (assuming that the metadata for apply_kernel specifies that it is the first field argument that is written to). The two CMA operators are then combined to produce a third, cma_op3. This is then applied to field1 and the result stored in field3.

Note that PSyclone identifies the type of kernels performing column-wise operations based on their arguments as described in metadata (see *Rules for Kernels that work with CMA Operators* below). The names of the kernels in the above example are purely illustrative and are not used by PSyclone when determining kernel type.

A full example of CMA operator construction is available in examples/lfric/eg7.

12.1.7 Quadrature

Kernels conforming to the LFRic API may require quadrature information (specified using e.g. `gh_shape = gh_quadrature_XYoZ` in the kernel metadata - see Section [gh_shape and gh_evaluator_targets](#)). This information must be passed to the kernel from the Algorithm layer in the form of one or more `quadrature_type` objects. These must be the last arguments passed to the kernel and must be provided in the same order that they are specified in the kernel metadata, e.g. if the metadata for kernel `pressure_gradient_kernel_type` specified `gh_shape = gh_quadrature_XYoZ` and that for kernel `geopotential_gradient_kernel` had `gh_shape(2) = (\ gh_quadrature_XYoZ, gh_quadrature_face \)` then the corresponding invoke would look something like:

```
...
qr_xyoz = quadrature_xyoz_type(nqp_exact, rule)
qr_face = quadrature_face_type(nqp_exact, ..., rule)
call invoke(pressure_gradient_kernel_type(rhs_tmp(igh_u), rho, theta, qr_xyoz), &
            geopotential_gradient_kernel_type(rhs_tmp(igh_u), geopotential, &
            qr_xyoz, qr_face))
```

These quadrature objects specify the set(s) of points at which the basis/differential-basis functions required by the kernel are to be evaluated.

12.1.8 Stencils

The metadata for a Kernel which operates on a cell-column may specify that a Kernel performs a stencil operation on a field. Any such metadata must provide a stencil type. See the [meta_args](#) section for more details. The supported stencil types are X1D, Y1D, XORY1D, CROSS, CROSS2D or REGION.

If a stencil operation is specified by the Kernel metadata the algorithm layer must provide the extent of the stencil (the maximum distance from the central cell that the stencil extends). The LFRic API expects this information to be added as an additional integer argument immediately after the relevant field when specifying the Kernel via an invoke.

For example:

```
integer(kind=i_def) :: extent = 2
call invoke(kernel(field1, field2, extent))
```

where `field2` has kernel metadata specifying that it has a stencil access.

`extent` may also be passed as a literal. For example:

```
call invoke(kernel(field1, field2, 2))
```

where, again, `field2` has kernel metadata specifying that it has a stencil access.

Note: The stencil extent specified in the Algorithm layer is not the same as the stencil size passed in to the Kernel. The latter contains the number of cells in the stencil which is dependent on both the stencil type and extent.

If the Kernel metadata specifies that the stencil is of type XORY1D (which means X1D or Y1D) then the algorithm layer must specify whether the stencil is X1D or Y1D for that particular kernel call. The LFRic API expects this information to be added as an additional argument immediately after the relevant stencil extent argument. The argument should be an integer with valid values being `x_direction` or `y_direction`, both being supplied by the LFRic infrastructure via the `flux_direction_mod` fortran module

For example:

```

use flux_direction_mod, only : x_direction
integer(kind=i_def) :: direction = x_direction
integer(kind=i_def) :: extent = 2
! ...
call invoke(kernel(field1, field2, extent, direction))

```

direction may also be passed as a literal. For example:

```

use flux_direction_mod, only : x_direction
integer(kind=i_def) :: extent = 2
! ...
call invoke(kernel(field1, field2, extent, x_direction))

```

If the stencil is of type CROSS2D then the arrays passed to the kernel are of different dimensions to those of other stencils. The CROSS2D stencil is designed for use when it is necessary for a kernel to know where the stencil cells are, relative to the current cell. For this reason, the `stencil_size` passed to the kernel is an array of length 4 containing sizes for each branch of the stencil. The `stencil_size` array is always ordered: West, South, East, North. This branch dimension is also part of the `stencil_dofmap` array making it possible to loop over each branch of the stencil individually. The `invoke` call for the CROSS2D stencil remains of the same form as for other stencils.

If certain fields use the same value of extent and/or direction then the same variable, or literal value can be provided.

For example:

```

call invoke(kernel1(field1, field2, extent, field3, extent, direction), &
           kernel2(field1, field2, extent2, field4, extent, direction))

```

In the above example `field2` and `field3` in `kernel1` and `field4` in `kernel2` will have the same extent value but `field2` in `kernel2` may have a different value. Similarly, `field3` in `kernel1` and `field4` in `kernel2` will have the same direction value.

An example of the use of stencils is available in `examples/lfric/eg5`.

There is currently no attempt to perform type checking in PSyclone so any errors in the type and/or position of arguments will not be picked up until compile time. However, PSyclone does check for the correct number of algorithm arguments. If the wrong number of arguments is provided then an exception is raised.

For example, running test 19.2 from the LFRic (Dynamo0.3) API test suite gives:

```

cd <PSYCLONEHOME>/src/psyclone/tests
psyclone test_files/dynamo0p3/19.2_single_stencil_broken.f90
"Generation Error: error: expected '5' arguments in the algorithm layer but found '4'.
Expected '4' standard arguments, '1' stencil arguments and '0' qr_arguments"

```

12.1.9 Inter-grid

From the Algorithm layer, an `Invoke` for inter-grid kernels (those that map fields between grids of different resolution) looks much like an `Invoke` containing general-purpose kernels. The only restrictions to be aware of are that inter-grid kernels accept only field or field-vectors as arguments and that an `Invoke` may not mix inter-grid kernels with any other kernel type. (Hence the second, separate `Invoke` in the example Algorithm code given at the beginning of this Section.)

12.2 Mixed Precision

The LFRic API supports the ability to specify the precision required by the model via precision variables. To make use of this, the code developer must declare scalars, fields and operators in the algorithm layer with the required LFRic-supported precision. In the current implementation there are two supported precisions for REAL data and one each for INTEGER and LOGICAL data. The actual precision used in the code can be set in a configuration file. For example, INTEGER data could be set to be 32-bit precision. As REAL data has more than one supported precision, different parts of the code can be configured to have different precision.

The table below gives the currently supported datatypes, their associated kernel metadata description and their precision:

Data Type	Kernel Metadata	Precision
REAL(R_DEF)	GH_SCALAR, GH_REAL	R_DEF
REAL(R_BL)	GH_SCALAR, GH_REAL	R_BL
REAL(R_PHYS)	GH_SCALAR, GH_REAL	R_PHYS
REAL(R_SOLVER)	GH_SCALAR, GH_REAL	R_SOLVER
REAL(R_TRAN)	GH_SCALAR, GH_REAL	R_TRAN
INTEGER(I_DEF)	GH_SCALAR, GH_INTEGER	I_DEF
LOGICAL(L_DEF)	GH_SCALAR, GH_LOGICAL	L_DEF
FIELD_TYPE	GH_FIELD, GH_REAL	R_DEF
R_BL_FIELD_TYPE	GH_FIELD, GH_REAL	R_BL
R_PHYS_FIELD_TYPE	GH_FIELD, GH_REAL	R_PHYS
R_SOLVER_FIELD_TYPE	GH_FIELD, GH_REAL	R_SOLVER
R_TRAN_FIELD_TYPE	GH_FIELD, GH_REAL	R_TRAN
INTEGER_FIELD_TYPE	GH_FIELD, GH_INTEGER	I_DEF
OPERATOR_TYPE	GH_OPERATOR, GH_REAL	R_DEF
R_SOLVER_OPERATOR_TYPE	GH_OPERATOR, GH_REAL	R_SOLVER
R_TRAN_OPERATOR_TYPE	GH_OPERATOR, GH_REAL	R_TRAN
COLUMNWISE_OPERATOR_TYPE	GH_COLUMNWISE_OPERATOR, GH_REAL	R_SOLVER

As can be seen from the above table, the kernel metadata does not capture all of the precision options. For example, from the metadata it is not possible to determine whether a REAL scalar, REAL field or REAL operator has precision R_DEF, R_SOLVER or R_TRAN.

If a scalar, field, or operator is specified with a particular precision in the algorithm layer then any associated kernels that it is passed to must have been written so that they support this precision. If a kernel needs to support data that can be stored with different precisions then appropriate precision-specific subroutines should be written. These precision-specific subroutine should be called via a generic interface (which lets Fortran choose the appropriate subroutine based on the precision of its argument(s)).

Below is a simple example of an algorithm code calling the same generic kernel twice with potentially different precision. The implementation of the generic kernel such that it supports both 32- and 64-bit precision is also shown. The use of LFRic names for precision in the algorithm code allows precision to be controlled in a simple way. For example, r_solver could be set to be 32-bits in one configuration and 64-bits in another:

```

program test

  use constants_mod,    only : r_def, r_solver
  use field_mod,        only : field_type
  use r_solver_field_mod, only : r_solver_field_type
  use example_mod,      only : example_type

```

(continues on next page)

(continued from previous page)

```

type(field_type)          :: field_r_def
type(r_solver_field_type) :: field_r_solver
real(kind=r_def)          :: x_r_def
real(kind=r_solver)       :: x_r_solver

call invoke( example_type(field_r_def, x_r_def), &
             example_type(field_r_solver, x_r_solver))

end program test

module example_mod

  use argument_mod
  use kernel_mod

  implicit none

  type, extends(kernel_type) :: example_type
    type(arg_type), dimension(2) :: meta_args = (/      &
      arg_type(gh_field, gh_real, gh_readwrite, w3), &
      arg_type(gh_scalar, gh_real, gh_read )      &
    /)
    integer :: operates_on = cell_column
  contains
    procedure, nopass :: code => example_code
  end type example_type

  private
  public :: example_code

  interface example_code
    module procedure example_code_32
    module procedure example_code_64
  end interface example_code

contains

  subroutine example_code_32(..., field1, x, ...)
    real*4, dimension(...), intent(inout) :: field1
    real*4, intent(in) :: x
    print *, "32-bit example called"
  end subroutine example_code_32

  subroutine example_code_64(..., field1, x, ...)
    real*8, dimension(...), intent(inout) :: field1
    real*8, intent(in) :: x
    print *, "64-bit example called"
  end subroutine example_code_64

end module example_mod

```

In order to support mixed precision, PSyclone needs to know the precision (as specified in the algorithm layer) of any kernel arguments that are of a type that supports different precisions (e.g. GH_FIELD). The reason for this is that

PSyclone needs to be able to declare data with the correct precision information within the PSy-layer to ensure that the correct flavour of kernels are called.

PSyclone must therefore determine this information from the algorithm layer. The rules for whether PSyclone requires information for particular LFRic datatypes and what it does with or without this information are given below:

12.2.1 Fields

PSyclone must be able to determine the datatype of a field from the algorithm layer declarations. If it is not able to do this, PSyclone will abort with a message that indicates the problem.

Supported field types, their Fortran datatype and precisions are outlined in the table below:

Field Type	Fortran Datatype	Precision
field_type	real	r_def
r_bl_field_type	real	r_bl
r_phys_field_type	real	r_phys
r_solver_field_type	real	r_solver
r_tran_field_type	real	r_tran
integer_field_type	integer	i_def

12.2.2 Field Vectors

In addition to fields, LFRic supports an abstract vector type for fields, used in the LFRic solver API. Please note that these structures are different from the *field vector* implementation of field bundles in the PSyclone LFRic API interface.

The LFRic abstract vector type has precision-specific implementations. If PSyclone finds such a specifically declared field vector argument in the algorithm layer, e.g. `r_solver_field_vector_type`, it will assume that the actual field being referenced is of the same datatype and precision (see [above](#) for details). The correspondence between the available field types and their vector implementations is given in the table below (note that only real-valued fields have abstract vector implementations for now):

Field Type	Field Vector Type
field_type	field_vector_type
r_bl_field_type	r_bl_field_vector_type
r_phys_field_type	r_phys_field_vector_type
r_solver_field_type	r_solver_field_vector_type
r_tran_field_type	r_tran_field_vector_type

If PSyclone finds an argument that is declared as an `abstract_field_type` then it will not know the actual type of the argument. For instance, the following algorithm layer code will cause PSyclone to raise an exception:

```
! ...
class (abstract_vector_type), intent(inout) :: x
! ...
select type (x)
type is (field_vector_type)
  call invoke(testkern_type(x%vector(1)))
class default
  print *, "Error"
end select
! ...
```

The suggested solution to this is to add a pointer variable to the code that is of the required type. This pointer can then be associated with the argument and passed into the routine:

```
! ...
class (abstract_vector_type), target, intent(inout) :: x
type(field_vector_type), pointer :: x_ptr
! ...
select type (x)
type is (field_vector_type)
  x_ptr => x
  call invoke(testkern_type(x_ptr%vector(1)))
class default
  print *, "Error"
end select
! ...
```

12.2.3 Scalars

It is not mandatory for PSyclone to be able to determine the datatype of a scalar from the algorithm layer. This constraint was considered to be too restrictive as PSyclone currently only examines the declarations in the same source file as the invoke when determining datatype. This means that if scalars are imported from other modules (as is often the case) then their datatype cannot be determined.

If the precision information for a scalar is found by PSyclone then this is used. If the scalar declaration is found and it contains no precision information then PSyclone will abort with a message that indicates the problem (since this violates LFRic coding standards). If no declaration information is found then default precision values are used, as specified in the PSyclone config file (r_def for real, i_def for integer and l_def for logical).

Supported precisions for scalars are outlined in the table below. If an unsupported scalar precision is found then PSyclone will abort with a message that indicates the problem.

Fortran Datatype	Supported Precision
real	r_def, r_bl, r_phys, r_solver, r_tran
integer	i_def
logical	l_def

12.2.4 LMA Operators

PSyclone must be able to determine the datatype of an LMA operator. If it is not able to do this, PSyclone will abort with a message that indicates the problem.

Supported LMA operator types, their Fortran datatype and precisions are outlined in the table below:

Operator Type	Fortran Datatype	Precision
operator_type	real	r_def
r_solver_operator_type	real	r_solver
r_tran_operator_type	real	r_tran

12.2.5 Column-wise Operators

It is not mandatory for PSyclone to be able to determine the datatype of a column-wise (CMA) operator. The reason for this is that only one datatype is supported, a `columnwise_operator_type` which contains real-valued data with precision `r_solver`. PSyclone can therefore simply add this datatype in the PSy-layer. However, if the datatype information is found in the algorithm layer and it is not of the expected type then PSyclone will abort with a message that indicates the problem.

12.2.6 Consistency

If PSyclone is able to determine the datatype of an LFRic datatype then PSyclone also checks that this datatype is consistent with the associated kernel metadata. If it is not consistent then PSyclone will abort with a message that indicates the problem.

12.3 PSy-layer

The general details of the PSy-layer are explained in the *PSy layer* section. This section describes any dynamo0p3 specific issues.

12.3.1 Module name

The PSy-layer code is contained within a Fortran module. The name of the module is determined from the algorithm-layer name with “_psy” appended. The algorithm-layer name is the algorithm’s module name if it is a module, its subroutine name if it is a subroutine that is not within a module, or the program name if it is a program.

So, for example, if the algorithm code is contained within a module called “fred” then the PSy-layer module name will be “fred_psy”.

Argument Intents

LFRic *fields*, *field vectors*, *operators* and *column-wise operators* are objects that contain pointers to data rather than data. The data are accessed by proxies of these objects and modified in *kernels*. As the objects themselves are not modified in the PSy layer, their Fortran intents there are always `intent(in)`.

The Fortran intent of *scalars* is still defined by their *access metadata* as they are actual data. This means `intent(in)` for `GH_READ` and `intent(out)` for `GH_SUM` (more details in *meta_args* section below).

The intent of other data structures is mandated by the relevant LFRic API rules described in sections below.

12.4 Kernel

The general requirements for the structure of a Kernel are explained in the *Kernel layer* section. In the LFRic API there are five different Kernel types; general purpose, CMA, inter-grid, domain and *Built-ins*. In the case of built-ins, PSyclone generates the source of the kernels. This section explains the rules for the other four, user-supplied kernel types and then goes on to describe their metadata and subroutine arguments.

Domain kernels are distinct from the other three, user-supplied kernel types in that they must be passed data for the whole domain rather than a single cell-column. This permits the use of kernels that have not been written to conform to the single-column approach which simplifies the integration with existing code. Obviously, any parallelisation in the ‘domain’ kernel must be consistent with that in the rest of the application. The motivation for such kernels in LFRic is

that they allow existing, “i-first” physics code to be called from the PSy layer. Since those routines currently contain their own, i-first looping structure (and associated OpenMP parallelisation), the most efficient way to use them is to avoid enclosing them within a loop in the PSy layer. This is a temporary measure and these kernels will ultimately be replaced once the LFRic infrastructure has support for i-first kernels (<https://code.metoffice.gov.uk/trac/lfric/ticket/2154>). At that point the looping (and associated parallelisation) will be put back into the PSy layer.

12.4.1 Rules for all User-Supplied Kernels that Operate on Cell-Columns

In the following, ‘operator’ refers to both LMA and CMA operator types.

- 1) A Kernel must have at least one argument that is a field, field vector, or operator. This rule reflects the fact that a Kernel operates on some subset of the whole domain (e.g. a cell-column) and is therefore designed to be called from within a loop that iterates over those subsets of the domain.
- 2) The continuity of the iteration space of the Kernel is determined from the function space of the modified argument (see Section *Supported Function Spaces* below). If more than one argument is modified then the iteration space is taken to be the largest required by any of those arguments. E.g. if a Kernel writes to two fields, the first on W3 (discontinuous) and the second on W1 (continuous), then the iteration space of that Kernel will be determined by the field on the continuous space.
- 3) If any of the modified arguments are declared with the generic function space metadata (e.g. ANY_SPACE_<n>, see *Supported Function Spaces*) and their actual space cannot be determined statically then the iteration space is assumed to be
 - 1) discontinuous for ANY_DISCONTINUOUS_SPACE_<n>;
 - 2) continuous for ANY_SPACE_<n> and ANY_W2. This assumption is always safe but leads to additional computation if the quantities being updated are actually on discontinuous function spaces.
- 4) Operators do not have halo operations operating on them as they are either cell- (LMA) or column-based (CMA) and therefore act like discontinuous fields.
- 5) Any Kernel that writes to an operator will have its iteration space expanded such that valid values for the operator are computed in the level-1 halo.
- 6) Any Kernel that reads from an operator must not access halos beyond level 1. In this case PSyclone will check that the Kernel does not require values beyond the level-1 halo. If it does then PSyclone will abort.
- 7) Any Kernel that takes an operator argument must not also take an integer-valued field as an argument.

12.4.2 Rules specific to General-Purpose Kernels without CMA Operators

- 1) General-purpose kernels with `operates_on = CELL_COLUMN` accept arguments of any of the following types: field, field vector, LMA operator, scalar (real, integer or logical).
- 2) A Kernel is permitted to write to more than one quantity (field or operator) and these quantities may be on the same or different function spaces.
- 3) A Kernel may not write to a scalar argument. (Only *built-ins* are permitted to do this.) Any scalar arguments must therefore be declared in the metadata as GH_READ - see *below*.

12.4.3 Rules for Kernels that work with CMA Operators

The LFRic API has support for kernels that assemble, apply (or inverse-apply) column-wise/Column Matrix Assembly (CMA) operators. Such operators may also be used by matrix-matrix kernels. There are thus three types of CMA-related kernels. Since, by definition, CMA operators only act on data within a column, they have no horizontal dependencies. Therefore, kernels that write to them may be parallelised without colouring.

All three CMA-related kernel types must obey the following rules:

- 1) Since a CMA operator only acts within a single column of data, stencil operations are not permitted.
- 2) No vector quantities (e.g. `GH_FIELD*3` - see below) are permitted as arguments.
- 3) The kernel must operate on cell-columns.

There are then additional rules specific to each of the three CMA kernel types. These are described below.

Assembly

CMA operators are themselves constructed from Local-Matrix-Assembly (LMA) operators. Therefore, any kernel which assembles a CMA operator must obey the following rules:

- 1) Have one or more LMA operators as read-only arguments.
- 2) Have exactly one CMA operator argument which must have write access.
- 3) Other types of argument (e.g. scalars or fields) are permitted but must be read-only.

Application and Inverse Application

Column-wise operators can only be applied to fields. CMA-Application kernels must therefore:

- 1) Have a single CMA operator as a read-only argument.
- 2) Have exactly two field arguments, one read-only and one that is written to.
- 3) The function spaces of the read and written fields must match the from and to spaces, respectively, of the supplied CMA operator.

Matrix-Matrix

A kernel that has just column-wise operators as arguments and zero or more read-only scalars is identified as performing a matrix-matrix operation. In this case:

- 1) Arguments must be CMA operators and, optionally, one or more scalars.
- 2) Exactly one of the CMA arguments must be written to while all other arguments must be read-only.

12.4.4 Rules for Inter-Grid Kernels

- 1) An inter-grid kernel is identified by the presence of a field or field-vector argument with the optional `mesh_arg` metadata element (see *Inter-Grid Metadata*).
- 2) An invoke that contains one or more inter-grid kernels must not contain any other kernel types. (This restriction is an implementation decision and could be lifted in future if there is a need.)
- 3) An inter-grid kernel is only permitted to have field or field-vector arguments.
- 4) All inter-grid kernel arguments must have the `mesh_arg` metadata entry.
- 5) An inter-grid kernel (and metadata) must have at least one field on each of the fine and coarse meshes. Specifying all fields as coarse or fine is forbidden.
- 6) Fields on different meshes must always live on different function spaces.
- 7) All fields on a given mesh must be on the same function space.
- 8) An inter-grid kernel must operate on cell-columns.

A consequence of Rules 5-7 is that an inter-grid kernel will only involve two function spaces.

12.4.5 Rules for User-Supplied Kernels that Operate on the Domain

The rules for kernels that have `operates_on = DOMAIN` are a subset of *those* for kernels that operate on a `CELL_COLUMN` without CMA Operators. Specifically:

- 1) Only *scalar*, *field* and *field vector* arguments are permitted.
- 2) All fields must be on discontinuous function spaces.
- 3) Stencil accesses are not permitted.

12.4.6 Metadata

The code below outlines the elements of the LFRic (Dynamo0.3) API Kernel metadata, 1) '*meta_args*', 2) '*meta_funcs*', 3) '*meta_reference_element*', 4) '*meta_mesh*', 5) '*gh_shape*' (*gh_shape* and *gh_evaluator_targets*), 6) '*operates_on*' and 7) '*procedure*':

```
type, public, extends(kernel_type) :: my_kernel_type
  type(arg_type) :: meta_args(...) = (/ ... /)
  type(func_type) :: meta_funcs(...) = (/ ... /)
  type(reference_element_data_type) :: meta_reference_element(...) = (/ ... /)
  type(mesh_data_type) :: meta_mesh(...) = (/ ... /)
  integer :: gh_shape = gh_quadrature_XYoZ
  integer :: operates_on = cell_column
contains
  procedure, nopass :: my_kernel_code
end type
```

These various metadata elements are discussed in order in the following sections.

meta_args

The `meta_args` array specifies information about data that the kernel code expects to be passed to it via its argument list. There is one entry in the `meta_args` array for each **scalar**, **field**, or **operator** passed into the Kernel and the order that these occur in the `meta_args` array must be the same as they are expected in the kernel code argument list. The entry must be of `arg_type` which itself contains metadata about the associated argument. The size of the `meta_args` array must correspond to the number of **scalars**, **fields** and **operators** passed into the Kernel.

Note: It makes no sense for a Kernel to have only **scalar** arguments (because the PSy layer will call a Kernel for each point in the spatial domain) and PSyclone will reject such Kernels.

For example, if there are a total of 2 **scalar** / **field** / **operator** entities being passed to the Kernel then the `meta_args` array will be of size 2 and there will be two `arg_type` entries:

```
type(arg_type) :: meta_args(2) = (/
    arg_type( ... ),      &
    arg_type( ... )      &
  /)
```

Argument metadata (information contained within the brackets of an `arg_type` entry), describes either a **scalar**, a **field** or an **operator** (either LMA or CMA).

The first argument-metadata entry describes whether the data that is being passed is for a scalar (`GH_SCALAR`), a field (`GH_FIELD`) or an operator (either `GH_OPERATOR` for LMA or `GH_COLUMNWISE_OPERATOR` for CMA). This information is mandatory.

Additionally, argument metadata can be used to describe a vector of fields (see the [Field Vector](#) section for more details).

As an example, the following `meta_args` metadata describes 4 entries, the first is a scalar, the next two are fields and the fourth is an operator. The third entry is a field vector of size 3.

```
type(arg_type) :: meta_args(4) = (/
    arg_type(GH_SCALAR, GH_REAL, ...),      &
    arg_type(GH_FIELD, GH_INTEGER, ... ),   &
    arg_type(GH_FIELD*3, GH_REAL, ... ),     &
    arg_type(GH_OPERATOR, GH_REAL, ...)     &
  /)
```

The second item in a metadata entry describes the Fortran primitive (intrinsic) type of the data of a kernel argument. The currently supported values are `GH_REAL`, `GH_INTEGER` and `GH_LOGICAL` for real, integer and logical data, respectively. This information is mandatory. Valid data types for each LFRic API argument type are specified later in this section (see [Valid Data Types](#)).

The third component of argument metadata describes how the Kernel makes use of the data being passed into it (the way it is accessed within a Kernel). This information is mandatory. There are currently 6 possible values of this metadata `GH_READ`, `GH_WRITE`, `GH_READWRITE`, `GH_INC`, `GH_READINC` and `GH_SUM`. However, not all combinations of metadata entries are valid and PSyclone will raise an exception if an invalid combination is specified. Valid combinations are specified later in this section (see [Valid Access Modes](#)).

- `GH_READ` indicates that the data is read and is unmodified.
- `GH_WRITE` indicates the data is modified in the Kernel before (optionally) being read. If any shared DoFs are written to then different iterations of the Kernel must write the same value.
- `GH_READWRITE` indicates that different iterations of a Kernel update quantities which do not share DoFs, such as operators and fields over discontinuous function spaces. If a Kernel modifies only discontinuous fields

and/or operators there is no need for synchronisation or colouring when running such Kernels in parallel. However, modifying another field with a GH_INC access in a Kernel means that synchronisation or colouring is required for parallel runs.

- GH_INC indicates that different iterations of a Kernel make contributions to shared values. For example, values at cell faces may receive contributions from cells on either side of the face. This means that such a Kernel needs appropriate synchronisation (or colouring) to run in parallel.
- GH_READINC indicates that the data is first read and then subsequently incremented. Therefore this is equivalent to a GH_READ followed by a GH_INC.
- GH_SUM is an example of a reduction and is the only reduction currently supported in PSyclone. This metadata indicates that values are summed over calls to Kernel code.

For example:

```
type(arg_type) :: meta_args(6) = (/
    arg_type(GH_OPERATOR, GH_REAL,  GH_READ,    ... ), &
    arg_type(GH_FIELD*3,  GH_REAL,  GH_WRITE,    ... ), &
    arg_type(GH_FIELD,    GH_REAL,  GH_READWRITE, ... ), &
    arg_type(GH_FIELD,    GH_INTEGER, GH_INC,      ... ), &
    arg_type(GH_FIELD,    GH_REAL,  GH_READINC,   ... ), &
    arg_type(GH_SCALAR,   GH_REAL,  GH_SUM)        &
    /)
```

Warning: It is important that GH_INC is not incorrectly used in place of a GH_READINC access as it could result in the reading of data from a dirty outermost halo when run in parallel, giving incorrect results. The reason for this is that PSyclone does not add a halo exchange for the outermost modified halo level of a field before a loop that contains a GH_INC access to that field, i.e. a loop iterating to the level- n halo will result in a halo exchange to the level- $(n-1)$ halo being added before the loop (which means no halo exchange is added when $n=1$). The reason this can be performed is because any computation in the outermost halo will be incorrect (will only compute partial sums) and PSyclone therefore sets this halo level to dirty after the loop has completed. There is, therefore, no reason to make the values of the incremented field clean for the outermost modified halo. However, this optimisation does require that any (dirty) data in the outermost modified halo does not result in exceptions. With some compilers an exception can occur for a field that has not yet had its outermost halo data written to, i.e. if the uninitialised data is read. To avoid this potential problem in user code it is recommended that a redundant computation *transformation* is added to compute all `setval_c`, `setval_x` and `setval_random` Built-in calls (see *Built-ins*) to the same halo depth as the associated GH_INC access - which is level-1 without any redundant computation transformations being applied to the associated loops. This will guarantee that all data has been initialised with a value before it is incremented and avoid any potential exceptions.

Note: In the LFRic API only *Built-ins* are permitted to write to scalar arguments (and hence perform reductions). Furthermore, this permission is currently restricted to real scalars (GH_SCALAR, GH_REAL) as the LFRic infrastructure does not yet support integer and logical reductions.

For a scalar, the argument metadata contains only these three entries. However, fields and operators require further entries specifying function-space information. The meaning of these further entries differs depending on whether a field or an operator is being described.

In the case of an operator, the fourth and fifth arguments describe the to and from function spaces respectively. In the case of a field the fourth argument specifies the function space that the field lives on. More details about the supported function spaces are in subsection *Supported Function Spaces*.

For example, the metadata for a kernel that applies a column-wise operator to a field might look like:

```

type(arg_type) :: meta_args(3) = (/
    arg_type(GH_FIELD, GH_REAL, GH_INC, W1),      &
    arg_type(GH_FIELD, GH_REAL, GH_READ, W2H),    &
    arg_type(GH_COLUMNWISE_OPERATOR, GH_REAL, GH_READ, W1, W2H) &
/)

```

In some cases a Kernel may be written so that it works for fields and/or operators from any type of a vector W2* space (all W2* spaces except for the W2*trace spaces, see Section [Supported Function Spaces](#) below). In this case the metadata should be specified as being ANY_W2.

Warning: In the current implementation it is assumed that all fields and/or operators specifying ANY_W2 within a kernel will use the **same** function space. It is up to the user to ensure this is the case as otherwise invalid code would be generated.

It may be that a Kernel is written such that a field and/or operators may be on/map-between any function space(s). In this case the metadata should be specified as being one of ANY_SPACE_1, ..., ANY_SPACE_<nmax> (see [Supported Function Spaces](#)), with the number of spaces, <nmax>, being set in the [PSyclone configuration file](#) (see [here](#) for more details on this option).

If the generic function spaces are known to be discontinuous the metadata may be specified as being one of ANY_DISCONTINUOUS_SPACE_1, ..., ANY_DISCONTINUOUS_SPACE_<nmax> in order to avoid unnecessary computation into the halos (see rules for [user-supplied kernels](#) above). The reason for having different names is that a Kernel might be written to allow 2 or more arguments to be able to support any function space but for a particular call the function spaces may have to be the same as each other. Again, <nmax> is the [configurable](#) number of generalised discontinuous function spaces.

In the example below, the first field entry supports any function space but it must be the same as the operator's to function space. Similarly, the second field entry supports any function space but it must be the same as the operator's from function space. Note, the metadata does not forbid ANY_SPACE_1 and ANY_SPACE_2 from being the same.

```

type(arg_type) :: meta_args(3) = (/
    arg_type(GH_FIELD, GH_REAL, GH_INC, ANY_SPACE_1),      &
    arg_type(GH_FIELD*3, GH_REAL, GH_INC, ANY_SPACE_2),    &
    arg_type(GH_OPERATOR, GH_REAL, GH_READ, ANY_SPACE_1, ANY_SPACE_2) &
/)

```

Note also that the scope of this naming of any-space function spaces is restricted to the argument list of individual kernels. I.e. if an Invoke contains say, two kernel calls that each support arguments on any function space, e.g. ANY_SPACE_1, there is no requirement that these two function spaces be the same. Put another way, if an Invoke contained two calls of a kernel with arguments described by the above metadata then the first field argument passed to each kernel call need not be on the same space.

Valid Data Types

As mentioned earlier, the currently supported Fortran primitive (intrinsic) types for kernel argument data are real, integer and logical, described by the GH_REAL, GH_INTEGER and GH_LOGICAL metadata descriptors. Supported data types for each argument type are given in the table below (please note that *field vectors* follow the same rules as the *LFRic fields*):

Argument Type	Data Type
GH_SCALAR	GH_REAL, GH_INTEGER, GH_LOGICAL
GH_FIELD	GH_REAL, GH_INTEGER
GH_OPERATOR	GH_REAL
GH_COLUMNWISE_OPERATOR	GH_REAL

Valid Access Modes

As mentioned earlier, not all combinations of metadata are valid. Valid combinations for each argument type in user-defined Kernels are summarised here. All argument types (GH_SCALAR, GH_FIELD, GH_OPERATOR and GH_COLUMNWISE_OPERATOR) may be read within a Kernel and this is specified in metadata using GH_READ. At least one kernel argument must be listed as being modified. When data is *modified* in a user-supplied Kernel (i.e. a Kernel that operates on a CELL_COLUMN, see *iteration space metadata*) then the permitted access modes depend upon the argument type and the function space it is on:

Argument Type	Function Space	Access Type
GH_SCALAR	n/a	GH_READ
GH_FIELD	Discontinuous	GH_READ, GH_WRITE, GH_READWRITE
GH_FIELD	Continuous	GH_READ, GH_WRITE, GH_INC, GH_READINC
GH_OPERATOR	Any for both 'to' and 'from'	GH_READ, GH_WRITE, GH_READWRITE
GH_COLUMNWISE_OPERATOR	Any for both 'to' and 'from'	GH_READ, GH_WRITE, GH_READWRITE

Note that scalar arguments to user-defined Kernels must be read-only. Only *Built-ins* are permitted to modify scalar arguments. In practice this means that the only allowed access for the scalars in user-defined Kernels is GH_READ (see the allowed accesses for arguments in Built-ins in the *section below*).

Note also that a GH_FIELD argument that has GH_WRITE or GH_READWRITE as its access pattern must typically (see below) be on a horizontally-discontinuous function space (see *Supported Function Spaces* for the list of discontinuous function spaces). Parallelisation of the loop over the horizontal domain for a Kernel that updates such a field will not require colouring for either of the above cases (since there are no shared entities).

There is however an exception to this - certain Kernels may write to shared entities but each Kernel iteration is guaranteed to write the *same value* to a given shared DoF. In this case, provided that the first access to any such shared DoF is a write, the loop containing such a Kernel may be parallelised without colouring. Therefore, GH_WRITE access is permitted for GH_FIELD arguments on continuous function spaces. Obviously, care must be taken to ensure that the Kernel implementation satisfies the constraints just described as PSyclone cannot currently check this.

If a field is described as being on ANY_SPACE_*, there is currently no way to determine its continuity from the metadata (unless we can statically determine the space of the field being passed in). At the moment this type of a user-supplied Kernel is always treated as if it is updating a field that is on a function space that is continuous in the horizontal, even if it is not (see rules for *user-supplied kernels* above).

There is no restriction on the number and function spaces of other quantities that a general-purpose kernel can modify other than that it must modify at least one. The rules for kernels involving CMA operators, however, are stricter and only one argument may be modified (the CMA operator itself for assembly, a field for CMA-application and a CMA operator for matrix-matrix kernels). If a kernel writes to quantities on different function spaces then PSyclone generates loop

bounds appropriate to the largest iteration space. This means that if a single kernel updates one quantity on a continuous function space and one on a discontinuous space then the resulting loop will include cells in the level-1 halo since they are required for a quantity on a continuous space. As a consequence, any quantities on a discontinuous space will then be computed redundantly in the level-1 halo. Currently PSyclone makes no attempt to take advantage of this (by e.g. setting the appropriate level-1 halo to ‘clean’).

PSyclone ensures that both CMA and LMA operators are computed (redundantly) out to the level-1 halo cells. This permits their use in kernels which modify quantities on continuous function spaces and also in subsequent redundant computation of other quantities on discontinuous function spaces. In conjunction with this, PSyclone also checks (when generating the PSy layer) that any kernels which read operator values do not do so beyond the level-1 halo. If any such accesses are found then PSyclone aborts.

Supported Function Spaces

As mentioned in the *Field* and *Field Vector* sections, the function space of an argument specifies how it maps onto the underlying topology and, additionally, whether the data at a point is a vector. In LFRic API the dimension of the basis function set for the scalar function spaces is 1 and for the vector function spaces is 3 (see the table in *Rules for General-Purpose Kernels* for the dimensions of the basis and differential basis functions).

Function spaces can share DoFs between cells in the horizontal, vertical or both directions. Depending on the function space and FEM order, the shared DoFs can lie on one or more cell entities (faces, edges and vertices) in each direction. This property is referred to as the **continuity** of a function space (horizontal, vertical or full). Alternatively, if there are no shared DoFs a function space is described as **discontinuous** (fully or in a particular direction).

The mixed FEM formulation is built on a foundation set of four function spaces described below.

- W0 is the space of scalar functions with full continuity. The shared DoFs lie on cell vertices in the lowest order FEM and on all three entities in higher order FEM.
- W1 is the space of vector functions with full continuity in the tangential direction only. In the lowest order FEM the shared DoFs lie on cell edges for each component, whereas in higher order they also lie on cell faces.
- W2 is the space of vector functions with full continuity in the normal direction only. The shared DoFs lie on cell faces for each component.
- W3 is the space of scalar functions with full discontinuity. All DoFs lie within the cell volume and are not shared across the cell boundaries.

Other spaces required for representation of scalar or component-wise vector variables are:

- Wtheta is the space of scalar functions based on the vertical part of W2, discontinuous in the horizontal and continuous in the vertical;
- W2H is the space of vector functions based on the horizontal part of W2, continuous in the horizontal and discontinuous in the vertical;
- W2V is the space of vector functions based on the vertical part of W2, discontinuous in the horizontal and continuous in the vertical;
- W2broken is the space of vector functions, locally identical to the W2 space. However, DoFs are topologically discontinuous in all directions despite their placement on cell faces;
- W2trace is the space of scalar functions defined only on cell faces, resulting from taking the trace of a W2 space. DoFs are shared between faces, hence making this space fully continuous;
- W2Htrace is the space of scalar functions defined only on cell faces in the horizontal, resulting from taking the trace of a W2H space. DoFs are shared between horizontal faces, hence making this space continuous in the horizontal and discontinuous in the vertical;

- W2Vtrace is the space of scalar functions defined only on cell faces in the vertical, resulting from taking the trace of a W2V space. DoFs are shared between vertical faces, hence making this space discontinuous in the horizontal and continuous in the vertical;
- Wchi is the space of scalar functions used to store coordinates in LFRic. It is fully discontinuous except for the coordinate order 0 when it becomes the W0 space (i.e. fully continuous). Please see the next section for more details on this function space.

In addition to the specific function space metadata, there are also three generic function space metadata descriptors mentioned in sections above:

- ANY_SPACE_<n>, $n = 1, 2, \dots, nmax$, for when the function space of the argument(s) cannot be determined and/or for when a Kernel has been written so that it works with fields on any of the available spaces (as mentioned in the [meta_args section](#), the number of spaces, <nmax>, is *configurable*);
- ANY_DISCONTINUOUS_SPACE_<n>, $n = 1, 2, \dots, nmax$, for when the function space of the argument(s) cannot be determined but is known to be discontinuous and/or for when a Kernel has been written so that it works with fields on any of the discontinuous spaces (again, the number of spaces, <nmax>, is *configurable*);
- ANY_W2 for any type of a vector W2* function space, i.e. W2, W2H, W2V and W2broken but not W2*trace spaces.

As mentioned [previously](#), ANY_SPACE_<n> and ANY_W2 function space types are treated as continuous while ANY_DISCONTINUOUS_SPACE_<n> spaces are treated as discontinuous.

Note: The name and use of ANY_W2 metadata (e.g. continuity and vector or/and scalar basis of W2* spaces the metadata can represent) are being reviewed in PSyclone issue #540.

Since the LFRic API operates on columns of data, function spaces are categorised as continuous or discontinuous with regard to their **continuity in the horizontal**. For example, a GH_FIELD that specifies GH_INC as its access pattern (see :ref:dynamo0.3-kernel-valid-access: above) may be continuous in the vertical (and discontinuous in the horizontal), continuous in the horizontal (and discontinuous in the vertical), or continuous in both. In each case the code is the same. This principle of horizontal continuity also applies to the three generic ANY_*_* function space identifiers above. The valid metadata values for continuous and discontinuous function spaces are summarised in the table below.

Function Space Continuity	Function Space Name
Continuous	W0, W1, W2, W2H, W2trace, W2Htrace, ANY_W2, ANY_SPACE_<n>
Discontinuous	W2broken, W2V, W2Vtrace, W3, Wtheta, ANY_DISCONTINUOUS_SPACE_<n>

Horizontally discontinuous function spaces and fields over them will not need colouring so PSyclone does not perform it. If such attempt is made, PSyclone will raise a Generation Error in the **Dynamo0p3ColourTrans** transformation (see [Transformations](#) for more details on transformations). An example of fields iterating over a discontinuous function space Wtheta is given in examples/lfric/eg9, with the GH_READWRITE access descriptor denoting an update to the relevant fields. This example also demonstrates how to only colour loops over continuous function spaces when transformations are applied.

Read-Only Function Spaces

LFRic supports the concept of a **read-only function space**. A field on such a function space must not be modified by any kernels contained within invoke calls (i.e. within any code that PSyclone is responsible for). Further, a field on a read-only function space must contain clean halos in order to avoid any halo exchanges that would occur if the field is read within a kernel where redundant computation is performed.

The primary reason for including a read-only function space is that it does not need any halo-exchange support e.g. it does not require a routing table, which can reduce the memory footprint.

Currently Wchi is the only read-only function space in LFRic.

As a read-only function space is not modified, it does not matter whether it is classified as continuous or discontinuous. LFRic therefore treats read-only as a third category of function space.

Optional Field Metadata

A field entry in the meta_args array may have an optional fifth element. This element describes either a stencil access or, for inter-grid kernels, which mesh the field is on. Since an inter-grid kernel is not permitted to have stencil accesses, these two options are mutually exclusive. The metadata for each case is described in the following sections.

Stencil Metadata

Stencil metadata specifies that the corresponding field argument is accessed as a stencil operation within the Kernel. Stencil metadata only makes sense if the associated field is read within a Kernel i.e. it only makes sense to specify stencil metadata if the first entry is GH_FIELD and the second entry is GH_READ.

Stencil metadata is written in the following format:

```
STENCIL(type)
```

where type may be one of X1D, Y1D, XORY1D, CROSS, CROSS2D or REGION. As the stencil extent (the maximum distance from the central cell that the stencil extends) is not provided in the metadata, it is expected to be provided by the algorithm writer as part of the invoke call (see Section [Stencils](#)). As there is currently no way to specify a fixed extent value for stencils in the Kernel metadata, Kernels must therefore be written to support different values of extent (i.e. stencils with a variable number of cells).

The XORY1D stencil type indicates that the Kernel can accept either X1D or Y1D stencils. In this case it is up to the algorithm developer to specify which of these it is from the algorithm layer as part of the invoke call (see Section [Stencils](#)).

For example, the following stencil (with extent=2):

```
| 3 | 2 | 1 | 4 | 5 |
```

would be declared as:

```
STENCIL(X1D)
```

and the following stencil (with extent=2):

```
| | | 9 | | |
| | | 8 | | |
| 3 | 2 | 1 | 6 | 7 |
```

(continues on next page)

(continued from previous page)

		4			
		5			

would be declared as:

```
STENCIL(CROSS)
```

The REGION stencil references a block of cells:

	9		8		7	
	2		1		6	
	3		4		5	

and would be declared as:

```
STENCIL(REGION)
```

Below is an example of stencil information within the full kernel metadata:

```
type(arg_type) :: meta_args(3) = (/
    arg_type(GH_FIELD, GH_REAL, GH_INC, W1),      &
    arg_type(GH_FIELD, GH_REAL, GH_READ, W2H, STENCIL(CROSS)), &
    arg_type(GH_OPERATOR, GH_REAL, GH_READ, W1, W2H)      &
    /)
```

There is a full example of this distributed with PSyclone. It may be found in `examples/lfric/eg5`.

Inter-Grid Metadata

The alternative form of the optional fifth metadata argument for a field specifies which mesh the associated field is on. This is required for inter-grid kernels which perform prolongation or restriction operations on fields (or field vectors) existing on grids of different resolutions.

Mesh metadata is written in the following format:

```
mesh_arg=type
```

where `type` may be one of `GH_COARSE` or `GH_FINE`. Any kernel having a field argument with this metadata is assumed to be an inter-grid kernel and, as such, all of its other arguments (which must also be fields) must have it specified too. An example of the metadata for such a kernel is given below:

```
type(arg_type) :: meta_args(2) = (/
    arg_type(GH_FIELD, GH_REAL, GH_READWRITE, ANY_DISCONTINUOUS_SPACE_1, &
        mesh_arg=GH_COARSE), &
    arg_type(GH_FIELD, GH_REAL, GH_READ, ANY_DISCONTINUOUS_SPACE_2, &
        mesh_arg=GH_FINE ) &
    /)
```

Note that an inter-grid kernel must have at least one field (or field- vector) argument on each mesh type. Fields that are on different meshes cannot be on the same function space while those on the same mesh must also be on the same function space.

Column-wise Operators (CMA)

In this section we provide example metadata for each of the three recognised kernel types involving CMA operators.

Column-wise operators are constructed from cell-wise (local) operators. Therefore, in order to **assemble** a CMA operator, a kernel must have at least one read-only LMA operator, e.g.:

```
type(arg_type) :: meta_args(2) = (/
    arg_type(GH_OPERATOR,          GH_REAL, GH_READ, ANY_SPACE_1, ANY_SPACE_2),
    ↪ &
    arg_type(GH_COLUMNWISE_OPERATOR, GH_REAL, GH_WRITE, ANY_SPACE_1, ANY_
    ↪ SPACE_2) &
    /)
```

CMA operators (and their inverse) are **applied** to fields. Therefore any kernel of this type must have one read-only CMA operator, one read-only field and a field that is updated, e.g.:

```
type(arg_type) :: meta_args(3) = (/
    arg_type(GH_FIELD,          GH_REAL, GH_INC, ANY_SPACE_1),          &
    arg_type(GH_FIELD,          GH_REAL, GH_READ, ANY_SPACE_2),          &
    arg_type(GH_COLUMNWISE_OPERATOR, GH_REAL, GH_READ, ANY_SPACE_1, ANY_
    ↪ SPACE_2) &
    /)
```

Matrix-matrix kernels compute the product/linear combination of CMA operators. They must therefore have one such operator that is updated while the rest are read-only. They may also have read-only scalar arguments, e.g.:

```
type(arg_type) :: meta_args(3) = (/
    arg_type(GH_COLUMNWISE_OPERATOR, GH_REAL, GH_WRITE, ANY_SPACE_1, ANY_
    ↪ SPACE_2), &
    arg_type(GH_COLUMNWISE_OPERATOR, GH_REAL, GH_READ, ANY_SPACE_1, ANY_
    ↪ SPACE_2), &
    arg_type(GH_COLUMNWISE_OPERATOR, GH_REAL, GH_READ, ANY_SPACE_1, ANY_
    ↪ SPACE_2), &
    arg_type(GH_SCALAR,          GH_REAL, GH_READ) /)
```

Note: The order with which arguments are specified in metadata for CMA kernels does not affect the process of identifying the type of kernel (whether it is assembly, matrix-matrix etc.)

meta_funcs

The (optional) second component of kernel metadata specifies whether any quadrature or evaluator data is required for a given function space. (If no quadrature or evaluator data is required then this metadata should be omitted.) Consider the following kernel metadata:

```
type, extends(kernel_type) :: testkern_operator_type
type(arg_type, dimension(3)) :: meta_args =
    (/ arg_type(gh_operator, gh_real, gh_write, w0, w0), &
    arg_type(gh_field*3, gh_real, gh_read, w1), &
    arg_type(gh_scalar, gh_integer, gh_read) &
    /)
```

(continues on next page)

(continued from previous page)

```

type(func_type) :: meta_funcs(2) =                &
  (/ func_type(w0, gh_basis, gh_diff_basis)         &
    func_type(w1, gh_basis)                         &
  /)
integer :: gh_shape = gh_quadrature_XYoZ
integer :: operates_on = cell_column
contains
  procedure, nopass :: code => testkern_operator_code
end type testkern_operator_type

```

The `arg_type` component of this metadata describes a kernel that takes three arguments (an operator, a field and an integer scalar). Following the `meta_args` array we now have a `meta_funcs` array. This allows the user to specify that the kernel requires basis functions (`gh_basis`) and/or the differential of the basis functions (`gh_diff_basis`) on one or more of the function spaces associated with the arguments listed in `meta_args`. In this case we require both for the W0 function space but only basis functions for W1.

Note: Basis and differential basis functions for both real- and integer-valued field arguments have real values on the points on which these functions are *required*.

meta_reference_element

A kernel that requires properties of the reference element in LFRic specifies those properties through the `meta_reference_element` metadata entry. (If no reference element properties are required then this metadata should be omitted.) Consider the following example kernel metadata:

```

type, extends(kernel_type) :: testkern_type
  type(arg_type), dimension(2) :: meta_args =      &
    (/ arg_type(gh_field, gh_real, gh_read, w1), &
      arg_type(gh_field, gh_real, gh_inc, w0) /)
  type(reference_element_data_type), dimension(2) ::      &
    meta_reference_element =                          &
    (/ reference_element_data_type(normals_to_horizontal_faces), &
      reference_element_data_type(normals_to_vertical_faces) /)
contains
  procedure, nopass :: code => testkern_code
end type testkern_type

```

This metadata specifies that the `testkern_type` kernel requires two properties of the reference element. The supported properties are listed below:

Name	Description
<code>normals_to_horizontal_faces</code>	Array of normals pointing in the positive (x, y, z) axis direction for each horizontal face indexed as (component, face).
<code>normals_to_vertical_faces</code>	Array of normals pointing in the positive (x, y, z) axis direction for each vertical face indexed as (component, face).
<code>normals_to_faces</code>	Array of normals pointing in the positive (x, y, z) axis direction for each face indexed as (component, face).
<code>outward_normals_to_horizontal_faces</code>	Array of outward-pointing normals for each horizontal face indexed as (component, face).
<code>outward_normals_to_vertical_faces</code>	Array of outward-pointing normals for each vertical face indexed as (component, face).
<code>outward_normals_to_faces</code>	Array of outward-pointing normals for each face indexed as (component, face).

meta_mesh

A kernel that requires properties of the LFRic mesh object specifies those properties through the `meta_mesh` metadata entry. (If no mesh properties are required then this metadata should be omitted.) Consider the following example kernel metadata:

```

type, extends(kernel_type) :: testkern_type
  type(arg_type), dimension(2) :: meta_args = &
    (/ arg_type(gh_field, gh_real, gh_read, w1), &
       arg_type(gh_field, gh_real, gh_inc, w0) /)
  type(mesh_data_type), dimension(1) :: &
    meta_mesh = &
    (/ mesh_data_type(adjacent_face) /)
contains
  procedure, nopass :: code => testkern_code
end type testkern_type

```

This metadata specifies that the `testkern_type` kernel requires one property of the mesh. There is currently one supported property:

Name	Description
<code>adjacent_face</code>	Local ID of a neighbouring face in each horizontally-adjacent cell indexed as (face).

gh_shape and gh_evaluator_targets

If a kernel requires basis or differential-basis functions then the metadata must also specify the set of points on which these functions are required. This information is provided by the `gh_shape` component of the metadata. Currently PSyclone supports four shapes; `gh_quadrature_XYoZ` for Gaussian quadrature points, `gh_quadrature_face` for quadrature points on cell faces, `gh_quadrature_edge` for quadrature points on cell edges and `gh_evaluator` for evaluation at nodal points. If a kernel requires just one of these then `gh_shape` is an integer scalar. However, if more than one is required then `gh_shape` becomes a one-dimensional, integer array, e.g.:

```
integer :: gh_shape(2) = (/ gh_quadrature_face, gh_quadrature_edge /)
```

If a kernel requires an evaluator then there are two options: if an evaluator is required for multiple function spaces then these can be specified using the additional `gh_evaluator_targets` metadata entry. This entry is a one-dimensional,

integer array containing the desired function spaces. For example, to request basis/differential-basis functions evaluated on both W0 and W1, the metadata would be:

```
integer :: gh_shape = gh_evaluator
integer :: gh_evaluator_targets(2) = (/W0, W1/)
```

The kernel must have an argument (field or operator) on each of the function spaces listed in `gh_evaluator_targets`. The default behaviour if `gh_evaluator_targets` is not specified is to provide evaluators for each function space associated with the quantities that the kernel is updating. All necessary data is extracted in the PSy layer and passed to the kernel(s) as required - nothing is required from the Algorithm layer. If a kernel requires quadrature on the other hand, the Algorithm writer must supply a `quadrature_type` object for each specified quadrature as the last argument(s) to the kernel (see Section [Quadrature](#)).

Note that it is an error for kernel metadata to specify a value for `gh_shape` if no basis or differential-basis functions are required. It is also an error to specify `gh_evaluator_targets` if the kernel does not require an evaluator (i.e. `gh_shape != gh_evaluator`).

operates_on

The fourth type of metadata provided is `OPERATES_ON`. This specifies that the Kernel has been written with the assumption that it is supplied with the specified data for each field/operator argument. For user-supplied kernels this is currently only permitted to be `CELL_COLUMN` or `DOMAIN`. The possible values for `OPERATES_ON` and their interpretation are summarised in the following table:

operates_on	Data passed for each field/operator argument
cell_column	Single column of cells
dof	Single DoF (currently <i>Built-ins</i> only)
domain	All columns of cells

procedure

The fifth and final type of metadata is procedure metadata. This specifies the name of the Kernel subroutine that this metadata describes.

For example:

```
procedure, nopass :: my_kernel_subroutine
```

12.4.7 Subroutine

Rules for General-Purpose Kernels

The arguments to general-purpose kernels (those that do not involve either CMA operators or prolongation/restriction operations) that operate on cell-columns follow a set of rules which have been specified for the LFRic API. These rules are encoded in the `generate()` method within the `ArgOrdering` abstract class in the `dynamo0p3.py` file. The rules, along with PSyclone's naming conventions, are:

- 1) If an LMA operator is passed then include the `cells` argument. `cells` is an integer of kind `i_def` and has intent `in`.
- 2) Include `nlayers`, the number of layers in a column. `nlayers` is an integer of kind `i_def` and has intent `in`.
- 3) For each scalar/field/vector_field/operator in the order specified by the `meta_args` metadata:

- 1) If the current entry is a scalar quantity then include the Fortran variable in the argument list. The intent is determined from the metadata (see [meta_args](#) for an explanation).
- 2) If the current entry is a field then include the field array. The field array name is currently specified as being "field_"<argument_position>" "<field_function_space>. A field array is a rank-1, real array with extent equal to the number of unique degrees of freedom for the space that the field is on. Its precision (kind) depends on how it is defined in the algorithm layer, see the [Mixed Precision](#) section for more details. This value is passed in separately. Again, the intent is determined from the metadata (see [meta_args](#)).
 - 1) If the field entry has a stencil access then add an integer (or if the stencil is of type CROSS2D, an integer rank-1 array of extent 4 and kind i_def) stencil-size argument with intent in. This will supply the number of cells in the stencil or, in the case of the CROSS2D stencil, the number of cells in each branch of the stencil.
 - 2) If the stencil is of type CROSS2D then an integer of kind i_def and intent in for the max branch length is needed. This is used in defining the dimensions of the stencil dofmap array and is required due to the varying length of the branches of the stencil when used on planar meshes.
 - 3) Also needed is a stencil dofmap array of type integer, kind i_def and intent in in either 2 or 3 dimensions. For a CROSS2D stencil the array needs dimensions of (number-of-dofs-in-cell, max-branch-length, 4). All other stencils need dimensions of (number-of-dofs-in-cell, stencil-size).
 - 4) If the field entry stencil access is of type XORY1D then add an additional integer direction argument of kind i_def and with intent in.
- 3) If the current entry is a field vector then for each dimension of the vector, include a field array. The field array name is specified as being using "field_"<argument_position>" "<field_function_space>"_v"<vector_position>. A field array in a field vector is declared in the same way as a field array (described in the previous step).
- 4) If the current entry is an operator then first include an integer extent of kind i_def. The name of this extent is <operator_name>"_ncell_3d". Next include the operator. This is a rank-3, real array. Its precision (kind) depends on how it is defined in the algorithm layer, see the [Mixed Precision](#) section for more details. The extents of the first two dimensions are the local degrees of freedom for the to and from function spaces, respectively, and that of the third is <operator_name>"_ncell_3d". The name of the operator is "op_"<argument_position>. Again the intent is determined from the metadata (see [meta_args](#)).
- 4) For each function space in the order they appear in the metadata arguments (the to function space of an operator is considered to be before the from function space of the same operator as it appears first in lexicographic order)
 - 1) Include the number of local degrees of freedom (i.e. number per-cell) for the function space. This is an integer of kind i_def and has intent in. The name of this argument is "ndf_"<field_function_space>.
 - 2) If there is a field on this space
 - 1) Include the unique number of degrees of freedom for the function space. This is an integer of kind i_def and has intent in. The name of this argument is "undf_"<field_function_space>.
 - 2) Include the **dofmap** for this function space. This is an integer array of kind i_def with intent in. It has one dimension sized by the local degrees of freedom for the function space.
 - 3) For each operation on the function space (basis, diff_basis), in the order specified in the metadata, pass real arrays of kind r_def with intent in. For each shape specified in the gh_shape metadata entry:
 - 1) If shape is gh_quadrature_* then the arrays are of rank four and are named "basis_"<field_function_space>"_<quadrature_arg_name>" or "diff_basis_"<field_function_space>"_<quadrature_arg_name>", as appropriate:
 - 1) If shape is gh_quadrature_xyoz then the arrays have extent (dimension, number_of_dofs, np_xy, np_z).

- 2) If `shape` is `gh_quadrature_face` or `gh_quadrature_edge` then the arrays have extent (dimension, number_of_dofs, np_xyz, nfaces or nedges).
- 2) If `shape` is `gh_evaluator` then we pass one array for each target function space (i.e. as specified by `gh_evaluator_targets`). Each of these arrays are of rank three with extent (dimension, number_of_dofs, ndf_<target_function_space>). The name of the argument is "basis_<field_function_space>_on_<target_function_space>" or "diff_basis_<field_function_space>_on_<target_function_space>", as appropriate.

Here <quadrature_arg_name> is the name of the corresponding quadrature object being passed to the Invoke. dimension is 1 or 3 and depends upon the function space (see [Supported Function Spaces](#) above for more information) and whether or not it is a basis or a differential basis function (see the table below). number_of_dofs is the number of degrees of freedom (DoFs) associated with the function space and np_* are the number of points to be evaluated: i) *_xyz in all directions (3D); ii) *_xy in the horizontal plane (2D); iii) *_x, *_y in the horizontal (1D); and iv) *_z in the vertical (1D). nfaces and nedges are the number of horizontal faces/edges obtained from the appropriate quadrature object supplied to the Invoke.

Function Type	Dimension	Function Space Name
Basis	1	W0, W2trace, W2Htrace, W2Vtrace, W3, Wtheta, Wchi
	3	W1, W2, W2H, W2V, W2broken, ANY_W2
Differential Basis	1	W2, W2H, W2V, W2broken, ANY_W2
	3	W0, W1, W2trace, W2Htrace, W2Vtrace, W3, Wtheta, Wchi

- 5) If either the `normals_to_horizontal_faces` or `outward_normals_to_horizontal_faces` properties of the reference element are required then pass the number of horizontal faces of the reference element (`nfaces_re_h`). Similarly, if either the `normals_to_vertical_faces` or `outward_normals_to_vertical_faces` are required then pass the number of vertical faces (`nfaces_re_v`). This also holds for the `normals_to_faces` and `outward_normals_to_faces` where the number of all faces of the reference element (`nfaces_re`) is passed to the kernel. (All of these quantities are integers of kind `i_def`.) Then, in the order specified in the `meta_reference_element` metadata:
 - 1) For the `normals_to_horizontal/vertical_faces`, pass a rank-2 integer array of kind `i_def` with dimensions (3, `nfaces_re_h/v`).
 - 2) For the `outward_normals_to_horizontal/vertical_faces`, pass a rank-2 integer array of kind `i_def` with dimensions (3, `nfaces_re_h/v`).
 - 3) For `normals_to_faces` or `outward_normals_to_faces` pass a rank-2 integer array of kind `i_def` with dimensions (3, `nfaces_re`).
- 6) If the `adjacent_face` mesh property is required then:
 - 1) If the number of horizontal cell faces obtained from the reference element (`nfaces_re_h`) is not already being passed to the kernel (due to rule 5 above) then supply it here. This is an integer of kind `i_def`.
 - 2) Pass a rank-1, integer array of kind `i_def` and extent `nfaces_re_h`.
- 7) If Quadrature is required (`gh_shape = gh_quadrature_*`) then, for each shape in the order specified in the `gh_shape` metadata:
 - 1) Include integer, scalar arguments of kind `i_def` with intent in that specify the extent of the basis/diff-basis arrays:
 - 1) If `gh_shape` is `gh_quadrature_XYoZ` then pass `np_xy_<quadrature_arg_name>` and `np_z_<quadrature_arg_name>`.
 - 2) If `gh_shape` is `gh_quadrature_face/_edge` then pass `nfaces/nedges_<quadrature_arg_name>` and `np_xyz_<quadrature_arg_name>`.

2) Include weights which are real arrays of kind `r_def`:

- 1) If `gh_quadrature_XYoZ` pass in `weights_xz_<quadrature_arg_name>` (rank one, extent `np_xy_<quadrature_arg_name>`) and `weights_z_<quadrature_arg_name>` (rank one, extent `np_z_<quadrature_arg_name>`).
- 2) If `gh_quadrature_face/_edge` pass in `weights_xyz_<quadrature_arg_name>` (rank two with extents [`np_xyz_<quadrature_arg_name>`, `nfaces/nedges_<quadrature_arg_name>`]).

Examples

For instance, if a kernel has only one written argument and requires an evaluator then its metadata might be:

```
type, extends(kernel_type) :: testkern_operator_type
  type(arg_type), dimension(2) :: meta_args =      &
    (/ arg_type(gh_operator, gh_real, gh_write, w0, w1), &
      arg_type(gh_field*3, gh_real, gh_read, w0) /)
  type(func_type) :: meta_funcs(1) =              &
    (/ func_type(w0, gh_basis) /)
  integer :: operates_on = cell_column
  integer :: gh_shape = gh_evaluator
contains
  procedure, nopass :: code => testkern_operator_code
end type testkern_operator_type
```

then we only pass the basis functions evaluated on `W0` (the space of the written kernel argument). The subroutine arguments will therefore be:

```
subroutine testkern_operator_code(cell, nlayers, ncell_3d,      &
  local_stencil, xdata, ydata, zdata, ndf_w0, undf_w0, map_w0, &
  basis_w0_on_w0, ndf_w1)
```

where `local_stencil` is the operator, `xdata`, `ydata` etc. are the three components of the field vector and `map_w0` is the dofmap for the `W0` function space.

If instead, `gh_evaluator_targets` is specified in the metadata:

```
type, extends(kernel_type) :: testkern_operator_type
  type(arg_type), dimension(2) :: meta_args =      &
    (/ arg_type(gh_operator, gh_real, gh_write, w0, w1), &
      arg_type(gh_field*3, gh_real, gh_read, w0) /)
  type(func_type) :: meta_funcs(1) =              &
    (/ func_type(w0, gh_basis) /)
  integer :: operates_on = cell_column
  integer :: gh_shape = gh_evaluator
  integer :: gh_evaluator_targets(2) = (/W0, W1/)
contains
  procedure, nopass :: code => testkern_operator_code
end type testkern_operator_type
```

then we will need to pass two sets of basis functions (evaluated at `W0` and at `W1`):

```
subroutine testkern_operator_code(cell, nlayers, ncell_3d,      &
  local_stencil, xdata, ydata, zdata, ndf_w0, undf_w0, map_w0, &
  basis_w0_on_w0, basis_w0_on_w1, ndf_w1)
```

If the metadata specifies that a kernel requires both an evaluator and quadrature:

```
type, extends(kernel_type) :: testkern_operator_type
  type(arg_type), dimension(2) :: meta_args =          &
    (/ arg_type(gh_operator, gh_real, gh_write, w0, w1), &
      arg_type(gh_field*3, gh_real, gh_read, w0) /)
  type(func_type) :: meta_funcs(1) =                  &
    (/ func_type(w0, gh_basis) /)
  integer :: operates_on = cell_column
  integer :: gh_shape(2) = (/ gh_evaluator, gh_quadrature_face /)
contains
  procedure, nopass :: code => testkern_operator_code
end type testkern_operator_type
```

then we will need to pass basis functions for both the evaluator and the quadrature (where `qr_face` is the name of the face-quadrature object passed to the `Invoke`):

```
subroutine testkern_operator_code(cell, nlayers, ncell_3d,          &
  local_stencil, xdata, ydata, zdata, ndf_w0, undf_w0, map_w0,    &
  basis_w0_on_w0, basis_w0_qr_face, ndf_w1,                      &
  np_xyz_qr_face, nfaces_qr_face, weights_xyz_qr_face)
```

If the metadata specifies that the kernel requires a property of the reference element:

```
type, extends(kernel_type) :: testkern_operator_type
  type(arg_type), dimension(2) :: meta_args =          &
    (/ arg_type(gh_operator, gh_real, gh_write, w0, w1), &
      arg_type(gh_field*3, gh_real, gh_read, w0) /)
  type(reference_element_data_type) :: meta_reference_element(1) = &
    (/ reference_element_data_type(normals_to_horizontal_faces) /)
  integer :: operates_on = cell_column
contains
  procedure, nopass :: code => testkern_operator_code
end type testkern_operator_type
```

then the kernel must be passed the number of faces of the reference element and the array of face normals in the specified direction (here horizontal):

```
subroutine testkern_operator_code(cell, nlayers, ncell_3d,          &
  local_stencil, xdata, ydata, zdata, ndf_w0, undf_w0, map_w0, &
  nfaces_re_h, normals_face_h)
```

Rules for CMA Kernels

Kernels involving CMA operators are restricted to just three types; assembly, application/inverse-application and matrix-matrix. We give the rules for each of these in the sections below.

Assembly

An assembly kernel requires the column-banded dofmap for both the to- and from-function spaces of the CMA operator being assembled as well as the number of DoFs for each of the dofmaps. The full set of rules is:

- 1) Include the cell argument. cell is an integer of kind i_def and has intent in.
- 2) Include nlayers, the number of layers in a column. nlayers is an integer of kind i_def and has intent in.
- 3) Include the total number of cells in the 2D mesh (including halos), ncell_2d, which is an integer of kind i_def with intent in.
- 4) Include the total number of cells, ncell_3d, which is an integer of kind i_def with intent in.
- 5) For each argument in the meta_args metadata array:
 - 1) If it is a LMA operator, include a real, 3-dimensional array. The first two dimensions are the local degrees of freedom for the to and from spaces, respectively. The third dimension is ncell_3d. The precision of the array depends on how it is defined in the algorithm layer, see the *Mixed Precision* section for more details;
 - 2) If it is a CMA operator, include a real, 3-dimensional array of kind r_solver. The first dimension is "bandwidth_"<operator_name>, the second is "nrow_"<operator_name>, and the third is ncell_2d.
 - 1) Include the number of rows in the banded matrix. This is an integer of kind i_def with intent in and is named as "nrow_"<operator_name>.
 - 2) If the from-space of the operator is *not* the same as the to-space then include the number of columns in the banded matrix. This is an integer of kind i_def with intent in and is named as "ncol_"<operator_name>.
 - 3) Include the bandwidth of the banded matrix. This is an integer of kind i_def with intent in and is named as "bandwidth_"<operator_name>.
 - 4) Include banded-matrix parameter alpha. This is an integer of kind i_def with intent in and is named as "alpha_"<operator_name>.
 - 5) Include banded-matrix parameter beta. This is an integer of kind i_def with intent in and is named as "beta_"<operator_name>.
 - 6) Include banded-matrix parameter gamma_m. This is an integer of kind i_def with intent in and is named as "gamma_m_"<operator_name>.
 - 7) Include banded-matrix parameter gamma_p. This is an integer of kind i_def with intent in and is named as "gamma_p_"<operator_name>.
 - 3) If it is a field or scalar argument then include arguments following the same rules as for general-purpose kernels.
- 6) For each unique function space in the order they appear in the metadata arguments (the to function space of an operator is considered to be before the from function space of the same operator as it appears first in lexicographic order):
 - 1) Include the number of degrees of freedom per cell for the space. This is an integer of kind i_def with intent in. The name of this argument is "ndf_"<arg_function_space>.
 - 2) If there is a field on this space then:

- 1) Include the unique number of degrees of freedom for the function space. This is an integer of kind `i_def` and has intent `in`. The name of this argument is `"undf_"<field_function_space>`.
- 2) Include the dofmap for this space. This is an integer array of kind `i_def` with intent `in`. It has one dimension sized by the local degrees of freedom for the function space.
- 3) If the CMA operator has this space as its to/from space then include the column-banded dofmap, the list of offsets for the to/from-space. This is an integer array of rank 2 and kind `i_def`. The first dimension is `"ndf_"<arg_function_space>` and the second is `nlayers`.

Application/Inverse-Application

A kernel applying a CMA operator requires the column-indirection dofmap for both the to- and from-function spaces of the CMA operator. Since it does not have any LMA operator arguments it does not require the `ncell_3d` and `nlayers` scalar arguments. (Since a column-wise operator is, by definition, assembled for a whole column, there is no loop over levels when applying it.) The full set of rules is then:

- 1) Include the cell argument. `cell` is an integer of kind `i_def` and has intent `in`.
- 2) Include the total number of cells in the 2D mesh (including halos), `ncell_2d`, which is an integer of kind `i_def` with intent `in`.
- 3) For each argument in the `meta_args` metadata array:
 - 1) If it is a field, include the field array. This is a real array of rank 1. Its precision (kind) depends on how it is defined in the algorithm layer, see the *Mixed Precision*. The field array name is currently specified as being `"field_"<argument_position>_"_"<field_function_space>`. The extent of the array is the number of unique degrees of freedom for the function space that the field is on. This value is passed in separately. The intent of the argument is determined from the metadata (see *meta_args*);
 - 2) If it is a CMA operator, include it and its associated parameters (see Rule 5 of CMA Assembly kernels).
- 4) For each of the unique function spaces encountered in the metadata arguments (the to function space of an operator is considered to be before the from function space of the same operator as it appears first in lexicographic order):
 - 1) Include the number of degrees of freedom per cell for the associated function space. This is an integer of kind `i_def` with intent `in`. The name of this argument is `"ndf_"<field_function_space>`;
 - 2) Include the number of unique degrees of freedom for the associated function space. This is an integer of kind `i_def` with intent `in`. The name of this argument is `"undf_"<field_function_space>`;
 - 3) Include the dofmap for this function space. This is a rank-1 integer array of kind `i_def` with extent equal to the number of degrees of freedom of the space (`"ndf_"<field_function_space>`).
- 5) Include the indirection map for the to-space of the CMA operator. This is a rank-1 integer array of kind `i_def` with extent `nrow`.
- 6) If the from-space of the operator is *not* the same as the to-space then include the indirection map for the from-space of the CMA operator. This is a rank-1 integer array of kind `i_def` with extent `ncol`.

Matrix-Matrix

Does not require any dofmaps and also does not require the `nlayers` and `ncell_3d` scalar arguments. The full set of rules are then:

- 1) Include the `cell` argument. `cell` is an integer of kind `i_def` and has intent `in`.
- 2) Include the total number of cells in the 2D mesh (including halos), `ncell_2d`, which is an integer of kind `i_def` with intent `in`.
- 3) For each CMA operator or scalar argument specified in metadata:
 - 1) If it is a CMA operator, include it and its associated parameters (see Rule 5 of CMA Assembly kernels);
 - 2) If it is a scalar argument include the corresponding Fortran variable in the argument list with intent `in`.

Rules for Inter-Grid Kernels

As already specified, inter-grid kernels are only permitted to take fields and/or field-vectors as arguments. Fields (and field-vectors) that are on different meshes must be on different function spaces. Fields on the same mesh must also be on the same function space.

Argument ordering follows the general pattern used for ‘normal’ kernels with field data being followed by dofmap data. The rules for arguments to inter-grid kernels are as follows:

- 1) Include `nlayers`, the number of layers in a column. `nlayers` is an integer of kind `i_def` and has intent `in`.
- 2) Include the `cell_map` for the current cell (column). This is an integer array of rank two, kind `i_def` and intent `in` which provides the mapping from the coarse to the fine mesh. It has extent `(ncell_f_per_c_x, ncell_f_per_c_y)`.
- 3) Include `ncell_f_per_c_x`, and `ncell_f_per_c_y`, the numbers of fine cells per coarse cell in the `x` and `y` directions, respectively. These are integers of kind `i_def` and have intent `in`.
- 4) Include `ncell_f`, the number of cells (columns) in the fine mesh. This is an integer of kind `i_def` and has intent `in`.
- 5) For each argument in the `meta_args` metadata array (which must be a field or field-vector):
 - 1) Pass in field data as done for a regular kernel.
- 6) For each unique function space (of which there will currently be two) in the order in which they are encountered in the `meta_args` metadata array, include dofmap information:

If the dofmap is associated with an argument on the fine mesh:

- 1) Include `ndf_fine`, the number of DoFs per cell for the FS of the field on the fine mesh;
- 2) Include `undf_fine`, the number of unique DoFs per cell for the FS of the field on the fine mesh;
- 3) Include `dofmap_fine`, the *whole* dofmap for the fine mesh. This is an integer array of rank two and kind `i_def` with intent `in`. The extent of the first dimension is `ndf_fine` and that of the second is `ncell_f`.

else, the dofmap is associated with an argument on the coarse mesh:

- 1) Include `undf_coarse`, the number of unique DoFs for the coarse field. This is an integer of kind `i_def` with intent `in`;
- 2) Include `dofmap_coarse`, the dofmap for the current cell (column) in the coarse mesh. This is an integer array of rank one, kind `i_def` and has intent `in`.

Rules for Domain Kernels

The rules for kernels that have `operates_on = DOMAIN` are almost identical to those for general-purpose kernels (described [above](#)), allowing for the fact that they are not permitted any type of operator argument or any argument with a stencil access. The only difference is that, since the kernel operates on the whole domain, the number of columns in the mesh excluding those in the halo (`ncell_2d_no_halos`), must be passed in. This is provided as the second argument to the kernel (after `nlayers`). `ncell_2d_no_halos` is an integer of kind `i_def` with intent `in`.

Argument Intents

As described [above](#), LFRic kernels read and/or update the data pointed to by objects such as *fields* or *operators*. This data is passed to the kernels as *subroutine arguments* and their Fortran intents usually follow the logic determined by their *access modes*.

- `GH_READ` indicates intent(`in`) as the argument is only ever read from.
- `GH_WRITE` (for discontinuous function spaces) indicates that the argument is only written to in a kernel. The field and operator arguments' data in LFRic are always defined outside of a kernel so the argument intent for this access type is intent(`inout`).
- `GH_INC`, `GH_READINC` and `GH_READWRITE` indicate intent(`inout`) as the arguments are updated (albeit in a different way due to different access to DoFs, see *meta_args* for more details).

12.4.8 Kernel Naming Conventions

LFRic development uses strict naming conventions related to kernels. While they are not a requirement for PSyclone itself, any LFRic development should follow these conventions (see e.g. *LFRic examples* in PSyclone):

Module name:

`<base_name>_kernel_mod`

Kernel type name:

`<base_name>_kernel_type`

Subroutine name:

`<base_name>_code`

The latest version of the LFRic coding style guidelines are available in this [LFRic wiki page](#) (requires login access to MOSRS, see the above *introduction* to the LFRic API).

12.5 Built-ins

The basic concept of a PSyclone Built-in is described in the *Built-ins* section. In the LFRic (Dynamo0.3) API, calls to Built-ins generally follow a convention that the field/scalar written to comes first in the argument list. LFRic Built-ins must conform to the following rules:

- 1) They must have one and only one modified (i.e. written to) argument.
- 2) They must operate on a DoF (`operates_on = DOF` metadata).
- 3) There must be at least one field in the argument list. This is so that we know the number of DoFs to iterate over in the PSy layer.
- 4) Kernel arguments must be either fields or scalars (real- and/or integer-valued).

- 5) All field arguments to a given Built-in must be on the same function space. This is because all current Built-ins operate on DoFs and therefore all fields should have the same number. It also means that we can determine the number of DoFs uniquely when a scalar is written to;
- 6) Built-ins that update real-valued fields can, in general, only read from other real-valued fields, but they can take both real and integer scalar arguments (see rule 8 for exceptions);
- 7) Built-ins that update integer-valued fields can, in general, only read from other integer-valued fields and take integer scalar arguments (see rule 8 for exceptions);
- 8) The only two exceptions from the rules 6) and 7) above regarding the same data type of “write” and “read” field arguments are Built-ins that convert field data from real to integer, `int_X`, and from integer to real, `real_X`.

The Built-ins supported for the LFRic API are listed in the related subsections, grouped first by the data type of fields they operate on (*real-valued* and *integer-valued*) and then by the mathematical operation they perform.

The field arguments in Built-ins are the derived types that represent the *LFRic fields*, however mathematical operations are actually performed on the data of the *field proxies* (e.g. `field1_proxy%data(:)`). For instance, `X_plus_Y` Built-in adds the values of two fields accessed via their proxies in a loop over DoFs:

```
DO df=loop0_start,loop0_stop
  field3_proxy%data(df) = field1_proxy%data(df) + field2_proxy%data(df)
```

where the precise values of the loop limits depend on the use of *distributed memory*, *annexed DoFs* or both.

As described in the PSy-layer *Argument Intents* section, the Fortran intent of LFRic *field* objects is always in (because it is only the data pointed to from within the object that is modified). The field or scalar that has its data modified by a Built-in is marked in **bold**.

For clarity, the calculation performed by each Built-in is described using Fortran array syntax without the details about field proxies. The actual implementation of the Built-in may change in future (e.g. it could be implemented by PSyclone generating a call to an optimised Maths library).

12.5.1 Metadata

The code below outlines the elements of the LFRic API Built-in metadata for the Built-ins that update a real-valued field, 1) ‘`meta_args`’, 2) ‘`operates_on`’ and 3) ‘`procedure`’:

```
type, public, extends(kernel_type) :: aX_plus_bY
  private
  type(arg_type) :: meta_args(5) = (/
    arg_type(GH_FIELD, GH_REAL GH_WRITE, ANY_SPACE_1), &
    arg_type(GH_SCALAR, GH_REAL, GH_READ), &
    arg_type(GH_FIELD, GH_REAL, GH_READ, ANY_SPACE_1), &
    arg_type(GH_SCALAR, GH_REAL, GH_READ), &
    arg_type(GH_FIELD, GH_REAL GH_READ, ANY_SPACE_1) &
  /)
  integer :: operates_on = DOF
contains
  procedure, nopass :: aX_plus_bY_code
end type aX_plus_bY
```

As can be seen, the metadata for a Built-in kernel is a subset of that for a *user-defined Kernel* with the exception that `operates_on` must be `DOF` instead of `CELL_COLUMN`.

The metadata for the LFRic Built-ins that update an integer-valued field is similar:


```

!> ifield3 = ifield1 + ifield2
type, public, extends(kernel_type) :: int_X_plus_Y
  private
  type(arg_type) :: meta_args(3) = (/
    arg_type(GH_FIELD, GH_INTEGER, GH_WRITE, ANY_SPACE_1), &
    arg_type(GH_FIELD, GH_INTEGER, GH_READ, ANY_SPACE_1), &
    arg_type(GH_FIELD, GH_INTEGER, GH_READ, ANY_SPACE_1) &
  /)
  integer :: operates_on = DOF
contains
  procedure, nopass :: int_X_plus_Y_code
end type int_X_plus_Y

```

Valid Data Types and Access Modes

The allowed data types and accesses for arguments in LFRic Built-in kernels are a bit different than for the *user-defined Kernels* and are listed in the table below.

Argument Type	Data Type	Function Space	Access Type
GH_SCALAR	GH_INTEGER	n/a	GH_READ
GH_SCALAR	GH_REAL	n/a	GH_READ, GH_SUM
GH_FIELD	GH_REAL, GH_INTEGER	ANY_SPACE_<n>	GH_READ, GH_WRITE, GH_READWRITE

Note: Since the LFRic infrastructure does not currently support integer reductions, integer scalar arguments in Built-ins are restricted to having read-only access. Also, logical scalar arguments are not permitted.

12.5.2 Naming scheme

The supported Built-ins in the LFRic API are named according to the scheme presented below. Any new Built-in needs to comply with these rules.

- 1) Ordering of arguments in Built-ins calls follows *LHS (result) <- RHS (operation on arguments)* direction, except where a Built-in returns the *LHS* result to one of the *RHS* arguments. In that case ordering of arguments remains as in the *RHS* expression, with the returning *RHS* argument written as close to the *LHS* as it can be without affecting the mathematical expression.
- 2) Field names begin with upper case in short form (e.g. **X, Y, Z**) and any case in long form (e.g. **Field1, field**).
- 3) Scalar names begin with lower case: e.g. **a, b**, are **scalar1, scalar2**. Special names for scalars are: **constant** (or **c**), **innprod** (inner/scalar product of two fields) and **sumfld** (sum of a field).
- 4) Arguments in Built-ins variable declarations and constructs (PSyclone Fortran and Python definitions):
 - 1) Are always written in long form and lower case (e.g. **field1, field2, scalar1, scalar2**);
 - 2) *LHS* result arguments are always listed first;
 - 3) *RHS* arguments are listed in order of appearance in the mathematical expression, except when one of them is the *LHS* result.
- 5) Built-ins names in Fortran consist of:
 - 1) *RHS* arguments in short form (e.g. **X, Y, a, b**) only;

- 2) Descriptive name of mathematical operation on *RHS* arguments in the form `<operationname>_<RHSargs>` or `<RHSargs>_<operationname>_<RHSargs>`;
- 3) Prefix `"inc_"` where the result is returned to one of the *RHS* arguments (i.e. `"inc_"<RHSargs>_<operationname>_<RHSargs>`);
- 4) Prefix `"int_"` for the Built-in operations on the integer-valued field arguments (i.e. `"int_inc_"<RHSargs>_<operationname>_<RHSargs>`), except for the Built-in that converts the data type of field arguments from integer to real (see rule 7 below).
- 6) Built-ins names in Python definitions are similar to their Fortran counterparts, with a few differences:
 - 1) Operators and *RHS* arguments are all in upper case (e.g. **X**, **Y**, **A**, **B**, **Plus**, **Minus**);
 - 2) There are no underscores;
 - 4) Common suffix is "Kern";
 - 3) Common prefix is "LFRic" for the Built-in operations on the real-valued arguments and "LFRicInt" for the Built-in operations on the integer-valued fields (except for the data-type conversion Built-ins, see rule 7 below).
- 7) As in the case of Built-in field argument rules, the names of the field data-type conversion Built-ins, `int_X` (converts field data from real to integer) and `real_X` (converts field data from integer to real), are the only exceptions for the naming of Built-ins in Fortran above.

12.5.3 Built-in operations on real-valued fields

As described [above](#), Built-ins that operate on real-valued fields mandate `GH_REAL` as the kernel metadata for fields and scalars.

The precision of fields and scalars, however, is determined by the algorithm layer via precision variables as described in the [Mixed Precision](#) section (see subsections on [fields](#) and [scalars](#)).

For instance, field and scalar declarations for the `aX_plus_Y` Built-in that operates on `r_solver_field_type` and uses `r_solver` scalar will be:

```
real(kind=r_solver), intent(in) :: ascalar
type(r_solver_field_type), intent(in) :: zfield, xfield, yfield
```

Mixing precisions is not explicitly forbidden, so we may have e.g. `X_divideby_a` Built-in where:

```
real(kind=r_def), intent(in) :: ascalar
type(r_tran_field_type), intent(in) :: yfield, xfield
```

Certain Built-ins are currently restricted in the precision of the arguments that they accept. Those that calculate the inner product and sum of a field are restricted to `r_def` precision because the scalar global reductions in the LFRic infrastructure are currently only able to support `field_type` and hence have `r_def` precision. In addition, all integer arguments to Built-ins are currently restricted to `i_def` precision.

Addition

Built-ins that add (scaled) real-valued fields and return the result as a real-valued field are denoted with the keyword **plus**.

X_plus_Y

X_plus_Y (*field3*, *field1*, *field2*)

Sums two fields and stores the result in the third field ($Z = X + Y$):

```
field3(:) = field1(:) + field2(:)
```

inc_X_plus_Y

inc_X_plus_Y (*field1*, *field2*)

Adds the second field to the first and returns it ($X = X + Y$):

```
field1(:) = field1(:) + field2(:)
```

a_plus_X

a_plus_X (*field2*, *rscalar*, *field1*)

Adds a real scalar value to all elements of a field and stores the result in another field ($Y = a + X$):

```
field2(:) = rscalar + field1(:)
```

inc_a_plus_X

inc_a_plus_X (*rscalar*, *field*)

Adds a real scalar value to all elements of a field and returns the field ($X = a + X$):

```
field(:) = rscalar + field(:)
```

aX_plus_Y

aX_plus_Y (*field3*, *rscalar*, *field1*, *field2*)

Performs $Z = aX + Y$:

```
field3(:) = rscalar*field1(:) + field2(:)
```

inc_aX_plus_Y

inc_aX_plus_Y (*rscalar*, **field1**, *field2*)

Performs $X = aX + Y$ (increments the first field):

```
field1(:) = rscalar*field1(:) + field2(:)
```

inc_X_plus_bY

inc_X_plus_bY (**field1**, *rscalar*, *field2*)

Performs $X = X + bY$ (increments the first field):

```
field1(:) = field1(:) + rscalar*field2(:)
```

aX_plus_bY

aX_plus_bY (**field3**, *rscalar1*, *field1*, *rscalar2*, *field2*)

Performs $Z = aX + bY$:

```
field3(:) = rscalar1*field1(:) + rscalar2*field2(:)
```

inc_aX_plus_bY

inc_aX_plus_bY (*rscalar1*, **field1**, *rscalar2*, *field2*)

Performs $X = aX + bY$ (increments the first field):

```
field1(:) = rscalar1*field1(:) + rscalar2*field2(:)
```

aX_plus_aY

aX_plus_aY (**field3**, *rscalar*, *field1*, *field2*)

Performs $Z = aX + aY = a(X + Y)$:

```
field3(:) = rscalar*(field1(:) + field2(:))
```

Subtraction

Built-ins which subtract (scaled) real-valued fields and return the result as a real-valued field are denoted with the keyword **minus**.

X_minus_Y**X_minus_Y** (*field3*, *field1*, *field2*)Subtracts the second field from the first and returns the result in the third field ($Z = X - Y$):

```
field3(:) = field1(:) - field2(:)
```

inc_X_minus_Y**inc_X_minus_Y** (*field1*, *field2*)Subtracts the second field from the first and returns it ($X = X - Y$):

```
field1(:) = field1(:) - field2(:)
```

a_minus_X**a_minus_X** (*field2*, *rscalar*, *field1*)Subtracts all elements of a field from a real scalar value and stores the result in another field ($Y = a - X$):

```
field2(:) = rscalar - field1(:)
```

inc_a_minus_X**inc_a_minus_X** (*rscalar*, *field*)Subtracts all elements of a field from a real scalar value and returns the field ($X = a - X$):

```
field(:) = rscalar - field(:)
```

X_minus_a**X_minus_a** (*field2*, *field1*, *rscalar*)Subtracts a real scalar value from all elements of a field and stores the result in another field ($Y = X - a$):

```
field2(:) = field1(:) - rscalar
```

inc_X_minus_a**inc_X_minus_a** (*field*, *rscalar*)Subtracts a real scalar value from all elements of a field and returns the field ($X = X - a$):

```
field(:) = field(:) - rscalar
```

aX_minus_Y

aX_minus_Y (*field3*, *rscalar*, *field1*, *field2*)

Performs $Z = aX - Y$:

```
field3(:) = rscalar*field1(:) - field2(:)
```

X_minus_bY

X_minus_bY (*field3*, *field1*, *rscalar*, *field2*)

Performs $Z = X - bY$:

```
field3(:) = field1(:) - rscalar*field2(:)
```

inc_X_minus_bY

inc_X_minus_bY (*field1*, *rscalar*, *field2*)

Performs $X = X - bY$ (decrements the first field):

```
field1(:) = field1(:) - rscalar*field2(:)
```

aX_minus_bY

aX_minus_bY (*field3*, *rscalar1*, *field1*, *rscalar2*, *field2*)

Performs $Z = aX - bY$:

```
field3(:) = rscalar1*field1(:) - rscalar2*field2(:)
```

Multiplication

Built-ins which multiply (scaled) real-valued fields and return the result as a real-valued field are denoted with the keyword **times**.

X_times_Y

X_times_Y (*field3*, *field1*, *field2*)

Multiplies two fields DoF by DoF and returns the result in a third field ($Z = X*Y$):

```
field3(:) = field1(:)*field2(:)
```

inc_X_times_Y**inc_X_times_Y** (*field1*, *field2*)Multiplies the first field by the second and returns it ($X = X*Y$):

```
field1(:) = field1(:)*field2(:)
```

inc_aX_times_Y**inc_aX_times_Y** (*rscalar*, *field1*, *field2*)Performs $X = a*X*Y$ (increments the first field):

```
field1(:) = rscalar*field1(:)*field2(:)
```

Scaling

Built-ins which scale real-valued fields are technically cases of multiplying a real-valued field by a real scalar and are hence also denoted with the keyword **times**.

a_times_X**a_times_X** (*field2*, *rscalar*, *field1*)Multiplies a field by a real scalar value and stores the result in another field ($Y = a*X$):

```
field2(:) = rscalar*field1(:)
```

inc_a_times_X**inc_a_times_X** (*rscalar*, *field*)Multiplies a field by a real scalar value and returns the field ($X = a*X$):

```
field(:) = rscalar*field(:)
```

Division

Built-ins which divide real-valued fields and return the result as a real-valued field are denoted with the keyword **divideby**.

X_divideby_Y

X_divideby_Y (*field3*, *field1*, *field2*)

Divides the first field by the second field, DoF by DoF, and stores the result in the third field ($Z = X/Y$):

```
field3(:) = field1(:)/field2(:)
```

inc_X_divideby_Y

inc_X_divideby_Y (*field1*, *field2*)

Divides the first field by the second and returns it ($X = X/Y$):

```
field1(:) = field1(:)/field2(:)
```

X_divideby_a

X_divideby_a (*field2*, *field1*, *rscalar*)

Divides each field element by a real scalar value and stores the result in another field ($Y = X/a$):

```
field2(:) = field1(:)/rscalar
```

inc_X_divideby_a

inc_X_divideby_a (*field*, *rscalar*)

Divides each field element by a real scalar value and returns the field ($X = X/a$):

```
field(:) = field(:)/rscalar
```

Inverse scaling

Built-ins which perform inverse scaling of real-valued fields are also denoted with the keyword **divideby** as they divide a real scalar by elements of a real-valued field.

a_divideby_X

a_divideby_X (*field2*, *rscalar*, *field1*)

Divides a real scalar value by each field element and stores the result in another field ($Y = a/X$):

```
field2(:) = rscalar/field1(:)
```


inc_a_divideby_X

inc_a_divideby_X (*rscalar*, **field**)

Divides a real scalar value by each field element and returns the field ($X = a/X$):

```
field(:) = rscalar/field(:)
```

Setting to a value

Built-ins which set real-valued field elements to some real value are denoted with the keyword **setval**.

setval_c

setval_c (**field**, *constant*)

Sets all elements of a field *field* to a real scalar *constant* ($X = c$):

```
field(:) = constant
```

setval_X

setval_X (**field2**, *field1*)

Sets a field *field2* equal (DoF per DoF) to another field *field1* ($Y = X$):

```
field2(:) = field1(:)
```

setval_random

setval_random (**field**)

Fills all elements of a field *field* using a sequence of real, pseudo-random numbers in the interval $0 \leq x < 1$:

```
do df = 1, ndofs
  field(df) = RAND()
end do
```

where `RAND()` is some function that returns a new pseudo-random number each time it is called.

Warning: This Built-in is implemented using the Fortran `random_number` intrinsic. Therefore no guarantee is made as to the quality of the sequence of pseudo-random numbers, especially when running in parallel.

Raising to power

Built-ins which raise real-valued field elements to an exponent are denoted with the keyword **powreal** for a real exponent or **powint** for an integer exponent.

inc_X_powreal_a

inc_X_powreal_a (*field*, *rscalar*)

Raises a field to a real scalar value and returns the field ($X = X^{**a}$):

```
field(:) = field(:)**rscalar
```

inc_X_powint_n

inc_X_powint_n (*field*, *iscalar*)

Raises a field to an integer scalar value and returns the field ($X = X^{**n}$):

```
field(:) = field(:)**iscalar
```

where *iscalar* is an integer scalar of *i_def* precision.

Inner product

Built-ins which calculate the inner product of two real-valued fields or of a real-valued field with itself and return the result as a real scalar are denoted with the keyword **innerproduct**.

Note: When used with distributed memory these Built-ins will trigger the addition of a global sum which may affect the performance and/or scalability of the code. Also, whilst the fields in these Built-ins can be of any supported real *precision*, the only currently supported precision for the global reductions in the LFRic infrastructure is *r_def*, hence the result will be converted accordingly.

X_innerproduct_Y

X_innerproduct_Y (*innprod*, *field1*, *field2*)

Computes the inner product of two fields, *field1* and *field2*, i.e.:

```
innprod = SUM(field1(:)*field2(:))
```

where **innprod** is a real scalar of *r_def* precision.

X_innerproduct_X

X_innerproduct_X (*innprod*, *field*)

Computes the inner product of the field *field1* by itself, *i.e.*:

```
innprod = SUM(field(:)*field(:))
```

where **innprod** is a real scalar of `r_def` precision.

Sum of elements

A Built-in which sums the elements of a real-valued field and returns the result as a real scalar is denoted with the keyword **sum**.

Note: When used with distributed memory this Built-in will trigger the addition of a global sum which may affect the performance and/or scalability of the code. Also, whilst the fields in these Built-ins can be of any supported real *precision*, the only currently supported precision for the global reductions in the LFRic infrastructure is `r_def`, hence the result will be converted accordingly.

sum_X

sum_X (*sumfld*, *field*)

Sums all of the elements of the field *field* and returns the result in the real scalar variable *sumfld*:

```
sumfld = SUM(field(:))
```

where **sumfld** is a real scalar of `r_def` precision.

Sign of elements

A Built-in which returns the sign of a real-valued field is denoted with the keyword **sign**.

sign_X

sign_X (*field2*, *rscalar*, *field1*)

Returns the sign of a real-valued field, e.g. in Fortran: `Y = sign(a, X)`. Here *a* is a real scalar and *Y* and *X* are real-valued fields. The results are *a* for $X \geq 0$ and $-a$ for $X < 0$:

```
field2(:) = SIGN(rscalar, field1(:))
```

DoF-wise maximum of elements

Built-ins which return the DoF-wise maximum of a real scalar and a real-valued field are denoted with the keyword **max**.

max_aX

max_aX (**field2**, *rscalar*, *field1*)

Returns maximum of *rscalar* and each element of the field *field1* as the second field **field2** ($Y = \max(a, X)$):

`field2(:) = MAX(rscalar, field1(:))`

inc_max_aX

inc_max_aX (*rscalar*, **field**)

Returns maximum of *rscalar* and each element of the field *field* in the same field ($X = \max(a, X)$):

`field(:) = MAX(rscalar, field(:))`

DoF-wise minimum of elements

Built-ins which return the DoF-wise minimum of a real scalar and a real-valued field are denoted with the keyword **min**.

min_aX

min_aX (**field2**, *rscalar*, *field1*)

Returns minimum of *rscalar* and each element of the field *field1* as the second field **field2** ($Y = \min(a, X)$):

`field2(:) = MIN(rscalar, field1(:))`

inc_min_aX

inc_min_aX (*rscalar*, **field**)

Returns minimum of *rscalar* and each element of the field *field* in the same field ($X = \min(a, X)$):

`field(:) = MIN(rscalar, field(:))`

Conversion of real to integer field elements

A Built-in which takes a real field and converts it to an integer field is denoted with the keyword **int**.

int_X

int_X (ifield2, field1)

Converts real-valued field elements to integer-valued field elements, e.g. in Fortran this would be: $Y = \text{int}(X, i_def)$. Here Y is an integer-valued field and X is the real-valued field being converted:

```
ifield2(:) = INT(field1(:), i_def)
```

where **ifield2** is an integer_field_type of i_def precision and a real-valued field *field1* can be of any *supported precisions* for GH_REAL fields (e.g. r_tran for r_tran_field_type).

12.5.4 Built-in operations on integer-valued fields

The number of supported Built-in operations on the integer-valued fields is not as large as for their real counterparts as not all mathematical operations on integer-valued fields make sense.

As described *above*, Built-ins that operate on integer-valued fields mandate GH_INTEGER as the kernel metadata for fields and scalars. Both integer scalar arguments and integer-valued fields can only currently have i_def precision, as described in the *Mixed Precision* section.

For instance, field and scalar declarations for the X_minus_a Built-in will be:

```
integer(kind=i_def), intent(in) :: ascalar
type(integer_field_type), intent(in) :: yfield, xfield
```

Addition

Built-ins that add integer-valued fields and return the result as an integer-valued field are denoted with the keyword **plus** and the prefix **int**.

int_X_plus_Y

int_X_plus_Y (ifield3, ifield1, ifield2)

Sums two fields and stores the result in the third field ($Z = X + Y$):

```
ifield3(:) = ifield1(:) + ifield2(:)
```

int_inc_X_plus_Y

int_inc_X_plus_Y (*ifield1*, *ifield2*)

Adds the second field to the first and returns it ($X = X + Y$):

```
ifield1(:) = ifield1(:) + ifield2(:)
```

int_a_plus_X

int_a_plus_X (*ifield2*, *iscalar*, *ifield1*)

Adds an integer scalar value to all elements of a field and stores the result in another field ($Y = a + X$):

```
ifield2(:) = iscalar + ifield1(:)
```

int_inc_a_plus_X

int_inc_a_plus_X (*iscalar*, *ifield*)

Adds an integer scalar value to all elements of a field and returns the field ($X = a + X$):

```
ifield(:) = iscalar + ifield(:)
```

Subtraction

Built-ins which subtract integer-valued fields and return the result as an integer-valued field are denoted with the keyword **minus** and the prefix **int**.

int_X_minus_Y

int_X_minus_Y (*ifield3*, *ifield1*, *ifield2*)

Subtracts the second field from the first and returns the result in the third field ($Z = X - Y$):

```
ifield3(:) = ifield1(:) - ifield2(:)
```

int_inc_X_minus_Y

int_inc_X_minus_Y (*ifield1*, *ifield2*)

Subtracts the second field from the first and returns it ($X = X - Y$):

```
ifield1(:) = ifield1(:) - ifield2(:)
```

int_a_minus_X**int_a_minus_X** (ifield2, iscalar, ifield1)Subtracts all elements of a field from an integer scalar value and stores the result in another field ($Y = a - X$):

```
ifield2(:) = iscalar - ifield1(:)
```

int_inc_a_minus_X**int_inc_a_minus_X** (iscalar, ifield)Subtracts all elements of a field from an integer scalar value and returns the field ($X = a - X$):

```
ifield(:) = iscalar - ifield(:)
```

int_X_minus_a**int_X_minus_a** (ifield2, ifield1, iscalar)Subtracts an integer scalar value from all elements of a field and stores the result in another field ($Y = X - a$):

```
ifield2(:) = ifield1(:) - iscalar
```

int_inc_X_minus_a**int_inc_X_minus_a** (ifield, iscalar)Subtracts an integer scalar value from all elements of a field and returns the field ($X = X - a$):

```
ifield(:) = ifield(:) - iscalar
```

MultiplicationBuilt-ins which multiply integer-valued fields and return the result as an integer-valued field are denoted with the keyword **times** and the prefix **int**.**int_X_times_Y****int_X_times_Y** (ifield3, ifield1, ifield2)Multiplies two fields DoF by DoF and returns the result in a third field ($Z = X*Y$):

```
ifield3(:) = ifield1(:)*ifield2(:)
```

int_inc_X_times_Y

int_inc_X_times_Y (*ifield1*, *ifield2*)

Multiplies the first field by the second and returns it ($X = X*Y$):

```
ifield1(:) = ifield1(:)*ifield2(:)
```

Scaling

Built-ins which scale integer-valued fields are denoted with the keyword **times** and prefixed by the keyword **int**.

int_a_times_X

int_a_times_X (*ifield2*, *iscalar*, *ifield1*)

Multiplies a field by an integer scalar and stores the result in another field ($Y = a*X$):

```
ifield2(:) = iscalar*ifield1(:)
```

int_inc_a_times_X

int_inc_a_times_X (*iscalar*, *ifield*)

Multiplies a field by an integer scalar value and returns the field ($X = a*X$):

```
ifield(:) = iscalar*ifield(:)
```

Setting to a value

Built-ins which set integer-valued field elements to some integer value are denoted with the keyword **setval** and the prefix **int**.

int_setval_c

int_setval_c (*ifield*, *constant*)

Sets all elements of a field *ifield* to an integer scalar *constant* ($X = c$):

```
ifield(:) = constant
```


int_setval_X

int_setval_X (*ifield2*, *ifield1*)

Sets a field *ifield2* equal (DoF per DoF) to another field *ifield1* ($Y = X$):

```
ifield2(:) = ifield1(:)
```

Sign of elements

A Built-in which returns the sign of an integer-valued field is denoted with the keyword **sign** and the prefix **int**.

int_sign_X

int_sign_X (*ifield2*, *iscalar*, *ifield1*)

Returns the sign of an integer-valued field, e.g. in Fortran: $Y = \text{sign}(a, X)$. Here *a* is an integer scalar and *Y* and *X* are integer-valued fields. The results are *a* for $X \geq 0$ and $-a$ for $a < 0$:

```
ifield2(:) = SIGN(iscalar, ifield1(:))
```

DoF-wise maximum of elements

Built-ins which return the DoF-wise maximum of an integer scalar and an integer-valued field are denoted with the keyword **max**.

int_max_aX

int_max_aX (*ifield2*, *iscalar*, *ifield1*)

Returns maximum of *iscalar* and each element of the field *ifield1* as the second field **ifield2** ($Y = \max(a, X)$):

```
ifield2(:) = MAX(iscalar, ifield1(:))
```

int_inc_max_aX

int_inc_max_aX (*iscalar*, *ifield*)

Returns maximum of *iscalar* and each element of the field *ifield* in the same field ($X = \max(a, X)$):

```
ifield(:) = MAX(iscalar, ifield(:))
```

DoF-wise minimum of elements

Built-ins which return the DoF-wise minimum of an integer scalar and an integer-valued field are denoted with the keyword **min**.

int_min_aX

int_min_aX (*ifield2*, *iscalar*, *ifield1*)

Returns minimum of *iscalar* and each element of the field *ifield1* as the second field **ifield2** ($Y = \min(a, X)$):

```
ifield2(:) = MIN(iscalar, ifield1(:))
```

int_inc_min_aX

int_inc_min_aX (*iscalar*, *ifield*)

Returns minimum of *iscalar* and each element of the field *ifield* in the same field ($X = \min(a, X)$):

```
ifield(:) = MIN(iscalar, ifield(:))
```

Conversion of integer to real field elements

A Built-in which takes an integer field and converts it to a real field is denoted with the keyword **real**.

real_X

real_X (*field2*, *ifield1*)

Converts integer-valued field elements to real-valued field elements, e.g. in Fortran this would be $Y = \text{real}(X, r_def)$. Here Y is a real-valued field and X is the integer-valued field being converted:

```
field2(:) = REAL(ifield1(:), r_<prec>)
```

where *ifield1* is an integer_field_type of i_def precision. The real-valued **field1** can be of any *supported precisions* for GH_REAL fields, hence $r_<prec>$ is determined from the algorithm layer (e.g. r_solver for $r_solver_field_type$).

12.6 Boundary Conditions

In the Dynamo0.3 API, boundary conditions for a field or LMA operator can be enforced by the algorithm developer by calling the `Kernels enforce_bc_type` or `enforce_operator_bc_type`, respectively. These kernels take a field or operator as input and apply boundary conditions. For example:

```
call invoke( kernel_type(field1, field2),    &
             enforce_bc_type(field1),       &
             kernel_with_op_type(field1, op1), &
             enforce_operator_bc_type(op1)   &
             )
```

The particular boundary conditions that are applied are not known by PSyclone, PSyclone simply recognises these kernels by their names and passes pre-specified dofmap and boundary_value arrays into the kernel implementations, the contents of which are set by the LFRic infrastructure.

Up to and including version 1.4.0 of PSyclone, boundary conditions were applied automatically after a call to `matrix_vector_type` if the field arguments were on a vector function space (one of W1, W2, W2H, W2V or W2broken). With the subsequent introduction of the ability to apply boundary conditions to operators this functionality is no longer required and has been removed.

Example eg4 in the `examples/lfric` directory includes a call to `enforce_bc_kernel_type` so can be used to see the boundary condition code that is added by PSyclone. See the README in the `examples/lfric` directory for instructions on how to run this example.

An example of applying boundary conditions to an operator is the kernel `enforce_operator_bc_kernel_mod.F90` in the `<PSYCLONEHOME>/src/psyclone/tests/test_files/dynamo0p3` directory. Since operators are discontinuous quantities, updating their values can be safely performed in parallel (see Section [Kernel](#)). The `GH_READWRITE` access is used for updating discontinuous operators (see subsection [Valid Access Modes](#) for more details).

12.7 Conventions

The naming of Dynamo0.3 API kernels and associated entities (types, subroutines and modules) follows the PSyclone Fortran naming conventions (see [Fortran Naming Conventions](#)). However, PSyclone does not need this convention to be followed apart from the stub generator (see the [Kernel-stub Generator](#) Section) where the name of the metadata to be parsed is determined from the module name.

The contents of the metadata is also usually declared private but this does not affect PSyclone.

Finally, the procedure metadata (located within the kernel metadata) usually has `nopass` specified but again this is ignored by PSyclone.

12.8 Configuration

The general and the LFRic-API-specific configuration options are described in the [Configuration](#) section.

12.8.1 Annexed DoFs

When a kernel operates on DoFs (rather than cell-columns) for a continuous field using distributed memory (see the [Distributed Memory](#) Section), then PSyclone need only ensure that DoFs owned by a processor are computed. However, for continuous fields, shared DoFs at the boundary between processors must be replicated (as different cells share the same DoF). Only one processor can own a DoF, therefore processors will have continuous fields which contain DoFs that the processor does not own. These unowned DoFs are called *annexed* in the Dynamo0.3 API and are a separate, but related, concept to field halos.

When a kernel that operates on a cell-column needs to read a continuous field then the annexed DoFs must be up-to-date on all processors. If they are not then a halo exchange must be added. Currently PSyclone defaults, for kernels which iterate over DoFs, to iterating over only owned DoFs. This behaviour can be changed by setting `COMPUTE_ANNEXED_DOFS` to true in the `dynamo0.3` section of the configuration file (see the [Configuration](#) section). PSyclone will then generate code to iterate over both owned and annexed DoFs, thereby reducing the number of halo exchanges required (at the expense of redundantly computing annexed DoFs). For more details please refer to the [LFRic \(Dynamo0.3\) developers](#) section.

12.8.2 Run-time Checks

PSyclone performs static consistency checks where possible. When this is not possible PSyclone can generate run-time checks. As there may be performance costs associated with run-time checks they may be switched on or off by the `RUN_TIME_CHECKS` option in the configuration file.

Currently run-time checks can be generated to:

- 1) Check that a field with a read-only function space (see section *Read-Only Function Spaces*) is not modified by a kernel. This is enforced by checking that all fields that are marked (in kernel metadata) as being updated by a kernel are not on a read-only function space. A second check that is required for fields on read-only function spaces is to ensure that the halo is clean before it is accessed. This check is currently implemented within the LFRic infrastructure halo exchange call (that the PSyclone LFRic API places at appropriate locations). If the halo is clean then the halo exchange will not be called. However, if the halo is not clean then the resulting halo exchange call will cause the infrastructure to raise an error (because the field is on a read-only space).
- 2) Check that the function space of a field is consistent with the kernel function space metadata that the field's data is passed into. For example, if kernel metadata specifies that a field is on the W2 function space then a run-time check is added to ensure that the field object passed into the PSy layer is indeed on that space. For more general kernel function space metadata, such as `ANY_DISCONTINUOUS_SPACE_*` then a run-time check is added to ensure that the field is on one of the discontinuous function spaces supported in the LFRic API.

12.8.3 Supported Data Types and Default Kind

The LFRic API supports three Fortran primitive (intrinsic) data types, real, integer and logical (listed in the *supported_fortran_datatypes* section of the *PSyclone configuration file*). All three data types are used for *scalars*. *Fields* and *field vectors* are allowed to have real and integer data. *Operators* and *column-wise operators* are only allowed to have real data. These supported primitive types are linked to the respective *kernel data type* metadata descriptors, `GH_REAL` and `GH_INTEGER`.

The default kind (precision) for these supported data types is set to `r_def`, `i_def` and `l_def`, respectively, in the `default_kind` dictionary in the configuration file. These default values are defined in the LFRic infrastructure code.

Note: Whilst the logical Fortran primitive (intrinsic) data type is supported in the LFRic API for scalar arguments, it is not yet available for fields and operators. This will be added as required in future releases.

12.8.4 Number of Generalised ANY_*_SPACE Function Spaces

As outlined in the *meta_args* and the *Supported Function Spaces* sections above, the number of generalised `ANY_SPACE_<n>` and `ANY_DISCONTINUOUS_SPACE_<n>` function spaces can be set in the *PSyclone configuration file*.

The relevant parameters are `NUM_ANY_SPACE` and `NUM_ANY_DISCONTINUOUS_SPACE`, respectively. Their default values in the configuration file are 10 and their allowed values are positive non-zero integers. PSyclone will raise a `ConfigurationError` if a supplied value is invalid.

12.9 Transformations

This section describes the Dynamo0.3-API-specific transformations. In cases, excepting **Dynamo0p3RedundantComputationTrans**, **Dynamo0p3AsyncHaloExchangeTrans** and **Dynamo0p3KernelConstTrans**, these transformations are specialisations of generic transformations described in the *Transformations* section. The difference between these transformations and the generic ones is that these perform Dynamo0.3-API-specific checks to make sure the transformations are valid. In practice these transformations perform the required checks then call the generic ones internally.

The use of the Dynamo0.3-API-specific transformations is exactly the same as the equivalent generic ones in all cases excepting **LFRicLoopFuseTrans**. In this case an additional optional argument **same_space** can be set when applying the transformation. The reason for this is to allow loop fusion when one or more of the iteration spaces is determined by a function space that is unknown by PSyclone at compile time. This is the case when the `ANY_SPACE_<n>` function space is specified in the Kernel metadata. Adding `{"same_space": True}` as option when applying the transformation allows the user to specify that the spaces are the same (see *Standard Functionality* for using options in transformations). This option should therefore be used with caution. PSyclone will raise an error if **same_space** is used when at least one of the function spaces is not `ANY_SPACE_<n>` or both spaces are not the same. In general, PSyclone will not allow loop fusion if it does not know the spaces are the same. The exception are loops over discontinuous spaces (see *Supported Function Spaces* for list of discontinuous function spaces) for which loop fusion is allowed (unless the loop bounds become different due to a prior transformation).

The **Dynamo0p3RedundantComputationTrans** and **Dynamo0p3AsyncHaloExchange** transformations are only valid for the Dynamo0.3 API. This is because this API is currently the only one that supports distributed memory. An example of redundant computation can be found in `examples/lfric/eg8` and an example of asynchronous halo exchanges can be found in `examples/lfric/eg11`.

The **Dynamo0p3KernelConstTrans** transformation is only valid for the Dynamo0.3 API. This is because the properties that it makes constant are API specific.

The LFRic (dynamo0.3) API-specific transformations currently available are given below. Early transformations include “Dynamo0p3” or “Dynamo” in their name to indicate that these transformations are only valid for this particular API. More recent transformations typically include “LFRic” in their name to indicate the same restriction. However, more importantly, transformations that are specific to LFRic reside in the LFRic-specific “psyclone.domain.lfric.transformations” directory. Note, the early LFRic (dynamo0.3) API-specific transformations have not yet been migrated to this directory.

Note: Only the loop-colouring and OpenMP transformations are currently supported for loops that contain inter-grid kernels. Attempting to apply other transformation types will result in PSyclone raising an error.

class `psyclone.domain.lfric.transformations.LFRicExtractTrans`

Dynamo0.3 API application of `ExtractTrans` transformation to extract code into a stand-alone program. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>>
>>> API = "dynamo0.3"
>>> FILENAME = "solver_alg.x90"
>>> ast, invokeInfo = parse(FILENAME, api=API)
>>> psy = PSyFactory(API, distributed_memory=False).create(invoke_info)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>>
>>> from psyclone.domain.lfric.transformations import LFRicExtractTrans
```

(continues on next page)

(continued from previous page)

```

>>> etrans = LFRicExtractTrans()
>>>
>>> # Apply LFRicExtractTrans transformation to selected Nodes
>>> etrans.apply(schedule.children[0:3])
>>> print(schedule.view())

```

`apply(nodes, options=None)`

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Nodes in the schedule within a single PSyData region. It first uses the DependencyTool to determine input- and output-parameters. If requested, it will then call the LFRicExtractDriverCreator to write the stand-alone driver program. Then it will call apply of the base class.

Parameters

- `nodes` (`psyclone.psyir.nodes.Node` or `List[psyclone.psyir.nodes.Node]`) – can be a single node or a list of nodes.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["prefix"]` (`str`) – a prefix to use for the PSyData module name (`prefix_psy_data_mod`) and the PSyDataType (`prefix_PSyDataType`) - a “_” will be added automatically. It defaults to “extract”, resulting in e.g. `extract_psy_data_mod`.
- `options["create_driver"]` (`bool`) – whether or not to create a driver program at code-generation time. If set, the driver will be created in the current working directory with the name “driver-MODULE-REGION.f90” where MODULE and REGION will be the corresponding values for this region. Defaults to False.
- `options["region_name"]` (`Tuple[str, str]`) – an optional name to use for this PSyData area, provided as a 2-tuple containing a location name followed by a local name. The pair of strings should uniquely identify a region unless aggregate information is required (and is supported by the runtime library).

`validate(node_list, options=None)`

Perform Dynamo0.3 API specific validation checks before applying the transformation.

Parameters

- `node_list` (`List[psyclone.psyir.nodes.Node]`) – the list of Node(s) we are checking.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Raises

`TransformationError` – if transformation is applied to a Loop over cells in a colour without its parent Loop over colours.

`class psyclone.domain.lfric.transformations.LFRicLoopFuseTrans`

Dynamo0.3 API specialisation of the base class in order to fuse two Dynamo loops after performing validity checks. For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>>
>>> API = "dynamo0.3"
>>> FILENAME = "alg.x90"
>>> ast, invokeInfo = parse(FILENAME, api=API)
>>> psy = PSyFactory(API, distributed_memory=False).create(invoke_info)

```

(continues on next page)

(continued from previous page)

```

>>> schedule = psy.invokes.get('invoke_0').schedule
>>>
>>> from psyclone.domain.lfric.transformations import LFRicLoopFuseTrans
>>> ftrans = LFRicLoopFuseTrans()
>>>
>>> ftrans.apply(schedule[0], schedule[1])
>>> print(schedule.view())

```

The optional argument *same_space* can be set as

```

>>> ftrans.apply(schedule[0], schedule[1], {"same_space": True})

```

when applying the transformation.

`validate(node1, node2, options=None)`

Performs various checks to ensure that it is valid to apply the LFRicLoopFuseTrans transformation to the supplied loops.

Parameters

- *node1* (`psyclone.dynamo0p3.DynLoop`) – the first Loop to fuse.
- *node2* (`psyclone.dynamo0p3.DynLoop`) – the second Loop to fuse.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- *options*["same_space"] (`bool`) – this optional flag, set to *True*, asserts that an unknown iteration space (i.e. *ANY_SPACE*) matches the other iteration space. This is set at the user's own risk. If both iteration spaces are discontinuous the loops can be fused without having to use the *same_space* flag.

Raises

- `TransformationError` – if either of the supplied loops contains an inter-grid kernel.
- `TransformationError` – if one or both function spaces have invalid names.
- `TransformationError` – if the *same_space* flag was set, but does not apply because neither field is on *ANY_SPACE* or the spaces are not the same.
- `TransformationError` – if one or more of the iteration spaces is unknown (*ANY_SPACE*) and the *same_space* flag is not set to *True*.
- `TransformationError` – if the loops are over different spaces that are not both discontinuous and the loops both iterate over cells.
- `TransformationError` – if the loops' upper bound names are not the same.
- `TransformationError` – if the halo-depth indices of two loops are not the same.
- `TransformationError` – if each loop already contains a reduction.
- `TransformationError` – if the first loop has a reduction and the second loop reads the result of the reduction.

`class psyclone.domain.lfric.transformations.RaisePSyIR2LFRicKernTrans`

Raise a generic PSyIR representation of a kernel-layer routine and metadata to an LFRic version with specialised domain-specific nodes and symbols. This is currently limited to the specialisation of kernel metadata.

```

>>> from psyclone.domain.lfric.transformations import RaisePSyIR2LFRicKernTrans
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> CODE = """
... MODULE example
... TYPE, EXTENDS(kernel_type) :: compute_cu
...   TYPE(arg_type), DIMENSION(4) :: meta_args = (/    &
...     arg_type(GH_FIELD, GH_REAL, GH_INC, W1),      &
...     arg_type(GH_FIELD, GH_REAL, GH_READ, W3),      &
...     arg_type(GH_FIELD, GH_REAL, GH_READ, W3),      &
...     arg_type(GH_FIELD, GH_REAL, GH_READ, W3)/)
...   INTEGER :: OPERATES_ON = CELL_COLUMN
... CONTAINS
...   PROCEDURE, NOPASS :: code => compute_cu_code
... END TYPE compute_cu
... contains
...   subroutine compute_cu_code()
...   end subroutine
... end module"""
>>> fortran_reader = FortranReader()
>>> kernel_container = fortran_reader.psyir_from_source(CODE)
>>> trans = RaisePSyIR2LFRicKernTrans()
>>> trans.apply(kernel_container, {"metadata_name": "compute_cu"})

```

`apply(node, options=None)`

Raise the supplied language-level kernel to LFRic-specific kernel PSyIR. Specialises the kernel container to an LFRic-specific subclass, populates this subclass with the kernel metadata extracted from the metadata symbol as specified in `metadata_name` (which is supplied via the `options` argument) and removes the symbol from the symbol table.

Parameters

- `node` (`psyclone.psyir.node.Container`) – a kernel represented in generic PSyIR.
- `options` (`Optional[Dict[str: str]]`) – a dictionary with options for transformations. This is expected to contain the `metadata_name`.

`validate(node, options=None)`

Validate the supplied PSyIR tree.

Parameters

- `node` (`psyclone.psyir.node.Container`) – a PSyIR node that is the root of a PSyIR tree.
- `options` (`Optional[Dict[str: str]]`) – a dictionary with options for transformations.

Raises

- `TransformationError` – if the supplied node is not a `Container`.
- `TransformationError` – if the supplied node argument has a parent.
- `TransformationError` – if the metadata name has not been provided in the options argument.
- `TransformationError` – if the metadata name has not been set or does not exist in the code.

`class psyclone.transformations.DynamoOMPParallelLoopTrans(omp_directive='do', omp_schedule='static')`

Dynamo-specific OpenMP loop transformation. Adds Dynamo specific validity checks. Actual transformation is done by the `base` class.

Parameters

- `omp_directive` (`str`) – choose which OpenMP loop directive to use. Defaults to “do”.
- `omp_schedule` (`str`) – the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

`apply(node, options=None)`

Perform Dynamo specific loop validity checks then call the `apply()` method of the base class.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the Node in the Schedule to check
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Raises

`TransformationError` – if the associated loop requires colouring.

`class psyclone.transformations.Dynamo0p3AsyncHaloExchangeTrans`

Splits a synchronous halo exchange into a halo exchange start and halo exchange end. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "dynamo0.3"
>>> ast, invokeInfo = parse("file.f90", api=api)
>>> psy=PSyFactory(api).create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import Dynamo0p3AsyncHaloExchangeTrans
>>> trans = Dynamo0p3AsyncHaloExchangeTrans()
>>> trans.apply(schedule.children[0])
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(node, options=None)`

Transforms a synchronous halo exchange, represented by a `HaloExchange` node, into an asynchronous halo exchange, represented by `HaloExchangeStart` and `HaloExchangeEnd` nodes.

Parameters

- `node` (`psyclone.psygen.HaloExchange`) – a synchronous haloexchange node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

property name

Returns

the name of this transformation as a string.

Return type

`str`

`validate(node, options)`

Internal method to check whether the node is valid for this transformation.

Parameters

- `node` (`psyclone.psygen.HaloExchange`) – a synchronous Halo Exchange node

- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

TransformationError – if the node argument is not a HaloExchange (or subclass thereof)

class `psyclone.transformations.Dynamo0p3ColourTrans`

Split a Dynamo 0.3 loop over cells into colours so that it can be parallelised. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> import transformations
>>> import os
>>> import pytest
>>>
>>> TEST_API = "dynamo0.3"
>>> _,info=parse(os.path.join(os.path.dirname(os.path.abspath(__file__)),
>>>     "tests", "test_files", "dynamo0p3",
>>>     "4.6_multikernel_invokes.f90"),
>>>     api=TEST_API)
>>> psy = PSyFactory(TEST_API).create(info)
>>> invoke = psy.invokes.get('invoke_0')
>>> schedule = invoke.schedule
>>>
>>> ctrans = Dynamo0p3ColourTrans()
>>> otrans = DynamoOMPParallelLoopTrans()
>>>
>>> # Colour all of the loops
>>> for child in schedule.children:
>>>     ctrans.apply(child)
>>>
>>> # Then apply OpenMP to each of the colour loops
>>> for child in schedule.children:
>>>     otrans.apply(child.children[0])
>>>
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

Colouring in the LFRic (Dynamo 0.3) API is subject to the following rules:

- Only kernels which operate on ‘CELL_COLUMN’s and which increment a field on a continuous function space require colouring. Kernels that update a field on a discontinuous function space will cause this transformation to raise an exception. Kernels that only write to a field on a continuous function space also do not require colouring but are permitted.
- A kernel may have at most one field with ‘GH_INC’ access.
- A separate colour map will be required for each field that is coloured (if an invoke contains >1 kernel call).

`apply(node, options=None)`

Performs Dynamo0.3-specific error checking and then uses the parent class to convert the Loop represented by node into a nested loop where the outer loop is over colours and the inner loop is over cells of that colour.

Parameters

- node (`psyclone.dynamo0p3.DynLoop`) – the loop to transform.
- options – a dictionary with options for transformations. :type options: Optional[Dict[str, Any]]

class `psyclone.transformations.Dynamo0p3KernelConstTrans`

Modifies a kernel so that the number of dofs, number of layers and number of quadrature points are fixed in the kernel rather than being passed in by argument.

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "dynamo0.3"
>>> ast, invokeInfo = parse("file.f90", api=api)
>>> psy=PSyFactory(api).create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import Dynamo0p3KernelConstTrans
>>> trans = Dynamo0p3KernelConstTrans()
>>> for kernel in schedule.coded_kernels():
>>>     trans.apply(kernel, number_of_layers=150)
>>>     kernel_schedule = kernel.get_kernel_schedule()
>>>     # Uncomment the following line to see a text view of the
>>>     # symbol table
>>>     # print(kernel_schedule.symbol_table.view())
```

`apply(node, options=None)`

Transforms a kernel so that the values for the number of degrees of freedom (if a valid value for the `element_order` arg is provided), the number of quadrature points (if the `quadrature` arg is set to `True`) and the number of layers (if a valid value for the `number_of_layers` arg is provided) are constant in a kernel rather than being passed in by argument.

The “cellshape”, “element_order” and “number_of_layers” arguments are provided to mirror the namelist values that are input into an LFRic model when it is run.

Quadrature support is currently limited to XYoZ in this transformation. In the case of XYoZ the number of quadrature points (for horizontal and vertical) are set to the `element_order` + 3 in the LFRic infrastructure so their value is derived.

Parameters

- `node` (`psyclone.psygen.DynKern`) – a kernel node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["cellshape"]` (`str`) – the shape of the cells. This is provided as it helps determine the number of dofs a field has for a particular function space. Currently only “quadrilateral” is supported which is also the default value.
- `options["element_order"]` (`int`) – the order of the cell. In combination with `cellshape`, this determines the number of dofs a field has for a particular function space. If it is set to `None` (the default) then the dofs values are not set as constants in the kernel, otherwise they are.
- `options["number_of_layers"]` (`int`) – the number of vertical layers in the LFRic model mesh used for this particular run. If this is set to `None` (the default) then the `nlayers` value is not set as a constant in the kernel, otherwise it is.
- `options["quadrature"]` (`bool`) – whether the number of quadrature points values are set as constants in the kernel (`True`) or not (`False`). The default is `False`.

property name

Returns

the name of this transformation as a string.

Return type

`str`

`validate(node, options=None)`

This method checks whether the input arguments are valid for this transformation.

Parameters

- `node` (`psyclone.psygen.DynKern`) – a dynamo 0.3 kernel node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["cellshape"]` (`str`) – the shape of the elements/cells.
- `options["element_order"]` (`int`) – the order of the elements/cells.
- `options["number_of_layers"]` (`int`) – the number of layers to use.
- `options["quadrature"]` (`bool`) – whether quadrature dimension sizes should or shouldn't be set as constants in a kernel.

Raises

`TransformationError` – if the `node` argument is not a dynamo 0.3 kernel, the `cellshape` argument is not set to “quadrilateral”, the `element_order` argument is not a 0 or a positive integer, the `number of layers` argument is not a positive integer, the `quadrature` argument is not a boolean, neither `element_order` nor `number of layers` arguments are set (as the transformation would then do nothing), or the `quadrature` argument is `True` but the `element_order` is not provided (as the former needs the latter).

`class psyclone.transformations.Dynamo0p3OMPLoopTrans(omp_schedule='static')`

LFRic (Dynamo 0.3) specific orphan OpenMP loop transformation. Adds Dynamo-specific validity checks.

Parameters

`omp_schedule` (`str`) – the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

`apply(node, options=None)`

Apply LFRic (Dynamo 0.3) specific OMPLoopTrans.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the Node in the Schedule to check.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- `options["reprod"]` (`bool`) – indicating whether reproducible reductions should be used. By default the value from the config file will be used.

`validate(node, options=None)`

Perform LFRic (Dynamo 0.3) specific loop validity checks for the OMPLoopTrans.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the Node in the Schedule to check
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- `options["reprod"]` (`bool`) – indicating whether reproducible reductions should be used. By default the value from the config file will be used.

Raises

TransformationError – if an OMP loop transform would create incorrect code.

class psyclone.transformations.Dynamo0p3RedundantComputationTrans

This transformation allows the user to modify a loop's bounds so that redundant computation will be performed. Redundant computation can result in halo exchanges being modified, new halo exchanges being added or existing halo exchanges being removed.

- This transformation should be performed before any parallelisation transformations (e.g. for OpenMP) to the loop in question and will raise an exception if this is not the case.
- This transformation can not be applied to a loop containing a reduction and will again raise an exception if this is the case.
- This transformation can only be used to add redundant computation to a loop, not to remove it.
- This transformation allows a loop that is already performing redundant computation to be modified, but only if the depth is increased.

apply(*loop*, *options=None*)

Apply the redundant computation transformation to the loop *loop*. This transformation can be applied to loops iterating over 'cells' or 'dofs'. If *depth* is set to a value then the value will be the depth of the field's halo over which redundant computation will be performed. If *depth* is not set to a value then redundant computation will be performed to the full depth of the field's halo.

Parameters

- *loop* (psyclone.psyGen.DynLoop) – the loop that we are transforming.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- *options*["depth"] (*int*) – the depth of the stencil. Defaults to None.

validate(*node*, *options=None*)

Perform various checks to ensure that it is valid to apply the RedundantComputation transformation to the supplied *node*

Parameters

- *node* (psyclone.psyir.nodes.Node) – the supplied node on which we are performing validity checks
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- *options*["depth"] (*int*) – the depth of the stencil if the value is provided and None if not.

Raises

- TransformationError – if the parent of the loop is a psyclone.psyir.nodes.Directive.
- TransformationError – if the parent of the loop is not a psyclone.psyir.nodes.Loop or a psyclone.psyGen.DynInvokeSchedule.
- TransformationError – if the parent of the loop is a psyclone.psyir.nodes.Loop but the original loop does not iterate over 'colour'.
- TransformationError – if the parent of the loop is a psyclone.psyir.nodes.Loop but the parent does not iterate over 'colours'.
- TransformationError – if the parent of the loop is a psyclone.psyir.nodes.Loop but the parent's parent is not a psyclone.psyGen.DynInvokeSchedule.
- TransformationError – if this transformation is applied when distributed memory is not switched on.

- TransformationError – if the loop does not iterate over cells, dofs or colour.
- TransformationError – if the transformation is setting the loop to the maximum halo depth but the loop already computes to the maximum halo depth.
- TransformationError – if the transformation is setting the loop to the maximum halo depth but the loop contains a stencil access (as this would result in the field being accessed beyond the halo depth).
- TransformationError – if the supplied depth value is not an integer.
- TransformationError – if the supplied depth value is less than 1.
- TransformationError – if the supplied depth value is not greater than 1 when a continuous loop is modified as this is the minimum valid value.
- TransformationError – if the supplied depth value is not greater than the existing depth value, as we should not need to undo existing transformations.
- TransformationError – if a depth value has been supplied but the loop has already been set to the maximum halo depth.

GOCEAN1.0 API

13.1 Introduction

The GOcean 1.0 application programming interface (API) was originally designed to support ocean models that use the finite-difference scheme for two-dimensional domains. However, the approach is not specific to ocean models and can potentially be applied to any finite-difference code.

As with all PSyclone APIs, the GOcean 1.0 API specifies how a user must write the Algorithm Layer and the Kernel Layer to allow PSyclone to generate the PSy Layer. These Algorithm and Kernel APIs are discussed separately in the sections below. Before these we describe the functionality provided by the GOcean Library.

13.2 The GOcean Library

The use of PSyclone and the GOcean 1.0 API implies the use of a standard set of data types and associated infrastructure. This is provided by version 1.0 of the GOcean Library (GOLib v.1.0). Currently this library is distributed separately from PSyclone and is available from <https://puma.nerc.ac.uk/trac/GOcean>.

13.2.1 Grid

The GOLib contains a `grid_mod` module which defines a `grid_type` and associated constructor:

```
use grid_mod
...
!> The grid on which our fields are defined
type(grid_type), target :: model_grid
...
! Create the model grid
model_grid = grid_type(GO_ARAKAWA_C, &
                      (/GO_BC_EXTERNAL,GO_BC_EXTERNAL,GO_BC_NONE/), &
                      GO_OFFSET_NE)
```

Note: The grid object itself must be declared with the `target` attribute. This is because each field object will contain a pointer to it.

The `grid_type` constructor takes three arguments:

1. The type of grid (only `GO_ARAKAWA_C` is currently supported)

2. The boundary conditions on the domain for the x , y and z dimensions (see below). The value for the z dimension is currently ignored.
3. The ‘index offset’ - the convention used for indexing into offset fields.

Three types of boundary condition are currently supported:

Name	Description
GO_BC_NONE	No boundary conditions are applied.
GO_BC_EXTERNAL	Some external forcing is applied. This must be implemented by a kernel. The domain must be defined with a T-point mask (see <i>The grid_init Routine</i>).
GO_BC_PERIODIC	Periodic boundary conditions are applied.

The infrastructure requires this information in order to determine the extent of the model grid.

The index offset is required because a model (kernel) developer has choice in how they actually implement the staggering of variables on a grid. This comes down to a choice of which grid points in the vicinity of a given T point have the same array (i, j) indices. In the diagram below, the image on the left corresponds to choosing those points to the South and West of a T point to have the same (i, j) index. That on the right corresponds to choosing those points to the North and East of the T point (this is the offset scheme used in the NEMO ocean model):



The GOcean 1.0 API supports these two different offset schemes, which we term GO_OFFSET_SW and GO_OFFSET_NE.

Note that the constructor does not specify the extent of the model grid. This is because this information is normally obtained by reading a file (a namelist file, a netcdf file etc.) which is specific to an application. Once this information has been obtained, a second routine, grid_init, is provided with which to ‘load’ a grid object with state. This is discussed below.

The grid_init Routine

Once an application has determined the details of the model configuration, it must use this information to populate the grid object. This is done via a call to the grid_init subroutine:

```
subroutine grid_init(grid, m, n, dxarg, dyarg, tmask)
!> The grid object to configure
type(grid_type), intent(inout) :: grid
!> Dimensions of the model grid
integer,          intent(in)   :: m, n
!> The (constant) grid spacing in x and y (m)
real(wp),         intent(in)   :: dxarg, dyarg
!> Optional T-point mask specifying whether each grid point is
!! wet (1), dry (0) or external (-1).
integer, dimension(m,n), intent(in), optional :: tmask
```


If no T-mask is supplied then this routine configures the grid appropriately for an all-wet domain with periodic boundary conditions in both the x - and y -dimensions. It should also be noted that currently only grids with constant resolution in x and y are supported by this routine.

13.2.2 Fields

Once a model has a grid defined it will require one or more fields. The GOLib contains a `field_mod` module which defines an `r2d_field` type (real, 2-dimensional field) and associated constructor:

```
use field_mod
...
!> Current ('now') sea-surface height at different grid points
type(r2d_field) :: sshn_u_fld, sshn_v_fld, sshn_t_fld
...

! Sea-surface height now (current time step)
sshn_u = r2d_field(model_grid, GO_U_POINTS)
sshn_v = r2d_field(model_grid, GO_V_POINTS)
sshn_t = r2d_field(model_grid, GO_T_POINTS)
```

The constructor takes two arguments:

1. The grid on which the field exists
2. The type of grid point at which the field is defined (GO_U_POINTS, GO_V_POINTS, GO_T_POINTS or GO_F_POINTS)

Note that the grid object need not have been fully configured (by a call to `grid_init` for instance) before it is passed into this constructor.

13.2.3 Example

PSyclone is distributed with a full example of the use of the GOcean Library. See `<PSYCLONEHOME>/examples/gocean/shallow_alg.f90`. In what follows we will walk through a slightly cut-down example for a different program.

The following code illustrates the use of the GOLib in constructing an application:

```
program gocean2d
  use grid_mod ! From dl_esm_inf
  use field_mod ! From dl_esm_inf
  use model_mod
  use boundary_conditions_mod

  !> The grid on which our fields are defined. Must have the 'target'
  !! attribute because each field object contains a pointer to it.
  type(grid_type), target :: model_grid

  !> Current ('now') velocity component fields
  type(r2d_field) :: un_fld, vn_fld
  !> 'After' velocity component fields
  type(r2d_field) :: ua_fld, va_fld
  ...

  ! time stepping index
```

(continues on next page)

(continued from previous page)

```

integer :: istp

! Create the model grid. We use a NE offset (i.e. the U, V and F
! points immediately to the North and East of a T point all have the
! same i,j index). This is the same offset scheme as used by NEMO.
model_grid = grid_type(GO_ARAKAWA_C,                                &
                      (/GO_BC_EXTERNAL,GO_BC_EXTERNAL,GO_BC_NONE/), &
                      GO_OFFSET_NE)

!! read in model parameters and configure the model grid
CALL model_init(model_grid)

! Create fields on this grid

! Velocity components now (current time step)
un_fld = r2d_field(model_grid, GO_U_POINTS)
vn_fld = r2d_field(model_grid, GO_V_POINTS)

! Velocity components 'after' (next time step)
ua_fld = r2d_field(model_grid, GO_U_POINTS)
va_fld = r2d_field(model_grid, GO_V_POINTS)

...

!! time stepping
do istp = nit000, nitend, 1

    call step(istp,                                &
              ua_fld, va_fld, un_fld, vn_fld,      &
              ...)

end do
...
end program gocean2d

```

The `model_init` routine is application specific since it must determine details of the model configuration being run, *e.g.* by reading a namelist file. An example might look something like:

```

subroutine model_init(grid)
  type(grid_type), intent(inout) :: grid

  !> Problem size, read from namelist
  integer :: jpiglo, jpglo
  real(wp) :: dx, dy
  integer, dimension(:,:), allocatable :: tmask

  ! Read model configuration from namelist
  call read_namelist(jpiglo, jpglo, dx, dy, &
                    nit000, nitend, irecord, &
                    jphgr_msh, dep_const, rdt, cbfr, visc)

  ! Set-up the T mask. This defines the model domain.
  allocate(tmask(jpiglo,jpglo))

```

(continues on next page)

(continued from previous page)

```

call setup_tpoints_mask(jpiglo, jpjglo, tmask)

! Having specified the T points mask, we can set up mesh parameters
call grid_init(grid, jpiglo, jpjglo, dx, dy, tmask)

! Clean-up. T-mask has been copied into the grid object.
deallocate(tmask)

end subroutine model_init

```

Here, only `grid_type` and the `grid_init` routine come from the GOLib. The remaining code is all application specific.

Once the grid object is fully configured and all fields have been constructed, a simulation will proceed by performing calculations with those fields. In the example program given above, this calculation is performed in the time-stepping loop within the step subroutine. The way in which this routine uses Invoke calls is described in the [Invokes](#) Section.

13.3 Algorithm

The Algorithm is the top-level specification of the natural science implemented in the software. Essentially it consists of mesh setup, field declarations, initialisation of fields and (a series of) Kernel calls. Infrastructure to support these tasks is provided in version 1.0 of the GOcean library (see [The GOcean Library](#)).

13.3.1 Invokes

The Kernels to call are specified through the use of Invokes, e.g.:

```

call invoke( kernel1(field1, field2),      &
            kernel2(field1, field3)      &
            )

```

The location and number of these `call invoke(...)` statements within the source code is entirely up to the user. The only requirement is that PSyclone must be run on every source file that contains one or more Invokes. The body of each Invoke specifies the kernels to be called, the order in which they are to be applied and the fields (and scalars) that they work with.

Note that the kernel names specified in an Invoke are the names of the corresponding kernel *types* defined in the kernel metadata (see the [Kernel](#) Section). These are not the same as the names of the Fortran subroutines which contain the actual kernel code. The kernel arguments are typically field objects, as described in the [Fields](#) Section, but they may also be scalar quantities (real or integer).

In the example `gocean2d` program shown earlier, there is only one Invoke call and it is contained within the step subroutine:

```

subroutine step(istp,      &
               ua, va, un, vn,      &
               sshn_t, sshn_u, sshn_v, &
               ssha_t, ssha_u, ssha_v, &
               hu, hv, ht)
  use kind_params_mod ! From dl_esm_inf
  use grid_mod        ! From dl_esm_inf

```

(continues on next page)

(continued from previous page)

```

use field_mod      ! From dl_esm_inf
use model_mod, only: rdt ! The model time-step
use continuity_mod, only: continuity
use momentum_mod,  only: momentum_u, momentum_v
use boundary_conditions_mod, only: bc_ssh, bc_solid_u
!> The current time step
integer,          intent(inout) :: istp
type(r2d_field), intent(inout) :: un, vn, sshn_t, sshn_u, sshn_v
type(r2d_field), intent(inout) :: ua, va, ssha_t, ssha_u, ssha_v
type(r2d_field), intent(inout) :: hu, hv, ht

call invoke(
    continuity(ssha_t, sshn_t, sshn_u, sshn_v,    &
              hu, hv, un, vn, rdt),              &
    momentum_u(ua, un, vn, hu, hv, ht,          &
              ssha_u, sshn_t, sshn_u, sshn_v),    &
    momentum_v(va, un, vn, hu, hv, ht,          &
              ssha_v, sshn_t, sshn_u, sshn_v),    &
    bc_ssh(istp, ssha_t),                        &
    bc_solid_u(ua),                             &
    ...
)
end subroutine step

```

Note that in this example the grid was constructed for a model with ‘external’ boundary conditions. These boundary conditions are applied through several user-supplied kernels, two of which (`bc_ssh` and `bc_solid_u`) are include in the above code fragment.

13.4 Kernel

The general requirements for the structure of a Kernel are explained in the [Kernel layer](#) section. This section explains the metadata and subroutine arguments that are specific to the GOcean 1.0 API.

13.4.1 Metadata

The metadata for a GOcean 1.0 API kernel has four components:

- 1) ‘meta_args’,
- 2) ‘iterates_over’,
- 3) ‘index_offset’ and
- 4) ‘procedure’:

These are illustrated in the code below:

```

type, extends(kernel_type) :: my_kernel_type
  type(go_arg), dimension(...) :: meta_args = (/ ... /)
  integer :: iterates_over = ...
  integer :: index_offset = ...
contains

```

(continues on next page)

(continued from previous page)

```

    procedure, nopass :: code => my_kernel_code
end type my_kernel_type

```

These four metadata elements are discussed in order in the following sections.

Argument Metadata: meta_args

The meta_args array specifies information about data that the kernel code expects to be passed to it via its argument list. There is one entry in the meta_args array for each **scalar**, **field**, or **grid-property** passed into the Kernel. Their ordering in the meta_args array must be the same as that in the kernel code argument list. The entry must be of type go_arg which itself contains metadata about the associated argument. The size of the meta_args array must correspond to the total number of **scalars**, **fields** and **grid properties** passed into the Kernel.

For example, if there are a total of two **field** entities being passed to the Kernel then the meta_args array will be of size 2 and there will be two entries of type GO_arg:

```

type(GO_arg) :: meta_args(2) = (/
    go_arg( ... ),
    go_arg( ... )
/)

```

Argument-metadata (metadata contained within the brackets of an go_arg entry), describes either a **scalar**, a **field** or a **grid property**.

The first argument-metadata entry describes how the kernel will access the corresponding argument. As an example, the following meta_args metadata describes four entries, the first one is written to by the kernel while the remaining three are only read:

```

type(go_arg) :: meta_args(4) = (/
    go_arg(GO_WRITE, ... ),
    go_arg(GO_READ, ... ),
    go_arg(GO_READ, ... ),
    go_arg(GO_READ, ... )
/)

```

The second entry to argument-metadata (information contained within the brackets of an go_arg type) describes the type of data represented by the argument. This type falls into three categories; field data, scalar data and grid properties. For field data the metadata entry consists of the type of grid-point that field values are defined on. Since the GOcean API supports fields on an Arakawa C grid, the possible grid-point types are GO_CU, GO_CV, GO_CF and GO_CT. GOcean Kernels can also take scalar quantities as arguments. Since these do not live on grid-points they are specified as either GO_R_SCALAR or GO_I_SCALAR depending on whether the corresponding Fortran variable is a real or integer quantity. Finally, grid-property entries are used to specify any properties of the grid required by the kernel (*e.g.* the area of cells at U points or whether T points are wet or dry).

For example:

```

type(go_arg) :: meta_args(4) = (/
    go_arg(GO_WRITE, GO_CT, ... ),
    go_arg(GO_READ, GO_CU, ... ),
    go_arg(GO_READ, GO_R_SCALAR, ... ),
    go_arg(GO_READ, GO_GRID_AREA_U)
/)

```

Here, the first argument is a field on T points, the second is a field on U points, the fourth is a real scalar and the fifth is a property of the grid (cell area at U points).

The full list of supported grid properties in the GOcean 1.0 API is:

Table 13.1: Grid Properties Table

Name	Description	Type
go_grid_area_t	Cell area at T point	Real array, rank=2
go_grid_area_u	Cell area at U point	Real array, rank=2
go_grid_area_v	Cell area at V point	Real array, rank=2
go_grid_mask_t	T-point mask (1=wet, 0=dry)	Integer array, rank=2
go_grid_dx_t	Grid spacing in x at T points	Real array, rank=2
go_grid_dx_u	Grid spacing in x at U points	Real array, rank=2
go_grid_dx_v	Grid spacing in x at V points	Real array, rank=2
go_grid_dy_t	Grid spacing in y at T points	Real array, rank=2
go_grid_dy_u	Grid spacing in y at U points	Real array, rank=2
go_grid_dy_v	Grid spacing in y at V points	Real array, rank=2
go_grid_lat_u	Latitude of U points (gphiu)	Real array, rank=2
go_grid_lat_v	Latitude of V points (gphiv)	Real array, rank=2
go_grid_dx_const	Grid spacing in x if constant	Real, scalar
go_grid_dy_const	Grid spacing in y if constant	Real, scalar
go_grid_x_min_index	Minimum X index	Integer, scalar
go_grid_x_max_index	Maximum X index	Integer, scalar
go_grid_y_min_index	Minimum Y index	Integer, scalar
go_grid_y_max_index	Maximum Y index	Integer, scalar

These are defined in the psyclone config file (see [Configuration](#)), and the user or infrastructure library developer can provide additional entries if required. PSyclone will query PSyclone's Configuration class to get the properties required. All of the rank-two arrays have the first rank as longitude (x) and the second as latitude (y).

Scalars and fields contain a third argument-metadata entry which describes whether the kernel accesses the corresponding argument with a stencil. The value GO_POINTWISE indicates that there is no stencil access. Metadata for a scalar field is limited to this value. Grid-property arguments have no third metadata argument. If there are no stencil accesses then the full argument metadata for our previous example will be:

```
type(go_arg) :: meta_args(4) = (/
    go_arg(GO_WRITE, GO_CT, GO_POINTWISE),
    go_arg(GO_READ, GO_CU, GO_POINTWISE),
    go_arg(GO_READ, GO_R_SCALAR, GO_POINTWISE),
    go_arg(GO_READ, GO_GRID_AREA_U)
/)
```

If a kernel accesses a field using a stencil then the third argument metadata entry should take the form go_stencil(...). Note, a stencil access is only allowed for a field that is READ by a kernel.

In the GOcean API, fields are implemented as two-dimensional arrays. In Fortran, a standard 5-point stencil would look something like the following:

```
a(i,j) + a(i+1,j) + a(i-1,j) + a(i,j+1) + a(i,j-1)
```

If we view the above accesses as co-ordinates relative to the a(i,j) access we get (0,0), (1,0), (-1,0), (0,1), (0,-1). If we then view these accesses in graphical form with i being in the horizontal direction and j in the vertical and with a 1 indicating a (depth-1) access and a 0 indicating there is no access we get the following:

```
010
111
010
```

In the GOcean API a stencil access is captured as a triplet of integers (one row at a time from top to bottom) using the above view i.e.

```
go_stencil(010,111,010)
```

So far we have only considered depth-1 stencils. In our notation the depth of access is captured by the integer value (0 for no access, 1 for depth 1, 2 for depth 2 etc). For example:

```
a(i,j) + a(i,j+1) + a(i,j+2)
```

would be captured as:

```
go_stencil(020,010,000)
```

All forms of stencil can be **summarised** using this triplet notation up to a depth of 9 apart from the central $a(i,j)$ value which can either be 0 (not accessed) or 1 (accessed). Note, the central value is not currently used by PSyclone. The notation is a **summary** in two ways

- 1) it only captures the depth of the stencil in a particular direction, not the actual accesses. Therefore, there is no way to distinguish between the stencil $a(i+2,j)$ and the stencil $a(i+1,j) + a(i+2,j)$.
- 2) when there are offsets for both i and j e.g. $a(i+1,j+1)$ it only captures whether there is an access in that direction at a particular depth, not the details of the access. For example, there is no way to distinguish between $a(i+2,j+2)$ and $a(i+2,j+2) + a(i+1,j+2) + a(i+2,j+1)$.

Whilst the description is a summary, it is accurate enough for PSyclone as this information is primarily used to determine which grid partitions must communicate with which for the purposes of placing halo exchange calls. In this case, it is the depth and direction information that is most important.

Iterates Over

The second element of kernel metadata is `ITERATES_OVER`. This specifies that the Kernel has been written with the assumption that it is iterating over grid points of the specified type. By default the supported values are: `GO_INTERNAL_PTS`, `GO_EXTERNAL_PTS` and `GO_ALL_PTS`. These may be understood by considering the following diagram of an example model configuration:



GO_INTERNAL_PTS are then those points that are within the Model domain (fuchsia box),

GO_EXTERNAL_PTS are those outside the domain and GO_ALL_PTS encompasses all grid points in the model. The chosen value is specified in the kernel-meta data like so:

```
integer :: iterates_over = GO_INTERNAL_PTS
```

A user can use a config file (see [Configuration](#)) to add additional iteration spaces to PSyclone.

Index Offset

The third element of kernel metadata, INDEX_OFFSET, specifies the index-offset that the kernel uses. This is the same quantity as supplied to the grid constructor (see the [Grid](#) Section for a description).

The GOcean 1.0 API supports two different offset schemes; GO_OFFSET_NE, GO_OFFSET_SW. The scheme used by a kernel is specified in the metadata as, e.g.:

```
integer :: index_offset = GO_OFFSET_NE
```

Currently all kernels used in an application must use the same offset scheme which must also be the same as passed to the grid constructor.

Procedure

The fourth and final type of metadata is procedure metadata. This specifies the name of the Kernel Fortran subroutine that this metadata describes.

For example:

```
procedure :: my_kernel_code
```

13.4.2 Subroutine

Rules

Kernel arguments follow a set of rules which have been specified for the GOcean 1.0 API. These rules are encoded in the gen_code() method of the GOKern class in the gocean1p0.py file. The rules, along with PSyclone's naming conventions, are:

- 1) Every kernel has the indices of the current grid point as the first two arguments, i and j. These are integers and have intent in.
- 2) For each field/scalar/grid property in the order specified by the meta_args metadata:
 - 1) For a field; the field array itself. A field array is a real array of kind go_wp and rank two. The first rank is longitude (x) and the second latitude (y).
 - 2) For a scalar; the variable itself. A real scalar is of kind go_wp.
 - 3) For a grid property; the array or variable (see the earlier table) containing the specified property.

Note: Grid properties are not passed from the Algorithm Layer. PSyclone generates the necessary lookups in the PSy Layer and includes the resulting references in the arguments passed to the kernel.

As an example, consider the bc_solid_u kernel that is used in the gocean2d program shown earlier. The metadata for this kernel is:

```
type, extends(kernel_type) :: bc_solid_u
  type(go_arg), dimension(2) :: meta_args = &
    (/ go_arg(GO_WRITE, GO_CU, GO_POINTWISE), &
      go_arg(GO_READ, GO_GRID_MASK_T) &
    /)

!> This is a boundary-conditions kernel and therefore
!! acts on all points of the domain rather than just
!! those that are internal
integer :: ITERATES_OVER = GO_ALL_PTS

integer :: index_offset = GO_OFFSET_NE

contains
  procedure, nopass :: code => bc_solid_u_code
end type bc_solid_u
```

The interface to the subroutine containing the implementation of this kernel is:

```
subroutine bc_solid_u_code(ji, jj, ua, tmask)
  integer,          intent(in)  :: ji, jj
  integer, dimension(:, :), intent(in)  :: tmask
  real(wp), dimension(:, :), intent(inout) :: ua
```

As described above, the first two arguments to this subroutine specify the grid-point at which the computation is to be performed. The third argument is the field that this kernel updates and the fourth argument is the T-point mask. The latter is a property of the grid and is provided to the kernel call from the PSy Layer.

Comparing this interface definition with the use of the kernel in the Invoke call:

```
call invoke ( ..., &
             bc_solid_u(ua), &
             ... )
```

we see that in the Algorithm Layer the user need only provide the field(s) (and possibly scalars) that a kernel operates on. The index of the grid point and any grid properties are provided in the (generated) PSy Layer where the kernel subroutine proper is called.

13.5 Built-ins

The GOcean 1.0 API does not support any built-in operations.

13.6 Conventions

The GOcean 1.0 API kernel code conforms to the PSyclone Fortran naming conventions (see *Fortran Naming Conventions*). However, PSyclone's support for the GOcean 1.0 API does not rely on this convention.

The contents of the kernel metadata is usually declared private but this does not affect PSyclone.

Finally, the procedure metadata (located within the kernel metadata) usually has nopass specified but again this is ignored by PSyclone.

13.7 Configuration

The configuration file (see [Configuration](#)) used by PSyclone can contain GOcean 1.0 specific options. For example, after the default section the GOcean 1.0 specific section looks like this:

```
[gocean1.0]
iteration-spaces=offset_sw:ct:test_only:1:2:3:4
                offset_sw:ct:internal_ns_halo:{start}-1:{stop}+1:{start}:{stop}
```

The supported keys are listed in the next section.

13.7.1 Iteration-spaces

This section lists additional iteration spaces that can be used in a kernel metadata declaration to allow PSyclone to create a loop with different loop boundaries. Each line of the iteration-spaces declaration contains 7 values, separated by ‘:’. The fields are:

Field	Description	Details
1	Index Offset	See Index Offset .
2	grid-point types	See Grid point types .
3	Iterates Over	See Iterates Over .
4	Start index of outer loop	Start index of North-South loop.
5	End index of outer loop	End index of North-South loop.
6	Start index of inner loop	Start index of East-West loop.
7	End index of inner loop	End index of East-West loop.

Two special variables can be used in an iteration space: {start} and {stop}. These values will be replaced by PSyclone with the correct loop boundaries for the inner points of a grid (i.e. the non-halo area). This means that the depth-1 halo region can be specified using {start}-1 and {stop}+1.

For example, given the iteration-spaces declaration above, a kernel declared with iterates_over=internal_ns_halo for a field type ct and index offset offset_sw would create the following loop boundaries:

```
DO j=2-1,jstop+1
  DO i=2,istop
    CALL (i, j, ...)
  END DO
END DO
```

Warning: With user defined iteration spaces it is possible that PSyclone will create code that does not compile: if you specify syntactically correct, but semantically incorrect boundary definitions, the PSyclone internal tests will accept the new iteration space, but the compiler will not. For example if one of the loop boundaries contains the name of a variable that is not defined, compilation will fail. It is the responsibility of the user to make sure that valid loop boundaries are specified in a new iteration space definition.

13.7.2 Grid Properties

Various grid properties can be specified as parameters to a kernel. The actual names and meaning of these properties depend on the infrastructure library used. By default PSyclone provides settings for the `dl_esm_inf` infrastructure library. But the user or a library developer can change or add definitions to the configuration file as required.

The grid properties are specified as values for the key `grid-properties`. They consist of three entries, separated by “:”.

- The first entry is the name of the property as used in kernel metadata.
- The next entry is the way of dereferencing the corresponding value in Fortran. The expression `{0}` is replaced with the field name that is used. Note that any `%` must be replaced with `%%` (due to the way Python reads in configuration files).
- The last entry specifies whether the value is an array or a scalar.

Below an excerpt from the configuration file that is distributed with PSyclone:

```
grid-properties = go_grid_xstop: {0}%%grid%%subdomain%%internal%%xstop: scalar,
                  go_grid_ystop: {0}%%grid%%subdomain%%internal%%ystop: scalar,
                  go_grid_data: {0}%%data: array,
                  go_grid_internal_inner_stop: {0}%%internal%%xstop: scalar,
                  go_grid_internal_outer_stop: {0}%%internal%%ystop: scalar,
                  go_grid_whole_inner_stop: {0}%%whole%%xstop: scalar,
                  go_grid_whole_outer_stop: {0}%%whole%%ystop: scalar,
...
```

Most of the property names can be set arbitrarily by the user (to match whatever infrastructure library is being used), but PSyclone relies on a small number of properties that must be defined with the right name:

Key	Description
<code>go_grid_data</code>	This property gives access to the raw 2d-field.
<code>go_grid_xstop, go_grid_ystop</code>	These values specify the upper loop boundary when computing the constant loop boundaries.
<code>go_grid_{internal,whole}_ _{inner,outer}_{start,stop}</code>	These eight values are required to specify the loop boundaries depending on the field space.
<code>go_grid_nx, go_grid_ny</code>	These properties are only required when OpenCL is enabled. They specify the overall array size (including any padding that the infrastructure library might implement).

13.7.3 Debug Mode

The GOcean configuration also includes a boolean parameter to enable or disable the generation of additional code which may impact performance but is useful for debugging the application. By default it is set to `False`, but it can be changed by updating the following line in the configuration file:

```
[gocean1.0]
DEBUG_MODE = true
```

Currently, only the OpenCL Invokes generate additional debugging code.

13.8 Transformations

In this section we describe the transformations that are specific to the GOcean 1.0 API. For an overview of transformations in general see *Transformations*.

class `psyclone.domain.gocean.transformations.GOceanExtractTrans`

GOcean1.0 API application of ExtractTrans transformation to extract code into a stand-alone program. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>>
>>> API = "gocean1.0"
>>> FILENAME = "shallow_alg.f90"
>>> ast, invokeInfo = parse(FILENAME, api=API)
>>> psy = PSyFactory(API, distributed_memory=False).create(invoke_info)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>>
>>> from psyclone.domain.gocean.transformations import GOceanExtractTrans
>>> etrans = GOceanExtractTrans()
>>>
>>> # Apply GOceanExtractTrans transformation to selected Nodes
>>> etrans.apply(schedule.children[0])
>>> print(schedule.view())
```

`apply(nodes, options=None)`

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Nodes in the schedule within a single PSyData region. Note that this implementation just calls the base class, it is only added here to provide the documentation for this function, since it accepts different options to the base class (e.g. `create_driver`, which is passed to the `ExtractNode` instance that will be inserted.).

Parameters

- `nodes` (`psyclone.psyir.nodes.Node` or list of `psyclone.psyir.nodes.Node`) – can be a single node or a list of nodes.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- `options["prefix"]` (`str`) – a prefix to use for the PSyData module name (`prefix_psy_data_mod`) and the PSyDataType (`prefix_PSyDataType`) - a “_” will be added automatically. It defaults to “extract”, resulting in e.g. `extract_psy_data_mod`.
- `options["create_driver"]` (`bool`) – whether or not to create a driver program at code-generation time. If set, the driver will be created in the current working directory with the name “driver-MODULE-REGION.f90” where MODULE and REGION will be the corresponding values for this region. Defaults to False.
- `options["region_name"]` ((`str, str`)) – an optional name to use for this PSyData area, provided as a 2-tuple containing a location name followed by a local name. The pair of strings should uniquely identify a region unless aggregate information is required (and is supported by the runtime library).

`validate(node_list, options=None)`

Perform GOcean1.0 API specific validation checks before applying the transformation.

Parameters

- `node_list` (list of `psyclone.psyir.nodes.Node`) – the list of Node(s) we are checking.

- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- options["create_driver"] (bool) – whether or not to create a driver program at code-generation time. If set, the driver will be created in the current working directory with the name “driver-MODULE-REGION.f90” where MODULE and REGION will be the corresponding values for this region. This flag is forwarded to the ExtractNode. Its default value is False.
- options["region_name"] ((str,str)) – an optional name to use for this data-extraction region, provided as a 2-tuple containing a module name followed by a local name. The pair of strings should uniquely identify a region unless aggregate information is required (and is supported by the runtime library). This option is forwarded to the PSyDataNode (where it changes the region names) and to the ExtractNode (where it changes the name of the created output files and the name of the driver program).

Raises

TransformationError – if transformation is applied to an inner Loop without its parent outer Loop.

class psyclone.domain.gocean.transformations.GOceanLoopFuseTrans

GOcean API specialisation of the base class in order to fuse two GOcean loops after performing validity checks (e.g. that the loops are over the same grid-point type). For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> ast, invokeInfo = parse("shallow_alg.f90")
>>> psy = PSyFactory("gocean1.0").create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> print(schedule.view())
>>>
>>> from psyclone.transformations import GOceanLoopFuseTrans
>>> ftrans = GOceanLoopFuseTrans()
>>> ftrans.apply(schedule[0], schedule[1])
>>> print(schedule.view())
```

validate(*node1*, *node2*, *options=None*)

Checks if it is valid to apply the GOceanLoopFuseTrans transform. It ensures that the fused loops are over the same grid-point types, before calling the normal LoopFuseTrans validation function.

Parameters

- node1 (psyclone.gocean1p0.GOLoop) – the first Node representing a GOLoop.
- node2 (psyclone.gocean1p0.GOLoop) – the second Node representing a GOLoop.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

- TransformationError – if the supplied loops are over different grid-point types.
 - TransformationError – if invalid parameters are passed in.
-

```
class psyclone.transformations.GOceanOMPParallelLoopTrans(omp_directive='do', omp_schedule='static')
```

GOcean specific OpenMP Do loop transformation. Adds GOcean specific validity checks (that supplied Loop is an inner or outer loop). Actual transformation is done by [base class](#).

param str omp_directive

choose which OpenMP loop directive to use. Defaults to “do”.

param str omp_schedule

the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

```
apply(node, options=None)
```

Perform GOcean-specific loop validity checks then call [OMPParallelLoopTrans.apply\(\)](#).

Parameters

- *node* ([psyclone.psyir.nodes.Loop](#)) – a Loop node from an AST.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations and validation.

Raises

TransformationError – if the supplied node is not an inner or outer loop.

```
class psyclone.transformations.GOceanOMPLoopTrans(omp_directive='do', omp_schedule='static')
```

GOcean-specific orphan OpenMP loop transformation. Adds GOcean specific validity checks (that the node is either an inner or outer Loop).

Parameters

- *omp_directive* (*str*) – choose which OpenMP loop directive to use. Defaults to “do”.
- *omp_schedule* (*str*) – the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

```
validate(node, options=None)
```

Checks that the supplied node is a valid target for parallelisation using OMP directives.

Parameters

- *node* ([psyclone.psyir.nodes.Loop](#)) – the candidate loop for parallelising using OMP Do.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

TransformationError – if the loop_type of the supplied Loop is not “inner” or “outer”.

```
class psyclone.domain.gocean.transformations.GOConstLoopBoundsTrans
```

Use of a common constant variable for each loop bound within a GOInvokeSchedule. By default, PSyclone generates loops where the bounds are obtained by de-referencing a field object, e.g.:

```
DO j = my_field%grid%internal%ystart, my_field%grid%internal%ystop
```

Some compilers are able to produce more efficient code if they are provided with information on the relative trip-counts of the loops within an Invoke. With constant loop bounds, PSyclone generates code like:

```
ny = my_field%grid%subdomain%internal%ystop
...
DO j = 1, ny-1
```

In practice, the application of the constant loop bounds transformation looks something like, e.g.:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> import os
>>> TEST_API = "gocean1.0"
>>> _, info = parse(os.path.join("tests", "test_files", "gocean1p0",
...                               "single_invoke.f90"),
...                 api=TEST_API)
>>> psy = PSyFactory(TEST_API).create(info)
>>> invoke = psy.invokes.get('invoke_0_compute_cu')
>>> schedule = invoke.schedule
>>>
>>> from psyclone.transformations import GOConstLoopBoundsTrans
>>> clbtrans = GOConstLoopBoundsTrans()
>>>
>>> clbtrans.apply(schedule)
>>> print(schedule.view())
```

`apply(node, options=None)`

Modify the GOcean kernel loops in a GOInvokeSchedule to use common constant loop bound variables.

Parameters

- node (psyclone.gocean1p0.GOInvokeSchedule) – the GOInvokeSchedule of which all loops will get the constant loop bounds.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns

the name of the Transformation as a string.

Return type

str

`validate(node, options=None)`

Checks if it is valid to apply the GOConstLoopBoundsTrans transform.

Parameters

- node (psyclone.gocean1p0.GOInvokeSchedule) – the GOInvokeSchedule to transform.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

- TransformationError – if the supplied node is not a GOInvokeSchedule.
- TransformationError – if the supplied schedule has loops with a loop with loop_type different than 'inner' or 'outer'.
- TransformationError – if the supplied schedule has loops with attributes for index_offsets, field_space, iteration_space and loop_type that don't appear in the GOLoop.bounds_lookup table.

- TransformationError – if the supplied schedule doesn't have a field argument.

class psyclone.domain.gocean.transformations.GOMoveIterationBoundariesInsideKernelTrans

Provides a transformation that moves iteration boundaries that are encoded in the Loops lower_bound() and upper_bound() methods to a mask inside the kernel with the boundaries passed as kernel arguments.

For example the following kernel call:

```
do i = 2, N - 1
  do j = 2, N - 1
    kernel(i, j, field)
  end do
end do
```

will be transformed to:

```
startx = 2
stopx = N - 1
starty = 2
stopy = N - 1
do i = 1, size(field, 1)
  do j = 1, size(field, 2)
    kernel(i, j, field, startx, stopx, starty, stopy)
  end do
end do
```

additionally a mask like the following one will be introduced in the kernel code:

```
if (i < startx .or. i > stopx .or. j < starty .or. j > stopy) then
  return
end if
```

apply(*node*, *options*=None)

Apply this transformation to the supplied node.

Parameters

- node (psyclone.gocean1p0.GOKern) – the node to transform.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns the name of this transformation as a string.

validate(*node*, *options*=None)

Ensure that it is valid to apply this transformation to the supplied node.

Parameters

- node (psyclone.gocean1p0.GOKern) – the node to validate.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

TransformationError – if the node is not a GOKern.

NEMO API

In contrast to the other APIs supported by PSyclone, the NEMO API is designed to work with source code that does *not* follow the PSyKAl separation of concerns. Instead, the NEMO source code is treated as if it were a manually written PSy layer with all kernels in-lined. This approach relies upon the NEMO Coding Conventions [nem13] in order to reason about the code being processed. Rather than construct an InvokeSchedule for the PSy layer from scratch (as is done for other APIs), the InvokeSchedule is constructed by parsing the supplied Fortran code and generating a higher-level representation.

Note: the NEMO API is currently only a prototype. The known issues are listed in [Limitations](#).

14.1 Algorithm

Since NEMO source is treated as a pre-existing PSy layer, this API does not have the concept of an Algorithm layer.

14.2 Constructing the PSyIR

Transformations in PSyclone are applied to an Internal Representation, the “PSyIR.” In contrast to the other APIs where the PSyIR is constructed from scratch, for NEMO PSyclone must parse the existing Fortran and create a higher-level representation of it. This is done using rules based upon the NEMO Coding Conventions [nem13]. These rules are described in the following sections.

14.2.1 Loops

Explicit

PSyclone recognises the following loop types, based on the name of the loop variable:

Loop type	Loop variable
Vertical levels	jk
Latitude	ji
Longitude	jj
Tracer species	jn

PSyclone currently assumes that each of these loop types may be safely parallelised. In practice this will not always be the case (e.g. when performing a tri-diagonal solve) and this implementation will need to be refined.

Implicit

The use of Fortran array notation is encouraged in the NEMO Coding Conventions [nem13] (section 4.2) and is employed throughout the NEMO code base. The Coding Conventions mandate that the shape of every array in such expressions must be specified, e.g.:

```
onedarraya(:) = onedarrayb(:) + onedarrayc(:)
twodarray(:, :) = scalar * anothertwodarray(:, :)
```

PSyclone therefore also recognises the loops implied by this notation.

Note, not all uses of Fortran array notation in NEMO imply a loop. For instance:

```
ascalar = afunc(twodarray(:, :))
```

is actually a function call which is passed a reference to twodarray. However, if the quantity being assigned to is actually an array, e.g.:

```
twodarray2(:, :) = afunc(twodarray(:, :))
```

then this does represent a loop. However, currently PSyclone does not recognise any occurrences of array notation that are themselves within an array access or function call. It is therefore not yet possible to transform such implicit loops into explicit loops. It is hoped that this limitation will be removed in future releases of PSyclone by adding the ability to discover the interface to functions such as afunc and thus determining whether they return scalar or array quantities.

14.3 Example

A typical fragment of NEMO source code (taken from the traldf_iso routine) is shown below:

```
DO jn = 1, kjpt
  zdit (1, :, :) = 0._wp      ;    zdit (jpi, :, :) = 0._wp
  zdjt (1, :, :) = 0._wp      ;    zdjt (jpi, :, :) = 0._wp

  DO jk = 1, jpkml
    DO jj = 1, jpjml
      DO ji = 1, fs_jpim1
        zdit(ji, jj, jk) = ( ptb(ji+1, jj, jk, jn) - ptb(ji, jj, jk, jn) ) * umask(ji, jj, jk)
        zdjt(ji, jj, jk) = ( ptb(ji, jj+1, jk, jn) - ptb(ji, jj, jk, jn) ) * vmask(ji, jj, jk)
      END DO
    END DO
  END DO
```

PSyclone uses fparser2 to parse such source code and then generates the PSy Internal Representation of it:

```
Loop[type='tracers', field_space='None', it_space='None']
  Loop[type='None', field_space='None', it_space='None']
  Loop[type='None', field_space='None', it_space='None']
  Loop[type='None', field_space='None', it_space='None']
  Loop[type='None', field_space='None', it_space='None']
  Loop[type='levels', field_space='None', it_space='None']
    Loop[type='lat', field_space='None', it_space='None']
      Loop[type='lon', field_space='None', it_space='None']
        CodedKern[]
```

14.4 Transformations

The following transformations are specific to the NEMO API.

`class psyclone.domain.nemo.transformations.NemoLoopFuseTrans`

NEMO-specific implementation of the loop fusion transformation.

`apply(node1, node2, options=None)`

Fuses two loops represented by *psyclone.psyir.nodes.Node* objects after performing validity checks.

Parameters

- `node1` (*psyclone.psyir.nodes.Node*) – the first Node that is being checked.
- `node2` (*psyclone.psyir.nodes.Node*) – the second Node that is being checked.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

`validate(node1, node2, options=None)`

Perform NEMO API specific validation checks before applying the transformation.

Parameters

- `node1` (*psyclone.psyir.nodes.Node*) – the first Node that is being checked.
- `node2` (*psyclone.psyir.nodes.Node*) – the second Node that is being checked.
- `options` (Optional[Dict[str, Any]]) – a dict with options for transformations.

Raises

- `TransformationError` – if the lower or upper loop boundaries are not the same.
- `TransformationError` – if the loop step size is not the same.
- `TransformationError` – if the loop variables are not the same.

`class psyclone.domain.nemo.transformations.NemoArrayRange2LoopTrans`

Transformation that given an assignment with an `ArrayReference` Range in the LHS (equivalent to an array assignment statement in Fortran), it converts it to an explicit loop doing each of the individual element assignments separately. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> filename = "tra_adv.F90" # examples/nemo/code
>>> ast, invoke_info = parse(filename, api=api)
>>> psy = PSyFactory(api).create(invoke_info)
>>> schedule = psy.invokes.invoke_list[0].schedule
>>> print(schedule.view())
>>>
>>> from psyclone.psyir.nodes import Range
>>> from psyclone.domain.nemo.transformations import NemoArrayRange2LoopTrans
>>> from psyclone.transformations import TransformationError
>>>
>>> trans = NemoArrayRange2LoopTrans()
```

(continues on next page)

(continued from previous page)

```
>>> for my_range in reversed(schedule.walk(Range)):
>>>     try:
>>>         trans.apply(my_range)
>>>     except TransformationError:
>>>         pass
>>> print(schedule.view())
```

The specified Range node must be the outermost Range (specifying an access to an array index) within an Array Reference and the array reference must be on the left-hand-side of an Assignment node. This is required for correctness and if not satisfied the transformation will raise an exception.

`apply(node, options=None)`

Apply the transformation that given an assignment with an ArrayReference Range in the LHS (equivalent to an array assignment statement in Fortran), it converts it to an explicit loop doing each of the individual element assignments separately.

The Range node is provided to the apply method of the transformation to indicate which array index should be transformed. This can only be applied to the outermost Range of the ArrayReference.

This is currently specific to NEMO. It will create NemoLoops and put the loop body inside a NemoKern to conform to the NEMO API.

Parameters

- node (`psyclone.psyir.nodes.Range`) – a Range node.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.

`validate(node, options=None)`

Perform various checks to ensure that it is valid to apply the NemoArrayRange2LoopTrans transformation to the supplied PSyIR Node.

Parameters

- node (`psyclone.psyir.nodes.Range`) – the node that is being checked.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.

Raises

- TransformationError – if the node argument is not a Range, if the Range node is not part of an ArrayReference, if the Range node is not the outermost Range node of the ArrayReference or if that ArrayReference does not constitute the left hand side of an Assignment node.
- TransformationError – if the node argument has nested array expressions with Ranges or is an invalid tree with ranges in multiple locations of a structure of arrays.
- TransformationError – if the node argument contains a non-elemental Operation or Call.

`class psyclone.domain.nemo.transformations.NemoOuterArrayRange2LoopTrans`

Provides a transformation from the outermost PSyIR ArrayReference Range to a PSyIR NemoLoop. For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> filename = "tra_adv.F90" # examples/nemo/code
>>> ast, invoke_info = parse(filename, api=api)
>>> psy = PSyFactory(api).create(invoke_info)
>>> schedule = psy.invokes.invoke_list[0].schedule
>>>
>>> from psyclone.psyir.nodes import Assignment
>>> from psyclone.domain.nemo.transformations import
↳ NemoOuterArrayRange2LoopTrans
>>> from psyclone.transformations import TransformationError
>>>
>>> print(schedule.view())
>>> trans = NemoOuterArrayRange2LoopTrans()
>>> for assignment in schedule.walk(Assignment):
>>>     while True:
>>>         try:
>>>             trans.apply(assignment)
>>>         except TransformationError:
>>>             break
>>> print(schedule.view())

```

`apply(node, options=None)`

Apply the NemoOuterArrayRange2Loop transformation to the specified node if the node is an Assignment and the left-hand-side of the assignment is an Array Reference containing at least one Range node specifying an access to an array index. If this is the case then the outermost Range nodes within array references within the assignment are replaced with references to a loop index. A NemoLoop loop (with the same loop index) is also placed around the modified assignment statement. If the array reference on the left-hand-side of the assignment only had one range node as an index (so now has none) then the assignment is also placed within a NemoKern.

The name of the loop index is taken from the PSyclone configuration file if a name exists for the particular array index, otherwise a new name is generated. The bounds of the loop are taken from the Range node if they are provided. If not, the loop bounds are taken from the PSyclone configuration file if bounds values are supplied. If not, the LBOUND or UBOUND intrinsics are used as appropriate. The type of the NemoLoop is also taken from the configuration file if it is supplied for that index, otherwise it is specified as being “unknown”.

Parameters

- *node* (`psyclone.psyir.nodes.Assignment`) – an Assignment node.
- *options* (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.

`validate(node, options=None)`

Perform various checks to ensure that it is valid to apply the NemoOuterArrayRange2LoopTrans transformation to the supplied PSyIR Node.

Parameters

- *node* (`psyclone.psyir.nodes.Assignment`) – the node that is being checked.
- *options* (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.

Raises

TransformationError – if the supplied node is not an Assignment node, if the Assignment node does not have an Array-type Reference node on its left hand side or if the Array-type node does not contain at least one Range node.

class `psyclone.domain.nemo.transformations.NemoAllArrayRange2LoopTrans`

Provides a transformation for all PSyIR Array Ranges in an assignment to PSyIR NemoLoops. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> filename = "tra_adv.F90" # examples/nemo/code
>>> ast, invoke_info = parse(filename, api=api)
>>> psy = PSyFactory(api).create(invoke_info)
>>> schedule = psy.invokes.invoke_list[0].schedule
>>>
>>> from psyclone.psyir.nodes import Assignment
>>> from psyclone.domain.nemo.transformations import NemoAllArrayRange2LoopTrans
>>>
>>> print(schedule.view())
>>> trans = NemoAllArrayRange2LoopTrans()
>>> for assignment in schedule.walk(Assignment):
>>>     trans.apply(assignment)
>>> print(schedule.view())
```

`apply(node, options=None)`

Apply the NemoAllArrayRange2Loop transformation to the specified node if the node is an Assignment and the left-hand-side of the assignment is an Array Reference containing at least one Range node specifying an access to an array index. If this is the case then all Range nodes within array references within the assignment are replaced with references to the appropriate loop indices. The appropriate number of NemoLoop loops are also placed around the modified assignment statement and the assignment statement is placed within a NemoKern.

The name of each loop index is taken from the PSyclone configuration file if a name exists for the particular array index, otherwise a new name is generated. The bounds of each loop are taken from the Range node if they are provided. If not, the loop bounds are taken from the PSyclone configuration file if a bounds value is supplied. If not, the LBOUND or UBOUND intrinsics are used as appropriate. The type of the NemoLoop is also taken from the configuration file if it is supplied for that index, otherwise it is specified as being “unknown”.

Parameters

- `node` (`psyclone.psyir.nodes.Assignment`) – an Assignment node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.
- `options["verbose"]` (`bool`) – whether to print out the reason why the inner transformation was not applied. This is useful because this transformation succeeds even if one of the inner transformations fails, and therefore the reason why the inner transformation failed is not propagated.

`validate(node, options=None)`

Perform various checks to ensure that it is valid to apply the NemoArrayRange2LoopTrans transformation to the supplied PSyIR Node.

Parameters

- `node` (`psyclone.psyir.nodes.Assignment`) – the node that is being checked.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to `None`.

Raises

`TransformationError` – if the supplied node is not an `Assignment`.

```
class psyclone.domain.nemo.transformations.NemoArrayAccess2LoopTrans
```

Provides a transformation to transform a constant index access to an array (i.e. one that does not contain a loop iterator) to a single trip loop. For example:

```
>>> from psyclone.domain.nemo.transformations import \
...     NemoArrayAccess2LoopTrans
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Assignment
>>> code = ("program example\n"
...         "  real a(10)\n"
...         "  a(1) = 0.0\n"
...         "end program example\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> assignment = psyir.walk(Assignment)[0]
>>> NemoArrayAccess2LoopTrans().apply(assignment.lhs.children[0])
>>> print(FortranWriter()(psyir))
program example
  real, dimension(10) :: a
  integer :: ji

  do ji = 1, 1, 1
    a(ji) = 0.0
  enddo

end program example
```

```
apply(node, options=None)
```

Apply the `NemoArrayAccess2Loop` transformation if the supplied node is an access to an array index within an Array Reference that is on the left-hand-side of an `Assignment` node. The access must be a scalar (i.e. not a range) and must not include a loop variable (as we are transforming a single access to a loop).

These constraints are required for correctness and an exception will be raised if they are not satisfied. If the constraints are satisfied then the array access is replaced with a loop iterator and a single trip loop.

The new loop will be placed immediately around the assignment i.e. it will not take into account any expected nesting (`ji`, `jj`, `jk` etc) constraints. Loop re-ordering should be performed by a separate transformation.

The name of the loop index is taken from the PSyclone configuration file if a name exists for the particular array index, otherwise a new name is generated.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – an array index.

- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.

`validate(node, options=None)`

Perform various checks to ensure that it is valid to apply the NemoArrayAccess2LoopTrans transformation to the supplied PSyIR Node.

Parameters

- node (psyclone.psyir.nodes.Node) – the node that is being checked.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to None.

class psyclone.domain.nemo.transformations.NemoAllArrayAccess2LoopTrans

Provides a transformation from a PSyIR Assignment containing constant index accesses to an array into single trip loops: For example:

```
>>> from psyclone.domain.nemo.transformations import \
...     NemoAllArrayAccess2LoopTrans
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Assignment
>>> code = ("program example\n"
...        "  real a(10,10), b(10,10)\n"
...        "  integer :: n\n"
...        "  a(1,n-1) = b(1,n-1)\n"
...        "end program example\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> assignment = psyir.walk(Assignment)[0]
>>> NemoAllArrayAccess2LoopTrans().apply(assignment)
>>> print(FortranWriter()(psyir))
program example
  real, dimension(10,10) :: a
  real, dimension(10,10) :: b
  integer :: n
  integer :: ji
  integer :: jj

  do ji = 1, 1, 1
    do jj = n - 1, n - 1, 1
      a(ji,jj) = b(ji,jj)
    enddo
  enddo

end program example
```

`apply(node, options=None)`

Apply the NemoAllArrayAccess2Loop transformation if the supplied node is an Assignment with an Array Reference on its left-hand-side. Each constant array index access (i.e. one not containing a loop iterator or a range) is then transformed into an iterator and the assignment placed within a single trip loop, subject to any constraints in the NemoArrayAccess2Loop transformation.

If any of the NemoAllArrayAccess2Loop constraints are not satisfied for a loop index then this transformation does nothing for that index and silently moves to the next.

Parameters

- `node` (`psyclone.psyir.nodes.Assignment`) – an assignment.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to `None`.

`validate(node, options=None)`

Perform any checks to ensure that it is valid to apply the `NemoAllArrayAccess2LoopTrans` transformation to the supplied PSyIR Node.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the node that is being checked.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations. No options are used in this transformation. This is an optional argument that defaults to `None`.

14.5 Limitations

The NEMO API is currently under development. Here we list the current, known limitations/issues:

1. Scalar variables inside loops are not made private when parallelising using OpenMP;
2. Labelled do-loops are not handled (i.e. they will be put inside a ‘CodeBlock’ in the PSyIR);
3. Loops are currently only permitted to contain one kernel. This restriction will have to be lifted in order to permit loop fusion;
4. The `psyir.nodes.Node` base class now has an `_ast` property to hold a pointer into the associated `fparser2` AST. However, the `psyGen.Kern` class already has an `_fp2_ast` property that points to the whole `fparser2` AST of the kernel code. This will be rationalised in #241;

PSYIR : THE PSYCLONE INTERNAL REPRESENTATION

The PSyIR is at the heart of PSyclone, representing code (at both the PSy- and kernel-layer levels) in a language-agnostic form. A PSyIR may be constructed from scratch (in Python) or by processing existing source code using a frontend. Transformations act on the PSyIR and ultimately the generated code is produced by one of the PSyIR's backends.

15.1 PSyIR Nodes

The PSyIR consists of classes whose instances can be connected together to form a tree which represent computation in a language-independent way. These classes all inherit from the Node baseclass and, as a result, PSyIR instances are often referred to collectively as 'PSyIR nodes'.

At the present time PSyIR classes can be essentially split into two types. PSy-layer classes and Kernel-layer classes. PSy-layer classes make use of a `gen_code()` or an `update()` method to create Fortran code whereas Kernel-layer classes make use of PSyIR backends to create code.

Note: This separation will be removed in the future and eventually all PSyIR classes will make use of backends with the expectation that `gen_code()` and `update()` methods will be removed. Further this separation will be superseded by a separation between language-level PSyIR and domain-specific PSyIR.

15.1.1 PSy-layer nodes

PSy-layer PSyIR classes are primarily used to create the PSy-layer. These tend to be relatively descriptive and do not specify how a particular PSyclone frontend would implement them. With the exception of Loop, these classes are currently not compatible with the PSyIR backends. The generic (non-api-specific) PSy-layer PSyIR nodes are: InvokeSchedule, Directive, GlobalSum, HaloExchange, Loop and Kern. The Directive class is subclassed into many directives associated with OpenMP and OpenACC. The Kern class is subclassed into CodedKern, InlinedKern and BuiltinKern.

15.1.2 Kernel-layer nodes

Kernel-layer PSyIR classes are currently used to describe existing code in a language independent way. Consequently these nodes are more prescriptive and are independent of a particular PSyclone frontend. These nodes are designed to be used with PSyIR backends. Two PSy-layer classes (Loop and Schedule) can also be used as Kernel-layer classes. Additionally, the Schedule class is further subclassed into a Routine and then a kernel-layer KernelSchedule. In addition to KernelSchedule, Kernel-layer PSyIR nodes are: Loop, WhileLoop, IfBlock, CodeBlock, Assignment, Range, Reference, Operation, Literal, Call, Return and Container. The Reference class is further subclassed into ArrayReference, StructureReference and ArrayOfStructuresReference, the Operation class is further subclassed into UnaryOperation, BinaryOperation and NaryOperation and the Container class is further subclassed into FileContainer (representing a file that may contain more than one Container and/or Routine. Those nodes representing references to structures (derived types in Fortran) have a Member child node representing the member of the structure being accessed. The Member class is further subclassed into StructureMember (representing a member of a structure that is itself a structure), ArrayMember (a member of a structure that is an array of primitive types) and ArrayOfStructuresMember (a member of a structure this is itself an array of structures).

15.2 Node Descriptions

15.2.1 The Range node

```
class psyclone.psyir.nodes.Range(ast=None, children=None, parent=None, annotations=None)
```

The Range node is used to capture a range of integers via start, stop and step expressions. For example, start=2, stop=6 and step=2 indicates the values 2, 4 and 6.

At the moment the only valid use of Range in the PSyIR is to describe a set of accesses to an Array dimension (so-called array notation in Fortran). Therefore, the parent of a Range node should only be an Array node.

The Range node has three children nodes, the first child captures the start of the range, the second child captures the end of the range and the third captures the step within the range.

The nodes for each of the children must return an integer. Potentially valid nodes are therefore Literal, Reference, Operation and CodeBlock.

A common use case is to want to specify all the elements of a given array dimension without knowing the extent of that dimension. In the PSyIR this is achieved by using the LBOUND, and UBOUND binary operators:

```
>>> one = Literal("1", INTEGER_TYPE)
>>> # Declare a 1D real array called 'a' with 10 elements
>>> symbol = DataSymbol("a", ArrayType(REAL_TYPE, [10]))
>>> # Return the lower bound of the first dimension of array 'a'
>>> lbound = BinaryOperation.create(
    BinaryOperation.Operator.LBOUND,
    Reference(symbol), one.copy())
>>> # Return the upper bound of the first dimension of array 'a'
>>> ubound = BinaryOperation.create(
    BinaryOperation.Operator.UBOUND,
    Reference(symbol), one.copy())
>>> # Step defaults to 1 so no need to include it when creating range
>>> my_range = Range.create(lbound, ubound)
>>> # Create an access to all elements in the 1st dimension of array 'a'
>>> array_access = ArrayReference.create(symbol, [my_range])
```

In Fortran the above access array_access can be represented by a(:). The Fortran front-ends and back-ends are aware of array notation. Therefore the Fortran frontend is able to convert array notation to PSyIR and the Fortran

backend is able to convert PSyIR back to array notation.

static `create(start, stop, step=None)`

Create an internally-consistent Range object. If no step is provided then it defaults to an integer Literal with value 1.

Parameters

- `start` (`psyclone.psyir.nodes.Node`) – the PSyIR for the start value.
- `stop` (`psyclone.psyir.nodes.Node`) – the PSyIR for the stop value.
- `step` (`psyclone.psyir.nodes.Node` or `NoneType`) – the PSyIR for the increment/step or None.
- `parent` (`psyclone.psyir.nodes.Node` or `NoneType`) – the parent node of this Range in the PSyIR.

Returns

a fully-populated Range object.

Return type

`psyclone.psyir.nodes.ranges.Range`

property `start`

Checks that this Range is valid and then returns the PSyIR for the starting value of the range.

Returns

the starting value of this range.

Return type

`psyclone.psyir.nodes.Node`

property `step`

Checks that this Range is valid and then returns the step (increment) value/expression.

Returns

the increment used in this range.

Return type

`psyclone.psyir.nodes.Node`

property `stop`

Checks that this Range is valid and then returns the end value/expression.

Returns

the end value of this range.

Return type

`psyclone.psyir.nodes.Node`

15.3 Text Representation

When developing a transformation script it is often necessary to examine the structure of the PSyIR. All nodes in the PSyIR have the `view` method that writes a text-representation of that node and all of its descendants to `stdout`. If the `termcolor` package is installed (see [Getting Going](#)) then colour highlighting is used for this output. For instance, part of the Schedule constructed for the second NEMO [example](#) is rendered as:

```

6: If[]
    BinaryOperation[operator:'OR']
        BinaryOperation[operator:'AND']
            BinaryOperation[operator:'EQ']
                Reference[name:'kpass']
                Literal[value:'1']
            Reference[name:'ln_traldf_lap']
        BinaryOperation[operator:'AND']
            BinaryOperation[operator:'EQ']
                Reference[name:'kpass']
                Literal[value:'2']
            Reference[name:'ln_traldf_blp']
    Schedule[]
        0: If[annotations='was_single_stmt']
            Reference[name:'l_ptr']
            Schedule[]
                0: CodeBlock[[]<class 'fparser.two.Fortran2003.Call_Stmt'>]]
            1: If[annotations='was_single_stmt']
                Reference[name:'l_hst']
                Schedule[]
                    0: CodeBlock[[]<class 'fparser.two.Fortran2003.Call_Stmt'>]]
        7: Loop[type='levels', field_space='None', it_space='None']
            Literal[value:'1']
            Reference[name:'jpk']
            Literal[value:'1']
            Schedule[]
                0: NemoImplicitLoop[type='None', field_space='None', it_space='None']
        8: Loop[type='levels', field_space='None', it_space='None']
            Literal[value:'1']

```

Note that in this view, only those nodes which are children of Schedules have their indices shown. This means that nodes representing e.g. loop bounds or the conditional part of if statements are not indexed. For the example shown, the PSyIR node representing the `if(l_hst)` code would be reached by `schedule.children[6].if_body.children[1]` or, using the shorthand notation (see below), `schedule[6].if_body[1]` where `schedule` is the overall parent Schedule node (omitted from the above image).

One problem with the `view` method is that the output can become very large for big ASTs and is not readable for users unfamiliar with the PSyIR. An alternative to it is the `debug_string` method that generates a text representation with Fortran-like syntax but on which the high abstraction constructs have not yet been lowered to Fortran level and instead they will be embedded as `< node >` expressions.

15.4 Tree Navigation

Each PSyIR node provides several ways to navigate the AST:

The *children* and *parent* properties (available in all nodes) provide an homogeneous method to go up and down the tree hierarchy. This method is recommended when applying general operations or analysis to the tree, however, if one intends to navigate the tree in a way that depends on the type of node, the *children* and *parent* methods should be avoided. The structure of the tree may change in different versions of PSyclone and the encoded navigation won't be future-proof.

To solve this issue some Nodes also provide methods for semantic navigation:

- *Schedule*:
subscript operator for indexing the statements (children) inside the Schedule, e.g. `sched[3]` or `sched[2:4]`.

- Assignment:

Assignment.lhs()

Returns

the child node representing the Left-Hand Side of the assignment.

Return type

psyclone.psyir.nodes.Node

Raises

InternalError – Node has fewer children than expected.

Assignment.rhs()

Returns

the child node representing the Right-Hand Side of the assignment.

Return type

psyclone.psyir.nodes.Node

Raises

InternalError – Node has fewer children than expected.

- IfBlock:

IfBlock.condition()

Return the PSyIR Node representing the conditional expression of this IfBlock.

Returns

IfBlock conditional expression.

Return type

psyclone.psyir.nodes.Node

Raises

InternalError – If the IfBlock node does not have the correct number of children.

IfBlock.if_body()

Return the Schedule executed when the IfBlock evaluates to True.

Returns

Schedule to be executed when IfBlock evaluates to True.

Return type

psyclone.psyir.nodes.Schedule

Raises

InternalError – If the IfBlock node does not have the correct number of children.

IfBlock.else_body()

If available return the Schedule executed when the IfBlock evaluates to False, otherwise return None.

Returns

Schedule to be executed when IfBlock evaluates to False, if it doesn't exist returns None.

Return type

psyclone.psyir.nodes.Schedule or NoneType

- Loop:

Loop.loop_body()

Returns

the PSyIR Schedule with the loop body statements.

Return type

psyclone.psyir.nodes.Schedule

- WhileLoop:

WhileLoop.condition()

Return the PSyIR Node representing the conditional expression of this WhileLoop.

Returns

WhileLoop conditional expression.

Return type

psyclone.psyir.nodes.Node

Raises

InternalError – If the WhileLoop node does not have the correct number of children.

WhileLoop.loop_body()

Return the Schedule executed when the WhileLoop condition is True.

Returns

Schedule to be executed when WhileLoop condition is True.

Return type

psyclone.psyir.nodes.Schedule

Raises

InternalError – If the WhileLoop node does not have the correct number of children.

- Array **nodes** (e.g. ArrayReference, ArrayOfStructuresReference):

ArrayReference.indices()

Supports semantic-navigation by returning the list of nodes representing the index expressions for this array reference.

Returns

the PSyIR nodes representing the array-index expressions.

Return type

list of psyclone.psyir.nodes.Node

Raises

InternalError – if this node has no children or if they are not valid array-index expressions.

- RegionDirective:

RegionDirective.dir_body()

Returns

the Schedule associated with this directive.

Return type

psyclone.psyir.nodes.Schedule

Raises

InternalError – if this node does not have a Schedule as its first child.

RegionDirective.clauses()

Returns

the Clauses associated with this directive.

Return type

List of psyclone.psyir.nodes.Clause

- **Nodes representing accesses of data within a structure** (e.g. StructureReference, StructureMember):

StructureReference.member()

Returns

the member of the structure that this reference is to.

Return type

psyclone.psyir.nodes.Member

Raises

InternalError – if the first child of this node is not an instance of Member.

These are the recommended methods to navigate the tree for analysis or operations that depend on the Node type.

Additionally, the *walk* method (available in all nodes) is able to recurse through the tree and return objects of a given type. This is useful when the objective is to move down the tree to a specific node or list of nodes without information

about the exact location.

`Node.walk(my_type, stop_type=None)`

Recurse through the PSyIR tree and return all objects that are an instance of ‘my_type’, which is either a single class or a tuple of classes. In the latter case all nodes are returned that are instances of any classes in the tuple. The recursion into the tree is stopped if an instance of ‘stop_type’ (which is either a single class or a tuple of classes) is found. This can be used to avoid analysing e.g. inlined kernels, or as performance optimisation to reduce the number of recursive calls.

Parameters

- my_type (`type` | `Tuple[type, ...]`) – the class(es) for which the instances are collected.
- stop_type (`Optional[type | Tuple[type, ...]]`) – class(es) at which recursion is halted (optional).

Returns

list with all nodes that are instances of my_type starting at and including this node.

Return type

`List[psyclone.psyir.nodes.Node]`

Finally, all nodes also provide the *ancestor* method which may be used to recurse back up the tree from a given node in order to find a node of a particular type:

`Node.ancestor(my_type, excluding=None, include_self=False, limit=None, shared_with=None)`

Search back up the tree and check whether this node has an ancestor that is an instance of the supplied type. If it does then we return it otherwise we return None. An individual (or tuple of) (sub-) class(es) to ignore may be provided via the *excluding* argument. If *include_self* is True then the current node is included in the search. If *limit* is provided then the search ceases if/when the supplied node is encountered. If *shared_with* is provided, then the ancestor search will find an ancestor of both this node and the node provided as *shared_with* if such an ancestor exists.

Parameters

- my_type (`type` | `Tuple[type, ...]`) – class(es) to search for.
- excluding (`Optional[type | Tuple[type, ...]]`) – (sub-)class(es) to ignore or None.
- include_self (`bool`) – whether or not to include this node in the search.
- limit (`Optional[psyclone.psyir.nodes.Node]`) – an optional node at which to stop the search.
- shared_with (`Optional[psyclone.psyir.nodes.Node]`) – an optional node which must also have the found node as an ancestor.

Returns

First ancestor Node that is an instance of any of the requested classes or None if not found.

Return type

`Optional[psyclone.psyir.nodes.Node]`

Raises

- `TypeError` – if *excluding* is provided but is not a type or tuple of types.
- `TypeError` – if *limit* is provided but is not an instance of Node.

15.5 DataTypes

The PSyIR supports the following datatypes: `ScalarType`, `ArrayType`, `StructureType`, `DeferredType`, `UnknownType` and `NoType`. These datatypes are used when creating instances of `DataSymbol`, `RoutineSymbol` and `Literal` (although note that `NoType` may only be used with a `RoutineSymbol`). `DeferredType` and `UnknownType` are both used when processing existing code. The former is used when a symbol is being imported from some other scope (e.g. via a `USE` statement in Fortran) that hasn't yet been resolved and the latter is used when an unsupported form of declaration is encountered.

More information on each of these various datatypes is given in the following subsections.

15.5.1 Scalar DataType

A Scalar datatype consists of an intrinsic and a precision.

The intrinsic can be one of `INTEGER`, `REAL`, `BOOLEAN` and `CHARACTER`.

The precision can be `UNDEFINED`, `SINGLE`, `DOUBLE`, an integer value specifying the precision in bytes, or a `datasymbol` (see Section [Symbols and Symbol Tables](#)) that contains precision information. Note that `UNDEFINED`, `SINGLE` and `DOUBLE` allow the precision to be set by the system so may be different for different architectures. For example:

```
>>> char_type = ScalarType(ScalarType.Intrinsic.CHARACTER,
...                         ScalarType.Precision.UNDEFINED)
>>> int_type = ScalarType(ScalarType.Intrinsic.INTEGER,
...                       ScalarType.Precision.SINGLE)
>>> bool_type = ScalarType(ScalarType.Intrinsic.BOOLEAN, 4)
>>> symbol = DataSymbol("rdef", int_type, constant_value=4)
>>> scalar_type = ScalarType(ScalarType.Intrinsic.REAL, symbol)
```

For convenience PSyclone predefines a number of scalar datatypes:

`REAL_TYPE`, `INTEGER_TYPE`, `BOOLEAN_TYPE` and `CHARACTER_TYPE` all have precision set to `UNDEFINED`;

`REAL_SINGLE_TYPE`, `REAL_DOUBLE_TYPE`, `INTEGER_SINGLE_TYPE` and `INTEGER_DOUBLE_TYPE`;

`REAL4_TYPE`, `REAL8_TYPE`, `INTEGER4_TYPE` and `INTEGER8_TYPE`.

15.5.2 Array DataType

An Array datatype itself has another datatype (or `DataTypeSymbol`) specifying the type of its elements and a shape. The shape can have an arbitrary number of dimensions. Each dimension captures what is known about its extent. It is necessary to distinguish between four cases:

Description	Entry in shape list
An array has a static extent known at compile time.	<code>ArrayType.ArrayBounds</code> containing integer <code>Literal</code> values
An array has an extent defined by another symbol or (constant) PSyIR expression.	<code>ArrayType.ArrayBounds</code> containing <code>Reference</code> or <code>Operation</code> nodes
An array has a definite extent which is not known at compile time but can be queried at runtime.	<code>ArrayType.Extent.ATTRIBUTE</code>
It is not known whether an array has memory allocated to it in the current scoping unit.	<code>ArrayType.Extent.DEFERRED</code>

where `ArrayType.ArrayBounds` is a namedtuple with lower and upper members holding the lower- and upper-bounds of the extent of a given array dimension.

The distinction between the last two cases is that in the former the extents are known but are kept internally with the array (for example an assumed shape array in Fortran) and in the latter the array has not yet been allocated any memory (for example the declaration of an allocatable array in Fortran) so the extents may have not been defined yet.

For example:

```
>>> array_type = ArrayType(REAL4_TYPE, [5, 10])

>>> n_var = DataSymbol("n", INTEGER_TYPE)
>>> array_type = ArrayType(INTEGER_TYPE, [Reference(n_var),
...                                     Reference(n_var)])

>>> array_type = ArrayType(REAL8_TYPE, [ArrayType.Extent.ATTRIBUTE,
...                                     ArrayType.Extent.ATTRIBUTE])

>>> array_type = ArrayType(BOOLEAN_TYPE, [ArrayType.Extent.DEFERRED])
```

15.5.3 Structure Datatype

A Structure datatype consists of a dictionary of components where the name of each component is used as the corresponding key. Each component is stored as a named tuple with name, datatype and visibility members.

For example:

```
# Shorthand for a scalar type with REAL_KIND precision
SCALAR_TYPE = ScalarType(ScalarType.Intrinsic.REAL, REAL_KIND)

# Structure-type definition
GRID_TYPE = StructureType.create([
    ("dx", SCALAR_TYPE, Symbol.Visibility.PUBLIC),
    ("dy", SCALAR_TYPE, Symbol.Visibility.PUBLIC)])

GRID_TYPE_SYMBOL = DataTypeSymbol("grid_type", GRID_TYPE)

# A structure-type containing other structure types
FIELD_TYPE_DEF = StructureType.create(
    [("data", ArrayType(SCALAR_TYPE, [10]), Symbol.Visibility.PUBLIC),
     ("grid", GRID_TYPE_SYMBOL, Symbol.Visibility.PUBLIC),
     ("sub_meshes", ArrayType(GRID_TYPE_SYMBOL, [3]),
      Symbol.Visibility.PUBLIC),
     ("flag", INTEGER4_TYPE, Symbol.Visibility.PUBLIC)])
```

15.5.4 Unknown DataType

If a PSyIR frontend encounters an unsupported declaration then the corresponding Symbol is given `UnknownType`. The text of the original declaration is stored in the type object and is available via the `declaration` property.

15.5.5 NoType

NoType represents the empty type, equivalent to void in C. It is currently only used to describe a RoutineSymbol that has no return type (such as a Fortran subroutine).

15.6 Symbols and Symbol Tables

Some PSyIR nodes have an associated Symbol Table (*psyclone.psyir.symbols.SymbolTable*) which keeps a record of the Symbols (*psyclone.psyir.symbols.Symbol*) specified and used within them.

Symbol Tables can be nested (i.e. a node with an attached symbol table can be an ancestor or descendent of a node with an attached symbol table). If the same symbol name is used in a hierarchy of symbol tables then the symbol within the symbol table attached to the closest ancestor node is in scope. By default, symbol tables are aware of other symbol tables and will return information about relevant symbols from all symbol tables.

The SymbolTable has the following interface:

```
class psyclone.psyir.symbols.SymbolTable(node=None, default_visibility=Visibility.PUBLIC)
```

Encapsulates the symbol table and provides methods to add new symbols and look up existing symbols. Nested scopes are supported and, by default, the add and lookup methods take any ancestor symbol tables into consideration (ones attached to nodes that are ancestors of the node that this symbol table is attached to). If the default visibility is not specified then it defaults to `Symbol.Visibility.PUBLIC`.

Parameters

- *node* (*psyclone.psyir.nodes.Schedule*, *psyclone.psyir.nodes.Container* or *NoneType*) – reference to the Schedule or Container to which this symbol table belongs.
- *default_visibility* – optional default visibility value for this symbol table, if not provided it defaults to `PUBLIC` visibility.

Raises

`TypeError` – if *node* argument is not a Schedule or a Container.

Where each element is a Symbol with an immutable name:

```
class psyclone.psyir.symbols.Symbol(name, visibility=Visibility.PUBLIC, interface=None)
```

Generic Symbol item for the Symbol Table and PSyIR References. It has an immutable name label because it must always match with the key in the SymbolTable. If the symbol is private then it is only visible to those nodes that are descendants of the Node to which its containing Symbol Table belongs.

Parameters

- *name* (*str*) – name of the symbol.
- *visibility* (*psyclone.psyir.symbols.Symbol.Visibility*) – the visibility of the symbol.
- *interface* (*Optional[psyclone.psyir.symbols.symbol.SymbolInterface]*) – optional object describing the interface to this symbol (i.e. whether it is passed as a routine argument or accessed in some other way). Defaults to `psyclone.psyir.symbolsAutomaticInterface`

Raises

`TypeError` – if the *name* is not a *str*.

There are several Symbol sub-classes to represent different labeled entities in the PSyIR. At the moment the available symbols are:

- class `psyclone.psyir.symbols.ContainerSymbol(name, wildcard_import=False, **kwargs)`

Symbol that represents a reference to a Container. The reference is lazy evaluated, this means that the Symbol will be created without parsing and importing the referenced container, but this can be imported when needed.

Parameters

- name (`str`) – name of the symbol.
- wildcard_import (`bool`) – if all public Symbols of the Container are imported into the current scope. Defaults to False.
- kwargs (unwrapped dict.) – additional keyword arguments provided by `psyclone.psyir.symbols.Symbol`.

- class `psyclone.psyir.symbols.DataSymbol(name, datatype, constant_value=None, **kwargs)`

Symbol identifying a data element. It contains information about: the datatype, the shape (in column-major order) and the interface to that symbol (i.e. Local, Global, Argument).

Parameters

- name (`str`) – name of the symbol.
- datatype (`psyclone.psyir.symbols.DataType`) – data type of the symbol.
- constant_value (`NoneType`, item of `TYPE_MAP_TO_PYTHON` or `psyclone.psyir.nodes.Node`) – sets a fixed known expression as a permanent value for this `DataSymbol`. If the value is `None` then this symbol does not have a fixed constant. Otherwise it can receive PSyIR expressions or Python intrinsic types available in the `TYPE_MAP_TO_PYTHON` map. By default it is `None`.
- kwargs (unwrapped dict.) – additional keyword arguments provided by `psyclone.psyir.symbols.TypedSymbol`

- class `psyclone.psyir.symbols.DataTypeSymbol(name, datatype, visibility=Visibility.PUBLIC, interface=None)`

Symbol identifying a user-defined type (e.g. a derived type in Fortran).

Parameters

- name (`str`) – the name of this symbol.
- datatype (`psyclone.psyir.symbols.DataType`) – the type represented by this symbol.
- visibility (`psyclone.psyir.symbols.Symbol.Visibility`) – the visibility of this symbol.
- interface (`psyclone.psyir.symbols.SymbolInterface`) – the interface to this symbol.

- class `psyclone.psyir.symbols.IntrinsicSymbol(name, datatype=None, **kwargs)`

Symbol identifying a callable intrinsic routine.

Parameters

- name (`str`) – name of the symbol.
- datatype (`psyclone.psyir.symbols.DataType`) – data type of the symbol. Default to `NoType()`.
- kwargs (unwrapped dict.) – additional keyword arguments provided by `psyclone.psyir.symbols.TypedSymbol`

- class `psyclone.psyir.symbols.RoutineSymbol(name, datatype=None, **kwargs)`
Symbol identifying a callable routine.

Parameters

- name (`str`) – name of the symbol.
- datatype (`psyclone.psyir.symbols.DataType`) – data type of the symbol. Default to `NoType()`.
- kwargs (unwrapped dict.) – additional keyword arguments provided by `psyclone.psyir.symbols.TypedSymbol`

See the reference guide for the full API documentation of the [SymbolTable](#) and the [Symbol](#) types.

15.6.1 Symbol Interfaces

Each symbol has a Symbol Interface with the information about how the variable data is provided into the local context. The currently available Interfaces are:

- class `psyclone.psyir.symbolsAutomaticInterface`
The symbol is declared without attributes. Its data will live during the local context.
- class `psyclone.psyir.symbols.DefaultModuleInterface`
The symbol contains data declared in a module scope without additional attributes.
- class `psyclone.psyir.symbols.ImportInterface(container_symbol, orig_name=None)`
Describes the interface to a Symbol that is imported from an external PSyIR container. The symbol can be renamed on import and, if so, its original name in the Container is specified using the optional 'orig_name' argument.

Parameters

- container_symbol (`psyclone.psyir.symbols.ContainerSymbol`) – symbol representing the external container from which the symbol is imported.
- orig_name (Optional[`str`]) – the name of the symbol in the external container before it is renamed, or `None` (the default) if it is not renamed.

Raises

[TypeError](#) – if the `orig_name` argument is an unexpected type.

- class `psyclone.psyir.symbols.ArgumentInterface(access=None)`
Captures the interface to a Symbol that is accessed as a routine argument.

Parameters

access (`psyclone.psyir.symbols.ArgumentInterface.Access`) – specifies how the argument is used in the Schedule

- class `psyclone.psyir.symbols.StaticInterface`
The symbol contains data that is kept alive through the execution of the program.
- class `psyclone.psyir.symbols.CommonBlockInterface`
A symbol declared in the local scope but acts as a global that can be accessed by any scope referencing the same `CommonBlock` name.
- class `psyclone.psyir.symbols.UnresolvedInterface`
We have a symbol but we don't know where it is declared.

- class `psyclone.psyir.symbols.UnknownInterface`

We have a symbol with a declaration but PSyclone does not support its attributes.

15.7 Creating PSyIR

15.7.1 Symbol names

PSyIR symbol names can be specified by a user. For example:

```
var_name = "my_name"
symbol_table = SymbolTable()
data = DataSymbol(var_name, REAL_TYPE)
symbol_table.add(data)
reference = Reference(data)
```

However, the `SymbolTable.add()` method will raise an exception if a user tries to add a symbol with the same name as a symbol already existing in the symbol table.

Alternatively, the `SymbolTable` also provides the `new_symbol()` method (see Section [Symbols and Symbol Tables](#) for more details) that uses a new distinct name from any existing names in the symbol table. By default the generated name is the value `PSYIR_ROOT_NAME` variable specified in the `DEFAULT` section of the PSyclone config file, followed by an optional “_” and an integer. For example, the following code:

```
from psyclone.psyir.symbols import SymbolTable
symbol_table = SymbolTable()
for i in range(0, 3):
    var_name = symbol_table.new_symbol().name
    print(var_name)
```

gives the following output:

```
psyir_tmp
psyir_tmp_0
psyir_tmp_1
```

As the root name (`psyir_tmp` in the example above) is specified in PSyclone’s config file it can be set to whatever the user wants.

Note: The particular format used to create a unique name is the responsibility of the `SymbolTable` class and may change in the future.

A user might want to create a name that has some meaning in the context in which it is used e.g. `idx` for an index, `i` for an iterator, or `temp` for a temperature field. To support more readable names, the `new_symbol()` method allows the user to specify a root name as an argument to the method which then takes the place of the default root name. For example, the following code:

```
from psyclone.psyir.symbols import SymbolTable
symbol_table = SymbolTable()
for i in range(0, 3):
    var_name = symbol_table.new_symbol(root_name="something")
    print(var_name)
```

gives the following output:

```
something
something_0
something_1
```

By default, `new_symbol()` creates generic symbols, but often the user will want to specify a `Symbol` subclass with some given parameters. The `new_symbol()` method accepts a `symbol_type` parameter to specify the subclass. Arguments for the constructor of that subclass may be supplied as keyword arguments. For example, the following code:

```
from psyclone.psyir.symbols import SymbolTable, DataSymbol, REAL_TYPE
symbol_table = SymbolTable()
symbol_table.new_symbol(root_name="something",
                        symbol_type=DataSymbol,
                        datatype=REAL_TYPE,
                        constant_value=3)
```

declares a symbol named “something” of `REAL_TYPE` datatype where the `constant_value` argument will be passed to the `DataSymbol` constructor.

An example of using the `new_symbol()` method can be found in the PSyclone `examples/psyir` directory.

15.7.2 Nodes

PSyIR nodes are connected together via parent and child methods provided by the `Node` baseclass.

These nodes can be created in isolation and then connected together. For example:

```
assignment = Assignment()
literal = Literal("0.0", REAL_TYPE)
reference = Reference(symbol)
assignment.children = [reference, literal]
```

However, as connections get more complicated, creating the correct connections can become difficult to manage and error prone. Further, in some cases children must be collected together within a `Schedule` (e.g. for `IfBlock`, `Loop` and `WhileLoop`).

To simplify this complexity, each of the Kernel-layer nodes which contain other nodes have a static `create` method which helps construct the PSyIR using a bottom up approach. Using this method, the above example then becomes:

```
literal = Literal("0.0", REAL_TYPE)
reference = Reference(symbol)
assignment = Assignment.create(reference, literal)
```

Creating the PSyIR to represent a complicated access of a member of a structure is best performed using the `create()` method of the appropriate `Reference` subclass. For a relatively straightforward access such as (the Fortran) `field1%region%nx`, this would be:

```
from psyclone.psyir.nodes import StructureReference
fld_sym = symbol_table.lookup("field1")
ref = StructureReference.create(fld_sym, ["region", "nx"])
```

where `symbol_table` is assumed to be a pre-populated `Symbol Table` containing an entry for “field1”.

A more complicated access involving arrays of structures such as `field1%sub_grids(idx, 1)%nx` would be constructed as:

```

from psyclone.psyir.symbols import INTEGER_TYPE
from psyclone.psyir.nodes import StructureReference, Reference, Literal
idx_sym = symbol_table.lookup("idx")
fld_sym = symbol_table.lookup("field1")
ref = StructureReference.create(fld_sym,
    [("sub_grids", [Reference(idx_sym), Literal("1", INTEGER_TYPE)]),
     "nx"])

```

Note that the list of quantities passed to the `create()` method now contains a 2-tuple in order to describe the array access.

More examples of using this approach can be found in the PSyclone `examples/psyir` directory.

15.8 Comparing PSyIR nodes

The `==` (equality) operator for PSyIR nodes performs a specialised equality check to compare the value of each node. This is also useful when comparing entire subtrees since the equality operator automatically recurses through the children and compares each child with the appropriate equality semantics, e.g.

```

# Is the loop upper bound expression exactly the same?
if loop1.stop_expr == loop2.stop_expr:
    print("Same upper bound!")

```

The equality operator will handle expressions like `my_array%my_field(:3)` with the derived type fields and the range components automatically, but it cannot handle symbolically equivalent fields, i.e. `my_array%my_field(:3) != my_array%my_field(:2+1)`.

Annotations and code comments are ignored in the equality comparison since they don't alter the semantic meaning of the code. So these two statements compare to `True`:

```

a = a + 1
a = a + 1 !Increases a by 1

```

Sometimes there are cases where one really means to check for the specific instance of a node. In this case, Python provides the `is` operator, e.g.

```

# Is the self instance part of this routine?
is_here = any(node is self for node in routine.walk(Node))

```

Additionally, PSyIR nodes cannot be used as map keys or similar. The easiest way to do this is just use the `id` as the key:

```

node_map = {}
node_map[id(mynode)] = "element"

```

15.9 Modifying the PSyIR

Once we have a complete PSyIR AST there are 2 ways to modify its contents and/or structure: by applying transformations (see next section *Transformations*), or by direct PSyIR API methods. This section describes some of the methods that the PSyIR classes provide to modify the PSyIR AST in a consistent way (e.g. without breaking its many internal references). Some complete examples of modifying the PSyIR can be found in the PSyclone `examples/psyir/modify.py` script.

The rest of this section introduces examples of the available direct PSyIR modification methods.

15.9.1 Renaming symbols

The symbol table provides the method `rename_symbol()` that given a symbol and an unused name will rename the symbol. The symbol renaming will affect all the references in the PSyIR AST to that symbol. For example, the PSyIR representing the following Fortran code:

```
subroutine work(psyir_tmp)
  real, intent(inout) :: psyir_tmp
  psyir_tmp=0.0
end subroutine
```

could be modified by the following PSyIR statements:

```
symbol = symbol_table.lookup("psyir_tmp")
symbol_table.rename_symbol(tmp_symbol, "new_variable")
```

which would result in the following Fortran output code:

```
subroutine work(new_variable)
  real, intent(inout) :: new_variable
  new_variable=0.0
end subroutine
```

15.9.2 Specialising symbols

The Symbol class provides the method `specialise()` that given a subclass of Symbol will change the Symbol instance to the specified subclass. If the subclass has any additional properties then these would need to be set explicitly.

```
symbol = Symbol("name")
symbol.specialise(RoutineSymbol)
# Symbol is now a RoutineSymbol
```

This method is useful as it allows the class of a symbol to be changed without affecting any references to it.

15.9.3 Replacing PSyIR nodes

In certain cases one might want to replace a node in a PSyIR tree with another node. All nodes provide the *replace_with()* method to replace the node and its descendants with another given node and its descendants.

```
node.replace_with(new_node)
```

When the node being replaced is part of a named context (in Calls or Operations) the name of the argument is conserved by default. For example

```
call named_subroutine(name1=1)
```

```
call.children[0].replace_with(Literal('2', INTEGER_TYPE))
```

will become:

```
call named_subroutine(name1=2)
```

This behaviour can be changed with the *keep_name_in_context* parameter.

```
call.children[0].replace_with(
    Literal('3', INTEGER_TYPE),
    keep_name_in_context=False
)
```

will become:

```
call named_subroutine(3)
```

15.9.4 Detaching PSyIR nodes

Sometimes we just may wish to detach a certain PSyIR subtree in order to remove it from the root tree but we don't want to delete it altogether, as it may be re-inserted again in another location. To achieve this, all nodes provide the *detach* method:

```
tmp = node.detach()
```

15.9.5 Copying nodes

Copying a PSyIR node and its children is often useful in order to avoid repeating the creation of similar PSyIR subtrees. The result of the copy allows the modification of the original and the copied subtrees independently, without altering the other subtree. Note that this is not equivalent to the Python *copy* or *deepcopy* functionality provided in the *copy* library. This method performs a bespoke copy operation where some components of the tree, like children, are recursively copied, while others, like the top-level parent reference are not.

```
new_node = node.copy()
```

15.9.6 Named arguments

The *Call* and three sub-classes of *Operation* node (*UnaryOperation*, *BinaryOperation* and *NaryOperation*) all support named arguments.

Named arguments can be set or modified via the *create()*, *append_named_arg()*, *insert_named_arg()* or *replace_named_arg()* methods.

If an argument is inserted directly (via the children list) then it is assumed that this is not a named argument. If the top node of an argument is replaced by removing and inserting a new node then it is assumed that this argument is no longer a named argument. If it is replaced with the *replace_with* method, it has a *keep_name_in_context* argument to choose the desired behaviour (defaults to True). If arguments are re-ordered then the names follow the re-ordering.

The names of named arguments can be accessed via the *argument_names* property. This list has an entry for each argument and either contains a name or None (if this is not a named argument).

The PSyIR does not constrain which arguments are specified as being named and what those names are. It is the developer's responsibility to make sure that these names are consistent with any intrinsics that will be generated by the back-end. In the future, it is expected that the PSyIR will know about the number and type of arguments expected by Operation nodes, beyond simply being unary, binary or nary.

One restriction that Fortran has (but the PSyIR does not) is that all named arguments should be at the end of the argument list. If this is not the case then the Fortran backend writer will raise an exception.

TRANSFORMATIONS

As discussed in the previous section, transformations can be applied to PSyclone's internal representation (PSyIR) to modify it. Typically transformations will be used to optimise the Algorithm, PSy and/or Kernel layer(s) for a particular architecture, however transformations could be added for other reasons, such as to aid debugging or for performance monitoring.

16.1 Finding

Transformations can be imported directly, but the user needs to know what transformations are available. A helper class **TransInfo** is provided to show the available transformations

Note: The directory layout of PSyclone is currently being restructured. As a result of this some transformations are already in the new locations, while others have not been moved yet. Transformations in the new locations can at the moment not be found using the **TransInfo** approach, and need to be imported directly from the path indicated in the documentation.

```
class psyclone.psyGen.TransInfo(module=None, base_class=None)
```

This class provides information about, and access, to the available transformations in this implementation of PSyclone. New transformations will be picked up automatically as long as they subclass the abstract Transformation class.

For example:

```
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> print(t.list)
There is 1 transformation available:
  1: SwapTrans, A test transformation
>>> # accessing a transformation by index
>>> trans = t.get_trans_num(1)
>>> # accessing a transformation by name
>>> trans = t.get_trans_name("SwapTrans")
```

```
get_trans_name(name)
```

return the transformation with this name (use list() first to see available transformations)

```
get_trans_num(number)
```

return the transformation with this number (use list() first to see available transformations)

property list
 return a string with a human readable list of the available transformations

property num_trans
 return the number of transformations available

16.2 Standard Functionality

Each transformation must provide at least two functions for the user: one for validation, i.e. to verify that a certain transformation can be applied, and one to actually apply the transformation. They are described in detail in the [overview of all transformations](#), but the following general guidelines apply.

16.2.1 Validation

Each transformation provides a function `validate`. This function can be called by the user, and it will raise an exception if the transformation can not be applied (and otherwise will return nothing). Validation will always be called when a transformation is applied. The parameters for `validate` can change from transformation to transformation, but each `validate` function accepts a parameter `options`. This parameter is either `None`, or a dictionary of string keys, that will provide additional parameters to the validation process. For example, some validation functions allow part of the validation process to be disabled in order to allow the HPC expert to apply a transformation that they know to be safe, even if the more general validation process might reject it. Those parameters are documented for each transformation, and will show up as a parameter, e.g.: `options["node-type-check"]`. As a simple example:

```
# The validation might reject the application, but in this
# specific case it is safe to apply the transformation,
# so disable the node type check:
my_transform.validate(node, {"node-type-check": False})
```

16.2.2 Application

Each transformation provides a function `apply` which will apply the transformation. It will first validate the transform by calling the `validate` function. Each `apply` function takes the same `options` parameter as the `validate` function described above. Besides potentially modifying the validation process, optional parameters for the transformation are also provided this way. A simple example:

```
kctrans = Dynamo0p3KernelConstTrans()
kctrans.apply(kernel, {"element_order": 0, "quadrature": True})
```

The same `options` dictionary will be used when calling `validate`.

16.3 Available transformations

Some transformations are generic as the schedule structure is independent of the API, however it often makes sense to specialise these for a particular API by adding API-specific errors checks. Some transformations are API-specific. Currently these different types of transformation are indicated by their names.

The generic transformations currently available are listed in alphabetical order below (a number of these have specialisations which can be found in the API-specific sections).

Note: PSyclone currently only supports OpenCL and KernelImportsToArguments transformations for the GOcean 1.0 API, the OpenACC Data transformation is limited to the NEMO and GOcean 1.0 APIs and the OpenACC Kernels transformation is limited to the NEMO and LFRic (Dynamo0.3) APIs.

Note: The directory layout of PSyclone is currently being restructured. As a result of this some transformations are already in the new locations, while others have not been moved yet.

class psyclone.psyir.transformations.Abs2CodeTrans

Provides a transformation from a PSyIR ABS Operator node to equivalent code in a PSyIR tree. Validity checks are also performed.

The transformation replaces

$$R = \text{ABS}(X)$$

with the following logic:

```
IF X < 0.0:
    R = X*-1.0
ELSE:
    R = X
```

apply(*node*, *options=None*)

Apply the ABS intrinsic conversion transformation to the specified node. This node must be an ABS UnaryOperation. The ABS UnaryOperation is converted to equivalent inline code. This is implemented as a PSyIR transform from:

$$R = \dots \text{ABS}(X) \dots$$

to:

```
tmp_abs = X
if tmp_abs < 0.0:
    res_abs = tmp_abs*-1.0
else:
    res_abs = tmp_abs
R = ... res_abs ...
```

where X could be an arbitrarily complex PSyIR expression and ... could be arbitrary PSyIR code.

This transformation requires the operation node to be a descendent of an assignment and will raise an exception if this is not the case.

Parameters

- node (psyclone.psyir.nodes.UnaryOperation) – an ABS UnaryOperation node.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Warning: This transformation assumes that the ABS Operator acts on PSyIR Real scalar data and does not check that this is not the case. Once issue #658 is on master then this limitation can be fixed.

class `psyclone.transformations.ACCEnterDataTrans`

Add an OpenACC data region around a list of nodes in the PSyIR. COPYIN, COPYOUT and COPY clauses are added as required.

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> ast, invokeInfo = parse(NEMO_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCKernelsTrans, ACCDataTrans
>>> ktrans = ACCKernelsTrans()
>>> dtrans = ACCDataTrans()
>>>
>>> schedule = psy.invokes.get('tra_adv').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Add a kernels construct for execution on the device
>>> kernels = schedule.children[9]
>>> ktrans.apply(kernels)
>>>
>>> # Enclose the kernels in a data construct
>>> kernels = schedule.children[9]
>>> dtrans.apply(kernels)
```

`apply(node, options=None)`

Put the supplied node or list of nodes within an OpenACC data region.

Parameters

- `node` ((list of) `psyclone.psyir.nodes.Node`) – the PSyIR node(s) to enclose in the data region.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

class `psyclone.transformations.ACCEnterDataTrans`

Adds an OpenACC “enter data” directive to a Schedule. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCEnterDataTrans, ACCLoopTrans,
↪ACCPParallelTrans
>>> dtrans = ACCEnterDataTrans()
>>> ltrans = ACCLoopTrans()
```

(continues on next page)

(continued from previous page)

```

>>> ptrans = ACCParallelTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenACC Loop transformation to *every* loop in the schedule
>>> for child in schedule.children[:]:
...     ltrans.apply(child)
>>>
>>> # Enclose all of these loops within a single OpenACC parallel region
>>> ptrans.apply(schedule)
>>>
>>> # Add an enter data directive
>>> dtrans.apply(schedule)
>>>
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())

```

`apply(sched, options=None)`

Adds an OpenACC “enter data” directive to the invoke associated with the supplied Schedule. Any fields accessed by OpenACC kernels within this schedule will be added to this data region in order to ensure they remain on the target device.

Parameters

- `sched` (sub-class of `psyclone.psyir.nodes.Schedule`) – schedule to which to add an “enter data” directive.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

`class psyclone.transformations.ACCKernelsTrans`

Enclose a sub-set of nodes from a Schedule within an OpenACC kernels region (i.e. within “!\$acc kernels” ... “!\$acc end kernels” directives).

For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> ast, invokeInfo = parse(NEMO_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCKernelsTrans
>>> ktrans = ACCKernelsTrans()
>>>
>>> schedule = psy.invokes.get('tra_adv').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>> kernels = schedule.children[9]
>>> # Transform the kernel
>>> ktrans.apply(kernels)

```

`apply(node, options=None)`

Enclose the supplied list of PSyIR nodes within an OpenACC Kernels region.

Parameters

- `node` ((a list of) `psyclone.psyir.nodes.Node`) – a node or list of nodes in the PSyIR to enclose.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- `options["default_present"]` (bool) – whether or not the kernels region should have the ‘default present’ attribute (indicating that data is already on the accelerator). When using managed memory this option should be False.

`class psyclone.transformations.ACCLoopTrans`

Adds an OpenACC loop directive to a loop. This directive must be within the scope of some OpenACC Parallel region (at code-generation time).

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.parse.utils import ParseError
>>> from psyclone.psyGen import PSyFactory
>>> from psyclone.errors import GenerationError
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> ltrans = t.get_trans_name('ACCLoopTrans')
>>> rtrans = t.get_trans_name('ACCParellTrans')
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenACC Loop transformation to *every* loop in the schedule
>>> for child in schedule.children[:]:
...     ltrans.apply(child)
>>>
>>> # Enclose all of these loops within a single OpenACC parallel region
>>> rtrans.apply(schedule)
>>>
```

`apply(node, options=None)`

Apply the ACCLoop transformation to the specified node. This node must be a Loop since this transformation corresponds to inserting a directive immediately before a loop, e.g.:

```
!$ACC LOOP
do ...
...
end do
```

At code-generation time (when `psyclone.psyir.nodes.ACCLoopDirective.gen_code()` is called), this node must be within (i.e. a child of) a `PARALLEL` region.

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – the supplied node to which we will apply the Loop transformation.
 - `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
 - `options["collapse"]` (`int`) – number of nested loops to collapse.
 - `options["independent"]` (`bool`) – whether to add the “independent” clause to the directive (not strictly necessary within `PARALLEL` regions).
-

`class psyclone.transformations.ACCParallelTrans`

Create an OpenACC parallel region by inserting directives. This parallel region *must* come after an enter-data directive (see `ACCEnterDataTrans`) or within a data region (see `ACCDDataTrans`). For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> ptrans = t.get_trans_name('ACCParallelTrans')
>>> dtrans = t.get_trans_name('ACCDDataTrans')
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Enclose everything within a single OpenACC PARALLEL region
>>> ptrans.apply(schedule.children)
>>> # Add an enter-data directive
>>> dtrans.apply(schedule)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(target_nodes, options=None)`

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Loops in the schedule within a single parallel region.

Parameters

- `target_nodes` ((list of) `psyclone.psyir.nodes.Node`) – a single Node or a list of Nodes.
 - `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
 - `options["node-type-check"]` (`bool`) – this flag controls if the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.
-

class psyclone.psyir.transformations.ArrayRange2LoopTrans

Provides a transformation from a PSyIR Array Range to a PSyIR Loop. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> filename = "tra_adv_compute.F90"
>>> ast, invoke_info = parse(filename, api=api)
>>> psy = PSyFactory(api).create(invoke_info)
>>> schedule = psy.invokes.invoke_list[0].schedule
>>>
>>> from psyclone.psyir.nodes import Assignment
>>> from psyclone.psyir.transformations import ArrayRange2LoopTrans, >>> ↵
↵ TransformationError
>>>
>>> print(schedule.view())
>>> trans = ArrayRange2LoopTrans()
>>> for assignment in schedule.walk(Assignment):
>>>     while True:
>>>         try:
>>>             trans.apply(assignment)
>>>         except TransformationError:
>>>             break
>>> print(schedule.view())
```

`apply(node, options=None)`

Apply the ArrayRange2Loop transformation to the specified node. The node must be an assignment. The rightmost range node in each array within the assignment is replaced with a loop index and the assignment is placed within a loop iterating over that index. The bounds of the loop are determined from the bounds of the array range on the left hand side of the assignment.

Parameters

node (psyclone.psyir.nodes.Assignment) – an Assignment node.

class psyclone.psyir.transformations.ChunkLoopTrans

Apply a chunking transformation to a loop (in order to permit a chunked parallelisation). For example:

```
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.psyir.transformations import ChunkLoopTrans
>>> psyir = FortranReader().psyir_from_source("""
... subroutine sub()
...   integer :: ji, tmp(100)
...   do ji=1, 100
...     tmp(ji) = 2 * ji
...   enddo
... end subroutine sub""")
>>> loop = psyir.walk(Loop)[0]
>>> ChunkLoopTrans().apply(loop)
```

will generate:

```

subroutine sub()
  integer :: ji
  integer, dimension(100) :: tmp
  integer :: ji_el_inner
  integer :: ji_out_var
  do ji_out_var = 1, 100, 32
    ji_el_inner = MIN(ji_out_var + (32 - 1), 100)
    do ji = ji_out_var, ji_el_inner, 1
      tmp(ji) = 2 * ji
    enddo
  enddo
end subroutine sub

```

`apply(node, options=None)`

Converts the given Loop node into a nested loop where the outer loop is over chunks and the inner loop is over each individual element of the chunk.

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – the loop to transform.
- `options` (`Optional[Dict[str, Any]]`) – a dict with options for transformations.
- `options["chunksize"]` (`int`) – The size to chunk over for this transformation. If not specified, the value 32 is used.

`class psyclone.transformations.ColourTrans`

Apply a colouring transformation to a loop (in order to permit a subsequent parallelisation over colours). For example:

```

>>> invoke = ...
>>> schedule = invoke.schedule
>>>
>>> ctrans = ColourTrans()
>>>
>>> # Colour all of the loops
>>> for child in schedule.children:
>>>     ctrans.apply(child)
>>>
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())

```

`apply(node, options=None)`

Converts the Loop represented by `node` into a nested loop where the outer loop is over colours and the inner loop is over cells of that colour.

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – the loop to transform.
- `options` (`Optional[Dict[str, Any]]`) – options for the transformation.

class `psyclone.psyir.transformations.DotProduct2CodeTrans`

Provides a transformation from a PSyIR DOT_PRODUCT Operator node to equivalent code in a PSyIR tree. Validity checks are also performed.

If R is a scalar and A, and B have dimension N, The transformation replaces:

$$R = \dots \text{DOT_PRODUCT}(A,B) \dots$$

with the following code:

```

TMP = 0.0
do I=1,N
    TMP = TMP + A(i)*B(i)
R = ... TMP ...
    
```

For example:

```

>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import BinaryOperation
>>> from psyclone.psyir.transformations import DotProduct2CodeTrans
>>> code = ("subroutine dot_product_test(v1,v2)\n"
...         "real,intent(in) :: v1(10), v2(10)\n"
...         "real :: result\n"
...         "result = dot_product(v1,v2)\n"
...         "end subroutine\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> trans = DotProduct2CodeTrans()
>>> trans.apply(psyir.walk(BinaryOperation)[0])
>>> print(FortranWriter()(psyir))
subroutine dot_product_test(v1, v2)
  real, dimension(10), intent(in) :: v1
  real, dimension(10), intent(in) :: v2
  real :: result
  integer :: i
  real :: res_dot_product

  res_dot_product = 0.0
  do i = 1, 10, 1
    res_dot_product = res_dot_product + v1(i) * v2(i)
  enddo
  result = res_dot_product
end subroutine dot_product_test
    
```

`apply(node, options=None)`

Apply the DOT_PRODUCT intrinsic conversion transformation to the specified node. This node must be a DOT_PRODUCT BinaryOperation. If the transformation is successful then an assignment which includes a DOT_PRODUCT BinaryOperation node is converted to equivalent inline code.

Parameters

- `node` (`psyclone.psyir.nodes.BinaryOperation`) – a DOT_PRODUCT Binary-Operation node.
- `options` (`dict` of `str:str` or `None`) – a dictionary with options for transformations.

```
class psyclone.psyir.transformations.extract_trans.ExtractTrans(node_class=<class 'psy-
                                                                clone.psyir.nodes.extract_node.ExtractNode'>)
```

This transformation inserts an ExtractNode or a node derived from ExtractNode into the PSyIR of a schedule. At code creation time this node will use the PSyData API to create code that can write the input and output parameters to a file. The node might also create a stand-alone driver program that can read the created file and then execute the instrumented region. Examples are given in the derived classes DynamoExtractTrans and GOceanExtractTrans.

After applying the transformation the Nodes marked for extraction are children of the ExtractNode. Nodes to extract can be individual constructs within an Invoke (e.g. Loops containing a Kernel or BuiltIn call) or entire Invokes. This functionality does not support distributed memory.

Parameters

node_class (psyclone.psyir.nodes.ExtractNode or derived class) – The Node class of which an instance will be inserted into the tree (defaults to ExtractNode), but can be any derived class.

apply(nodes, options=None)

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Nodes in the schedule within a single PSyData region.

Parameters

- *nodes* (psyclone.psyir.nodes.Node or list of psyclone.psyir.nodes.Node) – can be a single node or a list of nodes.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- *options["prefix"]* (str) – a prefix to use for the PSyData module name (PREFIX_psy_data_mod) and the PSyDataType (PREFIX_PSYDATATYPE) - a “_” will be added automatically. It defaults to “”.
- *options["region_name"]* ((str,str)) – an optional name to use for this PSyData area, provided as a 2-tuple containing a location name followed by a local name. The pair of strings should uniquely identify a region unless aggregate information is required (and is supported by the runtime library).

```
class psyclone.psyir.transformations.HoistLocalArraysTrans
```

This transformation takes a Routine and promotes any local, ‘automatic’ arrays to Container scope:

```
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Assignment
>>> from psyclone.psyir.transformations import HoistLocalArraysTrans
>>> code = ("module test_mod\n"
...        "contains\n"
...        "  subroutine test_sub(n)\n"
...        "    integer :: i,j,n\n"
...        "    real :: a(n,n)\n"
...        "    real :: value = 1.0\n"
...        "    do i=1,n\n"
...        "      do j=1,n\n"
...        "        a(i,j) = value\n"
...        "      end do\n"
...        "    end do\n")
```

(continues on next page)

(continued from previous page)

```

...      " end do\n"
...      " end subroutine test_sub\n"
...      "end module test_mod\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> hoist = HoistLocalArraysTrans()
>>> hoist.apply(psyir.walk(Routine)[0])
>>> print(FortranWriter()(psyir).lower())
module test_mod
  implicit none
  real, allocatable, dimension(:,:), private :: a
  public

  public :: test_sub

  contains
  subroutine test_sub(n)
    integer :: n
    integer :: i
    integer :: j
    real :: value = 1.0

    if (.not.allocated(a) .or. ubound(a, 1) /= n .or. ubound(a, 2) /= n) then
      if (allocated(a)) then
        deallocate(a)
      end if
      allocate(a(1 : n, 1 : n))
    end if
    do i = 1, n, 1
      do j = 1, n, 1
        a(i,j) = value
      enddo
    enddo

    end subroutine test_sub
end module test_mod

```

By default, the target routine will be rejected if it is found to contain an `ACCRoutineDirective` since this usually implies that the routine will be launched in parallel on the OpenACC device. This check can be disabled by setting `'allow_accroutine'` to `True` in the *options* dictionary.

`apply(node, options=None)`

Applies the transformation to the supplied Routine node, moving any local arrays up to Container scope and adding a suitable allocation when they are first accessed. If there are no local arrays or the supplied Routine is a program then this method does nothing.

Parameters

- `node` (`psyclone.psyir.nodes.Routine`) – target PSyIR node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["allow_accroutine"]` (`bool`) – permit the target routine to contain an `ACCRoutineDirective`. These are forbidden by default because their presence usually indicates that the routine will be run in parallel on the OpenACC device.

```
class psyclone.psyir.transformations.HoistLoopBoundExprTrans
```

This transformation moves complex bounds expressions out of the loop construct and places them in integer scalar assignments before the loop.

```
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.psyir.transformations import HoistTrans
>>> code = ("program test\n"
...        "  use mymod, only: mytype\n"
...        "  integer :: i,j,n\n"
...        "  real :: a(n)\n"
...        "  do i=mytype%start, UBOUND(a,1)\n"
...        "    a(i) = 1.0\n"
...        "  end do\n"
...        "end program\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> hoist = HoistLoopBoundExprTrans()
>>> hoist.apply(psyir.walk(Loop)[0])
>>> print(FortranWriter()(psyir))
program test
  use mymod, only : mytype
  integer :: i
  integer :: j
  integer :: n
  real, dimension(n) :: a
  integer :: loop_bound
  integer :: loop_bound_1

  loop_bound_1 = UBOUND(a, 1)
  loop_bound = mytype%start
  do i = loop_bound, loop_bound_1, 1
    a(i) = 1.0
  enddo

end program test
```

```
apply(node, options=None)
```

Move complex bounds expressions out of the given loop construct and place them in integer scalar assignments before the loop.

Parameters

- *node* (`psyclone.psyir.nodes.Loop`) – target PSyIR loop.
- *options* (`Dict[str, Any]`) – a dictionary with options for transformations.

```
class psyclone.psyir.transformations.HoistTrans
```

This transformation takes an assignment and moves it outside of its parent loop if it is valid to do so. For example:

```
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Assignment
>>> from psyclone.psyir.transformations import HoistTrans
>>> code = ("program test\n"
...        "  integer :: i,j,n\n"
...        "  real :: a(n,n)\n"
...        "  real value\n"
...        "  do i=1,n\n"
...        "    value = 1.0\n"
...        "    do j=1,n\n"
...        "      a(i,j) = value\n"
...        "    end do\n"
...        "  end do\n"
...        "end program\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> hoist = HoistTrans()
>>> hoist.apply(psyir.walk(Assignment)[0])
>>> print(FortranWriter()(psyir))
program test
  integer :: i
  integer :: j
  integer :: n
  real, dimension(n,n) :: a
  real :: value

  value = 1.0
  do i = 1, n, 1
    do j = 1, n, 1
      a(i,j) = value
    enddo
  enddo

end program test
```

`apply(node, options=None)`

Applies the hoist transformation to the supplied assignment node within a loop, moving the assignment outside of the loop if it is valid to do so. Issue #1445 will also look to extend this transformation to other types of node.

Parameters

- *node* (subclass of `psyclone.psyir.nodes.Assignment`) – target PSyIR node.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

`class psyclone.psyir.transformations.InlineTrans`

This transformation takes a Call (which may have a return value) and replaces it with the body of the target routine. It is used as follows:

```
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Call, Routine
```

(continues on next page)

(continued from previous page)

```

>>> from psyclone.psyir.transformations import InlineTrans
>>> code = """
... module test_mod
... contains
...   subroutine run_it()
...     integer :: i
...     real :: a(10)
...     do i=1,10
...       a(i) = 1.0
...       call sub(a(i))
...     end do
...   end subroutine run_it
...   subroutine sub(x)
...     real, intent(inout) :: x
...     x = 2.0*x
...   end subroutine sub
... end module test_mod"""
>>> psyir = FortranReader().psyir_from_source(code)
>>> call = psyir.walk(Call)[0]
>>> inline_trans = InlineTrans()
>>> inline_trans.apply(call)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(psyir.walk(Routine)[0].view())
>>> print(FortranWriter()(psyir.walk(Routine)[0]))
subroutine run_it()
  integer :: i
  real, dimension(10) :: a

  do i = 1, 10, 1
    a(i) = 1.0
    a(i) = 2.0 * a(i)
  enddo

end subroutine run_it

```

Warning: Routines/calls with any of the following characteristics are not supported and will result in a `TransformationError`:

- the routine is not in the same file as the call;
- the routine contains an early `Return` statement;
- the routine contains a variable with `UnknownInterface`;
- the routine contains a variable with `StaticInterface`;
- the routine contains an `UnknownType` variable with `ArgumentInterface`;
- the routine has a named argument;
- the shape of any array arguments as declared inside the routine does not match the shape of the arrays being passed as arguments;
- the routine accesses an un-resolved symbol;

- the routine accesses a symbol declared in the Container to which it belongs.

Some of these restrictions will be lifted by #924.

`apply(node, options=None)`

Takes the body of the routine that is the target of the supplied call and replaces the call with it.

Parameters

- `node` (`psyclone.psyir.nodes.Routine`) – target PSyIR node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

`class psyclone.domain.common.transformations.KernelModuleInlineTrans`

Module-inlines (bring the subroutine to the same compiler-unit) the subroutine pointed by this Kernel. For example:

```
from psyclone.domain.common.transformations import \
    KernelModuleInlineTrans

inline_trans = KernelModuleInlineTrans()
inline_trans.apply(schedule.walk(CodedKern)[0])

print(schedule.parent.view())
```

Warning: Not all kernel subroutines can be module-inlined. This transformation will reject attempts to in-line kernels that access global data in the original module.

`apply(node, options=None)`

Bring the kernel subroutine into this Container.

Parameters

- `node` (`psyclone.psyGen.CodedKern`) – the kernel to module-inline.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

`class psyclone.psyir.transformations.LoopFuseTrans`

Provides a generic loop-fuse transformation to two Nodes in the PSyIR of a Schedule after performing validity checks for the supplied Nodes. Examples are given in the descriptions of any children classes.

`apply(node1, node2, options=None)`

Fuses two loops represented by `psyclone.psyir.nodes.Node` objects after performing validity checks.

Parameters

- `node1` (`psyclone.psyir.nodes.Node`) – the first Node that is being checked.
 - `node2` (`psyclone.psyir.nodes.Node`) – the second Node that is being checked.
 - `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
-

class psyclone.psyir.transformations.LoopSwapTrans

Provides a loop-swap transformation, e.g.:

```
DO j=1, m
  DO i=1, n
```

becomes:

```
DO i=1, n
  DO j=1, m
```

This transform is used as follows:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> ast, invokeInfo = parse("shallow_alg.f90")
>>> psy = PSyFactory("gocean1.0").create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import LoopSwapTrans
>>> swap = LoopSwapTrans()
>>> swap.apply(schedule.children[0])
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

apply(*node*, *options*=None)

The argument *outer* must be a loop which has exactly one inner loop. This transform then swaps the outer and inner loop.

Parameters

- *outer* (psyclone.psyir.nodes.Loop) – the node representing the outer loop.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

TransformationError – if the supplied node does not allow a loop swap to be done.

class psyclone.psyir.transformations.LoopTiling2DTrans

Apply a 2D loop tiling transformation to a loop. For example:

```
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.psyir.transformations import LoopTiling2DTrans
>>> psyir = FortranReader().psyir_from_source("""
... subroutine sub()
...   integer :: ji, tmp(100)
...   do i=1, 100
...     do j=1, 100
...       tmp(i, j) = 2 * tmp(i, j)
...     enddo
...   enddo
```

(continues on next page)

(continued from previous page)

```
... end subroutine sub""")
>>> loop = psyir.walk(Loop)[0]
>>> LoopTiling2DTrans().apply(loop)
```

will generate:

```
subroutine sub()
  integer :: ji
  integer, dimension(100) :: tmp
  integer :: ji_el_inner
  integer :: ji_out_var
  do i_out_var = 1, 100, 32
    i_el_inner = MIN(i_out_var + (32 - 1), 100)
    do j_out_var = 1, 100, 32
      do i = i_out_var, i_el_inner, 1
        j_el_inner = MIN(j_out_var + (32 - 1), 100)
        do j = j_out_var, j_el_inner, 1
          tmp(i, j) = 2 * tmp(i, j)
        enddo
      enddo
    enddo
  enddo
end subroutine sub
```

`apply(node, options=None)`

Converts the given 2D Loop construct into a tiled version of the nested loops.

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – the loop to transform.
- `options` (Optional[Dict[str, Any]]) – a dict with options for transformations.
- `options["tilesize"]` (`int`) – The size of the resulting tile, currently square tiles are always used. If not specified, the value 32 is used.

`class psyclone.psyir.transformations.Matmul2CodeTrans`

Provides a transformation from a PSyIR MATMUL Operator node to equivalent code in a PSyIR tree. Validity checks are also performed.

For a matrix-vector multiplication, if the dimensions of R, A, and B are $R(N)$, $A(N,M)$, $B(M)$, the transformation replaces:

```
R=MATMUL(A,B)
```

with the following code:

```
do i=1,N
  R(i) = 0.0
  do j=1,M
    R(i) = R(i) + A(i,j) * B(j)
```

For a matrix-matrix multiplication, if the dimensions of R, A, and B are $R(P,M)$, $A(P,N)$, $B(N,M)$, the MATMUL is replaced with the following code:


```

do j=1,M
  do i=1,P
    R(i,j) = 0.0
    do ii=1,N
      R(i,j) = R(i,j) + A(i,ii) * B(ii,j)
    
```

Note that this transformation does *not* support the case where A is a rank-1 array.

`apply(node, options=None)`

Apply the MATMUL intrinsic conversion transformation to the specified node. This node must be a MATMUL BinaryOperation. The first argument must currently have two dimensions while the second must have either one or two dimensions. Each argument is permitted to have additional dimensions (i.e. more than 2) but in each case it is only the first one or two which may be ranges. Further, the ranges must currently be for the full index space for that dimension (i.e. array subsections are not supported). If the transformation is successful then an assignment which includes a MATMUL BinaryOperation node is converted to equivalent inline code.

Parameters

- `node` (`psyclone.psyir.nodes.BinaryOperation`) – a MATMUL Binary-Operation node.
- `options` (`Optional[Dict[str, Any]]`) – options for the transformation.

Note: This transformation is currently limited to translating the matrix vector form of MATMUL to equivalent PSyIR code.

`class psyclone.psyir.transformations.Max2CodeTrans`

Provides a transformation from a PSyIR MAX Operator node to equivalent code in a PSyIR tree. Validity checks are also performed (by a parent class).

The transformation replaces

```
R = MAX(A, B, C ...)
```

with the following logic:

```

R = A
if B > R:
    R = B
if C > R:
    R = C
...

```

`apply(node, options=None)`

Apply this utility transformation to the specified node. This node must be a MIN or MAX BinaryOperation or NaryOperation. The operation is converted to equivalent inline code. This is implemented as a PSyIR transform from:

```
R = ... [MIN or MAX](A, B, C ...) ...
```

to:

```
res = A
tmp = B
IF tmp [< or >] res:
    res = tmp
tmp = C
IF tmp [< or >] res:
    res = tmp
...
R = ... res ...
```

where A, B, C ... could be arbitrarily complex PSyIR expressions and the ... before and after [MIN or MAX](A, B, C ...) can be arbitrary PSyIR code.

This transformation requires the operation node to be a descendent of an assignment and will raise an exception if this is not the case.

Parameters

- node (psyclone.psyir.nodes.BinaryOperation or psyclone.psyir.nodes.NaryOperation) – a MIN or MAX Binary- or Nary-Operation node.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Warning: This transformation assumes that the MAX Operator acts on PSyIR Real scalar data and does not check that this is not the case. Once issue #658 is on master then this limitation can be fixed.

class psyclone.psyir.transformations.Min2CodeTrans

Provides a transformation from a PSyIR MIN Operator node to equivalent code in a PSyIR tree. Validity checks are also performed (by a parent class).

The transformation replaces

R = MIN(A, B, C ...)

with the following logic:

```
R = A
if B < R:
    R = B
if C < R:
    R = C
...
```

apply(*node*, *options=None*)

Apply this utility transformation to the specified node. This node must be a MIN or MAX BinaryOperation or NaryOperation. The operation is converted to equivalent inline code. This is implemented as a PSyIR transform from:

R = ... [MIN or MAX](A, B, C ...) ...

to:

```

res = A
tmp = B
IF tmp [< or >] res:
    res = tmp
tmp = C
IF tmp [< or >] res:
    res = tmp
...
R = ... res ...

```

where A, B, C ... could be arbitrarily complex PSyIR expressions and the ... before and after [MIN or MAX](A, B, C ...) can be arbitrary PSyIR code.

This transformation requires the operation node to be a descendent of an assignment and will raise an exception if this is not the case.

Parameters

- node (psyclone.psyir.nodes.BinaryOperation or psyclone.psyir.nodes.NaryOperation) – a MIN or MAX Binary- or Nary-Operation node.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Warning: This transformation assumes that the MIN Operator acts on PSyIR Real scalar data and does not check that this is not the case. Once issue #658 is on master then this limitation can be fixed.

class psyclone.transformations.MoveTrans

Provides a transformation to move a node in the tree. For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> ast, invokeInfo = parse("dynamo.F90")
>>> psy = PSyFactory("dynamo0.3").create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_v3_kernel_type').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import MoveTrans
>>> trans = MoveTrans()
>>> trans.apply(schedule.children[0], schedule.children[2],
...             options = {"position": "after"})
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())

```

Nodes may only be moved to a new location with the same parent and must not break any dependencies otherwise an exception is raised.

apply(*node*, *location*, *options=None*)

Move the node represented by *node* before *location* (which is also a node) by default and after if the optional *position* argument is set to 'after'.

Parameters

- node (psyclone.psyir.nodes.Node) – the node to be moved.

- location (psyclone.psyir.nodes.Node) – node before or after which the given node should be moved.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- options["position"] (str) – either ‘before’ or ‘after’.

Raises

- TransformationError – if the given node is not an instance of psyclone.psyir.nodes.Node
 - TransformationError – if the location is not valid.
-

class psyclone.domain.gocean.transformations.GOOpenCLTrans

Switches on/off the generation of an OpenCL PSy layer for a given InvokeSchedule. Additionally, it will generate OpenCL kernels for each of the kernels referenced by the Invoke. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> API = "gocean1.0"
>>> FILENAME = "shallow_alg.f90" # examples/gocean/egl
>>> ast, invoke_info = parse(FILENAME, api=API)
>>> psy = PSyFactory(API, distributed_memory=False).create(invoke_info)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> ocl_trans = GOOpenCLTrans()
>>> ocl_trans.apply(schedule)
>>> print(schedule.view())
```

apply(node, options=None)

Apply the OpenCL transformation to the supplied GOInvokeSchedule. This causes PSyclone to generate an OpenCL version of the corresponding PSy-layer routine. The generated code makes use of the FortCL library (<https://github.com/stfc/FortCL>) in order to manage the OpenCL device directly from Fortran.

Parameters

- node (psyclone.psyGen.GOInvokeSchedule) – the InvokeSchedule to transform.
 - options (dict of str:value or None) – set of option to tune the OpenCL generation.
 - options["enable_profiling"] (bool) – whether or not to set up the OpenCL environment with the profiling option enabled.
 - options["out_of_order"] (bool) – whether or not to set up the OpenCL environment with the out_of_order option enabled.
 - options["end_barrier"] (bool) – whether or not to add an OpenCL barrier at the end of the transformed invoke.
-

class psyclone.transformations.OMPDeclareTargetTrans

Adds an OpenMP declare target directive to the specified routine.

For example:

```

>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.transformations import OMPDeclareTargetTrans
>>>
>>> tree = FortranReader().psyir_from_source("""
...     subroutine my_subroutine(A)
...         integer, dimension(10, 10), intent(inout) :: A
...         integer :: i
...         integer :: j
...         do i = 1, 10
...             do j = 1, 10
...                 A(i, j) = 0
...             end do
...         end do
...     end subroutine
... """)
>>> omptargettrans = OMPDeclareTargetTrans()
>>> omptargettrans.apply(tree.walk(Routine)[0])

```

will generate:

```

subroutine my_subroutine(A)
    integer, dimension(10, 10), intent(inout) :: A
    integer :: i
    integer :: j
    !$omp declare target
    do i = 1, 10
        do j = 1, 10
            A(i, j) = 0
        end do
    end do
end subroutine

```

`apply(node, options=None)`

Insert an OMPDeclareTargetDirective inside the provided routine.

Parameters

- `node` (`psyclone.psyir.nodes.Routine`) – the PSyIR routine to insert the directive into.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

`class psyclone.psyir.transformations.OMPLoopTrans(omp_directive='do', omp_schedule='auto')`

Adds an OpenMP directive to parallelise this loop. It can insert different directives such as “omp do/for”, “omp parallel do/for”, “omp teams distribute parallel do/for” or “omp loop” depending on the provided parameters. The OpenMP schedule to use can also be specified, but this will be ignored in case of the “omp loop” (as the ‘schedule’ clause is not valid for this specific directive). The configuration-defined ‘reprod’ parameter also specifies whether a manual reproducible reproduction is to be used. Note, reproducible in this case means obtaining the same results with the same number of OpenMP threads, not for different numbers of OpenMP threads.

Parameters

- `omp_schedule` (`str`) – the OpenMP schedule to use. Defaults to ‘auto’.
- `omp_directive` (`str`) – choose which OpenMP loop directive to use. Defaults to “omp do”

For example:

```
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.transformations import OMPLoopTrans, OMPParallelTrans
>>>
>>> psyir = FortranReader().psyir_from_source("""
...     subroutine my_subroutine()
...         integer, dimension(10, 10) :: A
...         integer :: i
...         integer :: j
...         do i = 1, 10
...             do j = 1, 10
...                 A(i, j) = 0
...             end do
...         end do
...     end subroutine
... """)
>>> loop = psyir.walk(Loop)[0]
>>> omplooptrans1 = OMPLoopTrans(omp_schedule="dynamic",
...                               omp_directive="parallel do")
>>> omplooptrans1.apply(loop)
>>> print(FortranWriter()(psyir))
subroutine my_subroutine()
  integer, dimension(10,10) :: a
  integer :: i
  integer :: j

  !$omp parallel do default(shared), private(i,j), schedule(dynamic)
  do i = 1, 10, 1
    do j = 1, 10, 1
      a(i,j) = 0
    enddo
  enddo
  !$omp end parallel do

end subroutine my_subroutine
```

`apply(node, options=None)`

Apply the OMPLoopTrans transformation to the specified PSyIR Loop.

Parameters

- *node* (`psyclone.psyir.nodes.Node`) – the supplied node to which we will apply the OMPLoopTrans transformation
- *options* (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- *options*["reprod"] (`bool`) – indicating whether reproducible reductions should be used. By default the value from the config file will be used.

property `omp_directive`

Returns

the type of OMP directive that this transformation will insert.

Return type

str

property omp_schedule

Returns

the OpenMP schedule that will be specified by this transformation.

Return type

str

class psyclone.transformations.OMPMasterTrans

Create an OpenMP MASTER region by inserting directives. The most likely use case for this transformation is to wrap around task-based transformations. Note that adding this directive requires a parent OpenMP parallel region (which can be inserted by OMPParallelTrans), otherwise it will produce an error in generation-time.

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import OMPParallelTrans, OMPMasterTrans
>>> mastertrans = OMPMasterTrans()
>>> paralleltrans = OMPParallelTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Enclose all of these loops within a single OpenMP
>>> # MASTER region
>>> mastertrans.apply(schedule.children)
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> paralleltrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

apply(target_nodes, options=None)

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Loops in the schedule within a single parallel region.

Parameters

- target_nodes ((list of) psyclone.psyir.nodes.Node) – a single Node or a list of Nodes.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- options["node-type-check"] (bool) – this flag controls if the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

get_node_list(nodes)

This is a helper function for region based transformations. The parameter for any of those transformations is either a single node, a schedule, or a list of nodes. This function converts this into a list of nodes according

to the parameter type. This function will always return a copy, to avoid issues e.g. if a child list of a node should be provided, and a transformation changes the order in this list (which would then also change the order of the nodes in the tree).

Parameters

- `nodes` (Union[psyclone.psyir.nodes.Node, psyclone.psyir.nodes.Schedule, List[psyclone.psyir.nodes.Node]]) – can be a single node, a schedule or a list of nodes.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Returns

a list of nodes.

Return type

List[psyclone.psyir.nodes.Node]

Raises

TransformationError – if the supplied parameter is neither a single Node, nor a Schedule, nor a list of Nodes.

`validate(node_list, options=None)`

Check that the supplied list of Nodes are eligible to be put inside a parallel region.

Parameters

- `node_list` (list) – list of nodes to put into a parallel region
- `options` – a dictionary with options for transformations. :type options: Optional[Dict[str, Any]]
- `options["node-type-check"]` (bool) – this flag controls whether or not the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

Raises

- TransformationError – if the supplied node is an InvokeSchedule rather than being within an InvokeSchedule.
- TransformationError – if the supplied nodes are not all children of the same parent (siblings).

Note: PSyclone does not support (distributed-memory) halo swaps or global sums within OpenMP master regions. Attempting to create a master region for a set of nodes that includes halo swaps or global sums will produce an error. In such cases it may be possible to re-order the nodes in the Schedule such that the halo swaps or global sums are performed outside the single region. The *MoveTrans* transformation may be used for this.

```
class psyclone.transformations.OMPParallelLoopTrans(omp_directive='do', omp_schedule='auto')
```

Adds an OpenMP PARALLEL DO directive to a loop.

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> ast, invokeInfo = parse("dynamo.F90")
>>> psy = PSyFactory("dynamo0.3").create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_v3_kernel_type').schedule
```

(continues on next page)

(continued from previous page)

```

>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import OMPParallelLoopTrans
>>> trans = OMPParallelLoopTrans()
>>> trans.apply(schedule.children[0])
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())

```

`apply(node, options=None)`

Apply an OMPParallelLoop Transformation to the supplied node (which must be a Loop). In the generated code this corresponds to wrapping the Loop with directives:

```

!$OMP PARALLEL DO ...
do ...
...
end do
!$OMP END PARALLEL DO

```

Parameters

- `node` (`psyclone.f2pygen.DoGen`) – the node (loop) to which to apply the transformation.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations and validation.

`class psyclone.transformations.OMPParallelTrans`

Create an OpenMP PARALLEL region by inserting directives. For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.parse.utils import ParseError
>>> from psyclone.psyGen import PSyFactory
>>> from psyclone.errors import GenerationError
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> ltrans = t.get_trans_name('GOceanOMPLoopTrans')
>>> rtrans = t.get_trans_name('OMPParallelTrans')
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenMP Loop transformation to *every* loop
>>> # in the schedule
>>> for child in schedule.children:
>>>     ltrans.apply(child)
>>>

```

(continues on next page)

(continued from previous page)

```
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> rtrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(target_nodes, options=None)`

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Loops in the schedule within a single parallel region.

Parameters

- `target_nodes` ((list of) `psyclone.psyir.nodes.Node`) – a single Node or a list of Nodes.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- `options["node-type-check"]` (bool) – this flag controls if the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

`get_node_list(nodes)`

This is a helper function for region based transformations. The parameter for any of those transformations is either a single node, a schedule, or a list of nodes. This function converts this into a list of nodes according to the parameter type. This function will always return a copy, to avoid issues e.g. if a child list of a node should be provided, and a transformation changes the order in this list (which would then also change the order of the nodes in the tree).

Parameters

- `nodes` (Union[`psyclone.psyir.nodes.Node`, `psyclone.psyir.nodes.Schedule`, List[`psyclone.psyir.nodes.Node`]]) – can be a single node, a schedule or a list of nodes.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Returns

a list of nodes.

Return type

List[`psyclone.psyir.nodes.Node`]

Raises

`TransformationError` – if the supplied parameter is neither a single Node, nor a Schedule, nor a list of Nodes.

`validate(node_list, options=None)`

Perform OpenMP-specific validation checks.

Parameters

- `node_list` (list of `psyclone.psyir.nodes.Node`) – list of Nodes to put within parallel region.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- `options["node-type-check"]` (bool) – this flag controls if the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

Raises

`TransformationError` – if the target Nodes are already within some OMP parallel region.

Note: PSyclone does not support (distributed-memory) halo swaps or global sums within OpenMP parallel regions. Attempting to create a parallel region for a set of nodes that includes halo swaps or global sums will produce an error. In such cases it may be possible to re-order the nodes in the Schedule such that the halo swaps or global sums are performed outside the parallel region. The *MoveTrans* transformation may be used for this.

class `psyclone.transformations.OMPSingleTrans(nowait=False)`

Create an OpenMP SINGLE region by inserting directives. The most likely use case for this transformation is to wrap around task-based transformations. The parent region for this should usually also be a `OMPParallelTrans`.

Parameters

`nowait` (`bool`) – whether to apply a `nowait` clause to this transformation. The default value is `False`

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import OMPParallelTrans, OMPSingleTrans
>>> singletrans = OMPSingleTrans()
>>> paralleltrans = OMPParallelTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Enclose all of these loops within a single OpenMP
>>> # SINGLE region
>>> singletrans.apply(schedule.children)
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> paralleltrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(node_list, options=None)`

Apply the `OMPSingleTrans` transformation to the specified node in a Schedule.

At code-generation time this node must be within (i.e. a child of) an OpenMP PARALLEL region. Code generation happens when `OMPLoopDirective.gen_code()` is called, or when the PSyIR tree is given to a backend.

If the keyword “`nowait`” is specified in the options, it will cause a `nowait` clause to be added if it is set to `True`, otherwise no clause will be added.

Parameters

- `node_list` ((a list of) `psyclone.psyir.nodes.Node`) – the supplied node or node list to which we will apply the `OMPSingleTrans` transformation
- `options` (Optional[Dict[str, Any]]) – a list with options for transformations and validation.

- `options["nowait"]` (`bool`) – indicating whether or not to use a `nowait` clause on this single region.

`get_node_list(nodes)`

This is a helper function for region based transformations. The parameter for any of those transformations is either a single node, a schedule, or a list of nodes. This function converts this into a list of nodes according to the parameter type. This function will always return a copy, to avoid issues e.g. if a child list of a node should be provided, and a transformation changes the order in this list (which would then also change the order of the nodes in the tree).

Parameters

- `nodes` (`Union[psyclone.psyir.nodes.Node, psyclone.psyir.nodes.Schedule, List[psyclone.psyir.nodes.Node]]`) – can be a single node, a schedule or a list of nodes.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Returns

a list of nodes.

Return type

`List[psyclone.psyir.nodes.Node]`

Raises

`TransformationError` – if the supplied parameter is neither a single `Node`, nor a `Schedule`, nor a list of `Nodes`.

property `omp_nowait`

Returns

whether or not this `Single` region uses a `nowait` clause to remove the end barrier.

Return type

`bool`

`validate(node_list, options=None)`

Check that the supplied list of `Nodes` are eligible to be put inside a parallel region.

Parameters

- `node_list` (`list`) – list of nodes to put into a parallel region
- `options` – a dictionary with options for transformations. :type options: `Optional[Dict[str, Any]]`
- `options["node-type-check"]` (`bool`) – this flag controls whether or not the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

Raises

- `TransformationError` – if the supplied node is an `InvokeSchedule` rather than being within an `InvokeSchedule`.
- `TransformationError` – if the supplied nodes are not all children of the same parent (siblings).

Note: PSyclone does not support (distributed-memory) halo swaps or global sums within OpenMP single regions. Attempting to create a single region for a set of nodes that includes halo swaps or global sums will produce an error. In such cases it may be possible to re-order the nodes in the `Schedule` such that the halo swaps or global sums are performed outside the single region. The *MoveTrans* transformation may be used for this.

class `psyclone.psyir.transformations.OMPTargetTrans`

Adds an OpenMP target directive to a region of code.

For example:

```
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.psyir.transformations import OMPTargetTrans
>>>
>>> tree = FortranReader().psyir_from_source("""
...  subroutine my_subroutine()
...    integer, dimension(10, 10) :: A
...    integer :: i
...    integer :: j
...    do i = 1, 10
...        do j = 1, 10
...            A(i, j) = 0
...        end do
...    end do
...  end subroutine
... """)
>>> OMPTargetTrans().apply(tree.walk(Loop)[0])
>>> print(FortranWriter()(tree))
subroutine my_subroutine()
  integer, dimension(10,10) :: a
  integer :: i
  integer :: j

  !$omp target
  do i = 1, 10, 1
    do j = 1, 10, 1
      a(i,j) = 0
    enddo
  enddo
  !$omp end target

end subroutine my_subroutine
```

`apply(node, options=None)`

Insert an OMPTargetDirective before the provided node or list of nodes.

Parameters

- `node` (`List[psyclone.psyir.nodes.Node]`) – the PSyIR node or nodes to enclose in the OpenMP target region.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

class `psyclone.transformations.OMPTaskloopTrans(grainsize=None, num_tasks=None, nogroup=False)`

Adds an OpenMP taskloop directive to a loop. Only one of `grainsize` or `num_tasks` must be specified.

TODO: #1364 Taskloops do not yet support reduction clauses.

Parameters

- `grainsize` (`int` or `None`) – the `grainsize` to use in for this transformation.
- `num_tasks` (`int` or `None`) – the `num_tasks` to use for this transformation.
- `nogroup` (`bool`) – whether or not to use a `nogroup` clause for this transformation. Default is `False`.

For example:

```
>>> from pysyclone.parse.algorithm import parse
>>> from pysyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from pysyclone.transformations import OMPParallelTrans, OMPSingleTrans
>>> from pysyclone.transformations import OMPTaskloopTrans
>>> from pysyclone.psyir.transformations import OMPTaskwaitTrans
>>> singletrans = OMPSingleTrans()
>>> paralleltrans = OMPParallelTrans()
>>> tasklooptrans = OMPTaskloopTrans()
>>> taskwaittrans = OMPTaskwaitTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenMP Taskloop transformation to *every* loop
>>> # in the schedule.
>>> # This ignores loop dependencies. These can be handled
>>> # by the OMPTaskwaitTrans
>>> for child in schedule.children:
>>>     tasklooptrans.apply(child)
>>> # Enclose all of these loops within a single OpenMP
>>> # SINGLE region
>>> singletrans.apply(schedule.children)
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> paralleltrans.apply(schedule.children)
>>> # Ensure loop dependencies are satisfied
>>> taskwaittrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(node, options=None)`

Apply the `OMPTaskloopTrans` transformation to the specified node in a `Schedule`. This node must be a `Loop` since this transformation corresponds to wrapping the generated code with directives like so:

```
!$OMP TASKLOOP
do ...
...
end do
!$OMP END TASKLOOP
```

At code-generation time (when `OMPTaskloopDirective.gen_code()` is called), this node must be within (i.e. a child of) an OpenMP SERIAL region.

If the keyword “nogroup” is specified in the options, it will cause a nogroup clause be generated if it is set to True. This will override the value supplied to the constructor, but will only apply to the apply call to which the value is supplied.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the supplied node to which we will apply the OMP-TaskloopTrans transformation
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- `options["nogroup"]` (`bool`) – indicating whether a nogroup clause should be applied to this taskloop.

property `omp_grainsize`

Returns the grainsize that will be specified by this transformation. By default the grainsize clause is not applied, so grainsize is None.

Returns

The grainsize specified by this transformation.

Return type

`int` or `None`

property `omp_num_tasks`

Returns the num_tasks that will be specified by this transformation. By default the num_tasks clause is not applied so num_tasks is None.

Returns

The grainsize specified by this transformation.

Return type

`int` or `None`

class `psyclone.psyir.transformations.OMPTaskwaitTrans`

Adds zero or more OpenMP Taskwait directives to an OMP parallel region. This transformation will add directives to satisfy dependencies between Taskloop directives without an associated taskgroup (i.e. no nogroup clause). It also tries to minimise the number added to maximise available parallelism.

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> filename = "nemolite2d_alg.f90"
>>> ast, invokeInfo = parse(filename, api=api, invoke_name="invoke")
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import OMPParallelTrans, OMPSingleTrans
>>> from psyclone.transformations import OMPTaskloopTrans
>>> from psyclone.psyir.transformations import OMPTaskwaitTrans
>>> singletrans = OMPSingleTrans()
>>> paralleltrans = OMPParallelTrans()
```

(continues on next page)

(continued from previous page)

```
>>> tasklooptrans = OMPTaskloopTrans()
>>> taskwaittrans = OMPTaskwaitTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> print(schedule.view())
>>>
>>> # Apply the OpenMP Taskloop transformation to *every* loop
>>> # in the schedule.
>>> # This ignores loop dependencies. These are handled by the
>>> # taskwait transformation.
>>> for child in schedule.children:
>>>     tasklooptrans.apply(child, nogroup = True)
>>> # Enclose all of these loops within a single OpenMP
>>> # SINGLE region
>>> singletrans.apply(schedule.children)
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> paralleltrans.apply(schedule.children)
>>> taskwaittrans.apply(schedule.children)
>>> print(schedule.view())
```

`apply(node, options=None)`

Apply an OMPTaskwait Transformation to the supplied node (which must be an OMPParallelDirective). In the generated code this corresponds to adding zero or more OMPTaskwaitDirectives as appropriate:

```
!$OMP PARALLEL
...
!$OMP TASKWAIT
...
!$OMP TASKWAIT
...
!$OMP END PARALLEL
```

Parameters

- `node` (`psyclone.psyir.nodes.OMPParallelDirective`) – the node to which to apply the transformation.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- `options["fail_on_no_taskloop"]` (`bool`) – indicating whether this should throw an error if no OMPTaskloop nodes are found in this tree. This can be safely disabled as if there are no Taskloop nodes the result of this transformation is valid OpenMP code. Default is `True`

`class psyclone.psyir.transformations.ProfileTrans`

Create a profile region around a list of statements. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.parse.utils import ParseError
>>> from psyclone.psyGen import PSyFactory, GenerationError
```

(continues on next page)

(continued from previous page)

```

>>> from psyclone.psyir.transformations import ProfileTrans
>>> api = "gocean1.0"
>>> filename = "nemolite2d_alg.f90"
>>> ast, invokeInfo = parse(filename, api=api, invoke_name="invoke")
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> p_trans = ProfileTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> print(schedule.view())
>>>
>>> # Enclose all children within a single profile region
>>> p_trans.apply(schedule.children)
>>> print(schedule.view())

```

This implementation relies completely on the base class PSyDataTrans for the actual work, it only adjusts the name etc, and the list of valid nodes.

`apply(nodes, options=None)`

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Nodes in the schedule within a single PSyData region.

Parameters

- `nodes` (`psyclone.psyir.nodes.Node` or list of `psyclone.psyir.nodes.Node`) – can be a single node or a list of nodes.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["prefix"]` (`str`) – a prefix to use for the PSyData module name (`PREFIX_psy_data_mod`) and the PSyDataType (`PREFIX_PSYDATATYPE`) - a “_” will be added automatically. It defaults to “”.
- `options["region_name"]` (`((str,str))`) – an optional name to use for this PSyData area, provided as a 2-tuple containing a location name followed by a local name. The pair of strings should uniquely identify a region unless aggregate information is required (and is supported by the runtime library).

```

class psyclone.psyir.transformations.ReadOnlyVerifyTrans(node_class=<class 'psyclone.psyir.nodes.read_only_verify_node.ReadOnlyVerifyNode'>)

```

This transformation inserts a `ReadOnlyVerifyNode` or a node derived from `ReadOnlyVerifyNode` into the PSyIR of a schedule. At code creation time this node will use the PSyData API to create code that will verify that read-only quantities are not modified.

After applying the transformation the Nodes marked for verification are children of the `ReadOnlyVerifyNode`. Nodes to verify can be individual constructs within an `Invoke` (e.g. Loops containing a `Kernel` or `BuiltIn` call) or entire `Invokes`.

Parameters

`node_class` (`psyclone.psyir.nodes.ReadOnlyVerifyNode` or derived class) – The class of Node which will be inserted into the tree (defaults to `ReadOnlyVerifyNode`), but can be any derived class.

`apply(nodes, options=None)`

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Nodes in the schedule within a single PSyData region.

Parameters

- nodes (psyclone.psyir.nodes.Node or list of psyclone.psyir.nodes.Node) – can be a single node or a list of nodes.
 - options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
 - options["prefix"] (str) – a prefix to use for the PSyData module name (PREFIX_psy_data_mod) and the PSyDataType (PREFIX_PSYDATATYPE) - a “_” will be added automatically. It defaults to “”.
 - options["region_name"] ((str,str)) – an optional name to use for this PSyData area, provided as a 2-tuple containing a location name followed by a local name. The pair of strings should uniquely identify a region unless aggregate information is required (and is supported by the runtime library).
-

class psyclone.psyir.transformations.Reference2ArrayRangeTrans

Provides a transformation from PSyIR Array Notation (a reference to an Array) to a PSyIR Range. For example:

```
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Reference
>>> from psyclone.psyir.transformations import TransformationError
>>> CODE = ("program example\n"
...         "real :: a(:)\n"
...         "a = 0.0\n"
...         "end program\n")
>>> trans = Reference2ArrayRangeTrans()
>>> psyir = FortranReader().psyir_from_source(CODE)
>>> for reference in psyir.walk(Reference):
...     try:
...         trans.apply(reference)
...     except TransformationError:
...         pass
>>> print(FortranWriter()(psyir))
program example
  real, dimension(:) :: a

  a(:) = 0.0

end program example
```

This transformation does not currently support arrays within structures, see issue #1858.

`apply(node, options=None)`

Apply the Reference2ArrayRangeTrans transformation to the specified node. The node must be a Reference to an array. The Reference is replaced by an ArrayReference with appropriate explicit range nodes (termed colon notation in Fortran).

Parameters

- node (psyclone.psyir.nodes.Reference) – a Reference node.
 - options (Optional[Dict[str, Any]]) – a dict with options for transformations.
-

class psyclone.psyir.transformations.ReplaceInductionVariablesTrans

Move all supported induction variables out of the loop, and replace their usage inside the loop. For example:

```
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.psyir.transformations import ReplaceInductionVariablesTrans
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> psyir = FortranReader().psyir_from_source("""
... subroutine sub()
...   integer :: i, im, ic, tmp(100)
...   do i=1, 100
...     im = i - 1
...     ic = 2
...     tmp(i) = ic * im
...   enddo
... end subroutine sub""")
>>> loop = psyir.walk(Loop)[0]
>>> ReplaceInductionVariablesTrans().apply(loop)
>>> print(FortranWriter()(psyir))
subroutine sub()
  integer :: i
  integer :: im
  integer :: ic
  integer, dimension(100) :: tmp

  do i = 1, 100, 1
    tmp(i) = 2 * (i - 1)
  enddo
  ic = 2
  im = i - 1 - 1

end subroutine sub
```

The replaced induction variables assignments are added after the loop, so these variables will have the correct value if they are used elsewhere.

The following restrictions apply for the assignment to an induction variable:

- the variable must be a scalar (i.e. no array access at all, not even a constant like `a(3)` or `a%c(3)%c`)
- none of variables on the right-hand side can be written in the loop body (the loop variable is written in the Loop statement, not in the body, so it can be used).
- Only intrinsic function calls are allowed on the RHS (since they are known to be elemental)
- the assigned variable must not be read before the assignment.
- the assigned variable cannot occur on the right-hand side (e.g. $k = k + 3$).
- there must be only one assignment to this induction variable.

`apply(node, options=None)`

Apply the `ReplaceInductionVariablesTrans` transformation to the specified node. The node must be a loop. In case of nested loops, the transformation might need to be applied several times, from the inner-most loop outwards.

Parameters

`node` (`psyclone.psyir.nodes.Loop`) – a Loop node.

class psyclone.psyir.transformations.Sign2CodeTrans

Provides a transformation from a PSyIR SIGN Operator node to equivalent code in a PSyIR tree. Validity checks are also performed.

The transformation replaces

$$R = \text{SIGN}(A, B)$$

with the following logic:

```
R = ABS(A)
if B < 0.0:
    R = R*-1.0
```

i.e. the value of A with the sign of B

`apply(node, options=None)`

Apply the SIGN intrinsic conversion transformation to the specified node. This node must be a SIGN BinaryOperation. The SIGN BinaryOperation is converted to equivalent inline code. This is implemented as a PSyIR transform from:

$$R = \dots \text{SIGN}(A, B) \dots$$

to:

```
tmp_abs = A
if tmp_abs < 0.0:
    res_abs = tmp_abs*-1.0
else:
    res_abs = tmp_abs
res_sign = res_abs
tmp_sign = B
if tmp_sign < 0.0:
    res_sign = res_sign*-1.0
R = ... res_sign ...
```

where A and B could be arbitrarily complex PSyIR expressions, ... could be arbitrary PSyIR code and where ABS has been replaced with inline code by the NemoAbsTrans transformation.

This transformation requires the operation node to be a descendent of an assignment and will raise an exception if this is not the case.

Parameters

- node (psyclone.psyir.nodes.BinaryOperation) – a SIGN BinaryOperation node.
- symbol_table (psyclone.psyir.symbols.SymbolTable) – the symbol table.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Warning: This transformation assumes that the SIGN Operator acts on PSyIR Real scalar data and does not check whether or not this is the case. Once issue #658 is on master then this limitation can be fixed.

class psyclone.psyir.transformations.Sum2CodeTrans

Provides a transformation from a PSyIR SUM Operator node to equivalent code in a PSyIR tree. Validity checks are also performed.

If SUM contains a single positional argument which is an array, all element on that array are summed and the result returned in the scalar R.

```
R = SUM(ARRAY)
```

For example, if the array is two dimensional, the equivalent code for real data is:

```
R = 0.0
DO J=LBOUND(ARRAY,2),UBOUND(ARRAY,2)
  DO I=LBOUND(ARRAY,1),UBOUND(ARRAY,1)
    R = R + ARRAY(I,J)
```

If the dimension argument is provided then only that dimension is summed:

```
R = SUM(ARRAY, dimension=2)
```

If the array is two dimensional, the equivalent code for real data is:

```
R(:) = 0.0
DO J=LBOUND(ARRAY,2),UBOUND(ARRAY,2)
  DO I=LBOUND(ARRAY,1),UBOUND(ARRAY,1)
    R(I) = R(I) + ARRAY(I,J)
```

If the mask argument is provided then the mask is used to determine whether the sum is applied:

```
R = SUM(ARRAY, mask=MOD(ARRAY, 2.0)==1)
```

If the array is two dimensional, the equivalent code for real data is:

```
R = 0.0
DO J=LBOUND(ARRAY,2),UBOUND(ARRAY,2)
  DO I=LBOUND(ARRAY,1),UBOUND(ARRAY,1)
    if (MOD(ARRAY(I,J), 2.0)==1):
      R = R + ARRAY(I,J)
```

For example:

```
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.transformations import Sum2CodeTrans
>>> code = ("subroutine sum_test(array,n,m)\n"
...        "  integer :: n, m\n"
...        "  real :: array(10,10)\n"
...        "  real :: result\n"
...        "  result = sum(array)\n"
...        "end subroutine\n")
>>> psyir = FortranReader().psyir_from_source(code)
>>> sum_node = psyir.children[0].children[0].children[1]
>>> Sum2CodeTrans().apply(sum_node)
>>> print(FortranWriter()(psyir))
subroutine sum_test(array, n, m)
```

(continues on next page)

(continued from previous page)

```
integer :: n
integer :: m
real, dimension(10,10) :: array
real :: result
real :: sum_var
integer :: i_0
integer :: i_1

sum_var = 0.0
do i_1 = 1, 10, 1
  do i_0 = 1, 10, 1
    sum_var = sum_var + array(i_0,i_1)
  enddo
enddo
result = sum_var

end subroutine sum_test
```

`apply(node, options=None)`

Apply the SUM intrinsic conversion transformation to the specified node. This node must be a SUM Operation which is converted to equivalent inline code.

Parameters

- `node` (`psyclone.psyir.nodes.IntrinsicCall`) – a Sum intrinsic.
- `options` (`Optional[Dict[str, Any]]`) – options for the transformation.

16.4 Algorithm-layer

The gocean1.0 API supports the transformation of the algorithm layer. In the future the LFRic (dynamo0.3) API will also support this. However, this is not relevant to the nemo API as it does not have the concept of an algorithm layer (just PSy and Kernel layers). The ability to transformation the algorithm layer is new and at this time no relevant transformations have been developed.

16.5 Kernels

PSyclone supports the transformation of Kernels as well as PSy-layer code. However, the transformation of kernels to produce new kernels brings with it additional considerations, especially regarding the naming of the resulting kernels. PSyclone supports two use cases:

1. the HPC expert wishes to optimise the same kernel in different ways, depending on where/how it is called;
2. the HPC expert wishes to transform the kernel just once and have the new version used throughout the Algorithm file.

The second case is really an optimisation of the first for the case where the same set of transformations is applied to every instance of a given kernel.

Since PSyclone is run separately for each Algorithm in a given application, ensuring that there are no name clashes for kernels in the application as a whole requires that some state is maintained between PSyclone invocations. This

is achieved by requiring that the same kernel output directory is used for every invocation of PSyclone when building a given application. However, this is under the control of the user and therefore it is possible to use the same output directory for a subset of algorithms that require the same kernel transformation and then a different directory for another subset requiring a different transformation. Of course, such use would require care when building and linking the application since the differently-optimised kernels would have the same names.

By default, transformed kernels are written to the current working directory. Alternatively, the user may specify the location to which to write the modified code via the `-okern` command-line flag.

In order to support the two use cases given above, PSyclone supports two different kernel-renaming schemes: “multiple” and “single” (specified via the `--kernel-renaming` command-line flag). In the default, “multiple” scheme, PSyclone ensures that each transformed kernel is given a unique name (with reference to the contents of the kernel output directory). In the “single” scheme, it is assumed that any given kernel that is transformed is always transformed in the same way (or left unchanged) and thus just one transformed version of it is created. This assumption is checked by examining the Fortran code for any pre-existing transformed version of that kernel. If another transformed version of that kernel exists and does not match that created by the current transformation then PSyclone will raise an exception.

16.5.1 Rules

Kernel code that is to be transformed is subject to certain restrictions. These rules are intended to make kernel transformations as robust as possible, in particular by limiting the amount of code that must be parsed by PSyclone (via `fparser`). The rules are as follows:

- 1) Any variable or procedure accessed by a kernel must either be explicitly declared or named in the only clause of a module use statement within the scope of the subroutine containing the kernel implementation. This means that:
 - 1) Kernel subroutines are forbidden from accessing data using `COMMON` blocks;
 - 2) Kernel subroutines are forbidden from calling procedures declared via the `EXTERN` statement;
 - 3) Kernel subroutines must not access data or procedures made available via their parent (containing) module.
- 2) The full Fortran source of a kernel must be available to PSyclone. This includes the source of any modules from which it accesses either routines or data. (However, kernel routines are permitted to make use of Fortran intrinsic routines.)

For instance, consider the following Fortran module containing the `bc_ssh_code` kernel:

```

module boundary_conditions_mod
  real :: forbidden_var

contains

  subroutine bc_ssh_code(ji, jj, istep, ssh)
    use kind_params_mod, only: go_wp
    use model_mod, only: rdt
    integer, intent(in) :: ji, jj, istep
    real(go_wp), dimension(:,:), intent(inout) :: ssh
    real(go_wp) :: rtime

    rtime = real(istep, go_wp) * rdt
    ...
  end subroutine bc_ssh_code
end module boundary_conditions_mod

```

Since the kernel subroutine accesses data (the `rdt` variable) from the `model_mod` module, the source of that module must be available to PSyclone if a transformation is applied to this kernel. Should `rdt` not actually be defined in `model_mod` (i.e. `model_mod` itself imports it from another module) then the source containing its definition must also be available to PSyclone. Note that the rules forbid the `bc_ssh_code` kernel from accessing the `forbidden_var` variable that is available to it from the enclosing module scope.

Note: these rules *only* apply to kernels that are the target of PSyclone kernel transformations.

16.5.2 Available Kernel Transformations

The transformations listed below have to be applied specifically to a PSyclone kernel. There are a number of transformations not listed here that can be applied to either or both the PSy-layer and Kernel-layer PSyIR.

Note: Some of these transformations modify the PSyIR tree of both the `InvokeSchedule` where the transformed `CodedKernel` is located and its associated `KernelSchedule`.

class `psyclone.transformations.ACCRoutineTrans`

Transform a kernel or routine by adding a “`!$acc routine`” directive (causing it to be compiled for the OpenACC accelerator device). For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCRoutineTrans
>>> rtrans = ACCRoutineTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>> kern = schedule.children[0].children[0].children[0]
>>> # Transform the kernel
>>> rtrans.apply(kern)
```

`apply(node, options=None)`

Add the ‘`!$acc routine`’ OpenACC directive into the code of the supplied Kernel (in a PSyKAI API such as GOcean or LFRic) or directly in the supplied Routine.

Parameters

- `node` (`psyclone.psyGen.Kern` or `psyclone.psyir.nodes.Routine`) – the kernel call or routine implementation to transform.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns

the name of this transformation class.

Return type

str

validate(*node*, *options*=None)

Perform checks that the supplied kernel or routine can be transformed.

Parameters

- *node* (psyclone.psyGen.Kern or psyclone.psyir.nodes.Routine) – the kernel which is the target of the transformation.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

- TransformationError – if the node is not a kernel or a routine.
- TransformationError – if the target is a built-in kernel.
- TransformationError – if it is a kernel but without an associated PSyIR.
- TransformationError – if any of the symbols in the kernel are accessed via a module use statement.

class psyclone.psyir.transformations.FoldConditionalReturnExpressionsTrans

Provides a transformation that folds conditional expressions with only a return statement inside so that the Return statement is moved to the end of the Routine and therefore it can be safely removed. This simplifies the control flow of the kernel to facilitate other transformations like kernel fusions. For example, the following code:

```
subroutine test(i)
  if (i < 5) then
    return
  endif
  if (i > 10) then
    return
  endif
  ! CODE
end subroutine
```

will be transformed to:

```
subroutine test(i)
  if (.not.(i < 5)) then
    if (.not.(i > 10)) then
      ! CODE
    endif
  endif
end subroutine
```

apply(*node*, *options*=None)

Apply this transformation to the supplied node.

Parameters

- *node* (psyclone.psyir.nodes.Routine) – the node to transform.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns the name of this transformation as a string.

`validate(node, options=None)`

Ensure that it is valid to apply this transformation to the supplied node.

Parameters

- node (`psyclone.psyir.nodes.Routine`) – the node to validate.
- options (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Raises

`TransformationError` – if the node is not a `Routine`.

`class psyclone.transformations.KernelImportsToArguments`

Transformation that removes any accesses of imported data from the supplied kernel and places them in the caller. The values/references are then passed by argument into the kernel.

`apply(node, options=None)`

Convert the imported variables used inside the kernel into arguments and modify the `InvokeSchedule` to pass the same imported variables to the kernel call.

Parameters

- node (`psyclone.psyGen.CodedKern`) – a kernel call.
 - options (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
-

Note: This transformation is only supported by the GOcean 1.0 API.

16.6 Applying

Transformations can be applied either interactively or through a script.

16.6.1 Interactive

To apply a transformation interactively we first parse and analyse the code. This allows us to generate a “vanilla” PSy layer. For example:

```
>>> from fparser.common.readfortran import FortranStringReader
>>> from psyclone.parse.algorithm import Parser
>>> from psyclone.psyGen import PSyFactory
>>> from fparser.two.parser import ParserFactory

>>> example_str = (
...     "program example\n"
...     "  use field_mod, only: field_type\n"
...     "  type(field_type) :: field\n"
...     "  call invoke(setval_c(field, 0.0))\n"
...     "end program example\n")
```

(continues on next page)

(continued from previous page)

```

>>> parser = ParserFactory().create(std="f2008")
>>> reader = FortranStringReader(example_str)
>>> ast = parser(reader)
>>> invoke_info = Parser().invoke_info(ast)

# This example uses the LFRic (dynamo0.3) API
>>> api = "dynamo0.3"

# Create the PSy-layer object using the invokeInfo
>>> psy = PSyFactory(api, distributed_memory=False).create(invoke_info)

# Optionally generate the vanilla PSy layer fortran
>>> print(psy.gen)
MODULE example_psy
  USE constants_mod, ONLY: r_def, i_def
  USE field_mod, ONLY: field_type, field_proxy_type
  IMPLICIT NONE
  CONTAINS
  SUBROUTINE invoke_0(field)
    TYPE(field_type), intent(in) :: field
    INTEGER df
    INTEGER(KIND=i_def) loop0_start, loop0_stop
    TYPE(field_proxy_type) field_proxy
    INTEGER(KIND=i_def) undf_aspc1_field
    !
    ! Initialise field and/or operator proxies
    !
    field_proxy = field%get_proxy()
    !
    ! Initialise number of DoFs for aspc1_field
    !
    undf_aspc1_field = field_proxy%vspace%get_undf()
    !
    ! Set-up all of the loop bounds
    !
    loop0_start = 1
    loop0_stop = undf_aspc1_field
    !
    ! Call our kernels
    !
    DO df=loop0_start,loop0_stop
      field_proxy%data(df) = 0.0
    END DO
    !
  END SUBROUTINE invoke_0
END MODULE example_psy

```

We then extract the particular schedule we are interested in. For example:

```

# List the various invokes that the PSy layer contains
>>> print(psy.invokes.names)
dict_keys(['invoke_0'])

```

(continues on next page)

(continued from previous page)

```

# Get the required invoke
>>> invoke = psy.invokes.get('invoke_0')

# Get the schedule associated with the required invoke
> schedule = invoke.schedule
> print(schedule.view())
InvokeSchedule[invoke='invoke_0', dm=True]
  0: Loop[type='dof', field_space='any_space_1', it_space='dof', upper_bound='ndofs']
    Literal[value:'NOT_INITIALISED', Scalar<INTEGER, UNDEFINED>]
    Literal[value:'NOT_INITIALISED', Scalar<INTEGER, UNDEFINED>]
    Literal[value:'1', Scalar<INTEGER, UNDEFINED>]
    Schedule[]
    0: BuiltIn setval_c(field,0.0)

```

Now we have the schedule we can create and apply a transformation to it to create a new schedule and then replace the original schedule with the new one. For example:

```

# Create an OpenMPPParallelLoopTrans
> from psyclone.transformations import OMPPParallelLoopTrans
> ol = OMPPParallelLoopTrans()

# Apply it to the loop schedule of the selected invoke
> ol.apply(schedule.children[0])
> print(schedule.view())

# Generate the Fortran code for the new PSy layer
> print(psy.gen)

```

16.6.2 Script

PSyclone provides a Python script (**psyclone**) that can be used from the command line to generate PSy layer code and to modify algorithm layer code appropriately. By default this script will generate “vanilla” (unoptimised) PSy-layer and algorithm layer code. For example:

```

> psyclone algspec.f90
> psyclone -oalg alg.f90 -opsy psy.f90 -api dynamo0.3 algspec.f90

```

The **psyclone** script has an optional **-s** flag which allows the user to specify a script file to modify the PSy layer as required. Script files may be specified without a path. For example:

```

> psyclone -s opt.py algspec.f90

```

In this case, the current directory is prepended to the Python search path **PYTHONPATH** which will then be used to try to find the script file. Thus, the search begins in the current directory and continues over any pre-existing directories in the search path, failing if the file cannot be found.

Alternatively, script files may be specified with a path. In this case the file must exist in the specified location. This location is then added to the Python search path **PYTHONPATH** as before. For example:

```
> psyclone -s ./opt.py algspec.f90
> psyclone -s ../scripts/opt.py algspec.f90
> psyclone -s /home/me/PSyclone/scripts/opt.py algspec.f90
```

PSyclone also provides the same functionality via a function (which is what the **psyclone** script calls internally).

```
####. autofunction:: psyclone.generator.generate #### :noindex:
```

A valid script file must contain a **trans** function which accepts a **PSy** object as an argument and returns a **PSy** object, i.e.:

```
>>> def trans(psy):
...     # ...
...     return psy
```

It is up to the script what it does with the **PSy** object. The example below does the same thing as the example in the *Interactive* section.

```
>>> def trans(psy):
...     from psyclone.transformations import OMPParallelLoopTrans
...     invoke = psy.invokes.get('invoke_0_v3_kernel_type')
...     schedule = invoke.schedule
...     ol = OMPParallelLoopTrans()
...     ol.apply(schedule.children[0])
...     return psy
```

In the gocean1.0 API (and in the future the lfrc (dynamo0.3) API) an optional **trans_alg** function may also be supplied. This function accepts **PSyIR** (representing the algorithm layer) as an argument and returns **PSyIR** i.e.:

```
>>> def trans_alg(psyir):
...     # ...
...     return psyir
```

As with the *trans()* function it is up to the script what it does with the algorithm **PSyIR**. Note that the *trans_alg()* script is applied to the algorithm layer before the **PSy**-layer is generated so any changes applied to the algorithm layer will be reflected in the **PSy** object that is passed to the *trans()* function.

For example, if the *trans_alg()* function in the script merged two *invoke* calls into one then the **Alg** object passed to the *trans()* function of the script would only contain one schedule associated with the merged invoke.

Of course the script may apply as many transformations as is required for a particular algorithm and/or schedule and may apply transformations to all the schedules (i.e. invokes and/or kernels) contained within the **PSy** layer.

Examples of the use of transformation scripts can be found in many of the examples, such as examples/lfrc/eg3 and examples/lfrc/scripts. Please read the examples/lfrc/README file first as it explains how to run the examples (and see also the examples/check_examples script).

An example of the use of a script making use of the *trans_alg()* function can be found in examples/gocean/eg7.

16.7 OpenMP

OpenMP is added to a code by using transformations. The OpenMP transformations currently supported allow the addition of:

- an **OpenMP Parallel** directive
- an **OpenMP Target** directive
- an **OpenMP Declare Target** directive
- an **OpenMP Do/For/Loop** directive
- an **OpenMP Single** directive
- an **OpenMP Master** directive
- an **OpenMP Taskloop** directive
- multiple **OpenMP Taskwait** directives; and
- an **OpenMP Parallel Do** directive.

The generic versions of these transformations (i.e. ones that theoretically work for all APIs) were given in the *Standard Functionality* section. The API-specific versions of these transformations are described in the API-specific sections of this document.

16.7.1 Reductions

PSyclone supports parallel scalar reductions. If a scalar reduction is specified in the Kernel metadata (see the API-specific sections for details) then PSyclone ensures the appropriate reduction is performed.

In the case of distributed memory, PSyclone will add **GlobalSum's** at the appropriate locations. As can be inferred by the name, only “summation” reductions are currently supported for distributed memory.

In the case of an OpenMP parallel loop the standard reduction support will be used by default. For example

```
!$omp parallel do, reduction(+:x)
!loop
!$omp end parallel do
```

OpenMP reductions do not guarantee to give bit reproducible results for different runs of the same problem even if the same problem is run using the same resources. The reason for this is that the order in which data is reduced is not mandated.

Therefore, an additional **reprod** option has been added to the **OpenMP Do** transformation. If the **reprod** option is set to “True” then the OpenMP reduction support is replaced with local per-thread reductions which are reduced serially after the loop has finished. This implementation guarantees to give bit-wise reproducible results for different runs of the same problem using the same resources, but will not bit-wise compare if the code is rerun with different numbers of OpenMP threads.

16.7.2 Restrictions

If two reductions are used within an OpenMP region and the same variable is used for both reductions then PSyclone will raise an exception. In this case the solution is to use a different variable for each reduction.

PSyclone does not support (distributed-memory) halo swaps or global sums within OpenMP parallel regions. Attempting to create a parallel region for a set of nodes that includes halo swaps or global sums will produce an error. In such cases it may be possible to re-order the nodes in the Schedule using the *MoveTrans* transformation.

16.7.3 OpenMP Tasking

PSyclone supports OpenMP Tasking, through the *OMPTaskloopTrans* and *OMPTaskwaitTrans* transformations. *OMPTaskloopTrans* transformations can be applied to loops, whilst the *OMPTaskwaitTrans* operator is applied to an OpenMP Parallel Region, and computes the dependencies caused by Taskloops, and adds OpenMP Taskwait statements to satisfy those dependencies. An example of using OpenMP tasking is available in *PSyclone/examples/nemo/eg1/openmp_taskloop_trans.py*.

16.8 OpenCL

OpenCL is added to a code by using the *GOOpenCLTrans* transformation (see the *Standard Functionality* Section above). Currently this transformation is only supported for the GOCean1.0 API and is applied to the whole InvokeSchedule of an Invoke. This transformation will add an OpenCL driver infrastructure to the PSy layer and generate an OpenCL kernel for each of the Invoke kernels. This means that all kernels in that Invoke will be executed on the OpenCL device. The PSy-layer OpenCL code generated by PSyclone is still Fortran and makes use of the FortCL library (<https://github.com/stfc/FortCL>) to access OpenCL functionality. It also relies upon the device acceleration support provided by the *dl_esm_inf* library (https://github.com/stfc/dl_esm_inf).

Note: The generated OpenCL kernels are written in a file called `openc1_kernels_<index>.cl` where the index keeps increasing if the file name already exist.

The *GOOpenCLTrans* transformation accepts an *options* argument with a map of optional parameters to tune the OpenCL host code in the PSy layer. These options will be attached to the transformed InvokeSchedule. The current available options are:

Option	Description	Default
<code>end_barrier</code>	Whether a synchronization barrier should be placed at the end of the Invoke.	True
<code>enable_profiling</code>	Enables the profiling of OpenCL Kernels.	False
<code>out_of_order</code>	Allows the OpenCL implementation to execute the enqueued kernels out-of-order.	False

Additionally, each individual kernel (inside the Invoke that is going to be transformed) also accepts a map of options which are provided by the *set_openc1_options()* method of the *Kern* object. This can affect both the driver layer and/or the OpenCL kernels. The current available options are:

Option	Description	Default
<code>local_size</code>	Number of work-items to group together in a work-group execution (kernel instances executed at the same time).	64
<code>queue_number</code>	Identifier of the OpenCL command_queue to which the kernel should be submitted. If the kernel has a dependency on another kernel submitted to a different command_queue a barrier will be added to guarantee the execution order.	1

Below is an example of a PSyclone script that uses a GOOpenCLTrans with multiple InvokeSchedule and kernel-specific optimization options.

```

1 from psyclone.psyir.transformations import \
2     FoldConditionalReturnExpressionsTrans
3 from psyclone.domain.gocean.transformations import GOOpenCLTrans, \
4     GOMoveIterationBoundariesInsideKernelTrans
5
6
7 def trans(psy):
8     """
9     Transformation routine for use with PSyclone. Applies the OpenCL
10    transform to the first Invoke in the psy object.
11
12    :param psy: the PSy object which this script will transform.
13    :type psy: :py:class:`psyclone.psyGen.PSy`
14    :returns: the transformed PSy object.
15    :rtype: :py:class:`psyclone.psyGen.PSy`
16
17    """
18    ocl_trans = GOOpenCLTrans()
19    fold_trans = FoldConditionalReturnExpressionsTrans()
20    move_boundaries_trans = GOMoveIterationBoundariesInsideKernelTrans()
21
22    # Get the Schedule associated with the first Invoke
23    invoke = psy.invokes.invoke_list[0]
24    sched = invoke.schedule
25
26    # Provide kernel-specific OpenCL optimization options
27    for idx, kern in enumerate(sched.kernels()):
28        # Move the PSy-layer loop boundaries inside the kernel as a kernel
29        # mask, this allows to iterate through the whole domain
30        move_boundaries_trans.apply(kern)
31        # Change the syntax to remove the return statements introduced by the
32        # previous transformation
33        fold_trans.apply(kern.get_kernel_schedule())
34        # Specify the OpenCL queue and workgroup size of the kernel
35        # In this case we dispatch each kernel in a different queue to check
36        # that the output code has the necessary barriers to guarantee the
37        # kernel execution order.
38        kern.set_opencl_options({"queue_number": idx+1, 'local_size': 4})
39
40    # Transform the Schedule
41    ocl_trans.apply(sched, options={"end_barrier": True})

```

OpenCL delays the decision of which and where kernels will execute until run-time, therefore it is important to use the environment variables provided by FortCL and DL_ESM_INF to inform how things should execute. Specifically:

- FORTCL_KERNELS_FILE: Point to the file containing the kernels to execute, they can be compiled ahead-of-time or providing the source for JIT compilation. To link more than a single kernel, one must merge all the kernels generated by PSyclone in a single source file.
- FORTCL_PLATFORM: If the system has more than 1 OpenCL platform. This environment variable may be used to select which platform on which to execute the kernels.
- DL_ESM_ALIGNMENT: When using OpenCL <= 1.2 the local_size should be exactly divisible by the

total size. If this is not the case some implementations fail silently. A way to solve this issue is to set the `DL_ESM_ALIGNMENT` variable to be equal to the local size.

Note: The OpenCL generation can be combined with distributed memory generation. In the case where there is more than one accelerator available on each node, the PSyclone configuration file parameter `OCL_DEVICES_PER_NODE` has to be set to the appropriate value and the number of MPI-ranks-per-node set by the `mpirun` command has to match this value accordingly.

For instance if there are 2 accelerators per nodes, `psyclone.cfg` should have `OCL_DEVICES_PER_NODE=2` and the program must be executed with `mpirun -n <total_ranks> -ppn 2 ./application` (Note: `-ppn` is an Intel MPI specific parameter, use equivalent configuration parameters for other MPI implementations.)

For example, an execution of a PSyclone generated OpenCL code using all the mentioned run-time configuration options could look something like:

```
FORTCL_PLATFORM=3 FORTCL_KERNELS_FILE=allkernels.cl DL_ESM_ALIGNMENT=64 \
mpirun -n 2 ./application.exe
```

16.9 OpenACC

PSyclone supports the generation of code targetting GPUs through the addition of OpenACC directives. This is achieved by a user applying various OpenACC transformations to the PSyIR before the final Fortran code is generated. The steps to parallelisation are very similar to those in OpenMP with the added complexity of managing the movement of data to and from the GPU device. For the latter task PSyclone provides the `ACCDDataTrans` and `ACCEnterDataTrans` transformations, as described in the [Standard Functionality](#) Section above. These two transformations add statically- and dynamically-scoped data regions, respectively. The former manages what data is on the remote device for a specific section of code while the latter allows run-time control of data movement. This second option is essential for minimising data movement as, without it, PSyclone-generated code would move data to and from the device upon every entry/exit of an `Invoke`. The first option is mainly provided as an aid to incremental porting and/or debugging of an OpenACC application as it provides explicit control over what data is present on a device for a given (part of an) `Invoke` routine.

The PGI compiler provides an alternative approach to controlling data movement through its ‘unified memory’ option (`-ta=tesla:managed`). When this is enabled the compiler itself takes on the task of ensuring that data is copied to/from the GPU when required. (Note that this approach can struggle with Fortran code containing derived types however.)

As well as ensuring the correct data is copied to and from the remote device, OpenACC directives must also be added to a code in order to tell the compiler how it should be parallelised. PSyclone provides the `ACCKernelsTrans`, `ACCPParallelTrans` and `ACCLoopTrans` transformations for this purpose. The simplest of these is `ACCKernelsTrans` (currently only supported for the NEMO and Dynamo0.3 APIs) which encloses the code represented by a sub-tree of the PSyIR within an OpenACC kernels region. This essentially gives free-reign to the compiler to automatically parallelise any suitable loops within the specified region. An example of the use of `ACCDDataTrans` and `ACCKernelsTrans` may be found in `PSyclone/examples/nemo/eg3` and an example of `ACCKernelsTrans` may be found in `PSyclone/examples/lfric/eg14`.

However, as with any “automatic” approach, a more performant solution can almost always be obtained by providing the compiler with more explicit direction on how to parallelise the code. The `ACCPParallelTrans` and `ACCLoopTrans` transformations allow the user to define thread-parallel regions and, within those, define which loops should be parallelised. For an example of their use please see `PSyclone/examples/gocean/eg2` or `PSyclone/examples/lfric/eg14`.

In order for a given section of code to be executed on a GPU, any routines called from within that section must also have been compiled for the GPU. This then requires either that any such routines are in-lined or that the OpenACC routine directive be added to any such routines. This situation will occur routinely in those PSyclone APIs that use the PSyKAl separation of concerns since the user-supplied kernel routines are called from within PSyclone-generated loops

in the PSy layer. PSyclone therefore provides the ACCRoutineTrans transformation which, given a Kernel node in the PSyIR, creates a new version of that kernel with the routine directive added. See either PSyclone/examples/gocean/eg2 or PSyclone/examples/lfric/eg14 for an example (although please note that this transformation is not yet fully working for kernels in the LFRic (Dynamo0.3) API - see #1724).

16.10 SIR

It is currently not possible for PSyclone to output SIR code without using a script. Three examples of such scripts are given in example 4 for the NEMO API. The first *sir_trans.py* simply outputs SIR. This will raise an exception if used with the *tracer advection* example as the example contains array-index notation which is not supported by the SIR backend, but will generate code for the other examples. The second, *sir_trans_loop.py* includes transformations to hoist code out of a loop, translate array-index notation into explicit loops and translate a single access to an array dimension to a one-trip loop (to make the code suitable for the SIR backend). This works with the *tracer-advection* example. The third script *sir_trans_all.py* additionally replaces any intrinsics with equivalent code and can also be used with the *tracer-advection* example (and the *intrinsic_example.f90* example).

DISTRIBUTED MEMORY

PSyclone supports the generation of code for distributed memory machines. When this option is switched on, PSyclone takes on responsibility for both performance and correctness, as described below.

17.1 Correctness

PSyclone is responsible for adding appropriate distributed memory communication calls to the PSy layer to ensure that the distributed memory code runs correctly. For example, a stencil operation will require halo exchanges between the different processes.

The burden of correctly placing distributed memory communication calls has traditionally been born by the user. However, PSyclone is able to determine the placing of these within the PSy-layer, thereby freeing the user from this responsibility. Thus, the Algorithm and Kernel code remain the same, irrespective of whether the target architecture does or does not require a distributed memory solution.

17.2 Performance

PSyclone adds **HaloExchange** and **GlobalSum** objects to the generated PSyIR **InvokeSchedule** at the required locations. The halo-exchange and global-sum objects are exposed here for the purposes of optimisation. For example the halo-exchange and/or global-sum objects may be moved in the schedule (via appropriate transformations) to enable overlap of computation with communication.

Note: When these optimisations are implemented, add a reference to the *Transformations* Section.

A halo exchange is required with distributed memory when a processor requires data from its halo and the halo information is out of date. One example is where a field is written to and then read using a stencil access. Halo exchanges have performance implications so should only be used where necessary.

A global sum is required with distributed memory when a scalar is written to. Global sums can have performance implications so should only be used where necessary. Global sums currently only occur in certain Built-in kernels. The description of Built-ins indicates when this is the case.

17.3 Implementation

Within the contents of an `invoke()` call, PSyclone is able to statically determine which communication calls are required and where they should be placed. However, PSyclone has no information on what happens outside `invoke()` calls and thus is unable to statically determine whether communication is required between these calls. The solution we use is to add run-time flags in the PSy layer to keep track of whether data has been written to and read from. These flags are then used to determine whether communication calls are required upon entry to an `invoke()`.

17.4 Control

Support for distributed memory can be switched on or off with the default being on. The default can be changed permanently by modifying the `DISTRIBUTED_MEMORY` variable in the `psyclone.cfg` configuration file to false (see [Configuration](#)).

Distributed memory can be switched on or off from the `psyclone` script using the `-dm/--dist_mem` or `-nodm/--no_dist_mem` flags, respectively.

For interactive access, the distributed memory option can be changed interactively from the `PSyFactory` class by setting the optional `distributed_memory` flag; for example:

```
psy = PSyFactory(api=api, distributed_memory=False)
```

Similarly the distributed memory option can be changed interactively from the `generate` function by setting the optional `distributed_memory` flag, e.g.:

```
psy, alg = generate("file.f90", distributed_memory=False).
```

17.5 Status

Distributed memory support is currently supported by the `dynamo0.3` and the `gocean1p0` APIs. The remaining APIs ignore the distributed memory flag and continue to produce code without any distributed memory functionality, irrespective of its value.

PSYCLONE KERNEL TOOLS

In addition to the `psyclone` command, the PSyclone package also provides tools related to generating code purely from kernel metadata. Currently there are two such tools:

1. *Kernel-stub Generator*
2. *Algorithm Generator*

The kernel-stub generator takes a file containing kernel metadata as input and outputs the (Fortran) kernel subroutine arguments and declarations. The word “stub” is used to indicate that it is only the subroutine arguments and their declarations that are generated; the subroutine has no content.

The algorithm generator also takes a file containing a kernel implementation but this time generates an appropriate algorithm layer subroutine. This algorithm layer plus the associated kernel metadata may then be processed with PSyclone in the usual way to generate code which executes the supplied kernel.

This functionality is provided to the user via the `psyclone-kern` command, described in more detail below.

18.1 The `psyclone-kern` Command

Before using the `psyclone-kern` tool, PSyclone must be installed. If you have not already done so, please follow the instructions for setting up PSyclone in Section *Getting Going*.

PSyclone will be installed in a particular location on your machine, which will be referred to as the `<PSYCLONE-INSTALL>` directory. The `psyclone-kern` script comes with the PSyclone installation. A quick check `>` which `psyclone-kern` should return the location of the `<PSYCLONEINSTALL>/bin` directory.

The `psyclone-kern` command has the following arguments:

```
> psyclone-kern -h
usage: psyclone-kern [-h] [-gen {alg,stub}] [-o OUT_FILE] [-api API]
                    [-I INCLUDE] [-l {off,all,output}]
                    [--config CONFIG] [-v]
                    filename
```

Run the PSyclone kernel generator on a particular file

positional arguments:

filename file containing Kernel metadata

optional arguments:

-h, --help show this *help* message and *exit*
-gen {alg,stub} what to generate *for* the supplied kernel

(continues on next page)

(continued from previous page)

```

        (alg=algorithm layer, stub=kernel-stub subroutine).
        Defaults to stub.
-o OUT_FILE      filename for created code.
-api API         choose a particular API from ['dynamo0.3',
        'gocean1.0', 'nemo'], default 'dynamo0.3'.
-I INCLUDE, --include INCLUDE
        path to Fortran INCLUDE or module files
-l {off,all,output}, --limit {off,all,output}
        limit the Fortran line length to 132
        characters (default 'off'). Use 'all' to
        apply limit to both input and output
        Fortran. Use 'output' to apply line-length
        limit to output Fortran only.
--config CONFIG  config file with PSyclone specific options.
-v, --version    display version information (\ |release|\ )

```

The `-o` option allows the user to specify that the output should be written to a particular file. If this is not specified then the Python print statement is used to write to stdout. Typically this results in the output being printed to the terminal.

As is indicated when using the `-h` option, the `-api` option only accepts dynamo0.3 (LFRic) at the moment and is redundant as this option is also the default. However the number of supported APIs is expected to expand in the future.

The `-l`, or `--limit` option utilises the PSyclone support for wrapping of lines within the 132 character limit in the generated Fortran code (please see the [Line Length](#) chapter for more details).

18.2 Kernel-stub Generator

18.2.1 Quick Start

- 1) Use an existing Kernel file or create a Kernel file containing a Kernel module with the required metadata and an empty Kernel subroutine with no arguments.
- 2) Run the following command

```
> psyclone-kern -gen stub <PATH>/my_file.f90
```

- 3) To have the generated code written to file rather than stdout use the `-o` flag

```
> psyclone-kern -gen stub -o my_stub_file.f90 ./my_kernel_mod.f90
```

(Since stub generation is the default, the `-gen stub` may be omitted if desired.)

18.2.2 Introduction

PSyclone provides a kernel stub generator for the LFRic (Dynamo 0.3) API. The kernel stub generator takes a kernel file as input and outputs the kernel subroutine arguments and declarations. The word “stub” is used to indicate that it is only the subroutine arguments and their declarations that are generated; the subroutine has no content.

The primary reason the stub generator is useful is that it generates the correct Kernel subroutine arguments and declarations for the LFRic API as specified by the Kernel metadata. As the number of arguments to Kernel subroutines can become large and the arguments have to follow a particular order, it can become burdensome, and potentially error prone, for the user to have to work out the appropriate argument list if written by hand.

The stub generator can be used when creating a new Kernel. A Kernel can first be written to specify the required metadata and then the generator can be used to create the appropriate (empty) Kernel subroutine. The user can then fill in the content of the subroutine.

The stub generator can also be used to check whether the arguments for an existing Kernel are correct i.e. whether the Kernel subroutine and Kernel metadata are consistent. One example would be where a Kernel is updated resulting in a change to the metadata and subroutine arguments.

The LFRic API requires Kernels to conform to a set of rules which determine the required arguments and types for a particular Kernel. These rules are required as the generated PSy layer needs to know exactly how to call a Kernel. These rules are outlined in Section [Rules](#).

Therefore PSyclone has been coded with the LFRic API rules which are then applied when reading the Kernel metadata to produce the required Kernel call and its arguments in the generated PSy layer. These same rules are used by the Kernel stub generator to produce Kernel subroutine stubs, thereby guaranteeing that Kernel calls from the PSy layer and the associated Kernel subroutines are consistent.

18.2.3 Kernels

Any LFRic kernel can be used as input to the stub generator. Example Kernels can be found in the examples/lfric repository or, for more simple cases, in the tests/test_files/dynamo0p3 directory. These directories are located in the <PSYCLONEHOME>/src/psyclone directory where <PSYCLONEHOME> refers to the location where you download or clone PSyclone ([Getting Going](#)).

In the tests/test_files/dynamo0p3 directory the majority of examples start with testkern. Amongst the exceptions are: simple.f90, ru_kernel_mod.f90 and matrix_vector_kernel_mod.F90. The following test kernels can be used to generate kernel stub code (running stub generation from the <PSYCLONEHOME>/src/psyclone directory):

```
tests/test_files/dynamo0p3/testkern_chi_read_mod.F90
tests/test_files/dynamo0p3/testkern_coord_w0_mod.F90
tests/test_files/dynamo0p3/testkern_operator_mod.f90
tests/test_files/dynamo0p3/testkern_operator_nofield_mod.f90
tests/test_files/dynamo0p3/ru_kernel_mod.f90
tests/test_files/dynamo0p3/simple.f90
```

18.2.4 Example

A simple, single field example of a kernel that can be used as input for the stub generator is found in tests/test_files/dynamo0p3/simple.f90 and is shown below:

```
module simple_mod

  use argument_mod
  use fs_continuity_mod
  use kernel_mod
  use constants_mod

  implicit none

  type, extends(kernel_type) :: simple_type
    type(arg_type), dimension(1) :: meta_args = &
      (/ arg_type(gh_field, gh_real, gh_inc, w1) /)
    integer :: operates_on = cell_column
```

(continues on next page)

(continued from previous page)

```
contains
  procedure, nopass :: code => simple_code
end type simple_type

contains

  subroutine simple_code()
  end subroutine

end module simple_mod
```

Note: The module name `simple_mod` and the type name `simple_type` share the same root `simple` and have the extensions `_mod` and `_type` respectively. This is a convention in LFRic API and is required by the kernel stub generator as it needs to determine the name of the type containing the metadata and infers this by reading the module name. If this rule is not followed the kernel stub generator will return with an error message (see Section [Errors](#)).

Note: Whilst strictly the kernel stub generator only requires the Kernel metadata to generate the appropriate stub code, the parser that the generator relies on currently requires a dummy kernel subroutine to exist.

If we run the kernel stub generator on the `simple.f90` example:

```
> psyclone-kern -gen stub tests/test_files/dynamo0p3/simple.f90
```

we get the following kernel stub output:

```
MODULE simple_mod
  IMPLICIT NONE
  CONTAINS
  SUBROUTINE simple_code(nlayers, field_1_w1, ndf_w1, undf_w1, map_w1)
    USE constants_mod, ONLY: r_def, i_def
    IMPLICIT NONE
    INTEGER(KIND=i_def), intent(in) :: nlayers
    INTEGER(KIND=i_def), intent(in) :: ndf_w1
    INTEGER(KIND=i_def), intent(in), dimension(ndf_w1) :: map_w1
    INTEGER(KIND=i_def), intent(in) :: undf_w1
    REAL(KIND=r_def), intent(inout), dimension(undf_w1) :: field_1_w1
  END SUBROUTINE simple_code
END MODULE simple_mod
```

The subroutine content can then be copied into the required module, used as the basis for a new module, or checked with an existing subroutine for correctness.

Note: The output does not currently conform to Met Office coding standards so must be modified accordingly.

Note: The code will not compile without a) providing the `constants_mod`, `argument_mod` and `kernel_mod` modules in the compiler include path and b) adding in code that writes to any arguments declared as `intent out` or `inout`. For a quick check, the `USE` declaration and `KIND` declarations can be removed and the `field_1_w1` array can

be initialised with some value in the subroutine. At this point the Kernel should compile successfully.

Note: Whilst there is only one field declared in the metadata there are 5 arguments to the Kernel. The first argument `nlayers` specifies the number of layers in a column for a field. The second argument is the array associated with the field. The field array is dimensioned as the *number of unique degrees of freedom* (hereafter `undf`) which is also passed into the kernel (the fourth argument). The naming convention is to call each field a `field`, followed by its position in the (algorithm) argument list (which is reflected in the metadata ordering). The third argument is the number of degrees of freedom for the particular column and is used to dimension the final argument which is the *degrees of freedom map* (`dofmap`) which indicates the location of the required values in the field array. The naming convention for the `dofmap`, `undf` and `ndf` is to append the name with the space that it is associated with.

We now take a look at a more complicated example. The metadata in this example is the same as an actual LFRic (Dynamo 0.3) kernel, however the subroutine content and various comments have been removed. The metadata specifies that there are four fields passed by the algorithm layer, the fourth of which is a vector field of size three. All three of the spaces require a basis function and the `W0` and `W2` function spaces additionally require a differential basis function. The content of the Kernel, excluding the subroutine body, is given below:

```

module ru_kernel_mod

use argument_mod
use fs_continuity_mod
use kernel_mod
use constants_mod

implicit none

private

type, public, extends(kernel_type) :: ru_kernel_type
  private
  type(arg_type) :: meta_args(6) = (/
    arg_type(GH_FIELD, GH_REAL, GH_INC, W2),      &
    arg_type(GH_FIELD, GH_REAL, GH_READ, W3),    &
    arg_type(GH_SCALAR, GH_INTEGER, GH_READ),    &
    arg_type(GH_SCALAR, GH_REAL, GH_READ),        &
    arg_type(GH_FIELD, GH_REAL, GH_READ, W0),    &
    arg_type(GH_FIELD*3, GH_REAL, GH_READ, W0)    &
  /)
  type(func_type) :: meta_funcs(3) = (/
    func_type(W2, GH_BASIS, GH_DIFF_BASIS),      &
    func_type(W3, GH_BASIS),                     &
    func_type(W0, GH_BASIS, GH_DIFF_BASIS)        &
  /)
  integer :: operates_on = CELL_COLUMN
  integer :: gh_shape = gh_quadrature_XYZ
contains
  procedure, nopass :: ru_code
end type

public ru_code

```

(continues on next page)

(continued from previous page)

```
contains

  subroutine ru_code()
  end subroutine ru_code

end module ru_kernel_mod
```

If we run the kernel stub generator on this example:

```
> psyclone-kern -gen stub tests/test_files/dynamo0p3/ru_kernel_mod.f90
```

we obtain the following output:

```
MODULE ru_mod
  IMPLICIT NONE
  CONTAINS
  SUBROUTINE ru_code(nlayers, field_1_w2, field_2_w3, iscalar_3, rscalar_4, &
    field_5_w0, field_6_w0_v1, field_6_w0_v2, field_6_w0_v3, &
    ndf_w2, undf_w2, map_w2, basis_w2_qr_xyoz, &
    diff_basis_w2_qr_xyoz, ndf_w3, undf_w3, map_w3, &
    basis_w3_qr_xyoz, ndf_w0, undf_w0, map_w0, &
    basis_w0_qr_xyoz, diff_basis_w0_qr_xyoz, &
    np_xy_qr_xyoz, np_z_qr_xyoz, weights_xy_qr_xyoz, weights_z_qr_xyoz)
    USE constants_mod, ONLY: r_def, i_def
    IMPLICIT NONE
    INTEGER(KIND=i_def), intent(in) :: nlayers
    INTEGER(KIND=i_def), intent(in) :: ndf_w0
    INTEGER(KIND=i_def), intent(in), dimension(ndf_w0) :: map_w0
    INTEGER(KIND=i_def), intent(in) :: ndf_w2
    INTEGER(KIND=i_def), intent(in), dimension(ndf_w2) :: map_w2
    INTEGER(KIND=i_def), intent(in) :: ndf_w3
    INTEGER(KIND=i_def), intent(in), dimension(ndf_w3) :: map_w3
    INTEGER(KIND=i_def), intent(in) :: undf_w2, undf_w3, undf_w0
    REAL(KIND=r_def), intent(in) :: rscalar_4
    INTEGER(KIND=i_def), intent(in) :: iscalar_3
    REAL(KIND=r_def), intent(inout), dimension(undf_w2) :: field_1_w2
    REAL(KIND=r_def), intent(in), dimension(undf_w3) :: field_2_w3
    REAL(KIND=r_def), intent(in), dimension(undf_w0) :: field_5_w0
    REAL(KIND=r_def), intent(in), dimension(undf_w0) :: field_6_w0_v1
    REAL(KIND=r_def), intent(in), dimension(undf_w0) :: field_6_w0_v2
    REAL(KIND=r_def), intent(in), dimension(undf_w0) :: field_6_w0_v3
    INTEGER(KIND=i_def), intent(in) :: np_xy_qr_xyoz, np_z_qr_xyoz
    REAL(KIND=r_def), intent(in), dimension(3,ndf_w2,np_xy_qr_xyoz,np_z_qr_xyoz) ::
    ↪ basis_w2_qr_xyoz
    REAL(KIND=r_def), intent(in), dimension(1,ndf_w2,np_xy_qr_xyoz,np_z_qr_xyoz) ::
    ↪ diff_basis_w2_qr_xyoz
    REAL(KIND=r_def), intent(in), dimension(1,ndf_w3,np_xy_qr_xyoz,np_z_qr_xyoz) ::
    ↪ basis_w3_qr_xyoz
    REAL(KIND=r_def), intent(in), dimension(1,ndf_w0,np_xy_qr_xyoz,np_z_qr_xyoz) ::
    ↪ basis_w0_qr_xyoz
    REAL(KIND=r_def), intent(in), dimension(3,ndf_w0,np_xy_qr_xyoz,np_z_qr_xyoz) ::
    ↪ diff_basis_w0_qr_xyoz
```

(continues on next page)

(continued from previous page)

```

REAL(KIND=r_def), intent(in), dimension(np_xy_qr_xyoz) :: weights_xy_qr_xyoz
REAL(KIND=r_def), intent(in), dimension(np_z_qr_xyoz) :: weights_z_qr_xyoz
END SUBROUTINE ru_code
END MODULE ru_mod

```

The above example demonstrates that the argument list can get quite complex. Rather than going through an explanation of each argument you are referred to Section [Rules](#) for more details on the rules for argument types and argument ordering. Regarding naming conventions for arguments you can see that the arrays associated with the fields are labelled as 1-6 depending on their position in the metadata. For a vector field, each vector results in a different array. These are distinguished by appending `_vx` where `x` is the number of the vector.

The introduction of stencil operations on field arguments further complicates the argument list of a kernel. An example of the use of the stub generator for a kernel that performs stencil operations is provided in `examples/lfric/eg5`:

```
> psyclone-kern -gen stub ../../examples/lfric/eg5/conservative_flux_kernel_mod.F90
```

18.2.5 Errors

The stub generator has been written to provide useful errors if mistakes are found. If you run the generator and it does not produce a useful error - and in particular if it produces a stack trace - please contact the PSyclone developers.

The following tests do not produce stub kernel code either because they are invalid or because they contain functionality that is not supported in the stub generator:

```

tests/test_files/dynamo0p3/testkern_any_space_1_mod.f90
tests/test_files/dynamo0p3/testkern_any_space_4_mod.f90
tests/test_files/dynamo0p3/testkern_any_discontinuous_space_op_2_mod.f90
tests/test_files/dynamo0p3/testkern_dofs_mod.f90
tests/test_files/dynamo0p3/testkern_invalid_fortran.F90
tests/test_files/dynamo0p3/testkern_short_name.F90
tests/test_files/dynamo0p3/testkern_no_datatype.F90
tests/test_files/dynamo0p3/testkern_qr.F90

```

`testkern_invalid_fortran.F90`, `testkern_no_datatype.F90`, `testkern_short_name.F90` and `testkern_qr.F90` are designed to be invalid for PSyclone stub generation testing purposes and should produce appropriate errors. Two examples are below:

```

> psyclone-kern -gen stub tests/test_files/dynamo0p3/testkern_invalid_fortran.F90
Error: 'Parse Error: Code appears to be invalid Fortran'

> psyclone-kern -gen stub tests/test_files/dynamo0p3/testkern_no_datatype.F90
Error: 'Parse Error: Kernel type testkern_type does not exist'

```

`testkern_dofs_mod.f90` is an example with an unsupported feature, as the `operates_on` metadata specifies `dof`. Currently only kernels with `operates_on=CELL_COLUMN` are supported by the stub generator.

Generic function space metadata `any_space` and `any_discontinuous_space` (see Section [Supported Function Spaces](#) for function-space identifiers) are currently only supported for *LFRic (Dynamo 0.3) fields* in the stub generator. Basis and differential basis functions on these generic function spaces, required for *quadrature* and *evaluators*, are not supported. Hence, `testkern_any_space_1_mod.f90`, `testkern_any_space_4_mod.f90` and `testkern_any_discontinuous_space_op_2_mod.f90` should fail with appropriate warnings because of that. For example:

```
> psyclone-kern -gen stub tests/test_files/dynamo0p3/testkern_any_space_1_mod.f90
Error: "Generation Error: Unsupported space for basis function, expecting
one of ['w3', 'wtheta', 'w2v', 'w2vtrace', 'w2broken', 'w0', 'w1', 'w2',
'w2trace', 'w2h', 'w2htrace', 'any_w2', 'wchi'] but found 'any_space_1'"
```

As noted above, if the LFRic API naming convention for module and type names is not followed, the stub generator will return with an error message. For example:

```
> psyclone-kern -gen stub tests/test_files/dynamo0p3/testkern_qr.F90
Error: "Parse Error: Error, module name 'testkern_qr' does not have
'__mod' as an extension. This convention is assumed."
```

18.3 Algorithm Generator

18.3.1 Quick Start

- 1) Use an existing Kernel file containing a full LFRic kernel implementation.
- 2) Run the following command

```
> psyclone-kern -gen alg <PATH>/my_kern_file_mod.f90
```

- 3) The generated Algorithm code will be output to stdout by default. To have it written to a file use the `-o` flag.

18.3.2 Introduction

The ability to generate a valid LFRic Algorithm layer that calls a given kernel is useful for a number of reasons:

- 1) Starting point for creating a test for a kernel;
- 2) Benchmarking an individual kernel;
- 3) Constructing a test harness for the adjoint of a kernel produced by [PSyAD](#).

Currently algorithm generation is only supported for the LFRic (Dynamo 0.3) API but it could be extended to the GOcean API if desired.

Mapping of Function Spaces

Every field or operator argument to an LFRic kernel must have its function space(s) specified in the metadata of the kernel. This information is used by the algorithm generation to ensure that each kernel argument is correctly constructed. However, the metadata permits the use of certain ‘generic’ function-space specifiers (see [Supported Function Spaces](#)). If an argument is specified as being on one of these spaces then the algorithm generator chooses an appropriate, specific function space for that argument. e.g. an argument that is specified as being on `ANY_SPACE_<n>` will be constructed on `W0` while one on `ANY_DISCONTINUOUS_SPACE_<n>` will be constructed on `W3`.

18.3.3 Example

If we take the same kernel used in the stub-generation *example* then running

```
> psyclone-kern -gen alg tests/test_files/dynamo0p3/simple.f90
```

gives the following algorithm layer code:

```
module test_alg_mod
  implicit none
  public

  contains
  subroutine test_alg(mesh, chi, panel_id)
    use field_mod, only : field_type
    use function_space_mod, only : function_space_type
    use fs_continuity_mod, only : w1
    use function_space_collection_mod, only : function_space_collection
    use mesh_mod, only : mesh_type
    use simple_mod, only : simple_type
    use constants_mod, only : i_def, r_def
    integer(kind=i_def), parameter :: element_order = 1_i_def
    type(mesh_type), pointer, intent(in) :: mesh
    type(field_type), dimension(3), intent(in), optional :: chi
    type(field_type), intent(in), optional :: panel_id
    TYPE(function_space_type), POINTER :: vector_space_w1_ptr
    type(field_type) :: field_1

    vector_space_w1_ptr => function_space_collection % get_fs(mesh, element_order, w1)
    call field_1 % initialise(vector_space=vector_space_w1_ptr, name='field_1')
    call invoke(setval_c(field_1, 1.0_r_def), simple_type(field_1))

  end subroutine test_alg
end module test_alg_mod
```

Note that the generated code implements an Algorithm subroutine that is intended to be called from within an LFRic application that has already setup data structures for the mesh (and, optionally, the *chi* coordinate field and panel ID mapping). Since the *metadata* for the *simple_type* kernel specifies that the field argument is on *W1*, the generated code must ensure that the appropriate function space is set up and used to initialise the field. Once that's done, the interesting part is the *invoke* call:

```
call invoke(setval_c(field_1, 1.0_r_def), &
           simple_type(field_1))
```

(where a line-break has been added for clarity). In this example the *invoke* is for two kernels: the first is a *Built-in* that gives *field_1* the value *1.0* everywhere and the second is the ‘simple’ kernel itself which is passed the now initialised *field_1*.

This Algorithm code can now be processed by PSyclone in the normal way in order to generate a transformed version plus an associated PSy-layer routine. See *Example 20: Algorithm Generation* for a full example of doing this.

18.3.4 Limitations

- Algorithm generation is only currently supported for the LFRic (dynamo 0.3) API.
- All fields are currently set to unity. Obviously the generated algorithm code may be edited to change this.
- The generator does not currently recognise ‘special’ fields that hold geometry information (such as Chi or the face IDs) and these too will all be initialised to unity. This is the subject of Issue #1708 (although note that the generated code already permits the caller to supply Chi and/or face IDs).
- Kernels with operator arguments are not yet supported.
- Kernels with stencil accesses are not yet supported.

LINE LENGTH

By default PSyclone will generate Fortran code with no consideration of Fortran line-length limits. As the line-length limit for free-form Fortran is 132 characters, the code that is output may be non-conformant.

Line length is not an issue for many compilers as they allow compiler flags to be set which allow lines longer than the Fortran standard. However this is not the case for all compilers.

PSyclone therefore supports the wrapping of lines within the 132 character limit. The next two sections discuss how this is done when scripting and when working interactively respectively.

19.1 Script

The *psyclone* script provides the `-l` option to wrap lines. Please see the *Fortran line length* section for more details.

19.2 Interactive

When using PSyclone interactively the line lengths of the input algorithm and Kernel files can be checked by setting the `psyclone.parse.algorithm.parse()` function's `line_length` argument to `True`.

```
>>> from psyclone.parse.algorithm import parse
>>> ast, info = parse("argspec.F90", line_length=True)
```

Similarly the `line_length` argument can be set to `True` if calling the `generator.generate()` function. This function simply passes this argument on to the `psyclone.parse.algorithm.parse()` function.

```
>>> from psyclone.generator import generate
>>> alg, psy = generate("argspec.F90", line_length=True)
```

Line wrapping is performed as a post-processing step, i.e. after the code has been generated. This is done by an instance of the `line_length.FortLineLength` class. For example:

```
>>> from psyclone.generator import generate
>>> from psyclone.line_length import FortLineLength
>>> psy, alg = generate("argspec.f90", line_length=True)
>>> line_length = FortLineLength()
>>> psy_str = line_length.process(str(psy))
>>> print psy_str
>>> alg_str = line_length.process(str(alg))
>>> print alg_str
```

19.3 Limitations

The `line_length.FortLineLength` class is only partially aware of Fortran syntax. This awareness is required so that appropriate continuation characters can be used (for example `&` at the end of a line and `!$omp&` at the start of a line for OpenMP directives, `&` at the end of a line for statements and `&` at the end of a line and `&` at the beginning of a line for strings).

Whilst statements only require an `&` at the end of the line when line wrapping with free-form fortran they may optionally also have an `&` at the beginning of the subsequent line. In contrast, when splitting a string over multiple lines an `&` is required at both locations. Therefore an instance of the `line_length.FortLineLength` class will always add `&` at the beginning of a continuation line for a statement, in case the line is split within a string.

One known situation that could cause an instance of the `line_length.FortLineLength` class to fail is when an inline comment is used at the end of a line to make it longer than the 132 character limit. Whilst PSyclone does not generate such code for the PSy-layer, this might occur in Algorithm-layer code, even if the Algorithm-layer code conforms to the 132 line length limit. The reason for this is that PSyclone's internal parser concatenates lines together, thus a long line correctly split with continuation characters in the Algorithm-layer becomes a line that needs to be split by an instance of the `line_length.FortLineLength` class.

FORTRAN NAMING CONVENTIONS

There is a convention in the kernel code for the Dynamo0.3 and GOcean1.0 APIs that if the name of the operation being performed is `<name>` then a kernel file is `<name>_mod.[fF90]`, the name of the module inside the kernel file is `<name>_mod`, the name of the kernel metadata in the module is `<name>_type` and the name of the kernel subroutine in the module is `<name>_code`.

PSyclone itself does not rely on this convention apart from in the stub generator (see the [Kernel-stub Generator](#) Section) where the name of the metadata to be parsed is determined from the module name.

21.1 The generator module

This module provides the PSyclone ‘main’ routine which is intended to be driven from the bin/psyclone executable script. ‘main’ takes an algorithm file as input and produces modified algorithm code and generated PSy code. A function, ‘generate’, is also provided which has the same functionality as ‘main’ but can be called from within another Python program.

```
psyclone.generator.generate(filename, api="", kernel_paths=None, script_name=None, line_length=False,  
                           distributed_memory=None, kern_out_path="", kern_naming='multiple')
```

Takes a PSyclone algorithm specification as input and outputs the associated generated algorithm and psy codes suitable for compiling with the specified kernel(s) and support infrastructure. Uses the `parse.algorithm.parse()` function to parse the algorithm specification, the `psyGen.PSy` class to generate the PSy code and the `alg_gen.Alg` class to generate the modified algorithm code.

Parameters

- `filename` (`str`) – the file containing the algorithm specification.
- `api` (`str`) – the name of the API to use. Defaults to empty string.
- `kernel_paths` (`Optional[List[str]]`) – the directories from which to recursively search for the files containing the kernel source (if different from the location of the algorithm specification). Defaults to `None`.
- `script_name` (`str`) – a script file that can apply optimisations to the PSy layer (can be a path to a file or a filename that relies on the `PYTHONPATH` to find the module). Defaults to `None`.
- `line_length` (`bool`) – a logical flag specifying whether we care about line lengths being longer than 132 characters. If so, the input (algorithm and kernel) code is checked to make sure that it conforms. The default is `False`.
- `distributed_memory` (`bool`) – a logical flag specifying whether to generate distributed memory code. The default is set in the ‘config.py’ file.
- `kern_out_path` (`str`) – directory to which to write transformed kernel code. Defaults to empty string.
- `kern_naming` (`bool`) – the scheme to use when re-naming transformed kernels. Defaults to “multiple”.

Returns

2-tuple containing the `fparser1` AST for the algorithm code and the `fparser1` AST or a string (for NEMO) of the psy code.

Return type

Tuple[fparser.one.block_statements.BeginSource, fparser.one.block_statements.Module]
| Tuple[fparser.one.block_statements.BeginSource, str]

Raises

- `GenerationError` – if an invalid API is specified.
- `GenerationError` – if an invalid kernel-renaming scheme is specified.
- `IOError` – if the filename or search path do not exist.

For example:

```
>>> from psyclone.generator import generate
>>> alg, psy = generate("algspec.f90")
>>> alg, psy = generate("algspec.f90", kernel_paths=["src/kernels"])
>>> alg, psy = generate("algspec.f90", script_name="optimise.py")
>>> alg, psy = generate("algspec.f90", line_length=True)
>>> alg, psy = generate("algspec.f90", distributed_memory=False)
```

21.2 The parse module

Module that uses the Fortran parser `fparser2` to parse PSyclone-conformant Algorithm code.

```
psyclone.parse.algorithm.parse(alg_filename, api="", invoke_name='invoke', kernel_paths=None,
                               line_length=False)
```

Takes a PSyclone conformant algorithm file as input and outputs a parse tree of the code contained therein and an object containing information about the ‘invoke’ calls in the algorithm file and any associated kernels within the invoke calls.

Parameters

- `alg_filename` (`str`) – the file containing the algorithm specification.
- `api` (`str`) – the PSyclone API to use when parsing the code. Defaults to empty string.
- `invoke_name` (`str`) – the expected name of the invocation calls in the algorithm code. Defaults to “invoke”.
- `kernel_paths` (`list` of `str` or `NoneType`) – the paths to search for kernel source files (if different from the location of the algorithm source). Defaults to `None`.
- `line_length` (`bool`) – a logical flag specifying whether we care about line lengths being longer than 132 characters. If so, the input (algorithm and kernel) code is checked to make sure that it conforms and an error raised if not. The default is `False`.

Returns

2-tuple consisting of the `fparser2` parse tree of the Algorithm file and an object holding details of the invokes found.

Return type

(`fparser.two.Fortran2003.Program`, `psyclone.parse.FileInfo`)

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> ast, info = parse(SOURCE_FILE)
```

21.3 The transformations module

This module provides the various transformations that can be applied to PSyIR nodes. There are both general and API-specific transformation classes in this module where the latter typically apply API-specific checks before calling the base class for the actual transformation.

class `psyclone.transformations.ACCDataTrans`

Add an OpenACC data region around a list of nodes in the PSyIR. COPYIN, COPYOUT and COPY clauses are added as required.

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> ast, invokeInfo = parse(NEMO_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCKernelsTrans, ACCDataTrans
>>> ktrans = ACCKernelsTrans()
>>> dtrans = ACCDataTrans()
>>>
>>> schedule = psy.invokes.get('tra_adv').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Add a kernels construct for execution on the device
>>> kernels = schedule.children[9]
>>> ktrans.apply(kernels)
>>>
>>> # Enclose the kernels in a data construct
>>> kernels = schedule.children[9]
>>> dtrans.apply(kernels)
```

`apply(node, options=None)`

Put the supplied node or list of nodes within an OpenACC data region.

Parameters

- `node` ((list of) `psyclone.psyir.nodes.Node`) – the PSyIR node(s) to enclose in the data region.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns

the name of this transformation.

Return type

str

`validate(nodes, options)`

Check that we can safely add a data region around the supplied list of nodes.

Parameters

- nodes ((list of) subclasses of `psyclone.psyir.nodes.Node`) – the proposed node(s) to enclose in a data region.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

- `TransformationError` – if the Schedule to which the nodes belong already has an ‘enter data’ directive.
- `TransformationError` – if any of the nodes are themselves data directives.

class `psyclone.transformations.ACCEnterDataTrans`

Adds an OpenACC “enter data” directive to a Schedule. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCEnterDataTrans, ACCLoopTrans, \
↳ ACCParallelTrans
>>> dtrans = ACCEnterDataTrans()
>>> ltrans = ACCLoopTrans()
>>> ptrans = ACCParallelTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenACC Loop transformation to *every* loop in the schedule
>>> for child in schedule.children[:]:
...     ltrans.apply(child)
>>>
>>> # Enclose all of these loops within a single OpenACC parallel region
>>> ptrans.apply(schedule)
>>>
>>> # Add an enter data directive
>>> dtrans.apply(schedule)
>>>
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(sched, options=None)`

Adds an OpenACC “enter data” directive to the invoke associated with the supplied Schedule. Any fields accessed by OpenACC kernels within this schedule will be added to this data region in order to ensure they remain on the target device.

Parameters

- sched (sub-class of `psyclone.psyir.nodes.Schedule`) – schedule to which to add an “enter data” directive.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns

the name of this transformation.

Return type

str

validate(*sched*, *options=None*)

Check that we can safely apply the OpenACC enter-data transformation to the supplied Schedule.

Parameters

- *sched* (sub-class of `psyclone.psyir.nodes.Schedule`) – Schedule to which to add an “enter data” directive.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

TransformationError – if passed something that is not a (subclass of) `psyclone.psyir.nodes.Schedule`.

class `psyclone.transformations.ACCKernelsTrans`

Enclose a sub-set of nodes from a Schedule within an OpenACC kernels region (i.e. within “!\$acc kernels” ... “!\$acc end kernels” directives).

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "nemo"
>>> ast, invokeInfo = parse(NEMO_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCKernelsTrans
>>> ktrans = ACCKernelsTrans()
>>>
>>> schedule = psy.invokes.get('tra_adv').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>> kernels = schedule.children[9]
>>> # Transform the kernel
>>> ktrans.apply(kernels)
```

apply(*node*, *options=None*)

Enclose the supplied list of PSyIR nodes within an OpenACC Kernels region.

Parameters

- *node* ((a list of) `psyclone.psyir.nodes.Node`) – a node or list of nodes in the PSyIR to enclose.
- *options* (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- *options*["default_present"] (bool) – whether or not the kernels region should have the ‘default present’ attribute (indicating that data is already on the accelerator). When using managed memory this option should be False.

property name

Returns

the name of this transformation class.

Return type`str``validate(nodes, options)`

Check that we can safely enclose the supplied node or list of nodes within OpenACC kernels ... end kernels directives.

Parameters

- nodes ((list of) `psyclone.psyir.nodes.Node`) – the proposed PSyIR node or nodes to enclose in the kernels region.
- options (Optional[Dict[`str`, Any]]) – a dictionary with options for transformations.

Raises

- `NotImplementedError` – if the supplied Nodes belong to a `GOInvokeSchedule`.
- `TransformationError` – if there are no Loops within the proposed region.

`class psyclone.transformations.ACCLoopTrans`

Adds an OpenACC loop directive to a loop. This directive must be within the scope of some OpenACC Parallel region (at code-generation time).

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.parse.utils import ParseError
>>> from psyclone.psyGen import PSyFactory
>>> from psyclone.errors import GenerationError
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> ltrans = t.get_trans_name('ACCLoopTrans')
>>> rtrans = t.get_trans_name('ACCPParallelTrans')
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenACC Loop transformation to *every* loop in the schedule
>>> for child in schedule.children[:]:
...     ltrans.apply(child)
>>>
>>> # Enclose all of these loops within a single OpenACC parallel region
>>> rtrans.apply(schedule)
>>>
```

`apply(node, options=None)`

Apply the ACCLoop transformation to the specified node. This node must be a Loop since this transformation corresponds to inserting a directive immediately before a loop, e.g.:

```
!$ACC LOOP
do ...
```

(continues on next page)

(continued from previous page)

```
...
end do
```

At code-generation time (when `psyclone.psyir.nodes.ACCLoopDirective.gen_code()` is called), this node must be within (i.e. a child of) a PARALLEL region.

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – the supplied node to which we will apply the Loop transformation.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["collapse"]` (`int`) – number of nested loops to collapse.
- `options["independent"]` (`bool`) – whether to add the “independent” clause to the directive (not strictly necessary within PARALLEL regions).

`excluded_node_types`

alias of `PSyDataNode`

class `psyclone.transformations.ACCParallelTrans`

Create an OpenACC parallel region by inserting directives. This parallel region *must* come after an enter-data directive (see `ACCEnterDataTrans`) or within a data region (see `ACCDDataTrans`). For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> ptrans = t.get_trans_name('ACCPParallelTrans')
>>> dtrans = t.get_trans_name('ACCDDataTrans')
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Enclose everything within a single OpenACC PARALLEL region
>>> ptrans.apply(schedule.children)
>>> # Add an enter-data directive
>>> dtrans.apply(schedule)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

property `name`

Returns

the name of this transformation as a string.

Return type

`str`

class `psyclone.transformations.ACCRoutineTrans`

Transform a kernel or routine by adding a “!\$acc routine” directive (causing it to be compiled for the OpenACC accelerator device). For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import ACCRoutineTrans
>>> rtrans = ACCRoutineTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>> kern = schedule.children[0].children[0].children[0]
>>> # Transform the kernel
>>> rtrans.apply(kern)
```

`apply(node, options=None)`

Add the ‘!\$acc routine’ OpenACC directive into the code of the supplied Kernel (in a PSyKAI API such as GOcean or LFRic) or directly in the supplied Routine.

Parameters

- `node` (`psyclone.psyGen.Kern` or `psyclone.psyir.nodes.Routine`) – the kernel call or routine implementation to transform.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

property name

Returns

the name of this transformation class.

Return type

str

`validate(node, options=None)`

Perform checks that the supplied kernel or routine can be transformed.

Parameters

- `node` (`psyclone.psyGen.Kern` or `psyclone.psyir.nodes.Routine`) – the kernel which is the target of the transformation.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

- `TransformationError` – if the node is not a kernel or a routine.
- `TransformationError` – if the target is a built-in kernel.
- `TransformationError` – if it is a kernel but without an associated PSyIR.
- `TransformationError` – if any of the symbols in the kernel are accessed via a module use statement.

class `psyclone.transformations.ColourTrans`

Apply a colouring transformation to a loop (in order to permit a subsequent parallelisation over colours). For example:

```
>>> invoke = ...
>>> schedule = invoke.schedule
>>>
>>> ctrans = ColourTrans()
>>>
>>> # Colour all of the loops
>>> for child in schedule.children:
>>>     ctrans.apply(child)
>>>
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(node, options=None)`

Converts the Loop represented by node into a nested loop where the outer loop is over colours and the inner loop is over cells of that colour.

Parameters

- node (`psyclone.psyir.nodes.Loop`) – the loop to transform.
- options (`Optional[Dict[str, Any]]`) – options for the transformation.

class `psyclone.transformations.Dynamo0p3AsyncHaloExchangeTrans`

Splits a synchronous halo exchange into a halo exchange start and halo exchange end. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "dynamo0.3"
>>> ast, invokeInfo = parse("file.f90", api=api)
>>> psy=PSyFactory(api).create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import Dynamo0p3AsyncHaloExchangeTrans
>>> trans = Dynamo0p3AsyncHaloExchangeTrans()
>>> trans.apply(schedule.children[0])
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(node, options=None)`

Transforms a synchronous halo exchange, represented by a `HaloExchange` node, into an asynchronous halo exchange, represented by `HaloExchangeStart` and `HaloExchangeEnd` nodes.

Parameters

- node (`psyclone.psygen.HaloExchange`) – a synchronous haloexchange node.
- options (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

property name

Returns

the name of this transformation as a string.

Return type

str

validate(*node*, *options*)

Internal method to check whether the node is valid for this transformation.

Parameters

- node (psyclone.psygen.HaloExchange) – a synchronous Halo Exchange node
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.

Raises

TransformationError – if the node argument is not a HaloExchange (or subclass thereof)

class psyclone.transformations.Dynamo0p3ColourTrans

Split a Dynamo 0.3 loop over cells into colours so that it can be parallelised. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> import transformations
>>> import os
>>> import pytest
>>>
>>> TEST_API = "dynamo0.3"
>>> _,info=parse(os.path.join(os.path.dirname(os.path.abspath(__file__)),
>>>                          "tests", "test_files", "dynamo0p3",
>>>                          "4.6_multikernel_invokes.f90"),
>>>              api=TEST_API)
>>> psy = PSyFactory(TEST_API).create(info)
>>> invoke = psy.invokes.get('invoke_0')
>>> schedule = invoke.schedule
>>>
>>> ctrans = Dynamo0p3ColourTrans()
>>> otrans = DynamoOMPParallelLoopTrans()
>>>
>>> # Colour all of the loops
>>> for child in schedule.children:
>>>     ctrans.apply(child)
>>>
>>> # Then apply OpenMP to each of the colour loops
>>> for child in schedule.children:
>>>     otrans.apply(child.children[0])
>>>
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

Colouring in the LFRic (Dynamo 0.3) API is subject to the following rules:

- Only kernels which operate on ‘CELL_COLUMN’s and which increment a field on a continuous function space require colouring. Kernels that update a field on a discontinuous function space will cause this transformation to raise an exception. Kernels that only write to a field on a continuous function space also do not require colouring but are permitted.
- A kernel may have at most one field with ‘GH_INC’ access.
- A separate colour map will be required for each field that is coloured (if an invoke contains >1 kernel call).

`apply(node, options=None)`

Performs Dynamo0.3-specific error checking and then uses the parent class to convert the Loop represented by node into a nested loop where the outer loop is over colours and the inner loop is over cells of that colour.

Parameters

- node (psyclone.dynamo0p3.DynLoop) – the loop to transform.
- options – a dictionary with options for transformations. :type options: Optional[Dict[str, Any]]

class psyclone.transformations.Dynamo0p3KernelConstTrans

Modifies a kernel so that the number of dofs, number of layers and number of quadrature points are fixed in the kernel rather than being passed in by argument.

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "dynamo0.3"
>>> ast, invokeInfo = parse("file.f90", api=api)
>>> psy=PSyFactory(api).create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import Dynamo0p3KernelConstTrans
>>> trans = Dynamo0p3KernelConstTrans()
>>> for kernel in schedule.coded_kernels():
>>>     trans.apply(kernel, number_of_layers=150)
>>>     kernel_schedule = kernel.get_kernel_schedule()
>>>     # Uncomment the following line to see a text view of the
>>>     # symbol table
>>>     # print(kernel_schedule.symbol_table.view())
```

`apply(node, options=None)`

Transforms a kernel so that the values for the number of degrees of freedom (if a valid value for the `element_order` arg is provided), the number of quadrature points (if the `quadrature` arg is set to True) and the number of layers (if a valid value for the `number_of_layers` arg is provided) are constant in a kernel rather than being passed in by argument.

The “cellshape”, “element_order” and “number_of_layers” arguments are provided to mirror the namelist values that are input into an LFRic model when it is run.

Quadrature support is currently limited to XYoZ in this transformation. In the case of XYoZ the number of quadrature points (for horizontal and vertical) are set to the `element_order` + 3 in the LFRic infrastructure so their value is derived.

Parameters

- node (psyclone.psygen.DynKern) – a kernel node.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- options["cellshape"] (str) – the shape of the cells. This is provided as it helps determine the number of dofs a field has for a particular function space. Currently only “quadrilateral” is supported which is also the default value.
- options["element_order"] (int) – the order of the cell. In combination with cellshape, this determines the number of dofs a field has for a particular function space. If it is set

to None (the default) then the dofs values are not set as constants in the kernel, otherwise they are.

- `options["number_of_layers"]` (`int`) – the number of vertical layers in the LFRic model mesh used for this particular run. If this is set to None (the default) then the nlayers value is not set as a constant in the kernel, otherwise it is.
- `options["quadrature"]` (`bool`) – whether the number of quadrature points values are set as constants in the kernel (True) or not (False). The default is False.

property name

Returns

the name of this transformation as a string.

Return type

`str`

`validate(node, options=None)`

This method checks whether the input arguments are valid for this transformation.

Parameters

- `node` (`psyclone.psygen.DynKern`) – a dynamo 0.3 kernel node.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["cellshape"]` (`str`) – the shape of the elements/cells.
- `options["element_order"]` (`int`) – the order of the elements/cells.
- `options["number_of_layers"]` (`int`) – the number of layers to use.
- `options["quadrature"]` (`bool`) – whether quadrature dimension sizes should or shouldn't be set as constants in a kernel.

Raises

`TransformationError` – if the node argument is not a dynamo 0.3 kernel, the cellshape argument is not set to “quadrilateral”, the element_order argument is not a 0 or a positive integer, the number of layers argument is not a positive integer, the quadrature argument is not a boolean, neither element order nor number of layers arguments are set (as the transformation would then do nothing), or the quadrature argument is True but the element order is not provided (as the former needs the latter).

`class psyclone.transformations.Dynamo0p3OMPLoopTrans(omp_schedule='static')`

LFRic (Dynamo 0.3) specific orphan OpenMP loop transformation. Adds Dynamo-specific validity checks.

Parameters

`omp_schedule` (`str`) – the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

`apply(node, options=None)`

Apply LFRic (Dynamo 0.3) specific OMPLoopTrans.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the Node in the Schedule to check.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- `options["reprod"]` (`bool`) – indicating whether reproducible reductions should be used. By default the value from the config file will be used.

`validate(node, options=None)`

Perform LFRic (Dynamo 0.3) specific loop validity checks for the OMPLoopTrans.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the Node in the Schedule to check
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.
- `options["reprod"]` (`bool`) – indicating whether reproducible reductions should be used. By default the value from the config file will be used.

Raises

`TransformationError` – if an OMP loop transform would create incorrect code.

`class psyclone.transformations.Dynamo0p3RedundantComputationTrans`

This transformation allows the user to modify a loop's bounds so that redundant computation will be performed. Redundant computation can result in halo exchanges being modified, new halo exchanges being added or existing halo exchanges being removed.

- This transformation should be performed before any parallelisation transformations (e.g. for OpenMP) to the loop in question and will raise an exception if this is not the case.
- This transformation can not be applied to a loop containing a reduction and will again raise an exception if this is the case.
- This transformation can only be used to add redundant computation to a loop, not to remove it.
- This transformation allows a loop that is already performing redundant computation to be modified, but only if the depth is increased.

`apply(loop, options=None)`

Apply the redundant computation transformation to the loop `loop`. This transformation can be applied to loops iterating over 'cells' or 'dofs'. If `depth` is set to a value then the value will be the depth of the field's halo over which redundant computation will be performed. If `depth` is not set to a value then redundant computation will be performed to the full depth of the field's halo.

Parameters

- `loop` (`psyclone.psyGen.DynLoop`) – the loop that we are transforming.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["depth"]` (`int`) – the depth of the stencil. Defaults to None.

`validate(node, options=None)`

Perform various checks to ensure that it is valid to apply the RedundantComputation transformation to the supplied node

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the supplied node on which we are performing validity checks
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["depth"]` (`int`) – the depth of the stencil if the value is provided and None if not.

Raises

- `TransformationError` – if the parent of the loop is a `psyclone.psyir.nodes.Directive`.
- `TransformationError` – if the parent of the loop is not a `psyclone.psyir.nodes.Loop` or a `psyclone.psyGen.DynInvokeSchedule`.

- TransformationError – if the parent of the loop is a `psyclone.psyir.nodes.Loop` but the original loop does not iterate over ‘colour’.
- TransformationError – if the parent of the loop is a `psyclone.psyir.nodes.Loop` but the parent does not iterate over ‘colours’.
- TransformationError – if the parent of the loop is a `psyclone.psyir.nodes.Loop` but the parent’s parent is not a `psyclone.psyGen.DynInvokeSchedule`.
- TransformationError – if this transformation is applied when distributed memory is not switched on.
- TransformationError – if the loop does not iterate over cells, dofs or colour.
- TransformationError – if the transformation is setting the loop to the maximum halo depth but the loop already computes to the maximum halo depth.
- TransformationError – if the transformation is setting the loop to the maximum halo depth but the loop contains a stencil access (as this would result in the field being accessed beyond the halo depth).
- TransformationError – if the supplied depth value is not an integer.
- TransformationError – if the supplied depth value is less than 1.
- TransformationError – if the supplied depth value is not greater than 1 when a continuous loop is modified as this is the minimum valid value.
- TransformationError – if the supplied depth value is not greater than the existing depth value, as we should not need to undo existing transformations.
- TransformationError – if a depth value has been supplied but the loop has already been set to the maximum halo depth.

`class psyclone.transformations.DynamoOMPParallelLoopTrans(omp_directive='do', omp_schedule='static')`

Dynamo-specific OpenMP loop transformation. Adds Dynamo specific validity checks. Actual transformation is done by the [base class](#).

Parameters

- `omp_directive` (*str*) – choose which OpenMP loop directive to use. Defaults to “do”.
- `omp_schedule` (*str*) – the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

`apply(node, options=None)`

Perform Dynamo specific loop validity checks then call the [apply\(\)](#) method of the [base class](#).

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the Node in the Schedule to check
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Raises

TransformationError – if the associated loop requires colouring.

`class psyclone.transformations.GOceanOMPLoopTrans(omp_directive='do', omp_schedule='static')`

GOcean-specific orphan OpenMP loop transformation. Adds GOcean specific validity checks (that the node is either an inner or outer Loop).

Parameters

- `omp_directive` (*str*) – choose which OpenMP loop directive to use. Defaults to “do”.

- `omp_schedule` (`str`) – the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

`validate(node, options=None)`

Checks that the supplied node is a valid target for parallelisation using OMP directives.

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – the candidate loop for parallelising using OMP Do.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Raises

`TransformationError` – if the `loop_type` of the supplied `Loop` is not “inner” or “outer”.

`class psyclone.transformations.GOceanOMPParallelLoopTrans(omp_directive='do', omp_schedule='static')`

GOcean specific OpenMP Do loop transformation. Adds GOcean specific validity checks (that supplied `Loop` is an inner or outer loop). Actual transformation is done by [base class](#).

param str `omp_directive`

choose which OpenMP loop directive to use. Defaults to “do”.

param str `omp_schedule`

the OpenMP schedule to use. Must be one of ‘runtime’, ‘static’, ‘dynamic’, ‘guided’ or ‘auto’. Defaults to ‘static’.

`apply(node, options=None)`

Perform GOcean-specific loop validity checks then call [OMPParallelLoopTrans.apply\(\)](#).

Parameters

- `node` (`psyclone.psyir.nodes.Loop`) – a `Loop` node from an AST.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations and validation.

Raises

`TransformationError` – if the supplied node is not an inner or outer loop.

`class psyclone.transformations.KernelImportsToArguments`

Transformation that removes any accesses of imported data from the supplied kernel and places them in the caller. The values/references are then passed by argument into the kernel.

`apply(node, options=None)`

Convert the imported variables used inside the kernel into arguments and modify the `InvokeSchedule` to pass the same imported variables to the kernel call.

Parameters

- `node` (`psyclone.psyGen.CodedKern`) – a kernel call.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

property name

Returns

the name of this transformation.

Return type

`str`

`validate(node, options=None)`

Check that the supplied node is a valid target for this transformation.

Parameters

- `node` (`psyclone.psyGen.CodedKern`) – the PSyIR node to validate.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.

Raises

- `TransformationError` – if the supplied node is not a `CodedKern`.
- `TransformationError` – if this transformation is not applied to a Gocean API Invoke.
- `TransformationError` – if the supplied kernel contains wildcard imports of symbols from one or more containers (e.g. a USE without an ONLY clause in Fortran).

`class psyclone.transformations.MoveTrans`

Provides a transformation to move a node in the tree. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> ast,invokeInfo=parse("dynamo.F90")
>>> psy=PSyFactory("dynamo0.3").create(invokeInfo)
>>> schedule=psy.invokes.get('invoke_v3_kernel_type').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import MoveTrans
>>> trans=MoveTrans()
>>> trans.apply(schedule.children[0], schedule.children[2],
...             options = {"position":"after"})
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

Nodes may only be moved to a new location with the same parent and must not break any dependencies otherwise an exception is raised.

`apply(node, location, options=None)`

Move the node represented by `node` before `location` (which is also a node) by default and after if the optional *position* argument is set to ‘after’.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the node to be moved.
- `location` (`psyclone.psyir.nodes.Node`) – node before or after which the given node should be moved.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["position"]` (`str`) – either ‘before’ or ‘after’.

Raises

- `TransformationError` – if the given node is not an instance of `psyclone.psyir.nodes.Node`
- `TransformationError` – if the location is not valid.

property name

Returns the name of this transformation as a string.

`validate(node, location, options=None)`

validity checks for input arguments.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the node to be moved.
- `location` (`psyclone.psyir.nodes.Node`) – node before or after which the given node should be moved.
- `options` (`Optional[Dict[str, Any]]`) – a dictionary with options for transformations.
- `options["position"]` (`str`) – either ‘before’ or ‘after’.

Raises

- `TransformationError` – if the given node is not an instance of `psyclone.psyir.nodes.Node`
- `TransformationError` – if the location is not valid.

`class psyclone.transformations.OMPLoopTrans(omp_directive='do', omp_schedule='auto')`

Adds an OpenMP directive to parallelise this loop. It can insert different directives such as “omp do/for”, “omp parallel do/for”, “omp teams distribute parallel do/for” or “omp loop” depending on the provided parameters. The OpenMP schedule to use can also be specified, but this will be ignored in case of the “omp loop” (as the ‘schedule’ clause is not valid for this specific directive). The configuration-defined ‘reprod’ parameter also specifies whether a manual reproducible reproduction is to be used. Note, reproducible in this case means obtaining the same results with the same number of OpenMP threads, not for different numbers of OpenMP threads.

Parameters

- `omp_schedule` (`str`) – the OpenMP schedule to use. Defaults to ‘auto’.
- `omp_directive` (`str`) – choose which OpenMP loop directive to use. Defaults to “omp do”

For example:

```
>>> from psyclone.psyir.frontend.fortran import FortranReader
>>> from psyclone.psyir.backend.fortran import FortranWriter
>>> from psyclone.psyir.nodes import Loop
>>> from psyclone.transformations import OMPLoopTrans, OMPParallelTrans
>>>
>>> psyir = FortranReader().psyir_from_source("""
...     subroutine my_subroutine()
...         integer, dimension(10, 10) :: A
...         integer :: i
...         integer :: j
...         do i = 1, 10
...             do j = 1, 10
...                 A(i, j) = 0
...             end do
...         end do
...     end subroutine
... """)
>>> loop = psyir.walk(Loop)[0]
>>> omplooptrans1 = OMPLoopTrans(omp_schedule="dynamic",
...                               omp_directive="parallel do")
... 
```

(continues on next page)

(continued from previous page)

```

>>> omplooptrans1.apply(loop)
>>> print(FortranWriter()(psyir))
subroutine my_subroutine()
  integer, dimension(10,10) :: a
  integer :: i
  integer :: j

  !$omp parallel do default(shared), private(i,j), schedule(dynamic)
  do i = 1, 10, 1
    do j = 1, 10, 1
      a(i,j) = 0
    enddo
  enddo
  !$omp end parallel do

end subroutine my_subroutine

```

`apply(node, options=None)`

Apply the OMPLoopTrans transformation to the specified PSyIR Loop.

Parameters

- `node` (`psyclone.psyir.nodes.Node`) – the supplied node to which we will apply the OMPLoopTrans transformation
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations and validation.
- `options["reprod"]` (`bool`) – indicating whether reproducible reductions should be used. By default the value from the config file will be used.

property `omp_directive`

Returns

the type of OMP directive that this transformation will insert.

Return type

`str`

property `omp_schedule`

Returns

the OpenMP schedule that will be specified by this transformation.

Return type

`str`

class `psyclone.transformations.OMPMasterTrans`

Create an OpenMP MASTER region by inserting directives. The most likely use case for this transformation is to wrap around task-based transformations. Note that adding this directive requires a parent OpenMP parallel region (which can be inserted by `OMPParallelTrans`), otherwise it will produce an error in generation-time.

For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"

```

(continues on next page)

(continued from previous page)

```

>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import OMPParallelTrans, OMPMasterTrans
>>> mastertrans = OMPMasterTrans()
>>> paralleltrans = OMPParallelTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Enclose all of these loops within a single OpenMP
>>> # MASTER region
>>> mastertrans.apply(schedule.children)
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> paralleltrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())

```

property name

Returns

the name of this transformation as a string.

Return type

str

class psyclone.transformations.OMPParallelLoopTrans(*omp_directive='do', omp_schedule='auto'*)

Adds an OpenMP PARALLEL DO directive to a loop.

For example:

```

>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> ast, invokeInfo = parse("dynamo.F90")
>>> psy = PSyFactory("dynamo0.3").create(invokeInfo)
>>> schedule = psy.invokes.get('invoke_v3_kernel_type').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> from psyclone.transformations import OMPParallelLoopTrans
>>> trans = OMPParallelLoopTrans()
>>> trans.apply(schedule.children[0])
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())

```

apply(*node, options=None*)

Apply an OMPParallelLoop Transformation to the supplied node (which must be a Loop). In the generated code this corresponds to wrapping the Loop with directives:

```

!$OMP PARALLEL DO ...
do ...
...

```

(continues on next page)

(continued from previous page)

```
end do
!$OMP END PARALLEL DO
```

Parameters

- `node` (`psyclone.f2pygen.DoGen`) – the node (loop) to which to apply the transformation.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations and validation.

```
class psyclone.transformations.OMPParallelTrans
```

Create an OpenMP PARALLEL region by inserting directives. For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.parse.utils import ParseError
>>> from psyclone.psyGen import PSyFactory
>>> from psyclone.errors import GenerationError
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.psyGen import TransInfo
>>> t = TransInfo()
>>> ltrans = t.get_trans_name('GOceanOMPLoopTrans')
>>> rtrans = t.get_trans_name('OMPParallelTrans')
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Apply the OpenMP Loop transformation to *every* loop
>>> # in the schedule
>>> for child in schedule.children:
>>>     ltrans.apply(child)
>>>
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> rtrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

property name

Returns

the name of this transformation as a string.

Return type

str

```
validate(node_list, options=None)
```

Perform OpenMP-specific validation checks.

Parameters

- `node_list` (list of `psyclone.psyir.nodes.Node`) – list of Nodes to put within parallel region.
- `options` (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- `options["node-type-check"]` (bool) – this flag controls if the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

Raises

`TransformationError` – if the target Nodes are already within some OpenMP parallel region.

class `psyclone.transformations.OMPSingleTrans(nowait=False)`

Create an OpenMP SINGLE region by inserting directives. The most likely use case for this transformation is to wrap around task-based transformations. The parent region for this should usually also be a `OMPParallelTrans`.

Parameters

`nowait` (bool) – whether to apply a `nowait` clause to this transformation. The default value is `False`

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> from psyclone.psyGen import PSyFactory
>>> api = "gocean1.0"
>>> ast, invokeInfo = parse(GOCEAN_SOURCE_FILE, api=api)
>>> psy = PSyFactory(api).create(invokeInfo)
>>>
>>> from psyclone.transformations import OMPParallelTrans, OMPSingleTrans
>>> singletrans = OMPSingleTrans()
>>> paralleltrans = OMPParallelTrans()
>>>
>>> schedule = psy.invokes.get('invoke_0').schedule
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
>>>
>>> # Enclose all of these loops within a single OpenMP
>>> # SINGLE region
>>> singletrans.apply(schedule.children)
>>> # Enclose all of these loops within a single OpenMP
>>> # PARALLEL region
>>> paralleltrans.apply(schedule.children)
>>> # Uncomment the following line to see a text view of the schedule
>>> # print(schedule.view())
```

`apply(node_list, options=None)`

Apply the `OMPSingleTrans` transformation to the specified node in a Schedule.

At code-generation time this node must be within (i.e. a child of) an OpenMP PARALLEL region. Code generation happens when `OMPLoopDirective.gen_code()` is called, or when the PSyIR tree is given to a backend.

If the keyword “`nowait`” is specified in the options, it will cause a `nowait` clause to be added if it is set to `True`, otherwise no clause will be added.

Parameters

- `node_list` ((a list of) `psyclone.psyir.nodes.Node`) – the supplied node or node list to which we will apply the `OMPSingleTrans` transformation

- options (Optional[Dict[str, Any]]) – a list with options for transformations and validation.
- options["nowait"] (bool) – indicating whether or not to use a nowait clause on this single region.

property name

Returns

the name of this transformation.

Return type

str

property omp_nowait

Returns

whether or not this Single region uses a nowait clause to remove the end barrier.

Return type

bool

class psyclone.transformations.ParallelRegionTrans

Base class for transformations that create a parallel region.

apply(target_nodes, options=None)

Apply this transformation to a subset of the nodes within a schedule - i.e. enclose the specified Loops in the schedule within a single parallel region.

Parameters

- target_nodes ((list of) psyclone.psyir.nodes.Node) – a single Node or a list of Nodes.
- options (Optional[Dict[str, Any]]) – a dictionary with options for transformations.
- options["node-type-check"] (bool) – this flag controls if the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

abstract property name

Returns the name of this transformation as a string.

validate(node_list, options=None)

Check that the supplied list of Nodes are eligible to be put inside a parallel region.

Parameters

- node_list (list) – list of nodes to put into a parallel region
- options – a dictionary with options for transformations. :type options: Optional[Dict[str, Any]]
- options["node-type-check"] (bool) – this flag controls whether or not the type of the nodes enclosed in the region should be tested to avoid using unsupported nodes inside a region.

Raises

- TransformationError – if the supplied node is an InvokeSchedule rather than being within an InvokeSchedule.
- TransformationError – if the supplied nodes are not all children of the same parent (siblings).

21.4 The psyGen module

This module provides generic support for PSyclone's PSy code optimisation and generation. The classes in this method need to be specialised for a particular API and implementation.

class `psyclone.psyGen.PSy(invoke_info)`

Base class to help manage and generate PSy code for a single algorithm file. Takes the invocation information output from the function `parse.algorithm.parse()` as its input and stores this in a way suitable for optimisation and code generation.

Parameters

`invoke_info` (`psyclone.parse.algorithm.FileInfo`) – An object containing the required invocation information for code optimisation and generation. Produced by the function `parse.algorithm.parse()`.

For example:

```
>>> from psyclone.parse.algorithm import parse
>>> ast, info = parse("argspec.F90")
>>> from psyclone.psyGen import PSyFactory
>>> api = "."
>>> psy = PSyFactory(api).create(info)
>>> print(psy.gen)
```

property container

Returns

the container associated with this PSy object

Return type

`psyclone.psyir.nodes.Container`

abstract property gen

Abstract base class for code generation function.

Returns

root node of generated Fortran AST.

Return type

`psyclone.psyir.nodes.Node`

property invokes

Returns

the list of invokes.

Return type

`psyclone.psyGen.Invokes` or derived class

property name

Returns

the name of the PSy object.

Return type

`str`

21.5 The alg_gen module

This module provides the Alg class and supporting exception-handling to translate the original algorithm file into one that can be compiled and linked with the generated PSy code.

```
class psyclone.alg_gen.Alg(parse_tree, psy, invoke_name='invoke')
```

Generate a modified algorithm code for a single algorithm specification. Takes the parse tree of the algorithm specification output from the function `psyclone.parse.algorithm.parse()` and an instance of the `psyGen.PSy` class as input. The latter allows consistent names to be generated between the algorithm (calling) and `psy` (callee) layers.

For example:

```
>>> from psyclone.algorithm.parse import parse
>>> parse_tree, info = parse("argspec.F90")
>>> from psyclone.psyGen import PSy
>>> psy = PSy(info)
>>> from psyclone.alg_gen import Alg
>>> alg = Alg(parse_tree, psy)
>>> print(alg.gen)
```

Parameters

- `parse_tree` (`fparser.two.utils.Base`) – an object containing a parse tree of the algorithm specification which was produced by the function `psyclone.parse.algorithm.parse()`. Assumes the algorithm will be parsed by `fparser2` and expects a valid program unit, program, module, subroutine or function.
- `psy` (`psyclone.psyGen.PSy`) – an object containing information about the PSy layer.
- `invoke_name` (`str`) – the name that the algorithm layer uses to indicate an invoke call. This is an optional argument that defaults to the name “invoke”.

property `gen`

Modifies and returns the algorithm code. ‘invoke’ calls are replaced with calls to the corresponding PSy-layer routines and the USE statements for the kernels that were referenced by each ‘invoke’ are removed.

Returns

the modified algorithm specification as an `fparser2` parse tree.

Return type

`fparser.two.utils.Base`

Raises

`NoInvokesError` – if no ‘invoke()’ calls are found.

21.6 The `line_length` module

Provides support for breaking long fortran lines into smaller ones to allow the code to conform to the maximum line length limits (132 for f90 free format is the default)

`class psyclone.line_length.FortLineLength(line_length=132)`

This class take a free format fortran code as a string and line wraps any lines that are larger than the specified line length

property `length`

returns the maximum allowed line length

`long_lines(fortran_in)`

returns true if at least one of the lines in the input code is longer than the allowed length. Otherwise returns false

`process(fortran_in)`

takes fortran code as a string as input and output fortran code as a string with any long lines wrapped appropriately

PSYDATA API

PSyclone provides transformations that will insert callbacks to an external library at runtime. These callbacks allow third-party libraries to access data structures at specified locations in the code. The PSyclone *wrappers* to external libraries are provided with the *PSyclone installation*. Some example use cases are:

Profiling:

By inserting callbacks before and after a region of code, performance measurements can be added. PSyclone provides wrapper libraries for some common performance profiling tools, see *Profiling* for details.

Kernel Data Extraction:

PSyclone provides the ability to add callbacks that provide access to all input variables before, and output variables after a kernel invocation. This can be used to automatically create tests for a kernel, or to write a stand-alone driver that just calls one kernel, which can be used for performance tuning. Two example libraries that extract input and output data into either a Fortran binary or a NetCDF file are included with PSyclone (see *Extraction Libraries*).

Access Verification:

The callbacks can be used to make sure a field declared as read-only is not modified during a kernel call (either because of an incorrect declaration, or because memory is overwritten). The implementation included in PSyclone uses a simple 64-bit checksum to detect changes to a field (and scalar values). See *Read-Only Verification* for details.

NAN Test:

The callbacks can be used to make sure that all floating point input and output parameters of a kernel are not a NaN (not-a-number) or infinite. See *NAN Test* for the full description.

In-situ Visualisation:

By giving access to output fields of a kernel, an in-situ visualisation library can be used to plot fields while a (PSyclone-processed) application is running. There is no example library available at this stage, but the API has been designed with this application in mind.

The PSyData API should be general enough to allow these and other applications to be developed and used.

PSyclone provides transformations that will insert callbacks to the PSyData API, for example `ProfileTrans`, `GOceanExtractTrans` and `LFRicExtractTrans`. A user can develop additional transformations and corresponding run-time libraries for additional functionality. Refer to `psy_data` for full details about the PSyData API.

22.1 Read-Only Verification

The PSyData interface is being used to verify that read-only variables in a kernel are not overwritten. The `ReadOnlyVerifyTrans` (in `psyir.transformations.read_only_verify_trans`, or the [Transformation Reference Guide](#)) uses the dependency analysis to determine all read-only variables (i.e. arguments declared to be read-only in metadata, most implicit arguments in `LFRic`, grid properties in `GOcean`). A simple 64-bit checksum is then computed for all these arguments before a kernel call, and compared with the checksum after the kernel call. Any change in the checksum causes a message to be printed at runtime, e.g.:

```
-----
Double precision field b fld has been modified in main : update
Original checksum:  4611686018427387904
New checksum:      4638355772470722560
-----
```

The transformation that adds read-only-verification to an application can be applied for both the *LFRic* and *GOcean API* - no API-specific transformations are required. Below is an example that searches for each loop in an `invoke` (which will always surround kernel calls) and applies the transformation to each one. This code has been successfully used as a global transformation with the `LFRic Gravity Wave` miniapp (the executable is named `gravity_wave`):

```
def trans(psy):
    from psyclone.psyir.transformations import ReadOnlyVerifyTrans
    from psyclone.psyir.nodes import Loop
    read_only_verify = ReadOnlyVerifyTrans()

    for invoke in psy.invokes.invoke_list:
        schedule = invoke.schedule
        for node in schedule:
            if isinstance(node, Loop):
                read_only_verify.apply(node)

    return psy
```

Besides the transformation, a library is required to do the actual verification at runtime. There are two implementations of the read-only-verification library included in PSyclone: one for `LFRic`, and one for `GOcean`. Both libraries support the environment variable `PSYDATA_VERBOSE`. This can be used to control how much output is generated by the read-only-verification library at runtime. If the variable is not specified or has the value '0', warnings will only be printed if checksums change. If it is set to '1', a message will be printed before and after each kernel call that is checked. If the variable is set to '2', it will additionally print the name of each variable that is checked.

22.1.1 Read-Only Verification Library for LFRic

This library is contained in `lib/read_only/lfric` and it must be compiled before compiling any `LFRic`-based application that uses read-only verification. Compiling this library requires access to the `LFRic` infrastructure library (since it must implement a generic interface for e.g. the `LFRic field` class).

The Makefile uses the variable `LFRIC_INF_DIR` to point to the location where `LFRic`'s `field_mod` and `integer_field_mod` have been compiled. It defaults to the path to location of the pared-down `LFRic` infrastructure located in a clone of PSyclone repository, `<PSYCLONEHOME>/src/psyclone/tests/test_files/dynamo0p3/infrastructure`, but this will certainly need to be changed for any user (for instance with PSyclone installation). The `LFRic` infrastructure library is not used in linking the verification library. The application which uses the read-only-verification library needs to link in the infrastructure library anyway.

Compilation of the library is done by invoking `make` and setting the required variables:

```
make LFRIC_INF_DIR=some_path F90=ifort F90FLAGS="--some-flag"
```

This will create a library called `lib_read_only.a`.

22.1.2 Read-Only-Verification Library for GOcean

This library is contained in the `lib/read_only/dl_esm_inf` directory and it must be compiled before linking any GOcean-based application that uses read-only verification. Compiling this library requires access to the GOcean infrastructure library (since it must implement a generic interface for e.g. the `dl_esm_inf r2d_field` class).

The Makefile uses the variable `GOCEAN_INF_DIR` to point to the location where `dl_esm_inf`'s `field_mod` has been compiled. It defaults to the relative path to location of the `dl_esm_inf` version included in PSyclone repository as a Git submodule, `<PSYCLONEHOME>/external/dl_esm_inf/finite_difference/src`. It can be changed to a user-specified location if required (for instance with the PSyclone installation).

The `dl_esm_inf` library is not used in linking the verification library. The application which uses the read-only-verification library needs to link in the infrastructure library anyway.

Compilation of the library is done by invoking `make` and setting the required variables:

```
make GOCEAN_INF_DIR=some_path F90=ifort F90FLAGS="--some-flag"
```

This will create a library called `lib_read_only.a`. An executable example for using the GOcean read-only-verification library is included in `examples/gocean/eg5/readonly`, see [Example 5.3: Read-only-verification](#).

22.2 NAN Test

This transformation can be used for both LFRic and GOcean APIs. It will test all input and output parameters of a kernel to make sure they are not NaN or infinite. If they are, an error message like the following is printed, but the program is not aborted:

```
PSyData: Variable a_fld has the invalid value Inf at index/indices 1 1 in module 'main' region 'update'.
```

It uses the function `IEEE_IS_FINITE` from the `ieee_arithmetic` module for this test. Note that only floating point numbers will be tested. Integer numbers do not have a bit pattern for 'infinity' or NaN.

The runtime libraries for GOcean and LFRic are based on a jinja-template contained in the directory `<PSYCLONEHOME>/lib/nan_test`. The respective API-specific libraries map the internal field structures to Fortran basic types and call the functions from the base class to handle those.

The relevant libraries for the LFRic and GOcean APIs are contained in the `lib/nan_test/lfric` and `lib/nan_test/dl_esm_inf` subdirectories, respectively. For more information on how to build and link these libraries, please refer to the relevant `README.md` files.

An executable example for using the LFRic read-only-verification library is included in `tutorial/practicals/LFRic/building_code/4_psydata` directory, see [this link for more information](#).

PROFILING

PSyclone has the ability to define regions that can be profiled with various performance measurement tools. The profiling can be enabled automatically using command line parameters like:

```
psyclone --profile kernels ...
```

Or, for finer-grained control, it may be applied via a profiling transformation within a transformation script.

PSyclone can be used with a variety of existing profiling tools. It currently supports `dl_timer`, Dr Hook, the NVIDIA GPU profiling tools and it comes with a simple stand-alone timer library. The *PSyData API* (see also the [Developer Guide](#)) is utilised to implement wrapper libraries that connect the PSyclone application to the profiling libraries. Certain adjustments to the application's build environment are required:

- The compiler needs to be able to find the module files for the wrapper of the selected profiling library.
- The application needs to be linked with the wrapper library that interfaces between the PSyclone API and the tool-specific API.
- The tool-specific library also needs to be linked in.

It is the responsibility of the user to supply the corresponding compiler command line options when building the application that incorporates the PSyclone-generated code.

23.1 Interface to Third Party Profiling Tools

PSyclone comes with *wrapper libraries* to support usage of Dr Hook, `dl_timer`, NVTX (NVIDIA Tools Extension library), and a simple non-thread-safe timing library. Support for further profiling libraries will be added in the future. To compile the wrapper libraries, change into the directory `lib/profiling` of PSyclone and type `make` to compile all wrappers. If only some of the wrappers are required, you can either use `make wrapper-name` (e.g. `make drhook`), or change into the corresponding directory and use `make`. The corresponding `README.md` files contain additional parameters that can be set in order to find third party profiling tools.

Below are short descriptions of each of the various wrapper libraries that come with PSyclone:

`lib/profiling/template`

This is a simple library that just prints out the name as regions are entered and exited. It could act as a template to develop new wrapper libraries, hence its name.

`lib/profiling/simple_timing`

This is a simple, stand-alone library that uses Fortran system calls to measure the execution time, and reports average, minimum and maximum execution time for all regions. It is not MPI aware (i.e. it will just report independently for each MPI process), and not thread-safe.

`lib/profiling/dl_timer`

This wrapper uses the `apeg-dl_timer` library. In order to use this wrapper, you must download and install the

dl_timer library from https://bitbucket.org/apeg/dl_timer. This library has various compile-time options and may be built with MPI or OpenMP support. Additional link options might therefore be required (e.g. enabling OpenMP, or linking with MPI).

lib/profiling/drhook

This wrapper uses the Dr Hook library. You need to contact ECMWF to obtain a copy of Dr Hook.

lib/profiling/nvidia

This is a wrapper library that maps the PSyclone profiling API to the NVIDIA Tools Extension library (NVTX).

This library is available from <https://developer.nvidia.com/cuda-toolkit>.

lib/profiling/lfric_timer

This profile wrapper uses the timer functionality provided by LFRic, and it comes in two different versions:

- libpsy_lfric_timer.a This library just contains the PSyData wrapper, but not the actual timer code. It must therefore be linked with the LFRic infrastructure library. It is meant to be used by LFRic only.
- libpsy_lfric_timer_standalone.a This library contains the LFRic timer object and its dependencies. It can be used standalone (i.e. without LFRic) with any program. A runnable example using a GOcean code is included in `examples/gocean/eg5/profile`.

The LFRic timer writes its output to a file called `timer.txt` in the current directory, and will overwrite this file if it should already exist.

Any user can create similar wrapper libraries for other profiling tools by providing a corresponding Fortran module. The functions that need to be implemented are described in the developer's guide ([psy_data](#)).

Most libraries in `lib/profiling` need to be linked in with the corresponding 3rd party profiling tool. The exceptions are the template and `simple_timing` libraries, which are stand alone. The profiling example in `examples/gocean/eg5/profile` can be used with any of the wrapper libraries (except `nvidia`) to see how they work.

23.2 Required Modifications to the Program

In order to guarantee that any profiling library is properly initialised, PSyclone's profiling wrappers utilise two additional function calls that the user must manually insert into the program:

23.2.1 `profile_PSyDataInit()`

This method needs to be called once to initialise the profiling tool. At this stage this call is not automatically inserted by PSyclone, so it is the responsibility of the user to add the call to an appropriate location in the application:

```
use profile_psy_data_mod, only : profile_PSyDataInit
...
call profile_PSyDataInit()
```

The “appropriate” location might depend on the profiling library used. For example, it might be necessary to invoke this before or after a call to `MPI_Init()`.

23.2.2 profile_PSyDataShutdown()

At the end of the program the function `profile_PSyDataShutdown()` must be called. It will make sure that the measurements are printed, files are flushed, and that the profiling tool is closed correctly. Again at this stage it is necessary to manually insert the call at an appropriate location:

```
use profile_psy_data_mod, only : profile_PSyDataShutdown
...
call profile_PSyDataShutdown()
```

And again the appropriate location might depend on the profiling library used (e.g. before or after a call to `MPI_Finalize()`).

23.3 Profiling Command-Line Options

PSyclone offers two command line options to automatically instrument code with profiling regions. It can create profile regions around a full invoke (including all kernel calls in this invoke), and/or around each individual kernel.

The option `--profile` invokes will automatically add calls to start and end a profile region at the beginning and end of every invoke subroutine created by PSyclone. All kernels called within this invoke subroutine will be included in the profiled region.

The option `--profile kernels` will surround each outer loop created by PSyclone with start and end profiling calls.

Note: In some APIs (for example *LFRic* when using distributed memory) additional minor code might get included in a profiled kernel section, for example `setDirty()` calls (expensive calls like `HaloExchange` are excluded).

Note: If the `kernels` option is used in combination with an optimisation script that introduces OpenACC then profiling calls are automatically excluded from within OpenACC regions (since the PSyData wrappers are not compiled for GPU execution).

Note: It is still the responsibility of the user to manually add the calls to `profile_PSyDataInit` and `profile_PSyDataShutdown` to the code base (see *Required Modifications to the Program*).

PSyclone will modify the schedule of each invoke to insert the profiling regions. Below we show an example of a schedule created when instrumenting invokes - all children of a Profile-Node will be part of the profiling region, including all loops created by PSyclone and all kernel calls (note that for brevity, the nodes holding the loop bounds have been omitted for all but the first loop):

```
GOInvokeSchedule[invoke='invoke_1']
  0: [Profile]
    Schedule[]
      0: Loop[type='outer',field_space='go_cu',it_space='go_internal_pts']
        Literal[value:'2']
        Literal[value:'jstop']
        Literal[value:'1']
        Schedule[]
          0: Loop[type='inner',field_space='go_cu',
                it_space='go_internal_pts']
```

(continues on next page)

(continued from previous page)

```

...
Schedule[]
    0: CodedKern compute_unew_code(unew_fld,uold_fld,z_fld,
        cv_fld,h_fld,tdt,dy) [module_inline=False]
1: Loop[type='outer',field_space='cv',it_space='internal_pts']
...
Schedule[]
    0: Loop[type='inner',field_space='cv',it_space='internal_pts']
...
Schedule[]
    0: CodedKern compute_vnew_code(vnew_fld,vold_fld,z_fld,
        cu_fld,h_fld,tdt,dy) [module_inline=False]
2: Loop[type='outer',field_space='ct',it_space='internal_pts']
...
Schedule[]
    0: Loop[type='inner',field_space='ct',it_space='internal_pts']
...
Schedule[]
    0: CodedKern compute_pnew_code(pnew_fld,pold_fld,cu_fld,
        cv_fld,tdt,dx,dy) [module_inline=False]

```

And now the same schedule when instrumenting kernels. In this case each loop nest and kernel call will be contained in a separate region:

```

GOInvokeSchedule[invoke='invoke_1']
0: [Profile]
Schedule[]
    0: Loop[type='outer',field_space='go_cu',it_space='go_internal_pts']
...
Schedule[]
    0: Loop[type='inner',field_space='go_cu',
        it_space='go_internal_pts']
...
Schedule[]
    0: CodedKern compute_unew_code(unew_fld,uold_fld,z_fld,
        cv_fld,h_fld,tdt,dy) [module_inline=False]
1: [Profile]
Schedule[]
    0: Loop[type='outer',field_space='go_cv',it_space='go_internal_pts']
...
Schedule[]
    0: Loop[type='inner',field_space='go_cv',
        it_space='go_internal_pts']
...
Schedule[]
    0: CodedKern compute_vnew_code(vnew_fld,vold_fld,z_fld,
        cu_fld,h_fld,tdt,dy) [module_inline=False]
2: [Profile]
Schedule[]
    0: Loop[type='outer',field_space='go_ct',it_space='go_internal_pts']
...
Schedule[]

```

(continues on next page)

(continued from previous page)

```

0: Loop[type='inner',field_space='go_ct',
      it_space='go_internal_pts']
...
Schedule[]
0: CodedKern compute_pnew_code(pnew_fld,pold_fld,
      cu_fld,cv_fld,tdt,dx,dy) [module_inline=False]

```

Both options can be specified at the same time:

```

GOInvokeSchedule[invoke='invoke_1']
0: [Profile]
  Schedule[]
  0: [Profile]
    Schedule[]
    0: Loop[type='outer',field_space='go_cu',
          it_space='go_internal_pts']
    ...
    Schedule[]
    0: Loop[type='inner',field_space='go_cu',
          it_space='go_internal_pts']
    ...
    Schedule[]
    0: CodedKern compute_unew_code(unew_fld,uold_fld,
          ...) [module_inline=False]
1: [Profile]
  Schedule[]
  0: Loop[type='outer',field_space='go_cv',
        it_space='go_internal_pts']
  ...
  Schedule[]
  0: Loop[type='inner',field_space='go_cv',
        it_space='go_internal_pts']
  ...
  Schedule[]
  0: CodedKern compute_vnew_code(vnew_fld,vold_fld,
        ...) [module_inline=False]
2: [Profile]
  Schedule[]
  0: Loop[type='outer',field_space='go_ct',
        it_space='go_internal_pts']
  ...
  Schedule[]
  0: Loop[type='inner',field_space='go_ct',
        it_space='go_internal_pts']
  ...
  Schedule[]
  0: CodedKern compute_pnew_code(pnew_fld,pold_fld,
        ...) [module_inline=False]

```

23.4 Profiling in Scripts - ProfileTrans

The greatest flexibility is achieved by using the profiler transformation explicitly in a transformation script. The script takes either a single PSyIR Node or a list of PSyIR Nodes as argument, and will insert a Profile Node into the PSyIR, with the specified nodes as children. At code creation time the listed children will all be enclosed in one profile region. As an example:

```
from psyclone.psyir.transformations import ProfileTrans

p_trans = ProfileTrans()
schedule = psy.invokes.get('invoke_0').schedule
print(schedule.view())

# Enclose some children within a single profile region
p_trans.apply(schedule.children[1:3])
print(schedule.view())
```

The profiler transformation also allows the profile name to be set explicitly, rather than being automatically created (see *Naming Profiling Regions* for details). This allows for potentially more intuitive names or finer grain control over profiling (as particular regions could be provided with the same profile names). For example:

```
invoke = psy.invokes.invoke_list[0]
schedule = invoke.schedule
profile_trans = ProfileTrans()
# Use the actual psy-layer module and subroutine names.
options = {"region_name": (psy.name, invoke.name)}
profile_trans.apply(schedule.children, options=options)
# Use own names and repeat for different regions to aggregate profile.
options = {"region_name": ("my_location", "my_region")}
profile_trans.apply(schedule[0].children[1:2], options=options)
profile_trans.apply(schedule[0].children[5:7], options=options)
```

Warning: If “region_name” is misspelt in the options dictionary then the option will be silently ignored. This is true for all options. Issue #613 captures this problem.

Warning: It is the responsibility of the user to make sure that a profile region is only created inside a multi-threaded region if the profiling library used is thread-safe!

23.5 Naming Profiling Regions

A profile region derives its name from two components:

module_name

A string identifying the psy-layer containing this profile node.

region_name

A string identifying the invoke containing this profile node and its location within the invoke (where necessary).

By default PSyclone will generate appropriate names to uniquely determine a particular region. Since those names can be somewhat cryptic, alternative names can be specified by the user when adding profiling via a transformation script,

see [Passing Parameters From the User to the Node Constructor](#).

The automatic name generation depends on the API according to the following rules:

For the *NEMO API*,

- the *module_name* string is set to the name of the parent function/subroutine/program. This name is unique as Fortran requires these names to be unique within a program.
- the *region_name* is set to an *r* (standing for region) followed by an integer which uniquely identifies the profile within the parent function/subroutine/program (based on the profile node's position in the PSyIR representation relative to any other profile nodes).

For the *LFRic (Dynamo0.3)* and *GOcean1.0* APIs,

- the *module_name* string is set to the module name of the generated PSy-layer. This name should be unique by design (otherwise module names would clash when compiling).
- the *region_name* is set to the name of the invoke in which it resides, followed by a *:* and a kernel name if the profile region contains a single kernel, and is completed by *:r* (standing for region) followed by an integer which uniquely identifies the profile within the invoke (based on the profile node's position in the PSyIR representation relative to any other profile nodes). For example:

```
InvokeSchedule[invoke='invoke_0', dm=True]
0: Profile[]
  Schedule[]
    0: Profile[]
      Schedule[]
        0: HaloExchange[field='f2', type='region', depth=1,
          check_dirty=True]
        1: HaloExchange[field='m1', type='region', depth=1,
          check_dirty=True]
        2: HaloExchange[field='m2', type='region', depth=1,
          check_dirty=True]
      1: Profile[]
        Schedule[]
          0: Loop[type='', field_space='w1', it_space='cells',
            upper_bound='cell_halo(1)']
            Literal[value:'1', DataType.INTEGER]
            Literal[value:'mesh%get_last_halo_cell(1)',
              DataType.INTEGER]
            Literal[value:'1', DataType.INTEGER]
            Schedule[]
              0: CodedKern testkern_code(a,f1,f2,m1,m2)
                [module_inline=False]
          1: Profile[]
            Schedule[]
              0: Loop[type='', field_space='w1',
                it_space='cells',
                upper_bound='cell_halo(1)']
                Literal[value:'1', DataType.INTEGER]
                Literal[value:'mesh%get_last_halo_cell(1)',
                  DataType.INTEGER]
                Literal[value:'1', DataType.INTEGER]
                Schedule[]
                  0: CodedKern testkern_code(a,f1,f2,m1,m2)
                    [module_inline=False]
```

(continues on next page)

(continued from previous page)

```

2: Loop[type=' ', field_space='w1', it_space='cells',
    upper_bound='cell_halo(1)']
    Literal[value:'1', DataType.INTEGER]
    Literal[value:'mesh%get_last_halo_cell(1)', DataType.INTEGER]
    Literal[value:'1', DataType.INTEGER]
    Schedule[]
    0: CodedKern testkern_qr_code(f1,f2,m1,a,m2,istp)
        [module_inline=False]

```

This is the code created for this example:

```

MODULE container
CONTAINS
SUBROUTINE invoke_0(a, f1, f2, m1, m2, istp, qr)
...
CALL psy_data_3%PreStart("multi_functions_multi_invokes_psy", "invoke_0:r0", &
    0, 0)
CALL psy_data%PreStart("multi_functions_multi_invokes_psy", "invoke_0:r1", 0, 0)
IF (f2_proxy%is_dirty(depth=1)) THEN
    CALL f2_proxy%halo_exchange(depth=1)
END IF
IF (m1_proxy%is_dirty(depth=1)) THEN
    CALL m1_proxy%halo_exchange(depth=1)
END IF
IF (m2_proxy%is_dirty(depth=1)) THEN
    CALL m2_proxy%halo_exchange(depth=1)
END IF
CALL psy_data%PreEnd()
CALL psy_data_1%PreStart("multi_functions_multi_invokes_psy", "invoke_0:r2", &
    0, 0)
DO cell=1,mesh%get_last_halo_cell(1)
    CALL testkern_code(...)
END DO
...
CALL psy_data_2%PreStart("multi_functions_multi_invokes_psy", &
    "invoke_0:testkern_code:r3", 0, 0)
DO cell=1,mesh%get_last_halo_cell(1)
    CALL testkern_code(...)
END DO
...
CALL psy_data_2%PostEnd()
CALL psy_data_1%PostEnd()
...
DO cell=1,mesh%get_last_halo_cell(1)
    CALL testkern_qr_code(...)
END DO
...
CALL psy_data_3%PostEnd()
...
END SUBROUTINE invoke_0
END MODULE container

```


PSY KERNEL EXTRACTOR (PSYKE)

24.1 Introduction

PSyclone has the ability to define regions of a PSyclone-conformant code to be extracted and run as a stand-alone application. This ability, called PSyKE (PSy Kernel Extractor), can be useful for benchmarking parts of a model, such as LFRic, without the need for using its infrastructure.

24.1.1 Mechanism

The code marked for extraction can be (subject to *Restrictions*):

- One or more Nodes in an Invoke (e.g. Loops containing Kernel or Built-In calls, a Directive enclosing one or more Loops) or
- The entire Invoke (extraction applied to all Nodes).

The basic mechanism of code extraction is through applying the `ExtractTrans` transformation to selected Nodes. This transformation is further sub-classed into API-specific implementations, `LFRicExtractTrans` and `GOceanExtractTrans`. Both sub-classed transformations insert an instance of the `ExtractNode` object into the Schedule of a specific Invoke. All Nodes marked for extraction become children of the `ExtractNode`.

The `ExtractNode` class uses the dependency analysis to detect which variables are input-, and which ones are output-parameters. The lists of variables are then passed to the `PSyDataNode`, which is the base class of any `ExtractNode` (details of the `PSyDataNode` can be found in `psy_data`). This node then creates the actual code, as in the following LFRic example:

```
! ExtractStart
!
CALL extract_psy_data%PreStart("testkern_mod", "testkern_code", 4, 2)
CALL extract_psy_data%PreDeclareVariable("a", a)
CALL extract_psy_data%PreDeclareVariable("f2", f2)
CALL extract_psy_data%PreDeclareVariable("m1", m1)
CALL extract_psy_data%PreDeclareVariable("m2", m2)
CALL extract_psy_data%PreDeclareVariable("map_w1", map_w1)
...
CALL extract_psy_data%PreDeclareVariable("undf_w3", undf_w3)
CALL extract_psy_data%PreDeclareVariable("f1_post", f1)
CALL extract_psy_data%PreDeclareVariable("cell_post", cell)
CALL extract_psy_data%PreEndDeclaration
CALL extract_psy_data%ProvideVariable("a", a)
CALL extract_psy_data%ProvideVariable("f2", f2)
CALL extract_psy_data%ProvideVariable("m1", m1)
```

(continues on next page)

(continued from previous page)

```

CALL extract_psy_data%ProvideVariable("m2", m2)
CALL extract_psy_data%ProvideVariable("map_w1", map_w1)
...
CALL extract_psy_data%ProvideVariable("undf_w3", undf_w3)
CALL extract_psy_data%PreEnd
DO cell=1,f1_proxy%vspace%get_ncell()
!
  CALL testkern_code(nlayers, a, f1_proxy%data, f2_proxy%data, &
    m1_proxy%data, m2_proxy%data, ndf_w1, undf_w1, &
    map_w1(:,cell), ndf_w2, undf_w2, map_w2(:,cell), ndf_w3, &
    undf_w3, map_w3(:,cell))
END DO
CALL extract_psy_data%PostStart
CALL extract_psy_data%ProvideVariable("cell_post", cell)
CALL extract_psy_data%ProvideVariable("f1_post", f1)
CALL extract_psy_data%PostEnd
!
! ExtractEnd

```

The *PSyData API* relies on generic Fortran interfaces to provide the field-type-specific implementations of the Provide-Variable for different types. This means that a different version of the external PSyData library that PSyKE uses must be supplied for each PSyclone API.

24.1.2 Restrictions

Code extraction can be applied to unoptimised or optimised code. There are restrictions that check for correctness of optimising transformations when extraction is applied, as well as restrictions that eliminate dependence on the specific model infrastructure.

General

This group of restrictions is enforced irrespective of whether optimisations are used or not.

- Extraction can be applied to a single Node or a list of Nodes in a Schedule. For the latter, Nodes in the list must be consecutive children of the same parent Schedule.
- Extraction cannot be applied to an ExtractNode or a Node list that already contains one (otherwise we would have an extract region within another extract region).
- A Kernel or a Built-In call cannot be extracted without its parent Loop.

Distributed memory

As noted in the *Distributed Memory* section, support for distributed memory in PSyclone is currently limited to the *LFRic (Dynamo0.3) API*. Since the implementation generates calls to LFRic infrastructure (e.g. runtime checks for status of field halos), code extraction is not allowed when distributed memory is enabled.

Shared memory and API-specific

The ExtractTrans transformation cannot be applied to:

- A Loop without its parent Directive,
- An orphaned Directive (e.g. OMPDoDirective, ACCLoopDirective) without its parent Directive (e.g. ACC or OMP Parallel Directive),
- A Loop over cells in a colour without its parent Loop over colours in the LFRic API,
- An inner Loop without its parent outer Loop in the GOcean1.0 API.

24.2 Use

The code extraction is currently enabled by utilising a transformation script (see [Script](#) section for more details).

For example, the transformation script which extracts the first Kernel call in LFRic API test example 15.1.2_builtin_and_normal_kernel_invoke.f90 would be written as:

```
from psyclone.domain.lfric.transformations import LFRicExtractTrans

# Get instance of the ExtractRegionTrans transformation
etrans = LFRicExtractTrans()

# Get Invoke and its Schedule
invoke = psy.invokes.get("invoke_0")
schedule = invoke.schedule

# Apply extract transformation to the selected Node
etrans.apply(schedule.children[2])
print(schedule.view())
```

and called as:

```
> psyclone -nodm -s ./extract_single_node.py \
  <path-to-example>/15.1.2_builtin_and_normal_kernel_invoke.f90
```

PSyclone modifies the Schedule of the selected invoke_0:

```
Schedule[invoke='invoke_0' dm=False]
  0: Loop[type='dofs',field_space='any_space_1',it_space='dofs',
        upper_bound='ndofs']
    Literal[value:'NOT_INITIALISED']
    Literal[value:'NOT_INITIALISED']
    Literal[value:'1']
    Schedule[]
      0: BuiltIn setval_c(f5,0.0)
  1: Loop[type='dofs',field_space='any_space_1',it_space='dofs',
        upper_bound='ndofs']
    ...
    Schedule[]
      0: BuiltIn setval_c(f2,0.0)
  2: Loop[type='',field_space='w2',it_space='cells', upper_bound='ncells']
    ...
```

(continues on next page)

(continued from previous page)

```

Schedule[]
  0: CodedKern testkern_code_w2_only(f3,f2) [module_inline=False]
3: Loop[type='',field_space='wtheta',it_space='cells', upper_bound='ncells']
...
Schedule[]
  0: CodedKern testkern_wtheta_code(f4,f5) [module_inline=False]
4: Loop[type='',field_space='w1',it_space='cells', upper_bound='ncells']
...
Schedule[]
  0: CodedKern testkern_code(scalar,f1,f2,f3,f4) [module_inline=False]

```

to insert the extract region. As shown below, all children of an ExtractNode will be part of the region:

```

Schedule[invoke='invoke_0' dm=False]
  0: Loop[type='dofs',field_space='any_space_1',it_space='dofs',
        upper_bound='ndofs']
...
Schedule[]
  0: BuiltIn setval_c(f5,0.0)
1: Loop[type='dofs',field_space='any_space_1',it_space='dofs',
        upper_bound='ndofs']
...
Schedule[]
  0: BuiltIn setval_c(f2,0.0)
2: Extract
  Schedule[]
    0: Loop[type='',field_space='w2',it_space='cells', upper_bound='ncells']
    ...
    Schedule[]
      0: CodedKern testkern_code_w2_only(f3,f2) [module_inline=False]
3: Loop[type='',field_space='wtheta',it_space='cells', upper_bound='ncells']
...
Schedule[]
  0: CodedKern testkern_wtheta_code(f4,f5) [module_inline=False]
4: Loop[type='',field_space='w1',it_space='cells', upper_bound='ncells']
...
Schedule[]
  0: CodedKern testkern_code(scalar,f1,f2,f3,f4) [module_inline=False]

```

To extract multiple Nodes, ExtractTrans can be applied to the list of Nodes (subject to *General* restrictions above):

```

# Apply extract transformation to the selected Nodes
etrans.apply(schedule.children[1:3])

```

This modifies the above Schedule as:

```

...
Extract
Schedule[]
  0: Loop[type='dofs',field_space='any_space_1',it_space='dofs',
        upper_bound='ndofs']
...
Schedule[]

```

(continues on next page)

(continued from previous page)

```

    0: BuiltIn setval_c(f2,0.0)
1: Loop[type='',field_space='w2',it_space='cells', upper_bound='ncells']
...
    Schedule[]
    0: CodedKern testkern_code_w2_only(f3,f2) [module_inline=False]
...

```

As said above, extraction can be performed on optimised code. For example, the following example transformation script first adds !\$OMP PARALLEL DO directive and then extracts the optimised code in LFRic API test example 15.1.2_builtin_and_normal_kernel_invoke.f90:

```

from psyclone.domain.lfric.transformations import LFRicExtractTrans
from psyclone.transformations import DynamoOMPParallelLoopTrans

# Get instances of the transformations
etrans = LFRicExtractTrans()
otrans = DynamoOMPParallelLoopTrans()

# Get Invoke and its Schedule
invoke = psy.invokes.get("invoke_0")
schedule = invoke.schedule

# Add OMP PARALLEL DO directives
otrans.apply(schedule.children[1])
otrans.apply(schedule.children[2])
# Apply extract transformation to the selected Nodes
etrans.apply(schedule.children[1:3])
print(schedule.view())

```

The generated code is now:

```

! ExtractStart
CALL extract_psy_data%PreStart("unknown-module", "setval_c", 0, 4)
CALL extract_psy_data%PreDeclareVariable("cell_post", cell)
CALL extract_psy_data%PreDeclareVariable("df_post", df)
CALL extract_psy_data%PreDeclareVariable("f2_post", f2)
CALL extract_psy_data%PreDeclareVariable("f3_post", f3)
...
CALL extract_psy_data%PreEndDeclaration
...
CALL extract_psy_data%PreEnd
!
!$omp parallel do default(shared), private(df), schedule(static)
DO df=1,undf_asep1_f2
  f2_proxy%data(df) = 0.0
END DO
!$omp end parallel do
!$omp parallel do default(shared), private(cell), schedule(static)
DO cell=1,f3_proxy%vspace%get_ncell()
  !
  CALL testkern_code_w2_only(nlayers, f3_proxy%data, f2_proxy%data, ndf_w2, undf_w2, map_
  ↪w2(:,cell))

```

(continues on next page)

(continued from previous page)

```
END DO
!$omp end parallel do
CALL extract_psy_data%PostStart
CALL extract_psy_data%ProvideVariable("cell_post", cell)
CALL extract_psy_data%ProvideVariable("df_post", df)
CALL extract_psy_data%ProvideVariable("f2_post", f2)
CALL extract_psy_data%ProvideVariable("f3_post", f3)
CALL extract_psy_data%PostEnd
!
! ExtractEnd
```

Examples in `examples/lfric/eg12` directory demonstrate how to apply code extraction by utilising PSyclone transformation scripts (see [Examples](#) section for more information). The code in `examples/lfric/eg17/full_example_extract` can be compiled and run, and it will create two kernel data files.

24.3 Extraction Libraries

PSyclone comes with two extraction libraries: one is based on NetCDF and will create NetCDF files to contain all input- and output-parameters. The second one is a stand-alone library which uses only standard Fortran IO to write and read kernel data. The binary files produced using this library may not be portable between machines and compilers. If you require such portability then please use the NetCDF extraction library.

The two extraction *libraries* are in `lib/extract/standalone`. and in `lib/extract/netcdf`.

24.3.1 Extraction for GOcean

The extraction libraries in `lib/extract/standalone/dl_esm_inf` and `lib/extract/netcdf/dl_esm_inf` implement the full PSy-Data API for use with the *GOcean1.0* `dl_esm_inf` infrastructure library. When running the instrumented executable, it will create either a binary or a NetCDF file for each instrumented code region. It includes all variables that are read before the code is executed, and all variables that have been modified. The output variables have the postfix `_post` attached to the names, e.g. a variable `xyz` that is read and written will be stored with the name `xyz` containing the input values, and the name `xyz_post` containing the output values. Arrays have their size explicitly stored (in case of NetCDF as dimensions): again the variable `xyz` will have its sizes stored as `xyzdim1`, `xyzdim2` for the input values, and output arrays use the name `xyz_postdim1`, `xyz_postdim2`.

Note: The stand-alone library does not store the names of the variables in the output file, but these names will be used as variable names in the created driver.

The output file contains the values of all variables used in the subroutine. The `GOceanExtractTrans` transformation can automatically create a driver program which will read the corresponding output file, call the instrumented region, and compare the results. In order to create this driver program, the options parameter `create_driver` must be set to `true`:

```
extract = GOceanExtractTrans()
extract.apply(schedule.children,
              {"create_driver": True,
               "region_name": ("main", "init")})
```

This will create a Fortran file called `driver-main-init.f90`, which can then be compiled and executed. This stand-alone program will read the output file created during an execution of the actual program, call the kernel with all required input

parameter, and compare the output variables with the original output variables. This can be used to create stand-alone test cases to reproduce a bug, or for performance optimisation of a stand-alone kernel.

Warning: Care has to be taken that the driver matches the version of the code that was used to create the output file, otherwise the driver will likely crash. The stand-alone driver relies on a strict ordering of variable values in the output file and e.g. even renaming one variable can affect this. The NetCDF version stores the variable names and will not be able to find a variable if its name has changed.

24.3.2 Extraction for LFRic

The libraries in `lib/extract/standalone/lfric` and `lib/extract/netcdf/lfric` implement the full PSyData API for use with the *LFRic* infrastructure library. When running the code, it will create an output file for each instrumented code region. The same logic for naming variables (using `_post` for output variables) used in *Extraction for GOcean* is used here.

As in the case of e.g. *read-only verification*, this library uses the pared-down LFRic infrastructure located in a clone of PSyclone repository, `<PSYCLONEHOME>/src/psyclone/tests/test_files/dynamo0p3/infrastructure`. However, this needs to be changed for any user (for instance with PSyclone installation). Please refer to the relevant README.md documentation on how to build and link this library.

The output file contains the values of all variables used in the subroutine. The `LFRicExtractTrans` transformation can automatically create a driver program which will read the corresponding output file, call the instrumented region, and compare the results. In order to create this driver program, the options parameter `create_driver` must be set to `true`:

```
extract = LFRicExtractTrans()
extract.apply(schedule.children,
              {"create_driver": True,
               "region_name": ("main", "init")})
```

This will create a Fortran file called `driver-main-init.F90`, which can then be compiled and executed. This stand-alone program will read the output file created during an execution of the actual program, call the kernel with all required input parameter, and compare the output variables with the original output variables. This can be used to create stand-alone test cases to reproduce a bug, or for performance optimisation of a stand-alone kernel.

Warning: Care has to be taken that the driver matches the version of the code that was used to create the output file, otherwise the driver will likely crash. The stand-alone driver relies on a strict ordering of variable values in the output file and e.g. even renaming one variable can affect this. The NetCDF version stores the variable names and will not be able to find a variable if its name has changed.

Note: If the kernel, or any function called from an extracted kernel should use a variable from a module directly (as opposed to supplying this as parameter in the kernel call), this variable will not be written to the extract data file, and the driver will also not try to read in the value. As a result, the kernel will not be able to run stand-alone. As a work-around, these values can be added manually to the driver program. Issue #1990 tracks improvement of this situation.

The LFRic kernel driver will inline all required external modules into the driver. It uses a `ModuleManager` to find the required modules, based on the assumption that a file `my_special_mod.f90` will define exactly one module called `my_special_mod` (the `_mod` is required to be part of the filename). The driver creator will sort the modules in the appropriate order and add the source code directly into the driver. As a result, the driver program is truly stand-alone and does not need any external dependency (the only exception being NetCDF if the NetCDF-based extraction library is

used). The ModuleManager uses all kernel search paths specified on the command line (see `-d` option in *The psyclone command*), and it will recursively search for all files under each path specified on the command line.

Therefore, compilation for a created driver, e.g. the one created in `examples/lfric/eg17/full_example_extract`, is simple:

```
$ gfortran -g -O0 driver-main-update.F90 -o driver-main-update
$ ./driver-main-update
cell correct
field1 correct
```

Note that the Makefile in the example will actually provide additional include paths (infrastructure files and extraction library) for the compiler, but these flags are actually only required for compiling the example program, not for the driver.

24.3.3 Extraction for NEMO

The libraries in `lib/extract/standalone/nemo` and `lib/extract/netcdf/nemo` implement the full PSyData API for use with the *NEMO* API. When running the code, it will create an output file for each instrumented code region. The same logic for naming variables used in *Extraction for GOcean* is used here.

Note: Driver creation in NEMO is not yet supported, and is tracked in issue #2058.

CONFIGURATION

PSyclone reads various run-time configuration options from the `psyclone.cfg` file. As described in [Configuration](#), the default `psyclone.cfg` configuration file is installed in `<python-base-prefix>/share/psyclone/` during the installation process. The original version of this file is in the `PSyclone/config` directory of the PSyclone distribution.

At execution-time, the user can specify a custom configuration file to be used. This can either be done with the `--config` command line option, or by specifying the (full path to the) configuration file to use via the `PSYCLONE_CONFIG` environment variable. If the specified configuration file is not found then PSyclone will fall back to searching in a list of default locations.

The ordering of these locations depends upon whether PSyclone is being run within a Python virtual environment (such as `venv`). If no virtual environment is detected then the locations searched, in order, are:

1. `${PWD}/.psyclone/`
2. `${HOME}/.local/share/psyclone/`
3. `<python-base-dir>/share/psyclone/`

where `<python-base-dir>` is the path stored in Python's `sys.prefix`.

If a virtual environment is detected then it is assumed that the `share` directory will be a part of that environment. In order to maintain isolation of distinct virtual environments this directory is then checked *before* the user's home directory. i.e. the list of locations searched is now:

1. `${PWD}/.psyclone/`
2. `<python-base-dir>/share/psyclone/`
3. `${HOME}/.local/share/psyclone/`

Note that for developers a slightly different configuration handling is implemented, see [Module: configuration](#) for details.

25.1 Options

The configuration file is read by the Python `ConfigParser` class (<https://docs.python.org/3/library/configparser.html>) and must be formatted accordingly. It currently consists of a `DEFAULT` section e.g.:

```
[DEFAULT]
DEFAULTAPI = dynamo0.3
DEFAULTSTUBAPI = dynamo0.3
DISTRIBUTED_MEMORY = true
REPRODUCIBLE_REDUCTIONS = false
REPROD_PAD_SIZE = 8
```

(continues on next page)

(continued from previous page)

```
PSYIR_ROOT_NAME = psyir_tmp
VALID_PSY_DATA_PREFIXES = profile, extract
```

and an optional API specific section, for example for the dynamo0.3 section:

```
[dynamo0.3]
access_mapping = gh_read: read, gh_write: write, gh_readwrite: readwrite,
                 gh_inc: inc, gh_readinc: readinc, gh_sum: sum
COMPUTE_ANNEXED_DOFS = false
supported_fortran_datatypes = real, integer, logical
default_kind = real: r_def, integer: i_def, logical: l_def
RUN_TIME_CHECKS = false
NUM_ANY_SPACE = 10
NUM_ANY_DISCONTINUOUS_SPACE = 10
```

or for gocean1.0:

```
[gocean1.0]
access_mapping = go_read:read, go_write:write, go_readwrite:readwrite
grid-properties = go_grid_xstop: {0}%%grid%%subdomain%%internal%%xstop: scalar,
                  go_grid_ystop: {0}%%grid%%subdomain%%internal%%ystop: scalar,
                  go_grid_data: {0}%%data: array,
                  ...
```

The meaning of the various entries is described in the following sub-sections.

Note that ConfigParser supports various forms of boolean entry including “true/false”, “yes/no” and “1/0”. See <https://docs.python.org/3/library/configparser.html#supported-datatypes> for more details.

25.1.1 DEFAULT Section

This section contains entries that are, in principle, applicable to all APIs supported by PSyclone.

Entry	Description
DEFAULTAPI	The API that PSyclone assumes an Algorithm/Kernel conforms to if no API is specified. Must be one of the APIs supported by PSyclone (“dynamo0.3”, “gocean1.0” and “nemo”). If there is no API specified and there is only one API-specific section in the config file loaded, this API will be used. This value can be overwritten by the command line option ‘-api’. If there is no API entry in the config file, and ‘-api’ is not specified on the command line, “dynamo0.3” is used as default.
DEFAULTSTUBAPI	The API that the kernel-stub generator assumes by default. Must be one of the stub-APIs supported by PSyclone (“dynamo0.3” only at this stage).
DISTRIBUTED_MEMORY	Whether or not to generate code for distributed-memory parallelism by default. Note that this is currently only supported for the LFRic (Dynamo 0.3) API.
REPRODUCIBLE_REDUCTIONS	Whether or not to generate code for reproducible OpenMP reductions (see Reductions) by default.
REPROD_PAD_SIZE	If generating code for reproducible OpenMP reductions, this setting controls the amount of padding used between elements of the array in which each thread accumulates its local reduction. (This prevents false sharing of cache lines by different threads.)
PSYIR_ROOT_NAME	The root for generated PSyIR symbol names if one is not supplied when creating a symbol. Defaults to “psyir_tmp”.
VALID_PSY_DATA_PREFIXES	Which class prefixes are permitted in any PSyData-related transformations. See PSyData API for details.

25.1.2 Common Sections

The following entries must be defined for each API in order for PSyclone to work as expected:

Entry	Description
access_mapping	<p>This field defines the strings that are used by a particular API to indicate write, read, ... access. Its value is a comma separated list of access-string:access pairs, e.g.:</p> <pre>gh_read: read, gh_write: write, gh_readwrite: readwrite, gh_inc: inc, gh_readinc: gh_sum: sum</pre> <p>At this stage these 6 types are defined for read, write, read+write, increment, read+increment and summation access by PSyclone. Sum is a form of reduction. The GOcean API does not support increment or sum, so it only defines three mappings for read, write, and readwrite.</p>

25.1.3 dynamo0.3 Section

This section contains configuration options that are only applicable when using the LFRic (Dynamo 0.3) API.

Entry	Description
COMPUTE_ANNEXED_DOFS	Whether or not to perform redundant computation over annexed dofs in order to reduce the number of halo exchanges, see <i>Annexed DoFs</i> .
supported_fortran_datatypes	Captures the supported Fortran data types of LFRic arguments, see <i>Supported Data Types and Default Kind</i> .
default_kind	Captures the default kinds (precisions) for the supported Fortran data types in LFRic, see <i>Supported Data Types and Default Kind</i> .
RUN_TIME_CHECKS	Specifies whether to generate run-time validation checks, see <i>Run-time Checks</i> .
NUM_ANY_SPACE	Sets the number of ANY_SPACE function spaces in LFRic, see <i>Number of Generalised ANY_*_SPACE Function Spaces</i> .
NUM_ANY_DISCONTINUOUS_SPACE	Sets the number of ANY_DISCONTINUOUS_SPACE function spaces in LFRic, see <i>Number of Generalised ANY_*_SPACE Function Spaces</i> .

25.1.4 gocean1.0 Section

This section contains configuration options that are only applicable when using the Gocean 1.0 API.

Entry	Description
iteration-spaces	This contains definitions of additional iteration spaces used by PSyclone. A detailed description can be found in the <i>Iteration-spaces</i> section of the GOcean1.0 chapter.
grid-properties	This key contains definitions to access various grid properties. A detailed description can be found in the <i>Grid Properties</i> section of the GOcean1.0 chapter.

25.1.5 NEMO Section

This section contains configuration options that are only applicable when using the NEMO API.

Entry	Description
mapping-TYPE	This declares a mapping for a certain loop level, specified as TYPE. Each value must have three key:value pairs. A value can be empty if it is not required or not known, but the key must still be specified. The required keys are: var: the variable name that indicates the loop level, start: the first loop iteration, and stop: the last loop iteration. Each loop detected by the NEMO API will be given one of the TYPE values specified in the configuration file. See the example below for more details.
index-order	Specifies the order in which loops are created when converting an implicit loop to an explicit loop. All values in this comma-separated list must have a corresponding mapping-TYPE value defined.

Below we show an example of the NEMO section of a PSyclone configuration file. Note how the values in index-order have corresponding mapping entries, e.g. mapping-lon, mapping-lat etc.:

```
mapping-lon = var: ji, start: 1, stop: jpi
mapping-lat = var: jj, start: 1, stop: jpj
mapping-levels = var: jk, start: 1, stop: jpk
mapping-tracers = var: jt, start: 1, stop:
mapping-unknown = var: , start: 1, stop:

index-order = lon, lat, levels, tracers
```

If a NEMO loop then uses `Do jj=...`, PSyclone will give this loop the type ‘lat’, because the loop uses the variable name specified in the configuration file for a loop of type ‘lat’. The loop type can be accessed using `loop.loop_type`, i.e. in this example it will be `loop.loop_type == 'lat'`.

The entry `mapping-unknown` has an empty value for the key ‘var’. This means that the type ‘unknown’ will be used for any loop that can not be mapped using any of the other variable names in the configuration file.

BIBLIOGRAPHY

- [nem13] *NEMO Coding Conventions*. 2013. URL: https://forge.nemo-ocean.eu/nemo/attachment/wiki/Documentation/NEMO_coding.conv_v3.pdf2.
- [AFH+19] S. V. Adams, R. W. Ford, M. Hambley, J. M. Hobson, I. Kavčič, C. M. Maynard, T. Melvin, E. H. Müller, S. Mullerworth, A. R. Porter, M. Rezny, B. J. Shipway, and R. Wong. LFRic: Meeting the challenges of scalability and performance portability in Weather and Climate models. *Journal of Parallel and Distributed Computing*, 132:383–396, 2019. doi:<https://doi.org/10.1016/j.jpdc.2019.02.007>.

PYTHON MODULE INDEX

p

- [psyclone.alg_gen](#), 260
- [psyclone.generator](#), 237
- [psyclone.line_length](#), 261
- [psyclone.parse.algorithm](#), 238
- [psyclone.psyGen](#), 259
- [psyclone.transformations](#), 239

A

ACCDataTrans (class in *psyclone.transformations*), 239
 ACCEnterDataTrans (class in *psyclone.transformations*), 240
 ACKernelsTrans (class in *psyclone.transformations*), 241
 ACCLoopTrans (class in *psyclone.transformations*), 242
 ACCParallelTrans (class in *psyclone.transformations*), 243
 ACCRoutineTrans (class in *psyclone.transformations*), 243
 Alg (class in *psyclone.alg_gen*), 260
 ancestor() (*psyclone.psyir.nodes.Node* method), 157
 apply() (*psyclone.transformations.ACCDataTrans* method), 239
 apply() (*psyclone.transformations.ACCEnterDataTrans* method), 240
 apply() (*psyclone.transformations.ACKernelsTrans* method), 241
 apply() (*psyclone.transformations.ACCLoopTrans* method), 242
 apply() (*psyclone.transformations.ACCRoutineTrans* method), 244
 apply() (*psyclone.transformations.ColourTrans* method), 245
 apply() (*psyclone.transformations.Dynamo0p3AsyncHaloExchangeTrans* method), 245
 apply() (*psyclone.transformations.Dynamo0p3ColourTrans* method), 246
 apply() (*psyclone.transformations.Dynamo0p3KernelConstTrans* method), 247
 apply() (*psyclone.transformations.Dynamo0p3OMPLoopTrans* method), 248
 apply() (*psyclone.transformations.Dynamo0p3RedundantComputationTrans* method), 249
 apply() (*psyclone.transformations.DynamoOMPParallelLoopTrans* method), 250
 apply() (*psyclone.transformations.GOceanOMPParallelLoopTrans* method), 251
 apply() (*psyclone.transformations.KernelImportsToArguments* method), 251
 apply() (*psyclone.transformations.MoveTrans* method),

252

apply() (*psyclone.transformations.OMPLoopTrans* method), 254
 apply() (*psyclone.transformations.OMPParallelLoopTrans* method), 255
 apply() (*psyclone.transformations.OMPSingleTrans* method), 257
 apply() (*psyclone.transformations.ParallelRegionTrans* method), 258
 ArgumentInterface (class in *psyclone.psyir.symbols*), 162
 AutomaticInterface (class in *psyclone.psyir.symbols*), 162

C

clauses() (*psyclone.psyir.nodes.RegionDirective* method), 156
 ColourTrans (class in *psyclone.transformations*), 244
 CommonBlockInterface (class in *psyclone.psyir.symbols*), 162
 condition() (*psyclone.psyir.nodes.IfBlock* method), 155
 condition() (*psyclone.psyir.nodes.WhileLoop* method), 155
 container (*psyclone.psyGen.PSy* property), 259
 ContainerSymbol (class in *psyclone.psyir.symbols*), 161
 create() (*psyclone.psyir.nodes.Range* static method), 153

D

DataSymbol (class in *psyclone.psyir.symbols*), 161
 DataTypeSymbol (class in *psyclone.psyir.symbols*), 161
 DefaultModuleInterface (class in *psyclone.psyir.symbols*), 162
 dir_body() (*psyclone.psyir.nodes.RegionDirective* method), 156
 Dynamo0p3AsyncHaloExchangeTrans (class in *psyclone.transformations*), 245
 Dynamo0p3ColourTrans (class in *psyclone.transformations*), 246
 Dynamo0p3KernelConstTrans (class in *psyclone.transformations*), 247
 Dynamo0p3OMPLoopTrans (class in *psyclone.transformations*), 248

Dynamo0p3RedundantComputationTrans (class in *psyclone.transformations*), 249

DynamoOMPParallelLoopTrans (class in *psyclone.transformations*), 250

E

else_body() (*psyclone.psyir.nodes.IfBlock* method), 155

excluded_node_types (*psyclone.transformations.ACCLoopTrans* attribute), 243

F

FortLineLength (class in *psyclone.line_length*), 261

G

gen (*psyclone.alg_gen.Alg* property), 260

gen (*psyclone.psyGen.PSy* property), 259

generate() (in module *psyclone.generator*), 237

get_trans_name() (*psyclone.psyGen.TransInfo* method), 169

get_trans_num() (*psyclone.psyGen.TransInfo* method), 169

GOceanOMPLoopTrans (class in *psyclone.transformations*), 250

GOceanOMPParallelLoopTrans (class in *psyclone.transformations*), 251

I

if_body() (*psyclone.psyir.nodes.IfBlock* method), 155

ImportInterface (class in *psyclone.psyir.symbols*), 162

indices() (*psyclone.psyir.nodes.ArrayReference* method), 156

IntrinsicSymbol (class in *psyclone.psyir.symbols*), 161

invokes (*psyclone.psyGen.PSy* property), 259

K

KernelImportsToArguments (class in *psyclone.transformations*), 251

L

length (*psyclone.line_length.FortLineLength* property), 261

lhs() (*psyclone.psyir.nodes.Assignment* method), 155

list (*psyclone.psyGen.TransInfo* property), 169

long_lines() (*psyclone.line_length.FortLineLength* method), 261

loop_body() (*psyclone.psyir.nodes.Loop* method), 155

loop_body() (*psyclone.psyir.nodes.WhileLoop* method), 156

M

member() (*psyclone.psyir.nodes.StructureReference* method), 156

module

psyclone.alg_gen, 260

psyclone.generator, 237

psyclone.line_length, 261

psyclone.parse.algorithm, 238

psyclone.psyGen, 259

psyclone.transformations, 239

MoveTrans (class in *psyclone.transformations*), 252

N

name (*psyclone.psyGen.PSy* property), 259

name (*psyclone.transformations.ACCEnterDataTrans* property), 239

name (*psyclone.transformations.ACCEnterDataTrans* property), 240

name (*psyclone.transformations.ACCKernelsTrans* property), 241

name (*psyclone.transformations.ACCTrans* property), 243

name (*psyclone.transformations.ACCEnterDataTrans* property), 244

name (*psyclone.transformations.Dynamo0p3AsyncHaloExchangeTrans* property), 245

name (*psyclone.transformations.Dynamo0p3KernelConstTrans* property), 248

name (*psyclone.transformations.KernelImportsToArguments* property), 251

name (*psyclone.transformations.MoveTrans* property), 252

name (*psyclone.transformations.OMPMasterTrans* property), 255

name (*psyclone.transformations.OMPParallelTrans* property), 256

name (*psyclone.transformations.OMPSingleTrans* property), 258

name (*psyclone.transformations.ParallelRegionTrans* property), 258

num_trans (*psyclone.psyGen.TransInfo* property), 170

O

omp_directive (*psyclone.transformations.OMPLoopTrans* property), 254

omp_nowait (*psyclone.transformations.OMPSingleTrans* property), 258

omp_schedule (*psyclone.transformations.OMPLoopTrans* property), 254

OMPLoopTrans (class in *psyclone.transformations*), 253

OMPMasterTrans (class in *psyclone.transformations*), 254

OMPParallelLoopTrans (class in *psyclone.transformations*), 255

OMPParallelTrans (class in *psyclone.transformations*), 256

OMPSingleTrans (class in *psyclone.transformations*), 257

P

ParallelRegionTrans (class in *psyclone.transformations*), 258

parse() (in module *psyclone.parse.algorithm*), 238

process() (*psyclone.line_length.FortLineLength* method), 261

PSy (class in *psyclone.psyGen*), 259

psyclone.alg_gen
module, 260

psyclone.generator
module, 237

psyclone.line_length
module, 261

psyclone.parse.algorithm
module, 238

psyclone.psyGen
module, 259

psyclone.transformations
module, 239

validate() (*psyclone.transformations.Dynamo0p3AsyncHaloExchangeTrans* method), 246

validate() (*psyclone.transformations.Dynamo0p3KernelConstTrans* method), 248

validate() (*psyclone.transformations.Dynamo0p3OMPLoopTrans* method), 248

validate() (*psyclone.transformations.Dynamo0p3RedundantComputationTrans* method), 249

validate() (*psyclone.transformations.GOceanOMPLoopTrans* method), 251

validate() (*psyclone.transformations.KernelImportsToArguments* method), 251

validate() (*psyclone.transformations.MoveTrans* method), 253

validate() (*psyclone.transformations.OMPParallelTrans* method), 256

validate() (*psyclone.transformations.ParallelRegionTrans* method), 258

W

walk() (*psyclone.psyir.nodes.Node* method), 157

R

Range (class in *psyclone.psyir.nodes*), 152

rhs() (*psyclone.psyir.nodes.Assignment* method), 155

RoutineSymbol (class in *psyclone.psyir.symbols*), 161

S

start (*psyclone.psyir.nodes.Range* property), 153

StaticInterface (class in *psyclone.psyir.symbols*), 162

step (*psyclone.psyir.nodes.Range* property), 153

stop (*psyclone.psyir.nodes.Range* property), 153

Symbol (class in *psyclone.psyir.symbols*), 160

SymbolTable (class in *psyclone.psyir.symbols*), 160

T

TransInfo (class in *psyclone.psyGen*), 169

U

UnknownInterface (class in *psyclone.psyir.symbols*), 162

UnresolvedInterface (class in *psyclone.psyir.symbols*), 162

V

validate() (*psyclone.transformations.ACCEnterDataTrans* method), 239

validate() (*psyclone.transformations.ACCEnterDataTrans* method), 241

validate() (*psyclone.transformations.ACCKernelsTrans* method), 242

validate() (*psyclone.transformations.ACCEnterDataTrans* method), 244