


HTTP Methods

- In your coursework you are going to develop a dynamic website
- As a part of this you will use a database and perform different operations on the database based on your requirements.
- On a database, you are expected to perform **CRUD** operations.




- You will use **HTTP methods** to perform CRUD operations.

- You can use GET, PUT, POST, DELETE methods to accomplish the CRUD operations.
- **Search** and **Identify** the functionality of each of the above mentioned methods and replace the question marks below with suitable methods.



- You can use GET, PUT, POST, DELETE methods to accomplish the CRUD operations.
- **Search** and **Identify** the functionality of each of the above mentioned methods and replace the question marks below with suitable methods.



Parameters

- From your previous activity you must know how each HTTP request is made, i.e., the format of each request.
- Via HTTP requests, clients can pass **parameters** to the server (e.g. price=100)
- Parameters are simple **name** and **value** pairs
- Parameters are generally collected from **HTML forms**
- Form values are sent as parameters to the server when you click the `Submit` or `Next` button on the form
- The client **encodes** parameters before they are sent to the server (why?)
- Multiple parameters are separated by **ampersands** (&)



First Name

Last Name

Street Address

Red

☐ Male

☐ Female

URL Encoding reference: https://www.w3schools.com/tags/ref_urlencode.ASP

Parameters with GET and POST

GET and POST are two widely used HTTP methods. Find the dissimilarities between these two methods.

- With a GET request, parameters are added at the end of the URL in encoded form
- If your URL is the following
 - <http://www.mydomain.com/mypage>
- The parameter “user” added to the URL
 - <http://www.mydomain.com/mypage?user=myName>
- Additional parameters can be added, separated by &
 - <http://www.mydomain.com/mypage?user=myName&postcode=BD71DP>
- POST is basically the same as GET, but parameters are handled differently:
 - parameters are passed as the body of request with the same type of encoding
- If you have lots of parameters or binary data, you may use the POST request

PUT vs POST

- It appears that in many cases PUT and POST methods can achieve the same outcome. But these methods are not the same.
- The choice of a particular method to do a job can have significant side effects.
- Find the differences between the PUT and POST method.

Idempotent Safe

| | | | |
|---|--------|---|--------|
| ✓ | GET | ✓ | GET |
| ✓ | PUT | ✗ | PUT |
| ✗ | POST | ✗ | POST |
| ✓ | DELETE | ✗ | DELETE |

An idempotent HTTP method is a HTTP method that can be called many times without different outcomes.

Safe methods are HTTP methods that do not modify resources.