

Home

STM32F103C8Tx

test2.ioc - Pinout & Configuration

GENERATE CODE

Pinout & Configuration

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

I2C Mode and Configuration

I2C Mode

I2C I2C

Configuration

Reset Configuration

NVIC Settings

DMA Settings

GPIO Settings

Parameter Settings

User Constants

NVIC Interrupt Table	Enabled	Preemption Priority	Sub Priority
I2C2 event interrupt	☒	0	0
I2C2 error interrupt	☒	0	0

Categories

A->Z

System Core

DMA

GPIO

IWDG

NVIC

RCC

SYS

WWDG

Analog

Timers

RTC

TIM1

TIM2

TIM3

TIM4

Connectivity

CAN

I2C1

I2C2

SP11

SP12

USART1

USART2

Pinout view

System view

Pinout diagram of STM32F103C8Tx LQFP48 showing various pins and their connections.

Home

STM32F103C8Tx

test2.ioc - Pinout & Configuration

GENERATE CODE

Pinout & Configuration

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

Search

Categories

A-Z

System Core

DMA

GPIO

IWDG

NVIC

✓ RCC

⚠ SYS

WWDG

Analog

Timers

RTC

TIM1

⚠ TIM2

✓ TIM3

TIM4

Connectivity

CAN

I2C1

✓ I2C2

SPI1

SPI2

USART1

✗ USART2

TIM3 Mode and Configuration

Mode

Slave Mode

Disable

Trigger Source

Disable

☒ Internal Clock

Channel1

Disable

Channel2

Disable

Channel3

Disable

Channel4

Disable

Combined Channels

Disable

☐ XOR activation

☐ One Pulse Mode

Configuration

Reset Configuration

⚙ NVIC Settings

⚙ DMA Settings

✓ Parameter Settings

✓ User Constants

Configure the below parameters :

Search (Ctrl+F)

Counter Settings

Prescaler (PSC - 16 bits valu..7199

Counter Mode

Up

Counter Period (AutoReload ..4999

Internal Clock Division (CKD)

No Division

auto-reload preload

Disable

Trigger Output (TRGO) Parameters

Master/Slave Mode (MSM bit. Disable (Trigger input effect not delay...

Pinout view

System view

VDD

VSS

PC13-..

PC14-..

PC15-..

RCC_OSC_IN

RCC_OSC_OUT

PD0-O..

PD1-O..

NRST

VSSA

VDDA

GPIO_Outp..

GPIO_Outp..

GPIO_Outp..

PA3

PA4

PA5

PA6

PA7

PB0

PB1

PB2

PB10

PB11

VSS

VDD

GPIO_Inp..4

I2C2_SCL

I2C2_SDA

PA14

PA13

PA12

PA11

PA10

PA9

PA8

PB15

PB14

PB13

PB12

SYSTICK-SWCLK

SYSTICK-SWDIO

Pinout & Configuration

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

Search

Categories

A->Z

System Core

DMA

GPIO

IWDG

NVIC

✓ RCC

⚠ SYS

WWDG

Analog

Timers

RTC

TIM1

⚠ TIM2

✓ TIM3

TIM4

Connectivity

CAN

I2C1

✓ I2C2

SPI1

SPI2

USART1

✖ USART2

GPIO Mode and Configuration

Configuration

Group By Peripherals

✓ GPIO ✓ I2C ✓ RCC ✓ SYS

Search Signals

Search (Ctrl+F)

☐ Show only Modified Pins

Pin ...	Signal o...	GPIO o...	GPIO m...	GPIO P...	Maximu...	User La...	Modified
PA0-W...	n/a	Low	Output ...	No pull-...	Low		☐
PA1	n/a	n/a	Input m...	Pull-up	n/a		☒
PA2	n/a	n/a	Input m...	Pull-up	n/a		☒
PA3	n/a	n/a	Input m...	Pull-up	n/a		☒

?

Select Pins from table to configure them. **Multiple selection is Allowed.**

Pinout view

System view

Pinout diagram of the STM32F103C8Tx LQFP48 package. The diagram shows the chip with pins labeled around its perimeter. Key pins and their functions include:

- Top:** VDD, VSS, PB9, PB8, BOOT0, PB7, PB6, PB5, PB4, PB3, PB2, PB1, PA15, PA14, SYS_JTCK-SWCLK.
- Right:** VDD, VSS, PA13, SYS_JTMS-SWDIO, PA12, PA11, PA10, PA9, PA8, PB15, PB14, PB13, PB12.
- Bottom:** PA3, PA4, PA5, PA6, PA7, PB0, PB1, PB2, PB10, PB11, VSS, VDD, I2C2_SCL, I2C2_SDA.
- Left:** GPIO_Input, PA2, PA1, PA0, VDDA, VSSA, NRST, PD1-O, PD0-O, RCC_OSC_OUT, RCC_OSC_IN, PC15, PC14, PC13, VBAT.