

Adding Nobita (Human)

Postman interface showing a POST request to `http://localhost:5000/character`. The request body is a JSON object:

```
{  "charactername": "Nobita",  "role": "human",  "password": "human123"}
```

The response is a 201 Created status with a JSON body:

```
{  "success": true,  "data": {    "_id": "6821db341a8fbcc9e6955f5b",    "charactername": "Nobita",    "role": "human",    "token": "eyJ3b2ZlVHhE6QToS2NyXpEda8Wm_ywbQ87H811gn5fn5oQ"  }}}
```


MongoDB Compass interface showing the `characters` collection. The collection contains two documents:

```
{  "_id": ObjectId('6821da7f1a8fbcc9e6955f58'),  "charactername": "Doraemon",  "password": "$2b$10$XQtnbd7CFyWYrrAwm5WNN0dK/dvbKfQMbd/CTAUlWg1HqcqJfxk",  "role": "robot",  "createdAt": 2025-05-12T11:24:47.251+00:00,  "updatedAt": 2025-05-12T11:24:47.251+00:00,  "id": 1,  "__v": 0}
```


```
{  "_id": ObjectId('6821db341a8fbcc9e6955f5b'),  "charactername": "Nobita",  "password": "$2b$10$k8RTQZKhrQaVtV4AH51WGeFFLL9mQE4TkygAzryPtq2SouSAlsBEK",  "role": "human",  "createdAt": 2025-05-12T11:27:48.457+00:00,  "updatedAt": 2025-05-12T11:27:48.457+00:00,  "id": 2,  "__v": 0}
```

Login with Doraemon (Robot)





GET specific character with /:id



Using Doraemon Login to get Auth Key and Insert into Headers

The image displays two screenshots of the Postman API client interface, illustrating a successful login and an unauthorized access attempt.

Top Screenshot: Successful Login

- URL:** `http://localhost:5000/character/login`
- Method:** `POST`
- Body (raw):**

```
1 {
2   "charactername": "Doraemon",
3   "password": "robot123"
4 }
```
- Status:** `200 OK` (492 ms, 519 B)
- Body (JSON):**


```
1 {
2   "success": true,
3   "data": {
4     "_id": "6021da7f1a8fbcc9e6955f58",
5     "charactername": "Doraemon",
6     "role": "robot",
7     "token": "eyJ3ZGI6IjY4MjFkYTYdMmE4ZmZjYz11Nj1kNwY1OCIsImh0cCI6MTc0NzA8OTY4MSw1ZXhwIjoxNzQ5NjQxNjgxFQ.
8   }
9 }
```

Bottom Screenshot: Unauthorized Access


- URL:** `http://localhost:5000/gadgets`
- Method:** `POST`
- Headers:** Authorization: `Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpZCI6IjY4MjFkYTYdMmE4ZmZjYz11Nj1kNwY1OCIsImh0cCI6MTc0NzA8OTY4MSw1ZXhwIjoxNzQ5NjQxNjgxFQ.eyJ3ZGI6IjY4MjFkYTYdMmE4ZmZjYz11Nj1kNwY1OCIsImh0cCI6MTc0NzA8OTY4MSw1ZXhwIjoxNzQ5NjQxNjgxFQ.`
- Status:** `401 Unauthorized` (8 ms, 299 B)
- Body (JSON):**

```
1 {
2   "success": false,
3   "message": "Not authorized, no token"
4 }
```


Using the Key to Add Gadgets




GET all Gadgets (Authorized)




GET ?name=bamboo (Authorized)




GET gadget by /:id (Authorized)




GET gadget by Character ID /:id (Authorized)




Update gadget by /:id (Authorized)





DELETE gadget by ID (Authorized)





Hasan Yahya's Workspace

NewImport

Getting startedDEL http://localhost:5000/ga+No environment

Collections

Environments

Flows

History

Your collection

Authorization

TypeArray

Create a collection for your requests

A collection lets you group related requests and easily set common authorization, tests, scripts, and variables for all requests in it.

Create Collection

http://localhost:5000/gadgets/6821e5a19db8739442e23996

DELETEhttp://localhost:5000/gadgets/6821e5a19db8739442e23996

ParamsAuthorizationHeaders (7)BodyScriptsSettings

noneform-datax-www-form-urlencodedrawbinaryGraphQLJSON

1

BodyCookiesHeaders (7)Test Results403 Forbidden188 ms297 B

JSON

PreviewVisualization

1{2 "success": false,3 "message": "Not authorized as a robot"4 }

OnlineFind and replaceConsolePostbotRunnerStart ProxyCookiesVaultTrash