TABLE I

EMPIRICAL METRIC POSE-ERROR ADMISSIBILITY FOR SAFEVPR: THE BINARY RETRIEVAL LABEL IS REPLACED WITH $|\text{POSE ERROR}| \leq \tau_p$, SO THE CONFORMAL THRESHOLD TARGETS LOCALIZATION ERROR DIRECTLY. COMPUTED ON THE 20-SETUP OXFORD+NCLT SUBSET (ST LUCIA EXCLUDED: ITS ~ 5 M GPS SUBSAMPLING MAKES SUB-25 M METRIC LABELS UNSTABLE). † TRIVIALLY VALID (NO ACCEPTS): THE IN-CONDITION CAL POOL IS BELOW $5B/\alpha$, SO VANILLA LTT ABSTAINS AND FDR IS VACUOUS.

		$\alpha = 0.05$			$\alpha = 0.10$		
τ_p	Setting	Pass	FDR	TPR	Pass	FDR	TPR
5 m	cross-condition	20/20	0.0022	0.307	20/20	0.0052	0.390
5 m	in-condition	20/20†	—	0.000	20/20	0.0014	0.372
10 m	cross-condition	20/20	0.0018	0.449	20/20	0.0080	0.617
10 m	in-condition	20/20†	—	0.000	20/20	0.0019	0.398
25 m	cross-condition	19/20	0.0080	0.683	20/20	0.0180	0.748
25 m	in-condition	20/20†	—	0.000	20/20	0.0003	0.415