ROLL NO.	NAME	

CS 5316 – Natural Language Processing

Quiz 6 Solution

(Time limit: 12 minutes)

Design a feedforward neural network with 3 layers for document topic classification. Suppose there are 5 topics and documents have varying lengths from 300 to 500 words.

- a. (2 points) Draw the architecture of the network showing the input layer, output layer, hidden layer(s), and connectivity between layers.
- b. (2 points) Describe the representation that you would use for documents.
- c. (1 point) Select the number of units in all the layers.
- d. (1 point) Fix the activation function in all the layers.
- e. (2 points) Define the parameters of the network. Be precise.
- f. (2 points) Describe briefly how you would train the networkincluding mentioning the type of loss function.

(a)

Input, layer 1, layer 2, output layer Fully connected feedforward network from input to output layer 2 hidden layers

(b)

A number of representations can be used for documents.

- 1. TF-IDF vector representation: TF-IDF calculated over the entire corpus; vector length is equal to vocabulary size, M
- 2. Word embeddings: fix document length to first 400 words, concat word embeddings for these words in each document. If a document is shorter in length, pad with zeros.
- 3. Document vectors: learn fixed length document embeddings, e.g., doc2vec or auto-encoder trained on TF-IDF vectors.

(c)

Input: M (doc vector length)

Hidden 1: 300 Hidden 2: 150 Output: 5

(d)

Hidden layers: tanh or ReLU Output layer: soft max

(e)

Parameters include all weights and biases.

Input to hidden 1: 300 * M weights, 300 biases Hidden 1 to hidden 2: 150 * 300 weights, 150 biases Hidden 2 to output layer: 5 * 150 weights, 5 biases (f)

Randomly initialize parameters Feed each document through the network

Check the network's output with true label

If they differ update parameters such that categorical cross-entropy (loss function) is minimized

Repeat for all documents, and several epochs until convergence