



GPU • TOWER RACKMOUNT

GPU SuperServer SYS-741GE-TNRT

DP Intel Workstation with up to 4 NVIDIA H100 or A100 PCIe GPUs



Processor

CPU	Intel® Xeon® Gold 5520+ Processor 28-Core 2.20 GHz 52.5MB Cache (205W) ×2
CPU License	Intel On-Demand License with QuickAssist Technology (QAT) & Dynamic Load Balancer (DLB) for MCC ×2
Socket	Dual Socket E (LGA-4677)

Storage

HDD	4TB SATA HDD 3.5" 7.2K CMR 512N (Enterprise, STD, Regular)
SSD	1.9TB SATA SSD 2.5" 1DWPDL TLC E (SED, 7mm) ×7

Networking

Network	Supermicro 200-Gigabit CX6(1 x QSFP56) Ethernet Network Adapter
---------	---

Memory

Installed	128GB DDR5 6400MHz ECC RDIMM Server Memory ×16
Slots	16 of 16 slots populated

GPU

GPU	NVIDIA RTX PRO 6000 96GB GDDR7 Blackwell Max-Q Workstation Edition Graphics Card (300W) ×4
-----	--

Power Supply

Configuration	2x 2000W Redundant (1 + 1) Titanium Level (96%) power supplies
Input	100-127Vac; 200-240Vac; 1000W: 100-120Vac / 50-60Hz; 1800W: 200-220Vac / 50-60Hz; 1980W: 220-230Vac / 50-60Hz; 2000W: 230-240Vdc; 2000W: 230-240Vac / 50-60Hz; 2000W: 200-240Vac / 50-60Hz (for UL/cUL only)

Operating System

Installed	Microsoft Windows Server 2025 Datacenter (24-Core) ×2
Location	Slot OnBoard: INTEL SATA, 4TB 3.5" Exos 7E10 7200 RPM SATA3 6Gb/s 256MB Cache 512N Hard Drive Microsoft Windows Server 2025 Datacenter (4 Additional Cores) ×2

Software

Included	Supermicro DataCenter Management Suite (DCMS)
----------	--

Warranty & Service

Hardware	3 Years Parts and Labor + 1 Years of Cross Shipment
----------	--

Trusted Platform Module

Module	SPI capable vertical TPM 2.0
--------	------------------------------

Platform

Form factor	Tower Rackmount 177 × 465.4 × 678.5mm (W×H×D)	Expansion	Default: 7 PCIe 5.0 x16 FHFL slots
Weight	Gross Weight: 62 lbs (28.1 kg) Net Weight: 46 lbs (20.9 kg)	BIOS	AMI 32MB SPI Flash EEPROM
Cooling	Up to 4 heavy duty fans with optimal fan speed control	I/O	1 VGA port(Rear); 1 COM port(rear); Front Audio; 1 TPM Onboard/port 80
Heatsink	Supports up to 350W TDP CPUs (Air Cooled)		

Security

Hardware	Trusted Platform Module (TPM) 2.0; Silicon Root of Trust (RoT) – NIST 800- 193 Compliant
Features	• Cryptographically Signed Firmware • Secure Boot • Secure Firmware Updates • Automatic Firmware Recovery • Supply Chain Security: Remote Attestation • Runtime BMC Protections • System Lockdown

Management

Power	Power-on mode for AC power recovery; ACPI Power Management
Software	• SuperCloud Composer® (SCC) • Supermicro Server Manager (SSM) • Supermicro Update Manager (SUM) • Supermicro SuperDoctor® 5 (SD5) • Super Diagnostics Offline (SDO) • Supermicro Thin-Agent Service (TAS) • SuperServer Automation Assistant (SAA) New!

Certifications

Compliance	• ESXi 8.0, Hypervisor 8.2.1, Oracle Linux 9.0, RHEL 9.0, Windows Server 2022, Windows Server 2025
------------	--

On-board

Selected	2 10GbE RJ45 Ports
----------	--------------------