import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

df=pd.read_csv('/content/drive/MyDrive/DataSet/Real estate.csv')
df.head()

	No	X1 transaction date	X2 house age	X3 distance to the nearest MRT station	X4 number of convenience stores	X5 latitude	X6 longitude	Y house price of unit area
0	1	2012.917	32.0	84.87882	10	24.98298	121.54024	37.9
1	2	2012.917	19.5	306.59470	9	24.98034	121.53951	42.2
2	3	2013.583	13.3	561.98450	5	24.98746	121.54391	47.3
3	4	2013.500	13.3	561.98450	5	24.98746	121.54391	54.8

df.shape

(414, 8)

X=df.iloc[:,1:-1]

Y=df['Y house price of unit area']

from sklearn.model_selection import train_test_split

X_train,X_test,Y_train,Y_test=train_test_split(X,Y,test_size=0.3,random_state=3)

X_train

	X1 transaction date	X2 house age	X3 distance to the nearest MRT station	X4 number of convenience stores	X5 latitude	X6 longitude
75	2013.500	12.3	1360.1390	1	24.95204	121.54842
14	2013.500	13.2	1164.8380	4	24.99156	121.53406
397	2013.417	13.1	1164.8380	4	24.99156	121.53406
47	2013.583	35.9	640.7391	3	24.97563	121.53715
46	2013.417	21.7	463.9623	9	24.97030	121.54458
256	2012.667	14.6	339.2289	1	24.97519	121.53151
131	2013.500	4.0	2147.3760	3	24.96299	121.51284
249	2012.833	18.0	6306.1530	1	24.95743	121.47516
152	2013.333	12.0	1360.1390	1	24.95204	121.54842
362	2013 417	17 1	967 <u>4</u> 000	Δ	24 98872	121 53408

from sklearn.linear_model import LinearRegression
model=LinearRegression()

model.fit(X_train,Y_train)

LinearRegression()

y_pred=model.predict(X_test)

from sklearn.metrics import r2_score

score=r2_score(Y_test,y_pred)
score

0.61013019865237

z=pd.DataFrame({'actual':Y_test,'predicted':y_pred})

Pz.head()

	actual	predicted
161	39.6	41.400219
130	37.5	44.632017
227	40.2	43.212812
103	45.7	44.031988
240	28.8	33.343182

✓ 0s completed at 4:14 PM

• ×