

Zakat

smart contracts final audit report

April 2024



hashex.org



contact@hashex.org

Contents

1. Disclaimer	3
2. Overview	4
3. Project centralization risks	8
4. Found issues	9
5. Contracts	13
6. Conclusion	29
Appendix A. Issues severity classification	30
Appendix B. Issue status description	31
Appendix C. List of examined issue types	32
Appendix D. Centralization risks classification	33

1. Disclaimer

This is a limited report on our findings based on our analysis, in accordance with good industry practice at the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. In order to get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us on the basis of what it says or doesn't say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the disclaimer below - please make sure to read it in full.

By reading this report or any part of it, you agree to the terms of this disclaimer. If you do not agree to the terms, then please immediately cease reading this report, and delete and destroy any and all copies of this report downloaded and/or printed by you. This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and HashEx and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers, and other representatives) (HashEx) owe no duty of care towards you or any other person, nor does HashEx make any warranty or representation to any person on the accuracy or completeness of the report. The report is provided "as is", without any conditions, warranties, or other terms of any kind except as set out in this disclaimer, and HashEx hereby excludes all representations, warranties, conditions, and other terms (including, without limitation, the warranties implied by law of satisfactory quality, fitness for purpose and the use of reasonable care and skill) which, but for this clause, might have effect in relation to the report. Except and only to the extent that it is prohibited by law, HashEx hereby excludes all liability and responsibility, and neither you nor any other person shall have any claim against HashEx, for any amount or kind of loss or damage that may result to you or any other person (including without limitation, any direct, indirect, special, punitive, consequential or pure economic loss or damages, or any loss of income, profits, goodwill, data, contracts, use of money, or business interruption, and whether in delict, tort (including without limitation negligence), contract, breach of statutory duty, misrepresentation (whether innocent or negligent) or otherwise under any claim of any nature whatsoever in any jurisdiction) in any way arising from or connected with this report and the use, inability to use or the results of the use of this report, and any reliance on this report. The analysis of the security is purely based on the smart contracts alone. No applications or operations were reviewed for security. No product code has been reviewed. HashEx owns all copyright rights to the text, images, photographs, and other content provided in the following document. When using or sharing partly or in full, third parties must provide a direct link to the original document mentioning the author (hashex.org). HashEx has exclusive rights to publish the results of this audit on company's web and social sites.

2. Overview

HashEx was commissioned by the **Zakat** team to perform an audit of their smart contract. The audit was conducted between **2024-04-09** and **2024-04-16**.

The purpose of this audit was to achieve the following:

- Identify potential security issues with smart contracts
- Formally check the logic behind given smart contracts.

Information in this report should be used for understanding the risk exposure of smart contracts, and as a guide to improving the security posture of smart contracts by remediating the issues that were identified.

The code was provided directly in .sol files.

SHA-1 hashes of the audited files are:

./interfaces/IPool.sol **9b257f83499e8a56833f35043550823c92d16273**

./interfaces/IConfiguration.sol **10dc2ddd23eb566eb080dcffd7f5da22883c6701**

./interfaces/IVault.sol **1adec7ab6daffab284f9e745e6c4036efd0a9a6e**

./interfaces/IPoolManager.sol **d8b77723bdfc817851228adce07b2f3d352a92a8**

./interfaces/IMint.sol **5325b6e20bf981f2f42345993535700f85317153**

./interfaces/IRegistry.sol **333d94e8dd3dfe5991a33fe3bffe683f8df36bee**

./libraries/Data.sol **7d152e6b742ef543e830d7d699b350c71b2dfe11**

./libraries/Errors.sol **ca1cf4a190432431321a66e634459e2faefbb0b3**

./libraries/Roles.sol **b694bfaca1a1742d7d1d70a42be7dda04f61e7ac**

./libraries/svg/JSON.sol **f317eca37c63ae4bce510f6c4742c5161ed104c1**

./libraries/svg/SVG.sol 6e32f3f3bcc16bb00dc08e06a6dab73fe9fb2f12

./libraries/svg/HexStrings.sol a54c2ca3610c887ed20e37a4fead72f87cd1140a

./libraries/svg/Colors.sol aa855ef8daceb94613f1a60826b4f33f90fa104d

./libraries/logic/FeeLogic.sol 7d325461c5b617a37597eb2d4b2b5890ae97b40d

./libraries/logic/VaultLogic.sol a7a8f4fed1ea7c26fb534ec2aa1d2363cb6025d9

./platform/access-control/Authority.sol ff5156b65d89459ff6836b03d9d1ad5877470347

./platform/nft/Descriptor.sol 5071311fda87665b908d565ea805f7ed9ec0b75b

./platform/nft/Mint.sol f9ca2865fd91b6d6517d5a9c86e746571d8b9fa0

./platform/Configuration.sol a511054de3e2c541a486d1152296179c5ca66d82

./platform/pool/Vault.sol 83bf6e40ebc1861f78ac395f9b0a357103f930e2

./platform/pool/Pool.sol b59a7cc5538f21e0f5ad549eb8e8b60423fa4b18

./platform/pool/PoolManager.sol 5281b3cd1271b5540407939145292b3eef6da458

./platform/registry/RegisteredUpgradeable.sol 626a0fd6c1552450124908d991fad699e0d924f8

./platform/registry/Registered.sol 829af0366c42a4b3a561a521744d635594ef3b64

./platform/registry/Registry.sol aa1ee9245b4b7776fb243dad5b7ca06813d842d

./platform/request/RequestManager.sol 6668f1eac83aabfb01d1df55ca708eec1e1a60f5

Update. The team has responded to this report. The updated contracts are available in the @kozyilmaz/zakat GtiHub repository in the [v1.1.0](#) tree.

2.1 Summary

Project name	Zakat
URL	https://x.com
Platform	Binance Smart Chain
Language	Solidity
Centralization level	● High
Centralization risk	● High

2.2 Contracts

Name	Address
PoolManager	
Pool	
Vault	
Mint	
Descriptor	
Registry	
Registered and RegisteredUpgradeable	
Configuration	
RequestManager	

Authority

Libraries

Interfaces

3. Project centralization risks

The contracts of the project are designed to be deployed via upgradable proxies, meaning that accounts with privileged access can change implementations of the contracts. We recommend to avoid leaving an unspent allowance to an upgradable contract.

4. Found issues



● Critical	1 (3%)
● High	1 (3%)
● Medium	2 (6%)
● Low	20 (61%)
● Info	9 (27%)

Ceb. PoolManager

ID	Severity	Title	Status
Cebi7a	● Low	Concurrent authorization models	✓ Resolved
Cebi7b	● Low	Lack of input validation	✓ Resolved
Cebi74	● Info	No function that returns length	✓ Resolved
Cebi75	● Info	No visibility modifier	✓ Resolved

Cec. Pool

ID	Severity	Title	Status
Ceci7d	● High	Lack of input validation	✓ Resolved
Ceci80	● Medium	Possibly locked native coins	✓ Resolved
Ceci8b	● Low	Unused variable	✓ Resolved
Ceci7c	● Low	Lack of storage gap	✓ Resolved

Cecl7f	● Low	Lack of events	✔ Resolved
Cecl7e	● Info	Lack of NatSpec descriptions	✔ Resolved











Ced. Vault

ID	Severity	Title	Status
Cedl8a	● Critical	Owner can override consensus	✔ Resolved
Cedl83	● Low	Gas optimizations	🔧 Partially fixed
Cedl82	● Low	Lack of storage gap	✔ Resolved
Cedl84	● Low	Limited reentrancy protection	✔ Resolved
Cedl86	● Low	Lack of error message	✔ Resolved
Cedl85	● Info	Lack of NatSpec descriptions	✔ Resolved
Cedl81	● Info	Possibly unaddressed native coins	✔ Acknowledged





Ce2. Mint

ID	Severity	Title	Status
Ce2l87	● Low	Gas optimizations	✔ Acknowledged
Ce2l88	● Low	Lack of storage gap	✔ Resolved
Ce2l89	● Info	Lack of NatSpec descriptions	✔ Resolved









Ce9. Registry

ID	Severity	Title	Status
Ce9I8d	 Medium	Lack of input validation	 Resolved
Ce9I8c	 Low	Lack of storage gap	 Resolved
Ce9I71	 Low	No events	 Resolved
Ce9I70	 Low	Gas optimization	 Resolved
Ce9I72	 Info	Not used variable	 Resolved





Cea. Registered and RegisteredUpgradeable

ID	Severity	Title	Status
Ceal8e	 Low	Lack of storage gap	 Resolved
Ceal73	 Low	Gas optimizations	 Resolved

Cd8. RequestManager

ID	Severity	Title	Status
Cd8I8f	 Low	Gas optimizations	 Partially fixed
Cd8I90	 Low	Lack of storage gap	 Acknowledged
Cd8I91	 Info	Possible DoS by gas limit	 Resolved
Cd8I92	 Info	Function access	 Resolved

Cef. Libraries

ID	Severity	Title	Status
Cefl78	 Low	Lack of input validation	 Resolved
Cefl77	 Low	Gas optimizations	 Resolved

5. Contracts

Ceb. PoolManager

Overview

A factory contract to deploy and upgrade existing Pool contracts. Only privileged accounts can interact with the PoolManager.

Issues

Cebi7a Concurrent authorization models

 Low Resolved

The PoolManager contract uses the Beacon proxy pattern for upgrading deployed Pool contracts. The `upgradeTo()` function requires both external AccessManager and local Ownable authorization, unnecessary complicating the upgrade process.

```
contract PoolManager is
    IPoolManager,
    AccessManaged,
    Pausable,
    Registered,
    UpgradeableBeacon
{
    ...
    function upgradeTo(address _implementation) public override restricted {
        super.upgradeTo(_implementation);
        version++;
    }
}

contract UpgradeableBeacon is IBeacon, Ownable {
    ...
    function upgradeTo(address newImplementation) public virtual onlyOwner {
        _setImplementation(newImplementation);
    }
}
```

Cebi7b Lack of input validation

● Low

✓ Resolved

There is no protection for the same name pools in the `deployPool()` function. While the current implementation of the Registry contract denies duplicated pools, future upgrades may cause the `REGISTRY.registerPool()` call to overwrite pool address.

```
function deployPool(
    PoolParameters memory _parameters
) external restricted whenNotPaused {
    ...
    bytes32 id = _calculateId(version, _parameters.name);
    ...
    REGISTRY.registerPool(id, pool, _parameters);
}

function _calculateId(
    uint256 _version,
    string memory _name
) internal view returns (bytes32) {
    return keccak256(abi.encode(address(this), _version, _name));
}
```

Cebi74 No function that returns length

● Info

✓ Resolved

There are no functions that return the length of the `poolAddresses` and the `poolIds` `EnumerableSets`.

Cebi75 No visibility modifier

● Info

✓ Resolved

Global variable `vaultImplementation` don't have a visibility modifier. Default visibility is `internal`.


Cec. Pool

Overview

A contract for user interactions. The Pool allows users to donate their funds in ERC20 tokens or in native EVM coins in exchange for NFTs. Collected funds are stored in the Pool's individual Vault contract and may be transferred out by the Pool's owner's decision.

Issues

Cec17d Lack of input validation

 High Resolved

The ERC20 payment token address is defined by the user and isn't validated in any kind, although the Pool contract contains an explicit list of supported assets and has privileged functions to update this list.

```
function depositERC20WithPermit(
    address _token,
    uint256 _value,
    uint256 _deadline,
    uint8 _permitV,
    bytes32 _permitR,
    bytes32 _permitS
) external {
    vault.depositERC20WithPermit(
        _token,
        msg.sender,
        _value,
        _deadline,
        _permitV,
        _permitR,
        _permitS
    );

    donations[_token] += _value;
    donationsOf[_token][msg.sender] += _value;
```

```

        _mint(msg.sender, _token, _value);
    }

    function depositERC20(address _token, uint256 _value) external {
        vault.depositERC20(_token, msg.sender, _value);

        donations[_token] += _value;
        donationsOf[_token][msg.sender] += _value;

        _mint(msg.sender, _token, _value);
    }

```

Recommendation

Include validation of `require(isAssetEnabled(_token))` or similar to the `depositERC20()` and `depositERC20WithPermit()` functions.

Cecl80 Possibly locked native coins

Medium

Resolved

The contract contains empty function to receive native EVM coins with no clear use case. Any sent coins will remain locked in the contract's balance.

```
receive() external payable {}
```

Recommendation

Remove the `receive()` function.

Cecl8b Unused variable

Low

Resolved

The `factory` address is not initialized and not used anywhere in the Pool contract.

Cecl7c Lack of storage gap

Low

Resolved

The Pool contract is designed to be deployed via upgradable proxy but lacks reserved storage slots for possible future upgrades.

Cecl7f Lack of events

● Low

✓ Resolved

The functions `enableAsset()`, `disableAsset()`, `submitTX()`, `signTX()`, `executeTX()`, `_mint()` change important variable in the contract storage, but no event is emitted.

We recommend adding events to these functions to make it easier to track their changes offline.

Cecl7e Lack of NatSpec descriptions

● Info

✓ Resolved

Several functions lack descriptions. We recommend writing documentation using [NatSpec Format](#). This would help in development, as well as simplify user interaction with the contract (including using the block explorer).

Ced. Vault

Overview

A vault contract to be deployed by the Pool contract that stores collected funds in form of ERC20 tokens and native EVM coins. Stored funds can be transferred out to an arbitrary address by a consensus decision of owners, defined during the contract creation.

Issues

Cedl8a Owner can override consensus

● Critical

✓ Resolved

The owners need a consensus decision to submit and execute a transfer-out transaction, but any of the owners can upgrade the implementation and override the logic.

```
function _executeTX(
    uint256 _index,
    address _executor,
```

```

    uint24 _feeRatio,
    address[] memory _feeTakers
) internal {
    ...
    if (transaction.signatureCount < threshold)
        revert NotEnoughSignatures();
}

function _authorizeUpgrade(
    address _implementation
) internal override onlyOwners {}

```

Recommendation

The upgradability should either be a consensus decision or approved via the Authority.

CedI83 Gas optimizations

● Low

🔧 Partially fixed

1. Zero effect code in the `depositNative()` function:
`Address.sendValue(payable(address(this)), msg.value).`
2. Excessive stored data: `transactions[id].id = id.`
3. Unnecessary reads from storage in the `_submitTX()` function: `transactions[_id]` variable.
4. Unnecessary reads from storage in the `_signTX()` function: `transaction.signatureCount`, `transaction.id`, `transaction` variables.
5. Unnecessary reads from storage in the `_executeTX()` function: `transaction.token`, `transaction` variables.
6. Unnecessary reads from storage in the `_setOwners()` function: `owners[i]` variables.

CedI82 Lack of storage gap

● Low

✅ Resolved

The contract is designed to be deployed via upgradable proxy but lacks [reserved storage slots](#) for possible future upgrades.

Cedl84 Limited reentrancy protection

● Low

✓ Resolved

The **nonReentrant** modifier prevents reentrancy only for limited number of internal functions, specifically **_executeNative()**, **_executeERC20()**, **_adjustBalance()**. We recommend protect all external and public functions explicitly to prevent cross-function reentrancy.

Cedl86 Lack of error message

● Low

✓ Resolved

The **depositERC20WithPermit()** function contains possible silent failure on **IERC20Permit(_token).permit()** external call.

```
function depositERC20WithPermit(
    address _token,
    address _from,
    uint256 _value,
    uint256 _deadline,
    uint8 _permitV,
    bytes32 _permitR,
    bytes32 _permitS
) external onlyPool {
    try
        IERC20Permit(_token).permit(
            _from,
            address(this),
            _value,
            _deadline,
            _permitV,
            _permitR,
            _permitS
        )
    {} catch {}

    _depositERC20(_token, _from, _value);
}
```

Recommendation

Include a meaningful revert in the **catch** section.

Cedl85 Lack of NatSpec descriptions

● Info

✓ Resolved

Several functions lack descriptions. We recommend writing documentation using [NatSpec Format](#). This would help in development, as well as simplify user interaction with the contract (including using the block explorer).

Cedl81 Possibly unaddressed native coins

● Info

✓ Acknowledged

The contract contains empty function to receive native EVM coins with no clear use case. Any sent coins will remain locked in the contract's balance without accounting via **_adjustBalance()**. In addition, small number of native coins is locked as the division remainder in the **_executeTX()** function.

```
/// @notice Fallback function to receive native.  
receive() external payable virtual {}
```

Ce2. Mint

Overview

This is an ERC721 token that can be minted by any Pool contract (or any other granted account) to a user that made an asset donation. Newly minted token will represent his asset donation.

Issues

Ce2I87 Gas optimizations

 Low Acknowledged

1. The AccessManager authorization model can replace the Ownable contract inherited by the Mint contract.

Ce2I88 Lack of storage gap

 Low Resolved

The contract is designed to be deployed via upgradable proxy but lacks [reserved storage slots](#) for possible future upgrades.

Ce2I89 Lack of NatSpec descriptions

 Info Resolved

Several functions lack descriptions. We recommend writing documentation using [NatSpec Format](#). This would help in development, as well as simplify user interaction with the contract (including using the block explorer).

Cf1. Descriptor

Overview

A contract to encode SVG data for the Mint NFT contract.

Ce9. Registry

Overview

A contract allowing tracking of deployed pools and donations.

Issues

Ce9I8d Lack of input validation

Medium

Resolved

A donation can be registered for a non-existent pool in the `registerDonation()` function.

There's a possible length's mismatch in the `batchRegister()` and `batchUpdate()` functions.

Recommendation

Include explicit validation of the input data.

Ce9I8c Lack of storage gap

Low

Resolved

The contract is designed to be deployed via upgradable proxy but lacks [reserved storage slots](#) for possible future upgrades.

Ce9I71 No events

Low

Resolved

These functions don't have any events:

1. `register()`
2. `batchRegister()`
3. `update()`
4. `batchUpdate()`

Ce9I70 Gas optimization

Low

Resolved

1. To the `registerPool()` function has arguments that are not used anywhere: `_parameters.feeRatio`, `_parameters.permittedAssets`, and `_parameters.vaultParameters`.
2. The AccessManager authorization model can replace the Ownable contract inherited by the Registry contract.
3. The `generateAddressedId()` is called twice in the `registerDonation()` function.

Ce9I72 Not used variable

● Info

✔ Resolved

Global variable `MINT_CONTRACT` isn't used anywhere.

Cea. Registered and RegisteredUpgradeable

Overview

A contract modules to store address of the Registry contract.

Issues

Ceal8e Lack of storage gap

● Low

✔ Resolved

The RegisteredUpgradeable contract is designed to be deployed via upgradable proxy but lacks [reserved storage slots](#) for possible future upgrades.

Ceal73 Gas optimizations

● Low

✔ Resolved

Global variables `REGISTRY_ADDRESS` and `REGISTRY` hold the same value. One of the two variables can be deleted.

The non-upgradable Registered contract may store the Registry address in immutable form to reduce gas consumption.

Cd7. Configuration

Overview

A contract that holds information about fee takers. It will be used in the Pool contract.


Cd8. RequestManager

Overview

An entry point for users and pool owners to create, approve, and execute requests. The contract stores information about requests that were created by users.

Issues

Cd8I8f Gas optimizations

 Low Partially fixed

1. The AccessManager auth model can replace the Ownable contracts inherited by the RequestManager contract.
2. Excessive stored data: `requests[id].id = id`.
3. Multiple reads from storage in the `_bumpStatus()` function: `_request.status` variable.

Cd8I90 Lack of storage gap

 Low Acknowledged

The contract is designed to be deployed via upgradable proxy but lacks [reserved storage slots](#) for possible future upgrades.

Cd8I91 Possible DoS by gas limit

 Info Resolved

The `getRequests()` function returns full array of requests and may suffer from DoS due to gas limit since `requests[]` array is never purged.

Cd8I92 Function access

● Info

✓ Resolved

The `create()` function is marked as restricted, but in fact it's a public function.

```
// -----  
// Public API (Restricted)  
// -----  
  
function create(  
    bytes32 _poolId,  
    address _recipient,  
    string calldata _description,  
    address _token,  
    uint256 _amount  
) external returns (uint256) {  
    uint256 id = _create(  
        _poolId,  
        _recipient,  
        _description,  
        _token,  
        _amount  
    );  
  
    return id;  
}
```

Recommendation

Clarify the desired accessibility of the `create()` function.

Cd9. Authority

Overview

Implements [AccessManager](#) functionality from OpenZeppelin library.

Cef. Libraries

Overview

Various libraries contracts for the project contracts:

- related to SVG encoding: Colors, HexStrings, JSON, SVG;
- shared structs and errors: Data, Errors, Roles;
- related to fee logic: FeeLogic, VaultLogic.

Issues

Cef178 Lack of input validation

● Low

✓ Resolved

The SVG contract's function `formatted()` lacks validation of input parameters `_decimals` `>= _precision`. Without this safety check the `formatted()` function may experience underflow error.

```
function formatted(
    uint256 _amount,
    uint256 _decimals,
    uint256 _precision
) internal pure returns (string memory) {
    uint256 lExponent = 10 ** _decimals;
    uint256 left = (_amount / lExponent);

    uint256 rExponent = 10 ** (_decimals - _precision);
    uint256 right = (_amount / rExponent) % mod;

    string memory leftStr = left.toString();
```

```
string memory rightStr = right.toString();

uint256 fill = _precision - bytes(rightStr).length;

if (fill == 4) return leftStr;

unchecked {
    for (uint256 i; i < fill; i++) {
        rightStr = string(abi.encodePacked("0", rightStr));
    }
}

return string(abi.encodePacked(leftStr, ".", rightStr));
}
```

Cefl77 Gas optimizations

 Low Resolved

Data contract excessive storage usage:

1. the Transaction and Request structs contain duplicated data in **signatureCount** and **signatures.length** fields.

VaultLogic contract redundant code:

1. In the **checkThreshold()** function the **_parameters.threshold <= 0** check can be switched to **_parameters.threshold == 0** since the **uint256 threshold** can't be negative.

FeeLogic contract redundant code:

1. In the **calculateTotalFee()** function **_ratio <= 0** check can be replaced with **_ratio == 0**, it will be more gas-optimized and there is no such case when the **_ratio** variable is negative.
2. In the **clampFee()** function there is an excessive check **if (_value < 0)** that can be omitted, the variable **_value** can't be negative.
3. The function **clampFee()** isn't used anywhere.

Cf0. Interfaces

Overview

Various interface contracts for the project

contracts: IConfiguration, IMint, IPool, IPoolManager, IRegistry, IVault.

6. Conclusion

1 critical, 1 high, 2 medium, 20 low severity issues were found during the audit. 1 critical, 1 high, 2 medium, 16 low issues were resolved in the update. The reviewed contracts are highly dependent on the owner's account. See the centralization risks chapter.

This audit includes recommendations on code improvement and the prevention of potential attacks.

Appendix A. Issues severity classification

- **Critical.** Issues that may cause an unlimited loss of funds or entirely break the contract workflow. Malicious code (including malicious modification of libraries) is also treated as a critical severity issue. These issues must be fixed before deployments or fixed in already running projects as soon as possible.
- **High.** Issues that may lead to a limited loss of funds, break interaction with users, or other contracts under specific conditions. Also, issues in a smart contract, that allow a privileged account the ability to steal or block other users' funds.
- **Medium.** Issues that do not lead to a loss of funds directly, but break the contract logic. May lead to failures in contracts operation.
- **Low.** Issues that are of a non-optimal code character, for instance, gas optimization tips, unused variables, errors in messages.
- **Info.** Issues that do not impact the contract operation. Usually, info severity issues are related to code best practices, e.g. style guide.

Appendix B. Issue status description

- ✔ **Resolved.** The issue has been completely fixed.
- 🔄 **Partially fixed.** Parts of the issue have been fixed but the issue is not completely resolved.
- 🕒 **Acknowledged.** The team has been notified of the issue, no action has been taken.
- ❓ **Open.** The issue remains unresolved.

Appendix C. List of examined issue types

- Business logic overview
- Functionality checks
- Following best practices
- Access control and authorization
- Reentrancy attacks
- Front-run attacks
- DoS with (unexpected) revert
- DoS with block gas limit
- Transaction-ordering dependence
- ERC/BEP and other standards violation
- Unchecked math
- Implicit visibility levels
- Excessive gas usage
- Timestamp dependence
- Forcibly sending ether to a contract
- Weak sources of randomness
- Shadowing state variables
- Usage of deprecated code

Appendix D. Centralization risks classification

Centralization level

- **High.** The project owners can manipulate user's funds, lock user's funds on their will (reversible or irreversible), or maliciously update contracts parameters or bytecode.
- **Medium.** The project owners can modify contract's parameters to break some functions of the project contract or contracts, but user's funds remain withdrawable.
- **Low.** The contract is trustless or its governance functions are safe against a malicious owner.

Centralization risk

- **High.** Lost ownership over the project contract or contracts may result in user's losses. Contract's ownership belongs to EOA or EOAs, and their security model is unknown or out of scope.
- **Medium.** Contract's ownership is transferred to a contract with not industry-accepted parameters, or to a contract without an audit. Also includes EOA with a documented security model, which is out of scope.
- **Low.** Contract's ownership is transferred to a well-known or audited contract with industry-accepted parameters.

 contact@hashex.org

 [@hashex_manager](https://t.me/hashex_manager)

 blog.hashex.org

 [linkedin](https://www.linkedin.com/company/hashex)

 [github](https://github.com/hashex)

 [twitter](https://twitter.com/hashex)

#HashEx
BLOCKCHAIN SECURITY