

Trinity DAO

smart contracts
final audit report

November 2023



hashex.org



contact@hashex.org

Contents

1. Disclaimer	3
2. Overview	4
3. Project centralization risks	7
4. Found issues	8
5. Contracts	11
6. Conclusion	25
Appendix A. Issues' severity classification	26
Appendix B. Vulnerabilities checked	27

1. Disclaimer

This is a limited report on our findings based on our analysis, in accordance with good industry practice at the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. In order to get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us on the basis of what it says or doesn't say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the disclaimer below - please make sure to read it in full.

By reading this report or any part of it, you agree to the terms of this disclaimer. If you do not agree to the terms, then please immediately cease reading this report, and delete and destroy any and all copies of this report downloaded and/or printed by you. This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and HashEx and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers, and other representatives) (HashEx) owe no duty of care towards you or any other person, nor does HashEx make any warranty or representation to any person on the accuracy or completeness of the report. The report is provided "as is", without any conditions, warranties, or other terms of any kind except as set out in this disclaimer, and HashEx hereby excludes all representations, warranties, conditions, and other terms (including, without limitation, the warranties implied by law of satisfactory quality, fitness for purpose and the use of reasonable care and skill) which, but for this clause, might have effect in relation to the report. Except and only to the extent that it is prohibited by law, HashEx hereby excludes all liability and responsibility, and neither you nor any other person shall have any claim against HashEx, for any amount or kind of loss or damage that may result to you or any other person (including without limitation, any direct, indirect, special, punitive, consequential or pure economic loss or damages, or any loss of income, profits, goodwill, data, contracts, use of money, or business interruption, and whether in delict, tort (including without limitation negligence), contract, breach of statutory duty, misrepresentation (whether innocent or negligent) or otherwise under any claim of any nature whatsoever in any jurisdiction) in any way arising from or connected with this report and the use, inability to use or the results of the use of this report, and any reliance on this report. The analysis of the security is purely based on the smart contracts alone. No applications or operations were reviewed for security. No product code has been reviewed. HashEx owns all copyright rights to the text, images, photographs, and other content provided in the following document. When using or sharing partly or in full, third parties must provide a direct link to the original document mentioning the author (hashex.org).

2. Overview

HashEx was commissioned by the Trinity DAO team to perform an audit of their smart contracts. The audit was conducted between 25/10/2023 and 31/10/2023.

The purpose of this audit was to achieve the following:

- Identify potential security issues with smart contracts
- Formally check the logic behind given smart contracts.

Information in this report should be used for understanding the risk exposure of smart contracts, and as a guide to improving the security posture of smart contracts by remediating the issues that were identified.

The code was provided directly in .sol file with very limited tests and documentation. The SHA-1 hashes of audited contracts:

GTToken.sol **5365440375af18917e3fc154eaf5058459bd2216**

Distributor.sol **7ced4ce7ae73ba790aeaaca3e1fbbd37c97bc950**

LocalMatrix.sol **bf87b2f95c393254aa2e6dfae5022709a2250e7d**

LocalMatrixLib.sol **b82c6940db593f1a6d9b65ab6649d266c47e9922**

Core.sol **015e4750f599b590609ed38c1ebae347bd206442**

ILevelsContract.sol **032bd45a38a060aab1765a114918876c0127d5ea**

IDistributor.sol **282fe9cc02e7a13236b007d47d2ada8db8a4ed99**

IERC20.sol **90ebd78dd3051ecb612f01f57888986142102b3e**

IGTToken.sol **20fcaada386542113fba227b0d1b44a02d482a45**

IMatrix.sol **b08f637ba4434d7f4fd147d2f86471a1a35b7fc0**

Update: the Trinity DAO team has responded to this report. The updated contracts have

SHA-1:

GTToken.sol **eb7ae753591c5a274bffca05c92425521e699f73**

Distributor.sol **ff31f34c2dedc4537ea07adf2d736a04dfdd9a64**

LocalMatrix.sol **f223599ba3d6f746ac8799e54eca9615f970d6dc**

LocalMatrixLib.sol **b82c6940db593f1a6d9b65ab6649d266c47e9922**

Core.sol **015e4750f599b590609ed38c1ebae347bd206442**

ILevelsContract.sol **032bd45a38a060aab1765a114918876c0127d5ea**

IDistributor.sol **6d1e6baea8165f638483ad6013b74b3ff309845c**

IERC20.sol **90ebd78dd3051ecb612f01f57888986142102b3e**

IGTToken.sol **20fcaada386542113fba227b0d1b44a02d482a45**

IMatrix.sol **cd9eb252eabcc7271ea5d78b345e45914084c1ff**

2.1 Summary

Project name	Trinity DAO
URL	https://trinity-dao.com
Platform	Binance Smart Chain
Language	Solidity
Centralization level	● High
Centralization risk	● High

2.2 Contracts

Name	Address
GToken	
TrinityDAO	
LocalMatrix	
AccountsLocalMatrixes	
Core	
Interface and imports	

3. Project centralization risks

The project owner has indirect ability to withdraw user's funds without explicit permission.

4. Found issues









High	4 (22%)
Medium	2 (11%)
Low	8 (44%)
Info	4 (23%)

C41. GTToken













ID	Severity	Title	Status
C41lc9	High	ERC20 standard violation	Resolved
C41lca	Low	Default visibility of state variables	Resolved
C41lcb	Low	Inconsistent behavior between transfer() and transferFrom() functions	Acknowledged
C41lcd	Low	Gas optimizations	Acknowledged
C41lcc	Info	Possible transfer blocking by donating tokens to next level	Acknowledged

C42. TrinityDAO





ID	Severity	Title	Status
C42ld0	Low	Low entropy randomization in selecting random referrer	Acknowledged

C42Id3	 Low	Gas optimizations	 Acknowledged
C42Ice	 Low	Default visibility of state variables	 Resolved
C42Id2	 Info	Trinary bonus can exceed balance of the Matrix contract	 Resolved



C43. LocalMatrix

ID	Severity	Title	Status
C43Id8	 High	Refund amount can exceed input amount	 Acknowledged
C43Id5	 High	The getTrinaryBonus() function is callable with zero amount, leading to bonus being lost	 Partially fixed
C43Id6	 High	Refund success flag is not updated	 Resolved
C43Id9	 Low	Gas optimizations	 Partially fixed
C43Id4	 Low	Default visibility of state variables	 Resolved
C43Id2	 Info	Typographical error	 Open

C44. AccountsLocalMatrixes

ID	Severity	Title	Status
C44Idb	 Medium	Possible math problem	 Acknowledged
C44Idc	 Info	Possible surrogate handling logic problem	 Resolved

C45. Core

ID	Severity	Title	Status
C45lbf	 Medium	No mechanism to transfer contract ownership	 Acknowledged

5. Contracts

C41. GTToken

Overview

An ERC20 standard token with minting functionality for a selected address - TrinityDAO contract.

Issues

C41lc9 ERC20 standard violation

 High Resolved

The contract's **transfer** function exhibits behavior that is not compliant with the ERC20 standard:

1. The function returns **false** upon a successful transfer, which is contrary to the standard that expects a **true** value.
2. Transfers of a zero amount are prohibited. The ERC20 standard does not enforce such a restriction, and zero transfers should be treated as valid (often used to trigger side effects).

Non-compliance with established standards can lead to incompatibilities with third-party tools, services, and dApps that expect standard behavior. It also can introduce unexpected behaviors for users and developers familiar with ERC20 standard.

```
function transfer(address to, uint256 amount) public virtual override returns (bool) {
    if (amount == 0) { return false; }
    super.transfer(to, amount);
    emit TokenTransfer(to, _msgSender(), amount, 0, 0);
}
```

C41Ica Default visibility of state variables

● Low

✓ Resolved

The `tokenLimit`, `tokenAmount`, and `distributor` state variables in the contract have been declared without an explicit visibility specifier. In Solidity, if no visibility is specified, the default is `internal`. This means that while these variables are not directly accessible from external calls, they can be accessed and potentially modified by derived contracts. Not specifying visibility explicitly can lead to confusion about the intended accessibility of these variables and may inadvertently expose them to unintended modifications in future contract iterations.

C41Icb Inconsistent behavior between `transfer()` and `transferFrom()` functions

● Low

✓ Acknowledged

The `transfer` and `transferFrom` functions in the provided ERC20 implementation exhibit different behaviors:

1. The `transfer` function restricts transfers of a zero amount, whereas `transferFrom` (as per the provided information) does not enforce such a restriction.
2. The `transfer` function emits a custom `TokenTransfer` event, while `transferFrom` does not.

This inconsistency can lead to confusion for developers and users, potential issues in dApps or services built on top of this token, and makes the token's behavior deviate from standard ERC20 expectations.

```
function transfer(address to, uint256 amount) public virtual override returns (bool) {
    if (amount == 0) { return false; }
    super.transfer(to, amount);
    emit TokenTransfer(to, _msgSender(), amount, 0, 0);
}
```

C41Icd Gas optimizations

● Low

✓ Acknowledged

1. The `accountStatuses` data should be moved to immutable state.

2. Unnecessary read of user's balance in call of `getAccountStatusLevel()` inside the `_beforeTokenTransfer()` function.
3. Multiple reads from storage in the `getStatusLevelViaBalance()` function: `accountStatuses.length` and `accountStatuses[i].lowBorder` variables.

C41lcc Possible transfer blocking by donating tokens to next level

● Info

☑ Acknowledged

The contract's mechanism, which assigns status levels based on token balances and prohibits transfers that would decrease a user's status level, introduces a potential risk. A malicious actor or even an uninformed user could send tokens to an account, pushing it to a higher status level. Once this happens, the recipient becomes effectively "locked" from transferring any tokens out, as any transfer would lead to a level decrease and is thereby prohibited. This could lead to scenarios where token balances are inadvertently frozen, disrupting user activities and potentially leading to a loss of trust in the contract's functionality.

```
function _beforeTokenTransfer(address from, address to, uint256 amount)
internal
override
{
    if (contractOwner != msg.sender && from != address(0)) {
        uint balanceOf = balanceOf(from);
        uint8 currentAccountStatusLevel = getAccountStatusLevel(from);
        uint8 newAccountStatusLevel;
        if (currentAccountStatusLevel != 0) {
            newAccountStatusLevel = getStatusLevelViaBalance(balanceOf - amount);
        }
        require(newAccountStatusLevel == currentAccountStatusLevel, "GTE: 1");
    }
    super._beforeTokenTransfer(from, to, amount);
}
```

C42. TrinityDAO

Overview

Main contract of the project - an MLM staking for a fixed ERC20 token. The referral multilayer scheme is configured via instances of LocalMatrix contracts. Has access to minting GT tokens as an additional reward for staking.

Issues

C42Id0 Low entropy randomization in selecting random referrer ● Low ☑ Acknowledged

The `getRandomReferer` function attempts to generate a pseudo-random number by hashing a combination of `block.timestamp`, `block.difficulty`, and `msg.sender`. While this method does provide some level of randomness, it lacks sufficient entropy and is potentially vulnerable to manipulation.

1. `block.timestamp`: Miners can slightly manipulate timestamps, which could influence the result.
2. `block.difficulty`: Predictable and can't be used as a major source of randomness. For EVM versions after the Paris, it behaves as an alias for `block.prevrandao`.
3. `msg.sender`: Publicly known information.

Given the above inputs, a well-informed and well-resourced attacker could predict or influence the outcome of the `getRandomReferer` function.

C42Id3 Gas optimizations ● Low ☑ Acknowledged

1. The `GTToken`, `IERC20Token`, `gtTokenDecimal`, `gtTokenSize` variables can be declared immutable or constant.
2. Multiple reads from storage in the `isSubMatrix()` function: `matrixCount`.

3. The `isSubMatrix()` function should break the loop upon the first found condition.

C42Ice Default visibility of state variables

● Low

✓ Resolved

The contract contains several variables (`players`, `accountsByAddress`, `IERC20Token`, `GToken`, `gtTokenDecimal`, `gtTokenSize`, and `levelInfos`) that use the default visibility. By not explicitly specifying a visibility (like `public`, `internal`, or `private`), it can lead to confusion about the intended accessibility of these variables, possibly exposing them to unintended access patterns or making it harder to discern the contract's intended behavior.

C42Id2 Trinary bonus can exceed balance of the Matrix contract

● Info

✓ Resolved

The `TrinityDAO.getTrinaryBonus()` function calls for `LocalMatrix.getTrinaryBonus()` and transfers up to `account.balance[1] + account.balance[2] + account.balance[3]` amount to the user. In general, the Matrix contract's balance can be insufficient to perform such transfer due to possibility of adding a user without incoming payment via `onlyOwner buyProgram()` function.



C43. LocalMatrix

Overview

A referral model contract that stores staked user's funds. Some functions of LocalMatrix rely on the AccountsLocalMatrixes library. It can be called only via the Distributor contract.

Issues

C43Id8 Refund amount can exceed input amount

 High Acknowledged

The general nature of the TrinityDAO as a Ponzi scheme may cause an insufficient balance to complete a withdrawal. In particular, the `TrinityDAO.refundRequest()` can't be completed for a single user in overall due to refund amount being doubled against the input amount for the `buyProgram()` function.

```
function buyProgram(
    address accountAddress,
    address referer,
    uint8 level
) external isLevelTreeInitialized(level) nonReentrant {
    ...
    uint levelPrice = localMatrixes[level].getLevelPrice();
    _sendInLocalMatrix(level, levelPrice);\
}

function refundRequest(address accountAddress)
external
onlyDistributor
levelTreeInitialized
accountInTree(accountAddress)
nonReentrant {
    ...
    uint refundAmount = levelPrice;
    if (tree.accounts[accountAddress].balance[1] == 0) { refundAmount += levelPrice /
2; }
    else { refundAmount += tree.accounts[accountAddress].balance[1]; }
    if (tree.accounts[accountAddress].balance[2] == 0) { refundAmount += levelPrice /
2; }
    else { refundAmount += tree.accounts[accountAddress].balance[2]; }
    delete tree.accounts[accountAddress];
    IERC20Token.transfer(accountAddress, refundAmount);
}
```


Recommendation

Increase test coverage to eliminate possible problems with insufficient funds.

C43Id5 The `getTrinaryBonus()` function is callable with zero amount, leading to bonus being lost ● High ↻ Partially fixed

The `getTrinaryBonus()` function allows the caller to specify an amount, which is used to transfer the bonus to the `receiverAddress`. There is no check in place to ensure that this amount is greater than zero. If called with a zero amount, the function will effectively delete the bonus for the specified `accountAddress` without actually transferring any bonus to the receiver. This could lead to unintentional loss of bonuses, especially if the function is called programmatically.

```
function getTrinaryBonus(address accountAddress, uint amount, address receiverAddress)
external onlyDistributor {
    AccountsLocalMatrixes.LevelTree storage tree = matrixLevelTrees[0];
    require(
        roots[accountAddress] != address(0),
        "LME: 21"
    );
    require(
        tree.getAccountBalance(accountAddress) >= amount,
        "LME: 22"
    );
    IERC20Token.transfer(receiverAddress, amount);
    delete tree.accounts[accountAddress];
}
```

Recommendation

Add a `require` check to avoid invertedly passing not initialized parameter to the function.

C43Id6 Refund success flag is not updated ● High ✓ Resolved

The `refundRequest()` function checks whether a refund has been processed for an account

using the condition `if (!tree.accounts[accountAddress].isRefundDone)`. However, within this conditional block, there's no code that updates the `isRefundDone` attribute for the given account. This omission allows the condition to always be met, potentially allowing users to request multiple refunds which can be exploited to drain funds from the contract.

```
function refundRequest(address accountAddress)
external
onlyDistributor
levelTreeInitialized
accountInTree(accountAddress)
nonReentrant {
    AccountsLocalMatrixes.LevelTree storage tree = matrixLevelTrees[0];
    require(
        tree.accounts[accountAddress].programPurchaseTime + 365 days <=
block.timestamp,
        "LME: 9"
    );
    require(
        tree.accounts[accountAddress].reinvestCount == 0,
        "LME: 10"
    );
    require(
        roots[accountAddress] == address(0),
        "LME: 20"
    );
    if (!tree.accounts[accountAddress].isRefundDone) {
        uint refundAmount = levelPrice;
        address[3] memory childs;
        (childs,) = tree.getAccountMatrix(accountAddress);
        if (tree.accounts[accountAddress].balance[1] == 0) { refundAmount +=
levelPrice / 2; }
        else { refundAmount += tree.accounts[accountAddress].balance[1]; }
        if (tree.accounts[accountAddress].balance[2] == 0) { refundAmount +=
levelPrice / 2; }
        else { refundAmount += tree.accounts[accountAddress].balance[2]; }
        delete tree.accounts[accountAddress];
        IERC20Token.transfer(accountAddress, refundAmount);
        distributor.emitRefundsEvent(accountAddress, refundAmount, level);
    }
}
```

Recommendation

Update the `tree.accounts[accountAddress].isRefundDone` instead of fully deleting mapping item.

C43Id9 Gas optimizations

● Low

🔧 Partially fixed

1. The `distributor`, `IERC20Token`, `level`, `levelPrice`, `activationPrice` variables can be declared immutable.
2. The `selfAddress` variable is not initialized nor used anywhere.
3. The `childs[]` array is not used in the `refundRequest()` function.

C43Id4 Default visibility of state variables

● Low

✅ Resolved

The contract contains several variables (`distributor`, `IERC20Token`, `selfAddress`, and `matrixLevelTrees`) that use the default visibility. By not explicitly specifying a visibility (like `public`, `internal`, or `private`), it can lead to confusion about the intended accessibility of these variables, possibly exposing them to unintended access patterns or making it harder to discern the contract's intended behavior.

C43Id2 Typographical error

● Info

❓ Open

The term "referer" is used in the contract, which is presumably a typographical error. The correct term should be "referrer". Misnaming variables can lead to confusion for developers, maintainers, and auditors, potentially obscuring the intent and functionality of the code.

C44. AccountsLocalMatrixes

Overview

A library contract for LocalMatrix referral tree functions.

Issues

C44ldb Possible math problem

● Medium

✓ Acknowledged

The Matrix contract receives not more than **levelPrice** amount of payment tokens for **LocalMatrix.addAccountInLevelTree()**, and **_initiatePayment()** spends at most full **levelPrice** amount. Then **_proceedReinvest()** tries to spend more, and these payments may cause a general withdrawal failure due to insufficient funds.

```
function paste(
    LevelTree storage self,
    address accountAddress,
    address refererAddress,
    bool isRefererSurrogate,
    address levelsContractAddress,
    address distributorAddress
) internal {
    ...
    uint8 position = _findFreePosition(parentMatrix.connections);
    _initiatePayment(
        self,
        accountAddress,
        parentMatrixOwner.addr,
        position,
        levelsContract,
        distributorAddress
    );
    if (_isReinvest(position)) {
        IDistributor distributorContract = IDistributor(distributorAddress);
        _proceedReinvest(
            self,
            parentMatrixOwner,
```

```
        levelsContract,
        distributorAddress
    );
}
}

function _initiatePayment(
    LevelTree storage self,
    address sender,
    address receiver,
    uint position,
    ILevelsContract levelsContract,
    address distributorAddress
) private {
    uint amount;
    Account storage receiverAccount = self.accounts[receiver];
    ...
    if (position == 3) {
        amount = levelsContract.getLevelPrice();
        ...
    }
    if (amount != 0) {
        levelsContract.pay(receiver, amount);
        levelsContract.emitEvent(sender, receiver, position,
receiverAccount.reinvestCount, amount);
    }
}

function _proceedReinvest(
    LevelTree storage self,
    Account storage reinvestAccount,
    ILevelsContract levelsContract,
    address distributorAddress
) private {
    ...
    paste(
        self,
        reinvestAccount.addr,
        reinvestReferer,
        isRefererSurrogate,
        address(levelsContract),
        distributorAddress
    );
}
```

```
}
```

Recommendation

Increase test coverage to eliminate possible problems with insufficient funds.

C44Idc Possible surrogate handling logic problem

 Info Resolved

The function designed for reinvestment has inconsistent logic for handling surrogate referrers. Initially, it checks if the referrer is a surrogate, and subsequently, it calls `_closeAccountMatrix()`, which seems to be designed for non-surrogate referrers. Then, when the function tries to get the reinvest referrer, and if this referrer isn't a surrogate, it ends up calling `_closeAccountMatrixWithSurrogateReferer()`, which appears to be designed specifically for surrogate referrers. This logic can lead to potential discrepancies in how matrices are closed based on the referrer type.

```
function _proceedReinvest(
    LevelTree storage self,
    Account storage reinvestAccount,
    ILevelsContract levelsContract,
    address distributorAddress
) private {
    IDistributor distributorContract = IDistributor(distributorAddress);
    if (!reinvestAccount.isRefererSurrogate) {
        _closeAccountMatrix(self, reinvestAccount);
        paste(
            self,
            reinvestAccount.addr,
            reinvestAccount.refererAddress,
            false,
            address(levelsContract),
            distributorAddress
        );
        return;
    }
    (
        address reinvestReferer,
        bool isRefererSurrogate
```

```
    ) = _getReferer(  
        self,  
        reinvestAccount.addr,  
        levelsContract  
    );  
    if (!isRefererSurrogate) {  
        _closeAccountMatrixWithSurrogateReferer(  
            self, reinvestAccount, reinvestReferer  
        );  
    }  
    ...  
}
```

Update

The Trinity team answered that this behaviour is intended.

C45. Core

Overview

A simple authorization model for a single address ownership.

Issues

C45lbf No mechanism to transfer contract ownership

● Medium

☑ Acknowledged

The **Core** contract designates the contract deployer as the **contractOwner** upon deployment. However, there is no function available to transfer the ownership to another address after the contract has been deployed. This limitation means that if the original deployer's address gets compromised or if there's a need to delegate administrative control to another address, there's no way to do so, leaving the contract potentially stuck or at risk.

Recommendation

Use OpenZeppelin's Ownable contract for managing ownership.

C47. Interface and imports

Overview

Various interface contracts and direct forks from OpenZeppelin repository:

Context, IERC20, IERC20Metadata, IGTTToken, IDistributor, ILevelsContract, IMatrix.

No issues of any severity were found.

6. Conclusion

4 high, 2 medium, 8 low severity issues were found during the audit. 2 high, 3 low issues were resolved in the update. The reviewed contracts are highly dependent on the owner's account. See the centralization risks chapter.

This audit includes recommendations on code improvement and the prevention of potential attacks.

Appendix A. Issues' severity classification

- **Critical.** Issues that may cause an unlimited loss of funds or entirely break the contract workflow. Malicious code (including malicious modification of libraries) is also treated as a critical severity issue. These issues must be fixed before deployments or fixed in already running projects as soon as possible.
- **High.** Issues that may lead to a limited loss of funds, break interaction with users, or other contracts under specific conditions. Also, issues in a smart contract, that allow a privileged account the ability to steal or block other users' funds.
- **Medium.** Issues that do not lead to a loss of funds directly, but break the contract logic. May lead to failures in contracts operation.
- **Low.** Issues that are of a non-optimal code character, for instance, gas optimization tips, unused variables, errors in messages.
- **Informational.** Issues that do not impact the contract operation. Usually, informational severity issues are related to code best practices, e.g. style guide.

Appendix B. Vulnerabilities checked

Unchecked math	passed
Reentrancy attacks	passed
Front-run attacks	passed
Flashloot attacks	passed
DoS with (unexpected) revert	passed
DoS with block gas limit	passed
Transaction-ordering dependence	passed
ERC/BEP and other standards violation	passed
Implicit visibility levels	passed
Excessive gas usage	passed
Timestamp dependence	passed
Forcibly sending ether to a contract	passed
Weak sources of randomness	not passed
Shadowing state variables	passed
Usage of deprecated code	passed

 contact@hashex.org

 [@hashex_manager](https://t.me/hashex_manager)

 blog.hashex.org

 [linkedin](#)

 [github](#)

 [twitter](#)

#HashEx
BLOCKCHAIN SECURITY