

Adaptive dynamic query routing for Urdu information retrieval

Short title: Adaptive query routing for Urdu information retrieval

Hashim Shazad^{1*}, Adnan Aslam¹

¹ Department of Creative Technologies, Air University, Islamabad, Pakistan

* abbasihashim30@gmail.com

Abstract

Urdu news users often type native Perso-Arabic script, informal Roman Urdu, or a mixture of both, while many retrieval systems still apply one index to every query. This paper reports the official frozen retriever from an adaptive dynamic query-routing project for Urdu news search. The frozen system, M0, uses a Unicode detector over 111,860 news articles. Urdu, mixed, and other queries search an Urdu Okapi BM25 index. Roman queries search a second BM25 index whose documents were romanized with a closed character table and a 198-key reverse dictionary (Method D). Queries are not rewritten. BM25 uses $k_1 = 1.5$ and $b = 0.75$; lists are retrieved to depth 50 and scored at a Top-5 cutoff.

On a development/validation known-item pool of title-derived queries, ExactSource Hit@5 was 68/78 (87.18%; Clopper–Pearson 95% interval 77.68–93.68%). On a newly sealed known-item sample the same frozen system achieved 27/40 (67.50%; 50.87–81.43%). On a separate sealed naturalistic set with no gold article, a single annotator judged the Top-5 useful (at least one relevant or partially relevant document) for 23/40 queries (57.50%; 40.89–72.96%). Query-side Roman expansions did not raise the 68/78 development score, so the freeze was not replaced. In the naturalistic sample, Urdu-script queries succeeded in 17/18 cases and Roman queries in 6/18; all four mixed queries failed.

These three percentages answer different questions and must not be averaged. Native-script Urdu news search under this freeze is strong on the tested collection. Ordinary Roman Urdu remains the main limitation.

Introduction

Urdu is written in a cursive Perso-Arabic script, but that is not how everyone searches. A large share of users type Roman Urdu: Urdu words in Latin letters, with spelling that is informal and inconsistent [1–3]. A news collection indexed only in native script will not match those queries even when the article is sitting in the index. That mismatch is a retrieval failure, not a missing document.

Urdu remains thinner in shared information retrieval (IR) evaluation than English [4]. Collections exist. CURE provides an Urdu ranking resource [5]. An Urdu MS MARCO baseline reports MRR@10 of 0.247 in the abstract (0.248 in the results table) for a fine-tuned Urdu mT5-mMARCO configuration, under a passage-ranking protocol that is not the one used here [6]. Those resources do not freeze a script-conditional lexical system and then keep known-item recovery separate from human usefulness. Roman Urdu research is still mostly classification—sentiment, offensive language—rather than news search [1, 2]. Multilingual dense retrievers can lose effectiveness on languages that sit outside the pretraining head [7], even when scaled multilingual encoders help related tasks such as Urdu natural language inference [8]. Users of lower-resource varieties are also often pushed toward high-resource query forms [9]. Typing Roman Urdu into an Urdu-script index is a concrete instance of that pressure.

The ULTRA framework of Bashir, Qaiser, and Hussain supplies a dual-embedding Urdu news architecture and a large news corpus [10]. Its original switch is a static character-length threshold. Length is easy to implement and easy to fool: a short “why” question may need the article body, and a long factoid may be answered by a headline. Length also does not decide which *script index* to open. English work on query routing chooses among sparse and dense retrievers [11] or varies retrieval depth in retrieval-augmented generation [12]. Those systems were not designed for Roman Urdu.

This paper asks a narrower question that can be answered with a freeze and a protocol. Specify a lexical retriever. Hash the corpus and the Roman dictionary. Then measure three things that are easy to mix and should not be mixed. First, how often does the system recover a designated source article from title-derived queries on the development/validation pool used to select the Roman path? Second, does that known-item score hold on a newly sealed sample of title-like queries written after the freeze? Third, how often is the Top-5 useful when there is no gold article and a person judges the hits?

Official retrieval here is Okapi BM25 [13] with Unicode script routing. We call that frozen configuration M0. In this project, adaptive dynamic query routing is that script-conditional index choice, not a learned SHORT/LONG classifier. Earlier work in the same project trained a SHORT/LONG support vector machine and a MiniLM dual-index [14]. Those experiments are not the official retriever. We mention them only where they were actual development comparators, so that older classification or dense-index numbers are not mistaken for M0.

The contribution is the frozen system, the separated evaluations, and a measured Roman Urdu limitation. We do not claim that M0 is the first Urdu retriever, and we do not claim state of the art against CURE or Urdu MS MARCO.

Research questions

- **RQ1.** Can a script-aware lexical pipeline (Urdu BM25 plus Method D) recover known news articles from title-derived queries on a development/validation pool?
- **RQ2.** Does that known-item score transfer to a newly sealed known-item sample written independently of the freeze set?
- **RQ3.** How often is frozen M0 useful—at least one relevant or partially relevant document in the Top-5—on new naturalistic queries with no gold article?
- **RQ4.** Do query-side Roman expansions improve development/validation ExactSource Hit@5 enough to replace M0?

Materials and methods

Research design

The study is an offline IR evaluation of one frozen lexical system. Method selection used a pre-registered development split. The official unseen tests were sealed before retrieval. No test query was used to choose BM25 parameters, routing, the Roman method, or the dictionary. After the freeze, later query-side expansions were accepted only if they improved the development known-item score; they did not, and M0 was left in place.

Two tasks are reported. Known-item search asks whether a pre-assigned source document appears in the Top-5. Naturalistic search has no source identifier; a human labels the retrieved Top-5. Those tasks are not averaged.

Corpus

The collection is `data/clean_articles.csv`: 111,860 news articles. The precursor dump is `data/urdu_news.csv`, used in the ULTRA news-search setting [10]. Cleaning was limited to dropping rows with null fields and concatenating headline and body:

```
combined_text = Headline + ' ' + News Text
```

There was no Unicode NFKC folding, no ye/he/kaf canonicalization, no diacritic stripping, no stemming, and no stopword removal at indexing. HTML, punctuation, English tokens, and near-duplicate articles were left as in the source dump. Document identifiers equal the corpus row index after that cleaning step. Article categories in the dump are Sports, Business & Economics, Entertainment, and Science & Technology.

Corpus SHA-256: 8992a6acca3459eea17a7d7356dd490445daa00b958eab765713853c97a9f231 (540,050,203 bytes). The Roman dictionary is `models/roman_urdu_dict_expanded.json` (198 keys; SHA-256 30c3f61a64ec641abbb3acdbc7a8bc9f197f0238f1bf9e76c2c7ce8e590f86a3).

Official frozen system (M0)

Fig 1 summarizes M0. Internally the system retrieves 50 documents; the official cutoff is 5. Queries are not rewritten on the official path.

Fig 1. Official frozen retriever M0. A Unicode script detector routes URDU, MIXED, and OTHER queries to Urdu BM25 and ROMAN queries to Method D romanized-document BM25. Queries are not rewritten. This is not an SVM SHORT/LONG router and not a MiniLM dual-index pipeline.

The detector counts characters in the Arabic/Urdu block U+0600–U+06FF and ASCII letters A–Z/a–z. If both counts are zero the label is OTHER. If both are positive the label is MIXED. If only the Urdu count is positive the label is URDU. Otherwise the label is ROMAN. URDU, MIXED, and OTHER search Urdu BM25 over `combined_text`. ROMAN searches Method D BM25 over romanized documents. The detector is not a classifier. On the Phase 2 development/validation pool it agreed with the oracle script tags on 78/78 queries. The nine MIXED items in that pool were mixed by construction (an English template suffix), not detector errors.

Tokenization is the same on both indexes: the regular expression `[\u0600-\u06FF]+|[A-Za-z0-9]+`, lowercase, no stemming, no stopword list. BM25 is Okapi with frozen $k_1 = 1.5$ and $b = 0.75$. Inverse document frequency for term t with document frequency n in a collection of N documents is

$$\text{idf}(t) = \log \left(\frac{N - n + 0.5}{n + 0.5} + 1 \right). \quad (1)$$

The implementation is the custom BM25 class in `experiments/phase5_roman_urdu/run_phase5.py`. The Urdu index has 371,368 terms and mean document length 279.24 tokens. The Method D index has 358,497 terms and mean document length 279.19 tokens.

Method D

Method D keeps the typed Roman query and indexes romanized documents. Every article in the 111,860-document collection is romanized; the index is not restricted to evaluation source documents. After tokenization, each token is handled as follows. If it contains Urdu letters and that exact token is a value in the 198-key dictionary, emit the first reverse-mapped Latin key (`setdefault`; first key wins). Otherwise emit a character-table romanization (`_CHAR_ROMAN` from the Phase 2 pipeline). Tokens that are already Latin or alphanumeric are lowercased and kept. The character table maps, among other pairs, madda alif to `aa` and che to `ch`, and collapses several Urdu letters onto the same Latin letter (for example `te` and `tte` both map to `t`). That collision is intentional and lossy.

Method D is the document-side counterpart of Phase 2 `title_roman` generation. It is not a mapping fitted to evaluation query strings.

Roman-method selection (Phase 5)

Four Roman strategies were pre-registered and compared on development Roman known-item queries only ($n = 13$), before internal-validation scores were interpreted. Selection used ExactSource Hit@5, then nDCG@5, then lower mean query latency. BM25 hyperparameters were not retuned. Method comparison counts are in S3 Table.

Method A sends the raw Roman query to the Urdu-script BM25 index. Method B transliterates with the existing 198-key dictionary and then searches that same Urdu index; unmapped tokens stay Latin. Method C applies a closed spelling-variant table, dictionary lookup, and a greedy inverse of the Phase 2 character table, then searches Urdu BM25. Method D is the romanized-document index described above. A fifth analysis, Method E, reported the union of C and D; it was not a selectable system, and reciprocal rank fusion was not built [15].

The selected method was frozen in `artifacts/selected_method.json` before internal validation ($n = 10$ Roman queries) was read. Mixed queries in the deployable router go to Urdu BM25. Urdu queries always use Urdu BM25.

Development/validation known-item pool

Phase 2 built 260 title-derived known-item queries from corpus articles that were not used in earlier routing-trap sets. Each query has one `source_doc_id`. Templates include short title, romanized title, why/how/effects, lead excerpt, and mixed Urdu+English. Roman strings in this pool are `title_roman`: dictionary reverse lookup plus the character table applied to headlines. They are not chat-style Roman Urdu. The split (seed 42) is train $n = 182$, development $n = 39$, internal validation $n = 39$. Official M0 development/validation reporting uses development plus internal validation ($n = 78$). The train split was not used to select Method D; it was later used only as a diagnostic pool for query-side expansions.

Query-side expansions (Phase 11)

After M0 was frozen, four query-side Roman transforms were scored on the same $n = 78$ pool. The hard gate was ExactSource Hit@5 not below 68/78. A train-Roman diagnostic ($n = 64$) was used only among candidates that passed the gate. H001–H040 and the later sealed sets were not loaded.

M0 applies no query transform. M1 appends a closed alias list while keeping original tokens. M2 adds four further aliases. M3 applies M1 then drops a nine-token query stoplist. M4 combines M1, M2, and the stoplist. The 198-key dictionary file was not edited. Terms such as `diesel` and `iphone` were explicitly forbidden as new keys. The official Phase 12 run did not apply M1–M4.

Sealed evaluation (Phase 12)

K001–K040 (known-item) and U001–U040 (naturalistic) were written and checksum-sealed before retrieval (seed 120260827). Query-file SHA-256 values are
124e452693f98baedf510618240c154df68d56b6b7a37ed085a6512c13d13ff6 (K) and

684fd1e19eddb717f5897d869ef0ca0ed586316c5a7e1d2d23006e0748fc53b9 (U). One retrieval pass of frozen M0 produced Top-50 lists. Queries were not edited after ranks were seen. M1–M4 were not applied.

K queries are shortened or lightly paraphrased headlines from articles that were not Phase 2 QTRN sources (260 source identifiers excluded; eligible population 111,574 headlines of length at least 12 after stripping). The creator could see the source article in order to assign `source_doc_id` and did not run BM25 while writing. The 12 Roman K queries are ordinary Roman Urdu of the selected headline, not `title_roman` character-table strings. No mixed-script K query occurred naturally; mixed script was not forced.

U queries follow pre-registered naturalistic quotas: 18 Urdu, 18 Roman, 4 mixed; 12 short (≤ 5 whitespace tokens), 16 medium (6–12), 12 long (13+); 14 factoid, 14 explanatory, 12 named-entity. Four temporal factoids use *aaj* / *aaaj* / *mojooda* forms. U has no `source_doc_id`. Queries were not copied from H001–H040. After retrieval, detector counts were 18 URDU, 18 ROMAN, and 4 MIXED; retrieval-path counts were 22 Urdu BM25 (URDU plus MIXED) and 18 Method D. Thirty-nine queries returned 50 hits; U006 returned 28. No query returned fewer than five hits.

Human relevance protocol (U only)

After the sealed Top-5 dump existed, the first author labeled 200 documents (40 queries $\times$ 5) from headline and snippet only. The same author had written the sealed U queries under the Phase 12 protocol. Labels follow a five-way rubric: A, relevant (the reader could stop); B, partially relevant (same event or occasion, incomplete answer); C, topically related (same topic or entity, not the asked need); D, not relevant; E, ambiguous if A–D cannot be decided. The annotator preferred B over A unless the need was clearly satisfied, and preferred C over B unless the article helped answer the asked need. Temporal queries were judged as archive type-of-fact for a dated occasion in the article, not against the annotator’s calendar day. Recurring wires with no date in the query (gold price, budget date, eclipse, stock close) could be A even if dates differed. Named-entity lookups were A if the article’s main subject was that person. There was no second annotator. ExactSource Hit@5 was not computed on U. Label definitions are in S1 Text.

Metrics

For a known-item query with source identifier *s*, ExactSource Hit@*k* is 1 if and only if *s* appears in the retrieved top *k*. The official cutoff is *k* = 5. Secondary K cutoffs are 1, 10, and 50. Known-item nDCG@5 on the development pool uses gain $1/\log_2(\text{rank} + 1)$ when the source is in the Top-5, else 0. Known-item P@5 equals 0.2 times Hit@5 because there is a single relevant document.

For naturalistic queries, Success@5 is 1 if and only if at least one Top-5 document is A or B. Conservative P@5 is the mean of (count of A labels)/5. nDCG@5 uses gains A = 3, B = 2, C = 1, D = E = 0. MRR is the reciprocal rank of the first A or B, or 0 if none. nDCG@5 is secondary: a Top-5 of only topical C documents can score nDCG@5 = 1 with no A or B.

Clopper–Pearson 95% intervals were computed from the reported binomial counts using SciPy’s `binomtest` (SciPy 1.16.3). They were not part of method selection. No hypothesis test comparing systems on K or U was pre-registered; we do not report *p*-values for those splits.

Rejected alternatives

Development comparators on the same *n* = 78 pool include headline MiniLM, a truncated full-article Chroma index, a 96/32 chunk approximate nearest-neighbour index, and Urdu-only BM25. A pre-registered long-context `intfloat/multilingual-e5-small` index was not built: a CPU prototype ran at 2.3 documents/s (about 13.5 hours extrapolated for 111,860 articles) and failed a 4-hour gate. The encoder was not swapped after that failure. Fusion of headline and script-aware lists was not deployed: an oracle union added three known-item hits, which was judged insufficient. A reranker was not built. Historical SHORT/LONG SVM routing and MiniLM dual-index graded P@5 on H001–H040 are a separate study. They are not official M0 metrics.

Diagnostic set H001–H040

H001–H040 are routing-trap strings with no source identifier. ExactSource Hit@5 is undefined on that set. A later human pass (Phase 10C) labeled 196 retrieved rows (38 queries $\times$ 5, plus H027 $\times$ 5 and H036 $\times$ 1; H036 returned a single document). Success@5 was 25/40; conservative P@5 was 0.1250; 10/40 lists were all D. On that sample, Success@5 was 14/20 for Urdu-script queries and 11/20 for Roman; eight of the ten all-D lists were Roman. Labels were assigned from headline plus a 500-character snippet. Query text, rank-1, and labels are now known. The set is treated as a historical diagnostic and is not the official unseen usefulness result. It is not combined with U.

Software environment and reproducibility

M0 retrieval uses Python 3.13.9 (Anaconda, 64-bit Windows). Dense-index pilots in the same project ran on CPU (12 cores reported for the e5-small prototype). Method D index construction on the full corpus took 100.6 s (66.3 s tokenize and romanize, 34.3 s BM25 postings) and occupied 116.1 MB of in-memory postings. Entry points were not relocated: detector and BM25 in `experiments/phase5_roman_urdu/run_phase5.py`, character table in `experiments/phase2_oracle/run_phase2_pipeline.py`, sealed runner in `experiments/phase12_new_unseen_evaluation/run_phase12.py`. The freeze manifest is `experiments/phase8_final_freeze/FINAL_SYSTEM_MANIFEST.json` (S1 File).

Data availability

The news corpus (`data/clean_articles.csv`; 111,860 articles), the Roman Urdu dictionary (`models/roman_urdu_dict_expanded.json`; 198 keys), and the M0 retrieval code are publicly available at <https://github.com/HashimAbbasii/Dynammic-Query-Routing-Urdu-ILS> with no redistribution restrictions. SHA-256 hashes reported in the Corpus subsection identify the exact artifacts used for the scores in this paper. Official metrics were copied from sealed Phase 8–12 reports and were not recomputed for this manuscript.

Results

Table 1 reports the three official headlines. The rows are different tasks. They are not a single accuracy trajectory.

Table 1. Official M0 results. ExactSource Hit@5 and human Success@5 answer different questions. Intervals are Clopper–Pearson 95% intervals computed from the reported counts. Do not average rows. Do not treat 87.18% as unseen or as human usefulness.

Evaluation	Dataset	Metric	Result
Development/validation known-item	Phase 2, $n = 78$	ExactSource Hit@5	68/78 (87.18%; 77.68–93.68%)
New known-item	K001–K040	ExactSource Hit@5	27/40 (67.50%; 50.87–81.43%)
New naturalistic (human)	U001–U040	Success@5	23/40 (57.50%; 40.89–72.96%)

Development/validation known-item

ExactSource Hit@5 on development plus internal validation was 68/78. Secondary known-item metrics on that pool were $nDCG@5 = 0.8107$ and $MRR = 0.797$. An independent rebuild in a later phase reproduced $Hit@5 = 0.8718$.

Table 2 and Fig 2 place M0 against the development comparators that were actually run. Urdu-only BM25 (no Roman path) scored 0.5897. Headline MiniLM scored 0.4487. The truncated full-article dense

index scored 0.2564, worse than headlines, consistent with truncation at 128 tokens. Chunk ANN scored 0.2821. Those dense numbers are development evidence that a full MiniLM index was not a substitute for a Roman lexical path. They are not Phase 12 results.

Table 2. Development/validation comparators on the same $n = 78$ known-item pool. Official M0 is the script-aware row. Oracle unions were not deployed.

System	Hit@5	nDCG@5	MRR
Truncated full MiniLM (Chroma)	0.2564	0.2203	0.2103
Chunk ANN (96/32)	0.2821	0.2362	0.2309
Headline MiniLM	0.4487	0.4009	0.3885
Urdu BM25, no Roman path	0.5897	0.5509	0.5425
Script-aware M0	0.8718	0.8107	0.797
Headline + M0 oracle (not deployed)	0.9103	0.8703	0.8615

Fig 2. ExactSource Hit@5 on the Phase 2 development/validation pool ($n = 78$). Values are the frozen development comparators in Table 2. Script-aware M0 is the official system. This figure is not a Phase 12 result.

On the 46 Urdu-script queries in that pool, Urdu BM25 Hit@5 was 0.913; script-aware routing left that number unchanged because the Urdu path is the same index. On the 23 Roman queries, Method A was 0/23 and headline MiniLM was 1/23. Method D recovered 22/23 (development 13/13, internal validation 9/10). The remaining miss, QTRN_031, was rank 9 with 10 overlapping tokens against the romanized source: Hit@10 succeeded, so the residual was ranking competition rather than a remaining script mismatch. Method B remained 0/13 on development Roman queries: 22 of 23 Roman strings were still mostly Latin after dictionary lookup. Method C tied Method D on development Hit@5 (13/13) but lost on nDCG@5 (0.8004 versus 0.9331) and would have scored 6/10 on internal validation in a post-hoc diagnostic that was not used for selection. Mixed queries ($n = 9$) scored Hit@5 = 0.4444 on the Urdu path; a mixed-path union did not raise that figure.

A later rebuild (Phase 6) reproduced 68/78 and listed the ten residual misses: four URDU, one ROMAN (QTRN_031), and five MIXED. Four of those ten sat in ranks 6–10. Mixed-script items in this pool were generated with an English template suffix, so those misses are not a census of naturally mixed user queries.

The 87.18% result is genuine for title-derived known-item search on this pool, including Roman queries that resemble Method D’s own romanization. It is not a forecast of chat-style Roman performance.

Phase 11 ablation

Table 3 reports the query-side expansions. M0 through M4 all scored 68/78. Train-Roman Hit@5 stayed 61/64 (95.31%). M1–M4 nDCG@5 and MRR on that diagnostic were slightly below M0 (0.8940 and 0.8781 versus 0.8960 and 0.8807). No candidate beat 68/78. M1 passed the gate as the simplest non-destructive candidate and was not installed as the official system.

Table 3. Phase 11 query-side Roman expansions. The official system remains M0. Train Roman $n = 64$ is a selection diagnostic, not an unseen test.

Model	$n = 78$ Hit@5	Train Roman Hit@5	Train nDCG@5	Train MRR
M0 (official)	68/78	0.9531	0.8960	0.8807
M1	68/78	0.9531	0.8940	0.8781
M2	68/78	0.9531	0.8940	0.8781
M3	68/78	0.9531	0.8940	0.8781
M4	68/78	0.9531	0.8940	0.8781

New known-item (K001–K040)

Preflight passed: corpus and dictionary hashes matched the freeze, BM25 parameters were unchanged, and M1–M4 were off. Every query returned 50 hits. Detector counts were 28 URDU and 12 ROMAN, matching the retrieval-path counts.

Table 4 reports ExactSource Hit at four cutoffs. The primary metric is Hit@5 = 27/40. Hit@1 is 20/40. Two further sources appear between ranks 6 and 50 (Hit@10 = 28/40, Hit@50 = 30/40). Ten of the 13 Hit@5 misses are absent from the entire Top-50; three are in the list but below rank 5 (K002 rank 6, K010 rank 49, K031 rank 17). Per-query source ranks are in S1 Table.

Table 4. Phase 12 K ExactSource results, frozen M0. Primary metric is Hit@5. This evaluation does not replace 68/78 and is not human Success@5.

Metric	Result
ExactSource Hit@1	20/40 (50.00%)
ExactSource Hit@5	27/40 (67.50%; 50.87–81.43%)
ExactSource Hit@10	28/40 (70.00%)
ExactSource Hit@50	30/40 (75.00%)

The detector split was not used for tuning. Urdu-script K titles scored 26/28 ExactSource Hit@5 (92.86%; 76.50–99.12%). Ordinary Roman titles scored 1/12 (8.33%; 0.21–38.48%). Fig 3 shows that split beside the naturalistic script split. Fig 4 separates Hit@5 from “source present but below rank 5” and “source absent from the Top-50.” Both Urdu misses (K002 rank 6, K010 rank 49) are still in the list. Ten of eleven Roman misses never enter the Top-50; the remaining Roman miss (K031) is rank 17. The drop from 87.18% to 67.50% is concentrated on ordinary Roman title queries, and on matching rather than near-miss ranking, not on native-script Urdu BM25.

Fig 3. Descriptive script splits of frozen M0, not used for tuning. Left: ExactSource Hit@5 on K001–K040. Right: human Success@5 on U001–U040. Mixed $n = 4$ is descriptive only. The two panels are different metrics and must not be averaged.

Fig 4. Where sealed known-item misses sit. Counts from the K001–K040 per-query source ranks. Urdu misses remain inside the Top-50. Most Roman misses never appear in the retrieved 50.

Naturalistic human evaluation (U001–U040)

Success@5 was 23/40. Conservative P@5 was 0.2050 (variable-denominator P@5 was identical because every query had at least five hits). nDCG@5 was 0.6460. MRR was 0.4542. Among 200 labeled documents the counts were A 41, B 26, C 53, D 80, E 0 (Table 5; Fig 5). Forty-one fully answering documents across 40 queries is consistent with conservative P@5 = 0.2050: many Top-5 lists contain at most one A.

Table 5. Phase 12 U human metrics, frozen M0 Top-5. Success@5 is the usefulness headline. nDCG@5 includes gain 1 for topical C and is not a usefulness claim.

Metric	Result
Success@5 (any A or B)	23/40 (57.50%; 40.89–72.96%)
Conservative P@5 (A-count/5)	0.2050
nDCG@5 (A=3, B=2, C=1)	0.6460
MRR (first A or B)	0.4542
Label counts (200 documents)	A 41, B 26, C 53, D 80, E 0
All-D queries	12/40

Fig 5. Label mass on the 200 judged U Top-5 documents. A = relevant, B = partially relevant, C = topically related, D = not relevant, E = ambiguous. E did not occur. D is the modal label.

The gap between Success@5 and conservative P@5 is the shape of many successes: one useful document rather than a Top-5 packed with full answers. nDCG@5 overstates usefulness for the same reason the gain table is generous to C.

Fig 3 and Table 6 show descriptive slices. Urdu-script queries succeeded in 17/18 cases (94.44%; 72.71–99.86%). Roman queries succeeded in 6/18 (33.33%; 13.34–59.01%). Mixed queries were 0/4 (0–60.24%). Mixed $n = 4$ is too small for a population rate; it is reported because all four failed. These slices describe this sealed sample. They are not a licence to retune Method D on U failures.

Table 6. Descriptive U Success@5 slices. Script uses the detector label at retrieval time. Need type and length follow the sealed query file.

Slice	Successes	n	Rate
URDU	17	18	0.9444
ROMAN	6	18	0.3333
MIXED	0	4	0.0000
Factoid	9	14	0.6429
Explanatory	9	14	0.6429
Named entity	5	12	0.4167
Short (≤ 5 tokens)	9	12	0.7500
Medium (6–12)	6	16	0.3750
Long (13+)	8	12	0.6667
Temporal	3	4	0.7500
Non-temporal	20	36	0.5556

Complete Success@5 failures were U004, U006, U008, U010, U014, U016, U018, U020, U026, U028, U032, U034, U035, U037, U038, U039, and U040. Twelve of those lists were all D, including several English-loan or service queries (`psl points table`, train-ticket price, Netflix charges, 5G, dollar rate) and several chat-style Roman strings. Per-query labels are in S2 Table.

Diagnostic H001–H040

Phase 10C human Success@5 on H001–H040 was 25/40 (62.50%; 45.80–77.27%), with conservative P@5 = 0.1250 and 10/40 all-D lists. Urdu-script traps succeeded in 14/20 cases and Roman traps in 11/20; eight of the ten all-D lists were Roman. H036 returned one document, labeled D. The queries are routing traps, not the Phase 12 naturalistic sample. The number is recorded so it is not silently dropped; it is not the official unseen usefulness result.

Discussion

The three headline percentages look like a system falling apart. They are three measurements.

On the freeze pool, M0 often recovers a known article from a shortened headline, including Roman queries built as `title_roman`. Method D was selected on that construction. High Hit@5 is what one should expect when the query is a title fragment and, for Roman, when the spelling family matches the index. RQ1 is answered in that setting: 68 of 78 sources reached the Top-5, well above Urdu-only BM25 on the same pool, because the Roman path repaired a script mismatch that Method A could not (0/23).

K keeps the known-item question and changes the sample. Roman K queries were written as ordinary Roman Urdu of the headline, not as character-table `title_roman`. Urdu K stayed high (26/28), and both Urdu misses were still in the Top-50. Roman K did not (1/12), and ten of those misses never entered the Top-50. That pattern is a matching failure, not a near-miss ranking problem. The 19.7 point drop from

87.18% to 67.50% is therefore largely a Roman query-form shift, plus ordinary binomial variation on $n = 40$. It is not evidence that Urdu BM25 broke. RQ2 is answered in the negative if “transfer” means the 87% figure itself; the honest unseen known-item figure on this sealed K set is 27/40.

U asks a different question. There is no single right article. Factoids, explanations, named entities, underspecified strings, and chat Roman are harder than “find this headline.” Success@5 only requires one A or B, and still lands at 23/40. Conservative P@5 of 0.205, with 41 A labels in 200 documents, shows that the Top-5 is rarely full of complete answers; D is the most common label. Named-entity queries in this sample were weaker (5/12) than factoid or explanatory queries (each 9/14). Urdu-script needs were usually met (17/18). Roman needs often were not (6/18). RQ3 is therefore a usefulness rate near 58% overall, and near 94% when the user types Urdu script, on this $n = 40$ set with one annotator.

Query mix will move any headline number. A Roman-heavy sample will look worse than an Urdu-only test even if the Urdu component is unchanged. Averaging 87.18% with 57.50% answers no scientific question: it mixes development with new test, known-item with graded usefulness, and `title_roman` with chat Roman.

RQ4 is straightforward. Allowed query-side expansions did not move 68/78. A small spelling table is not a demonstrated fix for the Roman gap on K and U, and those sets were not used to invent a larger table.

The pattern is consistent with how Method D was built. Document romanization plus a 198-key reverse dictionary can match pipeline-romanized titles. It does not enumerate WhatsApp-style spelling, English loanwords that users type in Latin while the article uses Urdu, or mixed-script strings that the freeze sends to the Urdu index. Method B already showed that dictionary lookup on the query is too sparse for naive romanizations. The freeze kept the document-side index. That decision was justified for `title_roman`. It was not a solution to open-vocabulary Roman IR.

Relative to prior Urdu resources, these numbers are not a CURE or MS MARCO leaderboard entry [5,6]. The protocol is different, the collection is news, and the Roman path is the scientific point. Relative to English routers that choose sparse versus dense retrieval [11], M0 chooses which script index to open. That is a smaller, more local form of adaptivity, and it is the one the Unicode detector can actually implement without a learned classifier.

What remains strong is inspectable. Native-script Urdu BM25 on this news collection recovers title-like known items and, in this U sample, usually puts something useful in the Top-5. The contribution is that measurement, under a hashed freeze, with the Roman failure left in view.

Limitations

K and U each have $n = 40$. The intervals in Table 1 are wide. Point estimates should not be read as a precise “58% in the wild.”

U labels are from one annotator, the first author, who had also written the sealed U queries under the Phase 12 protocol. There is no inter-annotator agreement. Preferring B over A reduces over-claiming of full answers; it does not remove subjectivity. The dual role is a bias risk even though labels were assigned after retrieval, from headline and snippet only, and without searching for a better document.

Development Roman queries are `title_roman`. K Roman queries are ordinary Roman titles. U Roman queries are chat-style. Those are three related but distinct input families. Success on the first does not contradict failure on the other two.

The nine MIXED items in the $n = 78$ pool were generated with an English suffix. Phase 12 mixed queries ($n = 4$) are too few to estimate a rate. Both facts limit what can be said about mixed-script search.

The corpus is news only. Cleaning was a null drop. M0 does not rewrite queries, does not use dates, and does not generate answers. Temporal “today” items were judged as archive type-of-fact.

nDCG@5 with C-gain = 1 can look high when Success@5 fails. H001–H040 are diagnostic only. K, U, and H001–H040 are burned if M0 is changed. Post-freeze development work exists in the repository; it is not part of these official scores.

We do not claim 80% unseen usefulness, 87.18% real-world accuracy, or state-of-the-art ranking against CURE or Urdu MS MARCO.

Conclusions

M0 is a frozen script-aware BM25 news retriever developed as the official system of an adaptive dynamic query-routing project. On the development/validation known-item set it recovered the source article in the Top-5 for 68 of 78 queries. On a newly sealed known-item set it did so for 27 of 40. On a separate naturalistic set, a human found at least one useful document in the Top-5 for 23 of 40 queries. Native-script Urdu search is strong on this collection. Ordinary Roman Urdu is not. The contribution is that measured freeze and that limitation, not a single high percentage.

Supporting information

S1 Table. Per-query ExactSource ranks for K001–K040. Detector label, retrieval path, source document identifier, source rank, and Hit@5 for each sealed known-item query. Source: `experiments/phase12_new_unseen_evaluation/K_RESULTS.md`.

S2 Table. Per-query human labels for U001–U040. Raw query text, five Top-5 labels (A–E), Success@5, and rank of first A/B. Source: `experiments/phase12_human_relevance/PHASE12_HUMAN_RESULTS.md`.

S3 Table. Phase 5 development Roman method comparison. Methods A–D on DEV Roman queries ($n = 13$) with Hit@5, nDCG@5, MRR, and latency, plus internal-validation confirmation of Method D. Source: `experiments/phase5_roman_urdu/PHASE5_RESULTS.md`.

S1 File. Freeze manifest. Hashes, BM25 parameters, index statistics, and routing table. Source: `experiments/phase8_final_freeze/FINAL_SYSTEM_MANIFEST.json`.

S1 Text. U annotation protocol. Label definitions, temporal type-of-fact rule, and metric formulae. Source: `experiments/phase12_human_relevance/ANNOTATION_PROTOCOL.md`.

Acknowledgments

This work was completed as part of an M.S. thesis at Air University, Islamabad.

References

1. Hussain N, Qasim A, Mehak G, Usman M, Zain M, Hafeez M, et al. Fine-tuning large language models with QLoRA for offensive language detection in Roman Urdu-English code-mixed text. arXiv. 2025. Preprint. arXiv:2510.03683.
2. Mehmood F, Ghani MU, Ibrahim MA, Shehzadi R, Asim MN. A precisely Xtreme-multi channel hybrid approach for Roman Urdu sentiment analysis. arXiv. 2020. Preprint. arXiv:2003.05443.
3. Sitaram S, Chandu KR, Rallabandi SK, Black AW. A survey of code-switched speech and language processing. arXiv. 2019. Preprint. arXiv:1904.00784.
4. Daud A, Khan W, Che D. Urdu language processing: a survey. Artif Intell Rev. 2017;47:279-311.
5. Iqbal M, Tahir B, Mehmood MA. CURE: Collection for Urdu Information Retrieval Evaluation and Ranking. arXiv. 2021. Preprint. arXiv:2011.00565.
6. Butt U, Varanasi S, Neumann G. Enabling low-resource language retrieval: establishing baselines for Urdu MS MARCO. arXiv. 2024. Preprint. arXiv:2412.12997.

7. Wu J, Ren Z, Verberne S. What are the limits of cross-lingual dense passage retrieval for low-resource languages? arXiv. 2024. Preprint. arXiv:2408.11942.
8. Conneau A, Khandelwal K, Goyal N, Chaudhary V, Wenzek G, Guzmán F, et al. Unsupervised cross-lingual representation learning at scale. In: Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics; 2020. p. 8440-51. doi:10.18653/v1/2020.acl-main.747.
9. Chari A, MacAvaney S, Ounis I. Improving low-resource retrieval effectiveness using zero-shot linguistic similarity transfer. In: Advances in Information Retrieval: 47th European Conference on Information Retrieval (ECIR 2025). vol. 15575 of Lecture Notes in Computer Science. Springer, Cham; 2025. p. 290-306. doi:10.1007/978-3-031-88717-8_22.
10. Bashir A, Qaiser F, Hussain I. ULTRA: Urdu Language Transformer-based Recommendation Architecture. arXiv. 2026. Preprint. arXiv:2602.11836.
11. Arabzadeh N, Yan X, Clarke CLA. Predicting efficiency/effectiveness trade-offs for dense vs. sparse retrieval strategy selection. In: Proceedings of the 30th ACM International Conference on Information and Knowledge Management (CIKM '21); 2021. p. 2862-6. doi:10.1145/3459637.3482159.
12. Jeong S, Baek J, Cho S, Hwang SJ, Park JC. Adaptive-RAG: learning to adapt retrieval-augmented large language models through question complexity. In: Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies; 2024. p. 7036-50.
13. Robertson S, Zaragoza H. The probabilistic relevance framework: BM25 and beyond. Found Trends Inf Retr. 2009;3(4):333-89. doi:10.1561/15000000019.
14. Reimers N, Gurevych I. Sentence-BERT: sentence embeddings using Siamese BERT-networks. In: Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing; 2019. p. 3982-92. doi:10.18653/v1/D19-1410.
15. Cormack GV, Clarke CLA, Büttcher S. Reciprocal rank fusion outperforms Condorcet and individual rank learning methods. In: Proceedings of the 32nd International ACM SIGIR Conference on Research and Development in Information Retrieval; 2009. p. 758-9. doi:10.1145/1571941.1572114.