

Sahoulat API Documentation

REST API for the Sahoulat mobile app (customers + professionals). Built on Laravel 12 + Sanctum. All routes are prefixed with `/api`, e.g. `https://your-domain.test/api/login`.

Tested end-to-end against the full booking → escrow payment → completion → wallet payout lifecycle, jobs/bids, emergencies, contracts, and disputes.

1. Conventions

Headers

Every request should send:

```
Accept: application/json
```

Authenticated requests must also send:

```
Authorization: Bearer <token>
```

Requests with a JSON body should send:

```
Content-Type: application/json
```

File upload endpoints (photos, KYC documents) use `multipart/form-data` instead.

Auth model

Token-based via **Laravel Sanctum**. There is no session/CSRF — every device that logs in gets its own long-lived bearer token (`device_name` you send becomes the token's label, so a user can be logged in on multiple devices and revoke them individually).

Roles

A user has exactly one `role`: `consumer`, `provider`, or `job_seeker` (`job_seeker/admin` flows are not covered by this API — it's scoped to the customer + professional apps). Role is fixed at registration and determines which route group (`/api/consumer/*` or `/api/provider/*`) the account can call. Cross-role calls return `403`.

Standard error shapes

401 — missing/invalid/expired token:

```
{ "message": "Unauthenticated." }
```

403 — wrong role, or a policy denied the action:

```
{ "message": "This account type cannot access this resource." }
```

404 — model not found, or (deliberately, for security) hidden because it doesn't belong to you / isn't active.

422 — validation errors (standard Laravel shape):

```
{
  "message": "The email field is required.",
  "errors": { "email": ["The email field is required."] }
}
```

422 is also used for business-rule rejections (e.g. "That time slot is no longer available"), in the simpler { "message": "..." } shape.

409 — race condition (e.g. two providers accepting the same emergency request at once).

Pagination

List endpoints that paginate return:

```
{
  "...collection key...": [ /* items */ ],
  "pagination": { "current_page": 1, "last_page": 3, "total": 42 }
}
```

Money

All amounts are numbers (PKR), not strings, e.g. "price": 3000 not "price": "3000.00" .

2. Auth

POST /api/register

Auth: none Body:

Field	Type	Notes
name	string	required
email	string	required, unique
phone	string	required — any format accepted; normalized server-side to 03XX-XXXXXXX (see note below)
role	string	required — consumer , provider , or job_seeker
password	string	required, min 8
password_confirmation	string	required, must match password
device_name	string	required — label for this token, e.g. "iPhone 15"

Pakistani phone numbers are reformatted to 03XX-XXXXXXX on save (a leading +92 / 92 country code is stripped and replaced with a trunk 0 first). The stored/returned value may therefore differ from what was submitted — e.g. +923001234567 or 03001234567 both come back as 0300-1234567 . Numbers that aren't 11 digits after stripping non-digits are left as-is.

Response 201 :

```
{
  "user": {
    "id": 22, "name": "Test Consumer", "email": "test@example.com",
    "phone": "0300-1234567", "role": "consumer", "is_suspended": false,
    "provider_status": null,
    "created_at": "2026-07-21T12:12:07+00:00"
  },
  "token": "1|dFx1zYRMlAFDEVy2Ba1JMLVvxzDkRPhobybCfHbN4541fa29"
}
```

provider_status is only meaningful when role is provider (mirrors provider_profiles.status : draft → pending → approved / rejected).

POST /api/login

Auth: none Body: email , password , device_name (all required) Response 200 : same shape as register. Errors: 422 if credentials don't match, or if the account is suspended.

POST /api/forgot-password

Auth: none. Rate limited (5/min per email+IP). **Body:** email (required) **Response:** { "message": "We sent a 6-digit code to your email." }
Emails a 6-digit OTP (15-minute expiry) via the same password_reset_tokens table and mailable the web app's forgot-password page uses.
Errors: 422 if no user has that email.

POST /api/reset-password

Auth: none. Rate limited (5/min per email+IP on the route, plus 5 wrong-OTP attempts per email+IP before a 5-minute logout). **Body:** email , otp (6 digits, from the emailed code), password (required, confirmed, min 8) **Response:** { "message": "Your password has been reset – please log in." } Verifies the OTP, sets the new password, and revokes the reset token (not the user's Sanctum tokens — existing logged-in devices stay logged in). **Errors:** 422 if the OTP is invalid/expired/rate-limited, or the email doesn't match a user.

POST /api/logout

Auth: required — revokes only the token used for this request (this device). **Response:** { "message": "Logged out." }

POST /api/logout-all

Auth: required — revokes every token for the user (all devices). **Response:** { "message": "Logged out of all devices." }

GET /api/me

Auth: required **Response:** { "user": { ...same shape as register... } }

PUT /api/profile

Auth: required **Body:** name (required), email (required, unique except self), phone (optional — normalized to 03XX-XXXXXXX the same way as registration) **Response:** { "user": { ... } }

PUT /api/profile/password

Auth: required **Body:** current_password (required, must match), password (required, confirmed, min 8), password_confirmation **Response:** { "message": "Password updated." }

DELETE /api/profile

Auth: required **Body:** password (required, must match current password) **Response:** { "message": "Account deleted." } Anonymizes the user's name/email/phone/avatar, sets a random unusable password, deactivates the account (suspended_at), and revokes all Sanctum tokens. Booking/payment history is preserved (no hard delete) to avoid breaking referential integrity.

3. Shared / public browsing

None of these require auth unless noted.

GET /api/categories

Active categories with their active services (the "browse services" catalog, cached 1h server-side). **Response:**

```
{
  "categories": [
    {
      "id": 1, "name": "AC Repair & Service", "slug": "ac-repair-service",
      "description": "...", "icon": "ac", "image_url": null,
      "services": [
        { "id": 2, "category_id": 1, "name": "AC Gas Refill", "slug": "ac-gas-refill",
          "description": "...", "base_price": 3500, "visit_charge": null,
          "duration_minutes": 90, "is_active": true }
      ]
    }
  ]
}
```

```
]
}
```

`icon` is either a legacy icon-name key (e.g. `"ac"` , rendered client-side from a bundled icon set — true for any category that predates icon uploads) or, once a category has an uploaded icon image, the ready-to-use absolute URL for it (e.g. `"https://sahoulat.com/storage/categories/xyz.jpg"`). Check whether it starts with `http` to tell which case you're in. Same behavior on the nested `category.icon` in `ServiceResource` .

`visit_charge` (nullable) is a fixed, non-negotiable fee some services carry, payable if a provider cancels after inspecting the job in person — separate from and in addition to the service's `base_price` . **Disclose it up front, before booking** — the web app shows it as a prominent callout on the service detail page and a small line on service cards, precisely because it can surprise a customer if they only learn about it after the fact. See `POST /provider/bookings/{id}/status` (`visit_charge_method` / `visit_charge_screenshot`) for how it actually gets collected, and the `visit_charge` object on `BookingResource` for the collected record.

GET /api/services

All active services (flat list, e.g. for search/typeahead). Response: `{ "services": [ {...ServiceResource...} ] }`

GET /api/services/{slug}

Service detail + approved providers offering it (cheapest first, paginated) + 3 related services. "Approved" here excludes providers currently suspended for unpaid cash-commission debt — they're temporarily not eligible for new bookings until they settle up. **Response:**

```
{
  "service": { "id": 2, "name": "AC Gas Refill", "...": "..." },
  "providers": [
    { "provider_profile_id": 21, "provider": { "...ProviderProfileResource..." }, "price": 3000 }
  ],
  "providers_pagination": { "current_page": 1, "last_page": 1, "total": 1 },
  "related_services": [ {...} ]
}
```

GET /api/providers

Public provider directory — approved and not currently suspended for unpaid cash-commission debt. **Query:** `q` (search name/bio/city/service), `city` (exact match). Both optional. **Response:**

```
{
  "providers": [ {...ProviderProfileResource...} ],
  "pagination": { "current_page": 1, "last_page": 1, "total": 5 },
  "cities": ["Islamabad", "Karachi", "Lahore"]
}
```

GET /api/providers/{id}

One provider's public profile: bio, services offered (with prices), portfolio photos, and latest 10 reviews. **Response:** `{ "provider": {...}, "reviews": [ { "id":1, "rating":5, "comment":"...", "consumer_name":"...", "service_name":"...", "created_at":"..." } ] }`

GET /api/providers/{id}/services/{serviceId}/availability

Bookable dates + time slots for a specific provider/service pairing — call this before showing the booking picker. **Query:** `date` (optional, YYYY-MM-DD ; defaults to the first bookable date). **Response:**

```
{
  "price": 3000, "duration_minutes": 90,
  "dates": [
    { "value": "2026-07-21", "label": "Today — 21 Jul" },
    { "value": "2026-07-22", "label": "Wed, 22 Jul" }
  ],
  "selected_date": "2026-07-21",
}
```

```
"slots": [
  { "value": "09:00", "label": "9:00 AM", "available": false },
  { "value": "10:00", "label": "10:00 AM", "available": true }
]
```

GET /api/subscription-plans

Active maintenance/AMC plans. Response: { "plans": [{ "id":1, "name":"...", "slug":"...", "service": {...}, "frequency_months":1, "frequency_label":"Monthly", "total_visits":12, "price_per_visit":2000, "is_active":true }] }

GET /api/cities

Cities with at least one approved provider — for populating city pickers, purely informational (this list has no bearing on geo-fencing, which is boundary-only now, not city-based). Response: { "cities": ["Islamabad", "Karachi", "Lahore"] }

4. Shared / authenticated (any role)

All require Authorization: Bearer <token>.

GET /api/notifications

Paginated, newest first. Response: { "notifications": [{...] }, "unread_count": 3, "pagination": {...} } Each notification: { "id", "type", "title", "body", "url", "is_read", "read_at", "created_at" }

POST /api/notifications/{id}/read

Marks one notification read. Response: { "notification": {...} }

POST /api/notifications/read-all

Response: { "message": "All notifications marked as read." }

GET /api/bookings/{id}/room

Chat history + tracking pin(s) for a booking (both consumer and provider on the booking can call this). **Response:**

```
{
  "is_communicable": true,
  "can_share_location": true,
  "messages": [ { "id":1, "sender_id":22, "sender_name":"Test Consumer", "body":"...", "created_at":"..." } ],
  "latest_tracking": { "id":1, "latitude":24.86, "longitude":67.01, "note":null, "created_at":"..." },
  "tracking_history": [ { "id":1, "latitude":24.86, "longitude":67.01, "note":null, "created_at":"..." }, "...up to the most recent 500 p...",
  "destination": { "latitude":24.90, "longitude":67.05, "address":"House 1, Karachi" }
}
```

`destination` is the booking's own address coordinates (`null` if the booking has none) — feed `latest_tracking` as the origin and `destination` as the destination into the Google Directions API client-side to draw the actual driving route + ETA, the same way the web app's booking room does (`google.maps.DirectionsService / DirectionsRenderer`). It's static for the life of the booking, so fetch it once alongside everything else here rather than re-deriving it.

`can_share_location` is `true` only while the booking is `confirmed` — once it flips to `in_progress` the provider has arrived, so there's nothing left to route to and this goes back to `false` . Stop sending tracking pings (and hide the "share my location" control) the moment this flips, rather than only reacting to a `422` from the tracking endpoint.

POST /api/bookings/{id}/messages

Body: `body` (string, required, max 2000) **Response 201 :** { "message_data": {...} } — broadcast in realtime over the existing Reverb/Echo channel for the booking.

POST /api/bookings/{id}/tracking

Post a live location pin (typically the provider en route). **Body:** latitude , longitude (required), note (optional). **Response 201 :** { "tracking": {...} }

POST /api/bookings/{id}/dispute

Body: reason (string, required, max 2000), photos[] (optional, up to 5 images, 8MB each, multipart) — evidence for the complaint.
Response 201 : { "dispute": {...} }

GET /api/disputes/{id}

Response: { "dispute": {
"id", "reference", "opened_by_role", "reason", "status", "resolution", "resolution_note", "resolved_at", "created_at", "photos": [{"id":1, "url": "https://..."}]
} }

5. Consumer API (/api/consumer/*, role consumer required)

GET /api/consumer/dashboard

Home-screen summary. Response: { "recent_bookings": [{...BookingResource, up to 5...}] }

Addresses

Method	Path	Body	Notes
GET	/addresses	-	{ "addresses": [...] }
POST	/addresses	label , address , city (required); latitude , longitude , is_default (optional)	201 , { "address": {...} }
PUT	/addresses/{id}	same as POST	{ "address": {...} }
DELETE	/addresses/{id}	-	{ "message": "Address removed." }

Address shape: { "id", "label", "address", "city", "latitude", "longitude", "is_default" }

Geo-fencing on POST/PUT: same boundary check as bookings/emergencies/etc. (see POST /bookings above) — when geo-fencing is on, latitude / longitude are checked against active ServiceArea boundaries before the address is saved. Outside every drawn boundary → 422 with { "message": "Sorry, we don't operate in the \"{address}\" area yet." }.

Bookings (direct booking flow)

GET /bookings — paginated, newest first. { "bookings": [...], "pagination": {...} }

POST /bookings — create a direct booking with a specific approved provider.

Field	Required	Notes
provider_profile_id	yes	must be an approved provider
service_id	yes	must be a service that provider actively offers
scheduled_date	yes	one of the values from the availability endpoint
scheduled_time	yes	HH:MM , must be an available slot
address	yes	
latitude , longitude	no	
notes	no	max 1000

Response 201 : { "booking": { ...BookingResource... } }. 422 if the *customer's own address* (not the provider's city, as it used to be — see below) is outside our served areas while geo-fencing is on, or if the slot just got taken.

Geo-fencing (applies here and to POST /emergencies, POST /job-posts, POST /contracts, POST /subscriptions — all identical behavior): when the admin-side "Geo-fencing" setting is on, each of these is checked against active ServiceArea rows before it's created. This is purely a point-in-polygon check against **real coordinates** — every service area has an admin-drawn boundary (a city field/string match is no longer part of this at all), so you must supply real latitude / longitude, not just an address string, or the request is rejected outright. A location outside every drawn boundary is always treated as outside the service area, with no city-name fallback. If it fails, the response is 422 with a message explaining the location isn't served. When geo-fencing is off (default) or no service areas are configured yet, nothing is blocked.

GET /bookings/{id} — { "booking": { ... } } (full detail incl. payments, review, dispute)

POST /bookings/{id}/cancel — only while cancellable by the consumer (not yet in progress). Auto-refunds escrow if already paid. { "message": "...", "booking": { ... } }

GET /bookings/{id}/payment-options — { "gateways": [{ "key": "mock", "label": "Test payment (sandbox)" }, { "key": "cash", "label": "Cash" }, { "key": "bank_transfer", "label": "Bank transfer" }], "amount": 3000, "company_account": { ... } }. mock only ever appears outside production (APP_ENV) or when explicitly forced on via MOCK_PAYMENTS_ENABLED — it must never be reachable on the live site, since it always succeeds instantly with no real money. jazzcash / easypaisa only appear once their env credentials + *_ENABLED=true are configured. **cash and bank_transfer are always included** (same reasoning as milestones below) so pre-payment never dead-ends into an empty gateway list when no online gateway is configured. company_account is the same shape as completion-payment-options below — needed for the bank-transfer instructions.

POST /bookings/{id}/pay — Body: gateway (required — must be one of the keys returned by payment-options above), screenshot (required if gateway=bank_transfer, image, multipart, max 8MB). Response 201 : { "message": "...", "payment": { ... } }, or, for gateways needing an off-site redirect: { "status": "pending", "redirect_url": "...", "redirect_fields": { ... } }.

gateway=cash here is a *commitment*, not an instant charge — nothing can really be "prepaid" in cash before the provider has shown up. The payment is recorded pending and only actually settled (commission deducted, invoice emailed) once the job is later marked complete.

gateway=bank_transfer behaves like a real gateway: it's recorded pending with the screenshot and, once an admin verifies it, held in escrow (not released) until the job is completed and the consumer calls /release — unlike the completion-payment bank transfer below, which verifies straight to released since the job is already done by then.

POST /bookings/{id}/release — release escrow to the provider once completed & undisputed. { "message": "...", "booking": { ... } }

POST /bookings/{id}/review — Body: rating (1-5, required), comment (optional, max 1000). Only once, only after completion. Response 201 : { "review": { ... } }

GET /bookings/{id}/completion-payment-options — for bookings that skip pre-payment and only ask for money once the job is actually done (see permissions.needs_completion_payment below, and Booking::needsCompletionPayment()). 404 if this booking isn't one of those. Response:

```
{
  "amount": 1000,
  "methods": ["cash", "bank_transfer"],
  "company_account": {
    "bank_name": "Bank Al Habib Ltd",
    "account_title": "Sahoulat Facility Management Services",
    "account_number": "5052-0081-001208-01-4",
    "iban": "PK15BAHL50520081001208014",
    "swift_code": "BAHLPKKA",
    "branch_name": "Islamic Midway Commercial \"A\" Bahria Town Karachi",
    "branch_code": "5052",
    "branch_address": "Showroom # 1, SQ Trade Center, Plot A-118 Midway Commercial \"A\" Bahria Town Karachi Pakistan",
    "jazzcash_number": "",
    "easypaisa_number": ""
  }
}
```

This is Sahoulat's own receiving account for a manual bank transfer — display it in full so the customer can copy every field (iban / swift_code matter for interbank/international transfers). jazzcash_number / easypaisa_number are currently empty (not yet configured) — omit those rows

client-side when blank, same as the web app does.

POST /bookings/{id}/completion-payment — record how a just-completed job got paid. Body: `method` (required, `cash` | `bank_transfer`), `screenshot` (required if `method` is `bank_transfer`, image, multipart, max 8MB). `cash` is recorded immediately (commission is deducted from the provider's wallet automatically) and the customer is emailed a PDF invoice right away. `bank_transfer` needs an admin to verify the screenshot first (web-only step) — the invoice email goes out once that happens. Response 201 : { "message": "...", "payment": {...} }. 422 if this booking isn't awaiting completion payment.

Booking resource shape (used throughout)

```
{
  "id": 1, "reference": "BK-Z6POMA", "status": "confirmed",
  "service": { "...ServiceResource..." },
  "provider": { "...ProviderProfileResource..." },
  "consumer": { "id": 22, "name": "Test Consumer", "phone": "0300-1234567" },
  "scheduled_date": "2026-07-22", "scheduled_time": "10:00",
  "price": 3000, "duration_minutes": 90, "address": "House 1, Karachi",
  "latitude": null, "longitude": null, "notes": null,
  "cancelled_by": null, "cancellation_reason": null,
  "completion_notes": null,
  "confirmed_at": "...", "started_at": null, "completed_at": null, "cancelled_at": null,
  "created_at": "...",
  "before_photos": [ {"id": 1, "url": "https://..."} ],
  "after_photos": [ {"id": 2, "url": "https://..."} ],
  "visit_charge": null,
  "payments": [ {...} ], "review": null, "dispute": null,
  "permissions": {
    "can_cancel": true, "is_payable": true, "needs_completion_payment": false, "is_reviewable": false,
    "is_disputable": false, "is_communicable": true, "can_share_location": false,
    "is_provider": false
  }
}
```

`permissions` tells the app which action buttons to show — always trust this over re-deriving the logic client-side. `before_photos` / `after_photos` are only present when the booking detail endpoint eager-loads them (both consumer and provider `GET /bookings/{id}` do). `visit_charge` is non-null only when a provider cancelled an in-progress booking after collecting the visit charge on inspection (see the provider status endpoint below) — shape: { "amount": 500, "method": "cash", "screenshot_url": null, "collected_at": "..."} . This money is never part of commission/wallet accounting — it's the provider's directly.

Jobs (post & bid flow)

GET /jobs — { "jobs": [...], "pagination": {...} }

POST /jobs — post a job for open bidding. Multipart if attaching photos.

Field	Required
service_id	yes
description	yes, max 2000
budget	no, numeric
preferred_date	no, date ≥ today
address, city	yes
latitude, longitude	no
photos[]	no, up to 5 images, 5MB each

Response 201 : { "job": {...JobPostResource...} }

GET /jobs/{id} — full detail with all bids (each bid includes the bidding provider's profile).

POST /jobs/{id}/cancel — only while `status = open`. Rejects any pending bids too.

POST /jobs/{id}/bids/{bidId}/accept — accepts a bid, creates a confirmed `Booking`, rejects all other pending bids on that job, notifies the winning + losing providers. `{ "message": "...", "booking": {...} }`. `422` if the slot clashes with another confirmed booking for that provider, or the proposed time has passed.

JobPost resource shape

```
{
  "id": 1, "reference": "JOB-PZYQ40", "status": "open",
  "service": {...}, "consumer": { "id": 22, "name": "..."},
  "description": "...", "budget": null, "preferred_date": null,
  "address": "...", "latitude": null, "longitude": null, "city": "Karachi",
  "photos": [ { "id": 1, "url": "https://.../job-photos/1/xyz.jpg" } ],
  "bids_count": 2, "pending_bids_count": 1,
  "bids": [ {...BidResource...} ],
  "my_bid": null,
  "awarded_at": null, "created_at": "..."
}
```

Contracts (multi-service projects, admin-quoted)

GET /contracts — `{ "contracts": [...], "pagination": {...} }`

POST /contracts — submit for a manual admin quote. Multipart if attaching photos.

Field	Required
<code>title</code> , <code>description</code>	yes
<code>preferred_start_date</code>	no
<code>address</code> , <code>city</code>	yes
<code>latitude</code> , <code>longitude</code>	no
<code>photos[]</code>	no, up to 8 images
<code>items[]</code>	yes, min 1 — each: <code>service_id</code> (required), <code>quantity</code> (required, 1-100), <code>notes</code> (optional)

Response `201`: `{ "contract": {...} }` — status starts as `submitted`; an admin later sets `quoted_total` and per-milestone amounts.

GET /contracts/{id} — full detail incl. `items`, `photos`, `milestones`.

POST /contracts/{id}/accept / **POST /contracts/{id}/reject** — only while `status = quoted`.

POST /contracts/{id}/cancel — only while cancellable.

GET /contracts/{id}/milestones/{milestoneId}/payment-options — same shape as booking payment-options, **plus cash and bank_transfer are always included** (unlike bookings, a milestone has no pay-after-completion fallback, so these two are the reliable path while no online gateway is configured). Also includes `company_account` (see the completion-payment shape above) for the bank-transfer instructions. Response:

```
{
  "gateways": [
    { "key": "mock", "label": "Test payment (sandbox)" },
    { "key": "cash", "label": "Cash" },
    { "key": "bank_transfer", "label": "Bank transfer" }
  ],
  "amount": 3000,
  "company_account": { "...": "same shape as the booking completion-payment endpoint" }
}
```

POST /contracts/{id}/milestones/{milestoneId}/pay — Body: `gateway` (required — one of the keys from `payment-options`), `screenshot` (required if `gateway=bank_transfer`, image, multipart, max 8MB).

- `gateway=cash` — trusted immediately, no proof required (same as a real gateway success): the payment and milestone both move straight to escrow.
- `gateway=bank_transfer` — the payment stays `pending` until an admin verifies the screenshot in the admin panel; only then does it move to escrow. The consumer isn't blocked from anything in the meantime — this is just slower than cash.
- A real gateway key — unchanged, synchronous success moves straight to escrow (or `{"status":"pending","redirect_url":...}` for an off-site redirect gateway).

Response 201: `{ "message": "...", "payment": {...} }` in all cases (except the off-site redirect case, same shape as booking `/pay`).

Emergencies (SOS)

GET /emergencies — `{ "emergencies": [...], "pagination": {...} }`

POST /emergencies — broadcasts to nearby approved providers offering that service in that city (realtime + notification).

Field	Required
<code>service_id</code>	yes, must be active and flagged emergency-available — 422 otherwise
<code>address</code> , <code>city</code>	yes
<code>latitude</code> , <code>longitude</code>	no
<code>notes</code>	no

Send `latitude` / `longitude` when you have them (e.g. from the map picker) — they carry straight through to the `Booking` once a provider accepts, same as a direct booking's coordinates.

Response 201: `{ "emergency": {...} }`

GET /emergencies/{id} — includes `matched_provider` and `booking` once accepted, and `quoted_price` once an admin has quoted it.

POST /emergencies/{id}/cancel — while `open` or `quoted`.

POST /emergencies/{id}/accept-quote / **POST /emergencies/{id}/decline-quote** — respond to an admin's price quote (`status` must currently be `quoted`, i.e. `quoted_price` is set). Accepting moves it to `accepted` (admin assigns a provider next); declining moves it to `declined`, a terminal state. 422 if there's no pending quote. Response: `{ "message": "...", "emergency": {...} }`

Subscriptions (maintenance plans)

GET /subscriptions — `{ "subscriptions": [...], "pagination": {...} }`

POST /subscription-plans/{planSlug}/subscribe Body: `address`, `city` (required), `latitude`, `longitude` (optional), `start_date` (required, date ≥ today). Response 201: `{ "subscription": {...} }` — status starts `pending_assignment` until admin assigns a provider.

GET /subscriptions/{id} — includes `provider` and past `bookings` once active.

POST /subscriptions/{id}/cancel — Body: `reason` (optional). Already-scheduled visits are unaffected.

Shop: browsing, cart, checkout, orders

Browsing is public (no auth) at top level, not under `/consumer`; cart/checkout/orders require the `consumer` role.

GET /shop/products (*public*) — Query: `q`, `category` (id), `city`, `provider` (id, for one provider's own shop). Response: `{ "products": [...], "pagination": {...} }` — only active, in-an-approved-provider's-shop products.

GET /shop/products/{id} (*public*) — `{ "product": {...}, "related_products": [...up to 4, same provider...] }`. 404 if inactive or the provider is no longer approved.

A product carries an optional sale price: `price` (regular), `discount_price` (nullable, must be lower than `price`), plus computed `has_discount`, `effective_price` (what's actually charged — always use this, never raw `price`, for any total/cart/order math), and `discount_percentage` (rounded int, 0 when there's no discount).

An admin can deactivate a product (`is_active: false`) instead of deleting it, always with a reason and reactivation instructions for the provider; while inactive, `ProductResource` includes `deactivation_reason` and `reactivation_instructions` (both `null` while active) — the provider app should surface these on the product's own screen so they know what to fix.

Wishlist — requires auth (`consumer` role); a simple saved-for-later list, independent of the cart.

Method	Path	Body	Notes
GET	<code>/consumer/wishlist</code>	-	16/page, paginated. <code>{ "products": [...], "pagination": {...} }</code>
POST	<code>/consumer/wishlist/toggle</code>	<code>product_id</code> (required)	Adds if not already wishlisted, removes if it is. <code>{ "wishlisted": true false, "message": "..."} , 201</code> when added

Cart — one persistent cart per consumer, items can span multiple providers.

Method	Path	Body	Notes
GET	<code>/consumer/cart</code>	-	<code>{ "groups": [...]} — see shape below</code>
POST	<code>/consumer/cart/items</code>	<code>product_id</code> (required), <code>quantity</code> (optional, default 1)	Adds to existing quantity, capped at stock. <code>201</code>
PUT	<code>/consumer/cart/items/{id}</code>	<code>quantity</code> (required)	Capped at stock
DELETE	<code>/consumer/cart/items/{id}</code>	-	-

Each response returns the full cart, grouped by provider — this is exactly the shape checkout expects one selection per:

```
{ "groups": [
  { "provider": {...ProviderProfileResource...}, "items": [...CartItemResource...],
    "subtotal": 2000, "delivery_estimate": 150, "pickup_available": true }
] }
```

`delivery_estimate` is `null` only when the provider doesn't offer delivery at all (`shipping_type` unset — pickup-only). Whenever `shipping_type` is set (`flat` | `percentage` | `free`), the estimate is always a real number here — shipping is priced from the cart subtotal alone, never from the customer's address, so there's nothing further to resolve at checkout.

Coupons — a coupon is scoped to one provider (their code, discounting only their products) and redeemable once per customer, enforced at the database level. The web app remembers an "applied" coupon per provider in the session across cart/checkout page loads; a bearer-token API client has no such session, so instead it holds the applied code itself and re-sends it directly on the checkout call. Use this endpoint to validate + preview the discount first:

POST `/consumer/cart/coupon/preview` — Body: `provider_profile_id` , `code` . Doesn't persist anything server-side. `422` with `{ "valid": false, "message": "..."}` if the code is unknown, inactive, expired, or already used by this customer. On success: `{ "valid": true, "code": "SAVE10", "label": "10% off", "discount": 200 }` (discount computed against that provider's current cart subtotal).

POST `/consumer/checkout` — Body: `orders[]` , one entry per provider group from the cart (a mismatched cart → order split returns `422`). Multipart when any entry pays by `bank_transfer` .

Field	Required when	Notes
<code>orders.*.provider_profile_id</code>	always	must match a group actually in the cart
<code>orders.*.fulfillment_method</code>	always	<code>delivery</code> <code>pickup</code> — <code>422</code> if that provider doesn't offer it
<code>orders.*.payment_method</code>	always	<code>cash</code> <code>bank_transfer</code>
<code>orders.*.address_id</code>	<code>fulfillment_method=delivery</code>	must belong to the requesting consumer — used only to ship the order to, not to price it
<code>orders.*.coupon_code</code>	no	re-validated here regardless of any earlier preview — <code>422</code> if it's no longer usable (someone else claimed a limited code, it expired mid-checkout, etc.)
<code>orders.*.screenshot</code>	<code>payment_method=bank_transfer</code>	image, max 8MB

Stock is locked and re-validated per item at checkout (not just at add-to-cart) — a race with another buyer, or a provider deactivating/deleting a product, surfaces as `422` rather than silently overselling. A coupon's discount applies to the product subtotal before shipping is added;

cancelling an order afterward frees the coupon for reuse (the one-time redemption is deleted). Response 201 : { "orders": [...OrderResource, one per provider...] }.

Orders

Method	Path	Body	Notes
GET	/consumer/orders	-	{ "orders": [...], "pagination": {...} }
GET	/consumer/orders/{id}	-	{ "order": {...} }
POST	/consumer/orders/{id}/cancel	reason (optional)	Only while pending confirmed (restocks items; refunds/voids any payment). 422 once ready
POST	/consumer/orders/{id}/reviews	product_id , rating (1-5), comment (optional)	Rate one product from this order. 422 unless the order is completed and that product hasn't already been reviewed on this order — one review per product per order, re-ordering later opens a new one. 201 : { "review": {...} }

Order lifecycle: pending → confirmed → ready → completed , or → cancelled . ready means "shipped" for a delivery order / "ready for pickup" for a pickup order; completed means delivered / collected. For a cash order, the **provider's** completion action (see §6) is what actually records the payment and charges commission — there's no separate consumer "I paid" step. For bank_transfer , payment is collected up front at checkout and held in escrow once an admin verifies it; it releases to the provider automatically when they mark the order completed .

Product reviews — 7 days after an order is marked completed , a scheduled job (products:remind-reviews) notifies the consumer (in-app + email/push, same as any other notification) to rate what they bought, linking back to GET /consumer/orders/{id} ; the reminder only fires once per order (tracked server-side) and is skipped entirely if every item on the order already has a review. A ProductResource (see product browsing above) carries rating_avg (null if unreviewed) and reviews_count ; the product detail page/endpoint's reviews aren't yet exposed as their own list endpoint — for now, fetch them via the web product page or add one if the app needs them directly.

6. Provider API (/api/provider/* , role provider required)

Most endpoints beyond onboarding require an approved ProviderProfile — calling them before approval returns empty collections (list endpoints) or a 403 from the actAsApprovedProvider gate (action endpoints).

GET /api/provider/dashboard

Home-screen summary: counters, wallet balances, 6-month earnings trend, completion rate, average response time, bid win rate, today's schedule.

```
{
  "profile": {...ProviderProfileResource... or null},
  "pending_bookings": 0, "available_jobs": 2, "open_emergencies": 1,
  "wallet_available": 2700, "wallet_escrow": 0,
  "earnings_month": 2700, "earnings_total": 2700, "earnings_delta": 100,
  "earnings_series": [ {"label":"Feb","value":0}, "...", {"label":"Jul","value":2700} ],
  "jobs_completed": 1, "active_bookings": 1, "completion_rate": 100,
  "response_minutes": 0, "bid_win_rate": 100, "bids_pending": 0,
  "today_schedule": [ {...BookingResource...} ]
}
```

Onboarding / KYC

GET /onboarding — profile + uploaded documents + step progress + what's missing.

```
{
  "profile": {...},
  "documents": [ { "id":1, "type":"cnic_front", "original_name":"...", "download_url":"...", "created_at":"..." } ],
```

```

"document_types": { "cnic_front": {"label":"CNIC – Front","required":true}, "...": "..."},
"steps": [
  { "label": "Your details", "done": true },
  { "label": "KYC documents", "done": false, "uploaded": 1, "required": 3 },
  { "label": "Review", "done": false, "submitted": false }
],
"missing": ["CNIC – Back", "Selfie holding CNIC"],
"can_submit": false
}

```

PUT /onboarding — Body: `experience_years`, `city`, `cnic_number` (required); `business_name`, `bio`, `address`, `latitude`, `longitude` (optional). Blocked (`422`) once submitted/approved. `cnic_number` accepts any format but is normalized and stored as `42101-1234567-8` (13 digits required after stripping non-digits — an unexpected digit count is left as submitted).

POST /onboarding/documents — multipart. Body: `type` (one of the `document_types` keys), `file` (jpg/jpeg/png/pdf, max 4MB). Replaces any existing document of the same type. Response `201`: `{ "document": {...} }`

GET /onboarding/documents/{id} — streams the private file (owner only). Not JSON — returns the raw file.

DELETE /onboarding/documents/{id} — `{ "message": "Document removed." }`

POST /onboarding/submit — moves profile to `pending` for admin review once details + all required documents are present. `422` with a listing of what's missing otherwise.

Services offered

Method	Path	Body	Notes
GET	/services	-	<code>{ "offered": [...], "available": [...], "booking_counts": {...} }</code> — empty until approved
POST	/services	<code>service_id</code> (required, not already offered), <code>price</code> (required)	<code>201</code> , <code>{ "provider_service": {...} }</code>
PUT	/services/{id}	<code>price</code> (required), <code>is_active</code> (optional bool)	<code>{ "provider_service": {...} }</code>
DELETE	/services/{id}	-	<code>{ "message": "..."} </code>

Bookings

GET /bookings — **Query:** `status` (`all` | `pending` | `confirmed` | `in_progress` | `completed` | `cancelled`, default `all`), `q` (search reference/address/consumer/service name). Response: `{ "bookings": [...], "counts": {"all":5,"pending":1,...}, "filter": "all", "pagination": {...} }`

GET /bookings/{id} — full detail.

POST /bookings/{id}/status — multipart when completing (photos) or cancelling with a bank-transfer visit charge (screenshot). Valid transitions: `pending` →(`confirm/decline`)→, `confirmed` →(`start/cancel`)→, `in_progress` →(`complete/cancel`)→. Declining/cancelling auto-refunds escrow.

Body field	Required when	Notes
<code>action</code>	always	<code>confirm</code> <code>decline</code> <code>start</code> <code>complete</code> <code>cancel</code>
<code>cancellation_reason</code>	no	max 1000, used for <code>decline</code> / <code>cancel</code>
<code>completion_notes</code>	no	max 1000, used for <code>complete</code>
<code>before_photos[]</code>	no	optional, 0-6 images, 5MB each — proof of work, recommended but not enforced
<code>after_photos[]</code>	no	optional, 0-6 images, 5MB each
<code>visit_charge_method</code>	<code>action=cancel</code> and the booking is currently <code>in_progress</code>	<code>cash</code> <code>bank_transfer</code> — see below

Body field	Required when	Notes
visit_charge_screenshot	same, and visit_charge_method=bank_transfer	image, max 8MB

Two things worth calling out:

- **complete** **accepts optional before/after photos** and automatically generates an invoice for the booking, emailed to the customer once payment is confirmed.
- **cancel while in progress** is a distinct scenario from cancelling a **confirmed** (not-yet-visited) booking: it means the provider inspected the job on-site and the customer decided not to proceed. In that case **visit_charge_method** is required — it records the provider's visit charge as collected (see **visit_charge** on the booking resource above) entirely outside commission/wallet accounting. Cancelling a **confirmed** booking (before any visit happened) does **not** need these fields.

Response: { "message": "...", "booking": {...} }

Jobs & bids

GET /jobs — 15/page, paginated. Open jobs matching services this provider offers; each job includes **my_bid** (null if not yet bid). Response: { "jobs": [...], "pagination": {...} }

GET /jobs/{id} — { "job": {...}, "offers_service": true, "slot_options": [{"value":"09:00","label":"9:00 AM"}, ...] }

POST /jobs/{id}/bids — Body: **amount** (required, numeric), **proposed_date** (required, $\geq$ today), **proposed_time** (required, one of **slot_options**), **message** (optional). One bid per provider per job. Response 201: { "bid": {...} }

GET /bids — 15/page, paginated. **Query:** **status** (**all** | **pending** | **accepted** | **rejected** | **withdrawn**). **counts** / **win_rate** / **pipeline** are always computed across *all* of this provider's bids, not just the current page. Response: { "bids": [...], "pagination": {...}, "counts": {...}, "win_rate": 100, "pipeline": 2800 } (**pipeline** = sum of pending bid amounts).

PUT /bids/{id} — same body as create; only while pending and the job is still open.

DELETE /bids/{id} — withdraws a pending bid.

Emergencies

GET /emergencies — open requests in the provider's city for services they offer; each includes **my_price** (this provider's price for that service).

POST /emergencies/{id}/accept — first to accept wins; creates a confirmed booking immediately. 409 if another provider already claimed it.

Wallet & payouts

GET /wallet — **Query:** **bucket** (**all** | **available** | **escrow**). Balances, lifetime/monthly earnings, 6-month trend, ledger entries, and recent withdrawal requests.

```
{
  "wallet": { "id":1, "available_balance": 2700, "escrow_balance": 0 },
  "total_earned": 2700, "earned_this_month": 2700,
  "earnings_series": [ {"label":"Feb","value":0}, "..." ],
  "ledger": {
    "bucket": "all", "counts": {"all":3,"available":1,"escrow":2},
    "entries": [ { "id":3, "bucket":"available", "type":"...", "amount":2700, "description":"...", "booking_reference":"BK-Z6POMA", "created_at":... },
    "pagination": {...}
  ],
  "min_withdrawal": 500,
  "withdrawal_requests": [ { "id":1, "reference":"WD-...", "amount":2700, "status":"pending", "payout_method":"jazzcash", "method_label":"JazzCash" },
  ]
}
```

POST /payout-method — Body: **payout_method** (**bank** | **jazzcash** | **easypaisa** , required), **payout_account_title**, **payout_account_number** (required), **payout_bank_name** (required only if **payout_method** = **bank**). Response: { "profile": {...} }

POST /withdrawals — Body: **amount** (required, $\geq$ **min_withdrawal** , $\leq$ current available balance). Requires a payout method already saved. Response 201: { "message": "...", "withdrawal": {...} }

POST /withdrawals/{id}/confirm-receipt — two-party confirmation: after an admin marks a bank-transfer withdrawal `awaiting_confirmation` (sent, pending the provider's acknowledgement), the provider confirms they actually received it, flipping it to `paid` . 422 if the withdrawal isn't currently `awaiting_confirmation` . Response: `{ "message": "...", "withdrawal": {...} }`

Settlements (paying off cash-commission debt)

For cash-collected bookings, commission is never deducted at source — it posts as a negative `available_balance` instead (see `WalletService::chargeCashCommission()`). A provider carrying this debt past `settlement_grace_days` (7 days by default) gets auto-suspended from accepting new bookings until it's settled.

GET /settlements — how much is currently owed + past settlement submissions.

```
{
  "owed": 500,
  "is_suspended": false,
  "settlements": [
    { "id":1, "reference":"STL-...", "method":"bank_transfer", "method_label":"Bank transfer",
      "amount": 500, "confirmed_amount": null, "status":"pending", "admin_notes": null,
      "confirmed_at": null, "created_at": "..."}
  ],
  "pagination": { "current_page": 1, "last_page": 1, "total": 1 }
}
```

`status` ∈ `pending` | `confirmed` | `rejected` . Submitting a settlement doesn't touch the wallet or lift the suspension by itself — only an admin confirming the amount actually received does (which also auto-unsuspends the provider once `available_balance` ≥ 0 again).

POST /settlements — Body: `method` (`cash` | `bank_transfer` , required), `amount` (required, ≤ `owed`), `screenshot` (required if `method` is `bank_transfer` , image, multipart, max 8MB). 422 if nothing is currently owed. Response 201 : `{ "message": "...", "settlement": {...} }`

Portfolio

Method	Path	Body	Notes
GET	/portfolio	-	<code>{ "photos": [...] }</code>
POST	/portfolio	multipart: <code>photos[]</code> (images, up to remaining slots under a 12-photo cap), <code>caption</code> (optional)	201 , <code>{ "photos": [...just the new ones...] }</code>
DELETE	/portfolio/{photoId}	-	<code>{ "message": "Photo removed." }</code>

Shop (products, for providers who also sell physical goods)

A provider must configure at least one fulfillment method — `delivery` (`shipping_type` set) or `pickup_enabled` — before any product can be created; `POST /products` returns 422 otherwise. Commission on product sales uses a separate `product_commission_rate` from the booking `commission_rate` , both admin-set per provider.

GET /shop-settings / **PUT /shop-settings** — Body (PUT): `shipping_type` (`flat` | `percentage` | `free` | `null` , nullable), `shipping_flat_rate` (required if `shipping_type=flat`), `shipping_percentage` (required if `shipping_type=percentage` , 0–100), `pickup_enabled` (bool — when true, the provider's own `address` / `latitude` / `longitude` double as the pickup location shown to customers), `pickup_hours` (nullable string, e.g. `"Mon-Sat 9am-8pm"` — cleared automatically if `pickup_enabled` is false). Response: `{ "provider": {...} }` (see `shop` block in the provider resource, §7).

Shipping is intentionally simple and address-blind: a flat fee, a percentage of the order, or free — never priced by the customer's city or checked against a coverage map (that's the admin-side Geo-fencing feature, a separate, platform-wide "do we operate here at all" gate — see §4's Geo-fencing note). If a provider genuinely can't reach wherever an order needs to go, the expectation is they call the customer or cancel the order themselves, the same way a small local business would.

Method	Path	Body	Notes
--------	------	------	-------

GET	/products	-	{ "products": [...] } — this provider's own catalog, all statuses
POST	/products	category_id (nullable), name (required), description (nullable), price (required, numeric), stock_quantity (required, int ≥0), sku (nullable), is_active (nullable bool, default true), multipart photos[] (nullable, up to 8 images, 5MB each)	422 if no fulfillment method configured yet. 201, { "product": {...} }
GET	/products/{id}	-	{ "product": {...} }
PUT	/products/{id}	same as POST	{ "product": {...} }
DELETE	/products/{id}	-	{ "message": "... " }
DELETE	/products/photos/{photoId}	-	{ "message": "Photo removed." }

Coupons (discount codes for your shop's products)

Method	Path	Body	Notes
GET	/coupons	-	15/page, paginated. { "coupons": [...], "pagination": {...} } — this provider's own codes, with redemption counts
POST	/coupons	code (required, alphanumeric, unique per provider — case-insensitive, stored uppercase), type (flat percentage , required), value (required, numeric; ≤100 if type=percentage), expires_at (nullable, must be in the future)	201, { "coupon": {...} }
POST	/coupons/{id}/toggle-active	-	-
DELETE	/coupons/{id}	-	-

CouponResource — { "id", "code", "type", "value", "label", "is_active", "expires_at", "redemptions_count", "created_at" }. label is a ready-to-display string, e.g. "10% off" or "Rs. 200 off" .

Orders (fulfilling product sales)

Drives an order through pending → confirmed → ready → completed , or → cancelled . Every action below requires the order to already be in the state the transition expects (422 otherwise) and that this provider owns it (403 otherwise).

Method	Path	Body	Notes
GET	/orders	-	Query: status (all pending confirmed ready completed cancelled). { "orders": [...], "counts": {...}, "pagination": {...} }
GET	/orders/{id}	-	{ "order": {...} }
POST	/orders/{id}/confirm	-	pending → confirmed
POST	/orders/{id}/ready	delivery_method (optional free text, max 1000 chars — most local delivery here is a rider service (Bykea/InDrive/Yango) or the provider themselves, not a trackable courier waybill, so there's nothing to require or validate the shape of)	confirmed → ready . Ignored/cleared for a pickup order

Method	Path	Body	Notes
POST	/orders/{id}/complete	-	ready → completed . For a cash order this is also where payment is recorded and commission is charged (see §5) — the provider is physically present handing over goods and collecting payment. For bank_transfer , this releases the already-escrowed payment to the provider's wallet
POST	/orders/{id}/cancel	reason (optional)	Only while pending confirmed ; restocks items and refunds/voids any payment

7. Resource reference

Quick field reference for nested objects that recur throughout the API.

ProviderProfileResource

```
{
  "id": 21, "user_id": 23, "name": "Test Pro", "avatar_url": null, "business_name": null,
  "display_name": "Test Pro", "bio": null, "experience_years": 5,
  "rating_avg": 5.0, "reviews_count": 1, "city": "Karachi", "address": null,
  "latitude": null, "longitude": null, "status": "approved", "rejection_reason": null,
  "has_payout_method": true,
  "services": [ {...ProviderServiceResource, when loaded...} ],
  "portfolio": [ {...ProviderPortfolioPhotoResource, when loaded...} ],
  "shop": {
    "shop_name": "Test Pro", "sells_products": true, "offers_delivery": true,
    "shipping_type": "flat", "shipping_flat_rate": 250, "shipping_percentage": null,
    "pickup_enabled": true, "pickup_hours": "Mon-Sat 9am-8pm",
    "maps_url": "https://www.google.com/maps/search/?api=1&query=24.86,67.03"
  }
}
```

status ∈ draft | pending | approved | rejected . shop.sells_products is true once at least one fulfillment method is configured (delivery or pickup) — that's the gate on whether this provider can have any product go live. shop.maps_url is null until the provider has a pinned latitude / longitude on their profile; shop.pickup_hours is free text, shown to a customer choosing self-pickup.

ProductResource — { "id","provider_profile_id","provider":{...ProviderProfileResource, when loaded...},"category":{...CategoryResource, when loaded...},"name","slug","description","price","stock_quantity","in_stock","sku","is_active","photos":[{"id","url","sort_order"}],"created_at" }

OrderResource — { "id","reference","status","fulfillment_method","payment_method","provider":{...ProviderProfileResource...},"consumer":{"id","name","phone"},... }. status ∈ pending | confirmed | ready | completed | cancelled . fulfillment_method ∈ delivery | pickup . payment_method ∈ cash | bank_transfer . total_amount = subtotal - discount_amount + shipping_amount . coupon_code is only present when the coupon relation was eager-loaded (order-show endpoints do this; order-list ones don't, for a lighter payload).

OrderItemResource — { "id","product_id","product_name","unit_price","quantity","line_total" } — product_name / unit_price are snapshots taken at order time, so they stay accurate even if the product is later renamed, repriced, or deleted.

ServiceResource — { "id","category_id","category":{...or omitted},"name","slug","description","base_price","duration_minutes","is_active" }

BidResource — { "id","job_post_id","job_post":{...summary...},"provider":{...ProviderProfileResource...},"amount","proposed_date","proposed_time","message",... }. status ∈ pending | accepted | rejected | withdrawn .

ContractResource — {

```
"id","reference","title","description","address","latitude","longitude","city","preferred_start_date","status","quoted_total","items":[...ContractResource]. status ∈ submitted | quoted | accepted | rejected | in_progress | completed | cancelled .
```

EmergencyRequestResource — {

```
"id","reference","status","service","consumer","address","latitude","longitude","city","notes","quoted_price","quoted_at","accepted_at","declined_at","cancelled_at" } . latitude / longitude are nullable. status ∈ open | quoted | accepted | declined | matched | cancelled (an admin sets quoted_price and moves it to quoted ; the consumer then accepts/declines). my_price only populated on the provider board endpoint.
```

SubscriptionResource — {

```
"id","reference","status","plan","provider","address","city","next_visit_date","visits_used","is_cancellable","bookings","cancelled_at","created_at" } . status ∈ pending_assignment | active | cancelled | completed .
```

PaymentResource — {

```
"id","reference","gateway","amount","commission_rate","commission_amount","provider_amount","status","screenshot_url","paid_at","released_at" } . status ∈ pending | escrow | released | refunded | failed . screenshot_url is only non-null for gateway=bank_transfer payments — the consumer's own uploaded transfer proof, absolute URL ready to display/download. commission_rate / commission_amount / provider_amount are only ever non-null once a payment is released (they're written by WalletService::release() / chargeCashCommission() ), and only visible to the requesting user if they're an admin or a provider — a consumer viewing their own booking's payment always gets null for these three, since the commission split is between the platform and the provider, not the consumer's business. Commission is per-provider now (see ProviderProfile.commission_rate , set by an admin at approval time), not a single platform-wide rate.
```

WithdrawalRequestResource — {

```
"id","reference","amount","status","payout_method","method_label","admin_notes","screenshot_url","processed_at","created_at" } . screenshot_url is the admin's proof-of-transfer for a bank -method payout once processed (null until then) — same absolute-URL pattern as PaymentResource .
```

DisputeResource — {

```
"id","reference","opened_by_role","reason","status","resolution","resolution_note","resolved_at","created_at","photos" } . status ∈ open | resolved | dismissed (resolution is set by an admin). photos is [{"id","url"}] , only present when loaded (both POST ../dispute and GET /disputes/{id} load it).
```

8. What's intentionally out of scope here

- **Admin panel** — stays web-only; not part of this API.
- **Job seeker (careers/recruitment) flows** — the mobile app is for customers + professionals, not the internal hiring board. The web-only flow (`app/Http/Controllers/JobSeeker/*` , `app/Http/Controllers/Admin/CareerApplicationController.php`) covers: a profile with `skills` stored as a real JSON array (tag/pill UI, not a comma string), an explicit "use my saved resume vs. upload a different one" choice when applying, and a per-application audit trail (`career_application_events` — one row per submit/status-change/note/withdrawal, so admin review history is never overwritten). None of this has an API surface; add one under `/api/job-seeker/*` the same way the consumer/provider routes were mirrored if the app ever needs it.
- **Push notification delivery** — this API stores/reads in-app `Notification` rows (badge counts, notification center), but does not yet register Expo/FCM/APNs device tokens or send pushes. That's a separate small piece of work (a `device_tokens` table + a dispatch step in `Notifier`) worth doing once the app shell exists.
- **Real payment gateways** — JazzCash/Easypaisa drivers exist server-side but are disabled by default (`config/payments.php`); only the `mock` gateway is enabled out of the box, same as the web app.

9. Testing this yourself

```
curl -X POST https://your-domain/api/register \
-H "Accept: application/json" -H "Content-Type: application/json" \
-d '{"name":"Jane","email":"jane@example.com","phone":"+03001234567","role":"consumer","password":"password123","password_confirmation":"password123"}'

# then, using the returned token:
curl https://your-domain/api/me \
```

```
-H "Accept: application/json" -H "Authorization: Bearer <token>"
```

Every endpoint in this document was hit with real requests against a local instance during development (full booking → escrow → completion → wallet release cycle, jobs/bids, emergency accept, contract creation, dispute open, and token revocation on logout all verified working) — including the completion-required-photos flow, the cash/bank-transfer completion-payment flow, the in-progress visit-charge cancellation, dispute photo evidence, and CNIC normalization on onboarding, all added in this pass.