

Sahoulat API Documentation

REST API for the Sahoulat mobile app (customers + professionals). Built on Laravel 12 + Sanctum. All routes are prefixed with `/api`, e.g. `https://your-domain.test/api/login`.

Tested end-to-end against the full booking → escrow payment → completion → wallet payout lifecycle, jobs/bids, emergencies, contracts, and disputes.

1. Conventions

Headers

Every request should send:

```
Accept: application/json
```

Authenticated requests must also send:

```
Authorization: Bearer <token>
```

Requests with a JSON body should send:

```
Content-Type: application/json
```

File upload endpoints (photos, KYC documents) use `multipart/form-data` instead.

Auth model

Token-based via **Laravel Sanctum**. There is no session/CSRF — every device that logs in gets its own long-lived bearer token (`device_name` you send becomes the token's label, so a user can be logged in on multiple devices and revoke them individually).

Roles

A user has exactly one `role`: `consumer`, `provider`, or `job_seeker` (`job_seeker/admin` flows are not covered by this API — it's scoped to the customer + professional apps). Role is fixed at registration and determines which route group (`/api/consumer/*` or `/api/provider/*`) the account can call. Cross-role calls return `403`.

Standard error shapes

401 — missing/invalid/expired token:

```
{ "message": "Unauthenticated." }
```

403 — wrong role, or a policy denied the action:

```
{ "message": "This account type cannot access this resource." }
```

404 — model not found, or (deliberately, for security) hidden because it doesn't belong to you / isn't active.

422 — validation errors (standard Laravel shape):

```
{
  "message": "The email field is required.",
  "errors": { "email": ["The email field is required."] }
}
```

422 is also used for business-rule rejections (e.g. "That time slot is no longer available"), in the simpler `{ "message": "..." }` shape.

409 — race condition (e.g. two providers accepting the same emergency request at once).

Pagination

List endpoints that paginate return:

```
{
  "...collection key...": [ /* items */ ],
  "pagination": { "current_page": 1, "last_page": 3, "total": 42 }
}
```

Money

All amounts are numbers (PKR), not strings, e.g. `"price": 3000` not `"price": "3000.00"`.

2. Auth

POST `/api/register`

Auth: none **Body:**

Field	Type	Notes
name	string	required
email	string	required, unique
phone	string	required — any format accepted; normalized server-side to 03XX-XXXXXXX (see note below)
role	string	required — consumer, provider, or job_seeker
password	string	required, min 8
password_confirmation	string	required, must match password
referral_code	string	optional
device_name	string	required — label for this token, e.g. "iPhone 15"

Pakistani phone numbers are reformatted to 03XX-XXXXXXX on save (a leading +92 / 92 country code is stripped and replaced with a trunk 0 first). The stored/returned value may therefore differ from what was submitted — e.g. +923001234567 or 03001234567 both come back as 0300-1234567. Numbers that aren't 11 digits after stripping non-digits are left as-is.

Response 201 :

```
{
  "user": {
    "id": 22, "name": "Test Consumer", "email": "test@example.com",
    "phone": "0300-1234567", "role": "consumer", "referral_code": "0G1EGG",
    "credit_balance": 0, "is_suspended": false,
    "provider_status": null,
    "created_at": "2026-07-21T12:12:07+00:00"
  },
  "token": "1|dFx1zYRMlAFDEVy2Ba1JMLVvxzDkRPhobybCfHbN4541fa29"
}
```

provider_status is only meaningful when role is provider (mirrors provider_profiles.status : draft → pending → approved / rejected).

POST /api/login

Auth: none **Body:** email , password , device_name (all required) **Response 200 :** same shape as register. **Errors:** 422 if credentials don't match, or if the account is suspended.

POST /api/forgot-password

Auth: none. Rate limited (5/min per email+IP). **Body:** email (required) **Response:** { "message": "We sent a 6-digit code to your email." } Emails a 6-digit OTP (15-minute expiry) via the same password_reset_tokens table and mailable the web app's forgot-password page uses. **Errors:** 422 if no user has that email.

POST /api/reset-password

Auth: none. Rate limited (5/min per email+IP on the route, plus 5 wrong-OTP attempts per email+IP before a 5-minute lockout). **Body:** email , otp (6 digits, from the emailed code), password (required, confirmed, min 8) **Response:** { "message": "Your password has been reset — please log in." } Verifies the OTP, sets the new password, and revokes the reset token (not the user's Sanctum tokens — existing logged-in devices stay logged in). **Errors:** 422 if the OTP is invalid/expired/rate-limited, or the email doesn't match a user.

POST /api/logout

Auth: required — revokes only the token used for this request (this device). **Response:** { "message": "Logged out." }

POST /api/logout-all

Auth: required — revokes every token for the user (all devices). **Response:** { "message": "Logged out of all devices." }

GET /api/me

Auth: required **Response:** { "user": { ...same shape as register... } }

PUT /api/profile

Auth: required **Body:** name (required), email (required, unique except self), phone (optional — normalized to 03XX-XXXXXXX the same way as registration) **Response:** { "user": {...} }

PUT /api/profile/password

Auth: required **Body:** current_password (required, must match), password (required, confirmed, min 8), password_confirmation **Response:** { "message": "Password updated." }

DELETE /api/profile

Auth: required **Body:** password (required, must match current password) **Response:** { "message": "Account deleted." } Anonymizes the user's name/email/phone/avatar, sets a random unusable password, deactivates the account (suspended_at), and revokes all Sanctum tokens. Booking/payment history is preserved (no hard delete) to avoid breaking referential integrity.

3. Shared / public browsing

None of these require auth unless noted.

GET /api/categories

Active categories with their active services (the "browse services" catalog, cached 1h server-side). **Response:**

```
{
  "categories": [
    {
      "id": 1, "name": "AC Repair & Service", "slug": "ac-repair-service",
      "description": "...", "icon": "ac", "image_url": null,
      "services": [
        { "id": 2, "category_id": 1, "name": "AC Gas Refill", "slug": "ac-gas-refill",
          "description": "...", "base_price": 3500, "visit_charge": null,
            "duration_minutes": 90, "is_active": true }
      ]
    }
  ]
}
```

`icon` is either a legacy icon-name key (e.g. "ac" , rendered client-side from a bundled icon set — true for any category that predates icon uploads) or, once a category has an uploaded icon image, the ready-to-use absolute URL for it (e.g. "https://sahoulat.com/storage/categories/xyz.jpg"). Check whether it starts with `http` to tell which case you're in. Same behavior on the nested `category.icon` in `ServiceResource` .

`visit_charge` (nullable) is a fixed, non-negotiable fee some services carry, payable if a provider cancels after inspecting the job in person — separate from and in addition to the service's `base_price` . **Disclose it up front, before booking** — the web app shows it as a prominent callout on the service detail page and a small line on service cards, precisely because it can surprise a customer if they only learn about it after the fact. See `POST /provider/bookings/{id}/status` (`visit_charge_method` / `visit_charge_screenshot`) for how it actually gets collected, and the `visit_charge` object on `BookingResource` for the collected record.

GET /api/services

All active services (flat list, e.g. for search/typeahead). Response: { "services": [{...ServiceResource...}] }

GET /api/services/{slug}

Service detail + approved providers offering it (cheapest first, paginated) + 3 related services. "Approved" here excludes providers currently suspended for unpaid cash-commission debt — they're temporarily not eligible for new bookings until they settle up. **Response:**

```
{
  "service": { "id": 2, "name": "AC Gas Refill", "...": "..." },
  "providers": [
    { "provider_profile_id": 21, "provider": { "...ProviderProfileResource..." }, "price": 3000 }
  ],
  "providers_pagination": { "current_page": 1, "last_page": 1, "total": 1 },
  "related_services": [ {...} ]
}
```

GET /api/providers

Public provider directory — approved and not currently suspended for unpaid cash-commission debt. **Query:** `q` (search name/bio/city/service), `city` (exact match). Both optional. **Response:**

```
{
  "providers": [ {...ProviderProfileResource...} ],
  "pagination": { "current_page": 1, "last_page": 1, "total": 5 },
  "cities": ["Islamabad", "Karachi", "Lahore"]
}
```

GET /api/providers/{id}

One provider's public profile: bio, services offered (with prices), portfolio photos, and latest 10 reviews. **Response:** { "provider": {...}, "reviews": [{ "id":1, "rating":5, "comment":"...", "consumer_name":"...", "service_name":"...", "created_at":"..." }] }

GET /api/providers/{id}/services/{serviceId}/availability

Bookable dates + time slots for a specific provider/service pairing — call this before showing the booking picker. **Query:** `date` (optional, YYYY-MM-DD ; defaults to the first bookable date). **Response:**

```
{
  "price": 3000, "duration_minutes": 90,
  "dates": [
    { "value": "2026-07-21", "label": "Today – 21 Jul" },
    { "value": "2026-07-22", "label": "Wed, 22 Jul" }
  ]
}
```

```
  ],
  "selected_date": "2026-07-21",
  "slots": [
    { "value": "09:00", "label": "9:00 AM", "available": false },
    { "value": "10:00", "label": "10:00 AM", "available": true }
  ]
}
```

GET /api/subscription-plans

Active maintenance/AMC plans. Response: { "plans": [{ "id":1, "name":"...", "slug":"...", "service": {...}, "frequency_months":1, "frequency_label":"Monthly", "total_visits":12, "price_per_visit":2000, "is_active":true }] }

GET /api/cities

Cities currently served (for city pickers / client-side coverage checks). Response: { "cities": ["Islamabad", "Karachi", "Lahore"] }

4. Shared / authenticated (any role)

All require Authorization: Bearer <token> .

GET /api/notifications

Paginated, newest first. Response: { "notifications": [{...}], "unread_count": 3, "pagination": {...} } Each notification: { "id", "type", "title", "body", "url", "is_read", "read_at", "created_at" }

POST /api/notifications/{id}/read

Marks one notification read. Response: { "notification": {...} }

POST /api/notifications/read-all

Response: { "message": "All notifications marked as read." }

GET /api/bookings/{id}/room

Chat history + tracking pin(s) for a booking (both consumer and provider on the booking can call this). **Response:**

```
{
  "is_communicable": true,
  "can_share_location": true,
  "messages": [ { "id":1, "sender_id":22, "sender_name":"Test Consumer", "body":"...", "created_at":"..." } ],
  "latest_tracking": { "id":1, "latitude":24.86, "longitude":67.01, "note":null, "created_at":"..." },
  "tracking_history": [ { "id":1, "latitude":24.86, "longitude":67.01, "note":null, "created_at":"..." }, "...up to the most
recent 500 points, oldest first – draw as a breadcrumb trail" ],
  "destination": { "latitude":24.90, "longitude":67.05, "address":"House 1, Karachi" }
}
```

`destination` is the booking's own address coordinates (`null` if the booking has none) — feed `latest_tracking` as the origin and `destination` as the destination into the Google Directions API client-side to draw the actual driving route + ETA, the same way the web app's booking room does (`google.maps.DirectionsService / DirectionsRenderer`). It's static for the life of the booking, so fetch it once alongside everything else here rather than re-deriving it.

`can_share_location` is `true` only while the booking is `confirmed` — once it flips to `in_progress` the provider has arrived, so there's nothing left to route to and this goes back to `false` . Stop sending tracking pings (and hide the "share my location" control) the moment this flips, rather than only reacting to a 422 from the tracking endpoint.

POST /api/bookings/{id}/messages

Body: `body` (string, required, max 2000) **Response 201 :** { "message_data": {...} } — broadcast in realtime over the existing Reverb/Echo channel for the booking.

POST /api/bookings/{id}/tracking

Post a live location pin (typically the provider en route). **Body:** `latitude` , `longitude` (required), `note` (optional). **Response 201 :** { "tracking": {...} }

POST /api/bookings/{id}/dispute

Body: `reason` (string, required, max 2000), `photos[]` (optional, up to 5 images, 8MB each, multipart) — evidence for the complaint. **Response 201 :** { "dispute": {...} }

GET /api/disputes/{id}

Response: { "dispute": {
"id", "reference", "opened_by_role", "reason", "status", "resolution", "resolution_note", "resolved_at", "created_at", "photos":
[{"id":1, "url":"https://..."}] } }

5. Consumer API (/api/consumer/* , role consumer required)

GET /api/consumer/dashboard

Home-screen summary. Response: { "recent_bookings": [{...BookingResource, up to 5...}] }

Addresses

Method	Path	Body	Notes
GET	/addresses	–	{ "addresses": [...] }
POST	/addresses	label, address, city (required); latitude, longitude, is_default (optional)	201, { "address": {...} }
PUT	/addresses/{id}	same as POST	{ "address": {...} }
DELETE	/addresses/{id}	–	{ "message": "Address removed." }

Address shape: { "id", "label", "address", "city", "latitude", "longitude", "is_default" }

Bookings (direct booking flow)

GET /bookings — paginated, newest first. { "bookings": [...], "pagination": {...} }

POST /bookings — create a direct booking with a specific approved provider.

Field	Required	Notes
provider_profile_id	yes	must be an approved provider
service_id	yes	must be a service that provider actively offers
scheduled_date	yes	one of the values from the availability endpoint
scheduled_time	yes	HH:MM, must be an available slot
address	yes	
latitude, longitude	no	
notes	no	max 1000

Response 201 : { "booking": {...BookingResource...} } . 422 if the provider is outside served cities or the slot just got taken.

GET /bookings/{id} — { "booking": {...} } (full detail incl. payments , review , dispute)

POST /bookings/{id}/cancel — only while cancellable by the consumer (not yet in progress). Auto-refunds escrow if already paid. { "message": "...", "booking": {...} }

GET /bookings/{id}/payment-options — { "gateways": [{ "key": "mock", "label": "Test payment (sandbox)" }, { "key": "cash", "label": "Cash" }, { "key": "bank_transfer", "label": "Bank transfer" }], "max_credit_applicable": 0, "amount": 3000, "company_account": {...} } . mock only ever appears outside production (APP_ENV) or when explicitly forced on via MOCK_PAYMENTS_ENABLED — it must never be reachable on the live site, since it always succeeds instantly with no real money. jazzcash / easypaiza only appear once their env credentials + *ENABLED=true are configured. **cash and bank_transfer are always included** (same reasoning as milestones below) so pre-payment never dead-ends into an empty gateway list when no online gateway is configured. company_account is the same shape as completion-payment-options below — needed for the bank-transfer instructions.

POST /bookings/{id}/pay — Body: gateway (required unless referral credit fully covers the amount — must be one of the keys returned by payment-options above), apply_credit (bool, optional — applies available referral credit first), screenshot (required if gateway=bank_transfer , image, multipart, max 8MB). Response 201 : { "message": "...", "payment": {...} } , or, for gateways needing an off-site redirect: { "status": "pending", "redirect_url": "...", "redirect_fields": {...} } .

gateway=cash here is a commitment, not an instant charge — nothing can really be "prepaid" in cash before the provider has shown up. The payment is recorded pending and only actually settled (commission deducted, invoice emailed) once the job is later marked complete. gateway=bank_transfer behaves like a real gateway: it's recorded pending with the screenshot and, once an admin verifies it, held in escrow (not released) until the job is completed and the consumer calls /release — unlike the completion-payment bank transfer below, which verifies straight to released since the job is already done by then.

POST /bookings/{id}/release — release escrow to the provider once completed & undisputed. { "message": "...", "booking": {...} }

POST /bookings/{id}/review — Body: rating (1–5, required), comment (optional, max 1000). Only once, only after completion. Response 201 : { "review": {...} }

GET /bookings/{id}/completion-payment-options — for bookings that skip pre-payment and only ask for money once the job is actually done (see permissions.needs_completion_payment below, and Booking::needsCompletionPayment()). 404 if this booking isn't one of those. Response:

```
{
  "amount": 1000,
  "methods": ["cash", "bank_transfer"],
  "company_account": {
    "bank_name": "Bank Al Habib Ltd",
    "account_title": "Sahoulat Facility Management Services",
    "account_number": "5052-0081-001208-01-4",
    "iban": "PK15BAHL50520081001208014",
```

```

    "swift_code": "BAHLPKKA",
    "branch_name": "Islamic Midway Commercial \"A\" Bahria Town Karachi",
    "branch_code": "5052",
    "branch_address": "Showroom # 1, SQ Trade Center, Plot A-118 Midway Commercial \"A\" Bahria Town Karachi Pakistan",
    "jazzcash_number": "",
    "easypaisa_number": ""
  }
}

```

This is Sahoulat's own receiving account for a manual bank transfer — display it in full so the customer can copy every field (`iban` / `swift_code` matter for interbank/international transfers). `jazzcash_number` / `easypaisa_number` are currently empty (not yet configured) — omit those rows client-side when blank, same as the web app does.

POST /bookings/{id}/completion-payment — record how a just-completed job got paid. Body: `method` (required, `cash` | `bank_transfer`), `screenshot` (required if `method` is `bank_transfer` , image, multipart, max 8MB). `cash` is recorded immediately (commission is deducted from the provider's wallet automatically) and the customer is emailed a PDF invoice right away. `bank_transfer` needs an admin to verify the screenshot first (web-only step) — the invoice email goes out once that happens. Response `201` : { "message": "...", "payment": {...} }. `422` if this booking isn't awaiting completion payment.

Booking resource shape (used throughout)

```

{
  "id": 1, "reference": "BK-Z6POMA", "status": "confirmed",
  "service": { "...ServiceResource..." },
  "provider": { "...ProviderProfileResource..." },
  "consumer": { "id": 22, "name": "Test Consumer", "phone": "0300-1234567" },
  "scheduled_date": "2026-07-22", "scheduled_time": "10:00",
  "price": 3000, "duration_minutes": 90, "address": "House 1, Karachi",
  "latitude": null, "longitude": null, "notes": null,
  "cancelled_by": null, "cancellation_reason": null,
  "completion_notes": null,
  "confirmed_at": "...", "started_at": null, "completed_at": null, "cancelled_at": null,
  "created_at": "...",
  "before_photos": [ {"id": 1, "url": "https://..."} ],
  "after_photos": [ {"id": 2, "url": "https://..."} ],
  "visit_charge": null,
  "payments": [ {...} ], "review": null, "dispute": null,
  "permissions": {
    "can_cancel": true, "is_payable": true, "needs_completion_payment": false, "is_reviewable": false,
    "is_disputable": false, "is_communicable": true, "can_share_location": false,
    "is_provider": false
  }
}

```

`permissions` tells the app which action buttons to show — always trust this over re-deriving the logic client-side. `before_photos` / `after_photos` are only present when the booking detail endpoint eager-loads them (both consumer and provider `GET /bookings/{id}` do). `visit_charge` is non-null only when a provider cancelled an in-progress booking after collecting the visit charge on inspection (see the provider status endpoint below) — shape: { "amount": `500`, "method": "cash", "screenshot_url": null, "collected_at": "..."} . This money is never part of commission/wallet accounting — it's the provider's directly.

Jobs (post & bid flow)

GET /jobs — { "jobs": [...], "pagination": {...} }

POST /jobs — post a job for open bidding. Multipart if attaching photos.

Field	Required
<code>service_id</code>	yes
<code>description</code>	yes, max 2000
<code>budget</code>	no, numeric
<code>preferred_date</code>	no, date ≥ today
<code>address</code> , <code>city</code>	yes
<code>latitude</code> , <code>longitude</code>	no
<code>photos</code> []	no, up to 5 images, 5MB each

Response `201` : { "job": {...JobPostResource...} }

GET /jobs/{id} — full detail with all bids (each bid includes the bidding provider's profile).

POST /jobs/{id}/cancel — only while `status` = `open` . Rejects any pending bids too.

POST /jobs/{id}/bids/{bidId}/accept — accepts a bid, creates a confirmed `Booking` , rejects all other pending bids on that job, notifies the winning + losing providers. { "message": "...", "booking": {...} } . `422` if the slot clashes with another confirmed booking for that provider, or the proposed time has passed.

JobPost resource shape

```
{
  "id": 1, "reference": "JOB-PZYQ40", "status": "open",
  "service": {...}, "consumer": { "id":22, "name":"..." },
  "description": "...", "budget": null, "preferred_date": null,
  "address": "...", "latitude": null, "longitude": null, "city": "Karachi",
  "photos": [ { "id":1, "url":"https://.../job-photos/1/xyz.jpg" } ],
  "bids_count": 2, "pending_bids_count": 1,
  "bids": [ {...BidResource...} ],
  "my_bid": null,
  "awarded_at": null, "created_at": "..."
}
```

Contracts (multi-service projects, admin-quoted)

GET /contracts — { "contracts": [...], "pagination": {...} }

POST /contracts — submit for a manual admin quote. Multipart if attaching photos.

Field	Required
title, description	yes
preferred_start_date	no
address, city	yes
latitude, longitude	no
photos[]	no, up to 8 images
items[]	yes, min 1 — each: service_id (required), quantity (required, 1–100), notes (optional)

Response 201 : { "contract": {...} } — status starts as `submitted` ; an admin later sets `quoted_total` and per-milestone amounts.

GET /contracts/{id} — full detail incl. `items` , `photos` , `milestones` .

POST /contracts/{id}/accept / **POST /contracts/{id}/reject** — only while `status` = `quoted` .

POST /contracts/{id}/cancel — only while cancellable.

GET /contracts/{id}/milestones/{milestoneId}/payment-options — same shape as booking payment-options, **plus cash and bank_transfer are always included** (unlike bookings, a milestone has no pay-after-completion fallback, so these two are the reliable path while no online gateway is configured). Also includes `company_account` (see the completion-payment shape above) for the bank-transfer instructions. Response:

```
{
  "gateways": [
    {"key": "mock", "label": "Test payment (sandbox)"},
    {"key": "cash", "label": "Cash"},
    {"key": "bank_transfer", "label": "Bank transfer"}
  ],
  "max_credit_applicable": 0,
  "amount": 3000,
  "company_account": { "...": "same shape as the booking completion-payment endpoint" }
}
```

POST /contracts/{id}/milestones/{milestoneId}/pay — Body: `gateway` (required unless credit fully covers it — one of the keys from `payment-options`), `apply_credit` (bool, optional), `screenshot` (required if `gateway=bank_transfer` , image, multipart, max 8MB).

- `gateway=cash` — trusted immediately, no proof required (same as a real gateway success): the payment and milestone both move straight to escrow.
- `gateway=bank_transfer` — the payment stays `pending` until an admin verifies the screenshot in the admin panel; only then does it move to escrow. The consumer isn't blocked from anything in the meantime — this is just slower than cash.
- A real gateway key — unchanged, synchronous success moves straight to escrow (or {`"status":"pending","redirect_url":...`} for an off-site redirect gateway).

Response 201 : { "message": "...", "payment": {...} } in all cases (except the off-site redirect case, same shape as booking `/pay`).

Emergencies (SOS)

GET /emergencies — { "emergencies": [...], "pagination": {...} }

POST /emergencies — broadcasts to nearby approved providers offering that service in that city (realtime + notification).

Field	Required
service_id	yes, must be active and flagged emergency-available — 422 otherwise
address, city	yes
latitude, longitude	no

notes	no
-------	----

Send `latitude` / `longitude` when you have them (e.g. from the map picker) — they carry straight through to the `Booking` once a provider accepts, same as a direct booking's coordinates.

Response 201 : { "emergency": {...} }

GET /emergencies/{id} — includes `matched_provider` and `booking` once accepted, and `quoted_price` once an admin has quoted it.

POST /emergencies/{id}/cancel — while `open` or `quoted` .

POST /emergencies/{id}/accept-quote / **POST /emergencies/{id}/decline-quote** — respond to an admin's price quote (`status` must currently be `quoted` , i.e. `quoted_price` is set). Accepting moves it to `accepted` (admin assigns a provider next); declining moves it to `declined` , a terminal state. 422 if there's no pending quote. Response: { "message": "...", "emergency": {...} }

Subscriptions (maintenance plans)

GET /subscriptions — { "subscriptions": [...], "pagination": {...} }

POST /subscription-plans/{planSlug}/subscribe Body: `address` , `city` (required), `latitude` , `longitude` (optional), `start_date` (required, date ≥ today). Response 201 : { "subscription": {...} } — status starts `pending_assignment` until admin assigns a provider.

GET /subscriptions/{id} — includes `provider` and past `bookings` once active.

POST /subscriptions/{id}/cancel — Body: `reason` (optional). Already-scheduled visits are unaffected.

6. Provider API (/api/provider/* , role provider required)

Most endpoints beyond onboarding require an **approved** `ProviderProfile` — calling them before approval returns empty collections (list endpoints) or a 403 from the `actAsApprovedProvider` gate (action endpoints).

GET /api/provider/dashboard

Home-screen summary: counters, wallet balances, 6-month earnings trend, completion rate, average response time, bid win rate, today's schedule.

```
{
  "profile": {...ProviderProfileResource... or null},
  "pending_bookings": 0, "available_jobs": 2, "open_emergencies": 1,
  "wallet_available": 2700, "wallet_escrow": 0,
  "earnings_month": 2700, "earnings_total": 2700, "earnings_delta": 100,
  "earnings_series": [ {"label":"Feb","value":0}, "...", {"label":"Jul","value":2700} ],
  "jobs_completed": 1, "active_bookings": 1, "completion_rate": 100,
  "response_minutes": 0, "bid_win_rate": 100, "bids_pending": 0,
  "today_schedule": [ {...BookingResource...} ]
}
```

Onboarding / KYC

GET /onboarding — profile + uploaded documents + step progress + what's missing.

```
{
  "profile": {...},
  "documents": [ { "id":1, "type":"cnic_front", "original_name":"...", "download_url":"...", "created_at":"..." } ],
  "document_types": { "cnic_front": {"label":"CNIC – Front","required":true}, "...": "..." },
  "steps": [
    { "label": "Your details", "done": true },
    { "label": "KYC documents", "done": false, "uploaded": 1, "required": 3 },
    { "label": "Review", "done": false, "submitted": false }
  ],
  "missing": ["CNIC – Back", "Selfie holding CNIC"],
  "can_submit": false
}
```

PUT /onboarding — Body: `experience_years` , `city` , `cnic_number` (required); `business_name` , `bio` , `address` , `latitude` , `longitude` (optional). Blocked (422) once submitted/approved. `cnic_number` accepts any format but is normalized and stored as 42101–1234567–8 (13 digits required after stripping non-digits — an unexpected digit count is left as submitted).

POST /onboarding/documents — multipart. Body: `type` (one of the `document_types` keys), `file` (jpg/jpeg/png/pdf, max 4MB). Replaces any existing document of the same type. Response 201 : { "document": {...} }

GET /onboarding/documents/{id} — streams the private file (owner only). Not JSON — returns the raw file.

DELETE /onboarding/documents/{id} — { "message": "Document removed." }

POST /onboarding/submit — moves profile to `pending` for admin review once details + all required documents are present. 422 with a listing of what's missing otherwise.

Services offered

Method	Path	Body	Notes
GET	/services	–	{ "offered": [...], "available": [...], "booking_counts": {...} } — empty until approved
POST	/services	service_id (required, not already offered), price (required)	201, { "provider_service": {...} }
PUT	/services/{id}	price (required), is_active (optional bool)	{ "provider_service": {...} }
DELETE	/services/{id}	–	{ "message": "... " }

Bookings

GET /bookings — **Query:** status (all | pending | confirmed | in_progress | completed | cancelled , default all), q (search reference/address/consumer/service name). Response: { "bookings": [...], "counts": {"all":5,"pending":1,...}, "filter": "all", "pagination": {...} }

GET /bookings/{id} — full detail.

POST /bookings/{id}/status — multipart when completing (photos) or cancelling with a bank-transfer visit charge (screenshot). Valid transitions: pending →(confirm/decline)→ , confirmed →(start/cancel)→ , in_progress →(complete/cancel)→ . Declining/cancelling auto-refunds escrow.

Body field	Required when	Notes
action	always	confirm decline start complete cancel
cancellation_reason	no	max 1000, used for decline/cancel
completion_notes	no	max 1000, used for complete
before_photos[]	no	optional, 0–6 images, 5MB each — proof of work, recommended but not enforced
after_photos[]	no	optional, 0–6 images, 5MB each
visit_charge_method	action=cancel and the booking is currently in_progress	cash bank_transfer — see below
visit_charge_screenshot	same, and visit_charge_method=bank_transfer	image, max 8MB

Two things worth calling out:

- **complete** accepts optional before/after photos and automatically generates an invoice for the booking, emailed to the customer once payment is confirmed.
- **cancel while in_progress** is a distinct scenario from cancelling a confirmed (not-yet-visited) booking: it means the provider inspected the job on-site and the customer decided not to proceed. In that case visit_charge_method is required — it records the provider's visit charge as collected (see visit_charge on the booking resource above) entirely outside commission/wallet accounting. Cancelling a confirmed booking (before any visit happened) does **not** need these fields.

Response: { "message": "...", "booking": {...} }

Jobs & bids

GET /jobs — open jobs matching services this provider offers; each job includes my_bid (null if not yet bid).

GET /jobs/{id} — { "job": {...}, "offers_service": true, "slot_options": [{"value":"09:00","label":"9:00 AM"}, ...] }

POST /jobs/{id}/bids — Body: amount (required, numeric), proposed_date (required, ≥ today), proposed_time (required, one of slot_options), message (optional). One bid per provider per job. Response 201 : { "bid": {...} }

GET /bids — **Query:** status (all | pending | accepted | rejected | withdrawn). Response: { "bids": [...], "counts": {...}, "win_rate": 100, "pipeline": 2800 } (pipeline = sum of pending bid amounts).

PUT /bids/{id} — same body as create; only while pending and the job is still open.

DELETE /bids/{id} — withdraws a pending bid.

Emergencies

GET /emergencies — open requests in the provider's city for services they offer; each includes my_price (this provider's price for that service).

POST /emergencies/{id}/accept — first to accept wins; creates a confirmed booking immediately. 409 if another provider already claimed it.

Wallet & payouts

GET /wallet — **Query:** bucket (all | available | escrow). Balances, lifetime/monthly earnings, 6-month trend, ledger entries, and recent withdrawal requests.

```
{
  "wallet": { "id":1, "available_balance": 2700, "escrow_balance": 0 },
  "total_earned": 2700, "earned_this_month": 2700,
  "earnings_series": [ {"label":"Feb","value":0}, "... " ],
  "ledger": {
```

```

    "bucket": "all", "counts": {"all":3,"available":1,"escrow":2},
    "entries": [ { "id":3, "bucket":"available", "type":"...", "amount":2700, "description":"...", "booking_reference":"BK-
Z6POMA", "created_at":"..." } ],
    "pagination": {...}
  },
  "min_withdrawal": 500,
  "withdrawal_requests": [ { "id":1, "reference":"WD-...", "amount":2700, "status":"pending", "payout_method":"jazzcash",
"method_label":"JazzCash", "admin_notes":null, "processed_at":null, "created_at":"..." } ]
}

```

POST /payout-method — Body: payout_method (bank | jazzcash | easypaisa , required), payout_account_title , payout_account_number (required), payout_bank_name (required only if payout_method = bank). Response: { "profile": {...} }

POST /withdrawals — Body: amount (required, $\geq$ min_withdrawal , $\leq$ current available balance). Requires a payout method already saved. Response 201 : { "message": "...", "withdrawal": {...} }

POST /withdrawals/{id}/confirm-receipt — two-party confirmation: after an admin marks a bank-transfer withdrawal awaiting_confirmation (sent, pending the provider's acknowledgement), the provider confirms they actually received it, flipping it to paid . 422 if the withdrawal isn't currently awaiting_confirmation . Response: { "message": "...", "withdrawal": {...} }

Settlements (paying off cash-commission debt)

For cash-collected bookings, commission is never deducted at source — it posts as a negative available_balance instead (see WalletService::chargeCashCommission()). A provider carrying this debt past settlement_grace_days (7 days by default) gets auto-suspended from accepting new bookings until it's settled.

GET /settlements — how much is currently owed + past settlement submissions.

```

{
  "owed": 500,
  "is_suspended": false,
  "settlements": [
    { "id":1, "reference":"STL-...", "method":"bank_transfer", "method_label":"Bank transfer",
      "amount": 500, "confirmed_amount": null, "status":"pending", "admin_notes": null,
      "confirmed_at": null, "created_at": "..." }
  ],
  "pagination": { "current_page": 1, "last_page": 1, "total": 1 }
}

```

status $\in$ pending | confirmed | rejected . Submitting a settlement doesn't touch the wallet or lift the suspension by itself — only an admin confirming the amount actually received does (which also auto-unsuspends the provider once available_balance ≥ 0 again).

POST /settlements — Body: method (cash | bank_transfer , required), amount (required, $\leq$ owed), screenshot (required if method is bank_transfer , image, multipart, max 8MB). 422 if nothing is currently owed. Response 201 : { "message": "...", "settlement": {...} }

Portfolio

Method	Path	Body	Notes
GET	/portfolio	–	{ "photos": [...] }
POST	/portfolio	multipart: photos[] (images, up to remaining slots under a 12-photo cap), caption (optional)	201, { "photos": [...just the new ones...] }
DELETE	/portfolio/{photoId}	–	{ "message": "Photo removed." }

7. Resource reference

Quick field reference for nested objects that recur throughout the API.

ProviderProfileResource

```

{
  "id": 21, "user_id": 23, "name": "Test Pro", "avatar_url": null, "business_name": null,
  "display_name": "Test Pro", "bio": null, "experience_years": 5,
  "rating_avg": 5.0, "reviews_count": 1, "city": "Karachi", "address": null,
  "latitude": null, "longitude": null, "status": "approved", "rejection_reason": null,
  "has_payout_method": true,
  "services": [ {...ProviderServiceResource, when loaded...} ],
  "portfolio": [ {...ProviderPortfolioPhotoResource, when loaded...} ]
}

```

status $\in$ draft | pending | approved | rejected .

ServiceResource — { "id","category_id","category":{...or omitted},"name","slug","description","base_price","duration_minutes","is_active" }

BidResource — { "id","job_post_id","job_post":{...summary...},"provider": {...ProviderProfileResource...},"amount","proposed_date","proposed_time","message","status","booking_id","created_at" } . status $\in$

pending | accepted | rejected | withdrawn .

ContractResource — {
"id", "reference", "title", "description", "address", "latitude", "longitude", "city", "preferred_start_date", "status", "quoted_total", "items"
[...ContractItemResource...], "photos": [...], "milestones": [...ContractMilestoneResource...], "permissions":
{ "is_quoted", "is_accepted", "is_cancellable" }, "accepted_at", "completed_at", "cancelled_at", "created_at" } . status ∈ submitted |
quoted | accepted | rejected | in_progress | completed | cancelled .

EmergencyRequestResource — {
"id", "reference", "status", "service", "consumer", "address", "latitude", "longitude", "city", "notes", "quoted_price", "quoted_at", "accepted_at",
"declined_at", "matched_at", "cancelled_at" } . latitude / longitude are nullable. status ∈ open | quoted | accepted | declined | matched | cancelled (an admin sets quoted_price and
moves it to quoted ; the consumer then accepts/declines). my_price only populated on the provider board endpoint.

SubscriptionResource — {
"id", "reference", "status", "plan", "provider", "address", "city", "next_visit_date", "visits_used", "is_cancellable", "bookings", "cancelled_at",
"created_at" } . status ∈ pending_assignment | active | cancelled | completed .

PaymentResource — {
"id", "reference", "gateway", "amount", "credit_applied", "status", "screenshot_url", "paid_at", "released_at", "refunded_at" } . status ∈
pending | escrow | released | refunded | failed . screenshot_url is only non-null for gateway=bank_transfer payments — the consumer's own
uploaded transfer proof, absolute URL ready to display/download.

WithdrawalRequestResource — {
"id", "reference", "amount", "status", "payout_method", "method_label", "admin_notes", "screenshot_url", "processed_at", "created_at" } .
screenshot_url is the admin's proof-of-transfer for a bank -method payout once processed (null until then) — same absolute-URL pattern as
PaymentResource .

DisputeResource — {
"id", "reference", "opened_by_role", "reason", "status", "resolution", "resolution_note", "resolved_at", "created_at", "photos" } . status ∈
open | resolved | dismissed (resolution is set by an admin). photos is [{"id", "url"}] , only present when loaded (both POST .../dispute and
GET /disputes/{id} load it).

8. What's intentionally out of scope here

- **Admin panel** — stays web-only; not part of this API.
- **Job seeker (careers/recruitment) flows** — the mobile app is for customers + professionals, not the internal hiring board.
- **Corporate/B2B accounts, referrals dashboard** — not wired into this API pass; can be added the same way (they already have web controllers to mirror) if the app needs them later.
- **Push notification delivery** — this API stores/reads in-app Notification rows (badge counts, notification center), but does not yet register Expo/FCM/APNs device tokens or send pushes. That's a separate small piece of work (a device_tokens table + a dispatch step in Notifier) worth doing once the app shell exists.
- **Real payment gateways** — JazzCash/Easypaisa drivers exist server-side but are disabled by default (config/payments.php); only the mock gateway is enabled out of the box, same as the web app.

9. Testing this yourself

```
curl -X POST https://your-domain/api/register \  
-H "Accept: application/json" -H "Content-Type: application/json" \  
-d \  
'{"name":"Jane","email":"jane@example.com","phone":"+919876543210","role":"consumer","password":"password123","password_confirmation":"password123"}' \  
# then, using the returned token: \  
curl https://your-domain/api/me \  
-H "Accept: application/json" -H "Authorization: Bearer <token>"
```

Every endpoint in this document was hit with real requests against a local instance during development (full booking → escrow → completion → wallet release cycle, jobs/bids, emergency accept, contract creation, dispute open, and token revocation on logout all verified working) — including the completion-required-photos flow, the cash/bank-transfer completion-payment flow, the in-progress visit-charge cancellation, dispute photo evidence, and CNIC normalization on onboarding, all added in this pass.