

Sahoulat API Documentation

REST API for the Sahoulat mobile app (customers + professionals). Built on Laravel 12 + Sanctum. All routes are prefixed with `/api`, e.g. `https://your-domain.test/api/login`.

Tested end-to-end against the full booking → escrow payment → completion → wallet payout lifecycle, jobs/bids, emergencies, contracts, and disputes.

1. Conventions

Headers

Every request should send:

```
Accept: application/json
```

Authenticated requests must also send:

```
Authorization: Bearer <token>
```

Requests with a JSON body should send:

```
Content-Type: application/json
```

File upload endpoints (photos, KYC documents) use `multipart/form-data` instead.

Auth model

Token-based via **Laravel Sanctum**. There is no session/CSRF — every device that logs in gets its own long-lived bearer token (`device_name` you send becomes the token's label, so a user can be logged in on multiple devices and revoke them individually).

Roles

A user has exactly one `role`: `consumer`, `provider`, or `job_seeker` (`job_seeker/admin` flows are not covered by this API — it's scoped to the customer + professional apps). Role is fixed at registration and determines which route group (`/api/consumer/*` or `/api/provider/*`) the account can call. Cross-role calls return `403`.

Standard error shapes

401 — missing/invalid/expired token:

```
{ "message": "Unauthenticated." }
```

403 — wrong role, or a policy denied the action:

```
{ "message": "This account type cannot access this resource." }
```

404 — model not found, or (deliberately, for security) hidden because it doesn't belong to you / isn't active.

422 — validation errors (standard Laravel shape):

```
{
  "message": "The email field is required.",
  "errors": { "email": ["The email field is required."] }
}
```

422 is also used for business-rule rejections (e.g. "That time slot is no longer available"), in the simpler `{ "message": "..." }` shape.

409 — race condition (e.g. two providers accepting the same emergency request at once).

Pagination

List endpoints that paginate return:

```
{
  "...collection key...": [ /* items */ ],
  "pagination": { "current_page": 1, "last_page": 3, "total": 42 }
}
```

Money

All amounts are numbers (PKR), not strings, e.g. `"price": 3000` not `"price": "3000.00"`.

2. Auth

POST `/api/register`

Auth: none **Body:**

Field	Type	Notes
name	string	required
email	string	required, unique
phone	string	required — any format accepted; normalized server-side to 03XX-XXXXXX (see note below)
role	string	required — consumer, provider, or job_seeker
password	string	required, min 8
password_confirmation	string	required, must match password
referral_code	string	optional
device_name	string	required — label for this token, e.g. "iPhone 15"

Pakistani phone numbers are reformatted to 03XX-XXXXXX on save (a leading +92 / 92 country code is stripped and replaced with a trunk 0 first). The stored/returned value may therefore differ from what was submitted — e.g. +923001234567 or 03001234567 both come back as 0300-1234567. Numbers that aren't 11 digits after stripping non-digits are left as-is.

Response 201 :

```
{
  "user": {
    "id": 22, "name": "Test Consumer", "email": "test@example.com",
    "phone": "0300-1234567", "role": "consumer", "referral_code": "0G1EGG",
    "credit_balance": 0, "is_suspended": false,
    "provider_status": null,
    "created_at": "2026-07-21T12:12:07+00:00"
  },
  "token": "1|dFx1zYRMlAFDEvy2Ba1JMLVvxzDkRPhobybCfHbN4541fa29"
}
```

provider_status is only meaningful when role is provider (mirrors provider_profiles.status : draft → pending → approved / rejected).

POST /api/login

Auth: none **Body:** email , password , device_name (all required) **Response 200 :** same shape as register. **Errors:** 422 if credentials don't match, or if the account is suspended.

POST /api/forgot-password

Auth: none. Rate limited (5/min per email+IP). **Body:** email (required) **Response:** { "message": "We sent a 6-digit code to your email." } Emails a 6-digit OTP (15-minute expiry) via the same password_reset_tokens table and mailable the web app's forgot-password page uses. **Errors:** 422 if no user has that email.

POST /api/reset-password

Auth: none. Rate limited (5/min per email+IP on the route, plus 5 wrong-OTP attempts per email+IP before a 5-minute lockout). **Body:** email , otp (6 digits, from the emailed code), password (required, confirmed, min 8) **Response:** { "message": "Your password has been reset — please log in." } Verifies the OTP, sets the new password, and revokes the reset token (not the user's Sanctum tokens — existing logged-in devices stay logged in). **Errors:** 422 if the OTP is invalid/expired/rate-limited, or the email doesn't match a user.

POST /api/logout

Auth: required — revokes only the token used for this request (this device). **Response:** { "message": "Logged out." }

POST /api/logout-all

Auth: required — revokes every token for the user (all devices). **Response:** { "message": "Logged out of all devices." }

GET /api/me

Auth: required **Response:** { "user": { ...same shape as register... } }

PUT /api/profile

Auth: required **Body:** name (required), email (required, unique except self), phone (optional — normalized to 03XX-XXXXXX the same way as registration) **Response:** { "user": {...} }

PUT /api/profile/password

Auth: required **Body:** current_password (required, must match), password (required, confirmed, min 8), password_confirmation **Response:** { "message": "Password updated." }

DELETE /api/profile

Auth: required **Body:** password (required, must match current password) **Response:** { "message": "Account deleted." } Anonymizes the user's name/email/phone/avatar, sets a random unusable password, deactivates the account (suspended_at), and revokes all Sanctum tokens. Booking/payment history is preserved (no hard delete) to avoid breaking referential integrity.

3. Shared / public browsing

None of these require auth unless noted.

GET /api/categories

Active categories with their active services (the "browse services" catalog, cached 1h server-side). **Response:**

```
{
  "categories": [
    {
      "id": 1, "name": "AC Repair & Service", "slug": "ac-repair-service",
      "description": "...", "icon": "ac", "image_url": null,
      "services": [
        { "id": 2, "category_id": 1, "name": "AC Gas Refill", "slug": "ac-gas-refill",
          "description": "...", "base_price": 3500,
          "duration_minutes": 90, "is_active": true }
      ]
    }
  ]
}
```

`icon` is either a legacy icon-name key (e.g. `"ac"` , rendered client-side from a bundled icon set — true for any category that predates icon uploads) or, once a category has an uploaded icon image, the ready-to-use absolute URL for it (e.g. `"https://sahoulat.com/storage/categories/xyz.jpg"`). Check whether it starts with `http` to tell which case you're in. Same behavior on the nested `category.icon` in `ServiceResource` .

GET /api/services

All active services (flat list, e.g. for search/typeahead). Response: `{ "services": [ {...ServiceResource...} ] }`

GET /api/services/{slug}

Service detail + approved providers offering it (cheapest first, paginated) + 3 related services. "Approved" here excludes providers currently suspended for unpaid cash-commission debt — they're temporarily not eligible for new bookings until they settle up. **Response:**

```
{
  "service": { "id": 2, "name": "AC Gas Refill", "...": "..." },
  "providers": [
    { "provider_profile_id": 21, "provider": { "...ProviderProfileResource..." }, "price": 3000 }
  ],
  "providers_pagination": { "current_page": 1, "last_page": 1, "total": 1 },
  "related_services": [ {...} ]
}
```

GET /api/providers

Public provider directory — approved and not currently suspended for unpaid cash-commission debt. **Query:** `q` (search name/bio/city/service), `city` (exact match). Both optional. **Response:**

```
{
  "providers": [ {...ProviderProfileResource...} ],
  "pagination": { "current_page": 1, "last_page": 1, "total": 5 },
  "cities": ["Islamabad", "Karachi", "Lahore"]
}
```

GET /api/providers/{id}

One provider's public profile: bio, services offered (with prices), portfolio photos, and latest 10 reviews. **Response:** `{ "provider": {...}, "reviews": [ { "id":1, "rating":5, "comment":"...", "consumer_name":"...", "service_name":"...", "created_at":"..." } ] }`

GET /api/providers/{id}/services/{serviceId}/availability

Bookable dates + time slots for a specific provider/service pairing — call this before showing the booking picker. **Query:** `date` (optional, YYYY-MM-DD ; defaults to the first bookable date). **Response:**

```
{
  "price": 3000, "duration_minutes": 90,
  "dates": [
    { "value": "2026-07-21", "label": "Today - 21 Jul" },
    { "value": "2026-07-22", "label": "Wed, 22 Jul" }
  ],
  "selected_date": "2026-07-21",
  "slots": [
    { "value": "09:00", "label": "9:00 AM", "available": false },
    { "value": "10:00", "label": "10:00 AM", "available": true }
  ]
}
```

```
}
}
```

GET /api/subscription-plans

Active maintenance/AMC plans. Response: { "plans": [{ "id":1, "name":"...", "slug":"...", "service": {...}, "frequency_months":1, "frequency_label":"Monthly", "total_visits":12, "price_per_visit":2000, "is_active":true }] }

GET /api/cities

Cities currently served (for city pickers / client-side coverage checks). Response: { "cities": ["Islamabad", "Karachi", "Lahore"] }

4. Shared / authenticated (any role)

All require Authorization: Bearer <token> .

GET /api/notifications

Paginated, newest first. Response: { "notifications": [{...}], "unread_count": 3, "pagination": {...} } Each notification: { "id", "type", "title", "body", "url", "is_read", "read_at", "created_at" }

POST /api/notifications/{id}/read

Marks one notification read. Response: { "notification": {...} }

POST /api/notifications/read-all

Response: { "message": "All notifications marked as read." }

GET /api/bookings/{id}/room

Chat history + tracking pin(s) for a booking (both consumer and provider on the booking can call this). **Response:**

```
{
  "is_communicable": true,
  "can_share_location": true,
  "messages": [ { "id":1, "sender_id":22, "sender_name":"Test Consumer", "body":"...", "created_at":"..." } ],
  "latest_tracking": { "id":1, "latitude":24.86, "longitude":67.01, "note":null, "created_at":"..." },
  "tracking_history": [ { "id":1, "latitude":24.86, "longitude":67.01, "note":null, "created_at":"..." }, "...up to the most
recent 500 points, oldest first – draw as a breadcrumb trail" ],
  "destination": { "latitude":24.90, "longitude":67.05, "address":"House 1, Karachi" }
}
```

`destination` is the booking's own address coordinates (`null` if the booking has none) — feed `latest_tracking` as the origin and `destination` as the destination into the Google Directions API client-side to draw the actual driving route + ETA, the same way the web app's booking room does (`google.maps.DirectionsService` / `DirectionsRenderer`). It's static for the life of the booking, so fetch it once alongside everything else here rather than re-deriving it.

POST /api/bookings/{id}/messages

Body: `body` (string, required, max 2000) **Response 201 :** { "message_data": {...} } — broadcast in realtime over the existing Reverb/Echo channel for the booking.

POST /api/bookings/{id}/tracking

Post a live location pin (typically the provider en route). **Body:** `latitude` , `longitude` (required), `note` (optional). **Response 201 :** { "tracking": {...} }

POST /api/bookings/{id}/dispute

Body: `reason` (string, required, max 2000), `photos[]` (optional, up to 5 images, 8MB each, multipart) — evidence for the complaint. **Response 201 :** { "dispute": {...} }

GET /api/disputes/{id}

Response: { "dispute": {
"id", "reference", "opened_by_role", "reason", "status", "resolution", "resolution_note", "resolved_at", "created_at", "photos":
[{"id":1, "url":"https://..."}] } }

5. Consumer API (/api/consumer/* , role consumer required)

GET /api/consumer/dashboard

Home-screen summary. Response: { "recent_bookings": [{...BookingResource, up to 5...}] }

Addresses

Method	Path	Body	Notes
--------	------	------	-------

GET	/addresses	–	{ "addresses": [...] }
POST	/addresses	label, address, city (required); latitude, longitude, is_default (optional)	201, { "address": {...} }
PUT	/addresses/{id}	same as POST	{ "address": {...} }
DELETE	/addresses/{id}	–	{ "message": "Address removed." }

Address shape: { "id", "label", "address", "city", "latitude", "longitude", "is_default" }

Bookings (direct booking flow)

GET /bookings — paginated, newest first. { "bookings": [...], "pagination": {...} }

POST /bookings — create a direct booking with a specific approved provider.

Field	Required	Notes
provider_profile_id	yes	must be an approved provider
service_id	yes	must be a service that provider actively offers
scheduled_date	yes	one of the values from the availability endpoint
scheduled_time	yes	HH:MM, must be an available slot
address	yes	
latitude, longitude	no	
notes	no	max 1000

Response 201 : { "booking": {...BookingResource...} } . 422 if the provider is outside served cities or the slot just got taken.

GET /bookings/{id} — { "booking": {...} } (full detail incl. payments , review , dispute)

POST /bookings/{id}/cancel — only while cancellable by the consumer (not yet in progress). Auto-refunds escrow if already paid. { "message": "...", "booking": {...} }

GET /bookings/{id}/payment-options — { "gateways": [{"key":"mock","label":"Test payment (sandbox)"}], "max_credit_applicable": 0, "amount": 3000 }

POST /bookings/{id}/pay — Body: gateway (required unless referral credit fully covers the amount — currently only "mock" is enabled by default; jazzcash / easypaisa activate via env config), apply_credit (bool, optional — applies available referral credit first). Response 201 : { "message": "...", "payment": {...} }, or, for gateways needing an off-site redirect: { "status": "pending", "redirect_url": "...", "redirect_fields": {...} } .

POST /bookings/{id}/release — release escrow to the provider once completed & undisputed. { "message": "...", "booking": {...} }

POST /bookings/{id}/review — Body: rating (1–5, required), comment (optional, max 1000). Only once, only after completion. Response 201 : { "review": {...} }

GET /bookings/{id}/completion-payment-options — for bookings that skip pre-payment and only ask for money once the job is actually done (see permissions.needs_completion_payment below, and Booking::needsCompletionPayment()). 404 if this booking isn't one of those. Response:

```
{
  "amount": 1000,
  "methods": ["cash", "bank_transfer"],
  "company_account": {
    "bank_name": "Bank Al Habib Ltd",
    "account_title": "Sahoulat Facility Management Services",
    "account_number": "5052-0081-001208-01-4",
    "iban": "PK15BAHL50520081001208014",
    "swift_code": "BAHLPKKA",
    "branch_name": "Islamic Midway Commercial \"A\" Bahria Town Karachi",
    "branch_code": "5052",
    "branch_address": "Showroom # 1, SQ Trade Center, Plot A-118 Midway Commercial \"A\" Bahria Town Karachi Pakistan",
    "jazzcash_number": "",
    "easypaisa_number": ""
  }
}
```

This is Sahoulat's own receiving account for a manual bank transfer — display it in full so the customer can copy every field (iban / swift_code matter for interbank/international transfers). jazzcash_number / easypaisa_number are currently empty (not yet configured) — omit those rows client-side when blank, same as the web app does.

POST /bookings/{id}/completion-payment — record how a just-completed job got paid. Body: method (required, cash | bank_transfer), screenshot (required if method is bank_transfer , image, multipart, max 8MB). cash is recorded immediately (commission is deducted from the provider's wallet automatically) and the customer is emailed a PDF invoice right away. bank_transfer needs an admin to verify the screenshot first (web-only step) — the invoice email goes out once that happens. Response 201 : { "message": "...", "payment": {...} } . 422 if this booking isn't awaiting completion payment.

Booking resource shape (used throughout)

```
{
  "id": 1, "reference": "BK-Z6POMA", "status": "confirmed",
  "service": { "...ServiceResource..." },
  "provider": { "...ProviderProfileResource..." },
  "consumer": { "id": 22, "name": "Test Consumer", "phone": "0300-1234567" },
  "scheduled_date": "2026-07-22", "scheduled_time": "10:00",
  "price": 3000, "duration_minutes": 90, "address": "House 1, Karachi",
  "latitude": null, "longitude": null, "notes": null,
  "cancelled_by": null, "cancellation_reason": null,
  "completion_notes": null,
  "confirmed_at": "...", "started_at": null, "completed_at": null, "cancelled_at": null,
  "created_at": "...",
  "before_photos": [ { "id": 1, "url": "https://..." } ],
  "after_photos": [ { "id": 2, "url": "https://..." } ],
  "visit_charge": null,
  "payments": [ {...} ], "review": null, "dispute": null,
  "permissions": {
    "can_cancel": true, "is_payable": true, "needs_completion_payment": false, "is_reviewable": false,
    "is_disputable": false, "is_communicable": true, "can_share_location": false,
    "is_provider": false
  }
}
```

`permissions` tells the app which action buttons to show — always trust this over re-deriving the logic client-side. `before_photos` / `after_photos` are only present when the booking detail endpoint eager-loads them (both consumer and provider `GET /bookings/{id}` do). `visit_charge` is non-null only when a provider cancelled an in-progress booking after collecting the visit charge on inspection (see the provider status endpoint below) — shape: `{ "amount": 500, "method": "cash", "screenshot_url": null, "collected_at": "..." }`. This money is never part of commission/wallet accounting — it's the provider's directly.

Jobs (post & bid flow)

`GET /jobs` — `{ "jobs": [...], "pagination": {...} }`

`POST /jobs` — post a job for open bidding. Multipart if attaching photos.

Field	Required
service_id	yes
description	yes, max 2000
budget	no, numeric
preferred_date	no, date ≥ today
address, city	yes
latitude, longitude	no
photos[]	no, up to 5 images, 5MB each

Response 201 : `{ "job": {...JobPostResource...} }`

`GET /jobs/{id}` — full detail with all bids (each bid includes the bidding provider's profile).

`POST /jobs/{id}/cancel` — only while `status = open`. Rejects any pending bids too.

`POST /jobs/{id}/bids/{bidId}/accept` — accepts a bid, creates a confirmed `Booking`, rejects all other pending bids on that job, notifies the winning + losing providers. `{ "message": "...", "booking": {...} }`. 422 if the slot clashes with another confirmed booking for that provider, or the proposed time has passed.

JobPost resource shape

```
{
  "id": 1, "reference": "JOB-PZYQ40", "status": "open",
  "service": {...}, "consumer": { "id": 22, "name": "..." },
  "description": "...", "budget": null, "preferred_date": null,
  "address": "...", "latitude": null, "longitude": null, "city": "Karachi",
  "photos": [ { "id": 1, "url": "https://.../job-photos/1/xyz.jpg" } ],
  "bids_count": 2, "pending_bids_count": 1,
  "bids": [ {...BidResource...} ],
  "my_bid": null,
  "awarded_at": null, "created_at": "..."
}
```

Contracts (multi-service projects, admin-quoted)

GET /contracts — { "contracts": [...], "pagination": {...} }

POST /contracts — submit for a manual admin quote. Multipart if attaching photos.

Field	Required
title, description	yes
preferred_start_date	no
address, city	yes
latitude, longitude	no
photos[]	no, up to 8 images
items[]	yes, min 1 — each: service_id (required), quantity (required, 1–100), notes (optional)

Response 201 : { "contract": {...} } — status starts as `submitted` ; an admin later sets `quoted_total` and per-milestone amounts.

GET /contracts/{id} — full detail incl. `items` , `photos` , `milestones` .

POST /contracts/{id}/accept / **POST /contracts/{id}/reject** — only while `status` = `quoted` .

POST /contracts/{id}/cancel — only while cancellable.

GET /contracts/{id}/milestones/{milestoneId}/payment-options — same shape as booking `payment-options`.

POST /contracts/{id}/milestones/{milestoneId}/pay — same body/response shape as booking `/pay` .

Emergencies (SOS)

GET /emergencies — { "emergencies": [...], "pagination": {...} }

POST /emergencies — broadcasts to nearby approved providers offering that service in that city (realtime + notification).

Field	Required
service_id	yes, must be active
address, city	yes
notes	no

Response 201 : { "emergency": {...} }

GET /emergencies/{id} — includes `matched_provider` and `booking` once accepted.

POST /emergencies/{id}/cancel — only while still `open` .

Subscriptions (maintenance plans)

GET /subscriptions — { "subscriptions": [...], "pagination": {...} }

POST /subscription-plans/{planSlug}/subscribe Body: `address` , `city` (required), `latitude` , `longitude` (optional), `start_date` (required, date ≥ today). Response 201 : { "subscription": {...} } — status starts `pending_assignment` until admin assigns a provider.

GET /subscriptions/{id} — includes `provider` and past `bookings` once active.

POST /subscriptions/{id}/cancel — Body: `reason` (optional). Already-scheduled visits are unaffected.

6. Provider API (/api/provider/* , role provider required)

Most endpoints beyond onboarding require an **approved** `ProviderProfile` — calling them before approval returns empty collections (list endpoints) or a 403 from the `actAsApprovedProvider` gate (action endpoints).

GET /api/provider/dashboard

Home-screen summary: counters, wallet balances, 6-month earnings trend, completion rate, average response time, bid win rate, today's schedule.

```
{
  "profile": {...ProviderProfileResource... or null},
  "pending_bookings": 0, "available_jobs": 2, "open_emergencies": 1,
  "wallet_available": 2700, "wallet_escrow": 0,
  "earnings_month": 2700, "earnings_total": 2700, "earnings_delta": 100,
  "earnings_series": [ { "label": "Feb", "value": 0 }, "...", { "label": "Jul", "value": 2700 } ],
  "jobs_completed": 1, "active_bookings": 1, "completion_rate": 100,
  "response_minutes": 0, "bid_win_rate": 100, "bids_pending": 0,
  "today_schedule": [ {...BookingResource...} ]
}
```

Onboarding / KYC

GET /onboarding — profile + uploaded documents + step progress + what's missing.

```
{
  "profile": {...},
  "documents": [ { "id":1, "type":"cnic_front", "original_name":"...", "download_url":"...", "created_at":"..." } ],
  "document_types": { "cnic_front": { "label":"CNIC – Front","required":true}, "...": "..." },
  "steps": [
    { "label": "Your details", "done": true },
    { "label": "KYC documents", "done": false, "uploaded": 1, "required": 3 },
    { "label": "Review", "done": false, "submitted": false }
  ],
  "missing": ["CNIC – Back", "Selfie holding CNIC"],
  "can_submit": false
}
```

PUT /onboarding — Body: experience_years, city, cnic_number (required); business_name, bio, address, latitude, longitude (optional). Blocked (422) once submitted/approved. cnic_number accepts any format but is normalized and stored as 42101-1234567-8 (13 digits required after stripping non-digits — an unexpected digit count is left as submitted).

POST /onboarding/documents — multipart. Body: type (one of the document_types keys), file (jpg/jpeg/png/pdf, max 4MB). Replaces any existing document of the same type. Response 201 : { "document": {...} }

GET /onboarding/documents/{id} — streams the private file (owner only). Not JSON — returns the raw file.

DELETE /onboarding/documents/{id} — { "message": "Document removed." }

POST /onboarding/submit — moves profile to pending for admin review once details + all required documents are present. 422 with a listing of what's missing otherwise.

Services offered

Method	Path	Body	Notes
GET	/services	–	{ "offered": [...], "available": [...], "booking_counts": {...} } — empty until approved
POST	/services	service_id (required, not already offered), price (required)	201, { "provider_service": {...} }
PUT	/services/{id}	price (required), is_active (optional bool)	{ "provider_service": {...} }
DELETE	/services/{id}	–	{ "message": "..." }

Bookings

GET /bookings — **Query:** status (all | pending | confirmed | in_progress | completed | cancelled , default all), q (search reference/address/consumer/service name). Response: { "bookings": [...], "counts": { "all":5,"pending":1,...}, "filter": "all", "pagination": {...} }

GET /bookings/{id} — full detail.

POST /bookings/{id}/status — multipart when completing (photos) or cancelling with a bank-transfer visit charge (screenshot). Valid transitions: pending →(confirm/decline)→, confirmed →(start/cancel)→, in_progress →(complete/cancel)→. Declining/cancelling auto-refunds escrow.

Body field	Required when	Notes
action	always	confirm decline start complete cancel
cancellation_reason	no	max 1000, used for decline/cancel
completion_notes	no	max 1000, used for complete
before_photos[]	action=complete	required , 1–6 images, 5MB each — proof of work
after_photos[]	action=complete	required , 1–6 images, 5MB each
visit_charge_method	action=cancel and the booking is currently in_progress	cash bank_transfer — see below
visit_charge_screenshot	same, and visit_charge_method=bank_transfer	image, max 8MB

Two things worth calling out:

- **complete now requires before/after photos** (it didn't before) and automatically generates an invoice for the booking, emailed to the customer once payment is confirmed.
- **cancel while in_progress** is a distinct scenario from cancelling a confirmed (not-yet-visited) booking: it means the provider inspected the job on-site and the customer decided not to proceed. In that case visit_charge_method is required — it records the provider's visit charge as collected (see visit_charge on the booking resource above) entirely outside commission/wallet accounting. Cancelling a confirmed booking (before any visit happened) does **not** need these fields.

Response: { "message": "...", "booking": {...} }

Jobs & bids

GET /jobs — open jobs matching services this provider offers; each job includes my_bid (null if not yet bid).

GET /jobs/{id} — { "job": {...}, "offers_service": true, "slot_options": [{"value": "09:00", "label": "9:00 AM"}, ...] }

POST /jobs/{id}/bids — Body: amount (required, numeric), proposed_date (required, ≥ today), proposed_time (required, one of slot_options), message (optional). One bid per provider per job. Response 201 : { "bid": {...} }

GET /bids — Query: status (all | pending | accepted | rejected | withdrawn). Response: { "bids": [...], "counts": {...}, "win_rate": 100, "pipeline": 2800 } (pipeline = sum of pending bid amounts).

PUT /bids/{id} — same body as create; only while pending and the job is still open.

DELETE /bids/{id} — withdraws a pending bid.

Emergencies

GET /emergencies — open requests in the provider's city for services they offer; each includes my_price (this provider's price for that service).

POST /emergencies/{id}/accept — first to accept wins; creates a confirmed booking immediately. 409 if another provider already claimed it.

Wallet & payouts

GET /wallet — Query: bucket (all | available | escrow). Balances, lifetime/monthly earnings, 6-month trend, ledger entries, and recent withdrawal requests.

```
{
  "wallet": { "id":1, "available_balance": 2700, "escrow_balance": 0 },
  "total_earned": 2700, "earned_this_month": 2700,
  "earnings_series": [ { "label":"Feb","value":0}, ... ],
  "ledger": {
    "bucket": "all", "counts": { "all":3,"available":1,"escrow":2},
    "entries": [ { "id":3, "bucket":"available", "type":"...", "amount":2700, "description":"...", "booking_reference":"BK-Z6POMA", "created_at":"..." } ],
    "pagination": {...}
  },
  "min_withdrawal": 500,
  "withdrawal_requests": [ { "id":1, "reference":"WD-...", "amount":2700, "status":"pending", "payout_method":"jazzcash", "method_label":"JazzCash", "admin_notes":null, "processed_at":null, "created_at":"..." } ]
}
```

POST /payout-method — Body: payout_method (bank | jazzcash | easypaisa, required), payout_account_title , payout_account_number (required), payout_bank_name (required only if payout_method = bank). Response: { "profile": {...} }

POST /withdrawals — Body: amount (required, ≥ min_withdrawal , ≤ current available balance). Requires a payout method already saved. Response 201 : { "message": "...", "withdrawal": {...} }

Portfolio

Method	Path	Body	Notes
GET	/portfolio	–	{ "photos": [...] }
POST	/portfolio	multipart: photos[] (images, up to remaining slots under a 12-photo cap), caption (optional)	201, { "photos": [...just the new ones...] }
DELETE	/portfolio/{photoId}	–	{ "message": "Photo removed." }

7. Resource reference

Quick field reference for nested objects that recur throughout the API.

ProviderProfileResource

```
{
  "id": 21, "user_id": 23, "name": "Test Pro", "avatar_url": null, "business_name": null,
  "display_name": "Test Pro", "bio": null, "experience_years": 5,
  "rating_avg": 5.0, "reviews_count": 1, "city": "Karachi", "address": null,
  "latitude": null, "longitude": null, "status": "approved", "rejection_reason": null,
  "has_payout_method": true,
  "services": [ {...ProviderServiceResource, when loaded...} ],
  "portfolio": [ {...ProviderPortfolioPhotoResource, when loaded...} ]
}
```

status ∈ draft | pending | approved | rejected .

ServiceResource — { "id","category_id","category":{...or omitted},"name","slug","description","base_price","duration_minutes","is_active" }

BidResource — { "id","job_post_id","job_post":{...summary...},"provider": {...ProviderProfileResource...},"amount","proposed_date","proposed_time","message","status","booking_id","created_at" } . status ∈ pending | accepted | rejected | withdrawn .

ContractResource — {
"id","reference","title","description","address","latitude","longitude","city","preferred_start_date","status","quoted_total","items'
[...ContractItemResource...],"photos":[...],"milestones":[...ContractMilestoneResource...],"permissions":
{ "is_quoted","is_accepted","is_cancellable"},"accepted_at","completed_at","cancelled_at","created_at" } . status ∈ submitted |
quoted | accepted | rejected | in_progress | completed | cancelled .

EmergencyRequestResource — {
"id","reference","status","service","consumer","address","city","notes","booking_id","booking","matched_provider","matched_at","cance
lled_at" } . status ∈ open | matched | cancelled . my_price only populated on the provider board endpoint.

SubscriptionResource — {
"id","reference","status","plan","provider","address","city","next_visit_date","visits_used","is_cancellable","bookings","cancelled_d
ate" } . status ∈ pending_assignment | active | cancelled | completed .

PaymentResource — { "id","reference","gateway","amount","credit_applied","status","paid_at","released_at","refunded_at" } . status
∈ pending | escrow | released | refunded | failed .

DisputeResource — {
"id","reference","opened_by_role","reason","status","resolution","resolution_note","resolved_at","created_at","photos" } . status ∈
open | resolved | dismissed (resolution is set by an admin). photos is [{ "id","url" }] , only present when loaded (both POST .../dispute and
GET /disputes/{id} load it).

8. What's intentionally out of scope here

- **Admin panel** — stays web-only; not part of this API.
- **Job seeker (careers/recruitment) flows** — the mobile app is for customers + professionals, not the internal hiring board.
- **Corporate/B2B accounts, referrals dashboard** — not wired into this API pass; can be added the same way (they already have web controllers to mirror) if the app needs them later.
- **Push notification delivery** — this API stores/reads in-app Notification rows (badge counts, notification center), but does not yet register Expo/FCM/APNs device tokens or send pushes. That's a separate small piece of work (a device_tokens table + a dispatch step in Notifier) worth doing once the app shell exists.
- **Real payment gateways** — JazzCash/Easypaisa drivers exist server-side but are disabled by default (config/payments.php); only the mock gateway is enabled out of the box, same as the web app.

9. Testing this yourself

```
curl -X POST https://your-domain/api/register \  
-H "Accept: application/json" -H "Content-Type: application/json" \  
-d \  
'{"name":"Jane","email":"jane@example.com","phone":"+910000000000","role":"consumer","password":"password123","password_confirmation":  
"password123"}' \  
# then, using the returned token: \  
curl https://your-domain/api/me \  
-H "Accept: application/json" -H "Authorization: Bearer <token>"
```

Every endpoint in this document was hit with real requests against a local instance during development (full booking → escrow → completion → wallet release cycle, jobs/bids, emergency accept, contract creation, dispute open, and token revocation on logout all verified working) — including the completion-required-photos flow, the cash/bank-transfer completion-payment flow, the in-progress visit-charge cancellation, dispute photo evidence, and CNIC normalization on onboarding, all added in this pass.