

Security Audit

Haven1 (Layer 1)

Table of Contents

Executive Summary	4
Project Context	4
Audit scope	7
Security Rating	9
Intended Smart Contract Functions	10
Code Quality	11
Audit Resources	11
Dependencies	11
Severity Definitions	12
Status Definitions	13
Audit Findings	14
Centralisation	17
Conclusion	18
Our Methodology	19
Disclaimers	21
About Hashlock	22

CAUTION

THIS DOCUMENT IS A SECURITY AUDIT REPORT AND MAY CONTAIN CONFIDENTIAL INFORMATION. THIS INCLUDES IDENTIFIED VULNERABILITIES AND MALICIOUS CODE WHICH COULD BE USED TO COMPROMISE THE PROJECT. THIS DOCUMENT SHOULD ONLY BE FOR INTERNAL USE UNTIL ISSUES ARE RESOLVED. ONCE VULNERABILITIES ARE REMEDIATED, THIS REPORT CAN BE MADE PUBLIC. THE CONTENT OF THIS REPORT IS OWNED BY HASHLOCK PTY LTD FOR USE OF THE CLIENT.

Executive Summary

The Haven1 team partnered with Hashlock to conduct a security audit of their UniswapV3 smart contracts. Hashlock manually and proactively reviewed the code in order to ensure the project's team and community that the deployed contracts are secure.

Project Context

Haven1 is a REKT-resistant, EVM-compatible Layer 1 blockchain designed to safeguard users from on-chain hacks, scams, and rug pulls. By integrating advanced security measures such as the Haven1 Passport for verified access, a SafeHaven Council of reputable global validators, and 24/7 AI-powered threat monitoring, Haven1 ensures a secure environment for decentralized applications (hApps). The platform also offers innovative features like the 2FA Wallet Shield, providing on-chain two-factor authentication for enhanced asset protection. Developers benefit from EVM compatibility, comprehensive resources, and grant opportunities to build and deploy secure hApps. With a focus on deep, clean liquidity sourced from hundreds of vetted providers, Haven1 delivers a fortified SafeHaven for all participants in the Web3 ecosystem.

Project Name: Haven1


Project Type: Layer 1

Compiler Version: ^0.7.6

Website: <https://haven1.org>

Logo:



Visualised Context:

Project Visuals:



Audit scope

We at Hashlock audited the solidity code within the Haven1 project, the scope of work included a comprehensive review of the smart contracts listed below. We tested the smart contracts to check for their security and efficiency. These tests were undertaken primarily through manual line-by-line analysis and were supported by software-assisted testing.

Description	Haven1 Protocol Smart Contracts
Platform	Haven1 / Solidity
Audit Date	February, 2025
Contract 1	IUniswapV3Factory.sol
Contract 1 MD5 Hash	d039558126fcd96aba7c684a1d95abc7
Contract 2	UniswapV3Factory.sol
Contract 2 MD5 Hash	cd8294babfa3b2b1b8ff3ded83460c8f
Contract 3	UniswapV3Pool.sol
Contract 3 MD5 Hash	64ce7e6b083737a2d10d8e055b8e625e
Contract 4	NonfungiblePositionManager.sol
Contract 4 MD5 Hash	e136cf2ea78cf31e77ea524d07dc1bb1
Contract 5	SwapRouter.sol
Contract 5 MD5 Hash	73333599be93c18237d81af74242d315
Contract 6	V3Migrator.sol
Contract 6 MD5 Hash	162ace33ec135c9fc35790f26325cd6d
Contract 7	H1NativeBaseV07Downgrade.sol
Contract 7 MD5 Hash	044f26adf401f338be7b8164c19195a8
Contract 8	H1FlashRouter.sol
Contract 8 MD5 Hash	8a5106264105652bdda8da82f3ac5e08

Contract 9	H1NativeApplicationV07Downgrade.sol
Contract 9 MD5 Hash	044f26adf401f338be7b8164c19195a8



Security Rating

After Hashlock's Audit, we found the smart contracts to be **"Secure"**. The contracts all follow simple logic, with correct and detailed ordering. They use a series of interfaces, and the protocol uses a list of Open Zeppelin contracts. We initially identified some vulnerabilities that have since been addressed.



Not Secure

Vulnerable

Secure

Hashlocked

The 'Hashlocked' rating is reserved for projects that ensure ongoing security via bug bounty programs or on chain monitoring technology.

All issues uncovered during automated and manual analysis were meticulously reviewed and applicable vulnerabilities are presented in the [Audit Findings](#) section. The general security overview is presented in the [Standardised Checks](#) section and the project's contract functionality is presented in the [Intended Smart Contract Functions](#) section.

All vulnerabilities initially identified have now been resolved and acknowledged.

Hashlock found:

1 Low severity vulnerabilities

2 QAs

Caution: *Hashlock's audits do not guarantee a project's success or ethics, and are not liable or responsible for security. Always conduct independent research about any project before interacting.*

Intended Smart Contract Functions

Claimed Behaviour	Actual Behaviour
IUniswapV3Factory.sol - Factory interface	Contract achieves this functionality.
UniswapV3Factory.sol - Creation of new pools	Contract achieves this functionality.
UniswapV3Pool.sol - Pool logic	Contract achieves this functionality.
NonfungiblePositionManager.sol - Management of NFT issued on Uniswap positions change	Contract achieves this functionality.
SwapRouter.sol - Managing swap router	Contract achieves this functionality.
V3Migrator.sol - Migration feature	Contract achieves this functionality.
H1FlashRouter.sol - Callback implementation	Contract achieves this functionality.
H1NativeBaseV07Downgrade.sol - Manages fee logic	Contract achieves this functionality.
H1NativeApplicationV07Downgrade.sol - Update function implementation	Contract achieves this functionality.

Code Quality

This audit scope involves the smart contracts of the Haven1 project, as outlined in the Audit Scope section. All contracts, libraries, and interfaces mostly follow standard best practices and to help avoid unnecessary complexity that increases the likelihood of exploitation, however, some refactoring was required.

The code is very well commented on and closely follows best practice nat-spec styling. All comments are correctly aligned with code functionality.

Audit Resources

We were given the Haven1 project smart contract code in the form of Github access.

As mentioned above, code parts are well commented. The logic is straightforward, and therefore it is easy to quickly comprehend the programming flow as well as the complex code logic. The comments are helpful in providing an understanding of the protocol's overall architecture.

Dependencies

As per our observation, the libraries used in this smart contracts infrastructure are based on well-known industry standard open source projects.

Apart from libraries, its functions are used in external smart contract calls.

Severity Definitions

The severity levels assigned to findings represent a comprehensive evaluation of both their potential impact and the likelihood of occurrence within the system. These categorizations are established based on Hashlock's professional standards and expertise, incorporating both industry best practices and our discretion as security auditors. This ensures a tailored assessment that reflects the specific context and risk profile of each finding.

Significance	Description
High	High-severity vulnerabilities can result in loss of funds, asset loss, access denial, and other critical issues that will result in the direct loss of funds and control by the owners and community.
Medium	Medium-level difficulties should be solved before deployment, but won't result in loss of funds.
Low	Low-level vulnerabilities are areas that lack best practices that may cause small complications in the future.
Gas	Gas Optimisations, issues, and inefficiencies
QA	Quality Assurance (QA) findings are informational and don't impact functionality. Supports clients improve the clarity, maintainability, or overall structure of the code.

Status Definitions

Each identified security finding is assigned a status that reflects its current stage of remediation or acknowledgment. The status provides clarity on the handling of the issue and ensures transparency in the auditing process. The statuses are as follows:

Significance	Description
Resolved	The identified vulnerability has been fully mitigated either through the implementation of the recommended solution proposed by Hashlock or through an alternative client-provided solution that demonstrably addresses the issue
Acknowledged	The client has formally recognized the vulnerability but has chosen not to address it due to the high cost or complexity of remediation. This status is acceptable for medium and low-severity findings after internal review and agreement. However, all high-severity findings must be resolved without exception.
Unresolved	The finding remains neither remediated nor formally acknowledged by the client, leaving the vulnerability unaddressed.

Audit Findings

Low

[L-01] UniswapV3Factory.sol - Redundant router assignment to owner in constructor

Description

In UniswapV3Factory's constructor, the owner is automatically set as a router through `_setRouter(msg.sender, true)`. This is an unnecessary assignment since being an owner does not require router capabilities, and the two roles serve distinct purposes in the protocol.

The constructor performs two separate role assignments: setting the owner and adding the owner as a router. While the owner needs administrative privileges to manage the factory contract, they don't inherently need router capabilities to perform their governance duties. This creates an unnecessary privilege assignment that goes against the principle of least privilege.

Recommendation

Remove the `_setRouter(msg.sender, true)` call from the constructor, allowing the router role to be assigned explicitly when needed.

Status

Acknowledged

QA

[Q-01] UniswapV3Factory - Debug logs present in pool creation function

Description

The `createPool` function in `UniswapV3Factory.sol` contains multiple `console.log` statements used for debugging purposes. These logs track the execution flow through the pool creation process but should not be present in the production code. The function includes `console.log` statements with messages like `'createPool - 1'`, `'createPool - 2'`, and `'createPool - 3'` throughout its execution path. While helpful during development, these debug statements should be moved to separate unit test files for better code organization and clarity.

Recommendation

Remove `console.log` statements from the production code and move debugging logic to dedicated test files.

Status

Resolved

[Q-02] UniswapV3Pool - `increaseObservationCardinalityNext` missing `onlyRouters` modifier

Description

The `increaseObservationCardinalityNext` function in `UniswapV3Pool.sol` lacks the `onlyRouters` modifier that is consistently present on other state-changing functions in the contract. While no immediate exploit path is evident, this deviates from the established pattern of access control.

Recommendation

Add the `onlyRouters` modifier to maintain consistent access control across all state-modifying functions.

Status


Acknowledged



Centralisation

The Haven1 project values security and utility over decentralisation.

The owner executable functions within the protocol increase security and functionality but depend highly on internal team responsibility.



Centralised

Decentralised

Conclusion

After Hashlock's analysis, the Haven1 project seems to have a sound and well-tested code base, now that our vulnerability findings have been resolved and acknowledged. Overall, most of the code is correctly ordered and follows industry best practices. The code is well commented on as well. To the best of our ability, Hashlock is not able to identify any further vulnerabilities.

Our Methodology

Hashlock strives to maintain a transparent working process and to make our audits a collaborative effort. The objective of our security audits is to improve the quality of systems and upcoming projects we review and to aim for sufficient remediation to help protect users and project leaders. Below is the methodology we use in our security audit process.

Manual Code Review:

In manually analysing all of the code, we seek to find any potential issues with code logic, error handling, protocol and header parsing, cryptographic errors, and random number generators. We also watch for areas where more defensive programming could reduce the risk of future mistakes and speed up future audits. Although our primary focus is on the in-scope code, we examine dependency code and behaviour when it is relevant to a particular line of investigation.

Vulnerability Analysis:

Our methodologies include manual code analysis, user interface interaction, and white box penetration testing. We consider the project's website, specifications, and whitepaper (if available) to attain a high-level understanding of what functionality the smart contract under review contains. We then communicate with the developers and founders to gain insight into their vision for the project. We install and deploy the relevant software, exploring the user interactions and roles. While we do this, we brainstorm threat models and attack surfaces. We read design documentation, review other audit results, search for similar projects, examine source code dependencies, skim open issue tickets, and generally investigate details other than the implementation.

Documenting Results:

We undergo a robust, transparent process for analysing potential security vulnerabilities and seeing them through to successful remediation. When a potential issue is discovered, we immediately create an issue entry for it in this document, even though we have not yet verified the feasibility and impact of the issue. This process is vast because we document our suspicions early even if they are later shown to not represent exploitable vulnerabilities. We generally follow a process of first documenting the suspicion with unresolved questions, and then confirming the issue through code analysis, live experimentation, or automated tests. Code analysis is the most tentative, and we strive to provide test code, log captures, or screenshots demonstrating our confirmation. After this, we analyse the feasibility of an attack in a live system.

Suggested Solutions:

We search for immediate mitigations that live deployments can take and finally, we suggest the requirements for remediation engineering for future releases. The mitigation and remediation recommendations should be scrutinised by the developers and deployment engineers, and successful mitigation and remediation is an ongoing collaborative process after we deliver our report, and before the contract details are made public.

Disclaimers

Hashlock's Disclaimer

Hashlock's team has analysed these smart contracts in accordance with the best industry practices at the date of this report, in relation to: cybersecurity vulnerabilities and issues in the smart contract source code, the details of which are disclosed in this report, (Source Code); the Source Code compilation, deployment, and functionality (performing the intended functions).

Due to the fact that the total number of test cases is unlimited, the audit makes no statements or warranties on the security of the code. It also cannot be considered as a sufficient assessment regarding the utility and safety of the code, bug-free status, or any other statements of the contract. While we have done our best in conducting the analysis and producing this report, it is important to note that you should not rely on this report only. We also suggest conducting a bug bounty program to confirm the high level of security of this smart contract.

Hashlock is not responsible for the safety of any funds and is not in any way liable for the security of the project.

Technical Disclaimer

Smart contracts are deployed and executed on a blockchain platform. The platform, its programming language, and other software related to the smart contract can have their own vulnerabilities that can lead to attacks. Thus, the audit can't guarantee the explicit security of the audited smart contracts.

About Hashlock

Hashlock is an Australian-based company aiming to help facilitate the successful widespread adoption of distributed ledger technology. Our key services all have a focus on security, as well as projects that focus on streamlined adoption in the business sector.

Hashlock is excited to continue to grow its partnerships with developers and other web3-oriented companies to collaborate on secure innovation, helping businesses and decentralised entities alike.

Website: hashlock.com.au

Contact: info@hashlock.com.au



#hashlock.