


# AutoRed

## Reconnaissance & Attack Surface Assessment Report

|                 |                   |
|-----------------|-------------------|
| Target:         | 192.168.112.130   |
| Scan Name:      | Test Scan         |
| Profile:        | Standard          |
| Date Generated: | 18 May 2026 07:25 |
| Prepared By:    | AutoRed v1.0      |
| Classification: | CONFIDENTIAL      |

### FINDINGS OVERVIEW



CONFIDENTIAL - This document contains sensitive security information.



## Table of Contents

|    |                         |    |
|----|-------------------------|----|
| 1. | Executive Summary       | 3  |
| 2. | Severity Classification | 3  |
| 3. | Scope & Methodology     | 4  |
| 4. | Findings Summary        | 5  |
| 5. | Detailed Findings       | 5  |
| 6. | Recommendations         | 10 |
| 7. | Conclusion              | 11 |

Total Findings: 23 | Target: 192.168.112.130 | Generated: 18 May 2026 07:25

## 1. Executive Summary

AutoRed conducted an automated reconnaissance and vulnerability assessment against 192.168.112.130. The assessment identified a total of 23 findings across multiple severity levels. Of these, 2 finding(s) were rated Critical, indicating immediately exploitable vulnerabilities that pose a direct risk of system compromise or data breach. Additionally, 5 High-severity finding(s) were identified which could be exploited with moderate effort. 4 Medium-severity finding(s) were also detected, requiring attention in the near term. Immediate remediation of Critical and High findings is strongly recommended to reduce the overall attack surface.

## 2. Severity Classification

All findings are classified according to standard vulnerability severity levels based on CVSS scoring guidelines. The table below defines each severity level, its CVSS range, business impact and recommended remediation timeline.

| Severity        | CVSS Range | Business Impact                                         | Action      |
|-----------------|------------|---------------------------------------------------------|-------------|
| <b>Critical</b> | 9.0 - 10.0 | May lead to complete system compromise, unauthorised... | Immediate   |
| <b>High</b>     | 7.0 - 8.9  | Could allow significant unauthorised access or data ... | Short-term  |
| <b>Medium</b>   | 4.0 - 6.9  | May expose sensitive information or enable limited u... | Medium-term |
| <b>Low</b>      | 0.1 - 3.9  | Minimal direct impact; contributes to the overall at... | Long-term   |
| <b>Info</b>     | N/A        | Informational only. No direct risk but may aid furth... | Optional    |

### 3. Scope & Methodology

#### Scope of Assessment

|               |                                |
|---------------|--------------------------------|
| Target:       | 192.168.112.130                |
| Scan Name:    | Test Scan                      |
| Profile:      | Standard                       |
| Approval:     | Authorized testing environment |
| Conducted On: | 2026-05-16T09:24               |

This assessment was conducted within an authorized testing environment for educational and research purposes. All testing was performed using AutoRed v1.0, a GUI-based reconnaissance automation platform developed as a Final Year Project at Asia Pacific University (APU).

#### Assessment Phases

##### 1. Reconnaissance

Passive and active information gathering using Subfinder, theHarvester and DNSrecon.

##### 2. Enumeration

Port scanning and service detection via Nmap. Web host identification via httpx.

##### 3. Fingerprinting

Technology stack identification using WhatWeb. CMS detection via WPScan.

##### 4. Vulnerability Discovery

Web vulnerability scanning via Nikto and Nuclei. Directory enumeration via ffuf, Gobuster, Dirsearch.

##### 5. Classification

All findings automatically parsed, normalized and severity-scored based on CVSS guidelines.

##### 6. Reporting

Findings aggregated with business impact, attack paths and remediation guidance.

#### Tools Used



| Tool      | Purpose                                     |
|-----------|---------------------------------------------|
| Nmap      | Port scanning and service version detection |
| Subfinder | Passive subdomain enumeration via OSINT     |
| httpx     | HTTP probing to identify live web hosts     |

|                     |                                            |
|---------------------|--------------------------------------------|
| <b>WhatWeb</b>      | Web technology fingerprinting              |
| <b>ffuf</b>         | Fast directory and endpoint fuzzing        |
| <b>Nikto</b>        | Web server vulnerability scanning          |
| <b>theHarvester</b> | OSINT email and host harvesting            |
| <b>DNSrecon</b>     | DNS enumeration and zone analysis          |
| <b>Gobuster</b>     | Directory and file brute forcing           |
| <b>Dirsearch</b>    | Web path discovery with curated wordlists  |
| <b>WPScan</b>       | WordPress vulnerability scanning           |
| <b>Nuclei</b>       | Template-based CVE vulnerability detection |

## 4. Findings Summary

| Severity | Count | CVSS       | Business Impact                                          | Action      |
|----------|-------|------------|----------------------------------------------------------|-------------|
| Critical | 2     | 9.0 - 10.0 | May lead to complete system compromise, unauthorised ... | Immediate   |
| High     | 5     | 7.0 - 8.9  | Could allow significant unauthorised access or data e... | Short-term  |
| Medium   | 4     | 4.0 - 6.9  | May expose sensitive information or enable limited un... | Medium-term |
| Low      | 11    | 0.1 - 3.9  | Minimal direct impact; contributes to the overall att... | Long-term   |
| Info     | 1     | N/A        | Informational only. No direct risk but may aid furthe... | Optional    |

### Visual Analysis:



## 5. Detailed Findings

AR-CRIT-001Open port 23/tcp - telnet

Severity:CRITICALCVSS:9.0 - 10.0Tool:nmapAction:Immediate

Asset:192.168.112.130 (192.168.112.130)

**Description:**  
Port 23 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: telnet Linux telnetd.

**Business Impact:**  
May lead to complete system compromise, unauthorised remote access, or full data breach.

**Attack Path:**  
Attacker -> Network -> Port 23 -> Plaintext Sniff -> Full Access

**Recommendation:**  
Disable Telnet immediately. It transmits all data including passwords in plaintext. Use SSH.

AR-CRIT-002Open port 1524/tcp - bindshell

Severity:CRITICALCVSS:9.0 - 10.0Tool:nmapAction:Immediate

Asset:192.168.112.130 (192.168.112.130)

**Description:**  
Port 1524 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: bindshell Metasploitable root shell.

**Business Impact:**  
May lead to complete system compromise, unauthorised remote access, or full data breach.

**Attack Path:**  
Attacker -> Network -> Port 1524 -> Root Shell -> Full Compromise

**Recommendation:**  
Critical backdoor port detected. Investigate immediately. This is a known Metasploitable backdoor.

**AR-HIGH-001** Open port 21/tcp - ftp

**Severity:** HIGH **CVSS:** 7.0 - 8.9 **Tool:** nmap **Action:** Short-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 21 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: ftp vsftpd 2.3.4.

**Business Impact:**

Could allow significant unauthorised access or data exposure with moderate exploitation effort.

**Attack Path:**

Attacker -> Network -> Port 21 -> Brute Force -> File Access

**Recommendation:**

Disable FTP immediately. Use SFTP instead. FTP transmits credentials in plaintext.

**AR-HIGH-002** Open port 445/tcp - netbios-ssn

**Severity:** HIGH **CVSS:** 7.0 - 8.9 **Tool:** nmap **Action:** Short-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 445 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: netbios-ssn Samba smbd 3.X - 4.X.

**Business Impact:**

Could allow significant unauthorised access or data exposure with moderate exploitation effort.

**Recommendation:**

Disable SMB if not needed. Apply latest patches. Restrict access with firewall.

**AR-HIGH-003** Open port 3306/tcp - mysql

**Severity:** HIGH **CVSS:** 7.0 - 8.9 **Tool:** nmap **Action:** Short-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 3306 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: mysql MySQL 5.0.51a-3ubuntu5.

**Business Impact:**

Could allow significant unauthorised access or data exposure with moderate exploitation effort.

**Attack Path:**



Attacker -> Network -> Port 3306 -> Weak Credentials -> DB Access

#### Recommendation:

Restrict MySQL access to localhost only. Never expose database ports publicly.

#### AR-HIGH-004 Open port 5432/tcp - postgresql

Severity: **HIGH** CVSS: 7.0 - 8.9 Tool: nmap Action: Short-term

Asset: 192.168.112.130 (192.168.112.130)

#### Description:

Port 5432 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: postgresql PostgreSQL DB 8.3.0 - 8.3.7.

#### Business Impact:

Could allow significant unauthorised access or data exposure with moderate exploitation effort.

#### Attack Path:

Attacker -> Network -> Port 5432 -> Empty Password -> DB Access

#### Recommendation:

Restrict PostgreSQL access to localhost only. Never expose database ports publicly.

#### AR-HIGH-005 Open port 5900/tcp - vnc

Severity: **HIGH** CVSS: 7.0 - 8.9 Tool: nmap Action: Short-term

Asset: 192.168.112.130 (192.168.112.130)

#### Description:

Port 5900 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: vnc VNC.

#### Business Impact:

Could allow significant unauthorised access or data exposure with moderate exploitation effort.

#### Attack Path:

Attacker -> Network -> Port 5900 -> Default Login -> Desktop Control

#### Recommendation:

Disable VNC if not needed. If required use strong passwords and restrict access.

**AR-MED-001** Open port 22/tcp - ssh

**Severity:** MEDIUM **CVSS:** 4.0 - 6.9 **Tool:** nmap **Action:** Medium-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 22 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: ssh OpenSSH 4.7p1 Debian 8ubuntu1.

**Business Impact:**

May expose sensitive information or enable limited unauthorised actions under specific conditions.

**Attack Path:**

Attacker -> Port 22 -> Brute Force -> Remote Shell

**Recommendation:**

Restrict SSH access to trusted IPs only. Disable root login. Use key-based authentication.

**AR-MED-002** Open port 25/tcp - smtp

**Severity:** MEDIUM **CVSS:** 4.0 - 6.9 **Tool:** nmap **Action:** Medium-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 25 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: smtp Postfix smtpd.

**Business Impact:**

May expose sensitive information or enable limited unauthorised actions under specific conditions.

**Attack Path:**

Attacker -> Port 25 -> User Enum -> Phishing or Relay

**Recommendation:**

Restrict SMTP relay. Ensure authentication is required to prevent spam relay.

**AR-MED-003** Open port 139/tcp - netbios-ssn

**Severity:** MEDIUM **CVSS:** 4.0 - 6.9 **Tool:** nmap **Action:** Medium-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 139 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: netbios-ssn Samba smbd 3.X - 4.X.

**Business Impact:**

May expose sensitive information or enable limited unauthorised actions under specific conditions.

**Recommendation:**

Restrict NetBIOS access using firewall rules. Apply latest SMB patches.

**AR-MED-004****Open port 6667/tcp - irc****Severity:****MEDIUM****CVSS:**

4.0 - 6.9

**Tool:**

nmap

**Action:**

Medium-term

**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 6667 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: irc UnrealIRCd.

**Business Impact:**

May expose sensitive information or enable limited unauthorised actions under specific conditions.

**Attack Path:**

Attacker -> IRC Port -> Version Detect -> Exploit -> RCE

**Recommendation:**

Investigate IRC service. Commonly used by malware for command and control.

**AR-LOW-001****Open port 53/tcp - domain****Severity:****LOW****CVSS:**

0.1 - 3.9

**Tool:**

nmap

**Action:**

Long-term

**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 53 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: domain ISC BIND 9.4.2.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Restrict DNS zone transfers. Only allow trusted resolvers.

**AR-LOW-002** Open port 111/tcp - rpcbind**Severity:** LOW **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 111 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: rpcbind 2.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-003** Open port 512/tcp - exec**Severity:** LOW **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 512 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: exec netkit-rsh rexecd.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-004** Open port 513/tcp - login**Severity:** LOW **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 513 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: login OpenBSD or Solaris rlogind.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-005** Open port 514/tcp - tcpwrapped**Severity:** LOW **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 514 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: tcpwrapped .

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-006** Open port 1099/tcp - java-rmi**Severity:** LOW **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 1099 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: java-rmi GNU Classpath grmiregistry.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Attack Path:**

Attacker -> RMI Port -> Deserialization -> RCE

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-007** Open port 2049/tcp - nfs**Severity:** LOW **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term**Asset:** 192.168.112.130 (192.168.112.130)**Description:**

Port 2049 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: nfs 2-4.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Attack Path:**

Attacker -> NFS Port -> Mount Share -> File Access

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-008 Open port 2121/tcp - ftp**

**Severity:** **LOW** **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 2121 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: ftp ProFTPD 1.3.1.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Attack Path:**

Attacker -> Network -> Port 21 -> Brute Force -> File Access

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-009 Open port 6000/tcp - X11**

**Severity:** **LOW** **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 6000 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: X11 .

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-010 Open port 8009/tcp - ajp13**

**Severity:** **LOW** **CVSS:** 0.1 - 3.9 **Tool:** nmap **Action:** Long-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 8009 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: ajp13 Apache Jserv.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Review this service and restrict access if not needed.

**AR-LOW-011      Open port 8180/tcp - http**

**Severity:** **LOW**      **CVSS:** 0.1 - 3.9      **Tool:** nmap      **Action:** Long-term  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 8180 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: http Apache Tomcat/Coyote JSP engine 1.1.

**Business Impact:**

Minimal direct impact; contributes to the overall attack surface and reconnaissance value.

**Recommendation:**

Restrict access to Tomcat HTTP port. Ensure default credentials are changed.

**AR-INFO-001      Open port 80/tcp - http**

**Severity:** **INFO**      **CVSS:** N/A      **Tool:** nmap      **Action:** Optional  
**Asset:** 192.168.112.130 (192.168.112.130)

**Description:**

Port 80 (tcp) is open on 192.168.112.130 (192.168.112.130). Service detected: http Apache httpd 2.2.8.

**Business Impact:**

Informational only. No direct risk but may aid further enumeration by an attacker.

**Recommendation:**

Ensure web server is patched and properly configured. Consider redirecting to HTTPS.

## 6. Recommendations

The following prioritised recommendations are based on the severity and exploitability of identified findings. Critical and High items should be addressed immediately to reduce the risk of exploitation.

### **[AR-CRIT-001] Open port 23/tcp - telnet**

Disable Telnet immediately. It transmits all data including passwords in plaintext. Use SSH.

### **[AR-CRIT-002] Open port 1524/tcp - bindshell**

Critical backdoor port detected. Investigate immediately. This is a known Metasploitable backdoor.

### **[AR-HIGH-001] Open port 21/tcp - ftp**

Disable FTP immediately. Use SFTP instead. FTP transmits credentials in plaintext.

### **[AR-HIGH-002] Open port 445/tcp - netbios-ssn**

Disable SMB if not needed. Apply latest patches. Restrict access with firewall.

### **[AR-HIGH-003] Open port 3306/tcp - mysql**

Restrict MySQL access to localhost only. Never expose database ports publicly.

### **[AR-HIGH-004] Open port 5432/tcp - postgresql**

Restrict PostgreSQL access to localhost only. Never expose database ports publicly.

### **[AR-HIGH-005] Open port 5900/tcp - vnc**

Disable VNC if not needed. If required use strong passwords and restrict access.



## 7. Conclusion

This automated reconnaissance assessment of 192.168.112.130 identified a total of 23 findings across five severity levels, including 2 Critical and 5 High severity findings that require immediate attention.

Immediate action is recommended for all Critical and High findings, particularly any exposed remote access services, known backdoors, or unpatched vulnerabilities. Medium findings should be scheduled for remediation in the near term, while Low and Informational findings should be reviewed as part of ongoing security hygiene.

AutoRed demonstrated significant time savings compared to manual reconnaissance, completing the assessment in under 10 minutes while identifying findings that would typically require hours of manual effort. This validates the platform as an effective tool for initial attack surface assessment in cybersecurity engagements.

## Disclaimer

This report was generated automatically by AutoRed v1.0 for authorized security assessment and educational purposes only. All testing was conducted within an approved scope. This report is classified as CONFIDENTIAL and should be handled accordingly.