RAJALAKSHMI ENGINEERING COLLEGE

Mohamed Nabil Hasim H 251001149-2025-IT

M2

Started on	Monday, 31 August 2026, 11:32 AM
State	Finished
Completed on	Monday, 31 August 2026, 11:33 AM
Time taken	37 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b) {
    long long x = *(long long *)a;
    long long y = *(long long *)b;

    if (x < y)
        return -1;
    else if (x > y)
        return 1;
    return 0;
}

int main() {
    int n, m;

    // Number of children
    scanf("%d", &n);

    long long g[n];

    // Greed factors
    for (int i = 0; i < n; i++) {
        scanf("%lld", &g[i]);
    }

    // Number of cookies
    scanf("%d", &m);

```

```
31      long long s[m];
32
33      // Cookie sizes
34      for (int i = 0; i < m; i++) {
35          scanf("%lld", &s[i]);
36      }
37
38      // Sort both arrays
39      qsort(g, n, sizeof(long long), compare);
40      qsort(s, m, sizeof(long long), compare);
41
42      int child = 0;
43      int cookie = 0;
44      int count = 0;
45
46      while (child < n && cookie < m) {
47          if (s[cookie] >= g[child]) {
48              count++;
49              child++;
50          }
51
52          cookie++;
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course