




Description
No Data

Simulation of Auger


Date: Thursday, April 9, 2026
Designer: Solidworks
Study name: Auger static analysis
Analysis type: Static

Table of Contents

Description	1
Assumptions.....	2
Model Information	2
Study Properties.....	3
Units	3
Material Properties	4
Loads and Fixtures	4
Connector Definitions	5
Interaction Information	5
Mesh information.....	5
Sensor Details.....	5
Resultant Forces	6
Beams.....	6
Study Results	7
Conclusion.....	9

Assumptions

Model Information

 Model name: Auger Current Configuration: Default			
Solid Bodies			
Document Name and Reference	Treated As	Volumetric Properties	Document Path/Date Modified
Fillet18 	Solid Body	Mass:1.17609 kg Volume:0.00014702 m^3 Density:7,999.56 kg/m^3 Weight:11.5257 N	C:\Graduation graduate\Auger Filler of Powder VFFS\2. The second stage\AUGER FILLER SYSTEM\analysis\solidworks analysis\Auger analysis\Auger.SLDPRT Apr 9 11:38:58 2026

Study Properties

Study name	Auger static analysis
Analysis type	Static
Mesh type	Solid Mesh
Thermal Effect:	On
Thermal option	Include temperature loads
Zero strain temperature	298 Kelvin
Include fluid pressure effects from SOLIDWORKS Flow Simulation	Off
Solver type	Automatic
Inplane Effect:	Off
Soft Spring:	Off
Inertial Relief:	Off
Incompatible bonding options	Automatic
Large displacement	Off
Compute free body forces	On
Friction	Off
Use Adaptive Method:	Off
Result folder	SOLIDWORKS document (C:\Graduation graduate\Auger Filler of Powder VFFS\2. The second stage\AUGER FILLER SYSTEM\analysis\solidworks analysis\Auger analysis)

Units


Unit system:	SI (MKS)
Length/Displacement	mm
Temperature	Kelvin
Angular velocity	Rad/sec
Pressure/Stress	N/m ²





Material Properties

Model Reference	Properties	Components
	Name: AISI 304 Model type: Linear Elastic Isotropic Default failure criterion: Max von Mises Stress Yield strength: 2.06807e+08 N/m ² Tensile strength: 5.17017e+08 N/m ² Elastic modulus: 1.9e+11 N/m ² Poisson's ratio: 0.29 Mass density: 8,000 kg/m ³ Shear modulus: 7.5e+10 N/m ² Thermal expansion coefficient: 1.8e-05 /Kelvin	SolidBody 1(Fillet18)(0.Auger (الطول الكلي 444سم))
Curve Data:N/A		

Loads and Fixtures

Fixture name	Fixture Image	Fixture Details		
Fixed-1		Entities: 2 face(s) Type: Fixed Geometry		
Resultant Forces				
Components	X	Y	Z	Resultant
Reaction force(N)	-47.5094	-1.3853	-11.4987	48.9007
Reaction Moment(N.m)	0	0	0	0

Load name	Load Image	Load Details
Torque-1		Entities: 1 face(s) Type: Apply torque Value: 20 N.m
Gravity-1		Reference: Front Plane Values: 0 0 9.81 Units: m/s ²



Connector Definitions

No Data

Interaction Information

No Data

Mesh information

Mesh type	Solid Mesh
Mesher Used:	Blended curvature-based mesh
Jacobian points for High quality mesh	16 Points
Maximum element size	5.41099 mm
Minimum element size	0.27055 mm
Mesh Quality	High

Mesh information - Details

Total Nodes	104572
Total Elements	63131
Maximum Aspect Ratio	71.497
% of elements with Aspect Ratio < 3	99.3
Percentage of elements with Aspect Ratio > 10	0.0475
Percentage of distorted elements	0
Time to complete mesh(hh:mm:ss):	00:00:57
Computer name:	HASSAN

Sensor Details

No Data



Resultant Forces

Reaction forces

Selection set	Units	Sum X	Sum Y	Sum Z	Resultant
Entire Model	N	-47.5094	-1.3853	-11.4987	48.9007

Reaction Moments

Selection set	Units	Sum X	Sum Y	Sum Z	Resultant
Entire Model	N.m	0	0	0	0

Free body forces

Selection set	Units	Sum X	Sum Y	Sum Z	Resultant
Entire Model	N	0.580267	-0.0988879	-9.34634	9.36486

Free body moments



Selection set	Units	Sum X	Sum Y	Sum Z	Resultant
Entire Model	N.m	0	0	0	1e-33



Beams

No Data



Study Results





Conclusion

