DeployGuard

100-Repository Deployment & Blocker Certification Corpus

Python + JavaScript real-world repository matrix

Designed for deployment stability, service detection, ENV handling, database mapping, branch selection, and expected-blocker validation.

Corpus size	100 public GitHub repositories
Primary languages	50 JavaScript + 50 Python
Starter templates	Excluded as the intended test target; repository-style applications are preferred
Branches	main, master, dev, develop, gh-pages
Outcomes	DEPLOY, DIAGNOSTIC, EXPECTED BLOCKER
ENV modes	FULL_ENV, PARTIAL_ENV, MISSING_REQUIRED, EXTRA_UNKNOWN, NO_ENV
Secrets	No real credentials. Every secret/API key in this document is synthetic or a placeholder.

Important: this is a certification TEST PLAN, not a claim that every repository will deploy. Failures must be classified from real DeployGuard evidence.

1. How to use this corpus

Run repositories through the normal DeployGuard source-selection and deployment flow. Do not patch a target repository merely to force a PASS. The goal is to measure DeployGuard as it exists.

For multi-service repositories, use the selection instruction in each entry. If DeployGuard detects a different authoritative service boundary than the note below, record that difference rather than overriding it blindly.

For database-backed applications, select the database type listed below only when the application actually needs that database. Values such as <DEPLOYGUARD_MANAGED_MONGODB_URL> mean the URL produced by the managed database/runtime contract, not a literal string.

ENV test profiles are deliberate: some are complete, some omit values, and some add unknown keys. This lets you test whether DeployGuard preserves, validates, rejects, or safely ignores configuration according to its contracts.

For EXPECTED BLOCKER cases, a clean pre-deployment or build-target blocker is a success for the test. Do not reclassify an expected safety/admission blocker as a product defect unless the blocker is incorrect or misleading.

Branch names are part of the test. Do not silently switch master/dev/develop/gh-pages repositories to main.

ENV profile legend

FULL_ENV	Supply the listed deployment-test ENV values.
PARTIAL_ENV	Supply only the listed subset. Missing values should be optional for the selected path or should expose a precise blocker.
MISSING_REQUIRED	Intentionally leave the marked value absent. Expected behavior is a clear blocker or a deterministic application/config failure, not silent corruption.
EXTRA_UNKNOWN	Supply valid/minimal values plus one or more unknown variables. Verify DeployGuard preserves user-owned ENV and the app ignores values it does not consume.
NO_ENV	Do not add user ENV. Platform-owned runtime values such as PORT/HOST remain governed by DeployGuard.

Evidence discipline

Repository links and default/non-default branches were discovered from public GitHub metadata. Some exact ENV key names were observed directly in public source (for example MONGO_URI, JWT_SECRET, SERVICE_URL, SERVER_PORT, SECRET_KEY, DATABASE_URL).

Where a repository does not expose a clear .env example in the retrieved evidence, the document uses a conservative stack-derived test value or deliberately uses NO_ENV/EXTRA_UNKNOWN rather than pretending an unverified key is mandatory.

External integration placeholders (Stripe, PayPal, Cloudinary, Notion, Shopify, OpenAI, LINE, GitHub OAuth, etc.) are never real secrets. Use provider sandbox credentials only if you explicitly want the external feature to succeed.

2. Corpus distribution

JavaScript	50
Python	50
DEPLOY	60
DIAGNOSTIC	26
EXPECTED BLOCKER	14
Single-service notes	76
Multi-service notes	24
main branches	38
master branches	57
dev/develop/gh-pages	5

ENV-mode counts

FULL_ENV	29
PARTIAL_ENV	14
MISSING_REQUIRED	8
EXTRA_UNKNOWN	39
NO_ENV	10

Recommended execution: run compatibility waves of 20-30 repositories, then run a separate 30-40 concurrent stress wave. Compatibility percentage and concurrency stability are different measurements and should be reported separately.

3. Master index

#	Repository	Branch	Stack	DB	Intent
1	bradtraversy/proshop-v2	main	MERN e-commerce	MongoDB	DEPLOY
2	burakorkmez/mern-ecommerce	master	MERN e-commerce + Redis + Stripe	MongoDB + Redis	DIAGNOSTIC
3	bluebits-academy/mern-stack-ecommerce	master	MERN e-commerce	MongoDB	DIAGNOSTIC
4	basir/mern-amazona	master	MERN e-commerce	MongoDB	DEPLOY
5	techinfo-youtube/ecommerce-app-2023	main	Express + React e-commerce	MongoDB	DEPLOY
6	RishiBakshii/mern-ecommerce	main	MERN e-commerce	MongoDB	DEPLOY
7	IsAmitprajapati/BlinkIt-Clone-Full-Stack-Ecommerce	main	MERN e-commerce clone	MongoDB	DEPLOY
8	dhatGuy/PERN-Store	main	PERN store	PostgreSQL	DEPLOY
9	eknoorpreet/dev.to-clone	main	React + Express social/blog clone	MongoDB	DIAGNOSTIC
10	b30wulffz/job-portal	main	Full-stack job portal	MongoDB	DEPLOY
11	TannerReynolds/ShareX-Upload-Server	master	Node upload server	None / filesystem	DIAGNOSTIC
12	k-yle/rtsp-relay	main	Node media relay	None	DIAGNOSTIC
13	zhravan/github-readme-quotes	main	Express + frontend image/quote service	None / external quote service	DEPLOY
14	immers-space/activitypub-express	master	Express ActivityPub service/library	None / app-dependent	EXPECTED BLOCKER
15	iemafzalhassan/full-stack_chatApp	main	Full-stack chat	MongoDB	DEPLOY
16	IsAmitprajapati/chat-app	main	Full-stack chat	MongoDB	DEPLOY
17	WebDevSimplified/Realtime-Simple-Chat-App	master	Node realtime chat	None	DEPLOY
18	machadop1407/react-socketio-chat-app	main	React + Socket.IO chat	None	DEPLOY
19	codersgyan/realtime-chat-app	master	Realtime Node chat	None	DEPLOY
20	ed-roh/chat-app	master	Chat application	None / repo-defined	DIAGNOSTIC
21	burakorkmez/threads-clone	master	MERN social clone	MongoDB	DEPLOY
22	earthcomfy/lets-chat	main	Realtime chat	None	DEPLOY
23	mihir0699/Video-Chat	main	WebRTC video chat	None	DEPLOY
24	miroslavpejic85/mirotalkwebrtc	master	WebRTC conferencing platform	MongoDB optional	DIAGNOSTIC
25	miroslavpejic85/call-me	main	WebRTC calling app	None / optional external services	DEPLOY
26	geerlingguy/temperature-monitor	master	Node monitoring web app	None / time-series external depending config	DIAGNOSTIC
27	tdjsnelling/sqtracker	master	Node web application	SQLite / repo-local	DEPLOY
28	syxanash/maxheadbox	main	Node web app	None	DEPLOY
29	orifmilod/iCinema	master	Cinema web application	Repo-defined / likely SQL	DIAGNOSTIC
30	quintuslabs/fashion-	master	React + Express fashion store	Repo-defined	DIAGNOSTIC

	cube				
31	noorjsdivs/orebishopping	master	React shopping frontend	None	DEPLOY
32	ed-roh/react-ecommerce	master	React + Strapi e-commerce	Strapi database	DIAGNOSTIC
33	JiyaGupta-cs/ShopNex	master	E-commerce web app	Repo-defined	DEPLOY
34	harshalhonde21/EcommerceSpectastyle	main	React + Express e-commerce	MongoDB	DEPLOY
35	levelopers/Ecommerce-Reactjs	master	React e-commerce frontend	None	DEPLOY
36	stefanogali/panic-panini-next	main	Next.js web application	None / external API if configured	DEPLOY
37	luciovilla/notion-nextjs-blog	main	Next.js + Notion blog	Notion external API	EXPECTED BLOCKER
38	kinngh/shopify-nextjs-prisma-app	main	Next.js + Shopify + Prisma	Prisma DB + Shopify external API	EXPECTED BLOCKER
39	twreporter/twreporter-react	master	React news application	None / external APIs	DIAGNOSTIC
40	ZainRk/Personal-Portfolio-React	master	React portfolio	None	DEPLOY
41	feross/TheAnnoyingSite.com	master	Browser JavaScript site	None	DIAGNOSTIC
42	SafdarJamal/quiz-app	master	React PWA quiz	None	DEPLOY
43	s-shemmee/TikTok-UI-Clone	main	React UI clone	None	DEPLOY
44	gabrieldim/Task-Tracker	main	Task tracker web app	None / browser storage	DEPLOY
45	1j01/mopaint	master	Pure browser paint application	None	EXPECTED BLOCKER
46	1j01/guitar	master	Pure browser guitar application	None	EXPECTED BLOCKER
47	berbaquero/reeddit	gh-pages	Static Reddit reader web app	None / external Reddit API	EXPECTED BLOCKER
48	libreprojects/libreprojects	gh-pages	Static directory website	None	EXPECTED BLOCKER
49	malaohu/forsaken-mail	dev	Disposable mail web app	Repo-defined / mail infrastructure	EXPECTED BLOCKER
50	bitshares/bitshares-ui	develop	Large SPA / blockchain UI	None / external blockchain APIs	DIAGNOSTIC
51	helloflask/watchlist	main	Flask movie watchlist	SQLite by default; DATABASE_URL supported	DEPLOY
52	rtzll/flask-todolist	main	Flask todo application	SQLite	DEPLOY
53	Kartones/flask-calendar	master	Flask calendar application	SQLite / repo-local	DEPLOY
54	OndiekOchieng/User-Authentication-in-Flask	main	Flask authentication app	SQLite / repo-local	DEPLOY
55	mjhea0/flask-redis-queue	main	Flask + Redis queue	Redis	EXPECTED BLOCKER
56	vanna-ai/vanna-flask	main	Flask data/LLM web app	External data source / optional	EXPECTED BLOCKER
57	howarder3/ChatGPT-Linebot-using-python-flask-on-vercel	master	Flask LINE/OpenAI bot	None	EXPECTED BLOCKER
58	HarshShah1997/Shopping-Cart	master	Flask shopping cart	Repo-defined SQL DB	DEPLOY
59	we45/Vulnerable-Flask-App	master	Flask intentionally vulnerable web app	SQLite / repo-local	DIAGNOSTIC
60	RafaelMiquelino/	master	Dash + Flask login	SQLite / repo-local	DEPLOY

	dash-flask-login				
61	okomarov/dash_on_flask	master	Dash embedded in Flask	SQLite from DATABASE_URL filename	DEPLOY
62	kantancoding/FlaskDS	master	Flask data-science web app	None / repo-local	DIAGNOSTIC
63	noahgift/flask-ml-azure-serverless	master	Flask ML application	None	DIAGNOSTIC
64	cenkalti/github-flask	master	Flask GitHub integration	None	EXPECTED BLOCKER
65	dennisivy/django_ecommerce_mod5	master	Django e-commerce	SQLite by default	DEPLOY
66	shyam999/Django-ecommerce	master	Django e-commerce	SQLite / repo-defined	DEPLOY
67	omarreda22/Django-eCommerce-Store	main	Django e-commerce store	SQLite / repo-defined	DEPLOY
68	developerpe/ecommerce_rest	master	Django REST e-commerce	SQLite / repo-defined	DEPLOY
69	zinmyoswe/React-and-Django-Ecommerce	master	Django + React e-commerce	SQLite / repo-defined	DIAGNOSTIC
70	hackstarsj/AmazonCloneEcommerceProjectUsingDjangoReact	master	Django + React Amazon clone	SQLite / repo-defined	DIAGNOSTIC
71	yashgo0018/django-ecommerce	master	Django e-commerce	SQLite / repo-defined	DEPLOY
72	umutbektas/django-ecommerce	master	Django e-commerce	SQLite / repo-defined	DEPLOY
73	zareisajad/online-shop-django	master	Django online shop	SQLite / repo-defined	DEPLOY
74	dev-rathankumar/greatkart-pre-deploy	main	Django GreatKart application	PostgreSQL recommended for production	DIAGNOSTIC
75	ruhulaminparvez/eCommerce	main	Django e-commerce	SQLite / repo-defined	DEPLOY
76	donaldte/django-ecom	main	Django e-commerce	SQLite / repo-defined	DEPLOY
77	dotpep/fullstack-ecommerce	main	Django/full-stack e-commerce	Repo-defined SQL DB	DIAGNOSTIC
78	DonGuillotine/auto-sales	main	Django auto sales web app	SQLite / repo-defined	DEPLOY
79	hamdi-bouasker/mytek	main	Django commerce/catalog app	SQLite / repo-defined	DEPLOY
80	Madhur215/Django-ChatApp	master	Django chat application	SQLite / repo-defined	DEPLOY
81	redis-developer/basic-redis-chat-app-demo-python	master	Python chat + Redis	Redis	DIAGNOSTIC
82	TheAbhijeet/Django_blog	master	Django blog	SQLite	DEPLOY
83	mdn/django-diy-blog	main	Django blog application	SQLite	DEPLOY
84	jukanntenn/django-blog-project	master	Django blog	SQLite / repo-defined	DEPLOY
85	yongxinz/tech-blog	master	Django technical blog	Repo-defined SQL DB	DIAGNOSTIC
86	Akash1362000/Django_BlogApp	master	Django blog	SQLite	DEPLOY
87	deepak2431/djangoBlog	master	Django blog	SQLite	DEPLOY
88	simonw/simonwillisonblog	main	Production Django blog	SQLite/PostgreSQL depending config	DIAGNOSTIC
89	leeyis/jbt_blog	master	Django blog	Repo-defined SQL DB	DIAGNOSTIC
90	r26zhao/	master	Django blog	SQLite / repo-defined	DEPLOY

	django_blog				
91	enjoy-binbin/Django-blog	master	Django blog	SQLite / repo-defined	DEPLOY
92	jwt1399/django-matery-blog	master	Django blog	SQLite / repo-defined	DEPLOY
93	akhil-s-kumar/django-blog-app	master	Django blog	SQLite	DEPLOY
94	mavenium/PyEditorial	master	Django editorial/CMS	Repo-defined SQL DB	DIAGNOSTIC
95	vas3k/vas3k.blog	main	Production Python/Django blog	PostgreSQL/Redis likely production services	EXPECTED BLOCKER
96	luizomf/projeto-blog-django-23	main	Django blog	SQLite	DEPLOY
97	reljicd/django-blog	master	Django blog	SQLite / repo-defined	DEPLOY
98	devmahmud/DjangoBlog	master	Django blog	SQLite / repo-defined	DEPLOY
99	codewithmuh/blogprojectdrf	master	Django REST Framework blog API	SQLite / repo-defined	DEPLOY
100	nephila/djangocms-blog	develop	Django CMS blog package	Package/library; requires host Django CMS project	EXPECTED BLOCKER

4. JavaScript repository tests (1-50)

Primary GitHub language: JavaScript. Incidental HTML/CSS/JSON/SQL or generated assets are allowed; the corpus intentionally excludes other primary-language targets.

JS-001 bradtraversy/proshop-v2

https://github.com/bradtraversy/proshop-v2/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	MERN e-commerce
Select	repo root; verify backend/ + frontend/ services
Database	MongoDB

Sample ENV	`NODE_ENV=production`
	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`JWT_SECRET=dg-test-jwt-01`
	`PAYPAL_CLIENT_ID=sb-test-client`
	`PAYPAL_APP_SECRET=sb-test-secret`
	`PAYPAL_API_URL=https://api-m.sandbox.paypal.com`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Full-stack root scripts + frontend/backend + Mongo/JWT/PayPal env
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-002 burakorkmez/mern-ecommerce

https://github.com/burakorkmez/mern-ecommerce/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: PARTIAL_ENV

Stack	MERN e-commerce + Redis + Stripe
Select	repo root; select backend + frontend
Database	MongoDB + Redis

Sample ENV	`NODE_ENV=production`
	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`UPSTASH_REDIS_URL=<TEST_REDIS_URL>`
	`STRIPE_SECRET_KEY=sk_test_REPLACE_ME`
	`CLOUDINARY_CLOUD_NAME=dg-test`
	`CLOUDINARY_API_KEY=test-key`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Multiple external capabilities; verify env sealing and service isolation
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-003 bluebits-academy/mern-stack-ecommerce

https://github.com/bluebits-academy/mern-stack-ecommerce/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	MERN e-commerce
Select	select backend; exclude Expo/mobile directories from web deployment
Database	MongoDB

Sample ENV	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`NODE_ENV=production`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Mixed repository content; service-boundary selection
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-004 basir/mern-amazona

https://github.com/basir/mern-amazona/tree/master

Branch: master | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	MERN e-commerce
Select	select backend + frontend
Database	MongoDB

Sample ENV	`NODE_ENV=production`
	`MONGODB_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`BASE_URL=https://example.invalid`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Backend/frontend split and production build
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-005 techinfo-youtube/ecommerce-app-2023

https://github.com/techinfo-youtube/ecommerce-app-2023/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Express + React e-commerce
Select	repo root; client/ is frontend, root server is backend
Database	MongoDB
Sample ENV	`NODE_ENV=production` `MONGO_URL=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Root backend + nested client + Mongo URL
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-006 RishiBakshii/mern-ecommerce

https://github.com/RishiBakshii/mern-ecommerce/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	MERN e-commerce
Select	repo root; accept detected client/server services
Database	MongoDB
Sample ENV	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Typical MERN service detection
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-007 IsAmitprajapati/BlinkIt-Clone-Full-Stack-Ecommerce

https://github.com/IsAmitprajapati/BlinkIt-Clone-Full-Stack-Ecommerce/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: FULL_ENV

Stack	MERN e-commerce clone
Select	repo root; accept detected frontend/backend services
Database	MongoDB
Sample ENV	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>` `NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Larger real-user full-stack repo
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-008 dhatGuy/PERN-Store

https://github.com/dhatGuy/PERN-Store/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	PERN store
Select	repo root; select API + web service if both detected
Database	PostgreSQL
Sample ENV	`DATABASE_URL=<DEPLOYGUARD_MANAGED_POSTGRES_URL>` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Postgres instead of Mongo; database alias mapping
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-009 eknoorpreet/dev.to-clone

https://github.com/eknoorpreet/dev.to-clone/tree/main

Branch: main | Layout: multi | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	React + Express social/blog clone
Select	repo root; select server/ + client/
Database	MongoDB

Sample ENV	`NODE_ENV=production`
	`PORT=<PLATFORM>`
	`CLIENT_URL=https://example.invalid`
	`JWT_KEY=dg-test-jwt`
	`CLOUDINARY_CLOUD_NAME=dg-test`
	`CLOUDINARY_API_KEY=test-key`
	`CLOUDINARY_API_SECRET=test-secret`
	`TWITTER_CONSUMER_KEY=test-key`
	`TWITTER_CONSUMER_SECRET=test-secret`
	`REACT_APP_BASE_URL=https://example.invalid/api`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Many ENV classes: JWT, client URL, Cloudinary, OAuth, public build env
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-010 b30wulffz/job-portal

https://github.com/b30wulffz/job-portal/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Full-stack job portal
Select	repo root; accept detected web/API services
Database	MongoDB
Sample ENV	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Auth + CRUD + multi-service detection
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-011 TannerReynolds/ShareX-Upload-Server

https://github.com/TannerReynolds/ShareX-Upload-Server/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: PARTIAL_ENV

Stack	Node upload server
Select	repo root
Database	None / filesystem
Sample ENV	`NODE_ENV=production`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Writable-path/runtime persistence behavior
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-012 k-yle/rtsp-relay

https://github.com/k-yle/rtsp-relay/tree/main

Branch: main | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Node media relay
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Long-running process and media/network package behavior
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-013 zhravan/github-readme-quotes

https://github.com/zhravan/github-readme-quotes/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Express + frontend image/quote service
Select	repo root; server root + frontend/
Database	None / external quote service

Sample ENV	`NODE_ENV=PRODUCTION`
	`SERVICE_URL=https://example.invalid`
	`PORT=<PLATFORM>`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	SERVICE_URL + production frontend serving
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-014 immers-space/activitypub-express

https://github.com/immers-space/activitypub-express/tree/master

Branch: master | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Express ActivityPub service/library
Select	repo root
Database	None / app-dependent
Sample ENV	`NODE_ENV=production` `REQUIRED_TEST_VALUE=<INTENTIONALLY_OMITTED>`
ENV basis	Deliberate negative configuration; validate a clear blocker rather than a misleading runtime failure.
What this tests	Library-like repository may lack standalone product entrypoint; blocker correctness
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-015 iemafzalhassan/full-stack_chatApp

https://github.com/iemafzalhassan/full-stack_chatApp/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Full-stack chat
Select	repo root; select frontend + backend
Database	MongoDB

Sample ENV	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`NODE_ENV=production`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Sockets + auth + two services
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-016 IsAmitprajapati/chat-app

https://github.com/IsAmitprajapati/chat-app/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Full-stack chat
Select	repo root; select client/server services
Database	MongoDB
Sample ENV	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Realtime + database
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-017 WebDevSimplified/Realtime-Simple-Chat-App

https://github.com/WebDevSimplified/Realtime-Simple-Chat-App/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Node realtime chat
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Simple long-running socket server
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-018 machadop1407/react-socketio-chat-app

https://github.com/machadop1407/react-socketio-chat-app/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	React + Socket.IO chat
Select	repo root; client + server
Database	None
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Two-service websocket deployment
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-019 codersgyan/realtime-chat-app

https://github.com/codersgyan/realtime-chat-app/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Realtime Node chat
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Non-main branch plus websocket runtime
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-020 ed-roh/chat-app

https://github.com/ed-roh/chat-app/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	Chat application
Select	repo root
Database	None / repo-defined
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Small real app; start-command inference
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-021 burakorkmez/threads-clone

https://github.com/burakorkmez/threads-clone/tree/master

Branch: master | Layout: multi | Intent: DEPLOY | ENV: FULL_ENV

Stack	MERN social clone
Select	repo root; backend + frontend
Database	MongoDB

Sample ENV	`NODE_ENV=production`
	`MONGO_URI=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`JWT_SECRET=dg-test-jwt`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	MONGO_URI + JWT and frontend build
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-022 earthcomfy/lets-chat

https://github.com/earthcomfy/lets-chat/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Realtime chat
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Small socket application
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-023 mihir0699/Video-Chat

https://github.com/mihir0699/Video-Chat/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	WebRTC video chat
Select	repo root; Node server + client
Database	None
Sample ENV	`NODE_ENV=production` `PORT=<PLATFORM>`
ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	WebRTC signaling server and PORT handling
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-024 miroslavpejic85/mirotalkwebrtc

https://github.com/miroslavpejic85/mirotalkwebrtc/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	WebRTC conferencing platform
Select	repo root; backend/ plus frontend/static assets
Database	MongoDB optional

Sample ENV	`SERVER_HOST=0.0.0.0`
	`SERVER_PORT=<PLATFORM>`
	`SERVER_URL=https://example.invalid`
	`MONGO_URL=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`JWT_KEY=dg-test-jwt`
	`JWT_EXP=1h`
	`ADMIN_EMAIL=admin@example.invalid`
	`CORS_ORIGIN=*`
	`CORS_METHODS=GET,POST`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Large env surface, optional SaaS/Stripe/Sentry/ngrok features
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-025 miroslavpejic85/call-me

https://github.com/miroslavpejic85/call-me/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	WebRTC calling app
Select	repo root
Database	None / optional external services
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Modern Node realtime app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-026 geerlingguy/temperature-monitor

https://github.com/geerlingguy/temperature-monitor/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: PARTIAL_ENV

Stack	Node monitoring web app
Select	repo root
Database	None / time-series external depending config
Sample ENV	`NODE_ENV=production`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Non-main branch and runtime hardware/external dependency behavior
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-027 tdjsnelling/sqtracker

https://github.com/tdjsnelling/sqtracker/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Node web application
Select	repo root
Database	SQLite / repo-local
Sample ENV	`NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Local database file and production runtime
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-028 syxanash/maxheadbox

https://github.com/syxanash/maxheadbox/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Node web app
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Small production-style Node app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-029 orifmilod/iCinema

https://github.com/orifmilod/iCinema/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Cinema web application
Select	repo root
Database	Repo-defined / likely SQL
Sample ENV	`NODE_ENV=production`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Legacy app dependency/runtime detection
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-030 quintuslabs/fashion-cube

https://github.com/quintuslabs/fashion-cube/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	React + Express fashion store
Select	repo root; frontend root + server/ecommerce backend
Database	Repo-defined
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Nested backend and frontend service boundaries
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-031 noorjsdivs/orebishopping

https://github.com/noorjsdivs/orebishopping/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	React shopping frontend
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Frontend-only build/static serving
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-032 ed-roh/react-ecommerce

https://github.com/ed-roh/react-ecommerce/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	React + Strapi e-commerce
Select	repo root; client + server
Database	Strapi database
Sample ENV	`NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Stripe secret + external CMS/runtime split
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-033 JiyaGupta-cs/ShopNex

https://github.com/JiyaGupta-cs/ShopNex/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	E-commerce web app
Select	repo root
Database	Repo-defined
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Non-main branch app detection
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-034 harshalhonde21/EcommerceSpectastyle

https://github.com/harshalhonde21/EcommerceSpectastyle/tree/main

Branch: main | Layout: multi | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	React + Express e-commerce
Select	repo root; Backend/ + Frontend/
Database	MongoDB

Sample ENV	`NODE_ENV=production`
	`MONGO_URL=<DEPLOYGUARD_MANAGED_MONGODB_URL>`
	`SECRET=dg-test-jwt`
	`PORT=<PLATFORM>`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Case-sensitive service paths + MONGO_URL + JWT secret
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-035 levelopers/Ecommerce-Reactjs

https://github.com/levelopers/Ecommerce-Reactjs/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	React e-commerce frontend
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Legacy React production build
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-036 stefanogali/panic-panini-next

https://github.com/stefanogali/panic-panini-next/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Next.js web application
Select	repo root
Database	None / external API if configured
Sample ENV	`NODE_ENV=production`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Next build/start behavior
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-037 luciovilla/notion-nextjs-blog

https://github.com/luciovilla/notion-nextjs-blog/tree/main

Branch: main | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Next.js + Notion blog
Select	repo root
Database	Notion external API
Sample ENV	`NOTION_TOKEN=<INTENTIONALLY_OMITTED>` `NOTION_DATABASE_ID=test-db-id`
ENV basis	Deliberate negative test: one required external credential is omitted.
What this tests	Deliberately omit Notion credential to test required external config blocker
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-038 kinngh/shopify-nextjs-prisma-app

https://github.com/kinngh/shopify-nextjs-prisma-app/tree/main

Branch: main | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Next.js + Shopify + Prisma
Select	repo root
Database	Prisma DB + Shopify external API

Sample ENV	`SHOPIFY_API_KEY=<INTENTIONALLY_OMITTED>`
	`SHOPIFY_API_SECRET=test-secret`
	`DATABASE_URL=<DEPLOYGUARD_MANAGED_POSTGRES_URL>`

ENV basis	Deliberate negative test: one required external credential is omitted.
What this tests	External merchant credentials and DB config blocker
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-039 twreporter/twreporter-react

https://github.com/twreporter/twreporter-react/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	React news application
Select	repo root
Database	None / external APIs
Sample ENV	`NODE_ENV=production`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Large legacy React dependency graph
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-040 ZainRk/Personal-Portfolio-React

https://github.com/ZainRk/Personal-Portfolio-React/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	React portfolio
Select	repo root
Database	None
Sample ENV	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app` `DG_EXTRA_TWO=42`
ENV basis	Deliberate unknown ENV injection; application is not expected to consume these keys.
What this tests	Clean frontend-only baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-041 feross/TheAnnoyingSite.com

https://github.com/feross/TheAnnoyingSite.com/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: NO_ENV

Stack	Browser JavaScript site
Select	repo root
Database	None
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Static/browser app; test whether Railpack finds a valid static build
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

JS-042 SafdarJamal/quiz-app

https://github.com/SafdarJamal/quiz-app/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	React PWA quiz
Select	repo root
Database	None
Sample ENV	`NODE_ENV=production`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	PWA/service-worker production build
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-043 s-shemmee/TikTok-UI-Clone

https://github.com/s-shemmee/TikTok-UI-Clone/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: NO_ENV

Stack	React UI clone
Select	repo root
Database	None
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Modern frontend build baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-044 gabrieldim/Task-Tracker

https://github.com/gabrieldim/Task-Tracker/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Task tracker web app
Select	repo root
Database	None / browser storage
Sample ENV	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app` `DG_EXTRA_TWO=42`
ENV basis	Deliberate unknown ENV injection; application is not expected to consume these keys.
What this tests	Small app baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

JS-045 1j01/mopaint

https://github.com/1j01/mopaint/tree/master

Branch: master | Layout: single | Intent: EXPECTED BLOCKER | ENV: NO_ENV

Stack	Pure browser paint application
Select	repo root
Database	None
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Static JavaScript without a server/package contract should be safely blocked if unsupported
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-046 1j01/guitar

https://github.com/1j01/guitar/tree/master

Branch: master | Layout: single | Intent: EXPECTED BLOCKER | ENV: NO_ENV

Stack	Pure browser guitar application
Select	repo root
Database	None
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Static browser-only repository blocker
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-047 berbaquero/reeddit

https://github.com/berbaquero/reeddit/tree/gh-pages

Branch: gh-pages | Layout: single | Intent: EXPECTED BLOCKER | ENV: NO_ENV

Stack	Static Reddit reader web app
Select	gh-pages branch root
Database	None / external Reddit API
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Explicit gh-pages branch; static artifact/no normal server contract
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-048 libreprojects/libreprojects

https://github.com/libreprojects/libreprojects/tree/gh-pages

Branch: gh-pages | Layout: single | Intent: EXPECTED BLOCKER | ENV: EXTRA_UNKNOWN

Stack	Static directory website
Select	gh-pages branch root
Database	None
Sample ENV	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app` `DG_EXTRA_TWO=42`
ENV basis	Deliberate unknown ENV injection; application is not expected to consume these keys.
What this tests	Non-main gh-pages branch and static-only blocker
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-049 malaohu/forsaken-mail

https://github.com/malaohu/forsaken-mail/tree/dev

Branch: dev | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Disposable mail web app
Select	dev branch root
Database	Repo-defined / mail infrastructure
Sample ENV	`MAIL_HOST=<INTENTIONALLY_OMITTED>` `MAIL_DOMAIN=example.invalid`
ENV basis	Deliberate negative test: one required external credential is omitted.
What this tests	Explicit dev branch and external mail-service dependency
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

JS-050 bitshares/bitshares-ui

https://github.com/bitshares/bitshares-ui/tree/develop

Branch: develop | Layout: single | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	Large SPA / blockchain UI
Select	develop branch root
Database	None / external blockchain APIs
Sample ENV	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Large dependency graph + develop branch + external network dependency
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

5. Python repository tests (51-100)

Primary GitHub language: Python. Incidental HTML/CSS/JSON/SQL or generated assets are allowed; the corpus intentionally excludes other primary-language targets.

PY-051 helloflask/watchlist

https://github.com/helloflask/watchlist/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Flask movie watchlist
Select	repo root
Database	SQLite by default; DATABASE_URL supported
Sample ENV	`SECRET_KEY=dg-test-secret` `DATABASE_URL=sqlite:////tmp/watchlist.db`
ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Flask baseline with SECRET_KEY and DB URL
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-052 rtzll/flask-todolist

https://github.com/rtzll/flask-todolist/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Flask todo application
Select	repo root
Database	SQLite

Sample ENV	`APP_CONFIG=production`
	`SECRET_KEY=dg-test-secret`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	APP_CONFIG + SECRET_KEY; small Flask baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-053 Kartones/flask-calendar

https://github.com/Kartones/flask-calendar/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Flask calendar application
Select	repo root
Database	SQLite / repo-local
Sample ENV	`SECRET_KEY=dg-test-secret` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Non-main Flask app + local DB
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-054 OndiekOchieng/User-Authentication-in-Flask

https://github.com/OndiekOchieng/User-Authentication-in-Flask/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Flask authentication app
Select	repo root
Database	SQLite / repo-local
Sample ENV	`SECRET_KEY=dg-test-secret`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Session/auth runtime baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-055 mjhea0/flask-redis-queue

https://github.com/mjhea0/flask-redis-queue/tree/main

Branch: main | Layout: multi | Intent: EXPECTED BLOCKER | ENV: EXTRA_UNKNOWN

Stack	Flask + Redis queue
Select	repo root; web + worker dependency
Database	Redis

Sample ENV	`APP_SETTINGS=project.server.config.ProductionConfig`
	`REDIS_URL=<TEST_REDIS_URL>`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	Worker/Redis topology beyond single-web-service path
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

PY-056 vanna-ai/vanna-flask

https://github.com/vanna-ai/vanna-flask/tree/main

Branch: main | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Flask data/LLM web app
Select	repo root
Database	External data source / optional
Sample ENV	`OPENAI_API_KEY=<INTENTIONALLY_OMITTED>`
ENV basis	Deliberate negative test: one required external credential is omitted.
What this tests	Missing LLM/API credential expected blocker
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

PY-057 howarder3/ChatGPT-Linebot-using-python-flask-on-vercel

https://github.com/howarder3/ChatGPT-Linebot-using-python-flask-on-vercel/tree/master

Branch: master | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Flask LINE/OpenAI bot
Select	repo root
Database	None

Sample ENV	`LINE_CHANNEL_ACCESS_TOKEN=<INTENTIONALLY_OMITTED>`
	`LINE_CHANNEL_SECRET=test-secret`
	`OPENAI_API_KEY=test-placeholder`

ENV basis	Deliberate negative test: one required external credential is omitted.
What this tests	Third-party LINE/OpenAI credentials deliberately absent
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

PY-058 HarshShah1997/Shopping-Cart

https://github.com/HarshShah1997/Shopping-Cart/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Flask shopping cart
Select	repo root
Database	Repo-defined SQL DB
Sample ENV	`SECRET_KEY=dg-test-secret` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Larger Flask CRUD application
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-059 we45/Vulnerable-Flask-App

https://github.com/we45/Vulnerable-Flask-App/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Flask intentionally vulnerable web app
Select	repo root
Database	SQLite / repo-local
Sample ENV	`SECRET_KEY=dg-test-secret`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Security-scanner/blocker evidence; deploy only in isolated test account
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-060 RafaelMiquelino/dash-flask-login

https://github.com/RafaelMiquelino/dash-flask-login/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Dash + Flask login
Select	repo root
Database	SQLite / repo-local
Sample ENV	`SECRET_KEY=dg-test-secret` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Dash-on-Flask startup inference
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-061 okomarov/dash_on_flask

https://github.com/okomarov/dash_on_flask/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Dash embedded in Flask
Select	repo root
Database	SQLite from DATABASE_URL filename

Sample ENV	`SECRET_KEY=dg-test-secret`
	`DATABASE_URL=dashboard.db`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Observed key names in public repo code; values here are synthetic/test-only.
What this tests	SECRET_KEY + DATABASE_URL exact env handling
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-062 kantancoding/FlaskDS

https://github.com/kantancoding/FlaskDS/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Flask data-science web app
Select	repo root
Database	None / repo-local
Sample ENV	`SECRET_KEY=dg-test-secret`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Native/scientific dependency build behavior
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-063 noahgift/flask-ml-azure-serverless

https://github.com/noahgift/flask-ml-azure-serverless/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	Flask ML application
Select	repo root
Database	None
Sample ENV	`SECRET_KEY=dg-test-secret` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	ML dependency size and serverless-origin assumptions
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-064 cenkalti/github-flask

https://github.com/cenkalti/github-flask/tree/master

Branch: master | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Flask GitHub integration
Select	repo root
Database	None
Sample ENV	`GITHUB_CLIENT_ID=<INTENTIONALLY_OMITTED>` `GITHUB_CLIENT_SECRET=test-secret`
ENV basis	Deliberate negative test: one required external credential is omitted.
What this tests	GitHub OAuth/API credentials deliberately missing
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

PY-065 dennisivy/django_ecommerce_mod5

https://github.com/dennisivy/django_ecommerce_mod5/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django e-commerce
Select	repo root
Database	SQLite by default
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Django WSGI baseline and static files
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-066 shyam999/Django-ecommerce

https://github.com/shyam999/Django-ecommerce/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Django e-commerce
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Non-main Django e-commerce
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-067 omarreda22/Django-eCommerce-Store

https://github.com/omarreda22/Django-eCommerce-Store/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django e-commerce store
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Django main branch baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-068 developerpe/ecommerce_rest

https://github.com/developerpe/ecommerce_rest/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django REST e-commerce
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	REST API startup and migration behavior
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-069 zinmyoswe/React-and-Django-Ecommerce

https://github.com/zinmyoswe/React-and-Django-Ecommerce/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Django + React e-commerce
Select	repo root; detect Django backend + frontend
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Mixed Python/JS multi-service repository with Python primary language
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-070 hackstarsj/AmazonCloneEcommerceProjectUsingDjangoReact

https://github.com/hackstarsj/AmazonCloneEcommerceProjectUsingDjangoReact/tree/master

Branch: master | Layout: multi | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	Django + React Amazon clone
Select	repo root; backend + frontend
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Larger mixed service topology
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-071 yashgo0018/django-ecommerce

https://github.com/yashgo0018/django-ecommerce/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Django e-commerce
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Django baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-072 umutbektas/django-ecommerce

https://github.com/umutbektas/django-ecommerce/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django e-commerce
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Django baseline with alternate project structure
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-073 zareisajad/online-shop-django

https://github.com/zareisajad/online-shop-django/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django online shop
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Django shop baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-074 dev-rathankumar/greatkart-pre-deploy

https://github.com/dev-rathankumar/greatkart-pre-deploy/tree/main

Branch: main | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Django GreatKart application
Select	repo root
Database	PostgreSQL recommended for production
Sample ENV	`DATABASE_URL=<DEPLOYGUARD_MANAGED_POSTGRES_URL>` `DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Pre-deploy configuration and production DB mapping
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-075 ruhulaminparvez/eCommerce

https://github.com/ruhulaminparvez/eCommerce/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django e-commerce
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Main-branch Django app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-076 donaldte/django-ecom

https://github.com/donaldte/django-ecom/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Django e-commerce
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Django app with main branch
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-077 dotpep/fullstack-ecommerce

https://github.com/dotpep/fullstack-ecommerce/tree/main

Branch: main | Layout: multi | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Django/full-stack e-commerce
Select	repo root; detect backend/frontend if present
Database	Repo-defined SQL DB
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Full-stack service-boundary detection
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-078 DonGuillotine/auto-sales

https://github.com/DonGuillotine/auto-sales/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django auto sales web app
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Non-tutorial business-domain Django app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-079 hamdi-bouasker/mytek

https://github.com/hamdi-bouasker/mytek/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django commerce/catalog app
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Business-domain Django app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-080 Madhur215/Django-ChatApp

https://github.com/Madhur215/Django-ChatApp/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django chat application
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Chat workload on Django
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-081 redis-developer/basic-redis-chat-app-demo-python

https://github.com/redis-developer/basic-redis-chat-app-demo-python/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: PARTIAL_ENV

Stack	Python chat + Redis
Select	repo root
Database	Redis
Sample ENV	`REDIS_URL=<TEST_REDIS_URL>`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Redis dependency; use managed/external REDIS_URL
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-082 TheAbhijeet/Django_blog

https://github.com/TheAbhijeet/Django_blog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: NO_ENV

Stack	Django blog
Select	repo root
Database	SQLite
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Small Django baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-083 mdn/django-diy-blog

https://github.com/mdn/django-diy-blog/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: NO_ENV

Stack	Django blog application
Select	repo root
Database	SQLite
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Well-structured Django app; no starter generator
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-084 jukanntenn/django-blog-project

https://github.com/jukanntenn/django-blog-project/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django blog
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Larger blog app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-085 yongxinz/tech-blog

https://github.com/yongxinz/tech-blog/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	Django technical blog
Select	repo root
Database	Repo-defined SQL DB
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Large content project and dependency graph
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-086 Akash1362000/Django_BlogApp

https://github.com/Akash1362000/Django_BlogApp/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: NO_ENV

Stack	Django blog
Select	repo root
Database	SQLite
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Django blog baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-087 deepak2431/djangoBlog

https://github.com/deepak2431/djangoBlog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: NO_ENV

Stack	Django blog
Select	repo root
Database	SQLite
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Django baseline on master branch
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-088 simonw/simonwillisonblog

https://github.com/simonw/simonwillisonblog/tree/main

Branch: main | Layout: single | Intent: DIAGNOSTIC | ENV: EXTRA_UNKNOWN

Stack	Production Django blog
Select	repo root
Database	SQLite/PostgreSQL depending config

Sample ENV	`DATABASE_URL=<DEPLOYGUARD_MANAGED_POSTGRES_URL>`
	`DEPLOYGUARD_ENV_TEST=django-corpus`
	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`

ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Real production codebase, nontrivial dependencies/config
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-089 leeyis/jbt_blog

https://github.com/leeyis/jbt_blog/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Django blog
Select	repo root
Database	Repo-defined SQL DB
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	Larger legacy Django app
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-090 r26zhao/django_blog

https://github.com/r26zhao/django_blog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django blog
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Stack-derived minimum plus an intentionally unknown key.
What this tests	Django blog baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-091 enjoy-binbin/Django-blog

https://github.com/enjoy-binbin/Django-blog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: PARTIAL_ENV

Stack	Django blog
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Partial configuration test; optional/noncritical values intentionally withheld.
What this tests	Django blog baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-092 jwt1399/django-matery-blog

https://github.com/jwt1399/django-matery-blog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django blog
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Theme/static file handling
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-093 akhil-s-kumar/django-blog-app

https://github.com/akhil-s-kumar/django-blog-app/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: NO_ENV

Stack	Django blog
Select	repo root
Database	SQLite
Sample ENV	`(none - do not add user ENV for this case)`
ENV basis	Selected path should not require user ENV; platform-owned PORT/HOST remain platform concerns.
What this tests	Small Django app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-094 mavenium/PyEditorial

https://github.com/mavenium/PyEditorial/tree/master

Branch: master | Layout: single | Intent: DIAGNOSTIC | ENV: FULL_ENV

Stack	Django editorial/CMS
Select	repo root
Database	Repo-defined SQL DB
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	CMS-style static/media and DB behavior
Expected	No pre-declared PASS guarantee. Use this repository to expose compatibility, dependency, service-boundary, or runtime assumptions and classify the terminal result.

PY-095 vas3k/vas3k.blog

https://github.com/vas3k/vas3k.blog/tree/main

Branch: main | Layout: single | Intent: EXPECTED BLOCKER | ENV: MISSING_REQUIRED

Stack	Production Python/Django blog
Select	repo root
Database	PostgreSQL/Redis likely production services

Sample ENV	`DATABASE_URL=<DEPLOYGUARD_MANAGED_POSTGRES_URL>`
	`REDIS_URL=<TEST_REDIS_URL>`
	`DEPLOYGUARD_ENV_TEST=django-corpus`
	`REQUIRED_TEST_VALUE=<INTENTIONALLY_OMITTED>`

ENV basis	Deliberate negative configuration; validate a clear blocker rather than a misleading runtime failure.
What this tests	Complex external-service production topology; blocker/isolation test
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

PY-096 luizomf/projeto-blog-django-23

https://github.com/luizomf/projeto-blog-django-23/tree/main

Branch: main | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django blog
Select	repo root
Database	SQLite
Sample ENV	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app` `DG_EXTRA_TWO=42`
ENV basis	Deliberate unknown ENV injection; application is not expected to consume these keys.
What this tests	Modern small Django app
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-097 reljicd/django-blog

https://github.com/reljicd/django-blog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django blog
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Stack/repository-derived deployment-test values; replace placeholders only where the app truly needs an external service.
What this tests	Older Django branch/runtime compatibility
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-098 devmahmud/DjangoBlog

https://github.com/devmahmud/DjangoBlog/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: EXTRA_UNKNOWN

Stack	Django blog
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus` `DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app`
ENV basis	Tests preservation/handling of user-owned unknown ENV values.
What this tests	Django baseline
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-099 codewithmuh/blogprojectdrf

https://github.com/codewithmuh/blogprojectdrf/tree/master

Branch: master | Layout: single | Intent: DEPLOY | ENV: FULL_ENV

Stack	Django REST Framework blog API
Select	repo root
Database	SQLite / repo-defined
Sample ENV	`DEPLOYGUARD_ENV_TEST=django-corpus`
ENV basis	Deployment-test configuration; values are non-secret placeholders.
What this tests	DRF API deployment
Expected	Expected target: reach LIVE if repository/runtime dependencies are compatible. Any failure must be classified from actual DeployGuard evidence.

PY-100 nephila/djangocms-blog

https://github.com/nephila/djangocms-blog/tree/develop

Branch: develop | Layout: single | Intent: EXPECTED BLOCKER | ENV: EXTRA_UNKNOWN

Stack	Django CMS blog package
Select	develop branch root
Database	Package/library; requires host Django CMS project
Sample ENV	`DEPLOYGUARD_UNUSED_TEST=should_reach_container_but_be_ignored_by_app` `DG_EXTRA_TWO=42`
ENV basis	Deliberate unknown ENV injection; application is not expected to consume these keys.
What this tests	Develop branch + reusable package should be blocked as non-standalone
Expected	Expected target: a clean, explainable blocker or deterministic negative result. Do not modify DeployGuard or the repository merely to force deployment.

6. Result recording contract

For every repository, record one terminal classification and enough evidence to reproduce it. Do not collapse expected blockers into generic failures.

ID	Repo	Branch	Result	Stage	Duration	Evidence / root cause

Suggested terminal labels: PASS, EXPECTED_BLOCKER, CONFIRMED_DEFECT, EXTERNAL_DEPENDENCY_BLOCKER, REPOSITORY_DEFECT, UNVERIFIED. Keep build failures separate from infrastructure failures and runtime-health failures.

Recommended final metrics

- 100-repository attempted count and completion count
- Deploy success rate among DEPLOY-intent cases
- Expected-blocker precision (clean blocker vs misleading failure)
- P50/P95 deployment duration
- Failure stage distribution: source/detection/build/security/infrastructure/runtime
- Branch-selection failures
- ENV preservation/rejection discrepancies
- Database attachment/alias failures
- Multi-service isolation failures
- 30-40 concurrent stress-run queue/throttle/failure-isolation behavior