Quick Reference Guide

Module 1: Foundations of LLMs for Retrieval-Aware Systems

Learning Outcomes:

- Explain key limitations of LLMs that affect reliability and grounding.
- Implement a basic application that interacts with an LLM via an API.
- Determine when external retrieval is required for a given LLM-powered use case.
- Explain how the specificity, relevance, and accuracy of retrieved information affect LLM output quality.

Key Concepts

Understanding LLM Behavior and Limitations

- Large language models (LLMs) generate responses by predicting the next token from a probability distribution conditioned on prior context. This enables powerful reasoning over learned patterns but does not include an explicit factual verification step against ground truth, which is why fluent, confident outputs can still be factually wrong.
- Outputs are based on learned patterns from training data, not verified or real-time knowledge.
- Fluency does not guarantee correctness — models can produce confident but incorrect answers (hallucinations).
- Common failure modes include hallucination, knowledge gaps, knowledge staleness, and context limitations — both in total window size and in uneven recall across long contexts (e.g., reduced retrieval of information placed in the middle of a prompt).
- Context windows are finite (often hundreds of thousands to millions of tokens in modern models), but recall within the window is not uniform. Models tend to retrieve information more reliably from the beginning and end of the context than from the middle ("lost-in-the-middle" effect), which has implications for prompt design and retrieval strategies.
- Prompting alone cannot resolve missing, outdated, or private information.
- These limitations are inherent to how LLMs work, not edge cases.
- Different users may observe slightly different behaviors even with similar prompts, which highlights the probabilistic nature of LLM outputs.

© MIT xPRO® [current year to be added]. All rights reserved.

From LLM Limitations to the Need for Retrieval

- Retrieval augments LLMs by providing external, up-to-date, or domain-specific information.
- LLM-only systems rely on internal knowledge; retrieval-enabled systems ground outputs in real data.
- Retrieval improves performance when answering questions that require accuracy, specificity, or current information. For example, without retrieval, a model might give outdated World Cup results, while with retrieval, it can provide the exact final score of Argentina vs. France in 2022.
- The simple addition of more context does not improve results — irrelevant or excessive information can degrade output quality.
- Effective retrieval depends on selecting information that is:
- Relevant to the query
- Specific enough to answer the task
- Accurate and reliable
- The quality of retrieved information directly impacts system performance and user trust.
- Designers must consider that retrieval choices directly influence whether users perceive the system as trustworthy and reliable.

Applying Concepts to Your Project

- Building LLM applications involves interacting with models via APIs and testing behavior across prompts.
- Observing model outputs reveals patterns of failure such as inconsistency, vagueness, or incorrect answers.
- Retrieval is required when:
- Information is domain specific or proprietary
- Data is frequently changing or time sensitive
- High accuracy and reliability are critical
- Retrieval may not be necessary when:
- The task relies only on transformation (e.g., summarization and rewriting)
- All required information is already provided in the prompt
- Determining retrieval needs is a key system design decision, not just a technical implementation detail. These design choices — when and how to retrieve — form the foundation for building reliable, user-centered LLM applications.

© MIT xPRO® [current year to be added]. All rights reserved.