

National University of Computer and Emerging Sciences, Lahore Campus



Course:
Program:
Deadline:
Section:

Object Oriented Programming
BS (Data Science)
17-April-22
2A and 2C
HomeWork_1

Course Code: CS-1004
Semester: Spring 2022
Total Marks: 20

Instruction/Notes:

In case of plagiarism/cheating, this activity will be marked as zero.

Task#1: Create a 'Set' ADT, which will implement the basic operations of Set concept in mathematics. The data members and operations needed for this ADT are given below.

Data Members:

- int * data
- int noOfElements
- int capacity

Supported Operations:

The class 'Set' should support following operations

1. **Set (int cap = 0);**
Default parameterized constructor. Sets 'cap' to 'capacity' and initializes rest of the data members accordingly. If user sends any invalid value then sets the cap to default value.
2. **Set(const Set & ref);**
overloaded copy constructor to implement deep copy.
3. **~Set()**
Free the dynamically allocated memory.
4. **void insert (int element);**
Stores the element in the Set.
Remember! Set is a collection of distinct elements. If the array is full, then resize the capacity of Set by double.
5. **void remove (int element);**
remove the element from the Set. If the noOfElements in the Set are equal to or less than 50% of capacity then shrink the Set by 25% i.e., if the capacity was 12 and noOfElements are less than equals to 6 then the new Set should be of the capacity equals to 9.
6. **int getCardinality() const;**
returns the number of elements in the set.
7. **Set calcUnion (const Set & s2) const;**
returns a new Set object which contains the union of 's2' set and calling object set.

8. **Set calcSymmetricDifference (const Set & s2);**
returns a new Set object which contains the symmetric Difference of 's2' set and calling object set.
Where symmetric difference is: $A \Delta B = A \cup B - A \cap B$
9. **Set calcDifference (const Set & s2) const;**
returns a new Set object which contains the intersection of 's2' set and calling object set.
10. **int isMember (int val) const;**
returns 1 if 'val' is member of the set otherwise return 0.
11. **int isSubSet (const Set & s2) const;**
returns 1 if s2 is proper subset of calling object set, return 2 if improper subset otherwise returns 0.
12. **void reSize (int newcapacity);**
resize the set to new capacity. Make sure that elements in old set should be preserved in the new set if possible.
13. **void update(int prVal, int curVal);**
This function should replace the previous value(prVal) with current value (curVal). Make sure the property of set should not be violated (**distinct elements**). If the prVal is not present in the array, then display a message "**Target value not found**". In-case of successful modification then display a message "**Record update successfully**". If prVal is present in the set but curVal is also already available, then display a message "Violation set property. Can't Modify the data".
14. **void show() const;**
This function should display the contents of Set for calling object.

Write main function to test the functionalities of supporting functions of Set ADT

Task#2:

Create a class fraction with the following data members and supporting member functions.

Data Members

- static int fractionsCount;
- int numerator;
- int denominator;

Member functions:

1. **fraction(int n = 1, int d = 1);**
default parameterized constructor assigns the value of 'n' to **numerator** and 'd' to **denominator**. The value of 'd' should not be zero. Increment the value of static data member.
2. **void setNum(int n);**
Setter function to assign the value of 'n' to numerator.
3. **void setDen(int d);**
Setter function to assign the value of 'd' to denominator. Value should not be zero.
4. **int getNum() const;**
const getter function to return numerator
5. **int getDen() const;**
const getter function to return denominator
6. **fraction operator + (const fraction & f);**
overload addition operator (+). This function should store the sum of calling object and the parameter **f** in a newly created object and return the simplest form of object to the calling function. e.g.,
$$\frac{4}{7} + \frac{6}{8} = \frac{32}{56} + \frac{42}{56} = \frac{74}{56} \Rightarrow \text{simplified fraction } \frac{37}{28}$$
Remember! You can not add the fractions until their denominators are same.
7. **fraction operator * (const fraction & f);**
overload multiplication operator (*). This function should store the product of calling object and the parameter **f** in a newly created object and return the simplest form of object to the calling function. e.g.,
$$\frac{3}{4} * \frac{4}{8} = \frac{12}{32} \Rightarrow \text{simplified fraction } \frac{3}{8}$$
8. **bool isProper() const;**
This function should return true if the fraction is proper, false otherwise. A proper fraction is one in which numerator is greater than denominator.
9. **static int getCount();**
This function should return the count of total number of fractions.
Initialize the static data member by 0 outside the class.

10. `bool operator > (const fraction & f);`
overload relational operator (`>`). This function should return true if the calling fraction is greater than the parameter `f`. if the denominators of both the fractions are same then simply check the numerator.
11. `void show() const`
This function should display the data of calling object.

Write a main function to test the functionalities of all the member functions of fraction ADT.