


Lecture 5 Smaller Network: CNN


- 1 We know it is good to learn a small model.
- 1 From this fully connected model, do we really need all the edges?
- 1 Can some of these be shared?



Consider learning an image:



- 1 Some patterns are much smaller than the whole image

Can represent a small region with fewer parameters




Same pattern appears in different places:
They can be compressed!

What about training a lot of such “small” detectors
and each detector must “move around”.



A convolutional layer

A CNN is a neural network with some convolutional layers (and some other layers). A convolutional layer has a number of filters that does convolutional operation.



Convolution

1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0

6 x 6 image

These are the network parameters to be learned.

1	-1	-1
-1	1	-1
-1	-1	1

Filter 1

-1	1	-1
-1	1	-1
-1	1	-1

Filter 2

⋮ ⋮

Each filter detects a small pattern (3 x 3).

Convolution

stride=1

1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0

6 x 6 image

Dot
product



3

-1

1	-1	-1
-1	1	-1
-1	-1	1

Filter 1

Convolution

If stride=2

1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0

6 x 6 image

1	-1	-1
-1	1	-1
-1	-1	1

Filter 1

3

-3

Convolution

stride=1

1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0

6 x 6 image

1	-1	-1
-1	1	-1
-1	-1	1

Filter 1

3	-1	-3	-1
-3	1	0	-3
-3	-3	0	1
3	-2	-2	-1

Convolution

stride=1


1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0

6 x 6 image

-1	1	-1
-1	1	-1
-1	1	-1


Filter 2

Repeat this for each filter




Two 4 x 4 images
Forming 2 x 4 x 4 matrix

Color image: RGB 3 channels






Convolution v.s. Fully Connected



Fully-
connected



1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0







6 x 6 image

fewer parameters!





Only connect to 9 inputs, not fully connected



6 x 6 image



Fewer parameters

Even fewer parameters



The whole CNN

cat dog



Max Pooling

1	-1	-1
-1	1	-1
-1	-1	1

Filter 1

-1	1	-1
-1	1	-1
-1	1	-1

Filter 2

3	-1	-3	-1
-3	1	0	-3
-3	-3	0	1
3	-2	-2	-1

-1	-1	-1	-1
-1	-1	-2	1
-1	-1	-2	1
-1	0	-4	3

Why Pooling

- 1 Subsampling pixels will not change the object
bird



Subsampling



We can subsample the pixels to make image smaller



fewer parameters to characterize the image




A CNN compresses a fully connected network in two ways:

- 1 Reducing number of connections
- 1 Shared weights on the edges
- 1 Max pooling further reduces the complexity

Max Pooling

1	0	0	0	0	1
0	1	0	0	1	0
0	0	1	1	0	0
1	0	0	0	1	0
0	1	0	0	1	0
0	0	1	0	1	0


6 x 6 image




Conv



Max
Pooling




New image
but smaller



2 x 2 image

Each filter
is a channel



The whole CNN



A new image

Smaller than the original image



The number of channels is the number of filters




Can repeat many times

The whole CNN



cat dog



Flattening



Flattened



Fully Connected
Feedforward network

CNN in Keras

Only modified the *network structure* and *input format* (vector -> 3-D tensor)

```
model2.add( Convolution2D( 25, 3, 3,  
                           input_shape=(28, 28, 1)) )
```

1	-1	-1	1	-1
-1	1	-1	1	-1
-1	-1	-1	1	-1
-1	-1	-1	1	-1



There are
25 3x3
filters.

Input_shape = (28 , 28 , 1)

28 x 28 pixels

1: black/white, 3: RGB

```
model2.add(MaxPooling2D( (2, 2) ))
```



input

Convolution


Max Pooling

Convolution

Max Pooling


CNN in Keras

Only modified the *network structure* and *input format* (vector -> 3-D array)



CNN in Keras

Only modified the *network structure* and *input format* (vector -> 3-D array)



AlphaGo



19 x 19 matrix

Black: 1
white: -1
none: 0

Neural
Network

Next move
(19 x 19
positions)

Fully-connected feedforward
network can be used

But CNN performs much better


AlphaGo's policy network

The following is quotation from their Nature article:


Note: AlphaGo does not use Max Pooling.

Neural network architecture. The input to the policy network is a $19 \times 19 \times 48$ image stack consisting of 48 feature planes. The first hidden layer zero pads the input into a 23×23 image, then convolves k filters of kernel size 5×5 with stride 1 with the input image and applies a rectifier nonlinearity. Each of the subsequent hidden layers 2 to 12 zero pads the respective previous hidden layer into a 21×21 image, then convolves k filters of kernel size 3×3 with stride 1, again followed by a rectifier nonlinearity. The final layer convolves 1 filter of kernel size 1×1 with stride 1, with a different bias for each position, and applies a softmax function. The match version of AlphaGo used $k = 192$ filters; Fig. 2b and Extended Data Table 3 additionally show the results of training with $k = 128, 256$ and 384 filters.

CNN in speech recognition



CNN in text classification



Source of image:
<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.703.6858&rep=rep1&type=pdf>